October 31, 2001 G9701-SSG-037

DOCUMENT CONTROL DESK UNITED STSTES NUCLEAR REGULATORY COMMISSION WASHINGTON, D.C. 20555



Reference:

- a) Boeing Letter G-1151-RSO-92-365 dated August 31, 1992; R.S.
 - Orr to the NRC Operations Center
- b) NRC Letter Docket No. 99901227 dated August 12, 1992; L. J. Norrholm to R. S. Orr; Subject: Response to 10 CFR 21 Inquiry

Dear Sir or Madam:

In accordance with the Reference correspondence and 10 CFR 21, Boeing is sending the NRC the attached error notices received from our former software suppliers. Because of unknown current addresses, the following former customers were not notified:

Reactor Controls, Inc

Echo Energy Consultants

Nuclear Applications and Systems Analysis Company (Japan)

Nuclear Power Services

Jak Snyal

Error notices have been sent to our other former customers.

Very truly yours,

Mark S. Snyder

Nuclear Administrator

Mail Code 7A-43

Enclosures: GT STRUDL Program Report Forms 2001.6 through 2001.9

IÉ20

GPRF No.: __2001.06

FROM: Computer-Aided Structural Engineering Center Georgia Institute of Technology Atlanta, Georgia 30332-0355 **SEVERITY LEVEL:** Problem results in incorrect answers which may not be apparent or job X URGENT aborts and cannot be recovered within the session or job. SERIOUS Problem results in incorrect answers which are obvious or problem prevents completion of a particular user's task. _ MINOR Problem can be worked around or problem poses high frustration factor. _ INFORMATIVE Documentation error, program usage tip, user inconveniences. Date Problem Confirmed April 4, 2001 Date Notification Sent 4/6/01 Computers PC only Operating System DOS, Windows NT, 95, 98, 2000, ME Version 96.01 and later Target Release for Correction <u>Version 26.0</u> Title R & D Division Michael H. Swanger Typed or Printed Name Signature Professional Services Division Date of Signature Typed or Printed Name

Rev. 2.1

(Continued)

GPRF No.: 2001.06

DATE: 4/5/01

DESCRIPTION:

The RIGID BODY INCIDENCES command does not detect the specification of duplicate rigid body element identifiers. Any rigid body incidence entry, whose element identifier duplicates the identifier of any previously defined member, element, or rigid body, overwrites the incidences data for the previously defined member, element, or rigid body. No message indicating this situation is given. This problem was first detected when a list of rigid body incidences included element identifiers containing nine characters, such as the following:

TYPE RIGID SOLID
RIGID BODY INCIDENCES

'12345678A' 1 2 3

'12345678B' 2 3 4

'12345678C' 3 4 5

Because element identifiers are restricted to eight characters, all of these rigid body element identifiers were truncated to the identical name '12345678', and only the incidence data for the last entry were stored.

The workaround is to specify unique, valid rigid body element identifiers in the RIGID BODY INCIDENCES command. A valid identifier has eight or fewer characters, or digits in the case of pure integer identifiers.

GTSTRUDL User Reference Manual Sections:

Rigid Bodies

Section 2.6.4.2, Volume 3, Rev. P, GTSTRUDL Reference Manual

	G	PRF No.: 2001.07			
FROM:	Computer-Aided Structural Engineering Center Georgia Institute of Technology Atlanta, Georgia 30332-0355	DATE: <u>4/12/01</u>			
SEVERITY L	LEVEL:				
X URGEN		Problem results in incorrect answers which may not be apparent or job aborts and cannot be recovered within the session or job.			
_ SERIOUS	Problem results in incorrect answers which prevents completion of a particular user's task.	Problem results in incorrect answers which are obvious or problem prevents completion of a particular user's task.			
_ MINOR	Problem can be worked around or problem pose	Problem can be worked around or problem poses high frustration factor.			
INFORMATIVE Documentation error, program usage tip, user inconveniences.					
Problem Confirmed 4/11/01					
Date Notification Sent 4/12/01					
Computers Operating Sys	All stem All	·····			
Versions All versions prior to and including Version 25					
Target Release for Correction Version 26					
Signature R & D Division	In Will Director ASD Title				
Kenneth Will					
Signature Professional S	Configuration Con Title Services Division				
Typed or Prin		nature Rev. 2.3			

(Continued)

GPRF No.: 2001.07

DATE: 4/12/01

DESCRIPTION:

If a loading contains JOINT TEMPERATUREs and that loading is later changed with the JOINT TEMPERATURES deleted, the joints which contained the deleted JOINT TEMPERATUREs will be incorrectly changed to planar element joints. Subsequent analyses may produce structural instabilities. This can be checked by the PRINT JOINT COORDINATE command and checking to see if the joints are listed as PLAN-EL (planar element).

Example:

LOADING 1
JOINT TEMPERATURES
1 TO 8 CHANGE 20.
JOINT LOADS
2 3 FORCE X 100

CHANGES
LOADING 1
DELETIONS
JOINT TEMPERATURE
1 TO 4

\$

THE PRINT JOINT COORDINATE command will show that the joints have been changed to planar element (PLAN-EL)

Workaround:

Delete the loading and then redefine the loading with a new name.

Applicable Sections of the Documentation:

JOINT TEMPERATURE - SECTION 2.3.5.3 of Volume 3 of the GTSTRUDL Reference Manuals.

DETERMINE PLANAR JOINTS - SECTION 2.1.12.10 of Volume 1 of the GTSTRUDL Reference Manuals (describes PLAN-EL PLANAR joints).

PRINT JOINT COORDINATE - SECTION 2.1.14.2 of Volume 1 and Section 2.3.6 of Volume 3 of the GTSTRUDL Reference Manuals.

GPRF No.: 2001.08

DATE: 4/12/01

FROM:	Georgia Insti	outer-Aided Structural Engineering Center gia Institute of Technology ta, Georgia 30332-0355		
SEVERITY 1	LEVEL:			
X URGEN		Problem results in incorrect answers which may not be apparent or job aborts and cannot be recovered within the session or job.		
_ SERIOUS		Problem results in incorrect answers which are obvious or problem prevents completion of a particular user's task.		
_ MINOR	Proble	Problem can be worked around or problem poses high frustration factor.		
_ INFORMA	ATIVE Docui	mentation error, p	program usage tip, user inconveniences.	
Date Problem	Confirmed	4/11/01		
Date Notifica	tion Sent	4/12/01		
Computers Operating Sys	All stem All			
Versions A	Il versions pric	or to and includin	ng Version 25	
Target Releas	se for Correction	on <u>Version 26</u>	5	
Signature			Director ASD Title	
R & D Divisi <u>Kenneth Will</u>			4/12/01	
Typed or Prin	nted Name		Date of Signature	
Signature Professional S	Services Divisi	 on	Configuration Control Manager Title	
David C		·	4/12/01	
Typed or Prin			Date of Signature	

(Continued)

GPRF No.: 2001.08

DATE: 4/12/01

DESCRIPTION:

If a loading contains JOINT TEMPERATUREs and that loading is later deleted and a new loading is created with the same name, the JOINT TEMPERATUREs will still be present in the new loading.

Example:

LOADING 1 JOINT TEMPERATURES 1 TO 8 CHANGE 20.

DELETIONS LOADING 1

ADDITIONS

LOADING 1 JOINT LOADS 2 3 FORCE X 10

\$

A PRINT LOADING DATA will show that the JOINT TEMPERATURES from the original LOADING 1 still exist in the newly defined LOADING 1. Subsequent STIFFNESS or NONLINEAR ANALYSIS commands will consider JOINT TEMPERATUREs in LOADING 1.

Workaround:

Do not define a new loading with the same name as a deleted loading which contained JOINT TEMPERATURE specifications.

You can verify that this condition did not occur by issuing the PRINT LOADING DATA command and checking that incorrect JOINT TEMPERATUREs do not appear in the output.

Applicable Sections of the Documentation:

JOINT TEMPERATURE - SECTION 2.3.5.3 of Volume 3 of the GTSTRUDL Reference Manuals.

PRINT LOADING DATA - SECTION 2.1.14.2 of Volume 1 and Section 2.3.6 of Volume 3 of the GTSTRUDL Reference Manuals.

GPRF No.: 2001.09

FROM:	Computer-Aided Structural Engineering Center Georgia Institute of Technology Atlanta, Georgia 30332-0355	ATE: 7/27/01			
SEVERITY LEVEL:					
X URGEN		Problem results in incorrect answers which may not be apparent or job aborts and cannot be recovered within the session or job.			
_ SERIOUS	S Problem results in incorrect answers which are of prevents completion of a particular user's task.	Problem results in incorrect answers which are obvious or problem prevents completion of a particular user's task.			
_MINOR	Problem can be worked around or problem poses hig	h frustration factor.			
_ INFORMATIVE Documentation error, program usage tip, user inconveniences.					
Date Problem Confirmed July 24, 2001 Date Notification Sent 7/21/01					
'					
Computers PC only					
Operating System DOS, Windows NT, 95, 98, 2000, ME					
Version 96.01 and later					
Target Release for Correction Version 26.0					
Muhae H. Signature R & D Divisio	Sr. RE Title				
Michael H. S Typed or Prin					
Signature Professional S	Configuration Control Man. Title Services Division	"3¢ T			
Typed or Print	Key 7/27/01				
I VDed or Print	nted Name Date of Signature				

(Continued)

GPRF No.: _2001.09

DATE: 7/21/01

DESCRIPTION:

The presence of joint constraints – joint ties and/or rigid bodies – forces the system mass matrix to be assembled using the consistent format, including the automatic computation of consistent member and element mass matrices from the self-weight density of the members and elements, regardless of whether or not the INERTIA OF JOINTS LUMPED/CONSISTENT command had been given.

As a work-around when using joint constraints and you do not wish the member and element self-weight consistent mass to be computed and assembled into the system mass matrix, then specify a 0.0 value for the DENSITY constant for the members and elements.

GTSTRUDL User Reference Manual Sections:

Joint Constraints

Section 2.6.4, Volume 3, Rev. Q, GTSTRUDL

Reference Manual

Inertia Specification Command

Section 2.4.3.1, Volume 3, Rev. Q, GTSTRUDL

Reference Manual