TABLE OF CONTENTS

Section	Title	Page
CHAPTER 4	REACTOR	4.1-1
4.1	Summary Description	4.1-1
	4.1.1 Principal Design Requirements	4.1-4
	4.1.2 Combined License Information	4.1-5
	4.1.3 References	4.1-5
4.2	Fuel System Design	4.2-1
	4.2.1 Design Basis	4.2-2
	4.2.1.1 Cladding	4.2-3
	4.2.1.2 Fuel Material	4.2-4
	4.2.1.3 Fuel Rod Performance	4.2-4
	4.2.1.4 Spacer Grids	4.2-5
	4.2.1.5 Fuel Assembly Structural Design	4.2-5
	4.2.1.6 In-core Control Components	4.2-7
	4.2.1.7 Surveillance Program	4.2-9
	4.2.2 Description and Design Drawings	4.2-9
	4.2.2.1 Fuel Rods	4.2-10
	4.2.2.2 Fuel Assembly Structure	4.2-11
	4.2.2.3 In-core Control Components	4.2-16
	4.2.3 Design Evaluation	4.2-20
	4.2.3.1 Cladding	4.2-21
	4.2.3.2 Fuel Materials Considerations	4.2-23
	4.2.3.3 Fuel Rod Performance	4.2-24
	4.2.3.4 Spacer Grids	4.2-28
	4.2.3.5 Fuel Assembly	4.2-28
	4.2.3.6 Reactivity Control Assemblies and Burnable Absorber Rods	4.2-30
	4.2.4 Testing and Inspection Plan	4.2-32
	4.2.4.1 Quality Assurance Program	4.2-32
	4.2.4.2 Quality Control	4.2-33
	4.2.4.3 Letdown Radiation Monitoring	4.2-35
	4.2.4.4 In-core Control Component Testing and Inspection	4.2-35
	4.2.4.5 Tests and Inspections by Others	4.2-36
	4.2.4.6 Inservice Surveillance	4.2-36
	4.2.4.7 Onsite Inspection	4.2-37
	4.2.5 Combined License Information	4.2-37
	4.2.6 References	4.2-37
4.3	Nuclear Design	4.3-1
	4.3.1 Design Basis	4.3-1

TABLE OF CONTENTS (Cont.)

Section			Title	Page
		4.3.1.1	Fuel Burnup	4.3-2
		4.3.1.2	Negative Reactivity Feedbacks (Reactivity Coefficients)	4.3-3
		4.3.1.3	Control of Power Distribution	4.3-3
		4.3.1.4	Maximum Controlled Reactivity Insertion Rate	4.3-4
		4.3.1.5	Shutdown Margins	4.3-5
		4.3.1.6	Stability	4.3-6
		4.3.1.7	Anticipated Transients without SCRAM (ATWS)	4.3-7
	4.3.2		Description	4.3-7
		4.3.2.1	Nuclear Design Description	4.3-7
		4.3.2.2	Power Distribution	4.3-9
		4.3.2.3	Reactivity Coefficients	4.3-20
		4.3.2.4	Control Requirements	4.3-24
		4.3.2.5	Control Rod Patterns and Reactivity Worth	4.3-30
		4.3.2.6	Criticality of the Reactor During Refueling	4.3-31
		4.3.2.7	Stability	4.3-33
		4.3.2.8	Vessel Irradiation	4.3-38
	4.3.3		Analytical Methods	4.3-38
		4.3.3.1	Fuel Temperature (Doppler) Calculations	4.3-39
		4.3.3.2	Macroscopic Group Constants	4.3-40
		4.3.3.3	Spatial Few-Group Diffusion Calculations	4.3-41
	4.3.4		Combined License Information	4.3-42
	4.3.5		References	4.3-43
4.4			Thermal and Hydraulic Design	4.4-1
	4.4.1		Design Basis	4.4-1
		4.4.1.1	Departure from Nucleate Boiling Design Basis	4.4-1
		4.4.1.2	Fuel Temperature Design Basis	4.4-3
		4.4.1.3	Core Flow Design Basis	4.4-3
		4.4.1.4	Hydrodynamic Stability Design Basis	4.4-4
		4.4.1.5	Other Considerations	4.4-4
	4.4.2		Description of Thermal and Hydraulic Design of the Reactor Core	4.4-4
		4.4.2.1	Summary Comparison	4.4-4
		4.4.2.2	Critical Heat Flux Ratio or DNBR and Mixing Technology	4.4-4
		4.4.2.3	Linear Heat Generation Rate	4.4-10
		4.4.2.4	Void Fraction Distribution	4.4-10
		4.4.2.5	Core Coolant Flow Distribution	4.4-10
		4.4.2.6	Core Pressure Drops and Hydraulic Loads	4.4-11
		4.4.2.7	Correlation and Physical Data	4.4-12
		4.4.2.8	Thermal Effects of Operational Transients	4.4-14
		4.4.2.9	Uncertainties in Estimates	4.4-14
		4.4.2.10	Flux Tilt Considerations	4.4-16

TABLE OF CONTENTS (Cont.)

Section	Title	Page
	4.4.2.11 Fuel and Cladding Temperatures	4.4-17
4.4.3	Description of the Thermal and Hydraulic Design of the Reactor Coolant System	4.4-20
	4.4.3.1 Plant Configuration Data	4.4-20
	4.4.3.2 Operating Restrictions on Pumps	4.4-20
	4.4.3.3 Power-Flow Operating Map (Boiling Water Reactor [BWR])	4.4-20
	4.4.3.4 Temperature-Power Operating Map (PWR)	4.4-21
	4.4.3.5 Load Following Characteristics	4.4-21
	4.4.3.6 Thermal and Hydraulic Characteristics Summary Table	4.4-21
4.4.4	Evaluation	4.4-21
	4.4.4.1 Critical Heat Flux	4.4-21
	4.4.4.2 Core Hydraulics	4.4-21
	4.4.4.3 Influence of Power Distribution	4.4-23
	4.4.4.4 Core Thermal Response	4.4-25
	4.4.4.5 Analytical Methods	4.4-25
	4.4.4.6 Hydrodynamic and Flow Power Coupled Instability	4.4-27
	4.4.4.7 Fuel Rod Behavior Effects from Coolant Flow Blockage	4.4-29
4.4.5	Testing and Verification	4.4-30
	4.4.5.1 Tests Prior to Initial Criticality	4.4-30
	4.4.5.2 Initial Power and Plant Operation	4.4-31
	4.4.5.3 Component and Fuel Inspections	4.4-31
4.4.6	Instrumentation Requirements	4.4-31
	4.4.6.1 Incore Instrumentation	4.4-31
	4.4.6.2 Overtemperature and Overpower ΔT Instrumentation	4.4-32
	4.4.6.3 Instrumentation to Limit Maximum Power Output	4.4-32
	4.4.6.4 Digital Metal Impact Monitoring System	4.4-33
4.4.7	Combined License Information	4.4-35
4.4.8	References	4.4-35
4.5	Reactor Materials	4.5-1
4.5.1	Control Rod and Drive System Structural Materials	4.5-1
	4.5.1.1 Materials Specifications	4.5-1
	4.5.1.2 Fabrication and Processing of Austenitic Stainless Steel Components	4.5-2
	4.5.1.3 Other Materials	4.5-2
	4.5.1.4 Contamination Protection and Cleaning of Austenitic Stainless Steel	4.5-3

TABLE OF CONTENTS (Cont.)

Section	Title	Page
4.5.2	Reactor Internal and Core Support Materials	4.5-3
4.5.2.1	Materials Specifications	4.5-3
4.5.2.2	Controls on Welding	4.5-3
4.5.2.3	Nondestructive Examination of Tubular Products and Fittings	4.5-4
4.5.2.4	Fabrication and Processing of Austenitic Stainless Steel Components	4.5-4
4.5.2.5	Contamination Protection and Cleaning of Austenitic Stainless Steel	4.5-4
4.5.3	Combined License Information	4.5-4
4.5.4	References	4.5-4
4.6	Functional Design of Reactivity Control Systems	4.6-1
4.6.1	Information for Control Rod Drive System	4.6-1
4.6.2	Evaluations of the Control Rod Drive System	4.6-1
4.6.3	Testing and Verification of the Control Rod Drive System	4.6-2
4.6.4	Information for Combined Performance of Reactivity Systems	4.6-2
4.6.5	Evaluation of Combined Performance	4.6-3
4.6.6	Combined License Information	4.6-4

LIST OF TABLES

Table No.	Title	Page
4.1-1	Reactor Design Comparison Table (Sheets 1 - 3)	4.1-6
4.1-2	Analytical Techniques in Core Design (Sheets 1 - 2)	4.1-9
4.1-3	Design Loading Conditions for Reactor Core Components	4.1-11
4.3-1	Reactor Core Description (First Cycle) (Sheets 1 - 3)	4.3-48
4.3-2	Nuclear Design Parameters (First Cycle) (Sheets 1 - 2)	4.3-51
4.3-3	Reactivity Requirements for Rod Cluster Control Assemblies	4.3-53
4.3-4	Benchmark Critical Experiments	4.3-54
4.3-5	Stability Index for Pressurized Water Reactor Cores with a 12-Foot Height	4.3-55
4.3-6	Typical Neutron Flux Levels ($n/cm^2/s$) at Full Power	4.3-56
4.3-7	Comparison of Measured and Calculated Doppler Defects	4.3-57
4.3-8	Comparison of Measured and Calculated Ag-In-Cd Rod Worth	4.3-58
4.3-9	Comparison of Measured and Calculated Moderator Coefficients at HZP, BOL	4.3-59
4.4-1	Thermal and Hydraulic Comparison Table (AP600 and a Typical Westinghouse Four-Loop Plant) (Sheets 1 - 2)	4.4-42

LIST OF FIGURES

Figure No.	Title	Page
4.2-1	Fuel Assembly Cross-Section	4.2-40
4.2-2	Fuel Assembly Outline	4.2-41
4.2-3	Fuel Rod Schematic	4.2-43
4.2-4	Top Grid Sleeve Detail	4.2-44
4.2-5	Intermediate Grid to Thimble Attachment Joint	4.2-45
4.2-6	Intermediate Flow Mixer Grid to Thimble Attachment	4.2-46
4.2-7	Grid Thimble to Bottom Nozzle Joint	4.2-47
4.2-8	Rod Cluster Control and Drive Rod Assembly with Interfacing Components	4.2-48
4.2-9	Rod Cluster Control Assembly	4.2-49
4.2-10	Absorber Rod Detail	4.2-50
4.2-11	Gray Rod Cluster Assembly	4.2-51
4.2-12	Wet Annular Burnable Absorber Assembly	4.2-52
4.2-13	Wet Annular Burnable Absorber Rod Detail	4.2-53
4.2-14	Primary Source Assembly	4.2-54
4.2-15	Secondary Source Assembly	4.2-55
4.3-1	Fuel Loading Arrangement	4.3-60
4.3-2	Typical Production and Consumption of Higher Isotopes	4.3-61
4.3-3	Cycle 1 Soluble Boron Concentration Versus Burnup	4.3-62
4.3-4a	Cycle 1 Assembly Burnable Absorber Patterns	4.3-63
4.3-4b	Cycle 1 Assembly Burnable Absorber Patterns	4.3-64
4.3-5	Burnable Absorber, Primary, and Secondary Source Assembly Locations	4.3-65
4.3-6	Normalized Power Density Distribution Near Beginning of Life, Unrodded Core, Hot Full Power, No Xenon	4.3-66
4.3-7	Normalized Power Density Distribution Near Beginning of Life, Unrodded Core, Hot Full Power, Equilibrium Xenon	4.3-67
4.3-8	Normalized Power Density Distribution Near Beginning of Life, Gray Bank M0 Inserted, Hot Full Power, Equilibrium Xenon	4.3-68
4.3-9	Normalized Power Density Distribution Near Middle of Life, Unrodded Core, Hot Full Power, Equilibrium Xenon	4.3-69
4.3-10	Normalized Power Density Distribution Near End of Life, Unrodded Core, Hot Full Power, Equilibrium Xenon	4.3-70
4.3-11	Normalized Power Density Distribution Near End of Life, Gray Bank M0 Inserted, Hot Full Power, Equilibrium Xenon	4.3-71
4.3-12	Rodwise Power Distribution in a Typical Assembly (F-8) Near Beginning of Life, Hot Full Power, Equilibrium Xenon, Unrodded Core	4.3-72

LIST OF FIGURES (Cont.)

Figure No.	Title	Page
4.3-13	Rodwise Power Distribution in a Typical Assembly (F-8) Near End of Life, Hot Full Power, Equilibrium Xenon, Unrodded Core	4.3-73
4.3-14	Maximum F_Q x Power Versus Axial Height During Normal Operation	4.3-74
4.3-15	Comparison Between Calculated and Measured Relative Fuel Assembly Power Distribution	4.3-75
4.3-16	Typical Calculated Versus Measured Axial Power Distribution	4.3-76
4.3-17	Measured F_Q Values Versus Axial Offset for Full Power Rod Configurations	4.3-77
4.3-18	Typical Doppler Temperature Coefficient at BOL and EOL	4.3-78
4.3-19	Typical Doppler-Only Power Coefficient at BOL and EOL	4.3-79
4.3-20	Typical Doppler-Only Power Defect at BOL and EOL	4.3-80
4.3-21	Typical Moderator Temperature Coefficient at BOL, Unrodded	4.3-81
4.3-22	Typical Moderator Temperature Coefficient at EOL	4.3-82
4.3-23	Typical Moderator Temperature Coefficient as a Function of Boron Concentration at BOL, Unrodded	4.3-83
4.3-24	Typical Hot Full Power Temperature Coefficient Versus Cycle Burnup	4.3-84
4.3-25	Typical Total Power Coefficient at BOL and EOL	4.3-85
4.3-26	Typical Total Power Defect at BOL and EOL	4.3-86
4.3-27	Rod Cluster Control Assembly Pattern	4.3-87
4.3-28	Typical Accidental Simultaneous Withdrawal of Two Control Banks at EOL, HZP, Moving in the Same Plane	4.3-88
4.3-29	Typical Design Trip Curve	4.3-89
4.3-30	Typical Normalized Rod Worth Versus Percent Insertion All Rods Inserting Less Most Reactive Stuck Rod	4.3-90
4.3-31	X-Y Xenon Test Thermocouple Response Quadrant Tilt Difference Versus Time	4.3-91
4.3-32	Calculated and Measured Doppler Defect and Coefficients at BOL, Two-Loop Plant, 121 Assemblies, 12-Foot Core	4.3-92
4.4-1	Thermal Diffusion Coefficient (TDC) versus Reynolds Number for 26-Inch Grid Spacing	4.4-44
4.4-2	Void Fraction versus Thermodynamic Quality	4.4-45
4.4-3	Thermal Conductivity of Uranium Dioxide	4.4-46