NUCLEAR ORGANIZATION CONTROLLED DOCUMENT TRANSMITTAL NOTICE

CONTROLLED DOCUMENT TRANSMITTAL NOTICE
DOCUMENT TITLE: CP-2P-300, Rev. 4
Cmergency Plan Amplementing Procedure
TO: U.S.M. P.C. Washington DC MAIL:
CONTROLLED COPY NO .: // TRANSMITTAL NO .: 01-195 DATE: 5-1-0/
FOR DOCUMENT CONTROL USE ONLY
$/\overline{X}/$ 1. The attached controlled document(s) are transmitted for your use. Please insert/remove as indicated on the attached Change Instruction Notice. Please check Block 6, sign this form and return upon receipt.
/_/ 2. The controlled document(s) listed on the attached Change Instruction Notice have been retired from use. Please check Block 7, sign this form and return upon receipt.
/_/ 3. This is your notice. The document(s) indicated above were transmitted to you on Please check the status of your controlled copy, sign this document and return. If you do not have these documents, check Block 5 and a new copy will be issued.
// 4. Your name has been removed from the Distribution List of the controlled document listed above. Please check Block 7, sign this form and return it with the document to the Document Control Supervisor.
COPY HOLDER CHECK ONE
/_/ 5. I am not currently in possession of the above documents. Please issue another set to me.
/_/ 6. I have received from the sender the material and attachments as indicated above, and I have updated my controlled manual accordingly.
/ 7. I am returning the documents listed above.
PLEASE SIGN AND RETURN TO: Controlled Document Clerk, MAIL STOP #19 NO ENVELOPE REQUIRED FOR INTERNAL COMPANY MAIL
Entergy, Controlled Document Clerk Pilgrim Nuclear Power Station 600 Rocky Hill Road, Support Building Plymouth, Massachusetts 02360

Controlled Copy No.

CHANGE INSTRUCTION NOTICE (CIN)

r? vittal No. 01-195 Date: 5-1-01

lease update your copy of CP-P-300, ReU.Hvith the attachments to this transmittal as instructed below.

REMOVE AND DISCARD	REV. NO.	INSERT	REV. NO.
TOAC (3-30-01)	64	TOT (5-1-01)	48
PP-DP.300	S	CP-2P300	4
·			
	<u> </u>		
	· ·		
· · · · · · · · · · · · · · · · · · ·			

PNPS Emergency Plan Implementing	Number:
Procedure Manual	N/A

RType H8.24

TABLE OF CONTENTS

Number	Title	<u>Revision</u>	Effective <u>Date</u>
EP-IP-100	Emergency Classification and Notification	14	03/30/01
EP-IP-200	On-Call Emergency Director	9	02/07/01
EP-IP-201	Emergency Plant Manager	1	05/14/99
EP-IP-202	Company Spokesperson	3	02/07/01
EP-IP-210	Control Room Augmentation	7	12/12/00
EP-IP-220	TSC Activation and Response	11	11/15/00
EP-IP-229	TSC/OSC Equipment Operation	5	07/25/00
EP-IP-230	OSC Activation and Response	3	11/15/00
EP-IP-231	Onsite Radiation Protection	5	07/25/00
EP-IP-240	Emergency Security Organization Activation and Response	8	03/15/00
EP-IP-250	EOF Activation and Response	9	02/07/01
EP-IP-251	Offsite Radiation Protection	5	12/26/00
EP-IP-252	Facilities Support	7	02/01/01
EP-IP-253	Relocation of the EOF	3	07/13/00
EP-IP-254	Communications Support	2	12/06/00
EP-IP-259	EOF Equipment Operation	3	05/24/00
EP-IP-300	Offsite Radiological Dose Assessment	4	05/01/01
EP-IP-310	Radiation Monitoring Team Activation and Response	4	11/15/00
EP-IP-315	Personnel Monitoring Team Activation and Response	4	05/24/00
EP-IP-330	Core Damage	2B	06/19/98
EP-IP-400	Protective Action Recommendations	8	01/23/01
EP-IP-410	Evacuation/Assembly	4	05/24/00

PNPS Emergency Plan Implementing	Number:
Procedure Manual	N/A

RType H8.24

TABLE OF CONTENTS

Number	Title	<u>Revision</u>	Effective <u>Date</u>
EP-IP-420	Search and Rescue	3	02/12/01
EP-IP-440	Emergency Exposure Controls	5A	04/08/98
EP-IP-501	Transport of Contaminated Injured Personnel	3	05/24/00
EP-IP-520	Transition and Recovery	5	02/07/01

RTYPE H8.24

PILGRIM NUCLEAR POWER STATION

Procedure No. EP-IP-300

OFFSITE RADIOLOGICAL DOSE ASSESSMENT



SAFETY REVIEW REQUIRED

SAFETY RELATED

EPIP300

EP-IP-300 Rev. 4

REVISION LOG

REVISION 4	Date Originated 3/01
Pages Affected	Description
All	Reformat IAW current PNPS 1.3.4-1. Revision bars are not shown for reformatting.
1	Change "Protection" to "Assessment" in title.
4,6	Update to reflect current version of DAPAR program.
4	Add EP File 1.6.4 for DAPAR version 2.1 to References.
4	Change definition of "Planning Zone(s)" to "Emergency Planning Zones" and clarify the plume and ingestion pathways descriptions.
5,30	Revise/update organization titles.
7,8	Clarify DAPAR logon instructions.
9-13,16-22	Revise computer window screens and instructions to reflect new version of DAPAR 2.1.
11	Add clarification notes for obtaining meteorological data.
32	Add "Radiological" to Part A title.

TABLE OF CONTENTS

<u>Page</u>

1.0	PURF	POSE4			
2.0	REFE	RENCES4			
3.0	DEFI	NITIONS4			
4.0	DISC	USSION5			
5.0	RESF	PONSIBILITIES			
6.0	PRO	CEDURE			
	6.1	APPLICATION STARTUP6			
	6.2	TITLE SCREEN9			
	6.3	QUICK ASSESSMENT10			
	6.4	FULL ASSESSMENT			
	6.5	ASSESSMENT METHODS16			
	6.6	PROTECTIVE ACTION RECOMMENDATIONS			
	6.7	EMERGENCY WORKER DOSE PROJECTION			
	6.8	OFFSITE DOSE CALCULATION, BACKUP METHOD			
7.0	REC	ORDS			
8.0	ATTACHMENTS				
ATTA	CHME	NT 1 - OFFSITE DOSE AND PAR WORKSHEET			
ATTA	CHME	NT 2 - DOCUMENT CROSS-REFERENCES			
ATTA		NT 3 - IDENTIFICATION OF COMMITMENTS			

1.0 PURPOSE

The purpose of this Procedure is to provide guidance and clarification in the event of emergencies involving actual or potential radioactive releases from the Pilgrim Nuclear Power Station (PNPS) for the operation of the emergency dose assessment computer program 'DAPAR' version 2.1

2.0 <u>REFERENCES</u>

- [1] EP-PP-01, "PNPS Emergency Plan"
- [2] EPA 400-R-92-001, "Manual of Protective Action Guides and Protective Actions for Nuclear Incidents", October, 1991
- [3] EP File 1.6.4 "DAPAR Version 2.0 Computer Application Verification, Validation and Documentation"
- [4] EP File 1.6.4 "DAPAR Version 2.1 Computer Application Verification, Validation and Documentation"
- [5] NRC IE Information Notice No. 83-28, "Criteria for Protective Action Recommendations for General Emergencies", May 4, 1983
- [6] SAND 77-1725, "Public Protection Strategies for Potential Nuclear Reactor Accidents -Sheltering Concepts with Existing Public and Private Structures"

3.0 **DEFINITIONS**

- [1] <u>Core Melt Sequence</u> A situation in which the core is uncovered and there is no means for restoring coolant to the core. Without coolant, overheating and melting of the fuel will occur.
- [2] <u>Dose Commitment</u> The dose that will be accumulated by a specific organ over a specified period following uptake.
- [3] <u>Emergency Planning Zone (EPZs)</u> Two zones that are established around all nuclear power stations in which predetermined protective action plans are needed.
 - (a) The first EPZ (plume) has an approximate radius of 10 miles for plume exposure pathway.
 - (b) The second EPZ (ingestion) has an approximate radius of 50 miles for food ingestion exposure pathway.

- [4] <u>Evacuation Exposure Period</u> The period during which those being evacuated are exposed to the radioactive plume.
- [5] <u>Gap Release Sequence</u> A situation in which the core is overheated and/or uncovered and there is no rapid means for restoring coolant to the core. Without cooling, overheating and failure of the fuel cladding will occur.
- [6] <u>MEMA/OEP</u> Massachusetts Emergency Management Agency/Office of Emergency Preparedness.
- [7] MDPH Massachusetts Department of Public Health.
- [8] Offsite The area outside the Owner Controlled Area.
- [9] <u>Projected Exposure Time</u> That period of time in which the offsite population will be exposed to radiation as a result of an airborne radioactive release.
- [10] <u>Sheltering Dose</u> That dose received if the individual were to remain on the first floor within a wood framed shelter having ventilation control (that is, door, windows, and ventilation shut) during the passage of the plume.

4.0 DISCUSSION

None

5.0 **RESPONSIBILITIES**

- [1] The Emergency Director is responsible for recommending protective actions to offsite agencies (MEMA/OEP, State Police, EPZ and host communities) to protect the health and safety of the general public.
- [2] The Emergency Offsite Manager, following discussions with the Offsite Radiological Supervisor, is responsible for recommending offsite protective actions to the Emergency Director.
- [3] The Shift Control Room Engineer is responsible for:
 - (a) Advising the Operations Shift Superintendent on matters of offsite dose assessment and protective action recommendations.
 - (b) Performing all dose assessment activities prior to activation of the Emergency Operations Facility

- [4] The Offsite Radiological Supervisor is responsible for:
 - (a) Directing and monitoring all offsite dose assessment activities.
 - (b) Evaluating the results provided by the DAPAR computer program and adjusting or modifying these results if he/she believes that they do not provide an appropriate or reasonably accurate assessment of offsite dose consequences.
 - (c) Determining the need for offsite actions to protect the health and safety of the general public and providing these recommendations to the Emergency Offsite Manager for review.
- [5] The Dose Assessment Engineer is responsible for:
 - (a) Obtaining the necessary information from status boards and other sources to execute this program and to promptly report the results to the Offsite Radiological Supervisor.
 - (b) Immediately reporting significant changes in either input data or results to the Offsite Radiological Supervisor.
 - (c) Performing dose projections whenever significant changes occur in meteorological, radiological, or plant conditions.

6.0 PROCEDURE

'DAPAR' Version 2.1 is a Windows based application designed to operate within the Microsoft Access program environment. Application operation and system requirements are dictated by Microsoft Windows protocols. This Procedure is not required nor intended to be used as a step-by-step guide while operating 'DAPAR'. However, the user must be familiar with basic computer operations within the Microsoft Windows environment in order to utilize this application.

- 6.1 APPLICATION STARTUP
- [1] Verify the monitor is on. If it is not, start the monitor.
- [2] Verify the printer is connected to the computer and is turned on. If it is not, connect and start the printer.
- [3] Verify that a mouse or other type of pointing device is connected to the computer. If there is not, connect the mouse to the computer.
- [4] Verify that the keyboard is connected to the computer. If it is not, connect the keyboard to the computer.
- [5] Remove any floppy disks inserted in the 'A' drive.

[6] If the computer is off, perform the following steps:

NOTE

The computer should boot-up by executing the initial diagnostic checks and then the Windows NT Ctrl+Alt+Delete to logon should appear on the monitor.

- (a) Turn on the computer.
- (b) Push "Ctrl+Atl+Delete" keys to display the User Logon window.
- (c) Push "OK" to open the Windows NT Desktop.

NOTE

DAPAR program uses the computer internal date and time stamp for assessing program information that relates to date and time input parameters. The "Date/Time" property window can be assessed by double-clicking the time display located in the right-hand corner of the monitor or by opening the Windows Control Panel.

- (d) Verify and set (if necessary) the computer internal date and time stamp with current date and time.
- (e) Start DAPAR by double-clicking on DAPAR v2.1 icon.
- [7] If the computer is on and DAPAR is not running, or another program is being run, perform the following steps:
 - (a) Exit current programs or switch to the Windows desktop window.

NOTE

DAPAR program uses the computer internal date and time stamp for assessing program information that relates to date and time input parameters. The "Date/Time" property window can be assessed by double-clicking the time display located in the right-hand corner of the monitor or by opening the Windows Control Panel.

- (b) Verify and set (if necessary) the computer internal date and time stamp with current date and time.
- (c) Start DAPAR by double-clicking the mouse on the DAPAR v2.1 icon.

- [8] If the program is still not operating or the computer does not start up as described above, notify the appropriate supervisor and implement one of the following:
 - (a) Start DAPAR using another dose assessment computer.
 - (b) Obtain a backup application disk and install DAPAR program on any functional PC, preferably with a Microsoft Access 97 program installed.
 - (c) Proceed to Section 6.8 and implement backup dose assessment manual method until computer operational problems are resolved.

6.2 TITLE SCREEN

The title screen shows the application version and directs program flow to the desired

assessment method The 'Full Assessment' option is designed for use by a qualified dose assessment engineer. Four methods of dose assessment are available: monitored release, containment leakage/failure, field team analysis, and release point sample analysis. In the case of 'Full Assessment', multiple assessments can be performed simultaneously during a session. The 'Quick Assessment' option is designed for use in the Control Room. Assessment is performed from effluent information related to a monitored release using design basis accident (LOCA) default values. Once an assessment option is selected, the introduction screen cannot be recalled without guitting the application and beginning a new session.



A basic program flow diagram is illustrated below.



DAPAR Input Window Flow Diagram

6.3 QUICK ASSESSMENT

Quick assessment operation and calculation are identical to the full assessment method for a monitored release but utilize default release path and core damage assumptions for the determination of offsite doses. Default values incorporating a design basis LOCA accident are applied to allow a rapid assessment from within the Control Room during situations involving a monitored release. Base information is grouped into two areas: release information and meteorological data. The Quick Assessment window also contains command buttons for navigating to other areas or for performing application functions.

Release Informa	tion	Meteorological Data	
Monitor	Bange	Riower Used: NG: 220 CI 160	
C Main Stack - Constant	a C is High at	Wind Speed (MPH): 1.0	
C: Reactor Building Vent	C. Low A	wind Direction (Brom)	
C: Turbine Building Vent,			
Monitor Reading			
VentiFlow Rate (SCFM)		Stability Class of the second second	
Hours After SZD (h:mm):		Set Evacuation Conditions	
TO BENER		Computer Date: 02 Mar 0	

The quick assessment option takes monitor release and meteorological information inputs to determine whether dose projections have or have not exceeded the Protective Action Guides (PAGs) for recommending protective actions (PARs) to offsite agencies. Information is entered directly into the appropriate text box or by selecting a choice from a group of option buttons.

The inputs for this assessment option are as follows:

Release In	formation	
Input	Control	Options/Entry
Monitor	Option	Main Stack
	Button	Reactor Building Vent
		Turbine Building Vent
Range	Option	High
	Button	Low (not available for turbine building vent)
Reading	Text Box	As indicated on control room monitors in cps or R/hr (units are
, C		determined by the appropriate monitor range).

Release Info	ormation	
Input	Control	Options/Entry
Vent Flow Rate	Text Box	Values entered in SCFM for ventilation flow rate corresponding to the release point. If actual values are not known, the default values for the common release points below may be used:
		Main Stack Low Range 24,000 SCFM
		Main Stack High Range4,000 SCFM
		Reactor Building 200,000 SCFM
		Turbine Building 210,000 SCFM
		 Each Turbine Building fan (six total) default flow rate is 35,000 SCFM.
Hours After	Text Box	Entered as h:mm for time after reactor shutdown.
Shutdown		Use '0:00' for conditions where the reactor is not yet shutdown.
		Automatically updated when window is reentered from the PAR screen.

Meteorologi	cal Data	
Input	Control	Options/Entry
Met. Tower	Option Button	 220' Tower 160' Tower 220' Tower is first choice before using 160' Tower information. For an elevated release (Main Stack), ensure that upper sensor data are obtained and used from either the 220' Tower or 160' Tower. For a ground release (Reactor Bldg Vent, Turbine Bldg Vent, or Unmonitored Release), ensure that lower sensor data are obtained and used from either the 220' Tower or 160' Tower.
Wind Speed	Text Box	As indicated on Control Room monitors in MPH (valid input is 1 through 75 MPH).
Wind Direction	Text Box	As indicated on Control Room monitors in degrees from (valid input is 000° through 360°).
Delta T	Text Box	As indicated on Control Room monitors in °F (reported as 'N/A' when user specifies a stability class).
Stability Class	Text Box	Automatic update based on the entered delta-T and met tower. Can be changed without a delta-T.
Set Evacuation Conditions	Command Button	Displays pop-up window for entry of offsite evacuation conditions (see Evacuation Conditions Table).
Fumigation	Check Box	 Not visible unless appropriate conditions are met. Allows the selection of fumigation X/Qs for an elevated release. Necessary conditions are as follows: The stability class is E, F, or G. The date is 4/1 to 9/30. The time is 8 AM to 6 PM. Wind direction is between 000° and 120° or 270° and 360°. The wind speed at the top elevation is between 2 and 10 MPH. User is prompted to determine whether the 33' air temperature is greater than the condenser inlet temperature.
Max. ETE	Inf. Box	Information only. Maximum evacuation time based on wind direction and weather conditions.

Meteorologi	cal Data	
Input	Control	Options/Entry
Release	Text Box	Automatic update based on maximum evacuation time estimate.
Duration		Can be changed by user.

DAPAR uses the maximum Evacuation Time Estimates (ETEs) as the basis for the initial release duration. This method assumes that all of the affected (downwind) subareas out to 10 miles will be involved in the offsite protective action. By selecting the 'Set Evacuation Conditions' command button, the Evacuation Conditions window will display the applicable category options. Note that all options may not be available based on the selection within other categories (for example, if time of year is summer, snow will not be available as a condition). A selection within each category must be made, when more than one option is available, before the 'OK' command button is made visible to exit the window. ETEs are determined from a matrix by selecting the applicable conditions from the Evacuation Conditions window as follows:

Evacuation Conditions			
Input	Control	Options/Entry	
Time of	Option	Summer (Memorial Day through Labor Day)	
Year	Button	Off Season	
Time of	Option	Weekend	
Week	Button	Midweek	
Time of	Option	Evening (N/A for Summer and Off Season Weekend)	
Day	Button	Midday (N/A for Summer and Off Season Weekend)	
		All Day	
Conditions	Option	Good	
	Button	Rain	
		Snow (N/A for Summer)	
ОК	Command	Not visible unless each category has a selected item.	
	Button	Accepts the selected inputs and returns to the applicable assessment window	

Command B	ar Control	Options/Entry
PARs	Command	Initially disabled.
	Button	Enabled after the necessary base information is entered allowing the user to continue on to the Dose Assessment Results window (see Dose Assessment Results).
Quit	Command	The button may be used at any time to exit the application and
	Button	return to Windows.

6.4 FULL ASSESSMENT

Choosing the full assessment option directs the program to a baseline data entry window. The window is divided into three input areas: isotopic source term, dominant release path, and meteorological data.



Dominant release path determines the process reduction factors which are applied to all non-noble gas isotopes. It is allowable to choose a release path which does not relate to the specific accident in order to alter the process reduction factor. Isotopic source term establishes the source available for release from the core based on damage type, amount of damage, and time after shutdown. The source term is based on an end of life core, at 3.5% fuel enrichment, following operation at full power. This assumption will conservatively overestimate the long-lived isotopes for power operations and enrichments less than those described above. Damage defaults of 10% Gap are initially entered upon startup but can be changed to reflect PASS or better damage estimates as they become available. Meteorological data provide the conditions under which offsite dose calculations are performed and evacuation time estimations are determined. Assessment options available for dose assessment include monitored release, containment leakage/failure, field team analysis, and release point analysis.

The baseline information inputs are as follows:

Dominant Release Path		
Input	Control	Options/Entry
Path	Text Box	Information only.
Description		Describes the currently selected release path.

Dominant R	elease Path	
Input	Control	Options/Entry
Select Path	Command	Transfer to the Release Path Window for selection of dominant
	Button	release path (see Release Path Window).
PRF	Text Box	Information only.
		Gives the process reduction factor applied to all non-noble gas isotopes at the point of release.

The predominant release path is determined as follows:

Release Path and Process Reduction Inputs:		
Input	Control	Options/Entry
Path A-M	Option	Selects and highlights the dominant release path.
	Button	Once selected, additional windows may prompt for process conditions.
Accept Path	Command	Not visible before path is chosen.
	Button	Transfer to Full Assessment data entry window following selection of a release path.
Dry Well	Option	Containment Spray Off (default)
Spray	Button	Containment Spray On
Dry Well	Option	< 1 Hour (default)
Hold-Up	Button	2-12 Hours
		24 Hours
Torus	Option	Sub cooled (default)
Suppression	Button	Saturated
		Bypassed
Torus Hold-	Option	< 1 Hour (default)
Up	Button	2-12 Hours
		24 Hours
Reactor	Option	< 1 Hour (default)
Bldg Hold-	Button	2-12 Hours
Up		24 Hours
SBGT Filter	Text Box	99.0% (default)
Efficiency		

Isotopic Sou	Isotopic Source Term		
Input	Control	Options/Entry	
Damage	Option	Gap (default)	
Туре	Button	Melt	
Damage	Text Box	10% (default)	
Hours After	Text Box	Entered as h:mm for time after reactor shutdown.	
Shutdown		Use '0:00' for conditions where the reactor is not yet shutdown.	
		Automatically updated when window is reentered from any assessment method screen.	

DAPAR uses an illustrated flow diagram to display the source term release pathway from the RCS to the environment. The path selected will determine the reduction factor applied to non-noble gases released to the environment. Depending on the path selected by the user, a pop-up window may be displayed to allow appropriate hold-up times and/or conditions (such as filter efficiency) to be entered.

Command Bar		
Input	Control	Options/Entry
Method	List Box	Monitored Release (default)
		Containment Leakage/Failure
		Field Team Analysis
1		Release Point Analysis
Continue	Command	Initially disabled.
	Button	Enabled after the necessary base data is entered allowing the user to continue on to the window for the selected method.
Exit	Command Button	The button may be used at any time to exit the application and return to Windows.

6.5 ASSESSMENT METHODS

Four assessment methods are available from within the full assessment option: monitored release, containment leakage/failure, field team analysis, and release point sample analysis. Each of the assessment method screens is divided into several sections: data entry, protective actions, downwind dose estimates, and command options. Specific details on data entry for each method are described in the respective sections of this Procedure.

Protective action distances are presented for TEDE (whole body) and CDE thyroid dose exposure estimates which exceed the EPA-400 Protective Action Guides. The maximum distance at which the PAGs are exceeded are displayed in red for:

TEDE (Whole Body) \geq 1 rem CDE Thyroid \geq 5 rem

The colors are only presented to represent the magnitude of the projected doses. Protective actions for highlighted distances should always be to evacuate (shelter is an option if evacuation is not possible).

Downwind dose rate and dose estimates are given for site boundary and each 0.5 mile increment to 10 miles. For each method, except field team survey, data is presented on six columns which can be scrolled either up or down throughout the downwind distances. Information is given for external dose rate in mrem/hr, external dose, inhalation dose, deposition dose, Total (whole body) dose, and thyroid dose in rem. For the field team survey method, data is presented on four columns which can be scrolled either up or down throughout the downwind distances. Information is given for centerline X/Qs, external dose rate in mR/hr, and external dose in rem.

The command options section, common to all methods, contains controls which allow movement and functions within the application. Options are as follows:

Command Bar		
Input	Control	Options/Entry
Print	Command	Initially disabled.
r.	Button	Enabled after the necessary base data is entered to allow a dose assessment printout of current method screen information.
PARs	Command Button	Initially disabled. Enabled after the necessary base information is entered allowing the user to continue on to the Dose Assessment Results window (see PAR/Dose Assessment Results).
Exit	Command Button	May be used at any time to exit the current assessment method and return to the main data entry window.

[1] Monitored Release

The monitored release method is based on information, actual or estimated, from the plant effluent monitors. Downwind dose estimates and whether Protective Action Guides (PAGs) have been exceeded will be updated for each change in input data. The release point is initially set to correspond to the elevation applicable to the release path regardless of the monitor chosen. Changing the release point will determine the X/Q values used to calculate the downwind doses (elevated or ground level), but will not alter the dominant release path chosen on the main data entry window. When switching between monitors or release points, it is necessary to reenter the dominant release path if a new process reduction factor is desired or to reenter the meteorological data that corresponds to the chosen release point (elevated or ground level). Data entry options available in the monitored release window are as follows:

Monitored F	Monitored Release Information		
Input	Control	Options/Entry	
Monitor	Option	Main Stack	
	Button	Reactor Building Vent	
		Turbine Building Vent	
Range	Option	High	
	Button	Low (not available for Turbine Building vent)	
Reading	Text Box	As indicated on Control Room monitors in cps or R/hr (units are	
		determined by the selected monitor range).	
Vent Flow	Text Box	Default values in SCFM.	
Rate		Can be changed to user specified value if data is available.	
Release	Text Box	Information only.	
Duration		Corresponds to the release duration specified on the full	
		assessment window.	
Release	Option	Initially defaults to elevation of the applicable release path.	
Point	Button	Elevated	
		Ground	

[2] Containment Leakage/Failure

The containment leakage/failure method is based on information, actual or estimated. which assumes a significant release of Reactor coolant into Primary Containment (such as a LOCA). The amount of leakage is heavily dependent on containment pressure. Care should be taken when estimates of containment leakage are used to determine protective action recommendations. Containment penetrations and seals are not designed to withstand adverse environmental conditions for an extended period of time following a core damage accident. Under these conditions large leak rates are more appropriately considered as a failure to isolate. Controlled venting of containment can also be modeled as a failure to isolate, when the appropriate process reduction factor is utilized. A catastrophic containment failure is one that results in release of a large fraction of the fission products in the containment atmosphere in a very short period. Some examples of catastrophic failure include hydrogen detonation/burn. steam explosions or explosion induced missiles, direct containment heating, and containment overpressurization. Downwind dose estimates and whether Protective Action Guides (PAGs) have been exceeded will be updated for each change in input data. The release point is initially set to correspond to the elevation applicable to the release path. Changing the release point will determine the X/Q values used to calculate the downwind doses (elevated or ground level), but will not alter the dominant release path chosen on the main data entry window. When switching between release points, it is necessary to reenter the dominant release path if a new process reduction factor is desired or to reenter the meteorological data that corresponds to the chosen release point (elevated or ground level). Data entry options available for this method are as follows:

Containment Leakage/Failure Information		
Input	Control	Options/Entry
Discharge	Option	Leakage
Туре	Button	Failure to Isolate
		Catastrophic Failure
% Leakage	Text Box	0.5% (default).
X		Only affects PAR and dose data when the leakage option is selected.
Release	Option	Elevated
Point	Button	Ground Defaults to elevation for the applicable release path.
Release	Text Box	Information only.
Duration		Corresponds to release duration specified on the full assessment window.
		• If release duration > 24 hours and the failure to isolate option is chosen, release duration will default to 24 hours.
		• If release duration is > 1 hour and catastrophic failure is chosen, release duration will default to 1 hour.

[3] FIELD TEAM ANALYSIS

The field team analysis method is based on radiological survey or isotopic sample information taken within the plume. Downwind dose estimates and whether Protective Action Guides (PAGs) have been exceeded will be updated for each change in input data. Protective action distances and the 'PAR' command button are not available in the survey mode (ingestion and deposition components cannot be determined by surveys alone). Caution should be used when comparing external dose rates to field data. External dose rates are based on dose conversion factors in units of rem/hr applied to a projected isotopic concentration. All field team dose estimates are based on ground level X/Q values to eliminate the cross-distance effect of terrain elevation changes. Isotopic concentrations can only be entered while in the sample mode; however, previously entered concentrations will be retained when switching from the sample into the survey mode. Data entry options available for this method are as follows:

Field Team Analysis Information		
Input	Control	Options/Entry
Downwind	Text Box	As determined by field team location entered in miles.
Distance		Distances beyond 10 miles are not accepted within this field.
Crosswind	Text Box	As determined by field team location entered in miles.
Distance		Distances beyond 5 miles are not accepted within this field.
Level	Text Box	As determined by field team survey results reported in mR/hr.
Survey	Text Box	Entered as h:mm for the time that the survey was performed.
Time		
Travel	Text Box	Information only.
Time		Represents the time it would take (under the given meteorological
		conditions) for a plant release to reach the field team location.
Release	Text Box	Information only.
Time		Represents the time a release left the plant corresponding to the
		conditions observed at the field team location at the time of survey
		or sample.
Field Team	Text Box	Information only.
X/Q		X/Q value related to the field team location.
Release 🔨	Text Box	Information only.
Duration		Corresponds to release duration specified on the full assessment
		window.
Basis	Option	Survey (default)
	Button	Sample
Isotopic	Sub form	Scrolling list of 66 isotopes.
Conc		Values entered in µCi/cc.
		Disabled when 'Survey' option button is selected.
		Values are retained when switching between modes.

[4] Release Point Analysis

The release point analysis method is based on isotopic sample information taken from any release point to the environment. Downwind dose estimates and whether Protective Action Guides (PAGs) have been exceeded will be updated for each change in input data. The release point is initially set to correspond to the elevation applicable to the dominant release path. Changing the release point will determine the X/Q values used to calculate the downwind doses (elevated or ground level). The process reduction factor is not applied to release point isotopic concentrations. Data entry options available in the release point analysis window are as follows:

Release Poi	nt Analysis I	nformation
Input	Control	Options/Entry
Isotopic	Sub form	Scrolling list of 66 isotopes.
Conc		Values entered in µCi/cc.
Vent Flow Rate	Text Box	Values entered in SCFM for ventilation flow rate corresponding to the release point.
		If actual values are not known, the default values for the common release points below may be used:
		Main Stack Low Range 24,000 SCFM
		Main Stack High Range 4,000 SCFM
		Reactor Building
		Turbine Building 210,000 SCFM
		• Each Turbine Building fan (six total) default flow rate is 35,000 SCFM.
		 For release point samples taken at other locations, the release rate must be estimated from information specific to the sample point.
Release	Option	Elevated
Point	Button	Ground
		Defaults to elevation of the dominant release path.

6.6 PROTECTIVE ACTION RECOMMENDATIONS

The Dose Assessment Results window evaluates the downwind dose estimate in relation to the protective action guides (PAGs). The window is divided into four primary sections: key information, EPZ Subarea map, protective action guide information relating to EPZ Subareas, and dose projections. The key information section shows the assessment method, the current offsite evacuation conditions, meteorological data, and the release duration. The EPZ

Subarea map graphically illustrates and outlines the subareas within the 10 mile EPZ. The protective action guide relating to an EPZ Subarea section provides information on what EPZ Subareas have or have not exceeded the PAGs. Subareas in which the projected dose exceeds the protective action guides are boxed for determining protective action recommendations based on dose assessment results (EPZ Subareas that require evacuation). The dose projection section provides downwind radiological condition information in tabular format. Affected subareas and projected doses are given for the three rings surrounding the site. Dose information is color-coded



to indicate the projected exposure for unprotected and sheltered conditions. A value highlighted in red indicates a TEDE (whole body) dose equal to or greater than 1 rem or a CDE thyroid dose equal to or greater than 5 rem. Green values indicate TEDE (whole body) doses less than 1 rem and CDE thyroid doses less than 5 rem. A command options section is available to allow movement and provide functions within the Dose Assessment Results window. Command bar options are as follows:

Dose Assess	<u>sment Resul</u> Control	<u>ts</u> Options/Entry
RRs (Release Rates)	Command Button	Displays a pop-up window showing the projected release rates for noble gases, halogens, and particulates.
Print	Command Button	Prints a hard copy of the protective action recommendations.
Exit	Command Button	Used to exit the Dose Assessment Results window and return to the previous assessment method window.

The release rate information is necessary for compatibility with the NRC dose code RASCAL. Site team personnel and national or regional response centers do not maintain monitor conversion capabilities for each utility and therefore must rely on a common process to conduct independent dose assessment calculations.

6.7 EMERGENCY WORKER DOSE PROJECTION

Emergency worker dose projection allows for the quick evaluation of indicated to actual and thyroid dose rates, the comparison of projected doses for a given exposure period, and the estimation of the indicated dose and exposure period for targeted actual or thyroid doses. Projections are based on source term estimation decay time, damage type, and release path inputs. Projected doses are time integrated to account for decay during the exposure period. Projections should only be used for dose and exposure period evaluation prior to obtaining field sample analysis results. Data entry options and information available in the emergency worker dose projection window are as follows:

Emergency Worker Dose Projections Information			
Input	Control	Options/Entry	
Hours After	Text Box	Entered as h:mm for time after reactor shutdown when exposure	
Shutdown		period begins.	
		Enter '0:00' for conditions where the reactor is not yet shutdown.	
Indicated to	Text Box	Information only.	
Actual		Describes the instantaneous indicated to actual projected dose rate	
7		ratio.	
Indicated to	Text Box	Information only.	
Thyroid		Describes the instantaneous indicated to thyroid projected dose rate ratio.	
Indicated	Text Box	As determined by projection or field team survey results at the	
Dose Rate		exposure location reported in mR/hr.	
RPF	Text Box	Respiratory protection factor.	
		Can be used to account for inhalation source reduction by	
		filtration/exclusion.	
Exposure	Text Box	Entered as himm for the time duration of the projected exposure	
Period	True Dave		
Indicated	Text Box	Information only.	
Dose		Represents the indicated dose for the given exposure duration.	
Actual	Text Box	Information only.	
Dose		Represents the actual dose for the given exposure duration.	
Thyroid	Text Box	Information only.	
Dose		Represents the thyroid dose for the given exposure duration.	
Actual	Text Box	Entered as a targeted actual dose to obtain indicated dose and	
Dose		exposure duration information.	
Thyroid	Text Box	Entered as a targeted thyroid dose to obtain indicated dose and	
Drint	Command	Prints a bard copy of the emergency worker dose projection	
	Button		
Exit	Command	Used to exit the emergency worker dose projection window and	
	Button	return to the main data entry window.	

6.8 OFFSITE DOSE CALCULATION, BACKUP METHOD

Offsite dose rates may be estimated using data from effluent monitors. Release and meteorological data may be obtained from the Control Room via the Rad Data Communication Line. Attachment 1 (Offsite Dose and PAR Worksheet) should be used to calculate the dose rates. The step numbers in the following sections correspond to the item numbers on the worksheet.

Part A, Radiological Release Data

Ì.

1. Select the release point. The release point is determined by whichever effluent radiation monitor is reading above normal. If more than one monitor is reading above normal, perform additional calculations on separate worksheets for <u>all</u> affected release points.

NOTE

Normally, the Reactor Building Vent and Main Stack monitors read less than 1000 cps.

- 2. Record the release point radiation monitor reading and check the appropriate units (R/hr or cps). If the low range monitor is offscale high and the high range monitor is offscale low, record monitor reading of 0.1 R/hr.
- 3. Record the time elapsed since Reactor shutdown in hours. Shutdown refers to the time when the Reactor was made subcritical and therefore stopped generating fission.
- 4. Locate the appropriate monitor table (A.1 through A.5). Determine the time after shutdown (TAS) column which represents the recorded time after shutdown in block A.3 (do not interpolate).

<u>NOTE</u>

Monitor reading to release rate is a linear relationship. Identify the row in which the monitor reading is closest to the recorded monitor reading in block A.2 (do not interpolate). For example, a reading of 200 R/hr would correspond to the 2 R/hr row on the table. Record the group release rates for noble gases, halogens, particulates, and total, accounting for any order of magnitude adjustments.

	NOTE			
Example: Main stack high range reading 200 R/hr at 10 hours after shutdown. Find the 10 hour column and the 2 R/hr row.				
Noble Gas:	8.14E+01 X 100 = 8.14E+03 Ci/sec			
Halogen:	2.32E-01 X 100 = 2.32E+01 Ci/sec			
Particulate: 5.55E-02 X 100 = 5.55E+00 Ci/sec				
Total:	8.14E+01 X 100 = 8.14E+03 Ci/sec			

Table A.1: Main Stack High Range

Noble Gas Release Rate (Ci/sec) at TAS					
R/hr	T>0	T≥3.2hrs	T≥31.6hrs	T≥316hrs	
	T<3.2hr	s T<31.6hrs	T<316hrs	T≤1000hrs	
1	7.45E+(00 4.07E+01	1.21E+03	5.22E+01	
2	1.49E+0	01 8.14E+01	2.41E+03	1.04E+02	
3	2.23E+0	01 1.22E+02	3.62E+03	1.57E+02	
4	2.98E+0	01 1.63E+02	4.82E+03	2.09E+02	
5	3.72E+0	01 2.03E+02	2 6.03E+03	2.61E+02	
6	4.47E+0	01 2.44E+02	2 7.23E+03	3.13E+02	
7	5.21E+(01 2.85E+02	8.44E+03	3.65E+02	
8	5.96E+0	01 3.25E+02	9.65E+03	4.18E+02	
9	6.70E+0	01 3.66E+02	2 1.09E+04	4.70E+02	

Halogen Release Rate (Ci/sec) at TAS

T>0	T≥3.2hrs	T≥31.6hrs	T≥316hrs
T<3.2hrs	T<31.6hrs	T<316hrs	T≤1000hrs
2.74E-02	1.16E-01	1.69E+00	1.50E-01
5.49E-02	2.32E-01	3.37E+00	3.00E-01
8.23E-02	3.48E-01	5.06E+00	4.49E-01
1.10E-01	4.64E-01	6.74E+00	5.99E-01
1.37E-01	5.80E-01	8.43E+00	7.49E-01
1.65E-01	6.96E-01	1.01E+01	8.99E-01
1.92E-01	8.12E-01	1.18E+01	1.05E+00
2.20E-01	9.28E-01	1.35E+01	1.20E+00
2.47E-01	1.04E+00	1.52E+01	1.35E+00

Particulate Release Rate (Ci/sec) at TAS

R/hr T>0 T≥3.2hrs T≥31.6hrs T≥316hrs T<3.2hrs T<31.6hrs | T<316hrs | T≤1000hrs 2.78E-02 1.62E+00 3.51E+00 1.11E-02 1 5.55E-02 3.24E+00 7.01E+00 2.23E-02 2 8.33E-02 4.86E+00 1.05E+01 3 3.34E-02 6.48E+00 1.40E+01 4 4.45E-02 1.11E-01 1.39E-01 8.10E+00 1.75E+01 5 5.57E-02 9.72E+00 2.10E+01 6 6.68E-02 1.67E-01 1.13E+01 2.45E+01 7 7.79E-02 1.94E-01 1.30E+01 2.81E+01 8.91E-02 2.22E-01 8 2.50E-01 1.46E+01 3.16E+01 9 1.00E-01

Total Release Rate (Ci/sec) at TAS

T>0	T≥3.2hrs	T≥31.6hrs	T≥316hrs
T<3.2hrs	T<31.6hrs	T<316hrs	T≤1000hrs
7.48E+00	4.08E+01	1.21E+03	5.59E+01
1.50E+01	8.17E+01	2.42E+03	1.12E+02
2.25E+01	1.22E+02	3.63E+03	1.68E+02
2.99E+01	1.63E+02	4.84E+03	2.23E+02
3.74E+01	2.04E+02	6.04E+03	2.79E+02
4.49E+01	2.45E+02	7.25E+03	3.35E+02
5.24E+01	2.86E+02	8.46E+03	3.91E+02
5.99E+01	3.27E+02	9.67E+03	4.47E+02
6.74E+01	3.67E+02	1.09E+04	5.03E+02

Noble Gas Release Rate (Ci/sec) at TAS					
R/hr		T>0 T<3.2hrs	T≥3.2hrs T<31.6hrs	T≥31.6hrs T<316hrs	T≥316hrs T≤1000hrs
1		1.12E+01	3.60E+01	7.58E+01	3.65E+00
2		2.24E+01	7.20E+01	1.52E+02	7.31E+00
3		3.36E+01	1.08E+02	2.27E+02	1.10E+01
4		4.48E+01	1.44E+02	3.03E+02	1.46E+01
5		5.60E+01	1.80E+02	3.79E+02	1.83E+01
6		6.72E+01	2.16E+02	4.55E+02	2.19E+01
7		7.84E+01	2.52E+02	5.31E+02	2.56E+01
8		8.96E+01	2.88E+02	6.07E+02	2.92E+01
9		1.01E+02	3.24E+02	6.82E+02	3.29E+01

Table A.2: Reactor Building Vent High Range

Halogen Release Rate (Ci/sec) at TAS

	Contraction of the second second		
T>0	T≥3.2hrs	T≥31.6hrs	T≥316hrs
T<3.2hrs	T<31.6hrs	T<316hrs	T≤1000hrs
1.65E+00	4.11E+00	4.24E+00	4.19E-01
3.30E+00	8.21E+00	8.48E+00	8.39E-01
4.96E+00	1.23E+01	1.27E+01	1.26E+00
6.61E+00	1.64E+01	1.70E+01	1.68E+00
8.26E+00	2.05E+01	2.12E+01	2.10E+00
9.91E+00	2.46E+01	2.54E+01	2.52E+00
1.16E+01	2.87E+01	2.97E+01	2.94E+00
1.32E+01	3.29E+01	3.39E+01	3.35E+00
1.49E+01	3.70E+01	3.82E+01	3.77E+00

Particulate Release Rate (Ci/sec) at TAS

T>0	T≥3.2hrs	T≥31.6hrs	T≥316hrs
T<3.2hrs	T<31.6hrs	T<316hrs	T≤1000hrs
6.70E-01	9.83E-01	4.07E+00	9.82E+00
1.34E+00	1.97E+00	8.15E+00	1.96E+01
2.01E+00	2.95E+00	1.22E+01	2.94E+01
2.68E+00	3.93E+00	1.63E+01	3.93E+01
3.35E+00	4.92E+00	2.04E+01	4.91E+01
4.02E+00	5.90E+00	2.44E+01	5.89E+01
4.69E+00	6.88E+00	2.85E+01	6.87E+01
5.36E+00	7.87E+00	3.26E+01	7.85E+01
6.03E+00	8.85E+00	3.67E+01	8.83E+01
	T>0 T<3.2hrs 6.70E-01 1.34E+00 2.01E+00 2.68E+00 3.35E+00 4.02E+00 4.69E+00 5.36E+00 6.03E+00	T>0T≥3.2hrsT<3.2hrs	T>0T≥3.2hrsT≥31.6hrsT<3.2hrs

Total Release Rate (Ci/sec) at TAS

T>0	T≥3.2hrs	T≥31.6hrs	T≥316hrs
T<3.2hrs	T<31.6hrs	T<316hrs	T≤1000hrs
1.35E+01	4.11E+01	8.41E+01	1.39E+01
2.70E+01	8.22E+01	1.68E+02	2.78E+01
4.06E+01	1.23E+02	2.52E+02	4.17E+01
5.41E+01	1.64E+02	3.37E+02	5.56E+01
6.76E+01	2.06E+02	4.21E+02	6.94E+01
8.11E+01	2.47E+02	5.05E+02	8:33E+01
9.47E+01	2.88E+02	5.89E+02	9.72E+01
1.08E+02	3.29E+02	6.73E+02	1.11E+02
1.22E+02	3.70E+02	7.57E+02	1.25E+02

Table A.3: Turbine Building Vent High Range

	Noble Gas Release Rate (Ci/sec) at TAS					
R/hr	i I	T>0	T≥3.2hrs	T≥31.6hrs	T≥316hrs	
		T<3.2hrs	T<31.6hrs	T<316hrs	T≤1000hrs	
1		2.20E+00	6.85E+00	1.39E+01	7.20E-01	
2		4.39E+00	1.37E+01	2.78E+01	1.44E+00	
3		6.59E+00	2.06E+01	4.16E+01	2.16E+00	
4		8.78E+00	2.74E+01	5.55E+01	2.88E+00	
5		1.10E+01	3.43E+01	6.94E+01	3.60E+00	
6		1.32E+01	4.11E+01	8.33E+01	4.32E+00	
7		1.54E+01	4.80E+01	9.72E+01	5.04E+00	
8		1.76E+01	5.48E+01	1.11E+02	5.76E+00	
9		1.98E+01	6.17E+01	1.25E+02	6.48E+00	

Particulate Release Rate (Ci/sec) at TAS

R/hr	T>0	T≥3.2hrs	T≥31.6hrs	T≥316hrs
	T<3.2hrs	T<31.6hrs	T<316hrs	T≤1000hrs
1	1.31E-01	1.87E-01	7.46E-01	1.94E+00
2	2.63E-01	3.74E-01	1.49E+00	3.87E+00
3	3.94E-01	5.61E-01	2.24E+00	5.81E+00
4	5.25E-01	7.48E-01	2.98E+00	7.74E+00
5	6.56E-01	9.36E-01	3.73E+00	9.68E+00
6	7.88E-01	1.12E+00	4.48E+00	1.16E+01
7	9.19E-01	1.31E+00	5.22E+00	1.35E+01
8	1.05E+00	1.50E+00	5.97E+00	1.55E+01
9	1.18E+00	1.68E+00	6.71E+00	1.74E+01

Halogen Release Rate (Ci/sec) at TAS

T>0 T<3.2hrs	T≥3.2hrs T<31.6hrs	T≥31.6hrs T<316hrs	T≥316hrs T≤1000hrs
3.24E-01	7.81E-01	7.76E-01	8.27E-02
6.48E-01	1.56E+00	1.55E+00	1.65E-01
9.71E-01	2.34E+00	2.33E+00	2.48E-01
1.30E+00	3.13E+00	3.11E+00	3.31E-01
1.62E+00	3.91E+00	3.88E+00	4.13E-01
1.94E+00	4.69E+00	4.66E+00	4.96E-01
2.27E+00	5.47E+00	5.44E+00	5.79E-01
2.59E+00	6.25E+00	6.21E+00	6.61E-01
2.91E+00	7.03E+00	6.99E+00	7.44E-01

Total Release Rate (Ci/sec) at TAS

T>0	T≥3.2hrs	T≥31.6hrs	T≥316hrs		
T<3.2hrs	T<31.6hrs	T<316hrs	T≤1000hrs		
2.65E+00	7.82E+00	1.54E+01	2.74E+00		
5.30E+00	1.56E+01	3.08E+01	5.48E+00		
7.95E+00	2.35E+01	4.62E+01	8.22E+00		
1.06E+01	3.13E+01	6.16E+01	1.10E+01		
1.33E+01	3.91E+01	7.70E+01	1.37E+01		
1.59E+01	4.69E+01	9.24E+01	1.64E+01		
1.86E+01	5.48E+01	1.08E+02	1.92E+01		
2.12E+01	6.26E+01	1.23E+02	2.19E+01		
2.39E+01	7.04E+01	1.39E+02	2.46E+01		

Table A.4:	<u>Main</u>	Stack	Low	<u>Range</u>
				and the second

Noble Gas Release Rate (Ci/sec) at TAS				
cps	T>0	T≥3.2hrs	T≥31.6hrs	T≥316hrs
	T<3.2hrs	T<31.6hrs	T<316hrs	T≤1000hrs
1	2.88E-05	4.20E-05	5.61E-05	1.30E-04
2	5.77E-05	8.39E-05	1.12E-04	2.61E-04
3	8.65E-05	1.26E-04	1.68E-04	3.91E-04
4	1.15E-04	1.68E-04	2.24E-04	5.22E-04
5	1.44E-04	2.10E-04	2.80E-04	6.52E-04
6	1.73E-04	2.52E-04	3.36E-04	7.83E-04
7	2.02E-04	2.94E-04	3.93E-04	9.13E-04
8	2.31E-04	3.36E-04	4.49E-04	1.04E-03
9	2.60E-04	3.78E-04	5.05E-04	1.17E-03

Particulate Release Rate (Ci/sec) at TAS

cps	T>0 T<3.2hrs	T≥3.2hrs T<31.6hrs	T≥31.6hrs T<316hrs	T≥316hrs T≤1000hrs
1	4.31E-08	2.86E-08	7.53E-08	8.77E-06
2	8.62E-08	5.73E-08	1.51E-07	1.75E-05
3	1.29E-07	8.59E-08	2.26E-07	2.63E-05
4	1.72E-07	1.15E-07	3.01E-07	3.51E-05
5	2.16E-07	1.43E-07	3.77E-07	4.38E-05
6	2.59E-07	1.72E-07	4.52E-07	5.26E-05
7	3.02E-07	2.01E-07	5.27E-07	6.14E-05
8	3.45E-07	2.29E-07	6.03E-07	7.01E-05
9	3.88E-07	2.58E-07	6.78E-07	7.89E-05

Halogen Release Rate (Ci/sec) at TAS

T>0 T<3.2hrs	T≥3.2hrs T<31.6hrs	T≥31.6hrs T<316hrs	T≥316hrs T≤1000hrs
1.06E-07	1.20E-07	7.84E-08	3.74E-07
2.13E-07	2.39E-07	1.57E-07	7.49E-07
3.19E-07	3.59E-07	2.35E-07	1.12E-06
4.25E-07	4.79E-07	3.14E-07	1.50E-06
5.32E-07	5.98E-07	3.92E-07	1.87E-06
6.38E-07	7.18E-07	4.70E-07	2.25E-06
7.44E-07	8.38E-07	5.49E-07	2.62E-06
8.51E-07	9.57E-07	6.27E-07	3.00E-06
9.57E-07	1.08E-06	7.06E-07	3.37E-06

Total Release Rate (Ci/sec) at TAS

T>0	T≥3.2hrs	T≥31.6hrs	T≥316hrs
T<3.2hrs	T<31.6hrs	T<316hrs	T≤1000hrs
2.90E-05	4.21E-05	5.62E-05	1.40E-04
5.80E-05	8.42E-05	1.12E-04	2.79E-04
8.70E-05	1.26E-04	1.69E-04	4.19E-04
1.16E-04	1.68E-04	2.25E-04	5.58E-04
1.45E-04	2.11E-04	2.81E-04	6.98E-04
1.74E-04	2.53E-04	3.37E-04	8.38E-04
2.03E-04	2.95E-04	3.94E-04	9.77E-04
2.32E-04	3.37E-04	4.50E-04	1.12E-03
2.61E-04	3.79E-04	5.06E-04	1.26E-03

Table A.5: Reactor Building Vent Low Range

	Noble Gas Release Rate (Ci/sec) at TAS				
cps		T>0	T≥3.2hrs	T≥31.6hrs	T≥316hrs
		T<3.2hrs	T<31.6hrs	T<316hrs	T≤1000hrs
1		1.79E-04	2.60E-04	3.48E-04	8.10E-04
2		3.58E-04	5.21E-04	6.96E-04	1.62E-03
3		5.37E-04	7.81E-04	1.04E-03	2.43E-03
4		7.16E-04	1.04E-03	1.39E-03	3.24E-03
5		8.95E-04	1.30E-03	1.74E-03	4.05E-03
6		1.07E-03	1.56E-03	2.09E-03	4.86E-03
7		1.25E-03	1.82E-03	2.44E-03	5.67E-03
8		1.43E-03	2.08E-03	2.78E-03	6.48E-03
9		1.61E-03	2.34E-03	3.13E-03	7.29E-03

Particulate Release Rate (Ci/sec) at TAS T>0 T≥31.6hrs | T≥316hrs T≥3.2hrs cps_. T<3.2hrs T<31.6hrs T<316hrs |T≤1000hrs 2.18E-03 1 7.11E-06 1.87E-05 1.07E-05 2 2.14E-05 1.42E-05 3.74E-05 4.35E-03 2.13E-05 5.61E-05 6.53E-03 3 3.21E-05 7.48E-05 8.70E-03 4 4.28E-05 2.84E-05 9.35E-05 1.09E-02 5 5.35E-05 3.56E-05 1.12E-04 1.31E-02 6 6.42E-05 4.27E-05 7 1.31E-04 1.52E-02 7.49E-05 4.98E-05 1.50E-04 1.74E-02 8 8.56E-05 5.69E-05 9 6.40E-05 1.68E-04 1.96E-02 9.64E-05

Halogen Release Rate (Ci/sec) at TAS

T>0	T≥3.2hrs	T≥31.6hrs	T≥316hrs
T<3.2hrs	T<31.6hrs	T<316hrs	T≤1000hrs
2.64E-05	2.97E-05	1.95E-05	9.29E-05
5.28E-05	5.94E-05	3.89E-05	1.86E-04
7.92E-05	8.91E-05	5.84E-05	2.79E-04
1.06E-04	1.19E-04	7.79E-05	3.72E-04
1.32E-04	1.49E-04	9.73E-05	4.65E-04
1.58E-04	1.78E-04	1.17E-04	5.58E-04
1.85E-04	2.08E-04	1.36E-04	6.51E-04
2.11E-04	2.38E-04	1.56E-04	7.44E-04
2.38E-04	2.67E-04	1.75E-04	8.36E-04

Total Release Rate (Ci/sec) at TAS

			a company and the second se
T>0	T≥3.2hrs	T≥31.6hrs	T≥316hrs
T<3.2hrs	T<31.6hrs	T<316hrs	T≤1000hrs
2.16E-04	2.97E-04	3.86E-04	3.08E-03
4.32E-04	5.95E-04	7.72E-04	6.16E-03
6.48E-04	8.92E-04	1.16E-03	9.24E-03
8.64E-04	1.19E-03	1.54E-03	1.23E-02
1.08E-03	1.49E-03	1.93E-03	1.54E-02
1.30E-03	1.78E-03	2.32E-03	1.85E-02
1.51E-03	2.08E-03	2.70E-03	2.16E-02
1.73E-03	2.38E-03	3.09E-03	2.46E-02
1.95E-03	2.68E-03	3.48E-03	2.77E-02

Part B, Atmospheric Dispersion Factor

<u>NOTE</u>

Meteorological data from the 220' tower are available from the EOF and the Control Room. Data from the 160' tower are only available in the EOF and at the base of the 160' tower. If meteorological data from the 220' tower are unavailable, use the data from the 160' tower. If 160' tower data are necessary in the Control Room, dispatch a monitoring team to the tower to obtain readings and radio the results back.

- 1. Record the wind direction, in degrees, for the 220' (or the 160' tower if necessary) and 33' met tower elevations. This is read directly from the strip charts and represents the direction the wind is coming from, <u>not</u> the downwind affected direction.
- 2. Record the wind speed, in MPH, for the 220' (or the 160' tower if necessary) and 33' met tower elevations.
- 3. Record the ΔT (temperature change with height, in °F). ΔT from either tower is the difference in temperature between the uppermost sensor and the 33' sensor (higher lower).
- 4. Determine and record the atmospheric stability class from Table B.1 below:

	Table D	• 1
∆T (F) 220' Tower	Stability Class	∆T (F) 160' Tower
≤ -1.9	A	≤ -1.3
> -1.9 and ≤ -1.7	B	> -1.3 and ≤ -1.2
> -1.7 and ≤ -1.5	С	> -1.2 and ≤ -1.0
> -1.5 and ≤ -0.5	D	> -1.0 and ≤ -0.3
> -0.5 and ≤ +1.5	Е	> -0.3 and ≤ +1.0
> +1.5 and ≤ +4.1	F	> +1.0 and \leq +2.8
> +4.1	G	> +2.8

Table B.1

5. Determine and record the affected downwind subareas from Table B.2 using the appropriate wind direction reading (wind direction *FROM*). If the release is from the Main Stack, use the 220' (or the 160') elevation wind direction. If the release is not from the Main Stack, use the 33' wind direction reading.

Wind Direction	Inner	Middle	Outer
006° to 019°	1	2	5
020° to 021°	1	2, 3	5, 6
022° to 056°	1	2, 3	5, 6, 11
057° to 063°	1	2, 3	6, 11
064° to 066°	1, 12	2, 3	6, 11
067° to 069°	1, 12	2, 3	6, 7, 11
070° to 103°	1, 12	3	6, 7, 8, 11
104° to 109°	1, 12	3	6, 7, 8, 9, 11
110° to 115°	1, 12	3	6, 7, 8, 9
116° to 122°	1, 12	3	7, 8, 9
123° to 129°	1, 12	3, 4	7, 8, 9
130° to 132°	1, 12	3, 4	7, 8, 9, 10
133° to 140°	1, 12	3, 4	8, 9, 10
141° to 175°	1, 12	4	9, 10
176° to 179°	1, 12	4	10
180° to 183°	1, 12	4	N/A
184° to 305°	1, 12	N/A	N/A
306° to 318°	1, 12	2	N/A
319° to 005°	1, 12	2	5

Table B.2

6. Determine and record the uncorrected X/Q values for the three rings. If the release is from the Main Stack, record the X/Q values from Table B.3. Otherwise, use Table B.4.

14010 2101 11	Ring		B	C	D	E	F	G
350° to 011°	Inner	3.80E-05	3.12E-05	5.90E-05	5.81E-05	8.96E-05	1.32E-04	1.58E-04
	Middle	4.57E-07	1.95E-06	1.09E-05	2.53E-05	5.35E-05	1.20E-04	2.51E-04
	Outer	2.11E-07	2.54E-07	3.23E-06	7.81E-06	1.69E-05	3.65E-05	8.76E-05
012° to 034°	Inner	3.84E-05	3.12E-05	5.90E-05	6.87E-05	1.26E-04	2.01E-04	5.03E-04
	Middle	4.57E-07	1.95E-06	1.07E-05	2.56E-05	5.51E-05	1.32E-04	3.31E-04
	Outer	2.11E-07	2.54E-07	3.21E-06	7.70E-06	1.69E-05	3.74E-05	9.34E-05
035° to 056°	Inner	3.97E-05	3.06E-05	5.08E-05	4.55E-05	5.46E-05	3.78E-05	4.85E-06
	Middle	4.57E-07	1.96E-06	1.15E-05	2.19E-05	3.82E-05	3.91E-05	2.30E-05
	Outer	2.11E-07	2.54E-07	3.30E-06	8.03E-06	1.48E-05	2.25E-05	2.29E-05
057° to 079°	Inner	3.97E-05	3.04E-05	4.81E-05	4.23E-05	4.98E-05	3.78E-05	4.85E-06
	Middle	4.57E-07	1.96E-06	1.15E-05	2.19E-05	3.82E-05	3.91E-05	2.30E-05
	Outer	2.11E-07	2.54E-07	3.30E-06	8.03E-06	1.48E-05	2.25E-05	2.29E-05
080° to 101°	Inner	3.88E-05	3.02E-05	4.53E-05	3.02E-05	2.87E-05	6.65E-06	3.88E-08
	Middle	4.58E-07	1.97E-06	1.18E-05	1.88E-05	2.61E-05	1.46E-05	4.63E-06
	Outer	2.11E-07	2.54E-07	3.33E-06	8.05E-06	1.30E-05	1.90E-05	3.63E-05
102° to 124°	Inner	3.84E-05	2.96E-05	3.75E-05	2.24E-05	2.03E-05	2.21E-06	1.83E-09
	Middle	4.58E-07	1.97E-06	1.19E-05	1.72E-05	2.05E-05	9.63E-06	1.68E-06
	Outer	2.11E-07	2.54E-07	3.35E-06	8.04E-06	1.21E-05	9.76E-06	7.24E-06
125° to 146°	Inner	3.80E-05	2.81E-05	2.43E-05	1.31E-05	6.46E-06	5.57E-08	6.61E-14
	Middle	4.58E-07	1.97E-06	1.21E-05	1.37E-05	1.14E-05	2.88E-06	5.63E-08
	Outer	2.11E-07	2.55E-07	3.37E-06	8.01E-06	9.98E-06	9.02E-06	5.10E-06
147° to 169°	Inner	3.72E-05	2.77E-05	2.42E-05	1.15E-05	4.34E-06	1.41E-08	1.45E-15
	Middle	4.58E-07	1.97E-06	1.21E-05	1.29E-05	1.03E-05	1.89E-06	1.58E-08
	Outer	2.11E-07	2.55E-07	3.37E-06	8.00E-06	9.54E-06	4.05E-06	7.01E-07
170° to 281°	Inner	3.72E-05	2.77E-05	2.42E-05	1.15E-05	4.34E-06	1.41E-08	1.45E-15
	Middle	4.58E-07	1.97E-06	1.21E-05	1.29E-05	1.03E-05	1.89E-06	1.58E-08
	Outer	2.11E-07	2.55E-07	3.37E-06	8.00E-06	9.54E-06	3.45E-06	3.62E-07
282° to 304°	Inner	3.72E-05	2.77E-05	2.43E-05	1.24E-05	5.51E-06	3.26E-08	1.49E-14
	Middle	4.58E-07	1.97E-06	1.21E-05	1.33E-05	1.09E-05	2.43E-06	3.43E-08
	Outer	2.11E-07	2.55E-07	3.37E-06	8.01E-06	9.79E-06	3.79E-06	5.40E-07
305° to 326°	Inner	3.72E-05	2.77E-05	2.43E-05	1.31E-05	6.46E-06	5.57E-08	6.61E-14
	Middle	4.58E-07	1.97E-06	1.21E-05	1.37E-05	1.14E-05	2.88E-06	5.63E-08
	Outer	2.11E-07	2.55E-07	3.37E-06	8.01E-06	9.98E-06	4.05E-06	7.01E-07
327° to 349°	Inner	3.74E-05	2.93E-05	3.50E-05	4.23E-05	4.71E-05	2.27E-05	1.17E-06
	Middle	4.58E-07	1.96E-06	1.16E-05	2.09E-05	3.41E-05	2.72E-05	1.44E-05
	Outer	2.11E-07	2.54E-07	3.32E-06	8.04E-06	1.42E-05	1.93E-05	1.49E-05

Table B.4: Reactor and Turbine Building

King I	A	В	C	D	E	۲	G
ner	9.70E-05	2.57E-04	5.87E-04	1.59E-03	3.02E-03	6.77E-03	1.69E-02
ddle	4.58E-07	1.99E-06	1.53E-05	5.11E-05	1.10E-04	2.65E-04	6.62E-04
uter	2.11E-07	2.55E-07	3.59E-06	1.39E-05	3.37E-05	7.47E-05	1.87E-04
	ner ddle uter	ner 9.70E-05 ddle 4.58E-07 uter 2.11E-07	Iner 9.70E-05 2.57E-04 ddle 4.58E-07 1.99E-06 uter 2.11E-07 2.55E-07	Iner 9.70E-05 2.57E-04 5.87E-04 ddle 4.58E-07 1.99E-06 1.53E-05 uter 2.11E-07 2.55E-07 3.59E-06	Ming 9.70E-05 2.57E-04 5.87E-04 1.59E-03 ddle 4.58E-07 1.99E-06 1.53E-05 5.11E-05 uter 2.11E-07 2.55E-07 3.59E-06 1.39E-05	Ming 9.70E-05 2.57E-04 5.87E-04 1.59E-03 3.02E-03 ddle 4.58E-07 1.99E-06 1.53E-05 5.11E-05 1.10E-04 uter 2.11E-07 2.55E-07 3.59E-06 1.39E-05 3.37E-05	Ming 9.70E-05 2.57E-04 5.87E-04 1.59E-03 3.02E-03 6.77E-03 ddle 4.58E-07 1.99E-06 1.53E-05 5.11E-05 1.10E-04 2.65E-04 uter 2.11E-07 2.55E-07 3.59E-06 1.39E-05 3.37E-05 7.47E-05

EP-IP-300 Rev. 4 Page 29 of 35

- 7. Divide the uncorrected X/Q values in Part B.6 by the appropriate wind speed and record the results. If the release is from the Main Stack, use the 220' (or the 160') elevation wind speed reading. If the release is not from the Main Stack, use the 33' wind speed reading.
- 8. Multiply the corrected X/Q values by the *total release rate* value from Part A.4 and record the results as projected downwind concentration.

Part C, Dose Projection Calculation

1. Determine and record the whole body and thyroid dose conversion factors for the appropriate time after shutdown from Table B.5 below:

Dose Conversion Factors (R/hr/µCi/cc)	T>0 T<3.2hrs	T≥3.2hrs T<31.6hrs	T≥31.6hrs T<316hrs	T≥316hrs T≤1000hrs
Main Stack Whole Body	3.69E2	1.73E2	1.49E2	3.29E3
Main Stack Thyroid	9.68E2	1.42E3	1.67E3	3.49E3
Reactor & Turbine Bldg Whole Body	2.77E3	3.58E3	4.71E3	3.69E4
Reactor & Turbine Bldg Thyroid	3.22E4	5.01E4	6.03E4	3.92E4

Table B.5 Time After Shutdown

- 2. Multiply the projected downwind concentrations by the dose conversion factors and record the results as projected downwind dose rate.
- 3. Obtain and record an expected release duration based on plant conditions from Operations personnel. If the release duration is unknown, use 8 hours as an estimate until better information becomes available.
- 4. Multiply the projected downwind dose rate values by the release duration and record the results as projected downwind dose.

Part D, Protective Action Recommendations

- 1. For each ring, compare the projected downwind dose with the protective action criteria. If either the whole body or thyroid dose exceeds the criteria, record the affected subareas from Part B.5 in the evacuation block. If both the whole body and thyroid doses are less than the criteria, record the affected subareas from Part B.5 in the no action required block.
- 2. Complete the signature and date blocks and inform the Offsite Radiological Supervisor (or Operations Shift Superintendent if the EOF is not yet activated) of the results.

7.0 <u>RECORDS</u>

Dose assessment printouts are generated as a result of this Procedure.

- [1] The Protective Action Recommendation and Dose Estimation output shall be submitted to the Emergency Offsite Manager.
- [2] If the hand calculation method is used, the Offsite Dose and PAR Worksheet shall be submitted to the Emergency Offsite Manager.

8.0 ATTACHMENTS

ATTACHMENT 1 - OFFSITE DOSE AND PAR WORKSHEET

ATTACHMENT 2 - DOCUMENT CROSS-REFERENCES

ATTACHMENT 3 - IDENTIFICATION OF COMMITMENTS

OFFSITE DOSE AND PAR WORKSHEET

Pa	Part A: Radiological Release Data					
1.	Release Point: 🔲 Ma	ain Stack 🛛	Reactor Bldg Vent	Turbine Bldg Vent		
2.	2. Radiation Monitor Reading:					
3.	3. Elapsed Time Since Rx S/D: Hours					
4.	Group Release Rates (T	ables A.1-5):				
	Noble Gas:	Ci/sec	Halogens:	Ci/sec		
	Particulates:	Ci/sec	Total:	Ci/sec		
		-				
Pa	irt B: Atmospheric Disp	ersion Factor				
1.	Wind Direction From:	° (220'	' or 160')	° (33')		
2.	Wind Speed:	MPH	(220' or 160')	MPH (33')		
3.	Delta T:	~F	220' [] 160'			
4.	Stability Class:	(Tab	le B.1)			
5.	Affected Downwind Sub	areas (Table B.2	2):			
		Inner Ring	Middle Ring	Outer Ring		
	Subarea(s)					
6.	Uncorrected X/Q (Table	B.3-4):				
		Inner Ring	Middle Ring	Outer Ring		
			I	J		
7.	Corrected X/Q (Part B.6	/ Part B.2): Inner Ring	Middle Ring	Outer Ring		
8.	8. Downwind Concentrations (Part B.7 * Part A.4, Total Release Rate):					
		Inner Ring	Middle Ring	Outer Ring		
]		

OFFSITE DOSE AND PAR WORKSHEET (Cont.)

Part C: Dose Projection Calculation

1. Dose Conversion Factors (Table B.5): _____ (Whole Body)

_____ (Thyroid)

2. Downwind Dose Rates (Part B.8 * Part C.1): rem/hr Inner Ring Middle Ring Outer Ring Whole Body Thyroid

3. Release Duration: _____ Hours

4. Downwind Dose (Part C.2 * Part C.3):

rem	Inner Ring	Middle Ring	Outer Ring
Whole Body			
Thyroid			

Part D: Protective Action Recommendations

Criteria: Whole Body 1/1 rem southyrold 5 rem

1. Subarea Actions:

	Inner Ring	Middle Ring	Outer Ring
Evacuate			
No Action Required			

2. Completed By: _____

Date:	

Time: _____

EP-IP-300 Rev. 4 Page 33 of 35

DOCUMENT CROSS-REFERENCES

·•.

This Attachment lists those documents, other than source documents, which may be affected by changes to this Procedure.

Document Number	Document Title
EP-IP-100	Emergency Classification and Notification
EP-IP-520	Recovery

EP-IP-300 Rev. 4 Page 34 of 35

IDENTIFICATION OF COMMITMENTS

This Attachment lists those external commitments (NRC commitments, QA audit findings, and INPO inspection items) implemented in this Procedure.

Reference Document	Commitment	Affected Section(s)/Step(s)
NRC Inspection Finding 84-41-05	Provide guidance for protective action recommendations during adverse weather conditions.	Incorporated within DAPAR
PR 97.2381.02	Account for seabreeze effects	Incorporated within DAPAR