March 21, 1990

Docket No. 50-423

Mr. Edward J. Mroczka
Senior Vice President
Nuclear Engineering and Operations
Connecticut Yankee Atomic Power Company
Northeast Nuclear Energy Company
Post Office Box 270
Hartford, Connecticut 06141-0270

Dear Mr. Mroczka:

SUBJECT: CORRECTION TO AMENDMENT NO. 46 (TAC NO. 74110)

The subject amendment dated February 21, 1990, revised the Technical Specifications for Millstone Unit 3 and was in response to your application dated July 20, 1989, as supplemented October 16, 1989.

It has been brought to our attention that an incorrect version of Technical Specification page 3/4 7-9 was issued with the subject amendment. Enclosed is correct page 3/4 7-9.

Sincerely,

/s/

David H. Jaffe, Project Manager
Project Directorate I-4
Division of Reactor Projects - I/II
Office of Nuclear Reactor Regulation

Enclosure:
As stated

cc w/enclosure:
See next page

DISTRIBUTION	Docket File	NRC & Local PDR	Plant File
S. Varga (14E4)		B. Boger (14A2)	J. Stolz
S. Norris		D. Jaffe	OGC
D. Hagan (MNBB 3302)		E. Jordan (MNBB 3302)	G. Hill(4) (P1-137)
W. Jones (P-130A)		J. Calvo (11F23)	ACRS (10)
GPA/PA		ARM/LFMB	

*See previous concurrence

OFC	:LA:PDI-4*	:PM:PDI-4*	:PD:PDI-4	:	:	:	:
NAME	:SNorris	:DJaffe:lc	:JStolz	:	:	:	:
DATE	:03/20/90	:03/20/90	:03/21/90	:	:	:	:

OFFICIAL RECORD COPY
Document Name: CORR. TO AMDMT 46 TAC 74555

DF01
1/1
CP-1

Mr. E. J. Mroczka
Northeast Nuclear Energy Company

Millstone Nuclear Power Station
Unit No. 3

cc:

Gerald Garfield, Esquire
Day, Berry and Howard
Counselors at Law
City Place
Hartford, Connecticut 06103-3499

W. D. Romberg, Vice President
Nuclear Operations
Northeast Utilities Service Company
Post Office Box 270
Hartford, Connecticut 06141-0270

Kevin McCarthy, Director
Radiation Control Unit
Department of Environmental Protection
State Office Building
Hartford, Connecticut 06106

Bradford S. Chase, Under Secretary
Energy Division
Office of Policy and Management
80 Washington Street
Hartford, Connecticut 06106

S. E. Scace, Nuclear Station Director
Millstone Nuclear Power Station
Northeast Nuclear Energy Company
Post Office Box 128
Waterford, Connecticut 06385

C. H. Clement, Nuclear Unit Director
Millstone Unit No. 3
Northeast Nuclear Energy Company
Post Office Box 128
Waterford, Connecticut 06385

Ms. Jane Spector
Federal Energy Regulatory Commission
825 N. Capitol Street, N.E.
Room 8608C
Washington, D.C. 20426

Burlington Electric Department
c/o Robert E. Fletcher, Esq.
271 South Union Street
Burlington, Vermont 05402

R. M. Kacich, Manager
Generation Facilities Licensing
Northeast Utilities Service Company
Post Office Box 270
Hartford, Connecticut 06141-0270

D. O. Nordquist
Director of Quality Services
Northeast Utilities Service Company
Post Office Box 270
Hartford, Connecticut 06141-0270

Regional Administrator
Region I
U. S. Nuclear Regulatory Commission
475 Allendale Road
King of Prussia, Pennsylvania 19406

First Selectmen
Town of Waterford
Hall of Records
200 Boston Post Road
Waterford, Connecticut 06385

W. J. Raymond, Resident Inspector
Millstone Nuclear Power Station
c/o U. S. Nuclear Regulatory Commission
Post Office Box 811
Niantic, Connecticut 06357

M. R. Scully, Executive Director
Connecticut Municipal Electric
Energy Cooperative
30 Stott Avenue
Norwich, Connecticut 06360

Mr. Alan Menard, Manager
Technical Services
Massachusetts Municipal Wholesale
Electric Company
Post Office Box 426
Ludlow, Massachusetts 01056

PLANT SYSTEMS

MAIN STEAM LINE ISOLATION VALVES

LIMITING CONDITION FOR OPERATION

3.7.1.5 Each main steam line isolation valve (MSIV) shall be OPERABLE.

APPLICABILITY: MODES 1, 2, 3, and 4.

ACTION:

MODE 1:

With one MSIV inoperable but open, POWER OPERATION may continue provided the inoperable valve is restored to OPERABLE status within 4 hours; otherwise be in HOT STANDBY within the next 6 hours and in HOT SHUTDOWN within the following 6 hours.

MODES 2, 3, and 4:

With one MSIV inoperable, subsequent operation in MODE 2 or 3 or 4 may proceed provided the isolation valve is maintained closed. Otherwise, be in HOT STANDBY within the next 6 hours and in COLD SHUTDOWN within the following 30 hours.

SURVEILLANCE REQUIREMENTS

4.7.1.5.1 Each MSIV shall be demonstrated OPERABLE by verifying full closure within 5 seconds in Modes 1, 2, and 3 when tested pursuant to Specification 4.0.5. The provisions of Specification 4.0.4 are not applicable for entry into MODE 3.

4.7.1.5.2 Each MSIV shall be demonstrated OPERABLE by verifying full closure within 120 seconds in Mode 4 when tested pursuant to Specification 4.0.5. The provisions of Specification 4.0.4 are not applicable for entry into Mode 3.