

December 9, 1991

Docket No. 50-395

Mr. John L. Skolds  
Vice President, Nuclear Operations  
South Carolina Electric & Gas Company  
Virgil C. Summer Nuclear Station  
P. O. Box 88  
Jenkinsville, South Carolina 29065

Posted  
Correction to  
Amdt 104 to NPF-12

Dear Mr. Skolds:

SUBJECT: CORRECTION OF TECHNICAL SPECIFICATION PAGES FOR AMENDMENT  
NO. 104 - VIRGIL C. SUMMER NUCLEAR STATION, UNIT NO. 1  
(TAC NO. M80523)

On October 29, 1991, the Commission issued Amendment No. 104 to Facility Operating License No. NPF-12 for the Virgil C. Summer Nuclear Station, Unit No. 1. Because of repagination of section 6, the index needed to be renumbered and some minor deletions restored. The enclosed corrected pages reflect these changes.

We regret any inconveniences this may have caused.

Sincerely,

Original signed by:

George Wunder, Project Manager  
Project Directorate II-I  
Division of Reactor Projects - I/II  
Office of Nuclear Reactor Regulation

Enclosure:  
As stated

cc w/enclosure:  
See next page

OFC	:LA:PD21:DRPE	:PN:PD21:DRPE	:D:PD21:DRPE	:	:
NAME	:Panderson	:GWunder:db	:EAdensam	:	:
DATE	:12/6/91	:12/6/91	:12/6/91	:	:

OFFICIAL RECORD COPY  
Document Name: LETTER TO SKOLDS

Mr. John L. Skolds  
South Carolina Electric & Gas Company

Virgil C. Summer Nuclear Station

cc:

Mr. R. J. White  
Nuclear Coordinator  
S.C. Public Service Authority  
c/o Virgil C. Summer Nuclear Station  
P. O. Box 88 (Mail Code 802)  
Jenkinsville, South Carolina 29065

J. B. Knotts, Jr., Esq.  
Bishop, Cook, Purcell  
and Reynolds  
1400 L Street, N.W.  
Washington, D. C. 20005-3502

Resident Inspector/Summer NPS  
c/o U.S. Nuclear Regulatory Commission  
Route 1, Box 64  
Jenkinsville, South Carolina 29065

Regional Administrator, Region II  
U.S. Nuclear Regulatory Commission,  
101 Marietta Street, N.W., Suite 2900  
Atlanta, Georgia 30323

Chairman, Fairfield County Council  
P. O. Box 293  
Winnsboro, South Carolina 29180

Mr. Heyward G. Shealy, Chief  
Bureau of Radiological Health  
South Carolina Department of Health  
and Environmental Control  
2600 Bull Street  
Columbia, South Carolina 29201

South Carolina Electric & Gas Company  
Mr. A. R. Koon, Jr., Manager  
Nuclear Licensing  
Virgil C. Summer Nuclear Station  
P. O. Box 88  
Jenkinsville, South Carolina 29065

INDEX

LIMITING CONDITIONS FOR OPERATION AND SURVEILLANCE REQUIREMENTS

<u>SECTION</u>	<u>PAGE</u>
<u>3/4.2 POWER DISTRIBUTION LIMITS</u>	
3/4.2.1 AXIAL FLUX DIFFERENCE.....	3/4 2-1
3/4.2.2 HEAT FLUX HOT CHANNEL FACTOR.....	3/4 2-4
3/4.2.3 RCS FLOW RATE AND NUCLEAR ENTHALPY RISE HOT CHANNEL FACTOR.....	3/4 2-8
3/4.2.4 QUADRANT POWER TILT RATIO.....	3/4 2-12
3/4.2.5 DNB PARAMETERS.....	3/4 2-15
<u>3/4.3 INSTRUMENTATION</u>	
3/4.3.1 REACTOR TRIP SYSTEM INSTRUMENTATION.....	3/4 3-1
3/4.3.2 ENGINEERED SAFETY FEATURE ACTUATION SYSTEM INSTRUMENTATION.....	3/4 3-15
3/4.3.3 MONITORING INSTRUMENTATION	
Radiation Monitoring.....	3/4 3-41
Movable Incore Detectors.....	3/4 3-46
Seismic Instrumentation.....	3/4 3-47
Meteorological Instrumentation.....	3/4 3-50
Remote Shutdown Instrumentation.....	3/4 3-53
Accident Monitoring Instrumentation.....	3/4 3-56
Explosive Gas Monitoring Instrumentation.....	3/4 3-73
Loose-Part Detection Instrumentation.....	3/4 3-80

INDEX

LIMITING CONDITIONS FOR OPERATION AND SURVEILLANCE REQUIREMENTS

---

SECTION

PAGE

3/4.11 RADIOACTIVE EFFLUENTS

3/4.11.1 LIQUID EFFLUENTS

Liquid Holdup Tanks.....	3/4 11-7
Settling Pond.....	3/4 11-8

3/4.11.2 GASEOUS EFFLUENTS

Explosive Gas Mixture.....	3/4 11-17
Gas Storage Tanks.....	3/4 11-18

INDEX

BASES

---

---

SECTION

PAGE

3/4.11 RADIOACTIVE EFFLUENTS

3/4.11.1 LIQUID EFFLUENTS..... B 3/4 11-1

3/4.11.2 GASEOUS EFFLUENTS..... B 3/4 11-3

RADIOACTIVE EFFLUENTS

LIQUID HOLDUP TANKS

LIMITING CONDITION FOR OPERATION

---

3.11.1.4 The quantity of radioactive material contained in each of the following tanks shall be limited to less than or equal to 10 curies, excluding tritium and dissolved or entrained noble gases.

- a. Condensate Storage Tank
- b. Outside Temporary Storage Tank

APPLICABILITY: At all times.

ACTION:

- a. With the quantity of radioactive material in any of the above listed tanks exceeding the above limit, immediately suspend all additions or radioactive material to the tank and within 48 hours reduce the tank contents to within the limit.
- b. The provisions of Specifications 3.0.3 and 3.0.4 are not applicable.

SURVEILLANCE REQUIREMENTS

---

4.11.1.4 The quantity of radioactive material contained in each of the above listed tanks shall be determined to be within the above limit by analyzing a representative sample of the tank's contents at least once per 7 days when radioactive materials are being added to the tank.

RADIOACTIVE EFFLUENTS

EXPLOSIVE GAS MIXTURE

LIMITING CONDITION FOR OPERATION

---

---

3.11.2.5 The concentration of oxygen in the waste gas holdup system shall be limited to less than or equal to 2% by volume whenever the hydrogen concentration exceeds 4% by volume.

APPLICABILITY: At all times.

ACTION:

- a. With the concentration of oxygen in the waste gas holdup system greater than 2% by volume but less than or equal to 4% by volume, restore the concentration of oxygen to within the limit within 48 hours.
- b. With the concentration of oxygen in the waste gas holdup system greater than 4% by volume, immediately suspend all additions of waste gases to the system and reduce the concentration of oxygen to less than 4% by volume within 1 hour and less than or equal to 2% by volume within 48 hours.
- c. The provisions of Specifications 3.0.3 and 3.0.4 are not applicable.

SURVEILLANCE REQUIREMENTS

---

---

4.11.2.5 The concentration of hydrogen and oxygen in the waste gas holdup system shall be determined to be within the above limits by continuously monitoring the waste gases in the waste gas holdup system with the hydrogen and oxygen monitors required OPERABLE by Table 3.3-13 of Specification 3.3.3.9.

## RADIOACTIVE EFFLUENTS

### BASES

---

---

#### 3/4.11.1.3 Not Used

#### 3/4.11.1.4 LIQUID HOLDUP TANKS

Restricting the quantity of radioactive material contained in the specified tanks provides assurance that in the event of an uncontrolled release of the tanks' contents, the resulting concentrations would be less than the limits of 10 CFR Part 20, Appendix B, Table II, Column 2, at the nearest potable water supply and the nearest surface water supply in an unrestricted area.

#### 3/4 11.1.5 SETTLING PONDS

The inventory limits of the settling ponds (SP) are based on limiting the consequences of an uncontrolled release of the pond inventory. The expression in Specification 3.11.1.5 assumes the pond inventory is uniformly mixed, that the pond is located in an uncontrolled area as defined in 10 CFR 20, and that the concentration limit in Note 1 to Appendix B of 10 CFR 20 applies.

The batch limits of slurry to the chemical treatment ponds assure that radioactive material in the slurry transferred to the SP are "as low as is reasonably achievable" in accordance with 10 CFR 50.36a. The expression in Specification 4.11.1.5 assures no batch of slurry will be transferred to the SP unless the sum of the ratios of the activity of the radionuclides to their respective concentration limitation is less than the ratio of the 10 CFR 50, Appendix I, Section II.A, total body level to the 10 CFR 20, 105(a), whole body dose limitation, or that:

$$\sum_j \frac{c_j}{C_j} < \frac{3 \text{ mrem/yr}}{500 \text{ mrem/yr}} = 0.006$$

where

$c_j$  = radioactive slurry concentration for radionuclide "j" entering the unrestricted area SP, in microcuries/milliliter

$C_j$  = 10 CFR 20, Appendix B, Table II, Column 2, concentration for single radionuclide "j", in microcuries/milliliter.

For the design of filter/demineralizers using powder resin, the slurry wash volume and the weight of resin used per batch is fixed by the cell surface area and the slurry volume to resin weight ratio is constant at 100 milliliters/gram of wet, drained resin with a moisture content of approximately 55 to 60% (bulk density of about 58 pounds per cubic feet). The wet drained slurry density is



## RADIOACTIVE EFFLUENTS

### BASES

#### 3/4 11.1.5 SETTLING PONDS (Continued)

approximately 1 gr/ml and the absorption characteristic for gamma radiation is essentially that of water. Therefore,

$$\sum_j \frac{C_j}{C_j} = \sum_j \frac{Q_j}{C_j (10^2 \text{ ml/gm})} < 0.006, \text{ and}$$
$$\sum_j \frac{Q_j}{C_j} < .6 \frac{\mu\text{Ci/gm}}{\mu\text{Ci/ml}}$$

Where the terms are defined in Specification 4.11.1.5.

The batch limits provide assurance that activity input to the SP will be minimized, and a means of identifying radioactive material in the inventory limitation of Specification 3.11.1.5.

#### 3/4.11.2.5 EXPLOSIVE GAS MIXTURE

This specification is provided to ensure that the concentration of potentially explosive gas mixtures contained in the waste gas holdup system is maintained below the flammability limits of hydrogen and oxygen. Automatic control features are included in the system to prevent the hydrogen and oxygen concentrations from reaching these flammability limits. These automatic control features include isolation of the source of hydrogen and/or oxygen to reduce the concentration below the flammability limits. Maintaining the concentration of hydrogen and oxygen below their flammability limits provides assurance that the releases of radioactive materials will be controlled in conformance with the requirements of General Design Criterion 60 of Appendix A to 10 CFR Part 50.

#### 3/4.11.2.6 GAS STORAGE TANKS

Restricting the quantity of radioactivity contained in each gas storage tank provides assurance that in the event of an uncontrolled release of the tank's contents, the resulting total body exposure to an individual at the nearest exclusion area boundary will not exceed 0.5 rem. This is consistent with Standard Review Plan 15.7.1, "Waste Gas System Failure".