

INDEX

ADMINISTRATIVE CONTROLS

<u>SECTION</u>	<u>PAGE</u>
6.6 <u>REPORTABLE EVENT ACTION</u>	6-12
6.7 <u>SAFETY LIMIT VIOLATION</u>	6-12
6.8 <u>PROCEDURES AND PROGRAMS</u>	6-13
6.9 <u>REPORTING REQUIREMENTS</u>	
6.9.1 <u>ROUTINE REPORTS</u>	6-15d
Startup Report	6-15d
Annual Reports	6-16
Monthly Operating Reports	6-16a
Annual Radioactive Effluent Release Report	6-17
Annual Radiological Environmental Operating Report	6-18
Core Operating Limits Report (COLR)	6-19
6.9.2 <u>SPECIAL REPORTS</u>	6-19c
6.10 <u>RECORD RETENTION</u>	6-20
6.11 <u>RADIATION PROTECTION PROGRAM</u>	6-21
6.12 <u>HIGH RADIATION AREA</u>	6-22
6.13 <u>PROCESS CONTROL PROGRAM</u>	6-23
6.14 <u>OFFSITE DOSE CALCULATION MANUAL</u>	6-23

INDEX

LIST OF FIGURES

<u>FIGURE</u>	<u>PAGE</u>
2.1-1 REACTOR CORE THERMAL MARGIN SAFETY LIMIT LINES FOUR REACTOR COOLANT PUMPS OPERATING	2-3
2.2-1 LOCAL POWER DENSITY – HIGH TRIP SETPOINT PART 1 (FRACTION OF RATED THERMAL POWER VERSUS QR ₂)	2-7
2.2-2 LOCAL POWER DENSITY – HIGH TRIP SETPOINT PART 2 (QR ₂ VERSUS Y ₁)	2-8
2.2-3 THERMAL MARGIN/LOW PRESSURE TRIP SETPOINT PART 1 (Y ₁ , VERSUS A ₁).....	2-9
2.2-4 THERMAL MARGIN/LOW PRESSURE TRIP SETPOINT PART 2 (FRACTION OF RATED THERMAL POWER VERSUS QR ₁)	2-10
3.1-1 MINIMUM BORIC ACID STORAGE TANK VOLUME AS A FUNCTION OF STORED BORIC ACID CONCENTRATION	3/4 1-15
3.1-1a DELETED.....	
3.1-2 DELETED.....	
3.2-1 DELETED.....	
3.2-2 DELETED.....	
3.2-3 DELETED.....	
4.2-1 DELETED.....	
3.2-4 DELETED.....	
3.4-1 DOSE EQUIVALENT I-131 PRIMARY COOLANT SPECIFIC ACTIVITY LIMITS VERSUS PERCENT OF RATED THERMAL POWER WITH THE PRIMARY COOLANT SPECIFIC ACTIVITY > 1 µCi/GRAM DOSE EQUIVALENT I-131.....	3/4 4-28
3.4-2 REACTOR COOLANT SYSTEM PRESSURE TEMPERATURE LIMITATIONS FOR 21.7 EFY, HEATUP AND CORE CRITICAL.....	3/4 4-31a

INDEX

LIST OF FIGURES (continued)

<u>FIGURE</u>	<u>PAGE</u>
3.4-3 REACTOR CORE SYSTEM PRESSURE – TEMPERATURE LIMITATIONS FOR 21.7 EFY, COOLDOWN AND INSERVICE TEST	3/4 4-31b
3.4-4 REACTOR COOLANT SYSTEM PRESSURE-TEMPERATURE LIMITATIONS FOR 21.7 EFY, MAXIMUM ALLOWABLE COOLDOWN RATES	3/4 4-32
4.7-1 SAMPLING PLAN FOR SNUBBER FUNCTIONAL TEST.....	3/4 7-25
5.1-1 SITE AREA MAP	5-2
5.6-1a REQUIRED FUEL ASSEMBLY BURNUP vs INITIAL ENRICHMENT and DECAY TIME, REGION II, 1.3 w/o	5-4B
5.6-1b REQUIRED FUEL ASSEMBLY BURNUP vs INITIAL ENRICHMENT and DECAY TIME, REGION II, 1.5 w/o	5-4C
5.6-1c REQUIRED FUEL ASSEMBLY BURNUP vs INITIAL ENRICHMENT and DECAY TIME, REGION I, 1.4 w/o	5-4D
5.6-1d REQUIRED FUEL ASSEMBLY BURNUP vs INITIAL ENRICHMENT and DECAY TIME, REGION I, 1.82 w/o	5-4E
5.6-1e REQUIRED FUEL ASSEMBLY BURNUP vs INITIAL ENRICHMENT, REGION I, 2.82 w/o	5-4F
6.2-1 DELETED	6-3
6.2-2 DELETED	6-4