LICENSE AUTHORITY FILE COPY

DO NOT REMOVE



UNITED STATES NUCLEAR REGULATORY COMMISSION WASHINGTON, D. C. 20555 <u>TOSTEA</u> CORRECTION to AMOLT. 100 to DPR-41

December 13, 1984

Docket Nos. 50-250 and 50-251

Mr. J. W. Williams, Jr., Vice President Nuclear Energy Department Florida Power and Light Company Post Office Box 14000 Juno Beach, Florida 33408

Dear Mr. Williams:

During the period of August 27, 1984 through November 21, 1984, the Commission has issued six amendments to Operating License Nos. DPR-31 and DPR-41 for the Turkey Point Plant Units 3 and 4. Your staff has brought to our attention administrative errors on some of the Technical Specification pages. These typographical errors, inadvertent omissions or other errors were the result of issuing the amendments in a different sequence than they were requested. It is our understanding that a system has been initiated by your staff to track all active amendment requests to assure that administrative errors will be identified prior to issuance of amendments regardless of the request or issuance sequence. We will work closely with your staff to eliminate administrative errors prior to the issuance of future amendments.

Administrative errors are identified in the Technical Specification Table of Content pages i and iv, Technical Specification pages 1-9 and 3.1-4, Table 4.1-1 Sheets 3 and 4 and the Bases page B2.3-3. Amendments 110/104 = left out the identification of Section 1.35 on page i and Amendments 111/105 left out the identification of B4.18 and B4.19 on page iv. Amendments 108/102 resulted in an incorrect sequence of numbers and Item 1.35 was omitted from page 1-9. Amendments 110/104 had a typographical error which resulted in the last sentence in paragraph f being partially omitted. Amendments 110/104 omitted Item 31.b and Item 33 on Table 4.1-1 Sheet 3 and an incorrect numbering sequence on Sheet 4. Amendments 106/100 resulted in incorrect wording of the second paragraph on page B2.3-3.

Enclosed are the corrected pages i, iv, 1-9, 3.1-4, Table 4.1-1 Sheets 3 and 4, and B2.3-3. We have verified that the errors do not affect the amendments, the supporting Safety Evaluations and the corrections are consistent with their applicable amendments. Please use the enclosed instruction sheet and replace the pages identified in Appendix A of Facility Operating License Nos. DPR-31 and DPR-41 with the corrected pages and Tables.

Mr. Williams

Please accept our apologies for any inconvenience these errors may have caused. As stated above, we will work closely with your staff to eliminate administrative errors in issuance of future amendments.

-2-

Sincerely,

il Allaconald Jr.

Daniel G. McDonald, Project Manager Operating Reactors Branch #1 Division of Licensing

Enclosures: As stated

cc w/enclosures: See next page J. W. Williams, Jr. Florida Power and Light Company

cc: Harold F. Reis, Equire Newman and Holtziner P.C. 1615 L Street, N.W. Washington, DC 10036

> Bureau of Intergovernmental Relations 660 Apalachee Parkway Tallahassee, Florida 33130

Norman A. Coll, Esquire Steel, Hector and Davis 4000 Southeast Financial Center Miami, Florida 33131-2398

Mr. Ken N. Harris, Vice President Turkey Point Nuclear Plant Florida Power and Light Company P.O. Box 013100 Miami, Florida 33101

Mr. M. R. Stierheim County Manager of Metropolitan Dade County Miami, Florida 33130

Resident Inspector Turkey Point Nuclear Generating Station U.S. Nuclear Regulatory Commission Post Office Box 57-1185 Miami, Florida 33257-1185

Regional Radiation Representative EPA Region IV 345 Courtland Street, N.W. Atlanta, GA 30308

Mr. Jack Shreve Office of the Public Counsel Room 4, Holland Building Tallahassee, Florida 32304 Turkey Point Plants Units 3 and 4

Administrator Department of Environmental Regulation Power Plant Siting Section State of Florida 2600 Blair Stone Road Tallahassee, Florida 32301

James P. O'Reilly Regional Administrator, Region II U.S Nuclear Regulatory Commission Suite 2900 101 Marietta Street Atlanta, GA 30303

Martin H. Hodder, Esquire 1131 N.E. 86th Street Miami, Florida 33138

Joette Lorion 7269 SW 54 Avenue Miami, Florida 33143

Mr. Chris J. Baker, Plant Manager Turkey Point Nuclear Plant Florida Power and Light Company P.O. Box 013100 Miami, Florida 33101

Attorney General Department of Legal Affair<u>s</u> The Capitol – Tallahassee, Florida 32304

Mr. Allan Schubert, Manager Public Health Physicist Department of Health and Rehabilitative Services 1323 Winewood Blvd. Tallahassee, Florida 32301

 \checkmark

AMENDMENT CORRECTIONS FACILITY LICENSE NOS. DPR-31 AND DPR-41 DOCKET NOS. 50-250 AND 50-251

Revise Appendix A as follows:

| Remove Pages | Insert Pages |
|---|---|
| i Amendment Nos. 110 and 104 | i Amendment Nos. 110 and 104 |
| iv Amendment Nos. 111 and 105 | iv Amendment Nos. 111 and 105 |
| 1-9 Amendment Nos. 108 and 102 | 1-9 Amendment Nos. 108 and 102 |
| 3.1-4 Amendment Nos. 110 and 104 | 3.1-4 Amendment Nos. 110 and 104 |
| Table 4.1-1 Sh 3 & Sh 4 Amendment Nos. 110 and 104 | Table 4.1-1 Sh 3 & Sh 4 Amendment Nos. 110 and 104 |
| B 2.3-3 Amendment Nos. 106 and 100 | B 2.3-3 Amendment Nos. 106 and 100 |

_

TABLE OF CONTENTS

Section

<u>Title</u>

Page

TECHNICAL SPECIFICATIONS

| 1.0 | DEFINITIONS | 1-1 |
|------|--|-------|
| 1.1 | Safety Limits | 1-1 |
| 1.2 | Limiting Safety System Settings | 1-1 |
| 1.3 | Limiting Conditions for Operation | 1-1 |
| 1.4 | Operable | 1-1 |
| 1.5 | Containment Integrity | 1-2 |
| 1.6 | Protective Instrumentation Logic | 1-2 |
| 1.7 | Instrumentation Surveillance | 1-3 |
| 1.8 | Shutdown | 1-3 |
| 1.9 | Power Operation | 1-4 |
| 1.10 | Refueling Operation | 1-4 |
| 1.11 | Rated Power | 1-4 |
| 1.12 | Thermal Power | 1-4 |
| 1.13 | Design Power | 1-4 |
| 1.14 | Dose Equivalent I-131 | 1-5 |
| 1.15 | Power Tilt | 1-5 |
| 1.16 | Interim Limits | 1-6 |
| 1.17 | Low Power Physics Tests | 1-6 |
| 1.18 | Engineered Safety Features | 1-6 |
| 1.19 | Reactor Protection System | 1-6 |
| 1.20 | Safety Related Systems and Components | 1-6 |
| 1.21 | Per Annum | 1-6 |
| 1.22 | Reactor Coolant System Pressure Boundary Integrity | 1-6 |
| 1.23 | Coolant Loop | 1-7 |
| 1.24 | E-Average Disintegration Energy | 1-7 |
| 1.25 | Gas Decay Tank System | 1-8 |
| 1.26 | Ventilation Exhaust Treatment System | 1-8 |
| 1.27 | Process Control Program (PCP) | 1-8 |
| 1.28 | Offsite Dose Calculation Manual (ODCM) | ·1-8 |
| 1.29 | Dose Equivalent I-131 | 1-8 |
| 1.30 | Purge-Purging | 1-9 = |
| 1.31 | Venting | 1-9 |
| 1.32 | Site Boundary | 1-9 |
| 1.33 | Unrestricted Area | 1-9 |
| 1.34 | Member(s) of the Public | 1-9 |
| 1.35 | Heavy Loads | 1-9 |
| 2.0 | SAFETY LIMITS AND LIMITING SAFETY SYSTEM SETTINGS | 2.1-1 |
| 2.1 | Safety Limit, Reactor Core | 2.1-1 |
| 2.2 | Safety Limit, Reactor Coolant System Pressure | 2.2-1 |
| 2.3 | Limiting Safety System Setting, Protective | |
| | Instrumentation | 2.3-1 |
| 3.0 | LIMITING CONDITIONS FOR OPERATION | 3.0-1 |
| 3.1 | Reactor Coolant System | 3.1-1 |
| | Operational Components | 3.1-1 |
| | Pressure-Temperature Limits | 3.1-2 |
| | Leakage | 3.1-3 |
| | Maximum Reactor Coolant Activity | 3.1-4 |
| | Reactor Coolant Chemistry | 3.1-6 |
| | DNB Parameters | 3.1-7 |

-i- Amendment Nos. <u>110</u> and <u>104</u> CORRECTION Letter of 12-13-84

TABLE OF CONTENTS (Continued)

| Section | Title | Page |
|---------------|---|--------------------|
| B3.5 | Bases for Limiting Conditions for Operation, | |
| •••• | Instrumentation | B3.5-1 |
| B3.6 | Bases for Limiting Conditions for Operation, | |
| | Chemical and Volume Control System | B3.6 -1 |
| B3.7 | Bases for Limiting Conditions for Operation, | |
| | Electrical Systems | B3.7- 1 |
| B3.8 | Bases for Limiting Conditions for Operation, | |
| | Steam and Power Conversion Systems | B3.8-1 |
| B3.9 | Bases for Limiting Conditions for Operation, | |
| | Radioactive Materials Release | B3.9- 1 |
| B3. 10 | Bases for Limiting Conditions for Operation, | |
| | Refueling | B3.10-1 |
| B3.11 | Bases for Limiting Conditions for Operation, | |
| | Miscellaneous Radioactive Material Sources | B 3.11-1 |
| B3.12 | Bases for Limiting Conditions for Operation, | |
| | Cask Handling | B3.12-1 |
| B3.13 | Bases for Limiting Conditions for Operation, | |
| | Snubbers | B3.13-1 |
| B3.1 4 | Bases for Fire Protection System | B3.14 -1 |
| B3.15 | Bases for Limiting Conditions of Operation, | |
| | Overpressure Mitigating System | B3.15-1 |
| B3.17 | Bases for Limiting Conditions for Operation, | B3.17-1 |
| | Spent Fuel Storage | |
| B4. 1 | Bases for Operational Safety Review • | B4.1-1 |
| B4.2 | Bases for Reactor Coolant System In-Service Inspection | B4.2-1 |
| B4.3 | Bases for Reactor Coolant System Integrity | B4.3-1 |
| B4.4 | Bases for Containment Tests | B4.4 -1 |
| B4.5 | Bases for Safety Injection Tests | B4.5-1 |
| B 4.6 | Bases for Emergency Containment Cooling System Tests | B 4.6-1 |
| B4.7 | Bases for Emergency Containment Filtering and | |
| | Post Accident Containment Venting Systems Tests | B4.7-1 |
| B4.8 | Bases for Emergency Power System Periodic Tests | B4.8-1 |
| B4.9 | Bases for Main Steam Isolation Valve Tests | B4.9-Ī |
| B4.10 | Bases for Auxiliary Feedwater System Tests | B4.10-1 B4.11-1 |
| B4.11 | Bases for Reactivity Anomalies | B4.12-1 |
| B4.12 | Bases for Environmental Radiation Survey | B4.12-1 B4.13-1 |
| B4.13 | Bases for Fire Protection Systems | B4.13-1 B4.14-1 |
| B4.14 | Bases for Snubbers | D4.14-1 |
| B4.15 | Bases for Surveillance Requirements, Overpressure Mitigating System | B4.15-1 |
| D/1 19 | | B4.18-1 |
| B4.18 | Bases for System Flow Path Verifications Bases for Boaster Coolant Vent System | B4.19-1 |
| B4.19 | Bases for Reactor Coolant Vent System | D4.17-1 |

Amendment Nos. 111 and 105 CORRECTION Letter of 12-13-84

I

1.30 PURGE - PURGING

PURGE or PURGING is the controlled process of discharging air or gas from a confinement to maintain temperature, pressure, humidity, concentration or other operating condition, in such a manner that replacement air or gas is required to purify the confinement.

1.31 VENTING

VENTING is the controlled process of discharging air or gas from a confinement to maintain temperature, pressure, humidity, concentration or other operating condition, in such a manner that replacement air or gas is not provided or required during VENTING. Vent, used in system names, does not imply a VENTING process.

1.32 SITE BOUNDARY

The SITE BOUNDARY shall be that line beyond which the land is neither owned, leased nor otherwise controlled by the licensee.

1.33 UNRESTRICTED AREA

An UNRESTRICTED AREA shall be any area at or beyond the SITE BOUNDARY access to which is not controlled by the licensee for purposes of protection of individuals from exposure to radiation from radioactive materials, or any area within the SITE BOUNDARY used for residential quarters or for industrial, commercial, institutional and/or recreational purposes.

1.34 MEMBER(S) OF THE PUBLIC

MEMBER(S) OF THE PUBLIC shall include all persons who are not occupationally associated with the plant. This category does not include employees of the licensee, its contractors, vendors or members of the Armed Forces using property located within the SITE BOUNDARY. Also excluded from this category are persons who enter the site to service equipment or to make deliveries. This category does include persons who use portions of the site for recreational, occupational or other purposes not associated with the plant.

1.35 HEAVY LOADS

Any load in excess of the nominal weight of a fuel and control rod assembly and associated handling tool. For the purpose of this specification, HEAVY LOADS will be defined as loads in excess of 2000 pounds.

Amendment Nos. 108and 102 1-9 CORRECTION Letter of 12-13-84

- e. After shutdown, corrective action shall be taken before operation is resumed.
- f. Above 2% of rated power, two leak detection systems of different principles shall be operable, one of which is sensitive to radioactivity. The latter may be out of service for 48 hours provided 1) Two other systems are operable and 2) containment purge values are maintained closed.
- g. Reactor Coolant System leakage shall be limited to 1 gpm total primary-to-secondary leakage through all steam generators not isolated from the Reactor Coolant System and 500 gallons per day through any one steam generator not isolated from the Reactor Coolant System.

4. MAXIMUM REACTOR COOLANT ACTIVITY

*

The specific activity of the primary coolant shall be limited to:

- a. Less than or equal to 1.0 microcurie per gram DOSE EQUIVALENT I-131, and
- b. Less than or equal to 100/E microcuries per gram.

With the above limits being exceeded, the following actions shall be taken:

- 1. When the reactor is critical or average reactor coolant temperature is greater than 500 F:
 - a. With the specific activity of the primary coolant greater than 1.0 microcurie per gram DOSE EQUIVALENT I-131 but within the allowable limit (below and to the left of the line) shown on Figure 3.1-1, operation may continue for up to 48 hours provided that the cumulative operating time under these circumstances does not exceed 800 hours in any consecutive 12 month period. With the total cumulative operating time at a primary coolant specific activity greater than 1.0 microcurie per gram DOSE EQUIVALENT I-131 exceeding 500 hours in

Amendment Nos. 110 and 104 COPPLCTUSIN Letter Of 12-13-84 TABLE 4.1-1 SHEET 3

| | | Channel Description | Check | Calibrate | Test | Remarks |
|---|------------|--|-------|-------------------|--------|---|
| | | | N.A. | N.A. | i i Mt | |
| | 23. | Logic Channels | N.A. | • | M | |
| | 24. 25. | Emer. Portable Survey Instruments Seismograph | N.A. | N.A. | Q | Make trace. Test battery (change semi-annually) |
| | 26. | Auxillary Feedwater Flow Rate | Mt | R | N.A. | |
| | 27. | RCS Subcooling Margin Monitor | Mt | R | N.A. | |
|) | 28. | PORV Position Indicator (Primary Detector) | Mt | N.A. | R | Check consists of monitoring |
| | 29. | PORV Block Valve Position Indicator | Mt | ⁻ N.A. | R | indicated position and verifying |
| | 30. | Safety Valve Position Indicator | Mt | R | N.A.) | by observation of related |
| | 31. | a. Loss of Voltage (both 4kv bussess) | N.A. | N.A. | R | For AFW actuation at power only |
| | | b. Undervoltage (both 4KV busses and 480 volt Load Centers)** | St | R | MŤ | |
|) | 32. | Trip of both Main Feedwater Pump Breakers | N.A. | N. A. | R | For AFW actuation at power only |
| | 33. | Turbine Trip (Auto-Stop Oil Pressure Switches) | N.A. | R. | N.A. | |

This item does not apply on Unit 3 until after implementation of PC/M 79-116 and on Unit 4 until after implementation of .. PC/M 80-44. Amendment Nos. <u>110</u> and <u>104</u> CORRECTION LETTER of 12-13-SH

T18:4

TABLE 4.1-1 SHEET 4

.

1.

| | Channel Description | Check | <u>Calibrate</u> | Test | <u>Remarks</u> |
|-----|---|-------|------------------|------------------|---|
| 34. | Containment Water Level (Narrow Range) | M++ | R | N. A. | |
| 35. | Containment Water Level (Wide Range) | M++ | R | N.A. | |
| 36. | Containment High Range Area Radiation | S++ | R(Note 1) | M++ | |
| 37. | Containment Hydrogen Monitors | S† | Q(1) | M† | (1) Channel calibration using sample gas containing: a. One volume percent hydrogen, balance nitrogen. b. Four volume percent hydrogen, balance nitrogen. |
| 38. | High Range Noble Gas Effluent Monitors | | | | |
| | a. Plant Vent Exhaust | S | R | М | |
| | b. Unit 3 Spent Fuel Pit Exhaust | S | R | м | |
| | c. Condenser Air Ejectors | S† | R | M† | |
| | d. Main Steam Lines | S† | R | M† | |
| 39. | Incore Thermocouples (Core Exit Thermocouples) | M†† | R | N.A.(See Note 2) | |

Amendment Nos. <u>110</u> and <u>104</u> CORRECTION LETTER OB 12-13-54

4