

May 4 1988

DO NOT REMOVE

Docket Nos. 50-250  
and 50-251

Posted  
Collection to

Amat. 121 to DPR-41

Mr. W. F. Conway  
Vice President-Nuclear  
Florida Power and Light Company  
P.O. Box 14000  
Juno Beach, Florida 33408

E. Jordan  
J. Partlow  
ACRS (10)  
GPA/PA

Dear Mr. Conway:

SUBJECT: TURKEY POINT UNITS 3 AND 4 - ADMINISTRATIVE REVISION OF  
AMENDMENT NOS. 127 AND 121 TO UPGRADE TECHNICAL  
SPECIFICATIONS FOR DC POWER SOURCES (TAC NOS. 67074 AND 67075)

On April 18, 1988, the Commission issued Amendment Nos. 127 and 121 to Facility Operating License Nos. DPR-31 and DPR-41 respectively. The amendments revised the Technical Specifications for D.C. Power Sources to upgrade them towards Standard Technical Specifications by revising the surveillance and test requirements for station batteries and battery chargers.

An earlier version of Table 4.8-2 was inadvertently published in Amendment Nos. 127 and 121. Please replace that table with the enclosure, which was transmitted by FP&L letter L-88-135 dated March 17, 1988.

Sincerely,

Gordon E. Edison, Sr. Project Manager  
Project Directorate II-2  
Division of Reactor Projects-I/II  
Office of Nuclear Reactor Regulation

Enclosure:  
1. Table 4.8-2

cc w/enclosure:  
See next page

LA:PDII-2  
DM:ler  
5/3/88

*AEE*  
PM:PDII-2  
GEdison:bg  
5/3/88

D:PDII-2  
H Berkow  
5/4/88

Mr. W. F. Conway  
Florida Power and Light Company

Turkey Point Plant

cc:

Harold F. Reis, Esquire  
Newman and Holtzinger, P.C.  
1615 L Street, N.W.  
Washington, DC 20036

Mr. Jack Shreve  
Office of the Public Counsel  
Room 4, Holland Building  
Tallahassee, Florida 32304

John T. Butler, Esquire  
Steel, Hector and Davis  
4000 Southeast Financial  
Center  
Miami, Florida 33131-2398

Mr. J. Odom, Vice President  
Turkey Point Nuclear Plant  
Florida Power and Light Company  
P.O. Box 029100  
Miami, Florida 33102

Mr. Sergio Periera  
County Manager of Metropolitan  
Dade County  
Miami, Florida 33130

Resident Inspector  
U.S. Nuclear Regulatory Commission  
Turkey Point Nuclear Generating Station  
Post Office Box 57-1185  
Miami, Florida 33257-1185

Jacob Daniel Nash  
Office of Radiation Control  
Department of Health and  
Rehabilitative Services  
1317 Winewood Blvd.  
Tallahassee, Florida 32399-0700

Intergovernmental Coordination  
and Review  
Office of Planning & Budget  
Executive Office of the Governor  
The Capitol Building  
Tallahassee, Florida 32301

Administrator  
Department of Environmental  
Regulation  
Power Plant Siting Section  
State of Florida  
2600 Blair Stone Road  
Tallahassee, Florida 32301

Regional Administrator, Region II  
U.S. Nuclear Regulatory Commission  
Suite 2900  
101 Marietta Street  
Atlanta, Georgia 30323

Attorney General  
Department of Legal Affairs  
The Capitol  
Tallahassee, Florida 32304

Joette Lorion  
7269 SW, 54 Avenue  
Miami, Florida 33143

Mr. Chris J. Baker, Plant Manager  
Turkey Point Nuclear Plant  
Florida Power and Light Company  
P.O. Box 029100  
Miami, Florida 33102

**TABLE 4.8-2****BATTERY SURVEILLANCE REQUIREMENTS**

	CATEGORY A <sup>(1)</sup>	CATEGORY B <sup>(2)</sup>	
PARAMETER	LIMITS FOR EACH designated pilot cell	LIMITS FOR EACH connected cell	ALLOWABLE <sup>(3)</sup> value for Connected Cell
Electrolyte Level	Greater than minimum level indication mark, and no overflow	Greater than minimum level indication mark, and no overflow	Above top of plates and no overflow
Float Voltage	Greater than or equal to 2.13 volts	Greater than or equal to 2.13 volts <sup>(6)</sup>	Greater than or equal to 2.07 volts
Specific Gravity <sup>(4)</sup>	Greater than or equal to 1.200 <sup>(5)</sup>	Greater than or equal to 1.195	Not more than 0.020 below the average of all connected cells
		Average of all connected cells greater than 1.205	Average of all connected cells greater than or equal to 1.195 <sup>(5)</sup>

**TABLE NOTATIONS**

- (1) For any Category A parameter(s) outside the limit(s) shown, the battery may be considered OPERABLE provided that within 24 hours all the Category B measurements are taken and found to be within their allowable values, and equalizing charge is started. All Category A and B parameter(s) must be restored to within limits within the next 6 days.
- (2) For any Category B parameter(s) outside the limit(s) shown, the battery may be considered OPERABLE provided that the Category B parameters are within their allowable values, and equalizing charge is started. All Category B parameter(s) must be restored to within limits within 7 days.
- (3) Any Category B parameter not within its allowable value indicates an inoperable battery.
- (4) Corrected for electrolyte temperature and level.
- (5) Or battery charging current is less than 2 amps when on charge.
- (6) Corrected for average electrolyte temperature.