

January 26, 1989

Docket Nos. 50-259/260/296

Mr. Oliver D. Kingsley, Jr.
Senior Vice President, Nuclear Power
Tennessee Valley Authority
6N 38A Lookout Place
1101 Market Street
Chattanooga, Tennessee 37402-2801

Dear Mr. Kingsley:

SUBJECT: TECHNICAL SPECIFICATIONS ON ANTICIPATED TRANSIENTS WITHOUT SCRAM
(ATWS) - RECIRCULATION PUMP TRIP (RPT) (TAC 00436, 00437, 00438)
(TS 252) BROWNS FERRY NUCLEAR PLANTS, UNITS 1, 2, AND 3

The Commission has issued the enclosed Amendment Nos. 164, 161, and 135 to Facility Operating Licenses Nos. DPR-33, DPR-52 and DPR-68 for the Browns Ferry Nuclear Plant, Units 1, 2 and 3, respectively. These amendments are in response to your application dated August 4, 1988. These amendments incorporate Technical Specifications Limiting Conditions for Operation and Surveillance Requirements for the ATWS-RPT System.

A copy of the Safety Evaluation is also enclosed. Notice of Issuance will be included in the Commission's Bi-Weekly Federal Register Notice.

Sincerely,

Suzanne Black, Assistant Director
for Projects
TVA Projects Division
Office of Nuclear Reactor Regulation

Enclosures:

1. Amendment No. 164 to License No. DPR-33
2. Amendment No. 161 to License No. DPR-52
3. Amendment No. 135 to License No. DPR-68
4. Safety Evaluation

cc w/enclosures:
See next page

DISTRIBUTION:

Docket File
NRC PDR
Local PDR
Projects Reading
DCrutchfield
AD/SP Reading
BDLiaw
SBlack
MSimms
GGears
DMoran
JRutberg

RPierson
FMcCoy
WLittle
SVarga
BGrimes
EJordan
DHagan
TMeek(12)
WJones
EButcher
ACRS(10)
GPA/PA

GPA/CA
ARM/LFMB
BFN Rdg. File
FDaniels

OFFICIAL RECORD COPY

8902020416 890126
PDR ADDCK 05000259
PDC

But please change
to 50/2

DF01
C/P-1 1/1

OFC	:OSP:TVA/LA	:OSP:TVA/PM	:OGC	:TVA:AD/P	:	:	:
NAME	:MSimms	:TDaniels:as	:SBlack	:	:	:	:
DATE	:1/5/89	:1/5/88	:12/9/89	:01/26/89	:	:	:

OFFICIAL RECORD COPY

Mr. Oliver D. Kingsley, Jr.

-2-

Browns Ferry Nuclear Plant

cc:

General Counsel
Tennessee Valley Authority
400 West Summit Hill Drive
E11 B33
Knoxville, Tennessee 37902

Mr. R. L. Gridley
Tennessee Valley Authority
5N 157B Lookout Place
Chattanooga, Tennessee 37402-2801

Mr. C. Mason
Tennessee Valley Authority
Browns Ferry Nuclear Plant
P.O. Box 2000
Decatur, Alabama 35602

Mr. P. Carier
Tennessee Valley Authority
Browns Ferry Nuclear Plant
P.O. Box 2000
Decatur, Alabama 35602

Mr. D. L. Williams
Tennessee Valley Authority
400 West Summit Hill Drive
W10 B85
Knoxville, Tennessee 37902

Chairman, Limestone County Commission
P.O. Box 188
Athens, Alabama 35611

Claude Earl Fox, M.D.
State Health Officer
State Department of Public Health
State Office Building
Montgomery, Alabama 36130

Regional Administrator, Region II
U.S. Nuclear Regulatory Commission
101 Marietta Street, N.W.
Atlanta, Georgia 30323

Resident Inspector/Browns Ferry NP
U.S. Nuclear Regulatory Commission
Route 12, Box 637
Athens, Alabama 35611

Dr. Henry Myers, Science Advisor
Committee on Interior
and Insular Affairs
U. S. House of Representatives
Washington, D.C. 20515

Tennessee Valley Authority
Rockville Office
11921 Rockville Pike
Suite 402
Rockville, Maryland 20852



UNITED STATES
NUCLEAR REGULATORY COMMISSION
WASHINGTON, D. C. 20555

TENNESSEE VALLEY AUTHORITY

DOCKET NO. 50-259

BROWNS FERRY NUCLEAR PLANT, UNIT 1

AMENDMENT TO FACILITY OPERATING LICENSE

Amendment No. 164
License No. DPR-33

1. The Nuclear Regulatory Commission (the Commission) has found that:
 - A. The application for amendment by Tennessee Valley Authority (the licensee) dated August 4, 1988, complies with the standards and requirements of the Atomic Energy Act of 1954, as amended (the Act), and the Commission's rules and regulations set forth in 10 CFR Chapter I;
 - B. The facility will operate in conformity with the application, the provisions of the Act, and the rules and regulations of the Commission;
 - C. There is reasonable assurance (i) that the activities authorized by this amendment can be conducted without endangering the health and safety of the public, and (ii) that such activities will be conducted in compliance with the Commission's regulations;
 - D. The issuance of this amendment will not be inimical to the common defense and security or to the health and safety of the public; and
 - E. The issuance of this amendment is in accordance with 10 CFR Part 51 of the Commission's regulations and all applicable requirements have been satisfied.

2. Accordingly, the license is amended by changes to the Technical Specifications as indicated in the attachment to this license amendment and paragraph 2.C.(2) of Facility Operating License No. DPR-33 is hereby amended to read as follows:

(2) Technical Specifications

The Technical Specifications contained in Appendices A and B, as revised through Amendment No. 164, are hereby incorporated in the license. The licensee shall operate the facility in accordance with the Technical Specifications.

3. This license amendment is effective as of its date of issuance and shall be implemented within 60 days from the date of issuance.

FOR THE NUCLEAR REGULATORY COMMISSION



Suzanne Black, Assistant Director
for Projects
TVA Projects Division.
Office of Nuclear Reactor Regulation

Attachment:
Changes to the Technical
Specifications

Date of Issuance: January 26, 1989

ATTACHMENT TO LICENSE AMENDMENT NO. 164

FACILITY OPERATING LICENSE NO. DPR-33

DOCKET NO. 50-259

Revise the Appendix A Technical Specifications by removing the pages identified below and inserting the enclosed pages. The revised pages are identified by the captioned amendment number and contain marginal lines indicating the area of change. Overleaf pages* are provided to maintain document completeness.

REMOVE

i
ii
v
vi
vii
viii
-
3.2/4.2-14
3.2/4.2-15
-
3.2/4.2-44
3.2/4.2-45
3.2/4.2-59
3.2/4.2-60
3.2/4.2-61
-
3.2/4.2-69
3.2/4.2-70
-

INSERT

i
ii*
v*
vi
vii
viii*
3.2/4.2-6a
3.2/4.2-14*
3.2/4.2-15
3.2/4.2-39a
3.2/4.2-44
3.2/4.2-45*
3.2/4.2-59
3.2/4.2-60
3.2/4.2-61
3.2/4.2-63a
3.2/4.2-69*
3.2/4.2-70
3.2/4.2-70a

TABLE OF CONTENTS

<u>Section</u>		<u>Page No.</u>
1.0	Definitions.	1.0-1
	<u>SAFETY LIMITS AND LIMITING SAFETY SYSTEM</u> <u>SETTINGS</u>	
1.1/2.1	Fuel Cladding Integrity.	1.1/2.1-1
1.2/2.2	Reactor Coolant System Integrity	1.2/2.2-1
	<u>LIMITING CONDITIONS FOR OPERATION AND</u> <u>SURVEILLANCE REQUIREMENTS</u>	
3.1/4.1	Reactor Protection System	3.1/4.1-1
3.2/4.2	Protective Instrumentation.	3.2/4.2-1
	A. Primary Containment and Reactor Building Isolation Functions.	3.2/4.2-1
	B. Core and Containment Cooling Systems - Initiation and Control	3.2/4.2-2
	C. Control Rod Block Actuation.	3.2/4.2-2
	D. Radioactive Liquid Effluent Monitoring Instrumentation.	3.2/4.2-3
	E. Drywell Leak Detection	3.2/4.2-4
	F. Surveillance Instrumentation	3.2/4.2-4
	G. Control Room Isolation	3.2/4.2-4
	H. Flood Protection	3.2/4.2-4
	I. Meteorological Monitoring Instrumentation. . .	3.2/4.2-4
	J. Seismic Monitoring Instrumentation	3.2/4.2-5
	K. Radioactive Liquid Effluent Monitoring Instrumentation	3.2/4.2-6
	L. ATWS-Recirculation Pump Trip	3.2/4.2-6a
3.3/4.3	Reactivity Control	3.3/4.3-1
	A. Reactivity Limitations	3.3/4.3-1
	B. Control Rods	3.3/4.3-5
	C. Scram Insertion Times.	3.3/4.3-10

<u>Section</u>	<u>Page No.</u>
D. Reactivity Anomalies	3.3/4.3-11
E. Reactivity Control	3.3/4.3-12
F. Scram Discharge Volume	3.3/4.3-12
3.4/4.4 Standby Liquid Control System.	3.4/4.4-1
A. Normal System Availability	3.4/4.4-1
B. Operation with Inoperable Components	3.4/4.4-2
C. Sodium Pentaborate Solution.	3.4/4.4-3
3.5/4.5 Core and Containment Cooling Systems	3.5/4.5-1
A. Core Spray System (CSS).	3.5/4.5-1
B. Residual Heat Removal System (RHRS) (LPCI and Containment Cooling)	3.5/4.5-4
C. RHR Service Water System and Emergency Equipment Cooling Water System (EECWS)	3.5/4.5-10
D. Equipment Area Coolers	3.5/4.5-13
E. High Pressure Coolant Injection System (HPCIS).	3.5/4.5-13
F. Reactor Core Isolation Cooling System (RCICS).	3.5/4.5-14
G. Automatic Depressurization System (ADS).	3.5/4.5-15
H. Maintenance of Filled Discharge Pipe	3.5/4.5-17
I. Average Planar Linear Heat Generation Rate	3.5/4.5-18
J. Linear Heat Generation Rate (LHGR)	3.5/4.5-18
K. Minimum Critical Power Ratio (MCPR).	3.5/4.5-19
L. APRM Setpoints	3.5/4.5-20
3.6/4.6 Primary System Boundary.	3.6/4.6-1
A. Thermal and Pressurization Limitations	3.6/4.6-1
B. Coolant Chemistry.	3.6/4.6-5

ADMINISTRATIVE CONTROLS

<u>SECTION</u>		<u>PAGE</u>
<u>6.1</u>	<u>RESPONSIBILITY</u>	6.0-1
<u>6.2</u>	<u>ORGANIZATION</u>	6.0-1
6.2.1	Corporate.....	6.0-1
6.2.2	Plant Staff.....	6.0-1
<u>6.3</u>	<u>PLANT STAFF QUALIFICATIONS</u>	6.0-4
<u>6.4</u>	<u>TRAINING</u>	6.0-4
<u>6.5</u>	<u>PLANT REVIEW AND AUDIT</u>	6.0-4
6.5.1	Plant Operation Review Committee (PORC).....	6.0-4
6.5.2	Nuclear Safety Review Board (NSRB).....	6.0-10
6.5.3	Technical Review and Approval of Procedures.....	6.0-16
<u>6.6</u>	<u>REPORTABLE EVENT ACTIONS</u>	6.0-17
<u>6.7</u>	<u>SAFETY LIMIT VIOLATION</u>	6.0-18
<u>6.8</u>	<u>PROCEDURES/INSTRUCTION AND PROGRAMS</u>	6.0-19
6.8.1	Procedures.....	6.0-19
6.8.2	Drills.....	6.0-20
6.8.3	Radiation Control Procedures.....	6.0-20
6.8.4	Quality Assurance Procedures - Effluent and.....	
	Environmental Monitoring.....	6.0-22
<u>6.9</u>	<u>REPORTING REQUIREMENTS</u>	6.0-23
6.9.1	Routine Reports.....	6.0-23
	Startup Reports.....	6.0-23
	Annual Operating Report.....	6.0-24
	Monthly Operating Report.....	6.0-25
	Reportable Events.....	6.0-25
	Radioactive Effluent Release Report.....	6.0-25
	Source Tests.....	6.0-25
6.9.2	Special Reports.....	6.0-26
<u>6.10</u>	<u>STATION OPERATING RECORDS AND RETENTION</u>	6.0-28
<u>6.11</u>	<u>PROCESS CONTROL PROGRAM</u>	6.0-31
<u>6.12</u>	<u>OFFSITE DOSE CALCULATION MANUAL</u>	6.0-31
<u>6.13</u>	<u>RADIOLOGICAL EFFLUENT MANUAL</u>	6.0-32

LIST OF TABLES

<u>Table</u>	<u>Title</u>	<u>Page No.</u>
1.1	Surveillance Frequency Notation	1.0-12
3.1.A	Reactor Protection System (SCRAM) Instrumentation Requirements.	3.1/4.1-3
4.1.A	Reactor Protection System (SCRAM) Instrumentation Functional Tests Minimum Functional Test Frequencies for Safety Instr. and Control Circuits.	3.1/4.1-8
4.1.B	Reactor Protection System (SCRAM) Instrumentation Calibration Minimum Calibration Frequencies for Reactor Protection Instrument Channels. . . .	3.1/4.1-11
3.2.A	Primary Containment and Reactor Building Isolation Instrumentation	3.2/4.2-7
3.2.B	Instrumentation that Initiates or Controls the Core and Containment Cooling Systems.	3.2/4.2-14
3.2.C	Instrumentation that Initiates Rod Blocks	3.2/4.2-25
3.2.D	Radioactive Liquid Effluent Monitoring Instrumentation	3.2/4.2-28
3.2.E	Instrumentation that Monitors Leakage Into Drywell.	3.2/4.2-30
3.2.F	Surveillance Instrumentation.	3.2/4.2-31
3.2.G	Control Room Isolation Instrumentation.	3.2/4.2-34
3.2.H	Flood Protection Instrumentation.	3.2/4.2-35
3.2.I	Meteorological Monitoring Instrumentation	3.2/4.2-36
3.2.J	Seismic Monitoring Instrumentation.	3.2/4.2-37
3.2.K	Radioactive Gaseous Effluent Monitoring Instrumentation	3.2/4.2-38
3.2.L	ATWS - Recirculation Pump Trip Instrumentation . . .	3.2/4.2-39a
4.2.A	Surveillance Requirements for Primary Containment and Reactor Building Isolation Instrumentation. .	3.2/4.2-40
4.2.B	Surveillance Requirements for Instrumentation that Initiate or Control the CSCS.	3.2/4.2-44
4.2.C	Surveillance Requirements for Instrumentation that Initiate Rod Blocks	3.2/4.2-50
4.2.D	Radioactive Liquid Effluent Monitoring Instrumentation Surveillance Requirements	3.2/4.2-51

LIST OF TABLES (Cont'd)

<u>Table</u>	<u>Title</u>	<u>Page No.</u>
4.2.E	Minimum Test and Calibration Frequency for Drywell Leak Detection Instrumentation.	3.2/4.2-53
4.2.F	Minimum Test and Calibration Frequency for Surveillance Instrumentation	3.2/4.2-54
4.2.G	Surveillance Requirements for Control Room Isolation Instrumentation.	3.2/4.2-56
4.2.H	Minimum Test and Calibration Frequency for Flood Protection Instrumentation	3.2/4.2-57
4.2.J	Seismic Monitoring Instrument Surveillance Requirements	3.2/4.2-58
4.2.K	Radioactive Gaseous Effluent Instrumentation Surveillance	3.2/4.2-62
4.2.L	ATWS-Recirculation Pump Trip Instrumentation Surveillance	3.2/4.2-63a
3.5-1	Minimum RHRSW and EECW Pump Assignment	3.5/4.5-11
3.5.I	MAPLHGR Versus Average Planar Exposure	3.5/4.5-21
3.7.A	Primary Containment Isolation Valves	3.7/4.7-25
3.7.B	Testable Penetrations with Double O-Ring Seals	3.7/4.7-32
3.7.C	Testable Penetrations with Testable Bellows.	3.7/4.7-33
3.7.D	Air Tested Isolation Valves.	3.7/4.7-34
3.7.E	Primary Containment Isolation Valves which Terminate below the Suppression Pool Water Level.	3.7/4.7-37
3.7.F	Primary Containment Isolation Valves Located in Water Sealed Seismic Class 1 Lines	3.7/4.7-38
3.7.H	Testable Electrical Penetrations	3.7/4.7-39
4.9.A.4.C	Voltage Relay Setpoints/Diesel Generator Start	3.9/4.9-16
3.11.A	Fire Protection System Hydraulic Requirements.	3.11/4.11-10
6.2.A	Minimum Shift Crew Requirements.	6.0-3

LIST OF ILLUSTRATIONS

<u>Figure</u>	<u>Title</u>	<u>Page No.</u>
2.1.1	APRM Flow Reference Scram and APRM Rod Block Settings	1.1/2.1-6
2.1-2	APRM Flow Bias Scram Vs. Reactor Core Flow	1.1/2.1-7
4.1-1	Graphic Aid in the Selection of an Adequate Interval Between Tests	3.1/4.1-13
4.2-1	System Unavailability.	3.2/4.2-64
3.5.K-1	MCPR Limits.	3.5/4.5-24
3.5.2	K _f Factor.	3.5/4.5-25
3.6-1	Minimum Temperature ^o F Above Change in Transient Temperature.	3.6/4.6-24
3.6-2	Change in Charpy V Transition Temperature Vs. Neutron Exposure	3.6/4.6-25
4.8.1.a	Gaseous Release Points and Elevations	3.8/4.8-10
4.8.1.b	Land Site Boundary	3.8/4.8-11
6.2-1	Offsite Organization for Facility Management and Technical Support	6.0-33
6.2-2	Facility Organization	6.0-34

3.2/4.2 Protective Instrumentation

LIMITING CONDITIONS FOR OPERATION

3.2.L ATWS/RPT

1. The ATWS/RPT System Instrumentation shall be OPERABLE during REACTOR POWER OPERATION in accordance with Table 3.2.L.
2. The ATWS/RPT System Trip setpoints will be set in accordance with Table 3.2.L.
3. The actions required when the number of operable channels is less than the minimum OPERABLE channels per trip system is specified in Table 3.2.L.

SURVEILLANCE REQUIREMENTS

4.2.L ATWS/RPT

1. Each of the ATWS/RPT System Instrumentation channels shall be OPERABLE by performance of tests in Table 4.2.L.

TABLE 3.2.B
INSTRUMENTATION THAT INITIATES OR CONTROLS THE CORE AND CONTAINMENT COOLING SYSTEMS

Minimum No. Operable per Trip Sys(1)	Function	Trip Level Setting	Action	Remarks
2	Instrument Channel - Reactor Low Water Level	$\geq 470''$ above vessel zero.	A	1. Below trip setting initiated HPCI.
2	Instrument Channel - Reactor Low Water Level	$\geq 470''$ above vessel zero.	A	1. Multiplier relays initiate RCIC.
2	Instrument Channel - Reactor Low Water Level (LIS-3-58A-D, SW #1)	$\geq 378''$ above vessel zero.	A	1. Below trip setting initiates CSS. Multiplier relays initiate LPCI. 2. Multiplier relay from CSS initiates accident signal (15).
2(16)	Instrument Channel - Reactor Low Water Level (LIS-3-58A-D, SW #2)	$\geq 378''$ above vessel zero.	A	1. Below trip settings, in conjunction with drywell high pressure, low water level permissive, 120 sec. delay timer and CSS or RHR pump running, initiates ADS.
1(16)	Instrument Channel - Reactor Low Water Level Permissive (LIS-3-184 & 185, SW #1)	$\geq 544''$ above vessel zero.	A	1. Below trip setting permissive for initiating signals on ADS.
1	Instrument Channel - Reactor Low Water Level (LITS-3-52 and 62, SW #1)	$\geq 312 \frac{5}{16}''$ above vessel zero. A (2/3 core height)	A	1. Below trip setting prevents inadvertent operation of containment spray during accident condition.

BFN-Unit 1

TABLE 3.2.B (Continued)

BPN Unit 1	Minimum No. Operable Per Trip Sys(1)	Function	Trip Level Setting	Action	Remarks
	2	Instrument Channel - Drywell High Pressure (PS-64-58 E-H)	$1 \leq p \leq 2.5$ psig	A	1. Below trip setting prevents inadvertent operation of containment spray during accident conditions.
	2	Instrument Channel - Drywell High Pressure (PS-64-58 A-D, SW #2)	≤ 2.5 psig	A	1. Above trip setting in conjunction with low reactor pressure initiates CSS. Multiplier relays initiate HPCI. 2. Multiplier relay from CSS initiates accident signal. (15)
3.2/4.2-15	2	Instrument Channel - Drywell High Pressure (PS-64-58A-D, SW #1)	≤ 2.5 psig	A	1. Above trip setting in conjunction with low reactor pressure initiates LPCI.
Amendment No. 164	2(16)	Instrument Channel - Drywell High Pressure (PS-64-57A-D)	≤ 2.5 psig	A	1. Above trip setting, in conjunction with low reactor water level, drywell high pressure, 120 sec. delay timer and CSS or RHR pump running, initiates ADS.

Table 3.2.L
Anticipated Transient Without Scram (ATWS) -
Recirculation Pump Test (RPT) Surveillance Instrumentation

Minimum No. Channels operable per Trip Sys (1)	Function	Trip Setting	Value	Action	Allowable Remarks
2	ATWS/RPT Logic Reactor Dome Pressure High	1118 psig	≤ 1146.5 psig	(2)	Two out of two of the high reactor dome pressure channels or the low reactor vessel level channels in either trip system trips both reactor recirculation pumps.
2	Reactor Vessel Level Low	483" above vessel zero	≥ 471.52 " above vessel zero		

- (1) One channel in only one trip system may be placed in an inoperable status for up to 6 hours for required surveillance provided the other channels in that trip system are OPERABLE.
- (2) Two trip systems exist, either of which will trip both recirculation pumps. Perform Surveillance/maintenance/calibration on one channel in only one trip system at a time. If a channel is found to be inoperable or if the surveillance/maintenance/calibration period for one channel exceeds 6 consecutive hours, the trip system will be declared inoperable or the channel will be placed in a tripped condition. If in RUN mode and one trip system is inoperable for 72 hours or both trip systems are inoperable, the reactor shall be in at least the HOT STANDBY CONDITION within 6 hours.

TABLE 4.2.B
SURVEILLANCE REQUIREMENTS FOR INSTRUMENTATION THAT INITIATE OR CONTROL THE CSCS

BFN
Unit 1

<u>Function</u>	<u>Functional Test</u>	<u>Calibration</u>	<u>Instrument Check</u>
Instrument Channel - Reactor Low Water Level (LIS-3-58A-D)	(1)	once/3 months	once/day
Instrument Channel - Reactor Low Water Level (LIS-3-184 & 185)	(1)	once/3 months	once/day
Instrument Channel - Reactor Low Water Level (LITS-3-52 & 62)	(1)	once/3 months	once/day
Instrument Channel - Drywell High Pressure (PS-64-58E-H)	(1)	once/3 months	none
Instrument Channel - Drywell High Pressure (PS-64-58A-D)	(1)	once/3 months	none
Instrument Channel - Drywell High Pressure (PS-64-57A-D)	(1)	once/3 months	none
Instrument Channel - Reactor Low Pressure (PS-3-74A & B) (PS-68-95) (PS-68-96)	(1)	once/3 months	none

3.2/4.2-44

Amendment No. 164

TABLE 4.2.B (Continued)
SURVEILLANCE REQUIREMENTS FOR INSTRUMENTATION THAT INITIATE OR CONTROL THE CSCS

<u>Function</u>	<u>Functional Test</u>	<u>Calibration</u>	<u>Instrument Check</u>
Instrument Channel - Reactor Low Pressure (PS-68-93 & 94)	(1)	once/3 months	none
Core Spray Auto Sequencing Timers (Normal Power)	(4)	once/operating cycle	none
Core Spray Auto Sequencing Timers (Diesel Power)	(4)	once/operating cycle	none
LPCI Auto Sequencing Timers (Normal Power)	(4)	once/operating cycle	none
LPCI Auto Sequencing Timers (Diesel Power)	(4)	once/operating cycle	none
RHR SW A1, B3, C1, D3 Timers (Normal Power)	(4)	once/operating cycle	none
RHR SW A1, B3, C1, D3 Timers (Diesel Power)	(4)	once/operating cycle	none
ADS Timer	(4)	once/operating cycle	none

BFN-Unit 1

NOTES FOR TABLES 4.2.A THROUGH 4.2.L except 4.2.D AND 4.2.K

1. Functional tests shall be performed once per month.
2. Functional tests shall be performed before each startup with a required frequency not to exceed once per week.
3. This instrumentation is excepted from the functional test definition. The functional test will consist of injecting a simulated electrical signal into the measurement channel.
4. Tested during logic system functional tests.
5. Refer to Table 4.1.B.
6. The logic system functional tests shall include a calibration once per operating cycle of time delay relays and timers necessary for proper functioning of the trip systems.
7. The functional test will consist of verifying continuity across the inhibit with a volt-ohmmeter.
8. Instrument checks shall be performed in accordance with the definition of instrument check (see Section 1.0, Definitions). An instrument check is not applicable to a particular setpoint, such as Upscale, but is a qualitative check that the instrument is behaving and/or indicating in an acceptable manner for the particular plant condition. Instrument check is included in this table for convenience and to indicate that an instrument check will be performed on the instrument. Instrument checks are not required when these instruments are not required to be operable or are tripped.
9. Calibration frequency shall be once/year.
10. Deleted
11. Portion of the logic is functionally tested during outage only.
12. The detector will be inserted during each operating cycle and the proper amount of travel into the core verified.
13. Functional test will consist of applying simulated inputs (see note 3). Local alarm lights representing upscale and downscale trips will be verified, but no rod block will be produced at this time. The inoperative trip will be initiated to produce a rod block (SRM and IRM inoperative also bypassed with the mode switch in RUN). The functions that cannot be verified to produce a rod block directly will be verified during the operating cycle.

NOTES FOR TABLES 4.2.A THROUGH 4.2.L except 4.2.D AND 4.2.K (Continued)

14. (Deleted)
15. The flow bias comparator will be tested by putting one flow unit in "Test" (producing 1/2 scram) and adjusting the test input to obtain comparator rod block. The flow bias upscale will be verified by observing a local upscale trip light during operation and verified that it will produce a rod block during the operating cycle.
16. Performed during operating cycle. Portions of the logic is checked more frequently during functional tests of the functions that produce a rod block.
17. This calibration consists of removing the function from service and performing an electronic calibration of the channel.
18. Functional test is limited to the condition where secondary containment integrity is not required as specified in Sections 3.7.C.2 and 3.7.C.3.
19. Functional test is limited to the time where the SGTS is required to meet the requirements of Section 4.7.C.1.a.
20. Calibration of the comparator requires the inputs from both recirculation loops to be interrupted, thereby removing the flow bias signal to the APRM and RBM and scrambling the reactor. This calibration can only be performed during an outage.
21. Logic test is limited to the time where actual operation of the equipment is permissible.
22. One channel of either the reactor zone or refueling zone Reactor Building Ventilation Radiation Monitoring System may be administratively bypassed for a period not to exceed 24 hours for functional testing and calibration.
23. (Deleted)
24. This instrument check consists of comparing the thermocouple readings for all valves for consistence and for nominal expected values (not required during refueling outages).
25. During each refueling outage, all acoustic monitoring channels shall be calibrated. This calibration includes verification of accelerometer response due to mechanical excitation in the vicinity of the sensor.

NOTES FOR TABLES 4.2.A THROUGH 4.2.L except 4.2.D AND 4.2.K (Continued)

26. This instrument check consists of comparing the background signal levels for all valves for consistency and for nominal expected values (not required during refueling outages).
27. Functional test consists of the injection of a simulated signal into the electronic trip circuitry in place of the sensor signal to verify operability of the trip and alarm functions.
28. Calibration consists of the adjustment of the primary sensor and associated components so that they correspond within acceptable range and accuracy to known values of the parameter which the channel monitors, including adjustment of the electronic trip circuitry, so that its output relay changes state at or more conservatively than the analog equivalent of the trip level setting.
29. The functional test frequency decreased to once/3 months to reduce challenges to relief valves per NUREG-0737, Item II.K.3.16.

Table 4.2.L
Anticipated Transient Without Scram (ATWS) -
Recirculation Pump Test (RPT) Instrumentation Surveillance

Function	Functional Test	Channel Calibration	Instrument Check
Reactor Vessel Water Level Low LS-3-58A-D	M(27)	R(28)	N/A
Reactor Vessel Dome Pressure High PS-3-204-D	M(27)	R(28)	N/A

3.2 BASES (Cont'd)

Trip setting of 100 mr/hr for the monitors in the refueling zone are based upon initiating normal ventilation isolation and SGTS operation so that none of the activity released during the refueling accident leaves the Reactor Building via the normal ventilation path but rather all the activity is processed by the SGTS.

Flow integrators and sump fill rate and pump out rate timers are used to determine leakage in the drywell. A system whereby the time interval to fill a known volume will be utilized to provide a backup. An air sampling system is also provided to detect leakage inside the primary containment (See Table 3.2.E).

For each parameter monitored, as listed in Table 3.2.F, there are two channels of instrumentation except as noted. By comparing readings between the two channels, a near continuous surveillance of instrument performance is available. Any deviation in readings will initiate an early recalibration, thereby maintaining the quality of the instrument readings.

Instrumentation is provided for isolating the control room and initiating a pressurizing system that processes outside air before supplying it to the control room. An accident signal that isolates primary containment will also automatically isolate the control room and initiate the emergency pressurization system. In addition, there are radiation monitors in the normal ventilation system that will isolate the control room and initiate the emergency pressurization system. Activity required to cause automatic actuation is about one mRem/hr.

Because of the constant surveillance and control exercised by TVA over the Tennessee Valley, flood levels of large magnitudes can be predicted in advance of their actual occurrence. In all cases, full advantage will be taken of advance warning to take appropriate action whenever reservoir levels above normal pool are predicted; however, the plant flood protection is always in place and does not depend in any way on advanced warning. Therefore, during flood conditions, the plant will be permitted to operate until water begins to run across the top of the pumping station at elevation 565. Seismically qualified, redundant level switches each powered from a separate division of power are provided at the pumping station to give main control room indication of this condition. At that time an orderly shutdown of the plant will be initiated, although surges even to a depth of several feet over the pumping station deck will not cause the loss of the main condenser circulating water pumps.

3.2 BASES (Cont'd)

The operability of the meteorological instrumentation ensures that sufficient meteorological data is available for estimating potential radiation dose to the public as a result of routine or accidental release of radioactive materials to the atmosphere. This capability is required to evaluate the need for initiating protective measures to protect the health and safety of the public.

The operability of the seismic instrumentation ensures that sufficient capability is available to promptly determine the magnitude of a seismic event and evaluate the response of those features important to safety. This capability is required to permit comparison of the measured response to that used in the design basis for Browns Ferry Nuclear Plant. The instrumentation provided is consistent with specific portions of the recommendations of Regulatory Guide 1.12 "Instrumentation for Earthquakes."

The radioactive gaseous effluent instrumentation is provided to monitor and control, as applicable, the releases of radioactive materials in gaseous effluents during actual or potential releases of gaseous effluents. The alarm/trip setpoints for these instruments will be calculated in accordance with guidance provided in the ODCM to ensure that the alarm/trip will occur prior to exceeding the limits of 10 CFR Part 20. This instrumentation also includes provisions for monitoring the concentration of potentially explosive gas mixtures in the offgas holdup system. The operability and use of this instrumentation is consistent with the requirements of General Design Criteria 60, 63, and 64 of Appendix A to 10 CFR Part 50.

The radioactive liquid effluent instrumentation is provided to monitor and control, as applicable, the releases of radioactive materials in liquid effluents during actual or potential releases of liquid effluents. The alarm/trip setpoints for these instruments shall be calculated in accordance with guidance provided in the ODCM to ensure that the alarm/trip will occur prior to exceeding the limits of 10 CFR Part 20 Appendix B, Table II, Column 2. The OPERABILITY and use of this instrumentation is consistent with the requirements of General Design Criteria 60, 63, and 64 of Appendix A to 10 CFR Part 50.

ATWS/RPT, Anticipated Transients without Scram/Recirculation Pump Trip system provides a means of limiting the consequences of the unlikely occurrence of a failure to scram during an ATWS event. The response of the plant to this postulated event (ATWS/RPT) follows the BWR Owners Group Report by General Electric NEDE-31096-P-A and the accompanying NRC Staff Safety Evaluation Report.

ATWS/RPT utilizes the engineered safety feature (ESF) master/slave analog trip units (ATU) which consists of four level and four pressure channels total. The initiating logic consists of two independent trip systems each consisting of two reactor dome high pressure channels and two reactor vessel low level channels. A coincident trip of either two low levels or two high pressures in the same trip system causes initiation of ATWS/RPT. This signal from either trip system opens one of two EOC

3.2 BASES (Cont'd)

- (end-of-cycle) breakers in series (the other system opens the other breaker) between the pump motor and the Motor Generator set driving each recirculation pump. Both systems are completely redundant such that only one trip system is necessary to perform the ATWS/RPT function. Power comes from the 250 VDC shutdown boards.

Setpoints for reactor dome high pressure and reactor vessel low level are such that a normal Reactor Protection System scram and accompanying recirculation pump trip would occur before or coincident with the trip by ATWS/RPT.

4.2 BASES

The instrumentation listed in Tables 4.2.A through 4.2.F will be functionally tested and calibrated at regularly scheduled intervals. The same design reliability goal as the Reactor Protection System of 0.99999 generally applies for all applications of (1-out-of-2) X (2) logic. Therefore, on-off sensors are tested once/3 months, and bistable trips associated with analog sensors and amplifiers are tested once/week.



UNITED STATES
NUCLEAR REGULATORY COMMISSION
WASHINGTON, D. C. 20555

TENNESSEE VALLEY AUTHORITY

DOCKET NO. 50-260

BROWNS FERRY NUCLEAR PLANT, UNIT 2

AMENDMENT TO FACILITY OPERATING LICENSE

Amendment No. 161
License No. DPR-52

1. The Nuclear Regulatory Commission (the Commission) has found that:
 - A. The application for amendment by Tennessee Valley Authority (the licensee) dated August 4, 1988, complies with the standards and requirements of the Atomic Energy Act of 1954, as amended (the Act), and the Commission's rules and regulations set forth in 10 CFR Chapter I;
 - B. The facility will operate in conformity with the application, the provisions of the Act, and the rules and regulations of the Commission;
 - C. There is reasonable assurance (i) that the activities authorized by this amendment can be conducted without endangering the health and safety of the public, and (ii) that such activities will be conducted in compliance with the Commission's regulations;
 - D. The issuance of this amendment will not be inimical to the common defense and security or to the health and safety of the public; and
 - E. The issuance of this amendment is in accordance with 10 CFR Part 51 of the Commission's regulations and all applicable requirements have been satisfied.


2. Accordingly, the license is amended by changes to the Technical Specifications as indicated in the attachment to this license amendment and paragraph 2.C.(2) of Facility Operating License No. DPR-52 is hereby amended to read as follows:

(2) Technical Specifications

The Technical Specifications contained in Appendices A and B, as revised through Amendment No. 161, are hereby incorporated in the license. The licensee shall operate the facility in accordance with the Technical Specifications.

3. This license amendment is effective as of its date of issuance and shall be implemented within 60 days from the date of issuance.

FOR THE NUCLEAR REGULATORY COMMISSION



Suzanne Black, Assistant Director
for Projects
TVA Projects Division
Office of Nuclear Reactor Regulation

Attachment:
Changes to the Technical
Specifications

Date of Issuance: January 26, 1989

ATTACHMENT TO LICENSE AMENDMENT NO. 161

FACILITY OPERATING LICENSE NO. DPR-52

DOCKET NO. 50-260

Revise the Appendix A Technical Specifications by removing the pages identified below and inserting the enclosed pages. The revised pages are identified by the captioned amendment number and contain marginal lines indicating the area of change. Overleaf pages* are provided to maintain document completeness.

REMOVE

i
ii
v
vi
vii
viii
-
3.2/4.2-14
3.2/4.2-15
-
3.2/4.2-44
3.2/4.2-45
3.2/4.2-59
3.2/4.2-60
3.2/4.2-61
-
3.2/4.2-69
3.2/4.2-70
-

INSERT

i
ii*
v*
vi
vii
viii*
3.2/4.2-6a
3.2/4.2-14*
3.2/4.2-15
3.2/4.2-39a
3.2/4.2-44
3.2/4.2-45*
3.2/4.2-59
3.2/4.2-60
3.2/4.2-61
3.2/4.2-63a
3.2/4.2-69*
3.2/4.2-70
3.2/4.2-70a

TABLE OF CONTENTS

<u>Section</u>		<u>Page No.</u>
1.0	Definitions.	1.0-1
	<u>SAFETY LIMITS AND LIMITING SAFETY SYSTEM</u> <u>SETTINGS</u>	
1.1/2.1	Fuel Cladding Integrity.	1.1/2.1-1
1.2/2.2	Reactor Coolant System Integrity	1.2/2.2-1
	<u>LIMITING CONDITIONS FOR OPERATION AND</u> <u>SURVEILLANCE REQUIREMENTS</u>	
3.1/4.1	Reactor Protection System	3.1/4.1-1
3.2/4.2	Protective Instrumentation.	3.2/4.2-1
	A. Primary Containment and Reactor Building Isolation Functions.	3.2/4.2-1
	B. Core and Containment Cooling Systems - Initiation and Control	3.2/4.2-1
	C. Control Rod Block Actuation.	3.2/4.2-2
	D. Radioactive Liquid Effluent Monitoring Instrumentation.	3.2/4.2-3
	E. Drywell Leak Detection	3.2/4.2-4
	F. Surveillance Instrumentation	3.2/4.2-4
	G. Control Room Isolation	3.2/4.2-4
	H. Flood Protection	3.2/4.2-4
	I. Meteorological Monitoring Instrumentation. . .	3.2/4.2-4
	J. Seismic Monitoring Instrumentation	3.2/4.2-5
	K. Radioactive Gaseous Effluent Monitoring Instrumentation	3.2/4.2-6
	L. ATWS-Recirculation Pump Trip	3.2/4.2-6a
3.3/4.3	Reactivity Control	3.3/4.3-1
	A. Reactivity Limitations	3.3/4.3-1
	B. Control Rods	3.3/4.3-5
	C. Scram Insertion Times.	3.3/4.3-10

<u>Section</u>	<u>Page No.</u>
D. Reactivity Anomalies	3.3/4.3-11
E. Reactivity Control	3.3/4.3-12
F. Scram Discharge Volume	3.3/4.3-12
3.4/4.4 Standby Liquid Control System.	3.4/4.4-1
A. Normal System Availability	3.4/4.4-1
B. Operation with Inoperable Components	3.4/4.4-2
C. Sodium Pentaborate Solution.	3.4/4.4-3
3.5/4.5 Core and Containment Cooling Systems	3.5/4.5-1
A. Core Spray System (CSS).	3.5/4.5-1
B. Residual Heat Removal System (RHRS) (LPCI and Containment Cooling)	3.5/4.5-4
C. RHR Service Water System and Emergency Equipment Cooling Water System (EECWS)	3.5/4.5-9
D. Equipment Area Coolers	3.5/4.5-13
E. High Pressure Coolant Injection System (HPCIS).	3.5/4.5-13
F. Reactor Core Isolation Cooling System (RCICS).	3.5/4.5-14
G. Automatic Depressurization System (ADS).	3.5/4.5-15
H. Maintenance of Filled Discharge Pipe	3.5/4.5-17
I. Average Planar Linear Heat Generation Rate	3.5/4.5-18
J. Linear Heat Generation Rate (LHGR)	3.5/4.5-18
K. Minimum Critical Power Ratio (MCPR).	3.5/4.5-19
L. APRM Setpoints	3.5/4.5-20
M. Reporting Requirements	3.5/4.5-20
N. References	3.5/4.5-32
3.6/4.6 Primary System Boundary.	3.6/4.6-1
A. Thermal and Pressurization Limitations	3.6/4.6-1
B. Coolant Chemistry.	3.6/4.6-5

ADMINISTRATIVE CONTROLS

<u>SECTION</u>		<u>PAGE</u>
<u>6.1</u>	<u>RESPONSIBILITY</u>	6.0-1
<u>6.2</u>	<u>ORGANIZATION</u>	6.0-1
6.2.1	Corporate.....	6.0-1
6.2.2	Plant Staff.....	6.0-1
<u>6.3</u>	<u>PLANT STAFF QUALIFICATIONS</u>	6.0-4
<u>6.4</u>	<u>TRAINING</u>	6.0-4
<u>6.5</u>	<u>PLANT REVIEW AND AUDIT</u>	6.0-4
6.5.1	Plant Operation Review Committee (PORC).....	6.0-4
6.5.2	Nuclear Safety Review Board (NSRB).....	6.0-10
6.5.3	Technical Review and Approval of Procedures.....	6.0-16
<u>6.6</u>	<u>REPORTABLE EVENT ACTIONS</u>	6.0-17
<u>6.7</u>	<u>SAFETY LIMIT VIOLATION</u>	6.0-18
<u>6.8</u>	<u>PROCEDURES/INSTRUCTION AND PROGRAMS</u>	6.0-19
6.8.1	Procedures.....	6.0-19
6.8.2	Drills.....	6.0-20
6.8.3	Radiation Control Procedures.....	6.0-20
6.8.4	Quality Assurance Procedures - Effluent and.....	
	Environmental Monitoring.....	6.0-22
<u>6.9</u>	<u>REPORTING REQUIREMENTS</u>	6.0-23
6.9.1	Routine Reports.....	6.0-23
	Startup Reports.....	6.0-23
	Annual Operating Report.....	6.0-24
	Monthly Operating Report.....	6.0-25
	Reportable Events.....	6.0-25
	Radioactive Effluent Release Report.....	6.0-25
	Source Tests.....	6.0-25
6.9.2	Special Reports.....	6.0-26
<u>6.10</u>	<u>STATION OPERATING RECORDS AND RETENTION</u>	6.0-28
<u>6.11</u>	<u>PROCESS CONTROL PROGRAM</u>	6.0-31
<u>6.12</u>	<u>OFFSITE DOSE CALCULATION MANUAL</u>	6.0-31
<u>6.13</u>	<u>RADIOLOGICAL EFFLUENT MANUAL</u>	6.0-32

LIST OF TABLES

<u>Table</u>	<u>Title</u>	<u>Page No.</u>
1.1	Surveillance Frequency Notation	1.0-11
3.1.A	Reactor Protection System (SCRAM) Instrumentation Requirements.	3.1/4.1-3
4.1.A	Reactor Protection System (SCRAM) Instrumentation Functional Tests Minimum Functional Test Frequencies for Safety Instr. and Control Circuits.	3.1/4.1-8
4.1.B	Reactor Protection System (SCRAM) Instrumentation Calibration Minimum Calibration Frequencies for Reactor Protection Instrument Channels. . . .	3.1/4.1-11
3.2.A	Primary Containment and Reactor Building Isolation Instrumentation	3.2/4.2-7
3.2.B	Instrumentation that Initiates or Controls the Core and Containment Cooling Systems.	3.2/4.2-14
3.2.C	Instrumentation that Initiates Rod Blocks	3.2/4.2-25
3.2.D	Radioactive Liquid Effluent Monitoring.	3.2/4.2-28
3.2.E	Instrumentation that Monitors Leakage Into Drywell. .	3.2/4.2-30
3.2.F	Surveillance Instrumentation.	3.2/4.2-31
3.2.G	Control Room Isolation Instrumentation.	3.2/4.2-34
3.2.H	Flood Protection Instrumentation.	3.2/4.2-35
3.2.I	Meteorological Monitoring Instrumentation	3.2/4.2-36
3.2.J	Seismic Monitoring Instrumentation.	3.2/4.2-37
3.2.K	Radioactive Gaseous Effluent Monitoring Instrumentation	3.2/4.2-38
3.2.L	ATWS-Recirculation Pump Trip Instrumentation. . . .	3.2/4.2-39a
4.2.A	Surveillance Requirements for Primary Containment and Reactor Building Isolation Instrumentation. .	3.2/4.2-40
4.2.B	Surveillance Requirements for Instrumentation that Initiate or Control the CSCS.	3.2/4.2-44
4.2.C	Surveillance Requirements for Instrumentation that Initiate Rod Blocks	3.2/4.2-50
4.2.D	Radioactive Liquid Effluent Monitoring Instrumentation Surveillance Requirements	3.2/4.2-51

LIST OF TABLES (Cont'd)

<u>Table</u>	<u>Title</u>	<u>Page No.</u>
4.2.E	Minimum Test and Calibration Frequency for Drywell Leak Detection Instrumentation.	3.2/4.2-53
4.2.F	Minimum Test and Calibration Frequency for Surveillance Instrumentation	3.2/4.2-54
4.2.G	Surveillance Requirements for Control Room Isolation Instrumentation.	3.2/4.2-56
4.2.H	Minimum Test and Calibration Frequency for Flood Protection Instrumentation	3.2/4.2-57
4.2.J	Seismic Monitoring Instrument Surveillance Requirements	3.2/4.2-58
4.2.K	Radioactive Gaseous Effluent Instrumentation Surveillance	3.2/4.2-62
4.2.L	ATWS-Recirculation Pump Trip Instrumentation Surveillance	3.2/4.2-63a
3.5-1	Minimum RHRSW and EECW Pump Assignment	3.5/4.5-11
3.5.I	MAPLHGR Versus Average Planar Exposure	3.5/4.5-21
3.7.A	Primary Containment Isolation Valves	3.7/4.7-25
3.7.B	Testable Penetrations with Double O-Ring Seals . .	3.7/4.7-32
3.7.C	Testable Penetrations with Testable Bellows. . . .	3.7/4.7-33
3.7.D	Air Tested Isolation Valves.	3.7/4.7-34
3.7.E	Primary Containment Isolation Valves which Terminate below the Suppression Pool Water Level.	3.7/4.7-37
3.7.F	Primary Containment Isolation Valves Located in Water Sealed Seismic Class 1 Lines	3.7/4.7-38
3.7.H	Testable Electrical Penetrations	3.7/4.7-39
4.9.A.4.C	Voltage Relay Setpoints/Diesel Generator Start . .	3.9/4.9-16
3.11.A	Fire Protection System Hydraulic Requirements. . .	3.11/4.11-10
6.2.A	Minimum Shift Crew Requirements.	6.0-3

LIST OF ILLUSTRATIONS

<u>Figure</u>	<u>Title</u>	<u>Page No.</u>
2.1.1	APRM Flow Reference Scram and APRM Rod Block Settings	1.1/2.1-6
2.1-2	APRM Flow Bias Scram Vs. Reactor Core Flow	1.1/2.1-7
4.1-1	Graphic Aid in the Selection of an Adequate Interval Between Tests	3.1/4.1-13
4.2-1	System Unavailability.	3.2/4.2-64
3.5.K-1	MCPR Limits.	3.5/4.5-22
3.5.2	K_f Factor.	3.5/4.5-23
3.6-1	Minimum Temperature °F Above Change in Transient Temperature.	3.6/4.6-24
3.6-2	Change in Charpy V Transition Temperature Vs. Neutron Exposure	3.6/4.6-25
4.8.1.a	Gaseous Release Points and Elevations	3.8/4.8-10
4.8.1.b	Land Site Boundary	3.8/4.8-11
6.2-1	Offsite Organization for Facility Management and Technical Support	6.0-33
6.2-2	Facility Organization	6.0-34

3.2/4.2 Protective Instrumentation

LIMITING CONDITIONS FOR OPERATION

3.2.L ATWS/RPT

1. The ATWS/RPT System Instrumentation shall be OPERABLE during REACTOR POWER OPERATION in accordance with Table 3.2.L.
2. The ATWS/RPT System Trip setpoints will be set in accordance with Table 3.2.L.
3. The actions required when the number of operable channels is less than the minimum OPERABLE channels per trip system is specified in Table 3.2.L.

SURVEILLANCE REQUIREMENTS

4.2.L ATWS/RPT

1. Each of the ATWS/RPT System Instrumentation channels shall be OPERABLE by performance of tests in Table 4.2.L.

TABLE 3.2.B
INSTRUMENTATION THAT INITIATES OR CONTROLS THE CORE AND CONTAINMENT COOLING SYSTEMS

Minimum No. Operable Per Trip Sys(1)	Function	Trip Level Setting	Action	Remarks
2	Instrument Channel - Reactor Low Water Level (LIS-3-58A-D)	≥ 470 " above vessel zero.	A	1. Below trip setting initiated HPCI.
2	Instrument Channel - Reactor Low Water Level (LIS-3-58A-D)	≥ 470 " above vessel zero.	A RCIC.	1. Multiplier relays initiate
2	Instrument Channel - Reactor Low Water Level (LIS-3-58A-D)	≥ 378 " above vessel zero.	A	1. Below trip setting initiates CSS. Multiplier relays initiate LPCI. 2. Multiplier relay from CSS initiates accident signal (15).
2(16)	Instrument Channel - Reactor Low Water Level (LIS-3-58A-D)	≥ 378 " above vessel zero.	A	1. Below trip settings, in conjunction with drywell high pressure, low water level permissive, 120 sec. delay timer and CSS or RHR pump running, initiates ADS.
1(16)	Instrument Channel - Reactor Low Water Level Permissive (LIS-3-184, 185)	≥ 544 " above vessel zero.	A	1. Below trip setting permissive for initiating signals on ADS.
1	Instrument Channel - Reactor Low Water Level (LIS-3-52 and 62)	$\geq 312 \frac{5}{16}$ " above vessel zero. A (2/3 core height)	A	1. Below trip setting prevents inadvertent operation of containment spray during accident condition.

BFN
Unit 2

3.2/4.2-14

Amendment No. 144

TABLE 3.2.B (Continued)

Minimum No. Operable Per Trip Sys(1)	Function	Trip Level Setting	Action	Remarks
2	Instrument Channel - Drywell High Pressure (PS-64-58 E-H)	$1 \leq p \leq 2.5$ psig	A	1. Below trip setting prevents inadvertent operation of containment spray during accident conditions.
2	Instrument Channel - Drywell High Pressure (PS-64-58 A-D)	≤ 2.5 psig	A	1. Above trip setting in conjunction with low reactor pressure initiates CSS. Multiplier relays initiate HPCI. 2. Multiplier relay from CSS initiates accident signal. (15)
2	Instrument Channel - Drywell High Pressure (PIS-64-58A-D)	≤ 2.5 psig	A	1. Above trip setting in conjunction with low reactor pressure initiates LPCI.
2(16)	Instrument Channel - Drywell High Pressure (PIS-64-57A-D)	≤ 2.5 psig	A	1. Above trip setting, in conjunction with low reactor water level, drywell high pressure, 120 sec. delay timer and CSS or RHR pump running, initiates ADS.

Table 3.2.L
Anticipated Transient Without Scram (ATWS) -
Recirculation Pump Test (RPT) Surveillance Instrumentation

Minimum No. Channels operable per Trip Sys (1)	Function	Trip Setting	Value	Action	Allowable Remarks
2	ATWS/RPT Logic Reactor Dome Pressure High	1118 psig	≤ 1146.5 psig	(2)	Two out of two of the high reactor dome pressure channels or the low reactor vessel level channels in either trip system trips both reactor recirculation pumps.
2	Reactor Vessel Level Low	483" above vessel zero	≥ 471.52 " above vessel zero		

(1) One channel in only one trip system may be placed in an inoperable status for up to 6 hours for required surveillance provided the other channels in that trip system are OPERABLE.

(2) Two trip systems exist, either of which will trip both recirculation pumps. Perform Surveillance/maintenance/calibration on one channel in only one trip system at a time. If a channel is found to be inoperable or if the surveillance/maintenance/calibration period for one channel exceeds 6 consecutive hours, the trip system will be declared inoperable or the channel will be placed in a tripped condition. If in RUN mode and one trip system is inoperable for 72 hours or both trip systems are inoperable, the reactor shall be in at least the HOT STANDBY CONDITION within 6 hours.

TABLE 4.2.B
SURVEILLANCE REQUIREMENTS FOR INSTRUMENTATION THAT INITIATE OR CONTROL THE CSCS

<u>Function</u>	<u>Functional Test</u>	<u>Calibration</u>		<u>Instrument Check</u>
Instrument Channel Reactor Low Water Level (LIS-3-58A-D)	(1) (27)	Once/18 Months	(28)	Once/day
Instrument Channel Reactor Low Water Level (LIS-3-184 & 185)	(1) (27)	Once/18 Months	(28)	Once/day
Instrument Channel Reactor Low Water Level (LIS-3-52 & 62)	(1) (27)	Once/18 Months	(28)	Once/day
Instrument Channel Drywell High Pressure (PIS-64-58E-H)	(1) (27)	Once/18 Months	(28)	none
Instrument Channel Drywell High Pressure (PIS-64-58A-D)	(1) (27)	Once/18 Months	(28)	none
Instrument Channel Drywell High Pressure (PIS-64-57A-D)	(1) (27)	Once/18 Months	(28)	none
Instrument Channel Reactor Low Pressure (PIS-3-74A&B, PS-3-74A&B) (PIS-68-95, PS-68-95) (PIS-68-96, PS-68-96)	(1) (27)	Once/18 Months	(28)	none

TABLE 4.2.B (Continued)
SURVEILLANCE REQUIREMENTS FOR INSTRUMENTATION THAT INITIATE OR CONTROL THE CSCS

<u>Function</u>	<u>Functional Test</u>	<u>Calibration</u>	<u>Instrument Check</u>
Instrument Channel Reactor Low Pressure (PS-68-93 & 94)	(1)	Once/3 months	none
Core Spray Auto Sequencing Timers (Normal Power)	(4)	Once/operating cycle	none
Core Spray Auto Sequencing Timers (Diesel Power)	(4)	Once/operating cycle	none
LPCI Auto Sequencing Timers (Normal Power)	(4)	Once/operating cycle	none
LPCI Auto Sequencing Timers (Diesel Power)	(4)	Once/operating cycle	none
RHRSW A1, B3, C1, D3 Timers (Normal Power)	(4)	Once/operating cycle	none
RHRSW A1, B3, C1, D3 Timers (Diesel Power)	(4)	Once/operating cycle	none
ADS Timer	(4)	Once/operating cycle	none

BFN
Unit 2

3.2/4.2-45

NOTES FOR TABLES 4.2.A THROUGH 4.2.L except 4.2. D AND 4.2.K

1. Functional tests shall be performed once per month.
2. Functional tests shall be performed before each startup with a required frequency not to exceed once per week.
3. This instrumentation is excepted from the functional test definition. The functional test will consist of injecting a simulated electrical signal into the measurement channel.
4. Tested during logic system functional tests.
5. Refer to Table 4.1.B.
6. The logic system functional tests shall include a calibration once per operating cycle of time delay relays and timers necessary for proper functioning of the trip systems.
7. The functional test will consist of verifying continuity across the inhibit with a volt-ohmmeter.
8. Instrument checks shall be performed in accordance with the definition of instrument check (see Section 1.0, Definitions). An instrument check is not applicable to a particular setpoint, such as Upscale, but is a qualitative check that the instrument is behaving and/or indicating in an acceptable manner for the particular plant condition. Instrument check is included in this table for convenience and to indicate that an instrument check will be performed on the instrument. Instrument checks are not required when these instruments are not required to be OPERABLE or are tripped.
9. Calibration frequency shall be once/year.
10. Deleted
11. Portion of the logic is functionally tested during outage only.
12. The detector will be inserted during each operating cycle and the proper amount of travel into the core verified.
13. Functional test will consist of applying simulated inputs (see note 3). Local alarm lights representing upscale and downscale trips will be verified, but no rod block will be produced at this time. The inoperative trip will be initiated to produce a rod block (SRM and IRM inoperative also bypassed with the mode switch in RUN). The functions that cannot be verified to produce a rod block directly will be verified during the operating cycle.

NOTES FOR TABLES 4.2.A THROUGH 4.2.L except 4.2.D AND 4.2.K (Cont'd)

14. (Deleted)
15. The flow bias comparator will be tested by putting one flow unit in "Test" (producing 1/2 scram) and adjusting the test input to obtain comparator rod block. The flow bias upscale will be verified by observing a local upscale trip light during operation and verified that it will produce a rod block during the operating cycle.
16. Performed during operating cycle. Portions of the logic is checked more frequently during functional tests of the functions that produce a rod block.
17. This calibration consists of removing the function from service and performing an electronic calibration of the channel.
18. Functional test is limited to the condition where secondary containment integrity is not required as specified in Sections 3.7.C.2 and 3.7.C.3.
19. Functional test is limited to the time where the SGTS is required to meet the requirements of Section 4.7.C.1.a.
20. Calibration of the comparator requires the inputs from both recirculation loops to be interrupted, thereby removing the flow bias signal to the APRM and RBM and scrambling the reactor. This calibration can only be performed during an outage.
21. Logic test is limited to the time where actual operation of the equipment is permissible.
22. One channel of either the reactor zone or refueling zone Reactor Building Ventilation Radiation Monitoring System may be administratively bypassed for a period not to exceed 24 hours for functional testing and calibration.
23. (Deleted)
24. This instrument check consists of comparing the thermocouple readings for all valves for consistence and for nominal expected values (not required during refueling outages).
25. During each refueling outage, all acoustic monitoring channels shall be calibrated. This calibration includes verification of accelerometer response due to mechanical excitation in the vicinity of the sensor.

NOTES FOR TABLES 4.2.A THROUGH 4.2.L except 4.2.D AND 4.2.K (Cont'd)

26. This instrument check consists of comparing the background signal levels for all valves for consistency and for nominal expected values (not required during refueling outages).
27. Functional test consists of the injection of a simulated signal into the electronic trip circuitry in place of the sensor signal to verify operability of the trip and alarm functions.
28. Calibration consists of the adjustment of the primary sensor and associated components so that they correspond within acceptable range and accuracy to known values of the parameter which the channel monitors, including adjustment of the electronic trip circuitry, so that its output relay changes state at or more conservatively than the analog equivalent of the trip level setting.
29. The functional test frequency decreased to once/3 months to reduce challenges to relief valves per NUREG-0737, Item II.K.3.16.
30. Calibration shall consist of an electronic calibration of the channel, not including the detector, for range decades above 10 R/hr and a one-point source check of the detector below 10 R/hr with an installed or portable gamma source.

Table 4.2.L^a
Anticipated Transient Without Scram (ATWS) -
Recirculation Pump Test (RPT) Instrumentation Surveillance

Function	Functional Test	Channel Calibration	Instrument Check
Reactor Vessel Water Level Low LS-3-58A-D	M(27)	R(28)	N/A
Reactor Vessel Dome Pressure High PS-3-204-D	M(27)	R(28)	N/A

3.2 BASES (Cont'd)

Trip setting of 100 mr/hr for the monitors in the refueling zone are based upon initiating normal ventilation isolation and SGTS operation so that none of the activity released during the refueling accident leaves the Reactor Building via the normal ventilation path but rather all the activity is processed by the SGTS.

Flow integrators and sump fill rate and pump out rate timers are used to determine leakage in the drywell. A system whereby the time interval to fill a known volume will be utilized to provide a backup. An air sampling system is also provided to detect leakage inside the primary containment (See Table 3.2.E).

For each parameter monitored, as listed in Table 3.2.F, there are two channels of instrumentation except as noted. By comparing readings between the two channels, a near continuous surveillance of instrument performance is available. Any deviation in readings will initiate an early recalibration, thereby maintaining the quality of the instrument readings.

Instrumentation is provided for isolating the control room and initiating a pressurizing system that processes outside air before supplying it to the control room. An accident signal that isolates primary containment will also automatically isolate the control room and initiate the emergency pressurization system. In addition, there are radiation monitors in the normal ventilation system that will isolate the control room and initiate the emergency pressurization system. Activity required to cause automatic actuation is about one mRem/hr.

Because of the constant surveillance and control exercised by TVA over the Tennessee Valley, flood levels of large magnitudes can be predicted in advance of their actual occurrence. In all cases, full advantage will be taken of advance warning to take appropriate action whenever reservoir levels above normal pool are predicted; however, the plant flood protection is always in place and does not depend in any way on advanced warning. Therefore, during flood conditions, the plant will be permitted to operate until water begins to run across the top of the pumping station at elevation 565. Seismically qualified, redundant level switches each powered from a separate division of power are provided at the pumping station to give main control room indication of this condition. At that time an orderly shutdown of the plant will be initiated, although surges even to a depth of several feet over the pumping station deck will not cause the loss of the main condenser circulating water pumps.

3.2 BASES (Cont'd)

The operability of the meteorological instrumentation ensures that sufficient meteorological data is available for estimating potential radiation dose to the public as a result of routine or accidental release of radioactive materials to the atmosphere. This capability is required to evaluate the need for initiating protective measures to protect the health and safety of the public.

The operability of the seismic instrumentation ensures that sufficient capability is available to promptly determine the magnitude of a seismic event and evaluate the response of those features important to safety. This capability is required to permit comparison of the measured response to that used in the design basis for Browns Ferry Nuclear Plant. The instrumentation provided is consistent with specific portions of the recommendations of Regulatory Guide 1.12 "Instrumentation for Earthquakes."

The radioactive gaseous effluent instrumentation is provided to monitor and control, as applicable, the releases of radioactive materials in gaseous effluents during actual or potential releases of gaseous effluents. The alarm/trip setpoints for these instruments will be calculated in accordance with guidance provided in the ODCM to ensure that the alarm/trip will occur prior to exceeding the limits of 10 CFR Part 20. This instrumentation also includes provisions for monitoring the concentration of potentially explosive gas mixtures in the offgas holdup system. The operability and use of this instrumentation is consistent with the requirements of General Design Criteria 60, 63, and 64 of Appendix A to 10 CFR Part 50.

The radioactive liquid effluent instrumentation is provided to monitor and control, as applicable, the releases of radioactive materials in liquid effluents during actual or potential releases of liquid effluents. The alarm/trip setpoints for these instruments shall be calculated in accordance with guidance provided in the ODCM to ensure that the alarm/trip will occur prior to exceeding the limits of 10 CFR Part 20 Appendix B, Table II, Column 2. The OPERABILITY and use of this instrumentation is consistent with the requirements of General Design Criteria 60, 63, and 64 of Appendix A to 10 CFR Part 50.

ATWS/RPT, Anticipated Transients without Scram/Recirculation Pump Trip system provides a means of limiting the consequences of the unlikely occurrence of a failure to scram during an ATWS event. The response of the plant to this postulated event (ATWS/RPT) follows the BWR Owners Group Report by General Electric NEDE-31096-P-A and the accompanying NRC Staff Safety Evaluation Report.

ATWS/RPT utilizes the engineered safety feature (ESF) master/slave analog trip units (ATU) which consists of four level and four pressure channels total. The initiating logic consists of two independent trip systems each consisting of two reactor dome high pressure channels and two reactor vessel low level channels. A coincident trip of either two low levels or two high pressures in the same trip system causes initiation of ATWS/RPT. This signal from either trip system opens one of two EOC

3.2 BASES (Cont'd)

- (end-of-cycle) breakers in series (the other system opens the other breaker) between the pump motor and the Motor Generator set driving each recirculation pump. Both systems are completely redundant such that only one trip system is necessary to perform the ATWS/RPT function. Power comes from the 250 VDC shutdown boards.

Setpoints for reactor dome high pressure and reactor vessel low level are such that a normal Reactor Protection System scram and accompanying recirculation pump trip would occur before or coincident with the trip by ATWS/RPT.

4.2 BASES

The instrumentation listed in Tables 4.2.A through 4.2.F will be functionally tested and calibrated at regularly scheduled intervals. The same design reliability goal as the Reactor Protection System of 0.99999 generally applies for all applications of (1-out-of-2) X (2) logic. Therefore, on-off sensors are tested once/3 months, and bistable trips associated with analog sensors and amplifiers are tested once/week.



UNITED STATES
NUCLEAR REGULATORY COMMISSION
WASHINGTON, D. C. 20555

TENNESSEE VALLEY AUTHORITY

DOCKET NO. 50-296

BROWNS FERRY NUCLEAR PLANT, UNIT 3

AMENDMENT TO FACILITY OPERATING LICENSE

Amendment No. 135
License No. DPR-68

1. The Nuclear Regulatory Commission (the Commission) has found that:
 - A.. The application for amendment by Tennessee Valley Authority (the licensee) dated August 4, 1988, complies with the standards and requirements of the Atomic Energy Act of 1954, as amended (the Act), and the Commission's rules and regulations set forth in 10 CFR Chapter I;
 - B. The facility will operate in conformity with the application, the provisions of the Act, and the rules and regulations of the Commission;
 - C. There is reasonable assurance (i) that the activities authorized by this amendment can be conducted without endangering the health and safety of the public, and (ii) that such activities will be conducted in compliance with the Commission's regulations;
 - D. The issuance of this amendment will not be inimical to the common defense and security or to the health and safety of the public; and
 - E. The issuance of this amendment is in accordance with 10 CFR Part 51 of the Commission's regulations and all applicable requirements have been satisfied.


2. Accordingly, the license is amended by changes to the Technical Specifications as indicated in the attachment to this license amendment and paragraph 2.C.(2) of Facility Operating License No. DPR-68 is hereby amended to read as follows:

(2) Technical Specifications

The Technical Specifications contained in Appendices A and B, as revised through Amendment No. 135, are hereby incorporated in the license. The licensee shall operate the facility in accordance with the Technical Specifications.

3. This license amendment is effective as of its date of issuance and shall be implemented within 60 days from the date of issuance.

FOR THE NUCLEAR REGULATORY COMMISSION



Suzanne Black, Assistant Director
for Projects
TVA Projects Division
Office of Nuclear Reactor Regulation

Attachment:
Changes to the Technical
Specifications

Date of Issuance: January 26, 1989

ATTACHMENT TO LICENSE AMENDMENT NO. 135

FACILITY OPERATING LICENSE NO. DPR-68

DOCKET NO. 50-296

Revise the Appendix A Technical Specifications by removing the pages identified below and inserting the enclosed pages. The revised pages are identified by the captioned amendment number and contain marginal lines indicating the area of change. Overleaf pages* are provided to maintain document completeness.

REMOVE

i
ii
v
vi
vii
viii
-
3.2/4.2-14
3.2/4.2-15
-
3.2/4.2-43
3.2/4.2-44
3.2/4.2-58
3.2/4.2-59
3.2/4.2-60
-
3.2/4.2-68
3.2/4.2-69
-

INSERT

i
ii*
v*
vi
vii
viii*
3.2/4.2-6a
3.2/4.2-14*
3.2/4.2-15
3.2/4.2-38a
3.2/4.2-43
3.2/4.2-44*
3.2/4.2-58
3.2/4.2-59
3.2/4.2-60
3.2/4.2-62a
3.2/4.2-68*
3.2/4.2-69
3.2/4.2-69a

TABLE OF CONTENTS

<u>Section</u>	<u>Page No.</u>
1.0 Definitions.	1.0-1
<u>SAFETY LIMITS AND LIMITING SAFETY SYSTEM SETTINGS</u>	
1.1/2.1 Fuel Cladding Integrity.	1.1/2.1-1
1.2/2.2 Reactor Coolant System Integrity	1.2/2.2-1
<u>LIMITING CONDITIONS FOR OPERATION AND SURVEILLANCE REQUIREMENTS</u>	
3.1/4.1 Reactor Protection System	3.1/4.1-1
3.2/4.2 Protective Instrumentation.	3.2/4.2-1
A. Primary Containment and Reactor Building Isolation Functions.	3.2/4.2-1
B. Core and Containment Cooling Systems - Initiation and Control	3.2/4.2-1
C. Control Rod Block Actuation.	3.2/4.2-2
D. Radioactive Liquid Effluent Monitoring Instrumentation.	3.2/4.2-3
E. Drywell Leak Detection	3.2/4.2-4
F. Surveillance Instrumentation	3.2/4.2-4
G. Control Room Isolation	3.2/4.2-4
H. Flood Protection	3.2/4.2-4
I. Meteorological Monitoring Instrumentation. . .	3.2/4.2-4
J. Seismic Monitoring Instrumentation	3.2/4.2-5
K. Radioactive Gaseous Effluent Monitoring Instrumentation	3.2/4.2-6
L. ATWS-Recirculation Pump Trip	3.2/4.2-6a
3.3/4.3 Reactivity Control	3.3/4.3-1
A. Reactivity Limitations	3.3/4.3-1
B. Control Rods	3.3/4.3-5
C. Scram Insertion Times.	3.3/4.3-10

<u>Section</u>	<u>Page No.</u>
D. Reactivity Anomalies	3.3/4.3-11
E. Reactivity Control	3.3/4.3-12
F. Scram Discharge Volume	3.3/4.3-12
3.4/4.4 Standby Liquid Control System.	3.4/4.4-1
A. Normal System Availability	3.4/4.4-1
B. Operation with Inoperable Components	3.4/4.4-2
C. Sodium Pentaborate Solution.	3.4/4.4-3
3.5/4.5 Core and Containment Cooling Systems	3.5/4.5-1
A. Core Spray System (CSS).	3.5/4.5-1
B. Residual Heat Removal System (RHRS) (LPCI and Containment Cooling)	3.5/4.5-4
C. RHR Service Water System and Emergency Equipment Cooling Water System (EECWS)	3.5/4.5-9
D. Equipment Area Coolers	3.5/4.5-13
E. High Pressure Coolant Injection System (HPCIS).	3.5/4.5-13
F. Reactor Core Isolation Cooling System (RCICS).	3.5/4.5-14
G. Automatic Depressurization System (ADS). . . .	3.5/4.5-15
H. Maintenance of Filled Discharge Pipe	3.5/4.5-17
I. Average Planar Linear Heat Generation Rate . .	3.5/4.5-18
J. Linear Heat Generation Rate (LHGR)	3.5/4.5-18
K. Minimum Critical Power Ratio (MCPR).	3.5/4.5-19
L. APRM Setpoints	3.5/4.5-20
3.6/4.6 Primary System Boundary.	3.6/4.6-1
A. Thermal and Pressurization Limitations	3.6/4.6-1
B. Coolant Chemistry.	3.6/4.6-5

ADMINISTRATIVE CONTROLS

<u>SECTION</u>		<u>PAGE</u>
<u>6.1</u>	<u>RESPONSIBILITY</u>	6.0-1
<u>6.2</u>	<u>ORGANIZATION</u>	6.0-1
6.2.1	Corporate.....	6.0-1
6.2.2	Plant Staff.....	6.0-1
<u>6.3</u>	<u>PLANT STAFF QUALIFICATIONS</u>	6.0-4
<u>6.4</u>	<u>TRAINING</u>	6.0-4
<u>6.5</u>	<u>PLANT REVIEW AND AUDIT</u>	6.0-4
6.5.1	Plant Operation Review Committee (PORC).....	6.0-4
6.5.2	Nuclear Safety Review Board (NSRB).....	6.0-10
6.5.3	Technical Review and Approval of Procedures.....	6.0-16
<u>6.6</u>	<u>REPORTABLE EVENT ACTIONS</u>	6.0-17
<u>6.7</u>	<u>SAFETY LIMIT VIOLATION</u>	6.0-18
<u>6.8</u>	<u>PROCEDURES/INSTRUCTION AND PROGRAMS</u>	6.0-19
6.8.1	Procedures.....	6.0-19
6.8.2	Drills.....	6.0-20
6.8.3	Radiation Control Procedures.....	6.0-20
6.8.4	Quality Assurance Procedures - Effluent and.....	
	Environmental Monitoring.....	6.0-22
<u>6.9</u>	<u>REPORTING REQUIREMENTS</u>	6.0-23
6.9.1	Routine Reports.....	6.0-23
	Startup Reports.....	6.0-23
	Annual Operating Report.....	6.0-24
	Monthly Operating Report.....	6.0-25
	Reportable Events.....	6.0-25
	Radioactive Effluent Release Report.....	6.0-25
	Source Tests.....	6.0-25
6.9.2	Special Reports.....	6.0-26
<u>6.10</u>	<u>STATION OPERATING RECORDS AND RETENTION</u>	6.0-28
<u>6.11</u>	<u>PROCESS CONTROL PROGRAM</u>	6.0-31
<u>6.12</u>	<u>OFFSITE DOSE CALCULATION MANUAL</u>	6.0-31
<u>6.13</u>	<u>RADIOLOGICAL EFFLUENT MANUAL</u>	6.0-32

LIST OF TABLES

<u>Table</u>	<u>Title</u>	<u>Page No.</u>
1.1	Surveillance Frequency Notation	1.0-12
3.1.A	Reactor Protection System (SCRAM) Instrumentation Requirements.	3.1/4.1-2
4.1.A	Reactor Protection System (SCRAM) Instrumentation Functional Tests Minimum Functional Test Frequencies for Safety Instr. and Control Circuits.	3.1/4.1-7
4.1.B	Reactor Protection System (SCRAM) Instrumentation Calibration Minimum Calibration Frequencies for Reactor Protection Instrument Channels. . . .	3.1/4.1-10
3.2.A	Primary Containment and Reactor Building Isolation Instrumentation	3.2/4.2-7
3.2.B	Instrumentation that Initiates or Controls the Core and Containment Cooling Systems.	3.2/4.2-14
3.2.C	Instrumentation that Initiates Rod Blocks	3.2/4.2-24
3.2.D	Radioactive Liquid Effluent Monitoring Instrumentation	3.2/4.2-27
3.2.E	Instrumentation that Monitors Leakage Into Drywell.	3.2/4.2-29
3.2.F	Surveillance Instrumentation.	3.2/4.2-30
3.2.G	Control Room Isolation Instrumentation.	3.2/4.2-33
3.2.H	Flood Protection Instrumentation.	3.2/4.2-34
3.2.I	Meteorological Monitoring Instrumentation	3.2/4.2-35
3.2.J	Seismic Monitoring Instrumentation.	3.2/4.2-36
3.2.K	Radioactive Gaseous Effluent Monitoring Instrumentation	3.2/4.2-37
3.2.L	ATWS-Recirculation Pump Trip Instrumentation	3.2/4.2-38a
4.2.A	Surveillance Requirements for Primary Containment and Reactor Building Isolation Instrumentation. .	3.2/4.2-39
4.2.B	Surveillance Requirements for Instrumentation that Initiate or Control the CSCS.	3.2/4.2-43
4.2.C	Surveillance Requirements for Instrumentation that Initiate Rod Blocks	3.2/4.2-49
4.2.D	Radioactive Liquid Effluent Monitoring Instrumentation Surveillance Requirements	3.2/4.2-50

LIST OF TABLES (Cont'd)

<u>Table</u>	<u>Title</u>	<u>Page No.</u>
4.2.E	Minimum Test and Calibration Frequency for Drywell Leak Detection Instrumentation.	3.2/4.2-52
4.2.F	Minimum Test and Calibration Frequency for Surveillance Instrumentation	3.2/4.2-53
4.2.G	Surveillance Requirements for Control Room Isolation Instrumentation.	3.2/4.2-55
4.2.H	Minimum Test and Calibration Frequency for Flood Protection Instrumentation	3.2/4.2-56
4.2.J	Seismic Monitoring Instrument Surveillance Requirements	3.2/4.2-57
4.2.K	Radioactive Gaseous Effluent Instrumentation Surveillance	3.2/4.2-61
4.2.L	ATWS-Recirculation Pump Trip Instrumentation Surveillance	3.2/4.2-62a
3.5-1	Minimum RHRSW and EECW Pump Assignment	3.5/4.5-11
3.5.I	MAPLHGR Versus Average Planar Exposure	3.5/4.5-21
3.7.A	Primary Containment Isolation Valves	3.7/4.7-25
3.7.B	Testable Penetrations with Double O-Ring Seals . .	3.7/4.7-31
3.7.C	Testable Penetrations with Testable Bellows. . . .	3.7/4.7-32
3.7.D	Air Tested Isolation Valves.	3.7/4.7-33
3.7.E	Primary Containment Isolation Valves which Terminate below the Suppression Pool Water Level.	3.7/4.7-36
3.7.F	Primary Containment Isolation Valves Located in Water Sealed Seismic Class 1 Lines	3.7/4.7-37
3.7.H	Testable Electrical Penetrations	3.7/4.7-38
4.9.A.4.C	Voltage Relay Setpoints/Diesel Generator Start . .	3.9/4.9-15
3.11.A	Fire Protection System Hydraulic Requirements. . .	3.11/4.11-10
6.2.A	Minimum Shift Crew Requirements.	6.0-3

LIST OF ILLUSTRATIONS

<u>Figure</u>	<u>Title</u>	<u>Page No.</u>
2.1.1	APRM Flow Reference Scram and APRM Rod Block Settings	1.1/2.1-6
2.1-2	APRM Flow Bias Scram Vs. Reactor Core Flow	1.1/2.1-7
4.1-1	Graphic Aid in the Selection of an Adequate Interval Between Tests	3.1/4.1-12
4.2-1	System Unavailability.	3.2/4.2-63
3.5.K-1	MCPR Limits.	3.5/4.5-25
3.5.2	K _f Factor.	3.5/4.5-26
3.6-1	Minimum Temperature °F Above Change in Transient Temperature.	3.6/4.6-24
3.6-2	Change in Charpy V Transition Temperature Vs. Neutron Exposure	3.6/4.6-25
4.8.1.a	Gaseous Release Points and Elevation	3.8/4.8-10
4.8.1.b	Land Site Boundary	3.8/4.8-11
6.2-1	Offsite Organization for Facility Management and Technical Support	6.0-33
6.2-2	Facility Organization	6.0-34

3.2/4.2 Protective Instrumentation

LIMITING CONDITIONS FOR OPERATION

3.2.L ATWS/RPT

1. The ATWS/RPT System Instrumentation shall be OPERABLE during REACTOR POWER OPERATION in accordance with Table 3.2.L.
2. The ATWS/RPT System Trip setpoints will be set in accordance with Table 3.2.L.
3. The actions required when the number of operable channels is less than the minimum OPERABLE channels per trip system is specified in Table 3.2.L.

SURVEILLANCE REQUIREMENTS

4.2.L ATWS/RPT

1. Each of the ATWS/RPT System Instrumentation channels shall be OPERABLE by performance of tests in Table 4.2.L.

BFN
Unit 3

TABLE 3.2.B
INSTRUMENTATION THAT INITIATES OR CONTROLS THE CORE AND CONTAINMENT COOLING SYSTEMS

Minimum No.
Operable
per Trip Sys(1)

	Function	Trip Level Setting	Action	Remarks
2	Instrument Channel - Reactor Low Water Level	$\geq 470"$ above vessel zero.	A	1. Below trip setting initiated HPCI.
2	Instrument Channel - Reactor Low Water Level	$\geq 470"$ above vessel zero.	A	1. Multiplier relays initiate RCIC.
2	Instrument Channel - Reactor Low Water Level (LIS-3-58A-D, SW #1)	$\geq 378"$ above vessel zero.	A	1. Below trip setting initiates CSS. Multiplier relays initiate LPCI.
2(16)	Instrument Channel - Reactor Low Water Level (LIS-3-58A-D, SW #2)	$\geq 378"$ above vessel zero.	A	2. Multiplier relay from CSS initiates accident signal (15).
1(16)	Instrument Channel - Reactor Low Water Level Permissive (LIS-3-184 & 185, SW #1)	$\geq 544"$ above vessel zero.	A	1. Below trip settings, in conjunction with drywell high pressure, low water level permissive, 120 sec. delay timer and CSS or RHR pump running, initiates ADS.
1	Instrument Channel - Reactor Low Water Level (LIS-3-52 and 62, SW #1)	$\geq 312 \frac{5}{16}"$ above vessel zero. A (2/3 core height)	A	1. Below trip setting permissive for initiating signals on ADS. 1. Below trip setting prevents inadvertent operation of containment spray during accident condition.

3.2/4.2-14

TABLE 3.2.B (Continued)

Minimum No. Operable Per Trip Sys(1)	Function	Trip Level Setting	Action	Remarks
2	Instrument Channel - Drywell High Pressure (PS-64-58 E-H)	$1 \leq p \leq 2.5$ psig	A	1. Below trip setting prevents inadvertent operation of containment spray during accident conditions.
2	Instrument Channel - Drywell High Pressure (PS-64-58 A-D, SW #2)	≤ 2.5 psig	A	1. Above trip setting in con- junction with low reactor pressure initiates CSS. Multiplier relays initiate HPCI. 2. Multiplier relay from CSS initiates accident signal. (15)
2	Instrument Channel - Drywell High Pressure (PS-64-58A-D, SW #1)	≤ 2.5 psig	A	1. Above trip setting in conjunction with low reactor pressure initiates LPCI.
2(16)	Instrument Channel - Drywell High Pressure (PS-64-57A-D)	≤ 2.5 psig	A	1. Above trip setting, in conjunction with low reactor water level, drywell high pressure, 120 sec. delay timer and CSS or RHR pump running, initiates ADS.

BFN
Unit 3

3.2/4.2-15

Amendment No. 135

Table 3.2.L
Anticipated Transient Without Scram (ATWS) -
Recirculation Pump Test (RPT) Surveillance Instrumentation

Minimum No. Channels operable per Trip Sys (1)	Function	Trip Setting	Value	Action	Allowable Remarks
2	ATWS/RPT Logic Reactor Dome Pressure High	1118 psig	≤ 1146.5 psig	(2)	Two out of two of the high reactor dome pressure channels or the low reactor vessel level channels in either trip system trips both reactor recirculation pumps.
2	Reactor Vessel Level Low	483" above vessel zero	≥ 471.52 " above vessel zero		

- (1) One channel in only one trip system may be placed in an inoperable status for up to 6 hours for required surveillance provided the other channels in that trip system are OPERABLE.
- (2) Two trip systems exist, either of which will trip both recirculation pumps. Perform Surveillance/maintenance/calibration on one channel in only one trip system at a time. If a channel is found to be inoperable or if the surveillance/maintenance/calibration period for one channel exceeds 6 consecutive hours, the trip system will be declared inoperable or the channel will be placed in a tripped condition. If in RUN mode and one trip system is inoperable for 72 hours or both trip systems are inoperable, the reactor shall be in at least the HOT STANDBY CONDITION within 6 hours.

TABLE 4.2.B
SURVEILLANCE REQUIREMENTS FOR INSTRUMENTATION THAT INITIATE OR CONTROL THE CSCS

BFN Unit 3	Function	Functional Test	Calibration	Instrument Check
3.2/4.2-43	Instrument Channel - Reactor Low Water Level (LIS-3-58A-D)	(1)	once/3 months	once/day
	Instrument Channel - Reactor Low Water Level (LIS-3-184 & 185)	(1)	once/3 months	once/day
	Instrument Channel - Reactor Low Water Level (LITS-3-52 & 62)	(1)	once/3 months	once/day
	Instrument Channel - Drywell High Pressure (PS-64-58E-H)	(1)	once/3 months	none
	Instrument Channel - Drywell High Pressure (PS-64-58A-D)	(1)	once/3 months	none
	Instrument Channel - Drywell High Pressure (PS-64-57A-D)	(1)	once/3 months	none
Amendment No. 135	Instrument Channel - Reactor Low Pressure (PS-3-74A & B) (PS-68-95) (PS-68-96)	(1)	once/3 months	none

TABLE 4.2.B (Cont'd)
SURVEILLANCE REQUIREMENTS FOR INSTRUMENTATION THAT INITIATE OR CONTROL THE CSCS

<u>Function</u>	<u>Functional Test</u>	<u>Calibration</u>	<u>Instrument Check</u>
Instrument Channel - Reactor Low Pressure (PS-68-93 & 94)	(1)	once/3 months	none
Core Spray Auto Sequencing Timers (Normal Power)	(4)	once/operating cycle	none
Core Spray Auto Sequencing Timers (Diesel Power)	(4)	once/operating cycle	none
LPCI Auto Sequencing Timers (Normal Power)	(4)	once/operating cycle	none
LPCI Auto Sequencing Timers (Diesel Power)	(4)	once/operating cycle	none
RHR SW A3, B1, C3, D1 Timers (Normal Power)	(4)	once/operating cycle	none
RHR SW A3, B1, C3, D1 Timers (Diesel Power)	(4)	once/operating cycle	none
ADS Timer	(4)	once/operating cycle	none

NOTES FOR TABLES 4.2.A THROUGH 4.2.L except 4.2.D AND 4.2.K

1. Functional tests shall be performed once per month.
2. Functional tests shall be performed before each startup with a required frequency not to exceed once per week.
3. This instrumentation is excepted from the functional test definition. The functional test will consist of injecting a simulated electrical signal into the measurement channel.
4. Tested during logic system functional tests.
5. Refer to Table 4.1.B.
6. The logic system functional tests shall include a calibration once per operating cycle of time delay relays and timers necessary for proper functioning of the trip systems.
7. The functional test will consist of verifying continuity across the inhibit with a volt-ohmmeter.
8. Instrument checks shall be performed in accordance with the definition of instrument check (see Section 1.0, Definitions). An instrument check is not applicable to a particular setpoint, such as Upscale, but is a qualitative check that the instrument is behaving and/or indicating in an acceptable manner for the particular plant condition. Instrument check is included in this table for convenience and to indicate that an instrument check will be performed on the instrument. Instrument checks are not required when these instruments are not required to be operable or are tripped.
9. Calibration frequency shall be once/year.
10. (DELETED)
11. Portion of the logic is functionally tested during outage only.
12. The detector will be inserted during each operating cycle and the proper amount of travel into the core verified.
13. Functional test will consist of applying simulated inputs (see note 3). Local alarm lights representing upscale and downscale trips will be verified, but no rod block will be produced at this time. The inoperative trip will be initiated to produce a rod block (SRM and IRM inoperative also bypassed with the mode switch in RUN). The functions that cannot be verified to produce a rod block directly will be verified during the operating cycle.

NOTES FOR TABLES 4.2.A THROUGH 4.2.L except 4.2.D AND 4.2.K (Continued)

14. (Deleted)
15. The flow bias comparator will be tested by putting one flow unit in "Test" (producing 1/2 scram) and adjusting the test input to obtain comparator rod block. The flow bias upscale will be verified by observing a local upscale trip light during operation and verified that it will produce a rod block during the operating cycle.
16. Performed during operating cycle. Portions of the logic is checked more frequently during functional tests of the functions that produce a rod block.
17. This calibration consists of removing the function from service and performing an electronic calibration of the channel.
18. Functional test is limited to the condition where secondary containment integrity is not required as specified in Sections 3.7.C.2 and 3.7.C.3.
19. Functional test is limited to the time where the SGTS is required to meet the requirements of Section 4.7.C.1.a.
20. Calibration of the comparator requires the inputs from both recirculation loops to be interrupted, thereby removing the flow bias signal to the APRM and RBM and scrambling the reactor. This calibration can only be performed during an outage.
21. Logic test is limited to the time where actual operation of the equipment is permissible.
22. One channel of either the reactor zone or refueling zone Reactor Building Ventilation Radiation Monitoring System may be administratively bypassed for a period not to exceed 24 hours for functional testing and calibration.
23. (DELETED)
24. This instrument check consists of comparing the thermocouple readings for all valves for consistence and for nominal expected values (not required during refueling outages).
25. During each refueling outage, all acoustic monitoring channels shall be calibrated. This calibration includes verification of accelerometer response due to mechanical excitation in the vicinity of the sensor.

NOTES FOR TABLES 4.2.A THROUGH 4.2.L except 4.2.D AND 4.2.K (Continued)

26. This instrument check consists of comparing the background signal levels for all valves for consistency and for nominal expected values (not required during refueling outages).
27. Functional test frequency decreased to once/3 months to reduce the challenges to relief valves per NUREG-0737, Item II.K.3.16.
28. Functional test consists of the injection of a simulated signal into the electronic trip circuitry in place of the sensor signal to verify operability of the trip and alarm functions.
29. Calibration consists of the adjustment of the primary sensor and associated components so that they correspond within acceptable range and accuracy to known values of the parameter which the channel monitors, including adjustment of the electronic trip circuitry, so its output relay changes state at or more conservatively than the analog equivalent of the trip level settings.

Table 4.2.L
Anticipated Transient Without Scram (ATWS) -
Recirculation Pump Test (RPT) Instrumentation Surveillance

Function	Functional Test	Channel Calibration	Instrument Check
Reactor Vessel Water Level Low LS-3-58A-D	M(28)	R(29)	N/A
Reactor Vessel Dome Pressure High PS-3-204-D	M(28)	R(29)	N/A

3.2 BASES (Cont'd)

Trip setting of 100 mr/hr for the monitors in the refueling zone are based upon initiating normal ventilation isolation and SGTS operation so that none of the activity released during the refueling accident leaves the Reactor Building via the normal ventilation path but rather all the activity is processed by the SGTS.

Flow integrators and sump fill rate and pump out rate timers are used to determine leakage in the drywell. A system whereby the time interval to fill a known volume will be utilized to provide a backup. An air sampling system is also provided to detect leakage inside the primary containment (See Table 3.2.E).

For each parameter monitored, as listed in Table 3.2.F, there are two channels of instrumentation except as noted. By comparing readings between the two channels, a near continuous surveillance of instrument performance is available. Any deviation in readings will initiate an early recalibration, thereby maintaining the quality of the instrument readings.

Instrumentation is provided for isolating the control room and initiating a pressurizing system that processes outside air before supplying it to the control room. An accident signal that isolates primary containment will also automatically isolate the control room and initiate the emergency pressurization system. In addition, there are radiation monitors in the normal ventilation system that will isolate the control room and initiate the emergency pressurization system. Activity required to cause automatic actuation is about one mRem/hr.

Because of the constant surveillance and control exercised by TVA over the Tennessee Valley, flood levels of large magnitudes can be predicted in advance of their actual occurrence. In all cases, full advantage will be taken of advance warning to take appropriate action whenever reservoir levels above normal pool are predicted; however, the plant flood protection is always in place and does not depend in any way on advanced warning. Therefore, during flood conditions, the plant will be permitted to operate until water begins to run across the top of the pumping station at elevation 565. Seismically qualified, redundant level switches each powered from a separate division of power are provided at the pumping station to give main control room indication of this condition. At that time an orderly shutdown of the plant will be initiated, although surges even to a depth of several feet over the pumping station deck will not cause the loss of the main condenser circulating water pumps.

3.2 BASES (Cont'd)

The operability of the meteorological instrumentation ensures that sufficient meteorological data is available for estimating potential radiation dose to the public as a result of routine or accidental release of radioactive materials to the atmosphere. This capability is required to evaluate the need for initiating protective measures to protect the health and safety of the public.

The operability of the seismic instrumentation ensures that sufficient capability is available to promptly determine the magnitude of a seismic event and evaluate the response of those features important to safety. This capability is required to permit comparison of the measured response to that used in the design basis for Browns Ferry Nuclear Plant. The instrumentation provided is consistent with specific portions of the recommendations of Regulatory Guide 1.12 "Instrumentation for Earthquakes."

The radioactive gaseous effluent instrumentation is provided to monitor and control, as applicable, the releases of radioactive materials in gaseous effluents during actual or potential releases of gaseous effluents. The alarm/trip setpoints for these instruments will be calculated in accordance with guidance provided in the ODCM to ensure that the alarm/trip will occur prior to exceeding the limits of 10 CFR Part 20. This instrumentation also includes provisions for monitoring the concentration of potentially explosive gas mixtures in the offgas holdup system. The operability and use of this instrumentation is consistent with the requirements of General Design Criteria 60, 63, and 64 of Appendix A to 10 CFR Part 50.

The radioactive liquid effluent instrumentation is provided to monitor and control, as applicable, the releases of radioactive materials in liquid effluents during actual or potential releases of liquid effluents. The alarm/trip setpoints for these instruments shall be calculated in accordance with guidance provided in the ODCM to ensure that the alarm/trip will occur prior to exceeding the limits of 10 CFR Part 20 Appendix B, Table II, Column 2. The OPERABILITY and use of this instrumentation is consistent with the requirements of General Design Criteria 60, 63, and 64 of Appendix A to 10 CFR Part 50.

ATWS/RPT, Anticipated Transients without Scram/Recirculation Pump Trip system provides a means of limiting the consequences of the unlikely occurrence of a failure to scram during an ATWS event. The response of the plant to this postulated event (ATWS/RPT) follows the BWR Owners Group Report by General Electric NEDE-31096-P-A and the accompanying NRC Staff Safety Evaluation Report.

ATWS/RPT utilizes the engineered safety feature (ESF) master/slave analog trip units (ATU) which consists of four level and four pressure channels total. The initiating logic consists of two independent trip systems each consisting of two reactor dome high pressure channels and two reactor vessel low level channels. A coincident trip of either two low levels or two high pressures in the same trip system causes initiation of ATWS/RPT. This signal from either trip system opens one of two EOC

3.2 BASES (Cont'd)

(end-of-cycle) breakers in series (the other system opens the other breaker) between the pump motor and the Motor Generator set driving each recirculation pump. Both systems are completely redundant such that only one trip system is necessary to perform the ATWS/RPT function. Power comes from the 250 VDC shutdown boards.

Setpoints for reactor dome high pressure and reactor vessel low level are such that a normal Reactor Protection System scram and accompanying recirculation pump trip would occur before or coincident with the trip by ATWS/RPT.

4.2 BASES

The instrumentation listed in Tables 4.2.A through 4.2.F will be functionally tested and calibrated at regularly scheduled intervals. The same design reliability goal as the Reactor Protection System of 0.99999 generally applies for all applications of (1-out-of-2) X (2) logic. Therefore, on-off sensors are tested once/3 months, and bistable trips associated with analog sensors and amplifiers are tested once/week.



UNITED STATES
NUCLEAR REGULATORY COMMISSION
WASHINGTON, D. C. 20555

ENCLOSURE

SAFETY EVALUATION BY THE OFFICE OF SPECIAL PROJECTS

SUPPORTING AMENDMENT NO. 164 TO FACILITY OPERATING LICENSE NO. DPR-33

AMENDMENT NO. 161 TO FACILITY OPERATING LICENSE NO. DPR-52

AMENDMENT NO. 135 TO FACILITY OPERATING LICENSE NO. DPR-68

TENNESSEE VALLEY AUTHORITY

BROWNS FERRY NUCLEAR PLANT, UNITS 1, 2 AND 3

DOCKETS NOS. 50-259, 50-260 AND 50-296

1.0 INTRODUCTION

10 CFR 50.62 (c)(5) requires in part that each boiling water reactor must have equipment to trip the reactor recirculation pumps automatically under conditions indicative of an anticipated transient without scram (ATWS). The Tennessee Valley Authority (TVA) is installing at Browns Ferry Nuclear Plant (BFN) an ATWS-recirculation pump trip (RPT) to comply with the regulations. The NRC staff evaluation of TVA's ATWS modifications is the subject of a separate safety evaluation report.

By submittal dated August 4, 1988, TVA requested an amendment to the Technical Specifications (TS) for BFN Units 1, 2 and 3 to add limiting conditions for operation (LCO) and surveillance requirements (SR) for the above-mentioned ATWS-RPT system. The proposed addition of these TS provides additional assurance that the ATWS-RPT system will be operable and will perform its intended safety function.

2.0 EVALUATION

The BFN Units 1, 2, and 3 TS are being revised to incorporate requirements for the ATWS-RPT system. The proposed LCO of Section 3.2.L and Table 3.2.L, provide operability requirements for the ATWS-RPT system. The SRs of Section 4.2.L are being added to provide periodic verification of system operability. The appropriate TS Bases sections and indices are being revised to reflect this change.

The ATWS-RPT System is required to be operable during Reactor Power Operation. Reactor Power Operation is defined in the BFN TS as operation with the mode switch in startup or run with the reactor critical and above one percent power. This is more conservative than the operability requirements of the General Electric Standard Technical Specifications (NUREG-0123) which require operability whenever the mode switch is in run only (4-5 percent power).

The ATWS-RPT trip setpoint and allowable value for the low reactor water level are 483 and 471.5 inches above vessel zero, respectively. The trip setpoints for high reactor pressure are 1118 and 1146.5 psig. The existing Reactor Protection System (RPS) trip setpoints are 538 inches above vessel zero for low reactor water level and 1055 psig for reactor dome pressure. The ATWS-RPT setpoints were chosen such that a RPS trip would occur before the ATWS-RPT trip. The proposed setpoints are essentially equivalent to or more conservative than the existing RPT setpoints and are appropriate for the new ATWS-RPT System logic. The existing setpoints are being used in concurrence with the existing RPT-Motor Generator (MG) trip logic. The ATWS-RPT system will replace the existing RPT-MG logic, therefore, the proposed deletion of the old system setpoints is appropriate and acceptable.

The ATWS-RPT trip logic consists of a two-out-of-two low reactor water level signal or a two-out-of-two high reactor dome pressure signal. A coincident trip of either two low-level signals or two high-pressure signals in the same trip channel initiates an ATWS-RPT trip. The minimum number of channels operable per trip system remains at two and is therefore acceptable.

The NRC staff has not yet issued guidance on a generic basis regarding ATWS related TS; however, the proposed SR frequencies for the ATWS-RPT Functional Test, Channel Calibration and Instrument Check are presently acceptable as proposed as they are generally consistent with SR frequencies for other safety related logic circuitry. Upon receipt of the NRC staff's generic guidance, however, TVA may revise these TS to comply with the generic guidance. The remaining proposed changes, including bases changes, page number and indices changes are administrative in nature, do not affect safety, and are therefore found to be acceptable.

3.0 ENVIRONMENTAL CONSIDERATION

The amendments involve a change to a requirement with respect to installation or use of a facility component located within the restricted area as defined in 10 CFR Part 20 and changes to the surveillance requirements. The staff has determined that the amendments involve no significant increase in the amounts, and no significant change in the types, of any effluents that may be released offsite, and that there is no significant increase in individual or cumulative occupational radiation exposure. The Commission has previously issued a proposed finding that these amendments involve no significant hazards consideration and there has been no public comment on such finding. Accordingly, the amendments meet the eligibility criteria for categorical exclusion set forth in 10 CFR 51.22(c)(9). Pursuant to 10 CFR 51.22(b), no environmental impact statement nor environmental assessment need be prepared in connection with the issuance of these amendments.

4.0 CONCLUSION

The Commission made a proposed determination that the amendment involves no significant hazards consideration which was published in the Federal Register (53 FR 48836) on 30 November, 1988 and consulted with the State of Alabama. No public comments were received and the State of Alabama did not have any comments.

The staff has concluded, based on the considerations discussed above, that: (1) there is reasonable assurance that the health and safety of the public will not be endangered by operation in the proposed manner, and (2) such activities will be conducted in compliance with the Commission's regulations, and the issuance of the amendments will not be inimical to the common defense and security nor to the health and safety of the public.

Principal Contributor: T. Rotella

Dated: January 26, 1989