NRC FORM	618
(8-2000)	
10 CFR 71	

# CERTIFICATE OF COMPLIANCE

U.S. NUCLEAR REGULATORY COMMISSION

	FOR RADIOACTIVE MATERIAL PACKAGES							
1.	a. CERTIFICATE NUMBER	b. REVISION NUMBER	c. DOCKET NUMBER	d. PACKAGE IDENTIFICATION NUMBER	PAGE		PAGES	
	9272	6	71-9272	USA/9272/AF-85	1	OF	4	

- 2. PREAMBLE
  - a. This certificate is issued to certify that the package (packaging and contents) described in Item 5 below meets the applicable safety standards set forth in Title 10, Code of Federal Regulations, Part 71, "Packaging and Transportation of Radioactive Material."
  - b. This certificate does not relieve the consignor from compliance with any requirement of the regulations of the U.S. Department of Transportation or other applicable regulatory agencies, including the government of any country through or into which the package will be transported.
- 3. THIS CERTIFICATE IS ISSUED ON THE BASIS OF A SAFETY ANALYSIS REPORT OF THE PACKAGE DESIGN OR APPLICATION
  - a. ISSUED TO (Name and Address)

b. TITLE AND IDENTIFICATION OF REPORT OR APPLICATION

Westinghouse Electric Company LLC P.O. Box 355 Pittsburgh, PA 15230-0355 Westinghouse Electric Company LLC application dated January 4, 2002, as supplemented.

#### 4. CONDITIONS

This certificate is conditional upon fulfilling the requirements of 10 CFR Part 71, as applicable, and the conditions specified below.

5.

## (a) Packaging

- (1) Model No.: CE-B1
- (2) Description

A shipping container for unirradiated fuel assemblies. The package consists of a right rectangular metal inner container and a wooden outer container, with cushioning material between the inner and outer containers.

The metal inner container is approximately 11-1/4 inches by 18-1/8 inches by 182 inches long. There are two channel sections within the inner container, and each channel section holds one BWR fuel assembly. The inner container is equipped with a lid and an end cap that are closed by 18 bolts and fastening lugs. The overall dimensions of the wooden outer container are approximately 33-1/2 inches by 34-3/4 inches by 208-1/2 inches long. The cushioning material between the inner and outer containers is phenolic impregnated honeycomb and ethafoam. The inner container may be positioned on a series of vibration dampers mounted on the inside bottom of the wooden outer container.

The maximum weight of the package, including contents, is 2,964 pounds.

(3) Drawings

The packaging is constructed and assembled in accordance with Combustion Engineering Drawing Nos.:

L-9272-01, Sheets 1 and 2, Rev. 1, and L-9272-02, Rev. 1.

NRC FORM 618 U.S. NUCLEAR REGULATORY COMMISSION							
(8-2000) 10 CFR 71 CERTIFICATE OF COMPLIANCE			ANCE				
FOR RADIOACTIVE MATERIAL PACKAGES							
1. a. CERTIFICATE NUMBER	b. REVISION NUMBER	c. DOCKET NUMBER	d. PACKAGE IDENTIFICATION NUMBER	PAGE		PAGES	
9272	6	71-9272	USA/9272/AF-85	2	OF	4	

#### 5.(b) Contents

#### (1) Type and form of material

The package is designed to hold two unirradiated BWR fuel assemblies, comprised of  $UO_2$  fuel rods in a 10 x 10 square array. The fuel cross-sectional area is 25 square inches. Each assembly is made up of 96 full-length fuel rods having a maximum active fuel length of 150 inches. The fuel pellet diameter is  $0.819 \pm 0.002$  cm, encapsulated in 0.063 cm zirconium alloy cladding. There is a 0.0085 cm gap between the pellets and the cladding. The maximum U-235 enrichment of any fuel rod is 5.0 weight percent. Each assembly contains water holes in the four center rod positions of the assembly. Three different fuel package loadings have the following specifications:

- (i) Maximum average U-235 enrichment is 4.0 weight percent within any axial zone of the assembly; Maximum U-235 content is 3.25 weight percent of any gadolinia-urania rod or axial zone of any gadolinia-urania fuel rod; Maximum number of fuel rods per assembly containing 5.0 weight percent U-235 enriched pellets is 36; Maximum U-235 enrichment is 4.0 weight percent for all edge rods, and 3.5 weight percent for all corner rods; Each assembly must include at least eight fuel rods with a minimum gadolinia content of 2.5 weight percent in all axial regions with enriched pellets. The eight gadolinia rods are arranged with two rods in each quadrant of the fuel assembly. The two gadolinia rods within each quadrant must be symmetric about the geometric diagonal of the fuel assembly, and must not be in an edge or corner rod location. Other fuel rods containing gadolinia may be present.
- (ii) Maximum average U-235 enrichment is 4.725 weight percent within any axial zone of the assembly; Maximum U-235 content is 4.2 weight percent of any gadolinia-urania rod or axial zone of any gadolinia-urania fuel rod; Maximum number of fuel rods per assembly containing 5.0 weight percent U-235 enriched pellets is 52; Maximum U-235 enrichment is 4.5 weight percent for all edge rods, and 4.0 weight percent for all corner rods; Each assembly must include at least eight fuel rods with a minimum gadolinia content of 5.3 weight percent in all axial regions with enriched pellets. The eight gadolinia rods are arranged with two rods in each quadrant of the fuel assembly. The two gadolinia rods within each quadrant must be symmetric about the geometric diagonal of the fuel assembly, and must not be in an edge or corner rod location. Other fuel rods containing gadolinia may be present.

NRC FORM 618 U.S. NUCLEAR REGULATORY COMMISSION						
(8-2000) 10 CFR 71	CERTIFICATE OF COMPLIANCE					
	FOR RADIOACT	IVE MATERIAL PA	CKAGES			
1. a. CERTIFICATE NUMBER	b. REVISION NUMBER	c. DOCKET NUMBER	d. PACKAGE IDENTIFICATION NUMBER	PAGE	PAGES	
9272	6	71-9272	USA/9272/AF-85	3	OF 4	

5.(b)(1) Type and form of material (continued)

(iii) Maximum average U-235 enrichment is 4.858 weight percent within any axial zone of the assembly; Maximum U-235 content is 4.2 weight percent of any gadolinia-urania rod or axial zone of any gadolinia-urania fuel rod; Maximum number of fuel rods per assembly containing 5.0 weight percent U-235 enriched pellets is 80; Maximum U-235 enrichment is 4.0 weight percent for all corner rods; Each assembly must include at least twelve fuel rods with a minimum gadolinia content of 2.43 weight percent in all axial regions with enriched pellets. The twelve gadolinia rods are arranged with three rods in each quadrant of the fuel assembly. The three gadolinia rods within each quadrant must be symmetric about the geometric diagonal of the fuel assembly, and must not be in an edge or corner rod location. Other fuel rods containing gadolinia may be present.

1.0

5.(b) (2) Maximum quantity of material per package

Two fuel assemblies. The total weight of contents not to exceed 1,184 pounds.

(c) Transport Index for Criticality Control (Criticality Safety Index)

Minimum transport index to be shown on label for nuclear criticality control:

- 6. Each fuel assembly must be unsheathed or must be enclosed in an unsealed, polyethylene sheath which may not extend beyond the ends of the fuel assembly. The ends of the sheath may not be folded or taped in any manner that would prevent the flow of liquids into, or out of, the sheathed fuel assembly.
- 7. Polyethylene inserts may be positioned between rods within the fuel assemblies. The quantity of polyethylene must not exceed 18.33 g polyethylene per centimeter length of the fuel assembly, and must not exceed a total of 6.99 kg per fuel assembly. The polyethylene may be borated.
- 8. In addition to the requirements of Subpart G of 10 CFR Part 71:
  - (a) The package must be prepared for shipment and operated in accordance with the Operating Procedures in Chapter 7 of the application.
  - (b) Each packaging must be acceptance tested and maintained in accordance with the Acceptance Tests and Maintenance Program in Chapter 8 of the application.
- 9. Only ABB/Combustion Engineering packagings with Serial Nos. CE-B1/001 through CE-B1/039, inclusive, are authorized for use.
- 10. The package authorized by this certificate is hereby approved for use under the general license provisions of 10 CFR 71.12.
- 11. Expiration date: January 31, 2007.

NRC FORM 618 (8-2000) 10 CFR 71

## **CERTIFICATE OF COMPLIANCE**

U.S. NUCLEAR REGULATORY COMMISSION

#### FOR RADIOACTIVE MATERIAL PACKAGES b. REVISION NUMBER d. PACKAGE IDENTIFICATION NUMBER PAGE a. CERTIFICATE NUMBER c. DOCKET NUMBER PAGES USA/9272/AF-85 OF 9272 71-9272 4 6 4

## REFERENCES

Westinghouse Electric Company LLC application dated January 4, 2002.

Supplement dated: January 9, 2002.



Date January 25, 2002