

## INDEX

### LIMITING CONDITIONS FOR OPERATION AND SURVEILLANCE REQUIREMENTS

<u>SECTION</u>		<u>PAGE</u>
3/4.4.2	SAFETY VALVES . . . . .	3/4 4-2
3/4.4.3	RELIEF VALVES . . . . .	3/4 4-3
3/4.4.4	PRESSURIZER . . . . .	3/4 4-4
3/4.4.5	STEAM GENERATORS . . . . .	3/4 4-5
3/4.4.6	REACTOR COOLANT SYSTEM LEAKAGE . . . . .	3/4 4-8
	Leakage Detection Systems . . . . .	3/4 4-8
	Reactor Coolant System Leakage . . . . .	3/4 4-9
3/4.4.7	CHEMISTRY . . . . .	3/4 4-10
3/4.4.8	SPECIFIC ACTIVITY . . . . .	3/4 4-13
3/4.4.9	PRESSURE/TEMPERATURE LIMITS . . . . .	3/4 4-17
	Reactor Coolant System . . . . .	3/4 4-17
	Pressurizer . . . . .	3/4 4-21
	Overpressure Protection Systems . . . . .	3/4 4-21a
3/4.4.10	DELETED . . . . .	3/4 4-22
3/4.4.11	REACTOR COOLANT SYSTEM VENTS . . . . .	3/4 4-23
 <u>3/4.5 EMERGENCY CORE COOLING SYSTEMS (ECCS)</u>		
3/4.5.1	SAFETY INJECTION TANKS . . . . .	3/4 5-1
3/4.5.2	ECCS SUBSYSTEMS - $T_{avg} \geq 300^{\circ}\text{F}$ . . . . .	3/4 5-3
3/4.5.3	ECCS SUBSYSTEMS - $T_{avg} < 300^{\circ}\text{F}$ . . . . .	3/4 5-7
3/4 5.4	REFUELING WATER STORAGE TANK . . . . .	3/4 5-8
3/4 5.5	TRISODIUM PHOSPHATE (TSP) . . . . .	3/4 5-9

## INDEX

### BASES

---

<u>SECTION</u>	<u>PAGE</u>
<u>3/4.4 REACTOR COOLANT SYSTEM</u>	
3/4.4.1 COOLANT LOOPS AND COOLANT CIRCULATION . . . . .	B 3/4 4-1
3/4.4.2 SAFETY VALVES . . . . .	B 3/4 4-1
3/4.4.3 RELIEF VALVES . . . . .	B 3/4 4-2
3/4.4.4 PRESSURIZER . . . . .	B 3/4 4-2a
3/4.4.5 STEAM GENERATORS . . . . .	B 3/4 4-2a
3/4.4.6 REACTOR COOLANT SYSTEM LEAKAGE . . . . .	B 3/4 4-3
3/4.4.7 CHEMISTRY . . . . .	B 3/4 4-4
3/4.4.8 SPECIFIC ACTIVITY . . . . .	B 3/4 4-4
3/4.4.9 PRESSURE/TEMPERATURE LIMITS . . . . .	B 3/4 4-5
3/4.4.10 DELETED . . . . .	B 3/4 4-7
3/4.4.11 REACTOR COOLANT SYSTEM VENTS . . . . .	B 3/4 4-8
 <u>3/4.5 EMERGENCY CORE COOLING SYSTEMS (ECCS)</u>	
3/4.5.1 SAFETY INJECTION TANKS . . . . .	B 3/4 5-1
3/4.5.2 and 3/4.5.3 ECCS SUBSYSTEMS . . . . .	B 3/4 5-1
3/4.5.4 REFUELING WATER STORAGE TANK (RWST) . . . . .	B 3/4 5-2
3/4.5.5 TRISODIUM PHOSPHATE (TSP) . . . . .	B 3/4 5-3
 <u>3/4.6 CONTAINMENT SYSTEMS</u>	
3/4.6.1 PRIMARY CONTAINMENT . . . . .	B 3/4 6-1
3/4.6.2 DEPRESSURIZATION AND COOLING SYSTEMS . . . . .	B 3/4 6-3
3/4.6.3 CONTAINMENT ISOLATION VALVES . . . . .	B 3/4 6-3
3/4.6.4 COMBUSTIBLE GAS CONTROL . . . . .	B 3/4 6-4
3/4.6.5 SECONDARY CONTAINMENT . . . . .	B 3/4 6-5

## INDEX

### ADMINISTRATIVE CONTROLS

<u>SECTION</u>	<u>PAGE</u>
<u>6.9 REPORTING REQUIREMENTS</u>	
6.9.1 ROUTINE REPORTS . . . . .	6-16
STARTUP REPORTS . . . . .	6-16
ANNUAL REPORTS . . . . .	6-17
ANNUAL RADIOLOGICAL REPORTS . . . . .	6-18
MONTHLY OPERATING REPORT . . . . .	6-18
CORE OPERATING LIMITS REPORT . . . . .	6-18
6.9.2 SPECIAL REPORTS . . . . .	6-19
<u>6.10 DELETED</u>	
<u>6.11 RADIATION PROTECTION PROGRAM</u> . . . . .	6-22
<u>6.12 HIGH RADIATION AREA</u> . . . . .	6-22
<u>6.13 SYSTEMS INTEGRITY</u> . . . . .	6-23
<u>6.14 IODINE MONITORING</u> . . . . .	6-23
<u>6.15 RADIOLOGICAL EFFLUENT MONITORING AND OFFSITE DOSE</u> <u>CALCULATION MANUAL (REMODCM)</u> . . . . .	6-24
<u>6.16 RADIOACTIVE WASTE TREATMENT</u> . . . . .	6-24
<u>6.17 SECONDARY WATER CHEMISTRY</u> . . . . .	6-25
<u>6.18 PASS/SAMPLING AND ANALYSIS OF PLANT EFFLUENTS</u> . . . . .	6-25
<u>6.19 CONTAINMENT LEAKAGE RATE TESTING PROGRAM</u> . . . . .	6-26
<u>6.20 RADIOACTIVE EFFLUENT CONTROLS PROGRAM</u> . . . . .	6-26
<u>6.21 RADIOLOGICAL ENVIRONMENTAL MONITORING PROGRAM</u> . . . . .	6-27
<u>6.22 REACTOR COOLANT PUMP FLYWHEEL INSPECTION PROGRAM</u> . . . . .	6-28

This page intentionally left blank

## **ADMINISTRATIVE CONTROLS**

---

- b. A Land Use Census to ensure that changes in the use of areas at and beyond the SITE BOUNDARY are identified and that modifications to the monitoring program are made if required by the results of this census, and
- c. Participation in a Interlaboratory Comparison Program to ensure that independent checks on the precision and accuracy of the measurements of radioactive materials in environmental sample matrices are performed as part of the quality assurance program for environmental monitoring.

### **6.22 Reactor Coolant Pump Flywheel Inspection Report**

This program shall provide for the inspection of each reactor coolant pump flywheel by either qualified in-place UT examination over the volume from the inner bore of the flywheel to the circle of one-half the outer radius, or a surface examination (magnetic particle testing and/or penetrant testing) of exposed surfaces defined by the volume of the disassembled flywheels at least once every 10 years.

## REACTOR COOLANT SYSTEM

### BASES

---

These methods prevent inadvertent pump injections while allowing manual actions to rapidly restore the makeup capability if conditions require the use of additional charging or HPSI pumps for makeup in the event of a loss of RCS inventory or reduction in shutdown margin.

If a loss of RCS inventory or reduction in shutdown margin event occurs, the appropriate response will be to correct the situation by starting RCS makeup pumps. If the loss of inventory or shutdown margin is significant, this may necessitate the use of additional RCS makeup pumps that are being maintained not capable of injecting into the RCS in accordance with Technical Specification 3.4.9.3. The use of these additional pumps to restore RCS inventory or shutdown margin will require entry into the associated action statement. The action statement requires immediate action to comply with the specification. The restoration of RCS inventory or shutdown margin can be considered to be part of the immediate action to restore the additional RCS makeup pumps to a not capable of injecting status. While recovering RCS inventory or shutdown margin, RCS pressure will be maintained below the Appendix G limits. After RCS inventory or shutdown margin has been restored, the additional pumps should be immediately made not capable of injecting and the action statement exited.

An exception to Technical Specification 3.0.4 is specified for Technical Specification 3.4.9.3 to allow a plant cooldown to MODE 5 if one or both PORVs are inoperable. MODE 5 conditions may be necessary to repair the PORV(s).

3/4.4.10 DELETED