Docket Nos. 50-315 and 50-316

> Mr. Milton P. Alexich, Vice President Indiana Michigan Power Company c/o American Electric Power Service Corporation 1 Riverside Plaza Columbus, Ohio 43216

DISTRIBUTION Docket File DHagan EJordan NRC PDR **BGrimes** Local PDR OGC TMeeks (8) ARM/LFMB Wanda Jones **EButcher JGitter PShuttleworth** GPA/PA ACRS (10) MVirgilio | PD31 Plant File

Dear Mr. Alexich:

SUBJECT: ERRATA FOR AMENDMENTS NOS. 127 AND 113 TO FACILITY OPERATING LICENSES NOS. DPR-58 AND DPR-74 - (TACS NOS. 67786 AND 67787)

The changes to the Technical Specifications (TS) implemented by License Amendments Nos. 127 and 113 were transmitted to you by letter dated July 5, 1989. Table 3.3-8 "Meteorological Monitoring Instrumentation" contained errors in the text which affects both units.

The enclosed errata to the TS changes implemented by License Amendments Nos. 127 and 113 are hereby transmitted and should replace the pages previously transmitted.

Sincerely,

15/

Joseph Giitter, Project Manager Project Directorate III-1 Division of Reactor Projects - III, IV, V & Special Projects Office of Nuclear Reactor Regulation

Enclosure: As stated

cc w/enclosure: See next page

[COOK ERRATA FOR 127 AND 113]

LA:PD31:DRSP Pshuttleworth 8/3/89 www. PM:PD31:DRSP JGilter jw 8/3/89 (A)D:PD3::DRSP Lyandel1 8/3/89

DF01

8908160403 890803 PDR ADBCK 05000315 PNU A.J.



UNITED STATES NUCLEAR REGULATORY COMMISSION

WASHINGTON, D. C. 20555

August 3, 1989

Docket Nos. 50-315 and 50-316

> Mr. Milton P. Alexich, Vice President Indiana Michigan Power Company c/o American Electric Power Service Corporation 1 Riverside Plaza Columbus, Ohio 43216

Dear Mr. Alexich:

SUBJECT: ERRATA FOR AMENDMENTS NOS. 127 AND 113 TO FACILITY OPERATING LICENSES NOS. DPR-58 AND DPR-74 - (TACS NOS. 67786 AND 67787)

The changes to the Technical Specifications (TS) implemented by License Amendments Nos. 127 and 113 were transmitted to you by letter dated July 5, 1989. Table 3.3-8 "Meteorological Monitoring Instrumentation" contained errors in the text which affects both units.

The enclosed errata to the TS changes implemented by License Amendments Nos. 127 and 113 are hereby transmitted and should replace the pages previously transmitted.

Sincerely,

Joseph Y. Futter

Joseph Giitter, Project Manager
Project Directorate III-1
Division of Reactor Projects - III, IV, V
& Special Projects
Office of Nuclear Reactor Regulation

Enclosure: As stated

cc w/enclosure:
See next page

Mr. Milton Alexich Indiana Michigan Power Company Donald C. Cook Nuclear Plant

cc: Regional Administrator, Region III U.S. Nuclear Regulatory Commission 799 Roosevelt Road Glen Ellyn, Illinois 60137

Mr. S. Brewer
American Electric Power
Service Corporation
1 Riverside Plaza
Columbus, Ohio 43216

Attorney General Department of Attorney General 525 West Ottawa Street Lansing, Michigan 48913

Township Supervisor Lake Township Hall Post Office Box 818 Bridgeman, Michigan 49106

W. G. Smith, Jr., Plant Manager Donald C. Cook Nuclear Plant Post Office Box 458 Bridgman, Michigan 49106

U.S. Nuclear Regulatory Commission Resident Inspectors Office 7700 Red Arrow Highway Stevensville, Michigan 49127

Gerald Charnoff, Esquire Shaw, Pittman, Potts and Trowbridge 2300 N Street, N.W. Washington, DC 20037

Mayor, City of Bridgeman Post Office Box 366 Bridgeman, Michigan 49106

Special Assistant to the Governor Room 1 - State Capitol Lansing, Michigan 48909

Nuclear Facilities and Environmental Monitoring Section Office Division of Radiological Health Department of Public Health 3500 N. Logan Street Post Office Box 30035 Lansing, Michigan 48909

ERRATA**

ATTACHMENT TO LICENSE AMENDMENT NO. 127

TO FACILITY OPERATING LICENSE NO. DPR-58

DOCKET NO. 50-315

Revise Appendix A Technical Specifications by removing the pages identified below and inserting the attached pages. The revised pages are identified by amendment number and contain marginal lines indicating the area of change.

REMOVE	UNIT 1	INSERT
3/4 3-43		3/4 3-43*
3/4 3-44		3/4 3-44**
3/4 3-45	•	3/4 3-45
3/4 3-46		3/4 3-46*
B 3/4 3-2	•	B 3/4 3-2
5-9		5-9

^{*} Overleaf page provided to maintain document completeness. No change contained on this page.

TABLE 3.3-8

METEOROLOGICAL MONITORING INSTRUMENTATION

		INSTRUMENT MINIMUM ACCURACY	MINIMUM OPERABLE
TMC	TRUMENT LOCATION		
1113			Any 1/3 channels
1.	WIND SPEED a. Primary or Backup Meteorological Tower, Nominal Elev. 10 m	(1),(2)	
	b. Primary Meteorological Tower, Nominal Elev. 60 m	(1),(2)	
			Any 1/3
2.	WIND DIRECTION	.0	channels
	a. Primary or Backup Meteorological Tower, Nominal Elev. 10 m	<u>+</u> 5°	
	b. Primary Meteorological Tower, Nominal Elev. 60 m	<u>+</u> 5°	
			NA ⁽³⁾
,	AIR TEMPERATURE (for 60 m to 10 m delta T)		
3.		± 0.15°	С
	a. Primary Meteorological Tower, Nominal Elev. 10 m	<u>+</u> 0.15°	
	b. Primary Meteorological Tower, Nominal Elev. 60 m	± 0.13	

⁽¹⁾ Starting speed of anemometer shall be ≤ 1 mph.

⁽²⁾ \pm 1% or 0.5 mph, whichever is greater. (3) With delta T information unavailable, sigma theta (standard deviation of the horizontal wind direction as determined from emergency procedures) is to be used for the determination of stability class.

ERRATA*

ATTACHMENT TO LICENSE AMENDMENT NO. 113

TO FACILITY OPERATING LICENSE NO. DPR-74

DOCKET NO. 50-316

Revise Appendix A Technical Specifications by removing the pages identified below and inserting the attached pages. The revised pages are identified by amendment number and contain marginal lines indicating the area of change.

REMOVE	INSERT
	UNIT 2
3/4 3-40	3/4 3-40* 3/4 3-41
3/4 3-41 B 3/4 3-2	B 3/4 3-2 B 3/4 3-2 B 3/4 3-2a
5-0	5-9

TABLE 3.3-8

METEOROLOGICAL MONITORING INSTRUMENTATION

INS	TRUMENT LOCATION	INSTRUMEN MINIMUM ACCURACY	T MINIMUM OPERABLE
1.	WIND SPEED		Any 1/3 channels
	a. Primary or Backup Meteorological Tower, Nominal Elev. 10 m	(1),(2)	
	b. Primary Meteorological Tower, Nominal Elev. 60 m	(1),(2)	
2.	WIND DIRECTION		Any 1/3 channels
	a. Primary or Backup Meteorological Tower, Nominal Elev. 10 m	± 5°	
	b. Primary Meteorological Tower, Nominal Elev. 60 m	<u>+</u> 5°	
3.	AIR TEMPERATURE (for 60 m to 10 m delta T)		NA ⁽³⁾
	a. Primary Meteorological Tower, Nominal Elev. 10 m	± 0.15°0	
	b. Primary Meteorological Tower, Nominal Elev. 60 m	± 0.15°C	3

⁽¹⁾ Starting speed of anemometer shall be ≤ 1 mph.

⁽²⁾ \pm 1% or 0.5 mph, whichever is greater. (3) With delta T information unavailable, sigma theta (standard deviation of the horizontal wind direction as determined from emergency procedures) is to be used for the determination of stability class.