

**INDEX  
DEFINITIONS**

---

<u>SECTION</u>	<u>PAGE</u>
<u>3/4.9 REFUELING OPERATIONS (Continued)</u>	
3/4.9.6 DELETED .....	3/4 9-6
3/4.9.7 DELETED .....	3/4 9-8
3/4.9.8 RESIDUAL HEAT REMOVAL AND COOLANT CIRCULATION .....	3/4 9-9
3/4.9.9 CONTAINMENT PURGE AND EXHAUST ISOLATION SYSTEM .....	3/4 9-10
3/4.9.10 WATER LEVEL - REACTOR VESSEL .....	3/4 9-11
3/4.9.11 STORAGE POOL WATER LEVEL .....	3/4 9-12
3/4.9.12 STORAGE POOL VENTILATION SYSTEM .....	3/4 9-13
3/4.9.13 SPENT FUEL CASK MOVEMENT .....	3/4 9-17
3/4.9.14 SPENT FUEL CASK DROP PROTECTION SYSTEM .....	3/4 9-18
3/4.9.15 STORAGE POOL BORON CONCENTRATION .....	3/4 9-19
 <u>3/4.10 SPECIAL TEST EXCEPTIONS</u>	
3/4.10.1 SHUTDOWN MARGIN .....	3/4 10-1
3/4.10.2 GROUP HEIGHT, INSERTION AND POWER DISTRIBUTION LIMITS .....	3/4 10-2
3/4.10.3 PRESSURE/TEMPERATURE LIMITATION-REACTOR CRITICALITY .....	3/4 10-3
3/4.10.4 PHYSICS TESTS .....	3/4 10-5
3/4.10.5 NATURAL CIRCULATION TESTS .....	3/4 10-6
 <u>3/4.11 RADIOACTIVE EFFLUENTS</u>	
3/4.11.1 LIQUID HOLDUP TANKS .....	3/4 11-1
3/4.11.2 GASEOUS EFFLUENTS	
Explosive Gas Mixture .....	3/4 11-2
Gas Storage Tanks .....	3/4 11-3

**INDEX  
DEFINITIONS**

---

<u>SECTION</u>	<u>PAGE</u>
<u>3/4.7 PLANT SYSTEMS (Continued)</u>	
3/4.7.8 HYDRAULIC SNUBBERS.....	B 3/4 7-5a
<u>3/4.8 ELECTRICAL POWER SYSTEMS</u> .....	B 3/4 8-1
<u>3/4.9 REFUELING OPERATIONS</u>	
3/4.9.1 BORON CONCENTRATION.....	B 3/4 9-1
3/4.9.2 INSTRUMENTATION .....	B 3/4 9-1
3/4.9.3 DECAY TIME .....	B 3/4 9-1
3/4.9.4 CONTAINMENT BUILDING PENETRATIONS .....	B 3/4 9-1
3/4.9.5 COMMUNICATIONS.....	B 3/4 9-1
3/4.9.6 DELETED .....	B 3/4 9-2
3/4.9.7 DELETED .....	B 3/4 9-2
3/4.9.8 RESIDUAL HEAT REMOVAL AND COOLANT CIRCULATION.....	B 3/4 9-2
3/4.9.9 CONTAINMENT PURGE AND EXHAUST ISOLATION SYSTEM .....	B 3/4 9-2
3/4.9.10 and 3/4.9.11 WATER LEVEL - REACTOR VESSEL AND STORAGE POOL .....	B 3/4 9-3
3/4.9.12 STORAGE POOL VENTILATION SYSTEM .....	B 3/4 9-3
3/4.9.13 SPENT FUEL CASK MOVEMENT .....	B 3/4 9-4
3/4.9.14 SPENT FUEL CASK DROP PROTECTION SYSTEM.....	B 3/4 9-4
3/4.9.15 STORAGE POOL BORON CONCENTRATION .....	B 3/4 9-4
<u>3/4.10 SPECIAL TEST EXCEPTIONS</u>	
3/4.10.1 SHUTDOWN MARGIN.....	B 3/4 10-1
3/4.10.2 GROUP HEIGHT, INSERTION AND POWER DISTRIBUTION LIMITS .....	B 3/4 10-1

3/4 LIMITING CONDITIONS FOR OPERATION AND SURVEILLANCE REQUIREMENTS  
3/4.9 REFUELING OPERATIONS

---

3.9.6 DELETED

THIS PAGE INTENTIONALLY BLANK

3/4 LIMITING CONDITIONS FOR OPERATION AND SURVEILLANCE REQUIREMENTS  
3/4.9 REFUELING OPERATIONS

---

3.9.7 DELETED

3/4 BASES  
3/4.9 REFUELING OPERATIONS

---

3/4.9.6 DELETED

3/4.9.7 DELETED

3/4.9.8 RESIDUAL HEAT REMOVAL AND COOLANT CIRCULATION

The requirement that at least one residual heat removal (RHR) loop be in operation ensures that (1) sufficient cooling capacity is available to remove decay heat and maintain the water in the reactor pressure vessel below 140°F as required during the REFUELING MODE, and (2) sufficient coolant circulation is maintained through the reactor core to minimize the effect of a boron dilution incident and prevent boron stratification.

The requirement to have two RHR loops OPERABLE when there is less than 23 feet of water above the reactor pressure vessel flange ensures that a single failure of the operating RHR loop will not result in a complete loss of residual heat removal capability. With the reactor vessel head removed and 23 feet of water above the reactor pressure vessel flange, a large heat sink is available for core cooling. Thus, in the event of a failure of the operating RHR loop, adequate time is provided to initiate emergency procedures to cool the core.

3/4.9.9 CONTAINMENT PURGE AND EXHAUST ISOLATION SYSTEM

The OPERABILITY of this system ensures that the containment vent and purge penetrations will be automatically isolated upon detection of high radiation levels within the containment. The OPERABILITY of this system is required to restrict the release of radioactive material from the containment atmosphere to the environment.

**INDEX**  
**LIMITING CONDITIONS FOR OPERATION AND SURVEILLANCE REQUIREMENTS**

---

<u>SECTION</u>	<u>PAGE</u>
<u>23/4.9 REFUELING OPERATIONS (Continued)</u>	
3/4.9.6 DELETED .....	3/4 9-6
3/4.9.7 DELETED .....	3/4 9-7
3/4.9.8 RESIDUAL HEAT REMOVAL AND COOLANT CIRCULATION .....	3/4 9-8
3/4.9.9 CONTAINMENT PURGE AND EXHAUST ISOLATION SYSTEM .....	3/4 9-9
3/4.9.10 WATER LEVEL-REACTOR VESSEL .....	3/4 9-10
3/4.9.11 STORAGE POOL WATER LEVEL .....	3/4 9-11
3/4.9.12 STORAGE POOL VENTILATION SYSTEM .....	3/4 9-12
3/4.9.13 SPENT FUEL CASK MOVEMENT .....	3/4 9-16
3/4.9.14 SPENT FUEL CASK DROP PROTECTION SYSTEM .....	3/4 9-17
3/4.9.15 STORAGE POOL BORON CONCENTRATION .....	3/4 9-18
<u>3/4.10 SPECIAL TEST EXCEPTIONS</u>	
3/4.10.1 SHUTDOWN MARGIN .....	3/4 10-1
3/4.10.2 GROUP HEIGHT, INSERTION AND POWER DISTRIBUTION LIMITS .....	3/4 10-2
3/4.10.3 PHYSICS TESTS .....	3/4 10-3
3/4.10.4 REACTOR COOLANT LOOPS .....	3/4 10-4
3/4.10.5 POSITION INDICATOR CHANNELS - SHUTDOWN .....	3/4 10-5
<u>3/4.11 RADIOACTIVE EFFLUENTS</u>	
3/4.11.1 LIQUID HOLDUP TANKS .....	3/4 11-1
3/4.11.2 GASEOUS EFFLUENTS	
Explosive Gas Mixture .....	3/4 11-2
Gas Storage Tanks .....	3/4 11-3

**INDEX**  
**LIMITING CONDITIONS FOR OPERATION AND SURVEILLANCE REQUIREMENTS**

---

<u>SECTION</u>	<u>PAGE</u>
<u>3/4.7 PLANT SYSTEMS (Continued)</u>	
3/4.7.8 SEALED SOURCE CONTAMINATION.....	B 3/4 7-6
<u>3/4.8 ELECTRICAL POWER SYSTEMS</u> .....	B 3/4 8-1
<u>3/4.9 REFUELING OPERATIONS</u>	
3/4.9.1 BORON CONCENTRATION.....	B 3/4 9-1
3/4.9.2 INSTRUMENTATION .....	B 3/4 9-1
3/4.9.3 DECAY TIME.....	B 3/4 9-1
3/4.9.4 CONTAINMENT BUILDING PENETRATIONS.....	B 3/4 9-1
3/4.9.5 COMMUNICATIONS.....	B 3/4 9-1
3/4.9.6 DELETED .....	B 3/4 9-2
3/4.9.7 DELETED .....	B 3/4 9-2
3/4.9.8 RESIDUAL HEAT REMOVAL AND COOLANT CIRCULATION .....	B 3/4 9-2
3/4.9.9 CONTAINMENT PURGE AND EXHAUST ISOLATION SYSTEM .....	B 3/4 9-3
3/4.9.10 and 3/4 9.11 WATER LEVEL - REACTOR VESSEL AND STORAGE POOL .....	B 3/4 9-3
3/4.9.12 STORAGE POOL VENTILATION SYSTEM .....	B 3/4 9-3
3/4.9.13 SPENT FUEL CASK MOVEMENT.....	B 3/4 9-4
3/4.9.14 SPENT FUEL CASK DROP PROTECTION SYSTEM.....	B 3/4 9-4
3/4.9.15 STORAGE POOL BORON CONCENTRATION .....	B 3/4 9-4
<u>3/4.10 SPECIAL TEST EXCEPTIONS</u>	
3/4.10.1 SHUTDOWN MARGIN.....	B 3/4 10-1
3/4.10.2 GROUP HEIGHT, INSERTION AND POWER DISTRIBUTION LIMITS.....	B 3/4 10-1

**3/4 LIMITING CONDITIONS FOR OPERATION AND SURVEILLANCE REQUIREMENTS**  
**3/4.9 REFUELING OPERATIONS**

---

3.9.6 DELETED

3/4 LIMITING CONDITIONS FOR OPERATION AND SURVEILLANCE REQUIREMENTS  
3/4.9 REFUELING OPERATIONS

---

3.9.7 DELETED

3/4 BASES  
3/4.9 REFUELING OPERATIONS

---

3/4.9.6 DELETED

3/4.9.7 DELETED

3/4.9.8 RESIDUAL HEAT REMOVAL AND COOLANT CIRCULATION

The requirement that at least one residual heat removal (RHR) loop be in operation ensures that (1) sufficient cooling capacity is available to remove decay heat and maintain the water in the reactor pressure vessel below 140°F as required during the REFUELING MODE, and (2) sufficient coolant circulation is maintained through the reactor core to minimize the effect of a boron dilution incident and prevent boron stratification.

The requirement to have two RHR loops OPERABLE when there is less than 23 feet of water above the reactor pressure vessel flange ensures that a single failure of the operating RHR loop will not result in a complete loss of residual heat removal capability. With the reactor vessel head removed and 23 feet of water above the reactor pressure vessel flange, a large heat sink is available for core cooling. Thus, in the event of a failure of the operating RHR loop, adequate time is provided to initiate emergency procedures to cool the core.