

5.5 Procedures, Programs, and Manuals (continued)

---

5.5.2.11 Steam Generator (SG) Tube Surveillance Program (continued)

5.5.2.11.1 The inservice inspection may be limited to one SG on a rotating schedule encompassing 6% of the tubes if the results of the first or previous inspections indicate that all SGs are performing in a like manner. Note that under some circumstances, the operating conditions in one SG may be found to be more severe than those in the other SG. Under such circumstances the sample sequence shall be modified to inspect the most severe conditions.

5.5.2.11.2 The other SG not inspected during the first inservice inspection shall be inspected. The third and subsequent inspections should follow the instructions described in Specification 5.5.2.11.1 above.

5.5.2.12 Ventilation Filter Testing Program (VFTP)

This Program establishes the required testing of the Engineered Safety Feature filter ventilation systems, "Control Room Emergency Air Cleanup System" and "Fuel Handling Building Post-accident Cleanup Filter System." The frequency of testing shall be in accordance with Regulatory Guide 1.52, Revision 2. As a minimum the VFTP program shall include the following:

- a. Inplace testing of the high efficiency particulate air (HEPA) filters to demonstrate acceptable penetration and system bypass when tested at the appropriate system flowrate in accordance with Regulatory Guide 1.52, Revision 2, and ANSI N510-1975 (see Note 1); and
- b. Inplace testing of the charcoal adsorber to demonstrate acceptable penetration and system bypass when tested at the appropriate system flowrate in accordance with Regulatory Guide 1.52, Revision 2, and ANSI N510-1975 (see Note 1); and
- c. Laboratory testing of charcoal adsorber samples obtained in accordance with Regulatory Guide 1.52, Revision 2 and tested per the methodology of ASTM D3803-1989 at 30°C and 70% relative humidity to show acceptable methyl iodide penetration; and
- d. Testing to demonstrate the pressure drop across the combined HEPA filters, the prefilters, and the charcoal adsorbers, when tested at the appropriate system flowrate.

Note 1: Sample and injection points shall be qualified per ANSI N510-1975 unless manifolds have been qualified per ASME N510-1989. HEPA testing will be conducted with DOP aerosol or suitable alternate.

(continued)

---

5.5 Procedures, Programs, and Manuals (continued)

---

5.5.2.11 Steam Generator (SG) Tube Surveillance Program (continued)

5.5.2.11.1 The inservice inspection may be limited to one SG on a rotating schedule encompassing 6% of the tubes if the results of the first or previous inspections indicate that all SGs are performing in a like manner. Note that under some circumstances, the operating conditions in one SG may be found to be more severe than those in the other SG. Under such circumstances the sample sequence shall be modified to inspect the most severe conditions.

5.5.2.11.2 The other SG not inspected during the first inservice inspection shall be inspected. The third and subsequent inspections should follow the instructions described in Specification 5.5.2.11.1 above.

5.5.2.12 Ventilation Filter Testing Program (VFTP)

This Program establishes the required testing of the Engineered Safety Feature filter ventilation systems, "Control Room Emergency Air Cleanup System" and "Fuel Handling Building Post-accident Cleanup Filter System." The frequency of testing shall be in accordance with Regulatory Guide 1.52, Revision 2. As a minimum the VFTP program shall include the following:

- a. Inplace testing of the high efficiency particulate air (HEPA) filters to demonstrate acceptable penetration and system bypass when tested at the appropriate system flowrate in accordance with Regulatory Guide 1.52, Revision 2, and ANSI N510-1975 (see Note 1); and
- b. Inplace testing of the charcoal adsorber to demonstrate acceptable penetration and system bypass when tested at the appropriate system flowrate in accordance with Regulatory Guide 1.52, Revision 2, and ANSI N510-1975 (see Note 1); and
- c. Laboratory testing of charcoal adsorber samples obtained in accordance with Regulatory Guide 1.52, Revision 2 and tested per the methodology of ASTM D3803-1989 at 30°C and 70% relative humidity to show acceptable methyl iodide penetration; and
- d. Testing to demonstrate the pressure drop across the combined HEPA filters, the prefilters, and the charcoal adsorbers, when tested at the appropriate system flowrate.

Note 1: Sample and injection points shall be qualified per ANSI N510-1975 unless manifolds have been qualified per ASME N510-1989. HEPA testing will be conducted with DOP aerosol or suitable alternate.

(continued)

---