## CONTAINMENT SYSTEMS

# DRYWELL AVERAGE AIR TEMPERATURE

# LIMITING CONDITION FOR OPERATION

3.6.1.7 Drywell average air temperature shall not exceed 145°F.

APPLICABILITY: OPERATIONAL CONDITIONS 1, 2, and 3.

ACTION:

With the drywell average air temperature greater than 145°F, reduce the average air temperature to within the limit within 8 hours or be in at least HOT SHUTDOWN within the next 12 hours and in COLD SHUTDOWN within the following 24 hours.

#### SURVEILLANCE REQUIREMENTS

4.6.1.7 The drywell average air temperature shall be the volumetric average of the temperatures at the following locations and shall be determined to be within the limit at least once per 24 hours:

	Approximate <u>Elevation</u>	Number of <u>Installed Sensors</u> *
a.	330'	3
b.	320'	3
c.	260'	3
d.	248'	6

LIMERICK - UNIT 1

3/4 6-10

I

1

<sup>\*</sup> At least one reading from each elevation is required for a volumetric average calculation.

#### CONTAINMENT SYSTEMS

## DRYWELL AVERAGE AIR TEMPERATURE

## LIMITING CONDITION FOR OPERATION

3.6.1.7 Drywell average air temperature shall not exceed 145°F.

APPLICABILITY: OPERATIONAL CONDITIONS 1, 2, and 3.

## ACTION:

•

With the drywell average air temperature greater than 145°F, reduce the average air temperature to within the limit within 8 hours or be in at least HOT SHUTDOWN within the next 12 hours and in COLD SHUTDOWN within the following 24 hours.

## SURVEILLANCE REQUIREMENTS

4.6.1.7 The drywell average air temperature shall be the volumetric average of the temperatures at the following locations and shall be determined to be within the limit at least once per 24 hours:

	Approximate <u>Elevation</u>	Number of <u>Installed Sensors</u> *
a.	330'	3
b.	320'	3
c.	260'	3
d.	248'	6

\*At least one reading from each elevation is required for a volumetric average calculation.

LIMERICK - UNIT 2