TECHNOLOGY

 (\cdot)

Fuel Handling & Storage System (FHSS) PBMR

Hans-Wolfgang Chi MHTGR Brayton Cycle Technology Course September 10-14, 2001

Objectives

- Introduce Unique Features of the Pebble Bed Reactor
- Describe PBMR FHSS Requirements and the Resulting Design
- Elaborate PBMR FHSS Operating Modes
- Assess Experience Base for PBMR FHSS

D-34


Outline


- Pebble Bed Reactors
- Pebble Flow Pattern in the Core
- Pebble Bed FHSS requirements
- PBMR FHSS Description
- PBMR FHSS Operating Modes
- General FHSS Characteristics
- Pebble Bed FHSS Experience Base
- Are There Any Technology Risks?
- Discussion

Constantiation of the


Pebble Bed Gas-Cooled Reactors

- Arbeitsgemeinschaft Versuchs Reaktor (AVR), Juelich, Germany (1968 – 1988)
- Thorium Hoch-Temperatur Reaktor (THTR), Schmehausen, Germany (1985 -1988)
- High Temperature Reactor (HTR-10), Beijing, China (2000 -)





THTR Cut-Away



1920-


「たいがのないので、地方に対象など」

いやりに

ANNABEK Flow Model



TECHNOLOGY



Factors Influencing Pebble Flow Pattern


HNOLOGY INSIGHTS

INSIGHTS Side 12 (\cdot)

- Core Height to Diameter Ratio
- Core Diameter to Extraction Tube Diameter Ratio
- Pressure Drop Across Bed
- Friction Coefficient Variation
- Fragments

a Dilla C

씱



Pebble Friction Coefficient in Helium



Historical Pebble Flow Data

AVR

AND STREET

1

「日本の

≽ 1:2

- THTR
 - ➢ Expected 1:3
 - > Apparent 1:10 (may have been due to Pebble Fragments)
- ANNABEK Experiment (1980s)
 - > 1:10 Scale; Glass/Graphite Pebbles; Air
- PBMR Prediction

≽ 1:1.6

_	TECHNOLOG	
-	Slide 14	

Pebble Bed FHSS Requirements

Maintain On-line Refueling

A WAY TORE THE ADDRESS AL M. S.

一部にいる話 たてやい

> Add Fresh Fuel Elements


> Remove Spent Fuel Elements

Maintain Pebble Circulation


- MEDUL (multiple passes through the Core) - Two Zone Core
- > OTTO (Once Through Then Out)

Maintenance Requirements

> Unload/Reload Core (New Requirement)



TECHNOLOGY INSIGHTS Slide 16



PBMR Design Approach

- Follow THTR's Example to the Extent Practicable
 - > Functional Blocks Mounted in the Floor
 - Components Installed in Functional Blocks
 - > All Components monitored for leaks
- Improve Those Components with Known Deficiencies
 - > Pebble Counter

、状々などには自己構成の部合においたがら

- > Core Unloading Device and Lead-in Plenum
- Use Alternate Components where Circumstances
 Dictate
 - > Graphite/Fuel Discrimination Unit
 - > Burnup Measurement

INSIGHTS

Types of Components

Components without Drives

> Pebble Counter

Identifier/Verifier (Ion Chamber)

> Burn-up Measurement (Gamma-Spectrometer)

> Pebble Braking Device

≻ Filter

1

(1,1,2,2)

- 4121、1921年の第二日は精神の構成的に、

1912

Components with Drives

Core Unloading Device (CUD)

Fuel Loading Station

Double Seal Isolation Valves

> Diverter

> Collector

> Indexer

> Blower

Some PBMR Components with Drives

Last_Run Time= 0.0000 Frame=1


TECHNOLOGY INSIGHTS Side 20

Key PBMR Operating Modes


- Initial Core Loading
- Normal Online Refueling
 - > Circulation
 - > Adding Fresh Fuel
 - ➢ Removing Spent Fuel
- Core Unloading/Reloading for Maintenance
- Final De-fueling

「日本には、「日本には、「日本に、「日本など」」「日本などのです」」」





FHSS Core Unloading




一、小森市大学的学生、大学校学生学校学校学校学校

5

0.024

FHSS Core Reloading

 \bigcirc



General FHSS Characteristics

Characteristic	Value	Units
Daily Sphere Circulation Rate (normal)	5720	spheres/ FPD
Sphere circulation rate (normal)	515	spheres/hr
Sphere circulation rate (max)	900	spheres/hr
Daily operating time (normal)	12	hr/FPD
Number of fuel passes through core (nominal)	10	• .
FHSS operating pressure	1 to 7.2	MPa
FHSS operating temperature	0 to 260	°C
Total spheres in core (nominal)	440 000	spheres
Core sphere composition	75	% fuel

- 2時代になってきないがないたいであるがないない。ためになってもないたいは、ないていたな男体理論があいた

10011200

ŝ

TECHNOLOGY INSIGHTS Side 25

General FHSS Characteristics (continued)

Fuel spheres in core	330 000	spheres
Fuel sphere feeding points in core	9	
Graphite sphere feeding points in core	1	•
Fresh fuel storage capacity	70	canisters
Fresh fuel canister capacity	1000	spheres
Reactor fuel consumption (at full power)	375	spheres/FPD
Spent fuel storage capacity	5 000 000	spheres
Number of Spent Fuel Tanks	10	-
Storage medium	helium	at 100 kPa

TECHNOLOGY INSIGHTS Side 26

General FHSS Characteristics (continued)

Storage period	80	yrs
Spent fuel burn-up	80 000	MWd/tU
Spent fuel heat load (max per tank)	48	kW
Spent fuel storage temperature (max)	375	°C
Spent fuel tank wall temperature (max)	175	°C
Used Fuel Tank storage capacity	330 000	spheres
Time to unload full core of fuel	26	days
Used fuel tank decay heat load	0.6	MW

Pebble Bed FHSS Experiences

• AVR Operated Over 20 Years With Good Experience (2.4 Million pebbles processed)

Only 3% Outage due to FHSS

との意思なられていてもないというとい

30

こうの投影器の第二

\$0


安全省委任何的政策的理论。


ŷ.

- Problems with Core Unloading Device (singulizer) and Electric Motor Drives
- THTR Limited Experience Showed Improvements and New Problems
 - Revised Core Unloading Device (CUD), Changed Drives from Electro to Pneumatic
 - > Problem with Core Discharge Tube (lead-in to the CUD)
 - Problem with Addressing of Pebbles
- PBMR Design Based on Previous German Experience
 - Retained Proven Components
 - Revise Core Discharge Area
 - Improved Pebble Counters
 - Change Burnup Measurement



TECHNOLOGY





MATELIA DA DA CARA CARA A MARCA A MATTA MATANTATA


AL.

£,

**

TECHNOLOGY INSIGHTS


THTR Fuel Inspection Station




12時に、14時に19月1日第二十二

TECHNOLOGY INSIGHTS Slide 33

THTR FHSS R121




TECHNOLOGY INSIGHTS Silde 34




ki Ves

THTR Core Unloading Device

INSIGHTS





What Technology Development is Needed

Fundamentally All Required Technology Exists

Selection of

「大学」で「記録」にない話した

 Some Evolutionary Development May Help Improve Operability or Maintainability and may Help Reduce Cost