
Document Update Notification

COPYHOLDER NO: **TRM-U2-102**

TO: **GSB-NRC**

ADDRESS: **OS-DOCUMENT CONTROL,
WASHINGTON, D.C. 20555**

DOCUMENT NO: **TRM-U2**


TITLE: **TECHNICAL REQUIREMENTS MANUAL
(UNIT 2)**

REVISION NO: **012**

CHANGE NO: **AP-12**

SUBJECT: **MAKE LISTED UPDATES AND REMOVE
OLD TABS AND INSERT NEW TABS
BEFORE APPROPRIATE SECTIONS**

← *If this box is checked, please sign, date, and return within 5 days.*



ANO-1 Docket 50-313

ANO-2 Docket 50-368

Signature

Date

SIGNATURE CONFIRMS UPDATE HAS BEEN MADE

RETURN TO:

**ATTN: DOCUMENT CONTROL
ARKANSAS NUCLEAR ONE
1448 SR 333
RUSSELLVILLE, AR 72801**

1001

TECHNICAL REQUIREMENTS MANUAL REVISION: 12

ARKANSAS NUCLEAR ONE, UNIT NO. 2

Revise the following pages of the associated Technical Requirements Manual with the attached pages.

REMOVE PAGES

INSERT PAGES

Index Pages

i-2
i-3

-----i-2
-----i-3

Technical Requirements Pages

-----3.6-1

LIMITING CONDITIONS FOR OPERATION AND SURVEILLANCE REQUIREMENTS

<u>SECTION</u>	<u>PAGE</u>
3.1 REACTIVITY CONTROL SYSTEMS (Continued)	
3.1.2.6 Boric Acid Makeup Pumps - Operating.....	3.1-7
3.1.2.7 Borated Water Sources - Shutdown	3.1-8
3.1.2.8 Borated Water Sources - Operating	3.1-10
3.3 INSTRUMENTATION	
3.3.1.1 Reactor Protective Instrumentation	3.3-1
3.3.3.3 Seismic Instrumentation	3.3-4
3.3.3.4 Meteorological Instrumentation.....	3.3-7
3.3.3.7 Chlorine Detection Systems	3.3-10
3.3.4.1 Turbine Overspeed Protection.....	3.3-11
3.6 CONTAINMENT SYSTEMS	
3.6.4.3 Containment Recirculation System.....	3.6-1
3.9 REFUELING OPERATIONS	
3.9.3 Decay Time and Spent Fuel Storage.....	3.9-1

BASES

<u>SECTION</u>	<u>PAGE</u>
B 3.1 REACTIVITY CONTROL SYSTEMS	
B 3.1.2 Boration Systems	B 3.1-1

BASES

<u>SECTION</u>	<u>PAGE</u>
B 3.3 INSTRUMENTATION	
B 3.3.1.1 Reactor Protective Instrumentation	B 3.3-1
B 3.3.3.3 Seismic Instrumentation.....	B 3.3-1
B 3.3.3.4 Meteorological Instrumentation	B 3.3-2
B 3.3.3.7 Chlorine Detection Systems	B 3.3-2
B 3.3.4.1 Turbine Overspeed Protection	B 3.3-2
B 3.9 REFUELING OPERATIONS	
B 3.9.3 Decay Time	B 3.9-1

ADMINISTRATIVE CONTROLS

<u>SECTION</u>	<u>PAGE</u>
6.9 None	

CONTAINMENT SYSTEMS

CONTAINMENT RECIRCULATION SYSTEM

LIMITING CONDITION FOR OPERATION

3.6.4.3 At least two independent containment recirculation fans shall be OPERABLE.

APPLICABILITY: MODES 1 and 2.

ACTION:

With one containment recirculation fan inoperable, restore the inoperable fan to OPERABLE status within 30 days. If not restored within 30 days or with more than one containment recirculation fan inoperable, initiate a condition report to document the condition and determine any limitations for continued operation of the plant.

SURVEILLANCE REQUIREMENTS

4.6.4.3 Each of the above containment recirculation fans shall be demonstrated OPERABLE:

- a At least once per 92 days on a STAGGERED TEST BASIS BY:
 - 1. Verifying that the fan can be started on operator action in the control room, and
 - 2. Verifying that the fan operates for at least 15 minutes.
- b. At least once per 18 months by verifying a flow rate of at least 4500 cfm per fan.

)

)

)

∫

1.0 Use & Applications

)

)

)

∫

2.2 LSSS

)

)

)

2.2 Bases

3.0 Applicability

)

)

)

3.1 Reactivity
Control

)

)

)

3.2 Power Distribution

)

)

)

3.3 Instrumentation

∫

3.4 RCS

)

)

)

∫

3.5 ECCS

)

)

)

)

)

)

3.7 Plant Systems

✓

)

)

)

∫

3.8 Electrical Power

)

)

)

3.9 Refueling

)

)

)

∫

3.10 STE

)

)

)

)

)

)

4.0 Design Features

∫

5.0 Admin Controls

)

)

)

BASES

)

)

)