
SYSTEM DATA
SAFETY CLASS VERIFICATION
ORIGINATED BY CJA 2-12-79
REVIEWED BY RHK 2-12-79
TO BE USED NEXT
NOTE: A. TEMPORARY STRAINER FOR SYSTEM CLEAN UP, TO BE REMOVED AFTER FINAL FLUSH.
NOTE: A. FLOW LISTED IS THE ASME RATED CAPACITY KNEL ACTUAL AT 3% ACCUMULATION IN LBS PER HOUR WHEN THE SAFETY VALVE IS FULL OPEN AT THE HIGHEST SET SAFETY VALVE SET PRESSURE (1235 PSIG). THE PRESSURES LISTED ARE THE INDIVIDUAL SAFETY VALVES SET PRESSURE.
TURBINE DRIVEN EFP AUTO-START SIGNAL
1. 2/3 LOW-LOW LEVEL SIGNALS IN ANY 2 STEAM GENERATORS
2. UNDERVOLTAGE ON BOTH ESF BUSSES
3. AMSAC
EMERGENCY CLOSURE OF MAIN STEAM ISOLATION VALVE & BYPASS VALVE
1. 2/3 HI CONTAINMENT PRESSURE.
2. 2/3 HI STEAM FLOW WITH
2/3 LO-LO AVG. PRIMARY COOLANT TEMPERATURE.
3. MANUAL-CONTROL ROOM/A TRAIN HAS INDIVIDUAL SW PER VALVE & B TRAIN HAS COMMON S.W. FOR 3 VALVES.
4. 2/3 LOW STEAM PRESSURE.
MS ISOLATION VALVE RE-OPEN SIGNAL
MS ISOLATION VALVE TEST CLOSE SIGNAL G.A.I. DWG. 888-881
TO CONTROL & PROTECTION LOGIC DWGS. 1880932 & 1880837
OPEN LIMIT SWITCH ACTUATOR WILL ISOLATE BD. SEE B-288-001.
MOISTURE COLLECTOR OR VALVE CLOSURE
MANUAL - CONTROL ROOM "A" TRAIN HAS INDIVIDUAL SW PER VALVE "B" TRAIN HAS COMMON SW FOR 5 VALVES
FEEDWATER CONTROL DWG. 1880932, SHEETS 3,4,8
TO SOLENOID VALVE CONTROL POWER DISCONNECT SWITCHES IN THE MCB OR IN TERM. CABINETS IN THE CABLE SPREADING ROOM.
STEAM GENERATOR "A" XSG-2A-RC
STEAM GENERATOR "B" XSG-2B-RC
STEAM GENERATOR "C" XSG-2C-RC
REACTOR BUILDING
DETAIL "C" (E-6)
DETAIL "A" (B-6)
DETAIL "B" (G-6)
ALL PORTIONS OF THE MAIN STEAM PIPING WITH A WALL THICKNESS GREATER THAN ¾" TO BE HYDROSTATICALLY TESTED WITH WATER AT A MINIMUM TEMPERATURE OF 120°F. THE REMAINING PORTIONS OF THE SYSTEM MAY BE TESTED WITH WATER AT A TEMPERATURE OF 68°F.
DESIGN DATA
NOTES:
1. PIPING WITHIN THESE FLAGS IS TO MEET ALL THE REQUIREMENTS EXCEPT FOR STAMPING, OF ASME CODE SECTION III CLASS 2 AND IS SPECIFICALLY INCLUDED IN THE SCOPE OF SPECIFICATION SP-544-844461-000
2. DOUBLE ROOT VALVES ARE USED ON MAIN STEAM.
3. MAIN STEAM SYSTEM INSIDE/AIR IS DESIGNED IN CONFORMANCE WITH ASME BOILER & PRESSURE VESSEL CODE SECTION III (NT) AND S-73 ADDENDA.
4. ALL INSTRUMENTS WITH 400 TAG SERIES NUMBERS ARE SUPPLIED BY
5. ALL STATUS LIGHTS INDICATE BOTH OPEN & CLOSED POSITIONS UNLESS OTHERWISE NOTED.
6. FOR HYDRAULIC CLEANING OPENINGS, SEE PHYSICAL PIPING DWG.
7. THE EMERGENCY FEEDWATER PUMP DRIVE TURBINE EXHAUST PIPING SHALL BE DESIGNED FABRICATED & INSTALLED IN ACCORDANCE WITH ASME B & PV CODE SECTION III CLASS 3 RULES, HOWEVER, THIS PIPING DOES NOT REQUIRE HYDROSTATIC TESTING & CODE STAMPING. PIPING IS CLASSIFIED 2b, TECHNICAL REQUIREMENTS ARE DISCUSSED IN TRP-13.
PLEX Drawing TR00160-003
THIS IS A NUCLEAR SAFETY RELATED DOCUMENT, NO DEVIATION SHALL BE INITIATED OR PERFORMED WITHOUT PRIOR DOCUMENTATION AND WRITTEN APPROVAL
FSAR FIGURE 10.3-1
SOUTH CAROLINA ELECTRIC & GAS COMPANY
VIRGIL C. SUMMER NUCLEAR STATION
PIPING SYSTEM FLOW DIAGRAM
MAIN STEAM (NUCLEAR)
DESIGN ENGINEERING
V.C. SUMMER NUCLEAR STATION, JENKINSVILLE, S.C.
DRAWN RHM CHECKED MGR ENGR. APPROVAL JEW
D-302-011 SHEET 34
DRAWING NUMBER
SHT. NUMBER / REV.
DRAWING LEGIBILITY CLASS 1
SCALE: CAD ENHANCED
REVISION
X3020003
D-56