


Supplementary Shielding Calculation
for the GNS 11 Transport Cask



G N S

G N S
Gesellschaft für
Nuklear-Service mbH

Zweigertstr. 28 - 30
D-4300 Essen
Telefon 02 01/72 20-0
Telefax 02 01/72 20-181

Supplementary Shielding Calculation
for the GNS 11 Transport Cask

Report-No. : GNS B 87/89 E Rev. 0
Date (first edition) : June 1989

	Signature	Date
Author	Dr. KÜHL, WTI <i>Ulrich</i>	22.08.91
Checked by	<i>R. J. J.</i>	22.08.91
Released by	<i>P. B. H. W., QS</i>	26.08.91

This report may not be cited, reproduced on whole or in part, or made available to third parties without the permission of GNS, Gesellschaft für Nuklear-Service mbH, Essen. All rights reserved by GNS.

Table of contentsPage

- 0. Summary
- 1. Introduction and Tasks
- 2. Computational Method
- 3. Computer Model
- 4. Fuel Assembly and Structural Data
 - 4.1 General Input for the Reference F/A
 - 4.2 Special Input Data for the Various Types of Enrichment of the Reference Fuel Assembly
 - 4.3 Structural Data
- 5. Computational Results

References

List of Figures and TablesPage

Fig. 1: Geometry for Criticality Calculations

Fig. 2: Basket for 33 Square-shaped MTR F/As

Fig. 3: Computer Geometry for MTR F/As of the types GKSS, FZS, PSI

Fig. 4: Computer Printout of the Quarter Symmetry of the Cask Cross-section GNS 14

Fig. 5: Statistical Determination of the k_{eff} with Keno Run for the GNS 11 with 33 LEU F/As

0. Summary

In the GNS Report GNS B 38/86 /1/, criticality calculations were conducted for the GNS 11 transport cask with regard to different MTR fuel assemblies from research reactors with various variations of basket.

Among other things, the basket for 33 square-shaped MTR fuel assemblies was examined. The reference fuel assemblies used were of the types FRJ 1 (22 fuel plates), and FRM, BER and FRG (23 fuel plates in each case) with a U-235 content of 270 g per F/A at a maximum enrichment of 94 % (HEU F/A).

k_{eff} values of < 0.90 , and hence adequate criticality safety, were obtained for both types of fuel assembly.

Supplementary criticality calculations were conducted for this report with a view to the imminent or future transport of a maximum of 33 square-shaped MTR fuel assemblies with different fissile material - and total uranium masses with different types of enrichment (HEU, MEU, LEU). The reference fuel assembly used was the fuel assembly with 23 fuel plates, which is also used in the same form in other research reactors (e.g. GKSS, FZS, PSI etc.)

In the calculations the maximum expected fissile material masses (most reactive case) were allocated to each of the HEU, MEU and LEU fuel assemblies.

Three calculations were conducted with the following parameters:

F/A Data	Type of Enrichment for Reference F/A		
	HEU	MEU	LEU
Mass U-235 (nominal)	280 g \pm 1.5 %	322 g \pm 1.5 %	400 g \pm 1.5 %
Mass U-235 (maximum)	284.2 g	326.8 g	406 g
Enrichment	93 %	45 %	20 %
U total (nominal)	302 g 1.5 %	715.5 g \pm 1.5 %	2000 g \pm 1.5 %
U total	305.6 g	726.2 g	2030 g

The results of these calculations were as follows for 33 fuel assemblies in the cask in each case:

- HEU F/A: $k_{\text{eff}} = 0.0870 \pm 0.004 (1 \bar{5})$,
- HEU F/A: $k_{\text{eff}} = 0.9094 \pm 0.005 (1 \bar{5})$,
- LEU F/A: $k_{\text{eff}} = 0.9293 \pm 0.004 (1 \bar{5})$,

i.e. there was adequate criticality safety in each case.

With these results it can be seen that adequate criticality safety will be present for F/A loads with fissile material contents or enrichment below the above levels.

This also applies when the baskets are only partly loaded (e.g. 28 F/A in a 33 basket) and when there are mixed loads in the basket, containing HEU, MEU and LEU fuel assemblies, taking due account of the maximum U-235 masses listed above.

1. Introduction and Tasks

The aim of the following investigation is to verify the criticality safety of the GNS11 cask. The cask is designed for the dry transport of spent MTR fuel assemblies.

Supplementary calculations to those already conducted for GNS B 38/86 /1/ were conducted for fuel assemblies from other research reactors (e.g. GKSS, FZS and PSI), specifically with a view to imminent or future transport operations.

Fuel assemblies of the same design were used with different fissile material and total uranium masses and with different types of enrichment (HEU, MEU and LEU fuel assemblies).

The load in the GNS 11 was strictly limited to the already used basket for 33 square-shaped MTR fuel assemblies (see Fig. 2).

For the criticality safety analysis, only the flooded cask state was considered (with unborated water) such as may pertain when the casks are loaded or unloaded. A criticality analysis of the dry state is unnecessary since the MTR fuel assemblies are always subcritical, owing to the small quantity of fissile material in the dry state. The criticality calculations were always based on an unlimited number of casks.

The GNS 11 cask has a cylindrical cross section. The body of the cask consists of a sandwich configuration made of stainless steel/lead/stainless steel. The cavity cross section is 72.3 cm. The height of the cavity is 94.1 cm. The cask lid and the fuel basket are made of stainless steel.

In the criticality calculations, fresh, undepleted fuel assemblies were always assumed, ignoring any burn-up poisons.

2. Computational Method

The criticality calculations were performed with the aid of the SCALE program system /2/. For criticality calculations, this program contains various cross-sectional libraries, from which the 16 group Hansen-Roach library was selected here (with 5 thermal groups ≤ 3 eV). The program system possesses further routines for treating self-shielding according to Bondarenko's method /3/ or according to Nordheim's method /4/ for these cross sections. Each of the programs is called up according to the given resonance data.

Furthermore, the XSDRNPM code /5/ is integrated into the program system, and with this the cell-weighted cross sections can be generated. The self-shielded or cell-weighted cross sections are then fed into the KENO Va program /6/ to calculate the multiplication factor. The program system also possesses several auxiliary programs, e.g. to calculate the Dancoff factor of nuclide number densities or for the automated transfer of the cross sections.

The fuel assemblies were represented in the calculation by cell-weighted cross sections. The neutron statistics for determining the multiplication factor k_{eff} with the KENO Va program is based on 100 iterations of 300 neutrons each, although the first three iterations are not counted.


3. Computer Model

The computer model for the cask is sketched in Fig. 1. The cross section of the basket for 33 square-shaped MTR fuel assemblies is shown in Fig. 2. The computer model for the MTR reference fuel assembly can be seen in Fig. 3.

The radial structure of the various fuel baskets was modelled exactly in the computer model. Only those portions of the basket material and the F/A structures located in the region of the active fuel zone were taken into account. That is, only the steel portion of the basket above a height of 60 cm was considered in the calculations. The fuel assemblies were also only reproduced in the region of the active F/A zone, and the non-active upper and lower end pieces were replaced conservatively by moderating water.

The wall thickness of the cask in the side wall region consists of 4 cm stainless steel (outside), a 17 cm thick layer of lead in the middle and a 2 cm thick inner layer of stainless steel (1.4541 in each case). The bottom of the cask is similarly constructed; however, the thickness of the inner liner there is 4 cm, and the lead layer is 13.8 cm thick. The lid consists of 26.5 cm stainless steel (1.4313). On the outer side wall surface of the cask, mirror reflection of the neutrons was assumed. In this way, the multiplication factor calculated corresponds to an unlimited configuration of such casks.

In the calculation the reactivity-reducing effect of the 3.5 cm thick protection cap and the top and bottom impact limiters were ignored.



Alle Abmessungen in mm

All dimensions in mm




Blei / Lead




Stahl / Steel




UAl_x+Al
bzw. U₃Q₈+Al



Alle Abmessungen in mm
 All dimensions in mm



All Dimensions in mm
 Alle Abmessungen in mm



DETAIL "X"

4. Fuel Assembly and Structural Data

4.1 General Input Data for the Reference Fuel Assembly

F/A cross section:	(80.5 x 76.1) mm ²
Length of the active zone:	600 mm
Number of plates:	23
Distance between plates:	2.23 mm
Total F/A length:	873 mm

Plate structure:

- Total thickness	1.27 mm
- Cladding thickness	0.38 mm
- Fuel layer thickness	0.51 mm

Densities:

- Uranium density (HEU and MEU F/A)	19.05 g/cm ³
- U ₃ O ₈ density (LEU F/A)	8.30 g/cm ³
- Aluminium density	2.699 g/cm ³

4.2 Special Input Data for Different Types of Enrichment of the Reference Fuel Assembly

F/A Data	Type of Enrichment for Reference F/A		
	HEU	MEU	LEU
Mass U-235 (nominal)	280 g \pm 1.5 %	322 g \pm 1.5 %	400 g \pm 1.5 %
Mass U-235 (maximum)	284.2 g	326.8 g	406 g
Enrichment	93 %	45 %	20 %
U total (nominal)	302 g 1.5 %	715.5 g \pm 1.5 %	2000 g \pm 1.5 %
U total	305.6 g	726.2 g	2030 g

4.3 Structural Data

F/A structural parts: Aluminium

Fuel: Uranium-aluminium mixture /HEU, MEU F/A)
U₃O₈-aluminium mixture (LEU F/A)

Basket: Stainless steel No. 1.4541
Density = 7.80 g/cm³

Cask: Stainless steel/lead/stainless steel

Stainless steel, No. 1.4541
Density = 7.80 g/cm³

Lead, (DIN 1719, No. 2.3085)
Density = 11.0 g/cm³

Cask lid: Stainless steel, No. 1.4313
Density = 7.80 g/cm³

The calculations relate uniformly to a temperature of 293 K and a water density of = 1.0 g·cm⁻³.

5. Computational Results

The results of the criticality calculations are shown in Table 1 for the individual types of enrichment of the reference fuel assembly.

Type of enrichment	$k_{\text{eff}} \pm 1\sigma$
HEU F/A	0.8870 ± 0.004
MEU F/A	0.9094 ± 0.005
LEU F/A	0.9293 ± 0.004

Table 1: Results of Criticality Calculations for the GNS 11 Transport Casks

The maximum value in the double statistical scatter is, for the LEU fuel assembly, $k_{\text{eff}} + 2\sigma = 0.9373$ and is sufficiently below the design limit of 0.95. Thus, the usual mechanical tolerances, fluctuations in the material specifications or possible temperature effects are covered.


In this way mixed loads of, for example, HEU, MEU and LEU fuel assemblies in the 33 basket, as well as part loads (e.g. only 28 fuel assemblies in the basket), are also to be regarded as subcritical.

The same applies in a similar fashion to loads with fuel assemblies whose content of fissile material or degree of enrichment is smaller than assumed in section 4.2.

Fig. 4 shows the computer outprint of the quarter symmetry of the GNS 11 cask cross section loaded with 33 LEU fuel assemblies.

Fig. 5 highlights the statistical determination of the k_{eff} during the KENO run for the GNS 11 with 33 LEU fuel assemblies.

GNS11 MIT 33 MTR-BE TYP GKSS LEU 400 G U-235(20%)/BE
PLOT OF AVERAGE K-EFFECTIVE BY GENERATION RUN. THE FINAL VALUE IS 0.9291



GNS

Statistical Determination of the k_{eff} during the KENO Run for the GNS 11 with 33 LEU Fuel Assemblies

Fig. 5

References

- /1/ GNS B 38/86
Kritikalitätsberechnungen für den Transportbehälter GNS 11,
Rev. 0
October 1986
- /2/ J.A. Buchholz:
SCALE: A modular Code System for Performing Standardized
Computer Analyses for Licensing Evaluation
NUREG/CR-0200, ORNL/NUREG/CSD-2/V1R1 (1984)
Oak Ridge National Laboratory CCC-466
- /3/ N.M. Greene:
BONAMI: AMPX Module to Perform Bondarenko Resonance Self-
Shielding
RSIC/PSR-63/AMPX-II, Sect. 9.12 (1978)
- /4/ L.M. Petrie, N.M. Greene, J.L. Lucius, J.E. White:
NITAWL: AMPX Module for Resonance Self-Shielding and Working
Library Production
ORNL/TM-3706, AMPX, Sect. 7 (1976)
- /5/ L.M. Petrie, N.M. Greene:
XSDRNPM: AMPX Module with One-Dimensional SN
Capability for Spatial Weighting
ORNL/TM-3706, AMPX, Sect. 8 (1976)
- /6/ L.M. Petrie, N.F. Landers:
KENO-Va: An Improved Monte Carlo Criticality Program with
Supergrouping
NUREG/CR-0200 Volume 2, Section F11
ORNL/NUREG/CS-2/V1/R1 (1984)