4LICLEAR REGULATORY COMMISSION RAS 5261 . 72-22-ISFSI Applicant Exhibit YYY Official Exh. No. Discreet No. Rec'd 4/11/02 in the matter of Cole, Jack Stall Francis G Woods [francisw@juno com] From: RECEIVED **Applicant** Wednesday, March 13, 2002 1:21 PM ent: REJECTED Intervenor , O: wboyne@cgi.com Cc: Gilford_G_Robinson@mail.dbf.state fl.us Other WITHDRAWN Subject: Help for a Good Guy Witness Clerk The request for info on pilots trying to avoid causing death and destruction on the ground the risk of their own safety was passed to me by Gil Robinson, USMC (forever). My name is Frank Woods, retired naval aviator (1978). I flew primarily carrier aircraft, including fighters (F3H) and recce (RASC). I have two DOCKETED instances that might be on interest. USNRC When I was in the RAG (replacement all group. Naval Air Station in 1961, a fellow student (sorry, don't recall the name) had, I believe engine problems in the landing pattern. He had sufficient time and altitude to eject but because of the proximity of a sufficient time and altitude to eject but because of the proximity of a sufficient time and altitude to eject but because of the proximity of a RULLMAKINGS AND ADJUDICATIONS STAFF

ınjured

but the pilot who was lost. I believe the school was renamed after him.

The second instance is one of my own. This time it was the RA5C "Vigilante" RAG at NAS Sanford, FL. It occurred on my very first flight in the Viggie in 1966. The Vigilante is (there are still a few in museums) a two seat (pilot and reconnaissance attack navigator (RAN)), ery large, two engine (J79), carrier aircraft, converted from attack pomber (A5A) to recce (RA5C). Since there are no flight controls in the rear seat, the policy was to start new pilots off by themselves with an experienced pilot in a chase aircraft. Shortly after takeoff I had a generator malfunction. Procedures were to terminate the flight and land since the generator constant speed drive used engine oil and the failure could be indicative of something more sinister (like and oil leak). After dumping lots of JP4 over the swamps around Sanford, I entered the pattern for my first landing on what was not an overly long runway. Since no other indications of problems had developed, the chase and I decided that a touch and go was a good idea to make sure I had good control etc. Well, on the go around, just as I turned downwind at about

500', the starboard (right to USAF) nozzle failed open, essentially making that engine useless for flight. This occurred because the nozzle also used engine oil for operation. This should not have been a problem except I forgot to put the flaps to 30degrees, which was necessary for single engine flight. I selected afterburner on the good engine, almost immediately, I got a fire warning light (cooling doors didn't function), the airplane was not flying single engine (flaps!!) like the book said

would and I was losing altitude. The area below the aircraft was residential so I was looking for somewhere to go. I saw what turned out to be Crystal Lake in front of me. While all this was going on, I heard a voice from the chase plane say "flaps" and I took the belated action. I was still losing altitude and decided I had better depart the increasingly noisy cockpit (all the warning lights and buzzers were active). I was still over houses so I delayed ejecting. When I reached The lake, I pulled the nose up, and checked my altitude....175'. jection would have probably been successful but before I pulled the curtain, the aeronautics had finally caught up and the plane started to climb. Since my noise was pointed up, I now had the aircraft in the proper configuration for single engine flight and I was in burner, I

zoomed to 4000', "calmly called the tower and landed uneventfully.

I was consciously delaying ejecting for fear of hitting someone on the ground. You definitely have time to consider such things even under atress.

Don't know whether the above is of help, but I enjoyed writing it down.

Regards,

Ç

Frank Woods Orlando, FL