## \* RAS 5576

7

:

# 72-22-ISFSI - State Exhibit 117 - Recid 5/8/02

STONE & WEBSTER, INC.

CALCULATION SHEET

5010.64	C C	ALCOLAI	ION SHEET					
CLIENT & PROJECT	ORAGE LLC - PESE				PAGE 1 OF 59			
PRIVATE FUEL ST	UNAGE, EEU - ITOI				+ 6 pp of ATT.	ACHMEN	rs	
CALCULATION TITL	E					EGORY	(~)	
STABILITY ANALYS	ES OF CANISTER TRAP	SFER BUIL	ER BUILDING			I NUCLEAR SAFETY RELATED		
					III (other)			
		CURRENT	CURRENT OPTIONAL					
JOB ORDER NO.		CALC NO	CALC NO TASK (		WORK PA	<u>vo.</u>		
05996.02	BOVALS - SIGNATURE	& DATE			SUPERSEDES CONFIRMATIO		MATION	
PREPARER(S)/DATE(S	REVIEWER(S)/DATES	S) REVIEW	EPENDENT ER(S)/DATE(S)	OR NEW CALC NO.	CALC NO. OR REV NO.	REQUI YES	NO NO	
Original Signed By:	Original Signed By:	Origin	al Signed By:	0	N/A		~	
LPSingh / 12-9-98	DLAloysius / 12-10-9	8 DLAloy	rsiu / 12-10-98					
Original Signed By:	Original Signed By:	Origin	al Signed By:		6(0)-13			
DI Alovsius / 9-3-99	SYBoakye / 9-3-99	TYCh	nang / 9-3-99	1	Boy 0		1	
SYBoakye / 9-3-99	DLAloysius / 9-3-99	TYCh	TYChang / 9-3-99		nev. u			
See page 2-1 for ID	See page 2-1 for ID of Prepared / Reviewed By							
Original Signed By:	Original Signed By: Original Signed By:		Original Signed By:		1		1	
PJTrudeau / 1-21-00	udeau / 1-21-00 TYChang / 1-21-00		TYChang / 1-21-00					
Original Signed By:	Original Signed By:	Origin	Original Signed By:		2		1	
PJTrudeau / 6-19-00	TYChang / 6-19-00	TYCh	ang / 6-19-00					
Original Signed By:	Original Signed By:	Origin	Original Signed By:		3		1	
SYBoakye / 3-30-01	TYChang / 3-30-01	TYCh	TYChang / 3-30-01		ļ	<u> </u>		
Original Signed By:	Original Signed By:	Origin	Original Signed By:		4		1	
SYBoakye / 3-30-01	TYChang / 3-30-01	TYCh	TYChang / 3-30-01		<u> </u>	<u> </u>		
PJTrudeau / 7-26-01	TYChang / 7-26-01	TYCh	TYChang / 7-26-01		5		1	
Bul Z. Undea	Ful F. Rudeau Thomas H Chang		. Thowar by Chang					
-0								
		DISTR	IBUTION					
		COPY SENT	COPY SENT GROUP		NAME & LOCATION SEN		COPY SENT	
GROOT		(1)					· (~)	
RECORDS MGT.	JOB BOOK R4.2G	ORIG						
FILE IF NONE)	FIRE FILE - Denver	Ø						
Geotechnical	PJTrudeau - Stoughton	/3 🗹					•	
							<u> </u>	

State's Exhibit 117

SECY-02

Template = SECY-028



کې ۱۹۹۰ هو. د کې

2

. .

.

,

### 2003 JAN 29 PM 3: 13

OFFICE OF THE SECRETARY RULEMAKINGS AND ADJUDICATIONS STAFF

### ICLEAR REGULATURY COMMISSION

in the matter of	Official Exh. No// 7
Staff Applicant Intervenor Other DATE Clerkpmp	IDENTIFIED RECEIVED REJECTED WITHDRAWN Witness

#### STONE & WEBSTER, INC.

#### CALCULATION SHEET

	BACE 23			
J.O. OR W.O. NO.	J.O. OR W.O. NO. DIVISION & GROUP		OPTIONAL TASK CODE	FAGE 20
05996.02	G(B)	13-6	N/A	

the state of stress existing under the Canister Transfer Building mat. Note, that the average post-peak strength reduction for normal stress of 1.5 ksf for the three direct shear tests is only 15.6% for these very high shear displacements in the direct shear tests. The maximum value of the average the post-peak strength reductions for normal stress of 1.5 ksf occurred for Sample U-3B&C in CTB-6, and it equaled 20.8%. If the results of this test were used to define the residual strength of these soils, the analyses would be performed at c = 1.5 ksf, the average of the post-peak strengths measured at the maximum shear displacements in these tests for normal stresses of 1 ksf and 2 ksf. This would result in higher factors of safety than are calculated and presented in Table 2.6-14, based on c = 1.36 ksf.

CALCULATION OF AVERAGE POST-PEAK STRENGTH REDUCTION FOR NORMAL STRESS APPLICABLE TO FINAL TRESSES UNDER THE CANISTER TRANSFER BUILDING

	1	Normal Stress = 1 ksf			Normal Stress = 2 ksf			Average	
Boring	Sample	Peak Strength	Strength at Maximum Shear Displace- ment	Post-Peak Strength Reduction	Peak Strength	Strength at Maximum Shear Displace- ment	Post-Peak Strength Reduction	Strength Reduction for Normal Stress = 1.5 ksf	
		ksf	ksf	9%	ksf	ksf	%	<b>%</b>	
6.2	U-1C	1.67	1.2	28.1	2.13	2.1	1.4	14.8	
OTR C	ILSB&C	1.57	1.1	29.9	2.15	1.9	11.6	20.8	
C18-0	U-3Dac	1.57		00.5	1.59	17	~0.0	11.3	
CTB-S	U-IAA	1.42	1.1	22.5	1.50		0.0		

The results of the sliding stability analysis of the Canister Transfer Building for this case are presented in Table 2.6-14. In this table, the components of the driving and resisting forces are combined using the SRSS rule. All of these factors of safety are greater than 1.1. the minimum required value. These results indicate that the factors of safety are acceptable for all load combinations examined. The lowest factor of safety is 1.26, which applies for Cases IIIC and IVC, where 100% of the dynamic earthquake forces act in the N-S direction and 40% act in the other two directions. These results demonstrate that there is additional margin available to resist sliding of the building due to the earthquake loads, even when very conservative estimates of the residual shear strength of the clayey soils are used.

5010.85