

The crushed rock surface materials will be installed flush with the top of the storage pads and removed as required in order to accommodate the actual settlement of the pads. Exposed edges of the pads will be chamfered and the compacted aggregate surface material will be feathered to meet the edges of the raised pads for transporter access, as shown in Figure 4.2-7.

This settlement represents an upper-bound estimate of the total compression, because it was developed assuming that the consolidation characteristics that were measured for the clayey soils at a depth of about 10 ft are applicable for the entire upper layer (~25 to 30 ft). The SPT data from the borings and the CPT results indicate that the soils become stiffer within the 10 to 20 ft depth zone. Additional consolidation tests performed on samples obtained from depths of about 25 ft in the Canister Transfer Building area, reported in Attachment 6 of Appendix 2A, indicate that the soils at that depth are less compressible than those used to estimate the settlements presented above. Further, based on the CPT program, most of the soils underlying the pad emplacement area are characterized as soils that *behave* as "sandy" soils, rather than as cohesive soils. Such soils are much less compressible than the clayey soils described above. Therefore, assuming that the entire upper layer at the site was comprised of soils whose compressibilities are similar to those measured at a depth of 10 to 12 ft conservatively overestimates the expected settlements.

Effect of Cohesionless Soils Underlying the Cask Storage Pads on Settlements

As discussed above, the soil behavior types determined from the cone penetration test data and reported in ConeTec (1999) must be recalibrated to agree with the soil classifications determined based on samples obtained in the borings and tested in the laboratory. Figure 2.6-30, Sheets 1 through 6, present comparisons of the boring and laboratory soil classifications plotted vs elevation alongside the soil behavior type data from nearby cone penetration tests. These figures illustrate that the soil behavior type values reported in ConeTec (1999) that are greater than 5 (i.e., sandier soils), as well

168
 NUCLEAR REGULATORY COMMISSION
 Case File No. ~~100-100000~~
 Docket No. PF 5
 in the matter of _____
 IDENTIFIED
 RECEIVED
 REJECTED
 Intervenor
 WITHDRAWN _____
 Other _____
 Date: 4-29-02
 Clerk: gpc

OFFICE OF THE SECRETARY
 RULEMAKINGS AND
 ADJUDICATIONS STAFF

2003 JAN 31 PM 2:00

DOCKETED
 USNRC

