

see file packet 7A for end

WM Record File 101 SEP 3 1985 Subject 10  
Docket No. \_\_\_\_\_  
PDR ✓  
LPDR B

Distribution:  
WM 3101.5 sf ←  
NMSS rf  
WMGT rf  
MGordon & rf  
MFliegel  
MKnapp  
RNataraja  
RBrowning  
MBell  
PDR  
LPDR

8101 /MG/85/09/17

Distribution: \_\_\_\_\_ 1 \_\_\_\_\_  
\_\_\_\_\_  
(Return to WM, 623-SS) \_\_\_\_\_

MEMORANDUM FOR: John Greeves, Chief  
Engineering Branch  
Division of Waste Management

FROM: Malcolm R. Knapp, Chief  
Geotechnical Branch  
Division of Waste Management

SUBJECT: DRAFT FINAL REPORT - BASALT WASTE ISOLATION PROJECT:  
HANFORD SITE DISQUALIFYING CONDITION - PRELIMINARY POSITION  
FOR REPOSITORY WATER INFLOW UNDER HIGH PRESSURE SEPTEMBER 1984

As you requested, I have had Matthew Gordon of my staff review the hydrologic aspects of the subject report by R.D. Allen of PNL. His comments are summarized below:

1. The document presents three calculations of instantaneous water inflows into a tunnel beneath the Hanford Site. As discussed below, the calculations will likely lead to underestimates in initial water inflow. However, they may overestimate the longer-term inflow rate, as noted by Allen on page 5.7.
2. The document presents a summary of parameter values for hydraulic head, hydraulic conductivity, and storativity of the various aquifers and confining units, which are based on what the NRC staff considers to be optimistic interpretations of data in which the NRC staff has limited confidence. As noted in NUREG-0960, and in a letter from Wright to Olson (May 25, 1984) Attachment 1, the heads and hydraulic property data collected during the BWIP drill and test program reflect, at best, the conditions in the immediate vicinity (i.e., tens of meters) of the borehole. Higher conductivity zones, channels, etc., are not likely to have been detected in these tests. The measurements are further confounded by the effects of fluid temperature, wellbore skin, wellbore storage and irregular testing procedures as noted in the attached letter from Wright to Olson. There are also several cases of incorrect analytical interpretations of hydraulic tests, such as in the Strait and Spang reports listed in the documents' reference section. For example, the report on hydraulic testing of the Cohasset colonnade/entablature at RRL-2 has been reviewed by NRC (memo from Knapp to Miller, January 15, 1985, Attachment 2) and was found to probably underestimate the horizontal hydraulic conductivity of that unit by at least an order of magnitude.

8511140247 850930  
PDR WASTE  
WM-10 PDR

DFC	:WMGT	kd	:WMGT	:WMGT	:	:	:
NAME	:MGordon		:MFliegel	:MKnapp	:	:	:
DATE	:85/09/17		:85/09/	:85/09/	:	:	:

1590

Other tests were also analyzed incorrectly, e.g., the over-pressure pulse test of the Cohasset flow top. For this test, an incorrect application of the analytical method apparently resulted in an under-estimate of the hydraulic conductivity by a factor of twenty. These reports have never been corrected by BWIP. Due to the uncorrected analytical errors and the uninvestigated uncertainties, the test results should not have been used in the subject report. It would have been more appropriate to use a bounding value of horizontal hydraulic conductivity slightly higher than the highest measured values to date.

3. A two-order-of-magnitude uncertainty in the hydraulic conductivity is claimed to have been assumed in the calculations. This uncertainty does not seem to be reflected in the three cases analyzed. In any case, the uncertainty range described should be substantially larger than two orders of magnitude for the reasons noted in item 2 above. In fact, the actual systematic error in analysis, by itself, probably approached two orders of magnitude without even considering the uncertainties in scale, spatial variability, etc.
4. On page 4.11, estimates from uncited "earlier studies" of vertical hydraulic conductivity are presented. There have been no acceptable direct tests nor indirect interpretations of vertical conductivity to date. Thus, there is currently no basis for evaluating potential inflow into the roof or floor of the tunnel in the presence of a vertical gradient, unless DOE can develop a supportable bounding estimate of vertical conductivity.
5. The ambient horizontal hydraulic gradient is estimated to be in a range of  $10^{-4}$  to  $10^{-3}$ . However, the method used to calculate hydraulic gradients is faulty and non-conservative, as we noted in our comments on the draft BWIP EA (comment no. 6-15). Also, gradients higher than  $10^{-3}$  can be inferred, even based on the faulty method (see comment no. 6-15 from NRC's Draft EA review.)
6. The factor of 3.1 in each of the estimates of hydraulic conductivity on page 3.4 suggests that the values were obtained by converting order-of-magnitude estimates in terms of feet/sec to meters/sec. It may be more appropriate to convert hydraulic conductivity to meters/sec prior to rounding to the nearest order of magnitude.
7. It is indicated in the document that any aquifer would be incapable of supplying the calculated potential flow rates (page 5.6). The potential for local connections between aquifers has not been considered in reaching

---

FC	:WMGT	kd	:WMGT		:WMGT	:	:	:	:
NAME	:MGordon		:MFliege1		:MKnapp	:	:	:	:
DATE	:85/09/17		:85/09/		:85/09/	:	:	:	:

---

this conclusion. Recent data collected at the Hanford site appears to indicate strong vertical connection between the Rocky Coulee and Cohasset flow tops at DC-20C. While this observation may be an anomaly, it is possible that such vertical connections exist at other locations. Also, there may be other high-conductivity zones such as the fracture zone encountered in the Umtanum interior at RRL-2. These vertical connections and high conductivity zones might provide an increased water supply to allow sustained high water inflows into a tunnel.

- 8. In cases I, II, and III on pages 5.5 and 5.6, it is not clear how the numbers used for fracture and aquifer properties were derived. The numbers used for fracture properties appear to be fairly conservative compared to data in Long and WCC (1984). The 800 ft. head difference between the aquifer and the open tunnel does not appear unreasonable. However, the condition of a meter distance between the aquifer and the tunnel would not likely be present for the host rock units being considered.
- 9. In case III, the tunnel is assumed to intersect the Cohasset flow top. Apparently to avoid the infinite head gradient that occurs mathematically at the discontinuity in head, a one meter distance over which the head drop occurs is assumed. A more appropriate model may be one of the type described by McWhorter (1981); a discussion by Walton (1982) of this type of analytical model is attached (Attachment 3).
- 10. The concept of transient decay of inflow presented on page 5.7 appears to be reasonable; however, the calculated rate of decay and quantity of inflow are impossible to evaluate without more information about the boundary conditions and hydraulic properties assumed. (The McWhorter (1981) analytical solutions attached are appropriate for transient analysis.)

Malcolm R. Knapp, Chief  
Geotechnical Branch  
Division of Waste Management

Enclosures:  
As Stated

Enclosures available in DCC.

FC	:WMGT <i>MG</i> kd	:WMGT <i>MF</i>	:WMGT <i>MK</i>	:	:	:	:
NAME	:MGordon	:MFliegel	:MKnapp	:	:	:	:
DATE	:85/09/17	:85/09/30	:85/09/30	:	:	:	: