

**CERTIFICATE OF COMPLIANCE
FOR RADIOACTIVE MATERIAL PACKAGES**

1. a. CERTIFICATE NUMBER	b. REVISION NUMBER	c. DOCKET NUMBER	d. PACKAGE IDENTIFICATION NUMBER	PAGE	PAGES
9285	2	71-9285	USA/9285/AF-85	1	OF 2

2. PREAMBLE

- a. This certificate is issued to certify that the package (packaging and contents) described in Item 5 below meets the applicable safety standards set forth in Title 10, Code of Federal Regulations, Part 71, "Packaging and Transportation of Radioactive Material."
- b. This certificate does not relieve the consignor from compliance with any requirement of the regulations of the U.S. Department of Transportation or other applicable regulatory agencies, including the government of any country through or into which the package will be transported.

3. THIS CERTIFICATE IS ISSUED ON THE BASIS OF A SAFETY ANALYSIS REPORT OF THE PACKAGE DESIGN OR APPLICATION

- | | |
|---|--|
| <p>a. ISSUED TO (<i>Name and Address</i>)</p> <p>Global Nuclear Fuel - Americas, L.L.C.
P.O. Box 780
Wilmington, NC 28402</p> | <p>b. TITLE AND IDENTIFICATION OF REPORT OR APPLICATION</p> <p>General Electric Company application dated August 4, 1998, as supplemented.</p> |
|---|--|

4. CONDITIONS

This certificate is conditional upon fulfilling the requirements of 10 CFR Part 71, as applicable, and the conditions specified below.

5.

(a) Packaging

- (1) Model No.: SRP-1
- (2) Description

A steel drum for the transport of solid uranium contaminated residues. The packaging is a 55-gallon, open-head steel drum with a minimum 18-gauge shell and bottom head, and a minimum 16-gauge closure lid. The lid is closed by a 12-gauge bolted locking ring with drop forged lugs, one of which is threaded, having a 5/8 inch bolt and nut. The closure includes a gasket. The gross weight of the package, including the maximum weight of contents, is 825 pounds.

(3) Drawings

The packaging is constructed and assembled in accordance with General Electric Company Drawing. No. 0025E98, Rev. 1.

(b) Contents

- (1) Type and form of material
- Uranium-contaminated solid residues.
- (2) Maximum quantity of material per package

775 pounds. The maximum uranium enrichment is 5.0 weight percent U-235. The maximum fissile mass is 104 grams U-235 per package, and the maximum average fissile mass density in the package is 0.5 gram U-235 per liter. In addition, the uranium may not exceed 0.05 weight percent U-234 and 0.025 weight percent U-236.

**CERTIFICATE OF COMPLIANCE
FOR RADIOACTIVE MATERIAL PACKAGES**

1.	a. CERTIFICATE NUMBER	b. REVISION NUMBER	c. DOCKET NUMBER	d. PACKAGE IDENTIFICATION NUMBER	PAGE	PAGES
	9285	2	71-9285	USA/9285/AF-85	2	OF 2

(c) Transport Index for Criticality Control (Criticality Safety Index) |

Minimum transport index to be shown
on label for nuclear criticality control: 0.6

6. In addition to the requirements of Subpart G of 10 CFR Part 71:

- (a) The package must be prepared for shipment and operated in accordance with the Operating Procedures in Section 7 of the application.
- (b) Each packaging must be acceptance tested in accordance with the Acceptance Tests in Section 8 of the application.

7. The package authorized by this certificate is hereby approved for use under the general license provisions of 10 CFR §71.12.

8. Expiration date: October 31, 2008. |

REFERENCES

General Electric Company application dated August 4, 1998.

Supplements dated: October 2, 1998; October 14, 1999; and August 6, 2003. |

FOR THE U.S. NUCLEAR REGULATORY COMMISSION

/RA/
John D. Monninger, Chief
Spent Fuel Licensing Section
Spent Fuel Project Office
Office of Nuclear Material Safety
and Safeguards

Date: August 18, 2003