

2711

not a ML  
u n LL

**FRIANT &  
DOWDEN**

NNA 8712030015

## CONTRACTOR REPORT

SAND86-7004  
Unlimited Release  
UC-70

**Nevada Nuclear Waste Storage Investigations Project**

# **Design of a Machine to Bore and Line a Long Horizontal Hole in Tuff**

J. E. Friant, P. B. Dowden  
The Robbins Company  
22445 - 76th Ave., S.  
Kent, WA 98031-0427

Prepared by Sandia National Laboratories Albuquerque, New Mexico 87185  
and Livermore, California 94550 for the United States Department of Energy  
under Contract DE-AC04-76DP00789

**Printed September 1987**

SAIC/T&MSS

DEC 08 1987

CCF RECEIVED

"Prepared by Nevada Nuclear Waste Storage Investigations (NNWSI) Project participants as part of the Civilian Radioactive Waste Management Program (CRWM). The NNWSI Project is managed by the Waste Management Project Office (WMPO) of the U. S. Department of Energy, Nevada Operations Office (DOE/NV). NNWSI Project work is sponsored by the Office of Geologic Repositories (OGR) of the DOE Office of Civilian Radioactive Waste Management (OCRWM)."

Issued by Sandia National Laboratories, operated for the United States Department of Energy by Sandia Corporation.

**NOTICE:** This report was prepared as an account of work sponsored by an agency of the United States Government. Neither the United States Government nor any agency thereof, nor any of their employees, nor any of their contractors, subcontractors, or their employees, makes any warranty, express or implied, or assumes any legal liability or responsibility for the accuracy, completeness, or usefulness of any information, apparatus, product, or process disclosed, or represents that its use would not infringe privately owned rights. Reference herein to any specific commercial product, process, or service by trade name, trademark, manufacturer, or otherwise, does not necessarily constitute or imply its endorsement, recommendation, or favoring by the United States Government, any agency thereof or any of their contractors or subcontractors. The views and opinions expressed herein do not necessarily state or reflect those of the United States Government, any agency thereof or any of their contractors or subcontractors.

Printed in the United States of America  
Available from  
National Technical Information Service  
U.S. Department of Commerce  
5285 Port Royal Road  
Springfield, VA 22161

NTIS price codes  
Printed copy: A08  
Microfiche copy: A01

Distribution  
Category UC-70

SAND86-7004  
Unlimited Release  
Printed September 1987

DESIGN OF A MACHINE TO BORE AND LINE  
A LONG HORIZONTAL HOLE IN TUFF

by

The Robbins Company  
22445 - 76th Ave., S.  
Kent, WA 98031-0427

J. E. Friant, Program Manager  
P. B. Dowden, Project Engineer

for

Sandia National Laboratories  
P.O. Box 5800  
Albuquerque, NM 87185

Under Sandia Contract 47-2295

Sandia Contract Monitor  
Kenneth D. Young  
Nuclear Waste Engineering Products Division 6314

ABSTRACT

This report describes an engineering design for equipment capable of simultaneously drilling and lining deep horizontal bore holes. The ultimate use of the equipment is to bore up to 600 ft. long, 3 ft. diameter emplacement holes for a nuclear waste repository. The specific system designed is referred to as a Developmental Prototype Boring Machine (DPBM) which will be used to demonstrate the drilling/lining capability in field development tests.

The system utilizes an in-hole electric drive and a vacuum chip removal and handling system. The drilling unit is capable of active directional control and uses laser-type alignment equipment. The system combines the features of a small steerable tunnel boring machine, combined with a horizontally-oriented raise drill, thereby utilizing current technology. All elements of the system are compact and mobile as required for a shaft entry, underground mining environment.

## CONTENTS

|   | PAGE |
|---|------|
| 1.0 INTRODUCTION                          | 1    |
| 2.0 SUMMARY                               | 2    |
| 2.1 Background, Phase I Concept Design    | 2    |
| 2.2 Phase II Objectives and Requirements  | 4    |
| 2.3 Project Approach                      | 6    |
| 2.4 Brief Description of the DPBM System  | 7    |
| 2.4.1 In-Hole Assembly                    | 7    |
| 2.4.2 Mobile Derrick                      | 10   |
| 2.4.3 Mucking System                      | 11   |
| 2.4.4 Liner                               | 12   |
| 2.4.5 Hydraulic Power Unit                | 12   |
| 2.4.6 Welding System                      | 12   |
| 2.4.7 Control Station Assembly            | 12   |
| 2.4.8 Laser Guidance System               | 12   |
| 2.4.9 Muck Tube Assembly                  | 13   |
| 2.5 Operational Scenario                  | 13   |
| 2.6 Conclusions and Recommendations       | 13   |
| 3.0 TECHNICAL DESCRIPTION OF DPBM DESIGN  | 16   |
| 3.1 Review and Evaluation                 | 16   |
| 3.2 In-Hole Assembly                      | 17   |
| 3.2.1 Cutterhead Assembly                 | 17   |
| 3.2.2 Drive Assembly                      | 22   |
| 3.2.3 Steering and Muck Pickup            | 24   |
| 3.2.4 Shield Engagement System            | 26   |
| 3.2.5 Shield Weldment                     | 26   |
| 3.2.6 Laser Guidance System               | 27   |
| 3.2.7 In-Hole Power Unit                  | 27   |
| 3.3 Mobile Derrick Assembly               | 29   |
| 3.3.1 Crawler Unit                        | 29   |
| 3.3.2 Derrick                             | 29   |
| 3.4 Mucking System                        | 32   |
| 3.4.1 Muck Tube                           | 32   |
| 3.4.2 Derrick Telescopic Joint and Elbows | 33   |
| 3.4.3 Transfer Pipe Connection            | 33   |
| 3.4.4 Drop Boxes                          | 33   |
| 3.4.5 Filter Unit                         | 34   |
| 3.4.6 Vacuum Pump Unit                    | 34   |

|         |                                    |    |
|---------|------------------------------------|----|
| 3.5     | Liner                              | 35 |
| 3.6     | Derrick Power Unit                 | 35 |
| 3.7     | Welding System                     | 36 |
| 3.8     | Control Station Assembly           | 36 |
| 3.8.1   | Drill Panel                        | 38 |
| 3.8.2   | Derrick Panel                      | 39 |
| 3.8.3   | Vacuum Muck System Panel           | 40 |
| 3.9     | Vacuum System Control Console      | 40 |
| 4.0     | DPBM OPERATION                     | 43 |
| 4.1     | NTS Site Description               | 43 |
| 4.1.1   | Physical Features                  | 43 |
| 4.1.2   | Geology                            | 45 |
| 4.1.3   | Utilities Available                | 45 |
| 4.1.4   | Environment                        | 45 |
| 4.2     | Site Preparation                   | 45 |
| 4.2.1   | Excavation                         | 45 |
| 4.2.2   | Utilities Required                 | 48 |
| 4.2.3   | Special Provisions                 | 48 |
| 4.2.3.1 | DPBM Handling Equipment            | 48 |
| 4.2.3.2 | Mucking Equipment Revisions        | 49 |
| 4.2.3.3 | Load Bearing Pads                  | 49 |
| 4.2.3.4 | Collaring Fixture                  | 49 |
| 4.3     | System Mobilization                | 49 |
| 4.3.1   | Transport and Handling of the DPBM | 50 |
| 4.3.2   | DPBM Test Arrangement              | 50 |
| 4.3.3   | Instrumentation and Data           | 51 |
| 4.3.3.1 | Console Monitoring                 | 51 |
| 4.3.3.2 | Data Recording                     | 51 |
| 4.4     | Boring Operation                   | 51 |
| 4.4.1   | Setting Up                         | 52 |
| 4.4.1.1 | Derrick Positioning                | 52 |
| 4.4.1.2 | In-Hole Assembly Placement         | 52 |
| 4.4.1.3 | In-Hole Assembly Positioning       | 53 |
| 4.4.2   | Collaring-In                       | 53 |
| 4.4.3   | Liner and Muck Pipe Installation   | 55 |
| 4.4.4   | Drill Withdrawal                   | 57 |
| 4.4.5   | Drill Reinsertion                  | 58 |
| 4.4.6   | In-Hole Power Unit Withdrawal      | 59 |
| 4.4.7   | Test Set Up/Borehole No. 2         | 59 |
| 4.5     | Test Schedule Elements             | 59 |
| 4.6     | Personnel Requirements             | 63 |

## FIGURES

|           | <u>TITLE</u>                                | <u>PAGE</u> |
|-----------|---|-------------|
| Figure 1  | Phase I, Horizontal Drill<br>Concept Design | 3           |
| Figure 2  | Phase II, DPBM Drill and Derrick            | 8           |
| Figure 3  | Phase II, DPBM Muck Handling System         | 9           |
| Figure 4  | Steerable Cutterhead Drive Assembly         | 21          |
| Figure 5  | Five Row Cutter Carbide Insert Cutter       | 23          |
| Figure 6  | Steering and Shield Assemblies              | 25          |
| Figure 7  | DPBM Operating Components                   | 28          |
| Figure 8  | Mobile Derrick Assembly                     | 30          |
| Figure 9  | DPBM Control Station Assembly               | 37          |
| Figure 10 | Vacuum Pump Skid Control Console            | 41          |
| Figure 11 | NTS Site Test Location                      | 44          |
| Figure 12 | NTS Test Site Arrangement, Bore No. 1       | 46          |
| Figure 13 | NTS Test Site Arrangement, Bore No. 2       | 47          |
| Figure 14 | Collaring-In                                | 54          |
| Figure 15 | Liner Installation                          | 56          |
| Figure 16 | Boring Operation Durations                  | 60          |

## TABLES

|         | <u>TITLE</u>                    | <u>PAGE</u> |
|---------|---------------------------------|-------------|
| Table 1 | Condensed System Specifications | 18-20       |

## APPENDICES

|            | <u>TITLE</u>                              |        | <u>PAGE</u> |
|------------|---|--------|-------------|
| Appendix A | INDENTURED DRAWING LIST                   |        | A-1         |
| Appendix B | DPBM ASSEMBLY DRAWINGS                    |        | B-1         |
|            | Horizontal Boring System General Assembly | D35910 | B-3         |
|            | In-Hole Assembly                          | D35911 | B-4         |
|            | Mobile Derrick Assembly                   | D35920 | B-7         |
|            | Mucking System General Arrangement        | D35362 | B-8         |
|            | Muck Tube Assembly                        | D36136 | B-10        |
|            | Liner                                     | B36514 | B-11        |
|            | Hydraulic Installation Power Unit         | D35925 | B-12        |
|            | Control Station Assembly                  | D35927 | B-15        |
|            | Control Console Assembly                  | D35928 | B-16        |
|            | Vacuum Control Console Assembly           | D37173 | B-18        |
| Appendix C | THRUST REQUIREMENT ANALYSIS               |        | C-1         |
| Appendix D | LINER BUCKLING STUDY                      |        | D-1         |
| Appendix E | VACUUM SYSTEM COMPUTATIONS                |        | E-1         |
| Appendix F | RIB AND SEPDB                             |        | F-1         |

## DISTRIBUTION LIST

## 1.0 INTRODUCTION

The work described in this report was performed for Sandia National Laboratories (SNL) as part of the Nevada Nuclear Waste Storage Investigations (NNWSI) Project. Sandia is one of the principal organizations participating in the project, managed by the U.S. Department of Energy's Nevada Operations Office. The project is part of the Department of Energy's program to safely dispose of the radioactive waste from nuclear power plants.

The Department of Energy has determined that the safest and most feasible method currently known for the disposal of such wastes is to emplace them in mined geologic repositories. The NNWSI Project is conducting detailed studies of an area on and near the Nevada Test Site (NTS) in southern Nevada to determine the feasibility of developing a repository in tuff.

One promising method of storing radioactive containers is using long (up to 600 ft.) horizontal boreholes. The boreholes could be drilled into the rib (side) of an underground haulage way. The specifications for the hole, including those for accuracy, the use of a noncontaminating drilling fluid, and for simultaneous lining, require an extension of current drilling technology. Sandia report SAND84-7209, prepared by The Robbins Company under contract 47-2295 Phase I, presented a trade study and a conceptual design of a drilling system to meet the requirements.

This report, covering the effort authorized under Amendment 4 of contract 47-2295, documents the detailed design of the Developmental Prototype Boring Machine (DPBM). A complete set of shop drawings for the DPBM was the principal deliverable item and was transmitted to Sandia under separate cover in October 1985.

In addition to the design documentation, this report includes an operating scenario for testing the DPBM at a specific site in the G-Tunnel complex at the NTS. A layout of the site was made showing recommended additional excavation, placement of units of the system, and additional test support equipment required. An estimated drilling schedule and manpower requirements for a test operation are provided.

The remainder of this report contains three sections and numerous supporting appendices. Section 2 describes the technical basis (background, objectives, and approach) for the study, summarizes the DPBM design and operating scenario for testing, and provides the conclusions and recommendations drawn in this study. Sections 3 and 4 provide, respectively, detailed technical descriptions of the DPBM system and an operating scenario for testing the system.



## 2.0 SUMMARY

The design effort of the DPBM was accomplished in a two-phase project. Phase I of Contract 47-2295 completed an engineering trade study of design options and produced a conceptual system design. A separate Phase I report, SAND84-7209, detailed this effort. This report covers the Phase II effort, detail design of the DPBM.

### 2.1 Background, Phase I Concept Design

In Phase I, a matrix trade-off study evaluated a number of conceptual design options. The highest rated concept was a system featuring a non-rotating drill string with a pull-in liner. A major factor in the selection of this system is its operational independence from the liner. The design allows variable liner thickness, permits the option of a smooth I.D. protruding fittings, and minimizes the structural requirements of the liner. Further, the design allows drilling the hole with or without a liner.

Figure 1 illustrates the Phase I system concept for the simultaneous drilling/lining of horizontal emplacement holes. Principal features include:

- a. A drilling unit with an eccentric cutterhead. This feature allows the drill to be removed from the hole, through a permanently emplaced steel liner. The drill can also be withdrawn from a partially completed hole in the event repairs are required and can be reinserted through the liner to continue operations.
- b. An in-hole gear train and electric motor.
- c. A nonrotating drill string that provides thrust for the cutterhead and liner installation.
- d. A manually controlled laser guidance system.
- e. A vacuum muck removal subsystem.

One of the optional designs studied in Phase I, incorporated the lining as a non-rotating "drill string," providing both the cutterhead and pipe jacking forces. This configuration was of interest because it greatly simplified the drill design by eliminating all of the drill pipe components and their handling mechanisms.

The concept was not selected, however, because it incorporated the lining as an essential structural component of the drill system. At the close of Phase I (June 1985), the hole lining was still viewed as an option, and if




FIGURE 1 - Phase I, Horizontal Drill Concept Design

used, might only be thin shell to prevent water or raveling material from contacting canisters.

When Phase II was initiated, a minimum 3/8 inch thick liner was specified. This added specification re-opened the case for an integrated drill-string and liner. Therefore, before proceeding to detail design of the Phase I selected unit, a critical review of the concept was conducted. This resulted in substantial changes in the concept selected for detail design. Results of this review are discussed in Section 2.3.

## 2.2 Phase II Objectives and Requirements

The principal objective of Phase II was to produce detailed fabrication drawings and specifications for a DPBM. The DPBM was to be a functional version of the horizontal boring machine conceptually designed under Phase I of the contract but suitable for development and demonstration testing.

The DPBM was to be designed with a minimum of sophisticated parts and equipment, without jeopardizing the overall operation or performance of the system. The major performance requirements are those of the Phase I contract, modified by Amendments 4, 6, 7, and 8. These requirements are combined and summarized as follows:

- a. The machine shall be capable of boring and simultaneously lining the required hole with a steel liner. The liner will be 35.0 in. inside diameter with a wall thickness of .375 in. The borehole inside diameter shall not exceed 37.0 in.
- b. The maximum hole depth to be considered for design purposes shall be 600 ft.
- c. The method of drilling shall not result in contamination of the borehole or adjacent rock due to drilling fluids.
- d. The unit shall be as compact as reasonable and operate from a mine drift and cut out 30 ft. long by 11 ft. high by 20 ft. wide. Further, it shall break down into components 4.5 x 4.5 x 15 ft. for lowering into a shaft.
- e. The drill system shall be transportable from one drilling location to another. Set-up and knockdown shall be minimized.
- f. The unit shall comply with all applicable mining codes and standards.
- g. The hole deviation from a straight line shall not exceed 6.0 in. in 100 ft. The total deviation of a 600 ft. hole shall not exceed 12 in.

- h. The drill derrick structure shall provide the adjustment capability to permit holes to be drilled at an angle of  $1.5^{\circ}$  above or below the horizontal.
- i. The unit shall make use of standard components, such as drill pipes, bits, etc., where feasible.
- j. The centerline of the bore above the haulage way floor shall be 72 in.
- k. Following completion of the bore, or to perform machine repairs or to replace cutters, the inhole drill shall be capable of being withdrawn through the liner and shall be capable of reinsertion.
- l. Instrumentation, console, and controls shall provide for recording equipment and measurements for a permanent performance record for subsequent evaluation.
- m. Steel liner sections shall be welded to provide a continuous, watertight liner.
- n. The DPBM system shall be capable of operating in an underground environment and drilling rock having the following characteristics:

UNDERGROUND ENVIRONMENT

REPOSITORY

G-TUNNEL

|                          |           |          |
|--------------------------|-----------|----------|
| Ambient Rock Temp.       | 35°C      | 24°C     |
| Air Temperature          | 20 - 35°C | 20 - 30° |
| Relative Humidity        | to 100%   | to 100%  |
| Altitude above Sea Level | 3400 ft.  | 6300 ft. |

ROCK PROPERTIES

Repository:

- densely welded, devitrified tuff;
- fracture spacing approximately seven per ft.;
- density 2.2 gms/cm<sup>3</sup>;
- unconfined compressive strength 16,000 to 33,000 psi;
- rock may contain vugs (voids);
- uniaxial strain to failure approximately .41 to .97%;
- and
- rock may be saturated.

G-Tunnel:

- densely welded tuff;
- fracture spacing at least 12 per ft.;
- rock contains pumice inclusions and vugs, abrasive;

- unconfined compressive strength of 12,000 to 15,000 psi; and
- rock may be saturated.

A second objective, in addition to designing the drilling system, was to develop an operating scenario for initial tests at a specific location in the G-Tunnel complex of the Nevada Test Site. The scenario includes equipment layout, utility requirements, schedule, manpower requirements, and a step-by-step procedure for setup and operation of the DPBM. The intention is to drill two holes in a welded tuff formation between two existing drifts approximately 250 ft. apart.

### 2.3 Project Approach

Before initiating the Phase II effort detail design, a project review was conducted with three objectives:

- a. Review and assure validity of the Phase I conclusions;
- b. Assess current repository and project requirements; and
- c. Simplify the drilling system, with goals of increasing reliability and reducing costs.

The review concluded that an option to drill the repository hole with or without lining was no longer necessary. From a further understanding of the geology involved and an emphasis on long-term retrievability, simultaneous drill/line appears to be the most viable option. Also, two other parameters had changes: (1) the proposed operational drift height was lowered by 1.0 ft.; and (2) preliminary testing of the DPBM would occur at a higher elevation. With the above requirement modifications and the effort to simplify the DPBM system, the following changes were made to the Phase I concept design:

- a. Significant simplification of the drill and derrick units resulted by using the required liner to transmit thrust and torque reaction. This change eliminated the independent drill string, stabilizers, and related handling equipment.
- b. The muck tube function and design was revised to include removal and reinsertion of the in-hole drill unit.
- c. The drill electric drive motor is air cooled, rather than water cooled. This eliminated the need for a closed loop water supply in-hole.
- d. The method of steering on the Phase I design pivoted the rear of the drill assembly about a fulcrum located near the cutterhead. This was changed to a direct wedging arrangement using shoes at the forward end of the drill assembly. A ball joint was provided at the rear of the drill to permit the pivoting movement. The change eliminated a complex yoke and universal joint.

- e. The method of isolating the cutterhead load from the liner insertion thrust was redesigned. The modified system isolated stabilizer shoe friction, as well as liner friction from the cutterhead thrust. As overload protection for the cutterhead, instrumentation was included to warn the operator if "bottoming out" of the cutterhead isolation system had occurred.
- f. The laser beam position was moved from a perimeter location to the bore centerline. This position eliminated the requirement for roll correction.
- g. The in-hole hydraulic power pack was changed to a self-contained unit behind the motor, rather than being a power takeoff of the gearbox. This arrangement can provide hydraulic pressure without cutterhead rotation. This feature allows cutterhead indexing and positive functioning of the stabilizer/steering shoes for withdrawal and reinsertion of the drill unit.
- h. The tricone bit on the cutterhead and its associated air supply has been replaced by an improved cutter arrangement. This simplified the umbilical connection down-hole and replaced a low reliability component.
- i. The derrick system was rotated 90° on its carrier to permit side loading of the muck tube and liner. This makes installation of the liner physically simpler and reduces the head room requirement above the derrick.
- j. The vacuum system components were rearranged to provide smaller individual skid mounted elements. Total capacity was unchanged, but two drop box units in tandem are used. The filter unit was separated from the pump unit, each mounted on separate skids.

## 2.4 Brief Description of the DPBM System

Artist sketches of the drill and derrick are shown in Figure 2 and the muck handling system is shown in Figure 3. These sketches show major components of the system and how they might be arranged in the haulageway of a nuclear waste repository.

The immediately following paragraphs are summary descriptions of the principal components. Further details are located in Section 3 and Appendix 1 is a complete indentured parts list. Appendix 2 contains the assembly drawings of the principal system components.

### 2.4.1 In-Hole Assembly, Ref. Drawing D35911

The drill unit operates from within a 36 in. outside diameter shield. When the drill is removed after completing the hole, the shield is left behind and forms part of the continuous liner. The drill unit is anchored




FIGURE 2 - Phase II, DPBM Drill and Derrick




FIGURE 3 - Phase II, DPBM Muck Handling System



into the shield during the boring operation by a hydraulically operated locking device.

The cutterhead and its drive system can be pivoted about a torque reacting ball joint by means of four hydraulic cylinders. The pivoting action allows for directional corrections as well as for positioning the cutterhead for withdrawal. While boring, the cutterhead rotates about a point not its geometric center. This eccentric rotation permits the 34 in. diameter cutterhead to bore a 37 in. diameter hole. When the cutterhead is to be withdrawn from the liner (or inserted) it is indexed and moved to the center of the shield. Since the maximum diameter of the drill unit in this position is only 34 in., the drill clears the inside of the shield and liner.

The cutterhead is fitted with three tungsten carbide insert cutters on the head. The two inside cutters are cantilever-mounted and the outside, or gage cutter, is a three-row, saddle-mounted unit. This arrangement provides dynamic balance of the head while boring. Radial forces are stabilized by hydraulically loading the upper steering shoe against the bore.

Cutterhead rotation is provided by a 125 hp, air-cooled electric motor driving through a planetary gearbox. Cutterhead thrust, as well as lining insertion thrust, is provided by hydraulic cylinders mounted on the derrick. To prevent damage by overloading, cutterhead thrust is limited by a passive hydraulic cushion integral with the drive unit. Instrumentation is provided to control and monitor the thrust which is applied to the cutterhead.

The muck port into the vacuum tube is located immediately behind the cutterhead in the 4 to 5 o'clock position. Cuttings are propelled into the port by a single fixed blade mounted adjacent to the gage cutter on the cutterhead.

In-hole hydraulic power for steering, engaging the drill into the shield, etc., is supplied by a separate hydraulic pack. This 5 HP pack is mounted on a trailing unit immediately behind the ball joint. The functioning of cylinders is controlled by solenoid valves. This arrangement permits an umbilical connection with only electrical power and signal cables.

#### 2.4.2 Mobile Derrick, Ref. Drawing D35920

The derrick unit provides the thrust and torque reaction for the drill. It is mounted on a hydraulically driven crawler unit. The in-hole drill components can also be mounted on the derrick for transportation to the borehole locations.

When in operation, four corner-mounted leveling jacks lift the crawler assembly off the floor. These are also used to set the derrick at the correct angular position and height before boring is started. The main thrust is reacted into the rear wall by three jacks attached to the rear

of the derrick. Torque reaction is provided by the floor jacks and two jacks which are in contact with the repository roof.

The thrust is provided by two hydraulic cylinders, mounted vertically above below the bore centerline. The thrust is transmitted into the liner by a jacking collar attached to the cylinders. The torque is reacted by gripping the liner wall at two places on the horizontal centerline with hydraulically loaded calipers. The jacking collar slides on a pair of horizontal guide tubes which carry the torque reaction and dead weight loads.

The thrust cylinder stroke is 9.5 ft., which permits clearance for bolting up the muck pipe sections as new liner segments are added.

Attached to the rear of the jacking collar is a 90° muck tube elbow. A telescopic section attached to the elbow connects to the muck tube inside the liner.

When removing the drill from the bored hole by pulling on the muck tube, long stroke mechanical jacks normally nested in the guide tubes are extended to contact the forward tunnel wall and provide load reaction.

The hydraulic supply for the derrick and crawler functions is provided by an independent skid-mounted power unit.

#### 2.4.3 Mucking System, Ref. Drawing D35632

The mucking system, located downstream of the derrick, consists of a transfer pipe, two drop box units, a filter unit, and the vacuum pump unit. The first drop box is connected to the derrick muck pipe elbow by means of a rigid transfer pipe. Ball joints at each end of the pipe and a telescopic unit attached to the front end of the drop box permit the required articulation as the derrick is stroked. The holding capacity of the collection boxes is compatible with the muck quantity produced by one 8 ft. drilling stroke.

The two sequential drop box units separate most particles by deceleration and deflection. A vibrating, coarse mesh filter traps finer particles.

Dust particles are carried to the primary filter unit. This unit contains a number of fabric cartridges which are periodically purged by backflushing with a charge of compressed air. The dust collected is discharged by an inclined, enclosed screw feeder.

The cleaned air then flows to the vacuum pump unit. A secondary polishing or standby safety filter is located on the vacuum unit. The vacuum pump (a lobe-type blower) discharges into a plenum chamber and then via a silencer to atmosphere. The system removes harmful respirable dust particles.

During the time pipe and lining sections are added, the muck collected in the drop boxes is expelled by a pneumatic discharge system.

#### 2.4.4 Liner, Ref. Drawing D36514

The liner is a 36 in. outside diameter steel pipe with a wall thickness of .375 in. The segment length is 8 ft. Pipe is standard commercial tolerance except that ends are sized for alignment and beveled for the welding operation.

#### 2.4.5 Hydraulic Power Unit, Ref. Drawing D35925

This unit combines the hydraulic power supply and the main electric motor control cabinet. A single 75 HP electric motor drives a dual pump system that can supply both high flows at low pressure or low flows at high pressure, as the operating sequence demands.

#### 2.4.6 Welding System

An automatic orbital-type welder will be used to join the liner sections. The welding head is located on a circular track clamped adjacent to the pipe joint. The welding action is controlled by a variable duration pulse system which controls the puddle flow, depending on the arc location. A short test program to set the welding machine operating parameters is required. The test program could also be used to evaluate the best type liner alignment fixture to use.

#### 2.4.7 Control Station Assembly, Ref. Drawing D35928

The main operating controls for the drill, derrick and mucking system are located on the console. Read outs and warning lights on the console continuously monitor the important operating parameters. The controls are interlocked so that the mucking system must be operating before boring begins, and continues to operate after boring ceases to avoid clogging the system. Taps are provided to allow addition of a data recording system.

#### 2.4.8 Laser Guidance System

The laser beam is provided by a unit mounted rigidly to the tunnel wall behind the machine. A clearance hole in the derrick main frame provides a window. The laser is set up at the time of collaring-in the machine and must not be disturbed until the hole is complete. The laser is beamed through the bore centerline to a photo-diode array target located just aft of the ball joint. Steering control is manual in response to a display screen located at the control console.

#### 2.4.9 Muck Tube Assembly, Ref. Drawing D36136

In addition to conveying muck out of the hole, the muck tube is used to pull or push the drill unit in and out of the liner. The tube sections, 8 ft. long to match the liner segments, are joined together with a rigid four-bolt flange. The joints are sealed by a spigot-mounted O-ring. Hangers are attached to the tube to support the electric power and control cables.

#### 2.5 Operational Scenario

A contract change redirected the operational scenario effort from a generic situation to the specific site of initial field trials. A welded tuff formation is exposed at the far end of the G-Tunnel complex at the Nevada Test Site. The site was examined and is well suited for the tests for the following reasons:

- a. The rock is a welded tuff, a little lower in compressive strength and with a lower rock quality than is expected in the repository. Rock samples have been analyzed.
- b. The location permits drilling from one drift to another. This adds an emergency recovery feature to the test. The in-hole unit could be extracted by mining from the break-through end. The area has room to drill at least two 250 ft. long holes.
- c. The use of the area will not interfere with existing test plans.
- d. Utilities, power and labor support are close at hand.

The elevation, however, is over 6,300 ft. This substantially reduces the effectiveness of the vacuum muck removal system. However, since the vacuum unit was originally designed for a 600 ft. borehole and the experimental holes will be only 250 ft., the same system can be used.

Preliminary layouts of the site were made. Locations requiring additional excavation were identified, and special tooling requirements were established. A tentative study of operating procedures and manpower requirements was completed. The results are useful for reference and as a guide only. The exact schedule and test requirements will not be known until a definitive test plan is established. The information provided in Section 4.0 of this report can be used as baseline data for scheduling and costing an overall test program.

#### 2.6 Conclusions and Recommendations

The following conclusions and recommendations are not listed in any order that indicates relative significance:

- a. The DPBM system described in this report will provide a vehicle for demonstrating a production Horizontal Boring Machine. The principal differences between the DPBM unit and a production unit involve mobility, set-up/tear down, pipe handling, wear life and muck handling behind the system. All basic principles are intended to be equivalent to a production unit and all technology is considered available at this time.
- b. A re-evaluation of the operating mode determined that reliability of the boring operation could be increased and cost decreased by using the hole liner as an integral part of the drilling operation. Analyses showed that a maximum of 1.5 million lb. of thrust might be required to insert the lining, and that a .375 in. thick wall of API 5LX-52 pipe is sufficient to ensure against buckling failure.
- c. Two areas have been identified as requiring additional development before DPBM trials:
  - (1) Liner Welding. No automated, off-the-shelf equipment was found for welding the liner sections at an acceptable speed. Equipment which could be adapted was found, but exact setup, travel speed, bead alloys and number of passes for the weld operation must be established by a small testing program.
  - (2) Filter Cart. When physical size limitations for system components were reduced, a standard "bag house" set-up was precluded. Standard filter elements can be used, but the exact method of mounting the elements and installing the cleaning cycle equipment will have to be established before fabricating the filter cart.
- d. The design effort to minimize the effects of abrasive wear in the muck pipe, elbows, and drop boxes, etc., was not completed during this project phase. Abrasive wear should be carefully observed during DPBM tests to locate critical points and to determine how to increase the life of the affected components.
- e. Physical barriers for noise reduction should be considered for the vacuum muck system. The logical location of the muck system components for the trials of the DPBM is in the access haulage way. Without additional sound barriers, the noise will likely be annoying if not disruptive.
- f. The information provided in the operating scenario will be useful in scheduling, staffing and costing a definitive test program. However, because the detailed scope of the test trials was not established at the time this report was written, individual function times should be reviewed before use.

g. A recommended course of action is to build the DPBM, and at the same time create a definitive test plan. The purpose of the tests should be multipurpose and include:

- (1) demonstration of the ability of the drill to perform its function in a repository environment;
- (2) generation of parametric operating data to further refine a production situation; manpower, cost and schedule; and
- (3) design evaluation of the drill and an analysis of its reliability, availability and downtime.

These actions would provide the confidence level needed to make decisions on the layout of the repository so far as the emplacement hole drilling for the horizontal emplacement option is concerned.

### 3.0 TECHNICAL DESCRIPTION OF DPBM DESIGN

#### 3.1 Review and Evaluation

Before proceeding with detailed design and drawing of the conceptual unit, several critical reviews were held to determine whether or not the approach of the conceptual design study was valid. The conceptual approach for simultaneous boring and lining a long, accurate, horizontal hole was achieved by combining a small, steerable tunnel boring machine with the large thrusting capability of a horizontally-oriented raise drill. The use of an in-hole motor eliminated the rotating drill string and permitted an active steering capability.

A vacuum pneumatic muck removal system was selected through a process of elimination. Liquid drilling fluids were undesirable from the rock contamination stand point, and also presented logistic problems in basically dry repository formations. Mechanical muck removal systems were difficult to fit into the limited space available and lacked reliability in a long, 37 in. diameter hole. A pneumatic pressurized system would fail if leakage into the rock occurred. In contrast, a vacuum system provides cooling air in-hole, locates the mechanical systems outside of the hole and keeps the bore relatively free of dust, making a laser guidance system feasible.

The major performance assumptions of the Phase I conceptual study were deemed valid and again selected. However, when canister retrievability became essential to the repository, the originally optional hole casing, or liner, became a requirement. The major change in concept, therefore, was to reconsider using the liner as the nonrotating drill string during boring. The advantages of this approach include:

- a. The load bearing capacity of the in-hole drill-to-shield engagement can be significantly reduced. The thrust load path of the drill string design was down the string, through the attachment mechanism to the shield. Since the liner was being pulled into the hole, this connection had to sustain both the frictional load of the entire liner as well as provide cutterhead thrust. If the thrust is applied directly to the liner at the derrick, only the cutterhead load passes from the shield, through the engagement mechanism to the in-hole drive unit and cutterhead. Since frictional forces on the liner could be as much as ten times the cutterhead thrust, load capacity may be correspondingly reduced, and reliability increased.
- b. The elimination of the drill string is a direct cost saving and also reduces handling time.
- c. The elimination of the drill string leaves sufficient room inside the liner for personnel access to the in-hole assembly. In the event of a failure, persons could go in the hole to investigate.

- d. The torsional stiffness of the liner is very high. This virtually eliminates cumulative wind-up problems of the drill.
- e. During drilling, the liner welds are in compression rather than in tension, which is structurally safer.
- f. The maximum stress in the liner is adjacent to the derrick rather than at the in-hole unit. Any structural failure is likely to occur out of or near the end of the hole, rather than deep in the bore.

An analysis was conducted to estimate the maximum thrust which could be required to insert the liner to a depth of 600 ft. Appendix 3 states the assumptions and shows the computations. A total of 1.5 million lbs. of thrust will overcome the combination of cutterhead thrust and pipe jacking forces.

In the thrust-liner operating mode, the liner will be in compression, and the wall thickness must be adequate to resist shell buckling. An analytical study was conducted to determine the minimum shell (liner) thickness and material which would provide structural integrity. Appendix 4 contains the analysis and shows that an API 5LX-52 pipe with a wall thickness of .375 or greater is adequate. Optionally, pipe fabricated from A-36 steel at .5 in. minimum wall thickness is acceptable.

The only potential disadvantage of the liner-thrust operating mode is that the liner becomes an integral part of the boring process. Since the lining requirement is not likely to be rescinded, the associated equipment cost savings and reliability increases warranted revising the conceptual drill design. Detail design of the revised concept, therefore, proceeded. A description of the components is contained in the following paragraphs.

Table 1 contains the final system specifications for the DPBM as designed during Phase II.

### 3.2 In-Hole Assembly, Ref. Drawing D35911

#### 3.2.1 Cutterhead Assembly, Ref. Drawing D36120

The cutterhead arrangement is designed to fit through the liner for retrieval of the drill and also to meet the minimum out-of-balance force allowance.

Three each, multi-row carbide insert cutters are used as shown in Figure 4. Two are the cantilevered conical type, each having five rows of inserts (kerf cutters). The row spacing on each cutter is different to achieve balance and single tracking. The cutter shafts are cast as an integral part of the pedestal mount for strength reasons, and the pedestals are bolted to the machined cutterhead. Bolting allows the



TABLE 1

CONDENSED SYSTEM SPECIFICATIONSEmplacement Hole

|                |                            |
|----------------|----------------------------|
| Bored Diameter | 37 in. (new cutters)       |
| Bore Length    | to 600 ft.                 |
| Bore Angle     | Horizontal $\pm 1.5^\circ$ |

Liner

|                  |   |
|------------------|---|
| Diameter         | 36 in. O.D.   |
| Length           | 8 ft.   |
| Thickness        | .38 - .75 in.   |
| Material Options | .38 in. wall - API 5LX52 (52 ksi yield)<br>.50 in. wall - API 5L (35 ksi yield) |

Drill Unit

|                                      |  |
|--------------------------------------|--|
| Cutters                              | 3 multi-row tungsten carbide insert, 2 cantilevered conical (5 row) and 1 saddle mounted (3 row) |
| Instantaneous Penetration Rate       | 2 in./min. (10 ft./hr.)  |
| Cutterhead Total Thrust              | 150,000 lbs.   |
| Cutterhead Torque                    | 20,000 lb.ft.  |
| Cutterhead RPM                       | 30.3   |
| Gear Reducer                         | Two stage planetary, compound first stage; overall ratio 57.80                                   |
| Drive Motor                          | 125 HP; 1,800 RPM; 460 V; 3 Phase; 60 Hz.  |
| Diameter of Shield (Shoes Retracted) | 36 in.   |
| Length (less power unit)             | 14 ft. 3 in.   |
| Weight (less power unit)             | 18,500 lbs.  |

TABLE 1, continued

|   |  |
|---|--|
| <u>In-Hole Power Unit</u>                           |  |
| Motor   | 5 HP; 1,800 RPM; 460 V; 3 Phase; 60 Hz.                          |
| Pump  | Dual output (1.5/.38 gpm) Radial Piston                          |
| Fluid   | Petroleum base   |
| Pressure (maximum)                                  | 4,500 psi. (Maximum relief)                                      |
| Length  | 8 ft.  |
| Weight  | 950 lbs.   |
| <u>Derrick</u>                                      |  |
| Maximum Thrust                                      | 1,500,000 lbs.   |
| Maximum Pullback Force<br>(Limited by relief valve) | 100,000 lbs.   |
| Thrust Feed Rate                                    | 0 - 4 in./min.   |
| Rapid Traverse                                      | 44 in./min. (extend)<br>89 in./min. (retract)                    |
| Crawler Speed                                       | 0 - 2 mph (175 ft./min.)   |
| Length  | 17 ft. 10 in.  |
| Height (with crawler)                               | 9 ft. 6 in.  |
| Width (with crawler)                                | 6 ft. 10 in.   |
| Weight (with crawler)                               | 41,900 lbs.  |
| <u>Derrick Power Unit</u>                           |  |
| Motor   | 75 HP; 1,200 RPM; 460 V; 3 Phase; 60 Hz.                         |
| Pumps   | Variable Displacement, 72 gpm<br>Variable Displacement, 11.5 gpm |
| Fluid   | Petroleum Base   |
| Pressure  | 4,500 psi (Maximum relief)                                       |

TABLE 1, concluded

|        |              |
|--------|--------------|
| Length | 10 ft. 0 in. |
| Width  | 4 ft. 3 in.  |
| Height | 6 ft. 6 in.  |
| Weight | 5,000 lbs.   |

Vacuum Mucking System

|                             |   |
|-----------------------------|---|
| Maximum Capacity            | 5.5 tons per hr.                          |
| Maximum Length              | 600 ft. (In-hole)                         |
| Muck Pipe Inside Diameter   | 7 in. (In-hole)                           |
| Maximum Vacuum              | 18 in. Hg.                                |
| Vacuum Pump Capacity        | 2,400 scfm                                |
| Motor                       | 150 HP; 1,800 RPM; 460 V; 3 Phase; 60 Hz. |
| Drop Box Discharge Pressure | 20 psi.                                   |

\*Note: Vacuum system performance is dependent on altitude.

Laser

|                         |                |
|-------------------------|----------------|
| Power                   | 5 mw.          |
| Spot Diameter (600 ft.) | .6 in.         |
| Manufacturer            | Spectraphysics |

Utility Supplies

|             |                                 |
|-------------|---------------------------------|
| Electricity | 460 V; 350 KVA; 3 Phase; 60 Hz. |
| Air         | 90 psi.; 150 scfm               |




FIGURE 4 - Steerable Cutterhead Drive Assembly

cutters to be in close proximity to each other and does not compromise assembly or removal of the cutters. The outer (gage) cutter, has three rows of inserts and is saddle mounted on a welded-in-place pedestal. Figure 5 shows a similar five-kerf cutter.

The cutterhead is basically a thick plate structure onto which the cutters are mounted. It is then bolted to the flanged end of the gearbox output shaft. A spiraled, fixed blade is welded to the cutterhead to sweep rock chips rearward, toward the vacuum inlet.

### 3.2.2 Drive Assembly, Ref. Drawing D36121-1

The drive assembly provides cutterhead rotation and also carries the cutter thrust and lateral loading.

The main drive is a sealed 125 HP, 1,800 RPM electric air-cooled motor. The motor casing is designed to carry the full thrust and torque between the cutterhead and the steering system ball joint. A motor overtemperature indicator is provided at the console.

A double reduction planetary gearbox provides the required output torque and speed. The gearbox output shaft, to which the cutterhead is bolted directly, is supported by a triple bearing arrangement. Axial loads are reacted by a tapered roller thrust bearing. Moment loads are reacted by a forward mounted cylindrical roller bearing and by a rear mounted tapered roller bearing which also serves to preload the thrust bearing. A dual seal arrangement at the rear of the cutterhead mounting flange prevents oil leakage and ingress of dirt. Gearbox oil temperature is continuously monitored at the console.

The entire drive shaft and bearing assembly can float a distance of .75 in. relative to the gearbox outer housing. The assembly is normally thrust forward by pumping hydraulic fluid into the annular cavity behind the rear bearing housing. When thrust is applied to the cutterhead, the fluid pressure in the cavity rises, and is controlled by a pilot-operated check valve.

Because the thrust capability of the derrick unit is beyond the structural capability of the drill unit, a hydraulic isolation and monitoring system is used. Advance rate of the drill is controlled at the derrick and is limited to maintain limit load forces. If the load on the hydraulic isolation ring, located at the rear of the bearing housing, exceeds the limit (designed to be 3,500 psi), or should the system lose fluid, the drive assembly moves toward the rear. A proximity switch located in the gearbox cutter housing detects the "bottoming out." An interlock system shuts down the drilling unit and illuminates a warning light on the operator's console.

To permit removal of the drill through the liner, the cutterhead must be indexed to a specific position. A proximity switch is used to detect the location and trigger an indicating lamp at the console.




FIGURE 5 - Five Row Cutter Carbide Insert Cutter

### 3.2.3 Steering and Muck Pickup, Ref. Drawing D36105

Steering is achieved by radial movement of the cylinder actuated steering wedges against the gripping(stabilizer) shoes, as shown in Figure 6.

The basic method of making directional corrections is to move the head in the direction of the desired motion. This causes the cutterhead to slightly overcut in the direction it was moved and to undercut on the diametrically opposite side. The undercutting forms a ramp in the bore which the shield is obliged to follow. Thus, if the bore is descending below the true path, the cutterhead is raised slightly and the shield is forced upward by the resultant ramp. Sideways deviations are corrected in a similar way.

Steering corrections are necessarily limited because of the rigidity of the attached liner. Deviations must be detected as they occur, and steering corrections must be as small as possible. Normally, the gage of the bore at the floor line should be exactly in line with the bottom of the liner. As the cutters wear, the gage will tend to rise above the liner bottom, and the bore will tend to rise. This can be counteracted by lowering the cutterhead to compensate for such cutter wear. The steering deviation is monitored by the laser and in-hole target. As the steering corrections must be very small, and the angular change of the drill unit very slight, (about the same order as the resolution of the laser inclinometer), linear transducers are incorporated in the steering cylinders to more accurately monitor steering movement.

Apart from controlling direction, the steering cylinders (Figure 4) are also used to stabilize the drill in the bore. There are two shoes or grippers, one upper and one lower. The lower one remains in contact with the bottom of the shield at all times, while the upper one is pressed by hydraulic action of the upper cylinders against the roof of the bore. The degree of pressure can be adjusted from and monitored at the control console. The pressure should be adjusted so that the cutterhead is just stabilized, i.e., does not bounce around in the bore. If the pressure on the gripper shoe is above this level, the frictional sliding forces between the gripper shoe, the liner and bore could become excessive. The friction loading on the gripper shoe is reacted by a shear block located on the upper side of the gearbox housing.

The entire drive train and cutterhead can pivot about a splined ball joint arrangement, which is an integral part of the shield engagement mechanism. The outer part of the joint is fixed relative to the shield. The longitudinal crowned splines permit angular movement of the drive train but resist rotational movement about the drive train axis.

Cylinder actuated wedges (Figure 4) in a quadrant arrangement are located at the forward end of the gearbox housing. The shoe wedge arrangement permits radial movement of the cutterhead from cylinders which are mounted parallel to the axis of the drill. The steering cylinders are interconnected hydraulically in a manner that, during a steering motion,




FIGURE 6 - Steering and Shield Assemblies



one cylinder extends as much as its opposite partner retracts, thus maintaining the upper shoe in its stabilizing location.

After the location is set, the lower cylinders are hydraulically locked into position to assure that there will be no movement of the head relative to the bottom of the bore. The upper steering cylinders are not locked in position but apply a controlled pressure for stabilizing purposes as described previously.

To retract the entire drill, the head must be lowered to clear the top of the liner, after it has been indexed as (rotated) to the removal position. Both sets of steering cylinders are retracted to pull the upper shoe clear of the liner. A leaf spring attached to the upper shoe forces the shoe down in case of hang up.

The muck tube passing through the drill also forms part of the steering assembly structure. The muck entry port is cast into the lower steering shoe at the 5 o'clock position as shown in Figure 6. The entry is curved in the natural direction that muck will be struck by the cutterhead blade. A specially cast muck tube, extending from the rear of the bottom shoe to the invert level beneath the shield engagement mechanism, carries the muck through the machine. Because of the necessary curvature of the tube and consequent high-muck impact, a hard-wearing weld overlay will be applied on the inside at critical locations to resist abrasion.

#### 3.2.4 Shield Engagement System, Ref. Drawing D36106

During boring operations, the drill unit must be locked into the shield by a mechanism which will transmit both cutterhead thrust and torque reaction loads. Because of the drill removal features, the shield side of this mechanism must protrude into the shield bore as little as possible. The attachment consists of two engaging plates which have short buttress-like serrations (Figure 6). The serrated plates can spread the thrust loads over several "threads" to provide the shear area required for safe operation. The two sets of plates are hydraulically activated and are located 180° apart on the horizontal centerline.

Proximity switches on the mechanism provide indications at the control console that the plates are properly engaged before boring is started.

#### 3.2.5 Shield Weldment, Ref. Drawing D36130

The shield is basically a heavy wall length of pipe (Figure 6), cut away at the top of the front section to provide clearance for the stabilizer shoe. A pair of serrated engagement plates, as described in paragraph 3.2.4, are welded in at the rear end. The rear edge of the shield has a beveled weld preparation groove for the attachment of the first liner segment. The shield is an expendable portion of the drill and becomes a permanent part of the hole liner.

### 3.2.6 Laser Guidance System, Ref. Drawing D36106

The remote laser target is mounted inside the steering ball joint (Figure 4) and is, therefore, an integral part of the shield engagement assembly. Because it is on the centerline of the bore, any roll of the drill does not significantly alter the x and y axis readout.

The unit measures x and y (horizontal and vertical) axis displacement and yaw angle (commonly known as "lead") by optical means, and incorporates inclinometers to measure roll and pitch (commonly known as "look-up"). The unit, which will be supplied by Zed Instruments Ltd. (U.K.), is a specially designed, very compact version of a standard TBM alignment system.

A display at the control station provides digital readouts of the various offsets. In this application, the important data are the x and y axis deviations. The roll should be negligible, and the yaw and pitch angles are relative to the cutterhead drive axis, not the actual bore angle at any particular point. If a deviation is noticed on x or y axis, an immediate small correction should be applied. In practice, deviations are corrected within a few millimeters of offset.

The effect of steering corrections may not be immediately apparent to the operator because of the effect of the rigid liner, and to assist in steering, a permanent record of deviation change is necessary as boring proceeds. This is provided by a printer unit which is a standard Zed accessory.

### 3.2.7 In-Hole Power Unit, Ref. Drawing D36135

Hydraulic power for the drill is provided by a self-contained, electric drive unit, as shown in Figure 7. The unit is located immediately behind the drill in the first liner section behind the drill shield. It is mounted on rollers so that it can be pulled back through the liner should repairs be required during the boring operation.

The power unit's principal components are a 5 HP electric, 460 V AC motor, a dual output 1.5/.38 gpm hydraulic pump, and solenoid valves for control of the drilling functions. These valves are remotely activated from the control console. The console also monitors oil reservoir level and temperature.

In operation, the power unit, along with a section of muck pipe, would be subassembled adjacent to the drill derrick. The hydraulic connections are made to the drill unit. After the drill shield has been collared in a full derrick stroke, the liner with power unit is loaded into the derrick and the liner section is welded to the drill shield.




FIGURE 7 - DPBM Operating Components

### 3.3 Mobile Derrick Assembly, Ref. Drawing D35920

#### 3.3.1 Crawler Unit, Ref. Drawing D35985-1

A crawler unit (Figure 8) with a high load carrying capacity was chosen as the means of locomotion of the derrick for maneuver-ability in confined spaces. Its low travel speeds are perfectly acceptable in a development prototype machine. As the design of the repository and its mode of construction finalized, rubber-tired or a rail-mounted system could be considered. The derrick unit is mounted on the crawler frame by a bolted arrangement, so it could be removed easily for shipping purposes.

The design uses standard commercially available components as far as possible, including tracks, idlers and tensioners. The drive is provided by piston-type hydraulic motors and planetary reducers. A spring-loaded brake in each drive will hold the unit in case of hydraulic failure on an incline.

The hydraulic supply for crawler movement (Figure 7) is provided by an external hydraulic power unit (Pack "B"). The DPBM design of the power unit is skid mounted, although a production unit would probably be equipped with wheels.

The crawler is used for mobilization of the DPBM only. The dead weight of the crawler and the derrick are removed from the tracks during the boring operation by means of leveling jacks attached to the derrick frame.

#### 3.3.2 Derrick, Ref. Drawing D35921-1

The derrick configuration, as shown in Figure 8, is similar to a horizontally oriented raise drill, without a rotary drive. Two large thrust cylinders are attached by a crosshead which slides along two rigidly mounted guide tubes. The tubes carry the dead weight of the crosshead components and transmit the torque reaction from the liner to the derrick chassis. The tubes are mounted rigidly to the rear main frame and supported at the forward end by a headframe. The thrust cylinders are located one above the other on the vertical centerline.

Thrust is applied directly to the liner by a jacking thrust collar. Because of potential misalignment, the collar is attached to the crosshead via an elastomeric joint, which ensures that any eccentric loading is minimized. The surface which mates with the liner is at a 15° angle to match the liner weld preparation. In addition to thrust, the collar must also transmit the drilling torque reaction. Sliding gimbal joints at the top and bottom of the collar are used to prevent rotation yet permit alignment in the plane of the collar.

The liner is gripped by two pairs of opposed hydraulic clamping cylinders, on each side of the horizontal centerline, which apply a pinching action directly to the liner wall, similar to a caliper brake. Narrow slots in the collar are provided to allow the electrical cables to exit from the

**FIGURE 8 - Mobile Derrick Assembly**

liner without passing entirely through the crosshead. This permits loading of the liner into the derrick with the cable prestrung to avoid disconnecting and reconnecting the cables for each addition.

Four motorized leveling screw jacks on each corner of the derrick frame are used to relieve the load from the crawler and to orient the derrick at the required boring angle.

The thrust loads are transmitted to the rear wall of the tunnel by three thrust reaction jacks mounted on the main frame of the derrick. The jacks are located in a triangular arrangement. The upper, center jack is a mechanical screw jack, and the two lower jacks are hydraulically operated. Torque reaction is provided by the floor jacks and two vertical screw jacks located on each side of the main frame which are extended to contact the roof.

A muck elbow is required in the mucking system at the derrick to route the air and muck flow toward the separation units. The elbow is located immediately behind the crosshead and is attached to the in-hole muck pipe by means of a hydraulically pressurized telescopic joint. This joint serves two functions: (1) it precludes the requirement to bolt up the joint, which would have to be broken as each section of pipe is added, and (2) it permits relative movement of muck tube and liner which can occur as a result of compression of the liner under high loading.

When the drill must be withdrawn from the hole, the telescopic joint is removed, and a fixed retrieval tool is substituted. This has a bolted flange to match the muck pipe, and provides the means for pulling the pipe.

To react the pull on the derrick during drill withdrawal, screw-type reaction jacks, normally nested in the derrick guide tubes, can be extended to contact the front wall. These may also be extended during normal boring operations to prevent the derrick from creeping out of alignment when the thrust loads are relaxed.

To facilitate handling of liners, two sets of rollers are mounted on the lower thrust cylinder. The liner is inserted between the cylinders by a hoist and is lowered onto the rollers. The rollers assure the alignment of the liner and enable it to be moved axially, relative to the crosshead during the process of bolting up the muck tube and welding to the previous liner.

For strength and ease of manufacture, the main structure of the crosshead, which is a fairly complex shape, is a steel casting. Aluminum bronze bushings are used as the sliding medium on the guide tubes for strength and durability. The guide tubes are hard chrome plated to provide a wear-resistant, smooth surface.

### 3.4 Mucking System, Ref. Drawing D35632

The major components of the mucking system are shown in Figure 7. Since some elements fulfill dual roles, additional component descriptions are found in the descriptions of the in-hole assembly and the derrick.

Two sets of computations for air flow, pressure drops, etc., were made. Calculations were made for 600 ft. of borehole and an elevation of 1,200 ft. (original assumed repository elevation), and for 250 ft. of borehole and an elevation of 6,300 ft. This latter requirement is for the DPBM tests at the G-Tunnel complex of NTS.

These computations are located in Appendix 5.

The complete mucking system includes the following major components:

- a. In-hole muck tube (Ref. Dwg. D36136)
- b. Derrick telescopic joint (Ref. Dwg. D36509)
- c. Derrick elbow (Ref. Dwg. D36510)
- d. Transfer pipe with ball joints (Ref. Dwg. B36543-1)
- e. Telescopic joint (Ref. Dwg. D36528)
- f. Primary drop box (Ref. Dwg. D35620-1)
- g. Secondary drop box (Ref. Dwg. D35620-1)
- h. Filter unit (Ref. Dwg. D36545-1)
- i. Vacuum pump unit (Ref. Dwg. D36546-1) and
- j. Control station (Ref. Dwg. D36158)

#### 3.4.1 Muck Tube, Ref. Drawing D36136

The muck tube serves the dual purpose of conveying the muck and being used to withdraw or reinsert the drill. When the system is actually operating, the rate of abrasive wear must be observed. Excess wear could eventually compromise the strength of the pipe. Observations of wear locations and rates must be made during initial testing to permit design upgrading of a production system.

The muck tube sections are connected by four-bolt flanges and joints are sealed by a spigot-mounted O-ring. Hangers to support the electric power, control and instrumentation cables are attached to the muck tube assembly.

A pair of rollers, permanently attached to the mid-point of each pipe section, is used to hold the muck tube string clear of the liner. This reduces friction force when the string is moved in or out of the hole. The rollers also facilitate moving the tube inside the liner as new sections are installed during boring.

For test purposes, the piping material is mild steel. As dictated by test results, a longer wearing design may be required. The options include a harder, high-wearing material, hard facing, or replaceable inner liner sections.

#### 3.4.2 Derrick Telescopic Joint and Elbows, Ref. Drawing D36509

Just before the derrick-mounted muck elbow, (a horizontal right-angle bend), the pipe is telescoped within a larger pipe section (9.625 in. ID with .75 in. wall). The telescopic joint facilitates installation of new sections of muck pipe and provides compensation for relative movement between the muck tube and liner under high-thrust loads.

The telescopic joint section is flange mounted to the derrick-mounted elbow. The elbow is a flanged 9.625 in. diameter round tubing, bent to a 39 in. radius. The elbow is followed by a transition piece to an 8 in. diameter at the first ball joint.

#### 3.4.3 Transfer Pipe Connection, Ref. Drawing B36543-1

The transfer pipe is the principal connecting link between the derrick muck elbow and the first drop box. Ball joints are located at each end to permit angular movement as the derrick strokes forward. The pipe is 40 ft. long, 8 in. Schedule 80 pipe. A telescopic joint mounted on the front end of the drop box is incorporated to accommodate the shortening motion resulting from the angular movement of the transfer pipe as the derrick strokes.

#### 3.4.4 Drop Boxes, Ref. Drawing D35620-1

Two virtually identical drop boxes connected in series are utilized. This provides adequate collection volume for one liner length of advance (8 ft.) and provides a two-stage deceleration of the air flow. The heaviest particles will tend to drop out in the first box, lighter particles in the second.

Air and muck enter the first of the two drop boxes through an 8 in. pipe. Inside the box the pipe enlarges to a 12 in. diameter expansion pipe. The expansion pipe is slotted along the bottom length, permitting the rock particles to drop out as the air flow decelerates. A portion of the air in the first drop box is free to pass through a 75 mesh screen at the top of the box and into a clean air manifold.

The main stream, less the volume which passed into the clean air manifold from the primary box, passes to the secondary drop box. A similar slotted deceleration pipe is used to further reduce air velocity and drop out particles. One added feature of the secondary box is a deflector plate bolted onto the end of the pipe. This is designed in the manner of a stuffing box to reduce abrasive wear.

The air from the secondary box also passes through a 75 mesh screen and into the clean air manifold. An air vibrator on the screen, actuated by pressure drop, shakes the screen to keep it relatively free of lodged particles.



The two boxes are designed to work in tandem and when the primary box fills to the point that airflow is impeded, air velocity will increase and all particles will be carried to the secondary box.

Each drop box has two hoppers. The muck is ejected from the hoppers by an externally supplied low-pressure (20 psi) pneumatic discharge system. Hoppers are discharged only while the vacuum system is turned off. During operation of the discharge system, the drop boxes are subjected to internal air pressure. Isolation valves are required at each end of the drop box assembly to prevent air from escaping back up the muck pipe or into the filter unit, which is not designed to withstand internal pressure. In normal operation, electrical interlocks are employed to prevent applying discharge pressure until the isolation valves are closed. Pressure relief valves are included on both drop boxes and the filter unit for safety.

The discharge from the four hoppers of the drop boxes is manifolded into a single discharge pipe. This pipe could be directed to a haulage vehicle.

#### 3.4.5 Filter Unit, Ref. Drawing D36545-1

The function of the filter unit is to separate airborne dust before entry to the vacuum pump (blower) and subsequent discharge into the haulage way. The filtering device consists of eight commercially available cylindrical fabric cartridges, each 2 ft. long and 1 ft. in diameter. They are suspended below a dividing plate on a rack system for easy removal.

Air enters below the dividing plate, passes through the filter from the outside, and emerges above the plate. Air velocities through the fabric are generally .5 to .3 ft. per minute. Ample capacity (up to 6,000 cfm) is provided by the eight filter elements.

A nozzle, located above each filter outlet, periodically blasts compressed air to dislodge the dust cake from the filter. This backflushing action causes the majority of the dust to fall into the hopper arrangement located below.

The cycling of the purging system is controlled by an adjustable electric timer. A switch sensing the differential pressure across the filter pack signals a warning light on the operator's console if the cartridges become clogged.

The hoppers are designed to be emptied about once per shift by an inclined screw feeder unit enclosed in a tube. The dust can only be removed when the vacuum system is shut down. An airtight valve at the feeder outlet seals the vacuum during boring operations.

#### 3.4.6 Vacuum Pump Unit, Ref. Drawing D36546-1

The vacuum pump is a rotary lobe, axial-flow, positive displacement pump,

driven by a 150 HP electric motor with belt drive. The pump produces a dry vacuum of 12 in. of mercury at 2,400 cfm, at 1,400 rpm. Immediately ahead of the blower and located in the same skid is a secondary filter unit. This serves the dual purpose of polishing the already filtered air and acts as a safety filter in case a cartridge in the primary unit ruptures. This final system protects the blowers and assures that discharge air is respirable. Actually, the primary filter unit alone is probably efficient enough to assure that the discharged air is of respirable quality.

The secondary filter employs the same type of cartridges as in the primary unit, but a purging system is not used. Since little dust should be collected, removal is effected manually, after opening a cover plate.

A water injection unit, which is located just ahead of the pump intake, can be used if necessary to decrease the internal leakage of the pump and thus increase the working vacuum. The vacuum pump unit discharges into a plenum chamber and then to atmosphere via an air silencer unit.

### 3.5 Liner, Ref. Drawing D36514

The liner is an 8 ft. long pipe section (reference Figure 7). As a structure, it must withstand the maximum thrust and torque reaction loads without buckling or compression failure. An analysis (Attachment 4) showed that either a .38 in. thick wall in 52 ksi material or .5 in. wall in 35 ksi material would be suitable.

The ends of each pipe section are bevelled to permit a full penetration weld. Because a shallow angle is desirable at the jacking collar to avoid excessive wedge loads while providing sufficient opening at the joint for root penetration, the bevels at each end are at different angles. Tentatively, a 45° angle is shown in front and 15° at the rear, or thrust end, of the liner pipe. The selection of the exact angles should be determined in conjunction with the automatic welding machine manufacturer.

The manufacturing tolerances on the straightness of pipe, ovality, and squareness of the ends must be held to tolerances tighter than generally held on commercial tubing. Alternately, weld preparation on the pipe ends could include sizing or counterboring. Each liner section joint must be carefully aligned to avoid hang up of the liner in the bore or hang up of system units on misalignment ridges inside the liner.

### 3.6 Derrick Power Unit, Ref. Drawing D35925

The power unit (Pack B shown in Figure 7) provides the hydraulic supply for the derrick and crawler functions. A double-ended electric motor drives two variable displacement pumps. The largest pump has 72 gpm capacity and, at maximum stroke, will supply low-pressure fluid for rapidly traversing the derrick and for driving the crawler. The pump has a horsepower limit control which, when sensing increased pressure, will

automatically reduce the output volume.

The smaller pump has a maximum capacity of 11.5 gpm at 4,000 psi and is pressure compensated. This is used primarily as the thrust feed supply and also to operate the various jacking functions. The feed rate is controlled by a variable flow control located on the operator's console. Suction strainers, high pressure and return filters are incorporated to ensure system cleanliness. The reservoir capacity is 300 gallons of petroleum-based hydraulic fluid. Connections to the derrick unit are made by removable hoses equipped with sealing quick disconnects at both ends.

The power unit also houses the motor control center, various starters, overload relays and circuit breakers. It also includes a programmable controller which directs the interlock logic.

### 3.7 Welding System, Ref. Drawing A36516

An automatic orbital welding machine (reference Figure 7) is used to join the liner sections. The welding head moves along a circular track clamped to one of the liner sections adjacent to the joint. The flow characteristics of the weld puddle are affected by gravity and depend on the instantaneous location on the pipe circumference. A variable-pulse system is used to control the fluidity of the puddle. The quickest system uses the MIG (Metal Inert Gas) process. Automatic MIG processes which have the capability of laying 5 lbs. per hour are presently developed and can be used for this system.

A short development program to evaluate the exact heats, speeds and passes will be required before the boring test.

As each new section of liner is added, alignment with the previous section must be exact. Ideally, an external alignment fixture would be used, as it does not interfere with the muck tube and cables inside the liners. A backing plate, to prevent weld intrusion and increase the MIG welding speed, is recommended.

### 3.8 Control Station Assembly, Ref. Drawing D35915

The control console is a skid-mounted unit complete with a seat for the operator. All drill functions, and the major functions of the derrick and mucking system, are controlled from the console. Gages and indicator lights are used to monitor various parameters. The remote laser readout screen occupies a central position and monitors bore deviation.

The panel is divided into three clearly defined areas, as shown in Figure 9, grouping separately the drill, derrick and vacuum pump systems to avoid confusion during operation (refer to Drawing D35928). Each area is described in the following paragraphs.




FIGURE 9 - DPBM Control Station Assembly

### 3.8.1 Drill Panel, Ref. Drawing D35928

The DPBM control panel contains readouts and instrumentation designed for R&D purposes. It is more complete than usual drilling panels. The following controls are incorporated:

- a. Drill Motor. Besides on-off controls, jog control is provided to index the head for withdrawal.
- b. In-Hole Hydraulic System Motor. On-off controls.
- c. Steering. A single four-quadrant joystick controls the movement of the head up/down and right/left. Note that the mode select switch (e) must be in the "steer" position.
- d. Cylinder Setting. Four switches permit individual setting of the four steering cylinders. These are used in initially setting up the cutterhead location and also in lowering it before withdrawal. The mode select switch (e) must be in the "set" position.
- e. Mode Switch. This can be set to "steer" or "set" to operate those functions described previously. It is set to "bore" after the head is correctly located. In this mode, the pressure to the upper cylinders is controlled to provide the minimum force at the upper shoe for adequate stabilization.
- f. Cutterhead Thrust Monitor. In the "set" position, the cutterhead is pushed forward. In the "release" position, the head can be pushed back by an external load. (The thrust control system is single acting.) The set mode must be used when boring. The "release" mode is used when reinserting the drill after mid-bore withdrawal. It enables the drill unit to be pushed as far forward as possible to engage the shield properly, without the cutterhead actually contacting the face.
- g. Stabilizer Pressure. This operates a remote pressure control valve to set the stabilizer loading.
- h. Shield Engagement. A single switch is provided to control both of the two engagement mechanisms.

The following gages and indicators are incorporated in the control panel:

- i. Steering Cylinder Pressures. Each cylinder can be monitored individually. Note that in the bore mode, the two upper cylinders are connected and show the stabilizing pressure.
- j. Steering Cylinder Positions. The stroke of each cylinder is displayed on a digital meter. This provides an accurate indication of cutterhead movement, with greater resolution than obtainable by the inclino-meter.
- k. Drive and Pump Motor Amps. Meters are provided.

- l. Gearbox Temperature. A continuous readout is provided.
- m. Cutterhead Thrust. This measures the pressure of the fluid trapped in the control annulus.
- n. Warning Lights. Red light warnings are provided for high drive motor temperature, low hydraulic fluid level and high temperature and failure of the cutterhead thrust control system (head moving back).
- o. Interlock Lights. Amber lights indicate the correct functioning of the following systems. Failure of any of the following parts will cause shutdown of the drive motor and derrick feed: vacuum pump, stabilizer pressure, liner clamp (on derrick), or shield engagement.
- p. Indicator Lights. Green lights are provided to indicate that the cutterhead index location is correct and that the upper steering shoe is retracted to permit withdrawal.
- q. Laser Target Screen and Controls. A selector switch is incorporated so that the following parameters can be monitored: x and y deviation from the desired bore, roll, and look-up and lead (pitch and yaw). A set of thumbwheels is provided for initially zeroing the system to account for misalignments of mounting.

### 3.8.2 Derrick Panel, Ref. Drawing D35928

The following controls are incorporated on the derrick panel:

- a. Emergency Stop. Shuts down all system pumps and electric motors.
- b. Reset. Required for re-starting.
- c. Hydraulic Pump Motor. Derrick power unit on/off.
- d. Thrust Cylinder Extend and Retract. Two settings: High pressure, low speed or low pressure, high speed.
- e. Boring Feed Rate. This is a hydraulic flow control valve controlling high pressure flow to the thrust cylinders.
- f. Control Power Switch.
- g. Warning Siren Button. To signal startup.

The following gages and indicators are incorporated on the derrick panel:

- h. Pump Motor Amps.
- i. Pump Output Pressures.

- j. Thrust Pressure. Indicates thrust loading into liner in boring mode.
- k. Pullback Pressure. Indicates pull on muck pipe when withdrawing drill.
- l. Hydraulic Oil Level.

### 3.8.3 Vacuum Muck System Panel, Ref. Drawing D35928

The only control function is the vacuum pump motor start/stop switch. The system is interlocked such that the drill motor cannot be started until the vacuum pump has been running for a few seconds. This avoids choking the muck inlet at the drill. Similarly, the pump cannot be switched off until after the drill has been turned off, to avoid leaving material in the muck piping.

The following gages and indicators are incorporated on the vacuum pump panel:

- a. Pump Motor Amps.
- b. Vacuum at the Drill. (in Hg)
- c. Vacuum at Pump Drill. (in Hg)
- d. Vacuum Fault Light. This combines three fault indications from the vacuum system: (1) high pump inlet vacuum, indicating an overload situation or blocked pipeline; (2) low vacuum, indicating system leakage; and (3) high differential pressure at the primary filter unit, indicating clogged filters. Note that individual indications are displayed on the vacuum unit console (subsection 3.9).
- e. Temperature Fault Light. This combines two fault indications. One is high outlet air temperature, indicating a fault at the pump. The other is high pump gearbox temperature. Individual indication is displayed at the vacuum unit console.
- f. Isolation Valve Indicators. A green light indicates that the isolation valves on the drop boxes are open, and the system may be started.

### 3.9 Vacuum System Control Console, Ref. Drawing D37173

This unit, shown in Figure 10, provides local control of the vacuum pump for checking and troubleshooting purposes. An emergency stop button is also incorporated. The drop box isolation valve control switch also is located here.




FIGURE 10 - Vacuum Pump Skid Control Console



The following gages and indicators are provided. Some are duplicated at the main control station assembly so that monitoring is possible from either location.

- a. Vacuum Pump Amps. The current is monitored per phase, and a selector switch is provided.
- b. Inlet Air Temperature.
- c. Muck Inlet Vacuum at the Drill.
- d. Secondary Filter Pressure Drop.
- e. Outlet Air Pressure.
- f. Air Outlet Temperature.
- g. Gearbox Oil Temperature.
- h. Pressure drop across the Primary Filter.
- i. Pump Inlet Vacuum.
- j. Air Inlet Velocity. This provides an indication of air flow, and is included for experimental data. It normally would not be included in a production unit. Probably air outlet pressure and air inlet temperature also would be excluded.
- k. Isolation Valve Position Indicators. Note that if the system is started with the valves shut, excess inlet vacuum will immediately shut it down again.

If certain monitored parameters (f, g, h and i) exceed selected safety values, the system is automatically shut down. Latching indicator lights incorporated in the meter relays provide fault location after shutdown.

#### 4.0 DPBM OPERATION

Upon completion of assembly and shop check out, the DPBM could be acceptance tested at a local quarry. Functional reliability could be assessed by drilling several short holes. Following acceptance tests, the DPBM could be reconditioned as necessary and shipped by truck to the Nevada Test Site (NTS). At NTS, the DPBM would be tested for operational performance to determine the design adequacy of the system, and to obtain performance characteristics data for welded tuff.

This section describes DPBM operation, mobilization and test requirements for boring two 250 ft. horizontal holes at a specific site in an underground facility known as G-Tunnel. An estimate of the time for individual operations is provided. These data will provide the background for the preparation of a definitive test plan. This description reflects the state of development of the DPBM at the time that the engineering design work was completed. Therefore, there are some site-specific requirements of the system and of the specific NTS test location which are identified but which need further definition.

#### 4.1 NTS Site Description

The physical and geological data presented in the following paragraphs was obtained by a site visit, physical measurements, rock samples from the site, core and bore examination and drawings and logs provided by NTS personnel. A plan view of the selected site, the far end of G-Tunnel, is shown in Figure 11. The location of the two proposed DPBM test bores is indicated. The objective is to bore approximately 250 ft., up an incline of about  $3.3^\circ$  from the "laser drift" to the "rock mechanics drift." Following this course should keep the bores within a 30 ft. thick formation of welded tuff.

##### 4.1.1 Physical Features

The elevation of the main haulage way of G-Tunnel averages about 6,300 ft. above sea level. The tunnel is equipped for rail transport, which ends approximately 6,140 ft. from the portal. The tunnel railhead is about 240 ft. from the laser drift, and 510 ft. from the rock mechanics drift.

The laser drift is approximately 75 ft. long. The first 30 ft. is a  $15^\circ$  incline, with the remainder level. The cross-sectional dimensions of the first 40 ft. are 11 ft. wide by 14 ft. high, with the remainder 10 ft. wide by 10 ft. high.

The rock mechanics drift is approximately 130 ft. long on a  $14^\circ$  incline. The cross-sectional opening is 10 ft. wide by 12 ft. high.




FIGURE 11 - NTS Site Test Location

#### 4.1.2 Geology

The formation consists of densely welded tuff, containing a fracture frequency of 12 per foot minimum. The rock is abrasive and contains pumice inclusions and vugs. Unconfined compressive strengths vary from 12,000 to 15,000 psi. The rock may be saturated.

#### 4.1.3 Utilities Available

Electric power in the tunnel is 4160 VAC, three phase. A 90 psi air supply is available in the main drive for the muck box unloading system. Lighting and ventilation are not installed in the laser drift. The rock mechanics drift presently has both ventilation and lighting. Water is not generally available in the tunnel, but is not required by the DPBM system.

#### 4.1.4 Environment

Ambient temperature is in the range of 60 to 80°F with humidity to 80%. Activity may reduce the air quality level to necessitate personnel using dust masks during some phases of testing. During the collaring in operation and at break through, the ventilation system will not likely keep up with the dust generated. Also dumping the drop boxes could produce substantial dust. Filtration intake boxes for motor cooling air may be required.

#### 4.2 Site Preparation

The test arrangement for the first bore is shown in Figure 12. The additional excavation required for DPBM set up in the laser drift is indicated.

The test arrangement for the second bore is shown in Figure 13. The changes to the site shown are due to the relocation of the derrick from the first to the second site.

The required modifications to the site due to the physical and operational features of the DPBM are further discussed in the following paragraphs.

##### 4.2.1 Excavation

The requirement for increased chamber size is shown in Figures 12 and 13. Additional excavation will be required in the laser drift as shown in Figure 15, to accommodate the length of the derrick unit with an 8 ft. liner segment in place. In addition, an alcove will be required in the "main drift" for housing the mucking system. A barrier will be required to suppress the noise generated by the vacuum system blowers. This would be an additional modification to the arrangement shown in Figures 11 and 12.




FIGURE 12 - NTS Test Site Arrangement, Bore No. 1




FIGURE 13 - NTS Test Site Arrangement, Bore No. 2

#### 4.2.2 Utilities Required

The DPBM will require 400 kva of electrical power at 460 VAC; three phase. Transformers will be required to reduce the 4160 VAC mine supply.

Compressed air for the mucking system ancillary requirements such as the pneumatic discharge system (20 psi), filter purging, dust conveyor motors and isolation valve activation will be required. The existing 90 psi air supply should be adequate.

Lighting and ventilation will be required for the laser drift similar to that existing in the rock mechanics drift.

#### 4.2.3 Special Provisions

Other modifications and additional items necessary for the operation of the DPBM are identified in the following paragraphs.

##### 4.2.3.1 DPBM Handling Equipment

The following items will be required to handle the components of the DPBM:

- a. Liner Handler. A liner handler will be required to lift and position the liner sections into the derrick chassis. This could be accomplished by means of an overhead monorail or special handling fixture. The best approach will be determined after further investigation of detail conditions in the laser drift.
- b. Drill and Shield Handling Fixture. A means of handling the drill unit under two conditions is required. First, the drill unit must be installed with its shield and the entire assembly loaded into the derrick. Upon completion of the hole, or in the event of removal for repair, the fixture must be capable of handling the drill unit alone. The fixture to perform these functions has not been designed.
- c. Derrick Handling Fixture. The Mobile Derrick could be lifted as an assembly by pick points designed into the main chassis for loading and transport by railway into the tunnel. However, there are two sections of the tunnel with restricted headroom (7 ft. 10 in.) which must be considered in designing the transport car. The other alternative is to disassemble the crawler from the main chassis and reassemble the unit at the tunnel railhead. Once the derrick is assembled in the main drift, near the entrance to the laser drift, the derrick mounted crawler should provide adequate mobility.
- d. Power Unit Handling Fixture. A fixture will be needed to lift and position the Power Unit into the first liner section. Also, upon

withdrawal of the drill, this fixture must hoist the Power Unit clear of the derrick as the final section of muck pipe is removed.

#### 4.2.3.2 Mucking Equipment Revisions

Since the laser drift is neither long enough nor large enough in cross section, the mucking system drop boxes, filter car and blower should be located around the corner in the main drift. The preferred location would be in an alcove, excavated near the laser drift intersection. This permits the building of a noise reduction barrier without blocking the main drift. However, an extra elbow is required to duct the muck around the bend.

To accommodate the arc described by the muck transfer pipe as the derrick strokes, a telescopic joint is required. The present design houses the telescopic joint in the first drop box.

With the required positioning in the G-Tunnel complex, the joint must be accommodated in the transfer pipe. The design of pipe lengths and elbows must be accomplished and a revised telescoping joint fabricated and installed.

#### 4.2.3.3 Load Bearing Pads

Concrete pads are required on the floor and rear wall to withstand the dead weight of the equipment and the thrust reaction loads respectively. A concrete pad, approximately 5 ft. diameter and at least 6 in. thick, should be constructed at the point of bore entry in the front wall. This will ensure a sound starting point for the drill and provide a flat bolting surface for the selected method of collaring (using a "top hat" section as described in the following section).

#### 4.2.3.4 Collaring Fixture

A method of holding the cutterhead steady at the start of boring is necessary until the stabilizing shoes are inside the bore. Three options were considered. Briefly, (1) a collar, precast into a face pad; (2) a freestanding steel frame, stabilized at the floor and roof; and (3) a "top hat"-like steel collar, bolted to a minimal face pad were investigated. The "top hat" collar was chosen primarily because of its low cost, small size and ease of installation. The collar will be bolted to the concrete face pad through the use of rock bolts. The unit will be designed to separate in half to permit removal.

### 4.3 System Mobilization

The DPBM system will be transported from Seattle to NTS and offloaded near the mouth of G-Tunnel. The tunnel railway will move the components back



to the specific test site. From the railhead, the components and specialty items will be moved to the laser drift by a large front end loader. The derrick will move under its own power.

The following paragraphs describe the mobilization, installation and special features of the test arrangement.

#### 4.3.1 Transport and Handling of the DPBM

The transport of the DPBM follows the completion of the acceptance test activity in Seattle. Each component is prepared for shipment by truck for delivery to the NTS U12G Tunnel Complex portal. Components can be provided with pick points for lifting by crane for offloading onto the tunnel railway flatcars. Some items such as liner segments can be sling-lifted or handled by forklift. Items such as handling fixtures, cabling, collaring fixture and slings can be palletized for handling by forklift.

The equipment can be transported by tunnel rail to within 240 ft. of the laser drift. The use of the DPBM handling equipment described in paragraph 4.2.3.1 will facilitate placement of the system for testing.

#### 4.3.2 DPBM Test Arrangement

The test setup for the two bores is shown in Figure 11 (Bore No. 1) and Figure 12 (Bore No. 2). The first bore is located approximately 63 ft. from the laser drift entry. A 5 ft. recess needs to be excavated into the face to permit room for the derrick with the In-Hole Assembly mounted preparatory to drilling.

Four motorized floor screw jacks on each corner of the derrick frame are used to relieve the load from the crawler and to orient the derrick at the required boring angle. The operator's console should be located such that the operator can observe the derrick and drill during the collaring process.

Sufficient clearance must be permitted in the laser drift for translation of the muck transfer pipe as the derrick pushes the liner into the bore and retracts. The transfer pipe is the connecting link between the derrick muck elbow and the elbow leading to first drop box. Ball joints located at each end of the transfer pipe are required to permit its angular rotation as the derrick strokes forward. The telescopic joint must be located in the transfer pipe or at the downstream ball joint.

The Power Unit is located next to the derrick on the opposite side from the mucking system. It provides the high pressure hydraulic oil supply for the derrick and crawler functions. The power unit also houses the motor control center, various starters, overload relays and circuit breakers. A programmable controller which directs the interlock logic is also located on the Power Unit.

The automatic welding machine is located in front of the derrick where it can join a newly added liner segment to the installed section.

The second bore is to be located 17 ft. toward the laser drift entry from the first bore, with the same general arrangement of equipment. The primary exception being the shortening of the connecting pipe between the transfer pipe and the elbow leading to the first drop box.

#### 4.3.3 Instrumentation and Data

Although the extent of instrumentation is generally dictated by the requirements of a definitive test plan, the DPBM equipment was set up for R&D data collection. The instrumentation and real time readouts incorporated are as described in Paragraphs 3.8 and 3.9 and reflect past experience in tunneling equipment development. In addition, the console is designed to permit the installation of recording devices.

##### 4.3.3.1 Console Monitoring

All drill functions, and the major functions of the derrick and mucking system, are controlled from the control console. Gages and indicator lights are used to monitor various parameters. The remote laser readout screen occupies a central position and monitors bore deviation from true center.

The panel is divided into three clearly defined areas, grouping separately the drill, derrick and vacuum pump systems to avoid confusion during operation.

A vacuum pump console located at the blower cart provides local control of the vacuum pump for checking and troubleshooting purposes. An emergency stop button is also incorporated. The drop box isolation valve control switch also is located here.

##### 4.3.3.2 Data Recording

A permanent record of gage and indicator readings can be obtained by tapping off of the control console to electronic recording equipment. The selection of data to be recorded will be accomplished when preparing the definitive test plan.

#### 4.4 Boring Operation

The operation of the DPBM follows a sequence of events from the setting-up of the machine to the withdrawal of the drill upon completion of the finished bore. The following paragraphs describe the steps involved in the drilling. They provide the basis for generating the performance estimates and for developing the operation schedule.

#### 4.4.1 Setting Up

After making the electrical and hydraulic connections between the various components, preparations for start-up of drilling can be made.

##### 4.4.1.1 Derrick Positioning

By maneuvering the derrick (shown in Figure 7) with the crawler tracks, it can be aligned in the plane of the intended bore. The derrick is backed up toward the rear wall within reach of the thrust reaction jacks.

The laser unit can now be accurately positioned so that it lines up with the derrick centerline in plan view and is set to the exact inclination angle required. Two temporary targets defining the centerline of the derrick are installed, one at the rear of the machine and one at the end of the headframe bolted to the guide tubes.

The following steps describe the procedure involved in positioning the derrick:

- a. Align the derrick in the vertical plane using the four leveling floor jacks so that the laser spot strikes the front and rear target bullseyes.
- b. Extend the thrust reaction jacks to contact the rear wall. Lock the jacks into position.
- c. Extend the torque reaction jacks to contact the roof. Lock the jacks into position.
- d. Check laser alignment and readjust jacks. Note that if the inclination angle is within tolerance, the laser unit can be slightly readjusted.
- e. Extend the pull-back reaction jacks to contact the front wall.

##### 4.4.1.2 In-Hole Assembly Placement

With the derrick lined up and secured in position, the In-Hole Assembly can be hoisted into place using the Drill and Shield Handling Fixture described in Paragraph 4.2.3.1 (b).

The assembly will sit on rollers located on the lower thrust cylinder. The unit is rolled back to contact the thrust collar, and the liner clamp cylinders are pressurized, gripping the liner.

#### 4.4.1.3 In-Hole Assembly Positioning

In order to start the drilling process, the In-Hole Assembly must be connected to the In-Hole Power Unit. During collaring in of the shield, this power unit is to be positioned adjacent to the derrick and installed inside the first liner section. The following steps describe the procedure involved:

- a. Complete hydraulic connections between the power unit and the In-Hole Assembly.
- b. Complete electric connections between the power unit and the control console.
- c. Pressurize the shield engagement mechanism to the lock position.
- d. Raise the cutterhead to the boring position. Note: Stabilizer shoe is not extended at this time.
- e. Stroke the thrust cylinders until the cutterhead contacts the face.

#### 4.4.2 Collaring-In

The collaring process is performed in basically a two-step procedure as shown in Figure 14.

The temporary "top hat" collar is attached as shown in Step 1. This unit is split in the vertical plane so that it can be removed once the drill is collared in. When bolted together, it forms a 37 in. inside diameter heavy-wall steel tube. The shield is placed so that it is supported by the top hat collar.

The following steps describe the procedure involved:

- a. Extend the upper (stabilizing) shoe to contact the upper inner wall of the collaring fixture by placing the control console mode selection switch to the "bore" position.
- b. Extend the muck system telescopic connection at the crosshead to mate with the end of the muck pipe in the In-Hole Assembly.
- c. Switch vacuum system on. (Although it will not capture all the muck particles until the head is completely collared in, it will help to control the dust generated by the cutting action.)
- d. Switch cutterhead drive on. Begin boring at a very low feed rate.

In Step 2 of Figure 14, the stabilizer shoe is shown inside the freshly cut bore and the drill collar has been removed to permit the full stroke of the derrick.




FIGURE 14 - Collaring-In

As a standard operating procedure, the laser target readout should be monitored on a continuous basis during the boring operation. After the full stroke is reached, the liner clamps are released and the thrust cylinders completely retracted.

#### 4.4.3 Liner and Muck Pipe Installation

The installation of a liner and muck pipe segment is illustrated in two steps as shown in Figure 15.

The following are the procedures for Step 1:

- a. Hoist the first liner (with the In-Hole Power Unit and a length of muck pipe nested inside) into place on the derrick roller assemblies.
- b. Bolt the liner muck pipe to the In-Hole Assembly muck pipe rear unit.
- c. Feed the electric cables out of the slot in the jacking collar (cables should be prestrung through at least three liners).
- d. Pressurize liner clamps preparatory to boring.

The following are the procedures for Step 2:

- a. Install welding machine track and head.
- b. Weld the liner-to-shield joint.
- c. Extend telescopic muck joint to mate with new muck pipe.
- d. Restart boring operation. Complete full stroke of the derrick thrust cylinders.

The above boring and retraction of the thrust cylinders is repeated.

The second liner to be added contains a muck pipe with a large covered access hole to be used for mechanically dislodging any material which may later clog the muck passage through the In-Hole Assembly. The rear end of the In-Hole Power Unit is attached to the muck pipe in the second liner by a removable link.

Three liners should be prestrung with the electric cabling to reduce disconnection and reconnection efforts. The cabling is fabricated in 50 ft. lengths, and represents a compromise between minimizing the number of connections and causing difficult bundling and stringing problems.




FIGURE 15 - Liner Installation

Figure 7 depicts the operating cycle with the third liner shown in place and ready for boring.

#### 4.4.4 Drill Withdrawal

Drill withdrawal is required when the hole is completed or during drilling operations should problems develop with the in-hole components. The following steps describe the procedure involved:

- a. Remove the telescopic muck joint at the derrick.
- b. Install the muck pipe retrieval tool preparatory to pulling back muck pipe sections.
- c. Stroke the derrick forward to connect the bolted retrieval tool to muck pipe rear flange.
- d. Jog the drill motor until indicator lights on the console show that the drill head is correctly indexed for withdrawal.
- e. Retract the steering cylinders to allow the upper stabilizing shoe to lower and clear the roof of the shield.
- f. Release the shield engagement mechanism.
- g. Retract the derrick to withdraw the drill.
- h. At the completion of each retraction stroke of the derrick, remove the withdrawn section of muck pipe.
- i. Extend the derrick and bolt the retrieval tool to the next section of muck pipe.

The above steps (g) through (i) are repeated until the In-Hole Power Unit is withdrawn from the liner.

The power unit is removed by performing the following steps:

- a. Lift the In-Hole Power Unit using the fixture described in Paragraph 4.2.3.1 (d) sufficiently to disconnect the electrical and hydraulic connections. Detach the removable extraction link.
- b. Hoist the power unit clear of the derrick and store.
- c. Remove the first section of muck pipe.
- d. Withdraw the (drill) In-Hole Assembly using the fixture described in Paragraph 4.2.3.1 (b).



#### 4.4.5 Drill Reinsertion

Reinsertion is necessary if the drill has been removed for repair before completion of the hole.

With the retrieval tool still in place at the derrick, following the drill removal operation, the steps for reinsertion follow:

- a. Hoist the In-Hole Assembly into alignment with the bore using the fixture described in Paragraph 4.2.3.1 (b).
- b. Extend the derrick thrust cylinders, thereby pushing the drill into the bore.
- c. Upon full extension of the thrust cylinders, retract the crosshead to the rear starting position.
- d. Insert the first section of muck pipe and bolt it to the exit flange of the drill muck pipe.
- e. Hoist the In-Hole Power Unit into position over the muck pipe.
- f. Complete the hydraulic and electrical connections between the In-Hole Assembly drill and the In-Hole Power Unit.
- g. Extend the thrust cylinders to insert the power unit into the bore.
- h. Retract the thrust cylinders and install the second piece of muck pipe containing the access hole.
- i. Install the connecting link between the second muck pipe and the power unit.
- j. Extend the thrust cylinders to insert the second muck pipe into the bore.

The above steps (h) through (j) are repeated adding sections of muck pipe. The electric cabling is strung along the hangers attached to the pipe.

When the drill is almost in contact with the face, (determined by a count of the muck pipes inserted and the location of the crosshead), the thrust monitor selector on the control console must be in the "release" position. This permits the shield engagement mechanism to operate without the cutterhead being hard against the face. The following steps describe the procedure necessary to restart boring:

- a. Activate the shield engagement switch. Positive engagement of the locking device is indicated by lights on the control console.
- b. Position the cutterhead in accord with the last recorded position on the guidance system screen (before withdrawal) by use of the

steering cylinders. If a gage cutter change has been made, a correction will be necessary to compensate for the difference in gage diameter.

- c. Select "bore" mode at the console.
- d. Start the vacuum system.
- e. Switch on the cutterhead drive.
- f. Switch the thrust monitor to "set" at the console. This will cause the cutterhead to advance relative to the shield.

Boring can now be restarted. Begin boring at a very low feed rate.

#### 4.4.6 In-Hole Power Unit Withdrawal

Withdrawing only the power unit is not a routine procedure, but can be considered as an alternative to removal of the entire drill. Also, an emergency situation might exist where the hydraulic unit fails, preventing the drill from being extracted. This requires a man to go up the bore, disconnect the hydraulic lines to the drill and the drive link to the muck pipe, and attach a rope or small diameter push/pull rod. No ancillary equipment for withdrawal and reinsertion has been designed under the present contract. The power unit has been designed with wheels for removal and clearance are provided for it to pass over the muck pipe flanges and cable hangers.

#### 4.4.7 Test Set Up/Borehole No. 2

Following completion of the first bore, the equipment must be moved to begin operation on the second bore. The derrick can be maneuvered on its tracks. As the move distance is only 17 ft., the power unit does not need to be moved simultaneously. Hose connections of sufficient length are provided.

The other equipment items are repositioned as shown in Figure 13.

#### 4.5 Test Schedule Elements

The following estimates of overall boring operation times have been made by summing the times of a number of individual tasks. Some tasks are independent of the length of bore (e.g. collaring) while some are dependent on length (e.g. 8 ft. boring cycle). The analysis is for a 250 ft. length. Figure 16 shows the schedule of the major steps analyzed in Paragraph 4.5.1. To estimate the overall time required for any other bore length, recomputing the length-dependent items will provide corresponding schedules.




FIGURE 16 - Boring Operation Durations

The time estimates for individual tasks were assessments by experienced personnel from Robbins and specific vendors. There is a good deal of historical data from similar tasks. The schedule shown in Figure 16 does not account for the delays due to data collection, repairs or unanticipated geological conditions. It also does not account for pre-planned development test activity. The operational durations presented are intended to guide the writing of a definitive test plan. They are not indicative of a test hole schedule.

- a. Travel time between Bore No. 1 and Bore No. 2. Though the distance is only 17 ft., the activity involved in equipment movement, realignment of the derrick and muck system adjustments is estimated to take 16 hours.

16 hrs.

- b. Collaring-In. Total stroke during collaring is 9 ft. 6 in. Boring rate is slow to reduce forces plus time is needed to remove the temporary collar.

4 hrs.

- c. Liner and Muck Pipe Installation.

- (1) Handling. (Transport of liner to derrick, join muck pipe, feed cable, butt up liner before welding.)

.25 hr./liner

- (2) Welding of Liner.

Installation of alignment  
jig

0.1 hr.

Tacking

0.2 hr.

Weld time (based on auto-  
matic machine data)

1.75 hrs.

Inspection

0.6 hr.

Subtotal

2.9 hr./line

- (3) Bore 8 ft.

1 hr.

- (4) Cable handling 0.3 hr.  
every 3 liners

0.1 hr./liner

TOTAL CYCLE TIME PER 8 FT. SEGMENT 4.0 hr./liner

For the completed 250 ft. hole, 30 liners in addition to the sacrificial drill shield are required.

TOTAL BORING AND LINER INSTALLATION TIME 120 hrs.

d. Drill Withdrawal

- (1) Removal of the telescopic muck joint, installation of the retrieval tool, indexing and lowering of the cutterhead.

.25 hr.

- (2) Muck pipe removal including derrick traverse, unbolting two flanges, pipe removal, retraverse and bolting up of the retrieval tool, and cable disconnection. .25 hr. per pipe times 30 pipes

Total 7.5 hrs.

- (3) Removal of drill unit .25 hr.

TOTAL WITHDRAWAL TIME 8 hrs.

- e. Maintenance activities including clean up, replacement of consumable components (cutters, filters, etc.) greasing and functional checking.

8 hrs.

TOTAL EMPLACEMENT BORING CYCLE SUMMARY

|    |                  |          |
|----|------------------|----------|
| a. | Travel Time      | 16       |
| b. | Collaring-In     | 4        |
| c. | Lining/Boring    | 120      |
| d. | Drill Withdrawal | 8        |
| e. | Maintenance      | <u>8</u> |
|    |                  | 156 hrs. |

On a single-shift basis, an uninterrupted drilling sequence for a 250 ft. hole will consume 20 days. In the definitive test plan, all times for test, data collection, physical examination, etc. should be added to these time durations.

Note that this estimate assumes that emptying the muck system drop boxes and cleaning the vacuum unit, and the time required for cable threading, takes place during the liner welding operation. The supply of new liners and muck pipes to the ready area can be made at any time. Again, note that the times presented are intended only to guide the writing of a definitive test plan.

#### 4.6 Personnel Requirements

A four-man drilling crew plus supervisor will be required. While the machine is boring, one will be operating the drill, another will monitor the vacuum system and supervise muck haulage, and a third will be involved in organizing the movement of liners, muck pipes and electric cabling. The fourth will be general labor. All four will be needed for the liner installation operation and for set up of the welding machine. While one person is operating the welding machine, the others will be involved in emptying the drop box and filter units, and performing any necessary equipment maintenance.

In addition, the services of an independent welding inspector will be required for the checking of every liner joint.

Electrical and mechanical repair personnel should be available in case of breakdown.

#### REFERENCES

The Robbins Company, Final Report, Repository Drilled Hole Methods Study, SAND83-7085, (Albuquerque: Sandia National Laboratories, November, 1984).

The Robbins Company, Small Diameter Horizontal Hole Drilling: State of Technology, SAND84-7103, (Albuquerque: Sandia National Laboratories, November, 1984).

The Robbins Company, Feasibility Studies and Conceptual Design for Placing Steel Liner in Long, Horizontal Boreholes for a Prospective Nuclear Waste Repository in Tuff, SAND84-7209 (Albuquerque: Sandia National Laboratories, July, 1985).

APPENDIX A

to

DESIGN OF A MACHINE TO BORE AND LINE  
A LONG HORIZONTAL HOLE IN TUFF

INDENTURED DRAWING LIST



ASSEMBLY TITLE:

SITE INSTALLATION/GENERAL ARRANGEMENT

-DRAWING NO: D35910

| DRAWING NO. |   |   |   |   |   |  | REV | TITLE                         | RELEASE DATE |
|-------------|---|---|---|---|---|--|-----|-------------------------------|--------------|
| 1           | 2 | 3 | 4 | 5 | 6 |  |     |                               |              |
| D35910      |   |   |   |   |   |  |     | SITE INSTALLATION             | 10.25.85     |
| D35911      |   |   |   |   |   |  |     | IN-HOLE ASSEMBLY              | 10.25.85     |
| D35920      |   |   |   |   |   |  |     | MOBILE DERRICK ASSEMBLY       | 10.25.85     |
| D35632      |   |   |   |   |   |  |     | MUCKING SYSTEM ASSEMBLY       | 10.25.85     |
| D35927      |   |   |   |   |   |  |     | CONTROL STATION ASSEMBLY      | 10.25.85     |
| B36514      |   |   |   |   |   |  |     | LINER                         | 10.25.85     |
| D36136      |   |   |   |   |   |  |     | MUCK TUBE                     | 10.25.85     |
| A36515      |   |   |   |   |   |  |     | LASER                         | 10.25.85     |
| A36516      |   |   |   |   |   |  |     | WELDING SYSTEM                | 10.25.85     |
| D35914      |   |   |   |   |   |  |     | HYDRAULIC SYSTEM ASSEMBLY     | 10.25.85     |
| D35915      |   |   |   |   |   |  |     | ELECTRICAL SYSTEM ASSEMBLY    | 10.25.85     |
|             |   |   |   |   |   |  |     | <u>GENERAL SPECIFICATIONS</u> |              |
| A36160      |   |   |   |   |   |  |     | LOCKWIRE INSTALLATION         | 10.25.85     |
| A36165      |   |   |   |   |   |  |     | RADIOGRAPHIC INSPECTION       | 10.25.85     |
| A36166      |   |   |   |   |   |  |     | CARBURIZATION SPECIFICATION   | 10.25.85     |
| A35950      |   |   |   |   |   |  |     | ULTRASONIC TESTING            | 10.25.85     |
| A35952      |   |   |   |   |   |  |     | MAGNETIC PARTICLE INSPECTION  | 10.25.85     |
| A36544      |   |   |   |   |   |  |     | WELDING SPECIFICATION         | 10.25.85     |
| A36572      |   |   |   |   |   |  |     | FASTENER TORQUES :            | 10.25.85     |
| A36162      |   |   |   |   |   |  |     | HARDFACING PROCEDURE          | 10.25.85     |
| A37355      |   |   |   |   |   |  |     | HEAT TREATMENT SPECIFICATION  | 10.25.85     |
|             |   |   |   |   |   |  |     |                               |              |
|             |   |   |   |   |   |  |     |                               |              |
|             |   |   |   |   |   |  |     |                               |              |
|             |   |   |   |   |   |  |     |                               |              |
|             |   |   |   |   |   |  |     |                               |              |
|             |   |   |   |   |   |  |     |                               |              |
|             |   |   |   |   |   |  |     |                               |              |
|             |   |   |   |   |   |  |     |                               |              |
|             |   |   |   |   |   |  |     |                               |              |
|             |   |   |   |   |   |  |     |                               |              |
|             |   |   |   |   |   |  |     |                               |              |
|             |   |   |   |   |   |  |     |                               |              |
|             |   |   |   |   |   |  |     |                               |              |
|             |   |   |   |   |   |  |     |                               |              |
|             |   |   |   |   |   |  |     |                               |              |
|             |   |   |   |   |   |  |     |                               |              |
|             |   |   |   |   |   |  |     |                               |              |
|             |   |   |   |   |   |  |     |                               |              |
|             |   |   |   |   |   |  |     |                               |              |
|             |   |   |   |   |   |  |     |                               |              |
|             |   |   |   |   |   |  |     |                               |              |
|             |   |   |   |   |   |  |     |                               |              |
|             |   |   |   |   |   |  |     |                               |              |
|             |   |   |   |   |   |  |     |                               |              |
|             |   |   |   |   |   |  |     |                               |              |
|             |   |   |   |   |   |  |     |                               |              |
|             |   |   |   |   |   |  |     |                               |              |
|             |   |   |   |   |   |  |     |                               |              |
|             |   |   |   |   |   |  |     |                               |              |
|             |   |   |   |   |   |  |     |                               |              |
|             |   |   |   |   |   |  |     |                               |              |
|             |   |   |   |   |   |  |     |                               |              |
|             |   |   |   |   |   |  |     |                               |              |
|             |   |   |   |   |   |  |     |                               |              |
|             |   |   |   |   |   |  |     |                               |              |
|             |   |   |   |   |   |  |     |                               |              |
|             |   |   |   |   |   |  |     |                               |              |
|             |   |   |   |   |   |  |     |                               |              |
|             |   |   |   |   |   |  |     |                               |              |
|             |   |   |   |   |   |  |     |                               |              |
|             |   |   |   |   |   |  |     |                               |              |
|             |   |   |   |   |   |  |     |                               |              |
|             |   |   |   |   |   |  |     |                               |              |
|             |   |   |   |   |   |  |     |                               |              |
|             |   |   |   |   |   |  |     |                               |              |
|             |   |   |   |   |   |  |     |                               |              |
|             |   |   |   |   |   |  |     |                               |              |
|             |   |   |   |   |   |  |     |                               |              |
|             |   |   |   |   |   |  |     |                               |              |
|             |   |   |   |   |   |  |     |                               |              |
|             |   |   |   |   |   |  |     |                               |              |
|             |   |   |   |   |   |  |     |                               |              |
|             |   |   |   |   |   |  |     |                               |              |
|             |   |   |   |   |   |  |     |                               |              |
|             |   |   |   |   |   |  |     |                               |              |
|             |   |   |   |   |   |  |     |                               |              |
|             |   |   |   |   |   |  |     |                               |              |
|             |   |   |   |   |   |  |     |                               |              |
|             |   |   |   |   |   |  |     |                               |              |
|             |   |   |   |   |   |  |     |                               |              |
|             |   |   |   |   |   |  |     |                               |              |
|             |   |   |   |   |   |  |     |                               |              |
|             |   |   |   |   |   |  |     |                               |              |
|             |   |   |   |   |   |  |     |                               |              |
|             |   |   |   |   |   |  |     |                               |              |
|             |   |   |   |   |   |  |     |                               |              |
|             |   |   |   |   |   |  |     |                               |              |
|             |   |   |   |   |   |  |     |                               |              |
|             |   |   |   |   |   |  |     |                               |              |
|             |   |   |   |   |   |  |     |                               |              |
|             |   |   |   |   |   |  |     |                               |              |
|             |   |   |   |   |   |  |     |                               |              |
|             |   |   |   |   |   |  |     |                               |              |
|             |   |   |   |   |   |  |     |                               |              |
|             |   |   |   |   |   |  |     |                               |              |
|             |   |   |   |   |   |  |     |                               |              |
|             |   |   |   |   |   |  |     |                               |              |
|             |   |   |   |   |   |  |     |                               |              |
|             |   |   |   |   |   |  |     |                               |              |
|             |   |   |   |   |   |  |     |                               |              |
|             |   |   |   |   |   |  |     |                               |              |
|             |   |   |   |   |   |  |     |                               |              |
|             |   |   |   |   |   |  |     |                               |              |
|             |   |   |   |   |   |  |     |                               |              |
|             |   |   |   |   |   |  |     |                               |              |
|             |   |   |   |   |   |  |     |                               |              |
|             |   |   |   |   |   |  |     |                               |              |
|             |   |   |   |   |   |  |     |                               |              |
|             |   |   |   |   |   |  |     |                               |              |
|             |   |   |   |   |   |  |     |                               |              |
|             |   |   |   |   |   |  |     |                               |              |
|             |   |   |   |   |   |  |     |                               |              |
|             |   |   |   |   |   |  |     |                               |              |
|             |   |   |   |   |   |  |     |                               |              |
|             |   |   |   |   |   |  |     |                               |              |
|             |   |   |   |   |   |  |     |                               |              |
|             |   |   |   |   |   |  |     |                               |              |
|             |   |   |   |   |   |  |     |                               |              |
|             |   |   |   |   |   |  |     |                               |              |
|             |   |   |   |   |   |  |     |                               |              |
|             |   |   |   |   |   |  |     |                               |              |
|             |   |   |   |   |   |  |     |                               |              |
|             |   |   |   |   |   |  |     |                               |              |
|             |   |   |   |   |   |  |     |                               |              |
|             |   |   |   |   |   |  |     |                               |              |
|             |   |   |   |   |   |  |     |                               |              |
|             |   |   |   |   |   |  |     |                               |              |
|             |   |   |   |   |   |  |     |                               |              |
|             |   |   |   |   |   |  |     |                               |              |
|             |   |   |   |   |   |  |     |                               |              |
|             |   |   |   |   |   |  |     |                               |              |
|             |   |   |   |   |   |  |     |                               |              |
|             |   |   |   |   |   |  |     |                               |              |
|             |   |   |   |   |   |  |     |                               |              |
|             |   |   |   |   |   |  |     |                               |              |
|             |   |   |   |   |   |  |     |                               |              |
|             |   |   |   |   |   |  |     |                               |              |
|             |   |   |   |   |   |  |     |                               |              |
|             |   |   |   |   |   |  |     |                               |              |
|             |   |   |   |   |   |  |     |                               |              |
|             |   |   |   |   |   |  |     |                               |              |
|             |   |   |   |   |   |  |     |                               |              |
|             |   |   |   |   |   |  |     |                               |              |
|             |   |   |   |   |   |  |     |                               |              |
|             |   |   |   |   |   |  |     |                               |              |
|             |   |   |   |   |   |  |     |                               |              |
|             |   |   |   |   |   |  |     |                               |              |
|             |   |   |   |   |   |  |     |                               |              |
|             |   |   |   |   |   |  |     |                               |              |
|             |   |   |   |   |   |  |     |                               |              |
|             |   |   |   |   |   |  |     |                               |              |
|             |   |   |   |   |   |  |     |                               |              |
|             |   |   |   |   |   |  |     |                               |              |
|             |   |   |   |   |   |  |     |                               |              |
|             |   |   |   |   |   |  |     |                               |              |
|             |   |   |   |   |   |  |     |                               |              |
|             |   |   |   |   |   |  |     |                               |              |
|             |   |   |   |   |   |  |     |                               |              |
|             |   |   |   |   |   |  |     |                               |              |
|             |   |   |   |   |   |  |     |                               |              |
|             |   |   |   |   |   |  |     |                               |              |
|             |   |   |   |   |   |  |     |                               |              |
|             |   |   |   |   |   |  |     |                               |              |
|             |   |   |   |   |   |  |     |                               |              |
|             |   |   |   |   |   |  |     |                               |              |
|             |   |   |   |   |   |  |     |                               |              |
|             |   |   |   |   |   |  |     |                               |              |
|             |   |   |   |   |   |  |     |                               |              |
|             |   |   |   |   |   |  |     |                               |              |
|             |   |   |   |   |   |  |     |                               |              |
|             |   |   |   |   |   |  |     |                               |              |
|             |   |   |   |   |   |  |     |                               |              |
|             |   |   |   |   |   |  |     |                               |              |
|             |   |   |   |   |   |  |     |                               |              |
|             |   |   |   |   |   |  |     |                               |              |
|             |   |   |   |   |   |  |     |                               |              |
|             |   |   |   |   |   |  |     |                               |              |
|             |   |   |   |   |   |  |     |                               |              |
|             |   |   |   |   |   |  |     |                               |              |
|             |   |   |   |   |   |  |     |                               |              |
|             |   |   |   |   |   |  |     |                               |              |
|             |   |   |   |   |   |  |     |                               |              |
|             |   |   |   |   |   |  |     |                               |              |
|             |   |   |   |   |   |  |     |                               |              |
|             |   |   |   |   |   |  |     |                               |              |
|             |   |   |   |   |   |  |     |                               |              |
|             |   |   |   |   |   |  |     |                               |              |
|             |   |   |   |   |   |  |     |                               |              |
|             |   |   |   |   |   |  |     |                               |              |
|             |   |   |   |   |   |  |     |                               |              |
|             |   |   |   |   |   |  |     |                               |              |
|             |   |   |   |   |   |  |     |                               |              |
|             |   |   |   |   |   |  |     |                               |              |
|             |   |   |   |   |   |  |     |                               |              |
|             |   |   |   |   |   |  |     |                               |              |
|             |   |   |   |   |   |  |     |                               |              |
|             |   |   |   |   |   |  |     |                               |              |
|             |   |   |   |   |   |  |     |                               |              |
|             |   |   |   |   |   |  |     |                               |              |
|             |   |   |   |   |   |  |     |                               |              |
|             |   |   |   |   |   |  |     |                               |              |
|             |   |   |   |   |   |  |     |                               |              |
|             |   |   |   |   |   |  |     |                               |              |
|             |   |   |   |   |   |  |     |                               |              |
|             |   |   |   |   |   |  |     |                               |              |
|             |   |   |   |   |   |  |     |                               |              |
|             |   |   |   |   |   |  |     |                               |              |
|             |   |   |   |   |   |  |     |                               |              |
|             |   |   |   |   |   |  |     |                               |              |
|             |   |   |   |   |   |  |     |                               |              |
|             |   |   |   |   |   |  |     |                               |              |
|             |   |   |   |   |   |  |     |                               |              |
|             |   |   |   |   |   |  |     |                               |              |
|             |   |   |   |   |   |  |     |                               |              |
|             |   |   |   |   |   |  |     |                               |              |
|             |   |   |   |   |   |  |     |                               |              |
|             |   |   |   |   |   |  |     |                               |              |
|             |   |   |   |   |   |  |     |                               |              |
|             |   |   |   |   |   |  |     |                               |              |
|             |   |   |   |   |   |  |     |                               |              |
|             |   |   |   |   |   |  |     |                               |              |
|             |   |   |   |   |   |  |     |                               |              |
|             |   |   |   |   |   |  |     |                               |              |
|             |   |   |   |   |   |  |     |                               |              |
|             |   |   |   |   |   |  |     |                               |              |
|             |   |   |   |   |   |  |     |                               |              |
|             |   |   |   |   |   |  |     |                               |              |
|             |   |   |   |   |   |  |     |                               |              |
|             |   |   |   |   |   |  |     |                               |              |
|             |   |   |   |   |   |  |     |                               |              |
|             |   |   |   |   |   |  |     |                               |              |
|             |   |   |   |   |   |  |     |                               |              |
|             |   |   |   |   |   |  |     |                               |              |
|             |   |   |   |   |   |  |     |                               |              |
|             |   |   |   |   |   |  |     |                               |              |
|             |   |   |   |   |   |  |     |                               |              |
|             |   |   |   |   |   |  |     |                               |              |
|             |   |   |   |   |   |  |     |                               |              |
|             |   |   |   |   |   |  |     |                               |              |

ASSEMBLY TITLE: IN-HOLE ASSEMBLY

DRAWING NO: D35911

| DRAWING NO.                  |   |   |   |   |   |  | REV | TITLE                      | RELEASE DATE |       |
|------------------------------|---|---|---|---|---|--|-----|----------------------------|--------------|-------|
| 1                            | 2 | 3 | 4 | 5 | 6 |  |     |                            |              |       |
| D35911                       |   |   |   |   |   |  |     | IN-HOLE ASSEMBLY           | 10.25.85     |       |
| D36121                       |   |   |   |   |   |  |     | DRIVE ASSEMBLY             | 10.25.85     |       |
| D35947                       |   |   |   |   |   |  |     | OUTER HOUSING              | 10.25.85     |       |
| D35949                       |   |   |   |   |   |  |     | RING CARRIER               | 10.25.85     |       |
| D35950                       |   |   |   |   |   |  |     | SEAL RING                  | 10.25.85     |       |
| D35952                       |   |   |   |   |   |  |     | BEARING CARRIER            | 10.25.85     |       |
| D36072                       |   |   |   |   |   |  |     | CUTTERHEAD SHAFT           | 10.25.85     |       |
| D35940                       |   |   |   |   |   |  |     | FINAL REDUCTION PLANET HUB | 10.25.85     |       |
| D35939                       |   |   |   |   |   |  |     | 1ST REDUCTION PLANET HUB   | 10.25.85     |       |
| D35948                       |   |   |   |   |   |  |     | END CAP                    | 10.25.85     |       |
| D36061                       |   |   |   |   |   |  |     | MOTOR COUPLING             | 10.25.85     |       |
| D36057                       |   |   |   |   |   |  |     | COUPLING 1ST REDUCTION     | 10.25.85     |       |
| D35943                       |   |   |   |   |   |  |     | JUNCTION BOX               | 10.25.85     |       |
| D35941                       |   |   |   |   |   |  |     | ELECTRIC MOTOR - 125 HP    | 10.25.85     |       |
| D35909                       |   |   |   |   |   |  |     | SUN PINION OUTPUT          | 10.25.85     |       |
| D35908                       |   |   |   |   |   |  |     | PLANET - 1ST REDUCTION     | 10.25.85     |       |
| D36056                       |   |   |   |   |   |  |     | COUPLING - 2ND REDUCTION   | 10.25.85     |       |
| D35906                       |   |   |   |   |   |  |     | SUN PINION - 2ND REDUCTION | 10.25.85     |       |
| D35907                       |   |   |   |   |   |  |     | PLANET - 2ND REDUCTION     | 10.25.85     |       |
| D36060                       |   |   |   |   |   |  |     | SPLINED ADAPTER            | 10.25.85     |       |
| D36164                       |   |   |   |   |   |  |     | SPLINED COUPLING           | 10.25.85     |       |
| D36508                       |   |   |   |   |   |  |     | SPLINED COUPLING           | 10.25.85     |       |
| B35946                       |   |   |   |   |   |  |     | BEARING LIST               | 10.25.85     |       |
| A35945                       |   |   |   |   |   |  |     | CYLINDRICAL ROLLER BEARING | 10.25.85     |       |
| COMPILED BY: Peter B. Dowden |   |   |   |   |   |  |     | DATE: 10.25.85             | NO. A35926   | REV - |

| SANDIA DPBM - MASTER DRAWING LIST        |   |   |   |   |   |  |     |                           |              | SHEET 3 OF 28 |       |
|--|---|---|---|---|---|--|-----|---------------------------|--------------|---------------|-------|
| ASSEMBLY TITLE: IN-HOLE ASSEMBLY (CON'T) |   |   |   |   |   |  |     |                           |              |               |       |
| DRAWING NO: D35911                       |   |   |   |   |   |  |     |                           |              |               |       |
| DRAWING NO.                              |   |   |   |   |   |  | REV | TITLE                     | RELEASE DATE |               |       |
| 1  | 2 | 3 | 4 | 5 | 6 |  |     |                           |              |               |       |
|  |   |   |   |   |   |  |     | REDUCTION RING GEAR       | 10.25.85     |               |       |
|  |   |   |   |   |   |  |     | FRONT RETAINER            | 10.25.85     |               |       |
|  |   |   |   |   |   |  |     | SENSOR HOUSING            | 10.25.85     |               |       |
|  |   |   |   |   |   |  |     | RETAINER                  | 10.25.85     |               |       |
|  |   |   |   |   |   |  |     | RETAINER                  | 10.25.85     |               |       |
|  |   |   |   |   |   |  |     | RETAINER                  | 10.25.85     |               |       |
|  |   |   |   |   |   |  |     | SEAL RING                 | 10.25.85     |               |       |
|  |   |   |   |   |   |  |     | SEAL GUARD                | 10.25.85     |               |       |
|  |   |   |   |   |   |  |     | SPACER                    | 10.25.85     |               |       |
|  |   |   |   |   |   |  |     | PIN                       | 10.25.85     |               |       |
|  |   |   |   |   |   |  |     | PLANET PIN                | 10.25.85     |               |       |
|  |   |   |   |   |   |  |     | PLANET PIN                | 10.25.85     |               |       |
|  |   |   |   |   |   |  |     | BEARING SPACER            | 10.25.85     |               |       |
|  |   |   |   |   |   |  |     | THRUST BEARING            | 10.25.85     |               |       |
|  |   |   |   |   |   |  |     | BEARING SPACER            | 10.25.85     |               |       |
|  |   |   |   |   |   |  |     | THRUST SPACER             | 10.25.85     |               |       |
|  |   |   |   |   |   |  |     | THRUST WASHER             | 10.25.85     |               |       |
|  |   |   |   |   |   |  |     | SPACER RING               | 10.25.85     |               |       |
|  |   |   |   |   |   |  |     | SEAL SET                  | 10.25.85     |               |       |
|  |   |   |   |   |   |  |     | SENSOR BOSS               | 10.25.85     |               |       |
|  |   |   |   |   |   |  |     | INSTALLATION INSTRUCTIONS | 10.25.85     |               |       |
|  |   |   |   |   |   |  |     | SEAL WEAR RING            | 10.25.85     |               |       |
|  |   |   |   |   |   |  |     | SEAL PROTECTOR            | 10.25.85     |               |       |
|  |   |   |   |   |   |  |     | THERMOCOUPLE              | 10.25.85     |               |       |
| COMPILED BY: Peter B. Dowden             |   |   |   |   |   |  |     | DATE: 10.25.85            | NO. A35926   |               | REV - |

| SANDIA DPBM - MASTER DRAWING LIST |   |   |   |   |   |  |          |                                 |              |  | SHEET 4 OF 28 |  |
|-----------------------------------|---|---|---|---|---|--|----------|---------------------------------|--------------|--|---------------|--|
| ASSEMBLY TITLE: IN-HOLE ASSEMBLY  |   |   |   |   |   |  |          |                                 |              |  | (CON'T)       |  |
| DRAWING NO: D35911                |   |   |   |   |   |  |          |                                 |              |  |               |  |
| DRAWING NO.                       |   |   |   |   |   |  | REV      | TITLE                           | RELEASE DATE |  |               |  |
| 1                                 | 2 | 3 | 4 | 5 | 6 |  |          |                                 |              |  |               |  |
|                                   |   |   |   |   |   |  |          | BEARING SHIM                    | 10.25.85     |  |               |  |
|                                   |   |   |   |   |   |  |          | LOCKWIRE INSTRUCTIONS           | 10.25.85     |  |               |  |
|                                   |   |   |   |   |   |  |          | STEERING & MUCK SYSTEM ASSEMBLY | 10.25.85     |  |               |  |
|                                   |   |   |   |   |   |  |          | GRIPPING SHOE - UPPER           | 10.25.85     |  |               |  |
|                                   |   |   |   |   |   |  |          | GRIPPING SHOE - LOWER           | 10.25.85     |  |               |  |
|                                   |   |   |   |   |   |  |          | MUCK TUBE                       | 10.25.85     |  |               |  |
|                                   |   |   |   |   |   |  |          | WEDGE - TOP                     | 10.25.85     |  |               |  |
|                                   |   |   |   |   |   |  |          | WEDGE - BOTTOM                  | 10.25.85     |  |               |  |
|                                   |   |   |   |   |   |  |          | CYLINDER - TOP                  | 10.25.85     |  |               |  |
|                                   |   |   |   |   |   |  |          | CYLINDER - BOTTOM               | 10.25.85     |  |               |  |
|                                   |   |   |   |   |   |  |          | SHEAR LUG                       | 10.25.85     |  |               |  |
|                                   |   |   |   |   |   |  |          | BEAM                            | 10.25.85     |  |               |  |
|                                   |   |   |   |   |   |  |          | CYLINDER RETAINER               | 10.25.85     |  |               |  |
|                                   |   |   |   |   |   |  |          | FLANGE MALE                     | 10.25.85     |  |               |  |
|                                   |   |   |   |   |   |  |          | LINEAR TRANSDUCER SENSOR        | 10.25.85     |  |               |  |
|                                   |   |   |   |   |   |  |          | SPRING                          | 10.25.85     |  |               |  |
|                                   |   |   |   |   |   |  |          | RETAINER                        | 10.25.85     |  |               |  |
|                                   |   |   |   |   |   |  |          | SPHERICAL SEAT                  | 10.25.85     |  |               |  |
|                                   |   |   |   |   |   |  |          | SPRING HOLDER                   | 10.25.85     |  |               |  |
|                                   |   |   |   |   |   |  |          | SPRING RETAINER                 | 10.25.85     |  |               |  |
|                                   |   |   |   |   |   |  |          | SPRING HOLDER                   | 10.25.85     |  |               |  |
|                                   |   |   |   |   |   |  |          | ANGLE FOR MUCK TUBE             | 10.25.85     |  |               |  |
|                                   |   |   |   |   |   |  |          | ROLLER BALL                     | 10.25.85     |  |               |  |
|                                   |   |   |   |   |   |  |          | KEY                             | 10.25.85     |  |               |  |
| COMPILED BY:                      |   |   |   |   |   |  | DATE:    |                                 | NO.          |  | REV           |  |
| Peter B. Dowden                   |   |   |   |   |   |  | 10.25.85 |                                 | A35926       |  | -             |  |

## SANDIA DPBM - MASTER DRAWING LIST

SHEET 5 OF 28

ASSEMBLY TITLE: IN-HOLE ASSEMBLY

(CON'T)

DRAWING NO: D35911

| DRAWING NO. |   |   |   |   |   |  | REV | TITLE                    | RELEASE DATE |
|-------------|---|---|---|---|---|--|-----|--------------------------|--------------|
| 1           | 2 | 3 | 4 | 5 | 6 |  |     |                          |              |
|             |   |   |   |   |   |  |     | SPHERICAL NUT            | 10.25.85     |
|             |   |   |   |   |   |  |     | CYLINDER THRUST SOCKET   | 10.25.85     |
|             |   |   |   |   |   |  |     | LOCKWIRE INSTRUCTIONS    | 10.25.85     |
|             |   |   |   |   |   |  |     | SHIELD ENGAGEMENT SYSTEM | 10.25.85     |
|             |   |   |   |   |   |  |     | THRUST BALL HOUSING      | 10.25.85     |
|             |   |   |   |   |   |  |     | LOCKING LUG              | 10.25.85     |
|             |   |   |   |   |   |  |     | COUPLING                 | 10.25.85     |
|             |   |   |   |   |   |  |     | SPLIT CLAMP              | 10.25.85     |
|             |   |   |   |   |   |  |     | CROWN COUPLING           | 10.25.85     |
|             |   |   |   |   |   |  |     | WEDGE                    | 10.25.85     |
|             |   |   |   |   |   |  |     | CYLINDER                 | 10.25.85     |
|             |   |   |   |   |   |  |     | ZED LASER TARGET         | 10.25.85     |
|             |   |   |   |   |   |  |     | LINK                     | 10.25.85     |
|             |   |   |   |   |   |  |     | BARREL NUT               | 10.25.85     |
|             |   |   |   |   |   |  |     | PIN                      | 10.25.85     |
|             |   |   |   |   |   |  |     | SPHERICAL SEAT           | 10.25.85     |
|             |   |   |   |   |   |  |     | RETAINER - BALL          | 10.25.85     |
|             |   |   |   |   |   |  |     | ROLLER BALL              | 10.25.85     |
|             |   |   |   |   |   |  |     | TRUNNION                 | 10.25.85     |
|             |   |   |   |   |   |  |     | THREADED ROD             | 10.25.85     |
|             |   |   |   |   |   |  |     | LOCKWIRE INSTRUCTIONS    | 10.25.85     |
|             |   |   |   |   |   |  |     | SENSOR MOUNT BRACKET     | 10.25.85     |
|             |   |   |   |   |   |  |     | SHIELD WELDMENT          | 10.25.85     |
|             |   |   |   |   |   |  |     | LOCKPLATE                | 10.25.85     |

COMPILED BY:

Peter B. Dowden

DATE:

10.25.85

NO.

A35926

REV

-

## SANDIA DPBM - MASTER DRAWING LIST

SHEET 6 OF 28

ASSEMBLY TITLE: IN-HOLE ASSEMBLY

(CON'T)

DRAWING NO: D35911

| DRAWING NO.                  |   |   |   |   |   | REV | TITLE                                   | RELEASE DATE |
|------------------------------|---|---|---|---|---|-----|---|--------------|
| 1                            | 2 | 3 | 4 | 5 | 6 |     |   |              |
|                              |   |   |   |   |   |     | D36120 CUTTERHEAD ASSEMBLY              | 10.25.85     |
|                              |   |   |   |   |   |     | D36112 CUTTERHEAD MACHINING             | 10.25.85     |
|                              |   |   |   |   |   |     | D36118 CUTTERHEAD WELDMENT              | 10.25.85     |
|                              |   |   |   |   |   |     | A36568 CUTTER ASSEMBLY NO. 1            | 10.25.85     |
|                              |   |   |   |   |   |     | A36569 CUTTER ASSEMBLY NO. 2            | 10.25.85     |
|                              |   |   |   |   |   |     | A36570 GAGE CUTTER ASSEMBLY             | 10.25.85     |
|                              |   |   |   |   |   |     | D36664 DRIVE PLATE-POWER UNIT           | 10.25.85     |
|                              |   |   |   |   |   |     | D36136 MUCK TUBE ASSEMBLY (SEE SHT. 15) | 10.25.85     |
|                              |   |   |   |   |   |     | D36662 MUCK TUBE - DRIVER ASSEMBLY      | 10.25.85     |
|                              |   |   |   |   |   |     | D36136 MUCK TUBE ASSEMBLY               | 10.25.85     |
|                              |   |   |   |   |   |     | B36114 FLANGE - FEMALE                  | 10.25.85     |
|                              |   |   |   |   |   |     | B36115 FLANGE - MALE                    | 10.25.85     |
|                              |   |   |   |   |   |     | A36109 WHEEL BRACKET                    | 10.25.85     |
|                              |   |   |   |   |   |     | A36108 WHEEL                            | 10.25.85     |
|                              |   |   |   |   |   |     | B36137 CABLE SUPPORT BRACKET            | 10.25.85     |
|                              |   |   |   |   |   |     | A37333 STOP                             | 10.25.85     |
| COMPILED BY: Peter B. Dowden |   |   |   |   |   |     | DATE: 10.25.85                          | NO. A35926   |
|                              |   |   |   |   |   |     |   | REV -        |

| SANDIA DPBM - MASTER DRAWING LIST   |   |   |   |   |   |     |                         |              |  | SHEET 7 OF 28 |  |
|---|---|---|---|---|---|-----|-------------------------|--------------|--|---------------|--|
| ASSEMBLY TITLE:      MOBILE DERRICK ASSEMBLY<br>DRAWING NO:        D35920 |   |   |   |   |   |     |                         |              |  |               |  |
| DRAWING NO.   |   |   |   |   |   | REV | TITLE                   | RELEASE DATE |  |               |  |
| 1   | 2 | 3 | 4 | 5 | 6 |     |                         |              |  |               |  |
| D35920  |   |   |   |   |   |     | MOBILE DERRICK ASSEMBLY | 10.25.85     |  |               |  |
| D35985  |   |   |   |   |   |     | CRAWLER FRAME ASSEMBLY  | 10.25.85     |  |               |  |
| D35978  |   |   |   |   |   |     | CRAWLER FRAME WELDMENT  | 10.25.85     |  |               |  |
| D35979  |   |   |   |   |   |     | TRACK FRAME WELDMENT    | 10.25.85     |  |               |  |
| B35980  |   |   |   |   |   |     | SIDE RAIL               | 10.25.85     |  |               |  |
| A35981  |   |   |   |   |   |     | BAR                     | 10.25.85     |  |               |  |
| A35982  |   |   |   |   |   |     | WEAR STRIP              | 10.25.85     |  |               |  |
| D35983  |   |   |   |   |   |     | LOCATING TOOL (REF)     | 10.25.85     |  |               |  |
| D35984  |   |   |   |   |   |     | HUB DETAIL              | 10.25.85     |  |               |  |
| D35986  |   |   |   |   |   |     | CYL. TRACK ADJUSTER     | 10.25.85     |  |               |  |
| D35987  |   |   |   |   |   |     | CYLINDER BASE           | 10.25.85     |  |               |  |
| D35988  |   |   |   |   |   |     | CYLINDER BODY           | 10.25.85     |  |               |  |
| D35989  |   |   |   |   |   |     | PISTON                  | 10.25.85     |  |               |  |
| D35990  |   |   |   |   |   |     | SPRING ASSEMBLY         | 10.25.85     |  |               |  |
| A35991  |   |   |   |   |   |     | SHAFT                   | 10.25.85     |  |               |  |
| A35992  |   |   |   |   |   |     | SPRING RETAINER         | 10.25.85     |  |               |  |
| A35993  |   |   |   |   |   |     | SPRING RETAINER         | 10.25.85     |  |               |  |
| A35994  |   |   |   |   |   |     | COMPRESSION SPRING      | 10.25.85     |  |               |  |
| A35995  |   |   |   |   |   |     | COMPRESSION SPRING      | 10.25.85     |  |               |  |
| D35996  |   |   |   |   |   |     | SPROCKET                | 10.25.85     |  |               |  |
| D35997  |   |   |   |   |   |     | TRACK IDLER ASSEMBLY    | 10.25.85     |  |               |  |
| A35998  |   |   |   |   |   |     | STEEL BALL              | 10.25.85     |  |               |  |
| D35999  |   |   |   |   |   |     | TRACK ROLLER ASSEMBLY   | 10.25.85     |  |               |  |

|                 |  |  |  |          |        |     |
|-----------------|--|--|--|----------|--------|-----|
| COMPILED BY:    |  |  |  | DATE:    | NO.    | REV |
| Peter B. Dowden |  |  |  | 10.25.85 | A35926 | -   |

| SANDIA DPBM - MASTER DRAWING LIST               |   |   |   |   |   |  |     |                          |              | SHEET 8 OF 28 |  |
|---|---|---|---|---|---|--|-----|--------------------------|--------------|---------------|--|
| ASSEMBLY TITLE: MOBILE DERRICK ASSEMBLY (CON'T) |   |   |   |   |   |  |     |                          |              |               |  |
| DRAWING NO: D35920                              |   |   |   |   |   |  |     |                          |              |               |  |
| DRAWING NO.                                     |   |   |   |   |   |  | REV | TITLE                    | RELEASE DATE |               |  |
| 1   | 2 | 3 | 4 | 5 | 6 |  |     |                          |              |               |  |
|   |   |   |   |   |   |  |     | UPPER IDLER ASSEMBLY     | 10.25.85     |               |  |
|   |   |   |   |   |   |  |     | TRACK, CHAIN, COMPONENTS | 10.25.85     |               |  |
|   |   |   |   |   |   |  |     | TRACK SHOE               | 10.25.85     |               |  |
|   |   |   |   |   |   |  |     | SEAL - OIL               | 10.25.85     |               |  |
|   |   |   |   |   |   |  |     | SEAL - PISTON            | 10.25.85     |               |  |
|   |   |   |   |   |   |  |     | TORQUE HUB               | 10.25.85     |               |  |
|   |   |   |   |   |   |  |     | FAILSAFE BRAKE           | 10.25.85     |               |  |
|   |   |   |   |   |   |  |     | HYDRAULIC MOTOR          | 10.25.85     |               |  |
|   |   |   |   |   |   |  |     | DERRICK ASSEMBLY         | 10.25.85     |               |  |
|   |   |   |   |   |   |  |     | THRUST CYLINDER - UPPER  | 10.25.85     |               |  |
|   |   |   |   |   |   |  |     | SEAL KIT                 | 10.25.85     |               |  |
|   |   |   |   |   |   |  |     | THRUST REACTION JACK     | 10.25.85     |               |  |
|   |   |   |   |   |   |  |     | SEAL KIT                 | 10.25.85     |               |  |
|   |   |   |   |   |   |  |     | EXPANSION PIN            | 10.25.85     |               |  |
|   |   |   |   |   |   |  |     | TAPER PLUG               | 10.25.85     |               |  |
|   |   |   |   |   |   |  |     | TAPER PLUG               | 10.25.85     |               |  |
|   |   |   |   |   |   |  |     | EXPANSION PIN            | 10.25.85     |               |  |
|   |   |   |   |   |   |  |     | LEVELING JACK ASSEMBLY   | 10.25.85     |               |  |
|   |   |   |   |   |   |  |     | WORM GEAR                | 10.25.85     |               |  |
|   |   |   |   |   |   |  |     | COUPLING                 | 10.25.85     |               |  |
|   |   |   |   |   |   |  |     | HYDRAULIC MOTOR          | 10.25.85     |               |  |
|   |   |   |   |   |   |  |     | JACK BODY L.H.           | 10.25.85     |               |  |
|   |   |   |   |   |   |  |     | JACK BODH R.H.           | 10.25.85     |               |  |
|   |   |   |   |   |   |  |     | JACK LEG                 | 10.25.85     |               |  |
| COMPILED BY: Peter B. Dowden                    |   |   |   |   |   |  |     | DATE: 10.25.85           | NO. A25926   | REV -         |  |



## SANDIA DPBM - MASTER DRAWING LIST

SHEET 9 OF 28

ASSEMBLY TITLE: MOBILE DERRICK ASSEMBLY  
 DRAWING NO: D35920

(CON'T)

| DRAWING NO.  |   |   |   |   |   | REV             | TITLE                                   | RELEASE DATE |          |     |        |     |   |
|--------------|---|---|---|---|---|-----------------|---|--------------|----------|-----|--------|-----|---|
| 1            | 2 | 3 | 4 | 5 | 6 |                 |   |              |          |     |        |     |   |
|              |   |   |   |   |   |                 | B36025<br>PLATE                         | 10.25.85     |          |     |        |     |   |
|              |   |   |   |   |   |                 | D36026<br>TORQUE REACTION JACK ASSEMBLY | 10.25.85     |          |     |        |     |   |
|              |   |   |   |   |   |                 | B36027<br>ROD                           | 10.25.85     |          |     |        |     |   |
|              |   |   |   |   |   |                 | B36028<br>LOCKNUT                       | 10.25.85     |          |     |        |     |   |
|              |   |   |   |   |   |                 | B36029<br>SLEEVE                        | 10.25.85     |          |     |        |     |   |
|              |   |   |   |   |   |                 | D36037<br>PULLBACK REACTION JACK        | 10.25.85     |          |     |        |     |   |
|              |   |   |   |   |   |                 | B36036<br>SLEEVE                        | 10.25.85     |          |     |        |     |   |
|              |   |   |   |   |   |                 | D36034<br>ROD                           | 10.25.85     |          |     |        |     |   |
|              |   |   |   |   |   |                 | D36035<br>TUBE                          | 10.25.85     |          |     |        |     |   |
|              |   |   |   |   |   |                 | D36046<br>THRUST REACTION PAD ASSEMBLY  | 10.25.85     |          |     |        |     |   |
|              |   |   |   |   |   |                 | D36041<br>THRUST PAD                    | 10.25.85     |          |     |        |     |   |
|              |   |   |   |   |   |                 | B36042<br>RETAINER PLATE                | 10.25.85     |          |     |        |     |   |
|              |   |   |   |   |   |                 | B36043<br>PIN                           | 10.25.85     |          |     |        |     |   |
|              |   |   |   |   |   |                 | D36044<br>ROD EYE                       | 10.25.85     |          |     |        |     |   |
|              |   |   |   |   |   |                 | A36045<br>RUBBER CUSHION                | 10.25.85     |          |     |        |     |   |
|              |   |   |   |   |   |                 | D36040<br>FRAME ASSEMBLY                | 10.25.85     |          |     |        |     |   |
|              |   |   |   |   |   |                 | D36019<br>COLUMN ASSEMBLY               | 10.25.85     |          |     |        |     |   |
|              |   |   |   |   |   |                 | D36020<br>COLUMN                        | 10.25.85     |          |     |        |     |   |
|              |   |   |   |   |   |                 | D36021<br>COUPLING HALF                 | 10.25.85     |          |     |        |     |   |
|              |   |   |   |   |   |                 | D36033<br>HEAD FRAME ASSEMBLY           | 10.25.85     |          |     |        |     |   |
|              |   |   |   |   |   |                 | D36032<br>HEAD FRAME                    | 10.25.85     |          |     |        |     |   |
|              |   |   |   |   |   |                 | D36031<br>COUPLING HALF                 | 10.25.85     |          |     |        |     |   |
|              |   |   |   |   |   |                 | D36038<br>MAIN FRAME                    | 10.25.85     |          |     |        |     |   |
| COMPILED BY: |   |   |   |   |   | Peter B. Dowden |   | DATE:        | 10.25.85 | NO. | A35926 | REV | - |

## SANDIA DPBM - MASTER DRAWING LIST

SHEET 10 OF 28

ASSEMBLY TITLE: MOBILE DERRICK ASSEMBLY  
 DRAWING NO: D35920

(CON'T)

| DRAWING NO.     |   |   |   |   |   |  | REV | TITLE    | RELEASE DATE                   |          |
|-----------------|---|---|---|---|---|--|-----|----------|--------------------------------|----------|
| 1               | 2 | 3 | 4 | 5 | 6 |  |     |          |                                |          |
|                 |   |   |   |   |   |  |     | D36031   | COUPLING HALF                  | 10.25.85 |
|                 |   |   |   |   |   |  |     | D36039   | BEAM                           | 10.25.85 |
|                 |   |   |   |   |   |  |     | B36047   | THREADED SHAFT                 | 10.25.85 |
|                 |   |   |   |   |   |  |     | D36075   | CROSSHEAD                      | 10.25.85 |
|                 |   |   |   |   |   |  |     | D36074   | CROSSHEAD PRE-MACHINING        | 10.25.85 |
|                 |   |   |   |   |   |  |     | D36076   | CYLINDER RETAINER              | 10.25.85 |
|                 |   |   |   |   |   |  |     | D36077   | COLUMN RETAINER                | 10.25.85 |
|                 |   |   |   |   |   |  |     | D36078   | SEAL RETAINER - SPLIT          | 10.25.85 |
|                 |   |   |   |   |   |  |     | D36079   | BUSHING SPLIT                  | 10.25.85 |
|                 |   |   |   |   |   |  |     | B36080   | THRUST WASHER ASSEMBLY         | 10.25.85 |
|                 |   |   |   |   |   |  |     | D36081   | THRUST RING                    | 10.25.85 |
|                 |   |   |   |   |   |  |     | D36082   | PIVOT MOUNT                    | 10.25.85 |
|                 |   |   |   |   |   |  |     | D36083   | PIVOT BLOCK                    | 10.25.85 |
|                 |   |   |   |   |   |  |     | D36084   | CYLINDER MOUNT - INNER         | 10.25.85 |
|                 |   |   |   |   |   |  |     | D36085   | CYLINDER MOUNT - OUTER         | 10.25.85 |
|                 |   |   |   |   |   |  |     | D36741   | THRUST CYLINDER - LOWER        | 10.25.85 |
|                 |   |   |   |   |   |  |     | B36511   | LINER CLAMP CYLINDER           | 10.25.85 |
|                 |   |   |   |   |   |  |     | B36030   | BARREL NUT                     | 10.25.85 |
|                 |   |   |   |   |   |  |     | B36512   | GRIPPER PAD - INNER            | 10.25.85 |
|                 |   |   |   |   |   |  |     | B36513   | GRIPPER PAD - OUTER            | 10.25.85 |
|                 |   |   |   |   |   |  |     | D36510   | DERRICK MUCK ELBOW             | 10.25.85 |
|                 |   |   |   |   |   |  |     | D36509   | TELESCOPIC MUCK JOINT ASSEMBLY | 10.25.85 |
|                 |   |   |   |   |   |  |     | D36143   | TELESCOPIC TUBE                | 10.25.85 |
|                 |   |   |   |   |   |  |     | D36142   | CYLINDER MOUNT TUBE            | 10.25.85 |
| COMPILED BY:    |   |   |   |   |   |  |     | DATE:    | NO.                            | REV      |
| Peter B. Dowden |   |   |   |   |   |  |     | 10.25.85 | A35926                         | -        |



| SANDIA DPBM - MASTER DRAWING LIST       |   |   |   |   |   |  |     |                                      |              |  | SHEET 12 OF 29 |  |
|---|---|---|---|---|---|--|-----|--------------------------------------|--------------|--|----------------|--|
| ASSEMBLY TITLE: MUCKING SYSTEM ASSEMBLY |   |   |   |   |   |  |     |                                      |              |  |                |  |
| DRAWING NO: D35632                      |   |   |   |   |   |  |     |                                      |              |  |                |  |
| DRAWING NO.                             |   |   |   |   |   |  | REV | TITLE                                | RELEASE DATE |  |                |  |
| 1                                       | 2 | 3 | 4 | 5 | 6 |  |     |                                      |              |  |                |  |
| D35632                                  |   |   |   |   |   |  |     | MUCKING SYSTEM - GENERAL ARRANGEMENT | 10.25.85     |  |                |  |
| D35620                                  |   |   |   |   |   |  |     | DROP BOX ASSEMBLY                    | 10.25.85     |  |                |  |
| D36555                                  |   |   |   |   |   |  |     | SKID - DROP BOX                      | 10.25.85     |  |                |  |
| D36566                                  |   |   |   |   |   |  |     | EJECTOR DISCHARGE PIPE               | 10.25.85     |  |                |  |
| D35607                                  |   |   |   |   |   |  |     | EJECTOR VALVE ASSEMBLY               | 10.25.85     |  |                |  |
| D35595                                  |   |   |   |   |   |  |     | VALVE BODY                           | 10.25.85     |  |                |  |
| D35619                                  |   |   |   |   |   |  |     | BODY BLOCK                           | 10.25.85     |  |                |  |
| B35618                                  |   |   |   |   |   |  |     | BULB VALVE - EJECTOR VALVE           | 10.25.85     |  |                |  |
| B35603                                  |   |   |   |   |   |  |     | CAP - EJECTOR VALVE                  | 10.25.85     |  |                |  |
| A35612                                  |   |   |   |   |   |  |     | GASKET - EJECTOR VALVE               | 10.25.85     |  |                |  |
| A35601                                  |   |   |   |   |   |  |     | SPRING CAP - EJECTOR VALVE           | 10.25.85     |  |                |  |
| A35604                                  |   |   |   |   |   |  |     | LOCKNUT - EJECTOR VALVE              | 10.25.85     |  |                |  |
| B35602                                  |   |   |   |   |   |  |     | FORK END - EJECTOR VALVE             | 10.25.85     |  |                |  |
| B35611                                  |   |   |   |   |   |  |     | SPINDLE - EJECTOR VALVE              | 10.25.85     |  |                |  |
| B35609                                  |   |   |   |   |   |  |     | SPRING - EJECTOR VALVE               | 10.25.85     |  |                |  |
| B35606                                  |   |   |   |   |   |  |     | LINK - EJECTOR VALVE                 | 10.25.85     |  |                |  |
| B35605                                  |   |   |   |   |   |  |     | LEVER - EJECTOR VALVE                | 10.25.85     |  |                |  |
| B35608                                  |   |   |   |   |   |  |     | PIN - EJECTOR VALVE                  | 10.25.85     |  |                |  |
| B36565                                  |   |   |   |   |   |  |     | GASKET - DROP BOX HOPPER/VALVE       | 10.25.85     |  |                |  |
| D35625                                  |   |   |   |   |   |  |     | HOPPER - DROP BOX                    | 10.25.85     |  |                |  |
| D35638                                  |   |   |   |   |   |  |     | GASKET - DROP BOX                    | 10.25.85     |  |                |  |
| D35629                                  |   |   |   |   |   |  |     | DROP BOX BODY                        | 10.25.85     |  |                |  |
| D35630                                  |   |   |   |   |   |  |     | SLOTTED EXPANSION TUBE               | 10.25.85     |  |                |  |
| D36533                                  |   |   |   |   |   |  |     | GASKET                               | 10.25.85     |  |                |  |
| COMPILED BY: Peter B. Dowden            |   |   |   |   |   |  |     | DATE: 10.25.85                       | NO. A35926   |  | REV -          |  |

| SANDIA DPBM - MASTER DRAWING LIST               |   |   |   |   |   |  |     |                                      |              | SHEET 13 OF 28 |  |
|---|---|---|---|---|---|--|-----|--------------------------------------|--------------|----------------|--|
| ASSEMBLY TITLE: MUCKING SYSTEM ASSEMBLY (CON'T) |   |   |   |   |   |  |     |                                      |              |                |  |
| DRAWING NO: D35632                              |   |   |   |   |   |  |     |                                      |              |                |  |
| DRAWING NO.                                     |   |   |   |   |   |  | REV | TITLE                                | RELEASE DATE |                |  |
| 1   | 2 | 3 | 4 | 5 | 6 |  |     |                                      |              |                |  |
|   |   |   |   |   |   |  |     | DOOR - DROP BOX                      | 10.25.85     |                |  |
|   |   |   |   |   |   |  |     | DOOR GASKET - DROP BOX               | 10.25.85     |                |  |
|   |   |   |   |   |   |  |     | SCREEN ASSEMBLY                      | 10.25.85     |                |  |
|   |   |   |   |   |   |  |     | TOP SECTION - DROP BOX               | 10.25.85     |                |  |
|   |   |   |   |   |   |  |     | PRIMARY FILTER UNIT ASSEMBLY         | 10.25.85     |                |  |
|   |   |   |   |   |   |  |     | 45 DEGREE ELBOW                      | 10.25.85     |                |  |
|   |   |   |   |   |   |  |     | SKID - FILTER UNIT                   | 10.25.85     |                |  |
|   |   |   |   |   |   |  |     | SCREW CONVEYOR                       | 10.25.85     |                |  |
|   |   |   |   |   |   |  |     | MOUNTING SUPPORT                     | 10.25.85     |                |  |
|   |   |   |   |   |   |  |     | TRANSITION (45°)                     | 10.25.85     |                |  |
|   |   |   |   |   |   |  |     | HOPPER                               | 10.25.85     |                |  |
|   |   |   |   |   |   |  |     | FILTER BOX                           | 10.25.85     |                |  |
|   |   |   |   |   |   |  |     | COVER - TOP                          | 10.25.85     |                |  |
|   |   |   |   |   |   |  |     | GASKET                               | 10.25.85     |                |  |
|   |   |   |   |   |   |  |     | END COVER                            | 10.25.85     |                |  |
|   |   |   |   |   |   |  |     | END COVER GASKET                     | 10.25.85     |                |  |
|   |   |   |   |   |   |  |     | GASKET                               | 10.25.85     |                |  |
|   |   |   |   |   |   |  |     | GASKET                               | 10.25.85     |                |  |
|   |   |   |   |   |   |  |     | GASKET - MARLIN VALVE                | 10.25.85     |                |  |
|   |   |   |   |   |   |  |     | TRANSITION - SCREW CONVEYOR TO VALVE | 10.25.85     |                |  |
|   |   |   |   |   |   |  |     | TRANSITION - VALVE TO BAG            | 10.25.85     |                |  |
|   |   |   |   |   |   |  |     | VALVE - CLARKSON 6"                  | 10.25.85     |                |  |
|   |   |   |   |   |   |  |     | FILTER COMPONENTS                    | 10.25.85     |                |  |
| COMPILED BY: Peter B. Dowden                    |   |   |   |   |   |  |     | DATE: 10.25.85                       | NO. A35926   | REV -          |  |

## SANDIA DPBM - MASTER DRAWING LIST

SHEET 14 OF 28

ASSEMBLY TITLE: MUCKING SYSTEM ASSEMBLY

(CON'T)

DRAWING NO: D35632

| DRAWING NO.                  |   |   |   |   |   |  | REV | TITLE                         | RELEASE DATE |
|------------------------------|---|---|---|---|---|--|-----|-------------------------------|--------------|
| 1                            | 2 | 3 | 4 | 5 | 6 |  |     |                               |              |
|                              |   |   |   |   |   |  |     | VACUUM PUMP UNIT              | 10.25.85     |
|                              |   |   |   |   |   |  |     | SKID-VACUUM PUMP ASSEMBLY     | 10.25.85     |
|                              |   |   |   |   |   |  |     | SILENCER - VACUUM PUMP        | 10.25.85     |
|                              |   |   |   |   |   |  |     | BELT GUARD - PUMP DRIVE       | 10.25.85     |
|                              |   |   |   |   |   |  |     | ELECTRIC MOTOR 200HP          | 10.25.85     |
|                              |   |   |   |   |   |  |     | VACUUM PUMP                   | 10.25.85     |
|                              |   |   |   |   |   |  |     | EXPANSION JOINT               | 10.25.85     |
|                              |   |   |   |   |   |  |     | EXPANSION JOINT               | 10.25.85     |
|                              |   |   |   |   |   |  |     | DUCT ELBOW                    | 10.25.85     |
|                              |   |   |   |   |   |  |     | FILTER BOX - SECONDARY        | 10.25.85     |
|                              |   |   |   |   |   |  |     | COVER                         | 10.25.85     |
|                              |   |   |   |   |   |  |     | GASKET                        | 10.25.85     |
|                              |   |   |   |   |   |  |     | COVER                         | 10.25.85     |
|                              |   |   |   |   |   |  |     | GASKET                        | 10.25.85     |
|                              |   |   |   |   |   |  |     | GASKET                        | 10.25.85     |
|                              |   |   |   |   |   |  |     | FILTER PACK                   | 10.25.85     |
|                              |   |   |   |   |   |  |     | PEDESTAL - FILTER BOX         | 10.25.85     |
|                              |   |   |   |   |   |  |     | PEDESTAL - FILTER BOX         | 10.25.85     |
|                              |   |   |   |   |   |  |     | GASKET                        | 10.25.85     |
|                              |   |   |   |   |   |  |     | VACUUM SYSTEM CONTROL CONSOLE | 10.25.85     |
|                              |   |   |   |   |   |  |     | D.C. MILLIAMMETER (TEMP)      | 10.25.85     |
|                              |   |   |   |   |   |  |     | D.C. MILLIAMMETER (VACUUM)    | 10.25.85     |
|                              |   |   |   |   |   |  |     | D.C. MILLIAMMETER (TEMP)      | 10.25.85     |
|                              |   |   |   |   |   |  |     | D.C. MILLIAMMETER (VACUUM)    | 10.25.85     |
| COMPILED BY: Peter B. Dowden |   |   |   |   |   |  |     | DATE: 10.25.85                | NO. A35926   |
|                              |   |   |   |   |   |  |     |                               | REV -        |

| SANDIA DPBM - MASTER DRAWING LIST       |   |   |   |   |   |        |     |                                 |              | SHEET 15 OF 28 |  |
|---|---|---|---|---|---|--------|-----|---------------------------------|--------------|----------------|--|
| ASSEMBLY TITLE: MUCKING SYSTEM ASSEMBLY |   |   |   |   |   |        |     |                                 |              | (CON'T)        |  |
| DRAWING NO: D35632                      |   |   |   |   |   |        |     |                                 |              |                |  |
| DRAWING NO.                             |   |   |   |   |   |        | REV | TITLE                           | RELEASE DATE |                |  |
| 1                                       | 2 | 3 | 4 | 5 | 6 |        |     |                                 |              |                |  |
|   |   |   |   |   |   | A36505 |     | D.C. MILLIAMMETER(VACUUM)       | 10.25.85     |                |  |
|   |   |   |   |   |   | A37259 |     | AIR VELOCITY METER              | 10.25.85     |                |  |
|   |   |   |   |   |   | A37259 |     | PHASE SELECTOR SWITCH           | 10.25.85     |                |  |
|   |   |   |   |   |   | D36528 |     | EXPANSION JOINT TRANSFER PIPE   | 10.25.85     |                |  |
|   |   |   |   |   |   | D36534 |     | BODY                            | 10.25.85     |                |  |
|   |   |   |   |   |   | D36535 |     | PISTON                          | 10.25.85     |                |  |
|   |   |   |   |   |   | B36536 |     | FLANGE - ROD WIPER              | 10.25.85     |                |  |
|   |   |   |   |   |   | B37345 |     | PACKING RETAINER                | 10.25.85     |                |  |
|   |   |   |   |   |   | B37346 |     | PACKING                         | 10.25.85     |                |  |
|   |   |   |   |   |   | D35599 |     | RAIL - EXPANSION JOINT          | 10.25.85     |                |  |
|   |   |   |   |   |   | B37165 |     | THREADED PISTON STOP            | 10.25.85     |                |  |
|   |   |   |   |   |   | A37170 |     | KGA PNEUMATIC SOLENOID VALVE    | 10.25.85     |                |  |
|   |   |   |   |   |   | B37338 |     | SEAL - GUARD RETAINER           | 10.25.85     |                |  |
|   |   |   |   |   |   | D36537 |     | SUPPORT FRAME                   | 10.25.85     |                |  |
|   |   |   |   |   |   | D36533 |     | TRANSITION ASSEMBLY             | 10.25.85     |                |  |
|   |   |   |   |   |   | A37170 |     | PNEUMATIC SOLENOID VALVE        | 10.25.85     |                |  |
|   |   |   |   |   |   | A37171 |     | EXPANSION JOINT                 | 10.25.85     |                |  |
|   |   |   |   |   |   | D36531 |     | TRANSITION - DROP BOX           | 10.25.85     |                |  |
|   |   |   |   |   |   | D35624 |     | DROP BOX CONNECTION VACUUM PIPE | 10.25.85     |                |  |
|   |   |   |   |   |   | D35614 |     | DROP BOX CONNECTION MUCK PIPE   | 10.25.85     |                |  |
|   |   |   |   |   |   | D35596 |     | MUCK PIPE- DROP BOX CONNECTOR   | 10.25.85     |                |  |
|   |   |   |   |   |   | B35594 |     | SPLIT RING - DROP BOX CONNECTOR | 10.25.85     |                |  |
|   |   |   |   |   |   | B35615 |     | SLIDING FLANGE RING             | 10.25.85     |                |  |
| COMPILED BY: Peter B. Dowden            |   |   |   |   |   |        |     | DATE: 10.25.85                  | NO. A35926   | REV -          |  |

| SANDIA DPBM - MASTER DRAWING LIST       |   |   |   |   |   |  |     |                                     |              |  | SHEET 16 OF 28 |  |  |
|---|---|---|---|---|---|--|-----|-------------------------------------|--------------|--|----------------|--|--|
| ASSEMBLY TITLE: MUCKING SYSTEM ASSEMBLY |   |   |   |   |   |  |     |                                     |              |  | (CON'T)        |  |  |
| DRAWING NO: D35632                      |   |   |   |   |   |  |     |                                     |              |  |                |  |  |
| DRAWING NO.                             |   |   |   |   |   |  | REV | TITLE                               | RELEASE DATE |  |                |  |  |
| 1                                       | 2 | 3 | 4 | 5 | 6 |  |     |                                     |              |  |                |  |  |
|   |   |   |   |   |   |  |     | BALL JOINT ASSEMBLY                 | 10.25.85     |  |                |  |  |
|   |   |   |   |   |   |  |     | BALL JOINT SOCKET                   | 10.25.85     |  |                |  |  |
|   |   |   |   |   |   |  |     | BALL JOINT RETAINER                 | 10.25.85     |  |                |  |  |
|   |   |   |   |   |   |  |     | BALL JOINT                          | 10.25.85     |  |                |  |  |
|   |   |   |   |   |   |  |     | GASKET                              | 10.25.85     |  |                |  |  |
|   |   |   |   |   |   |  |     | END STOP - DROP BOX                 | 10.25.85     |  |                |  |  |
|   |   |   |   |   |   |  |     | VACUUM DUCT STOP                    | 10.25.85     |  |                |  |  |
|   |   |   |   |   |   |  |     | DROP BOX SKID HINGE                 | 10.25.85     |  |                |  |  |
|   |   |   |   |   |   |  |     | DROP BOX SKID HINGE                 | 10.25.85     |  |                |  |  |
|   |   |   |   |   |   |  |     | TRANSFER PIPE                       | 10.25.85     |  |                |  |  |
|   |   |   |   |   |   |  |     | WATER INJECTION - EJECTOR DISCHARGE | 10.25.85     |  |                |  |  |
|   |   |   |   |   |   |  |     | FLEXIBLE HOSE ASSEMBLY              | 10.25.85     |  |                |  |  |
|   |   |   |   |   |   |  |     | GASKET                              | 10.25.85     |  |                |  |  |
|   |   |   |   |   |   |  |     | GASKET                              | 10.25.85     |  |                |  |  |
|   |   |   |   |   |   |  |     | DISCHARGE PIPE INTERCONNECTORS      | 10.25.85     |  |                |  |  |
|   |   |   |   |   |   |  |     | 12.0 EXPANSION JOINT                | 10.25.85     |  |                |  |  |
|   |   |   |   |   |   |  |     | COMPOUND GAUGE ASSEMBLY             | 10.25.85     |  |                |  |  |
|   |   |   |   |   |   |  |     | VACUUM SENSOR                       | 10.25.85     |  |                |  |  |
|   |   |   |   |   |   |  |     | DIFF. VACUUM SENSOR                 | 10.25.85     |  |                |  |  |
|   |   |   |   |   |   |  |     | TRANS. PIPE - AIR INJECTION ASSY.   | 10.25.85     |  |                |  |  |
|   |   |   |   |   |   |  |     | WATER INJECTION - VAC. P. INLET     | 10.25.85     |  |                |  |  |
|   |   |   |   |   |   |  |     | TEMPERATURE SENSOR                  | 10.25.85     |  |                |  |  |
|   |   |   |   |   |   |  |     | VELOCITY SENSOR                     | 10.25.85     |  |                |  |  |
| COMPILED BY: Peter B. Dowden            |   |   |   |   |   |  |     | DATE: 10.25.85                      | NO. A35926   |  | REV -          |  |  |



| <b>SANDIA DPBM - MASTER DRAWING LIST</b>   |   |   |   |   |   |  |     |                                 |                             | <b>SHEET 17 OF 28</b> |                        |
|--|---|---|---|---|---|--|-----|---------------------------------|-----------------------------|-----------------------|------------------------|
| <b>ASSEMBLY TITLE:</b> <b>MUCKING SYSTEM ASSEMBLY</b> <b>(CON'T)</b><br><b>DRAWING NO:</b> <b>D35632</b> |   |   |   |   |   |  |     |                                 |                             |                       |                        |
| DRAWING NO.  |   |   |   |   |   |  | REV | TITLE                           | RELEASE DATE                |                       |                        |
| 1  | 2 | 3 | 4 | 5 | 6 |  |     |                                 |                             |                       |                        |
|  |   |   |   |   |   |  |     | DIFF. VACUUM SENSOR             | 10.25.85                    |                       |                        |
|  |   |   |   |   |   |  |     | TEMPERATURE SENSOR              | 10.25.85                    |                       |                        |
|  |   |   |   |   |   |  |     | PRESSURE SENSOR                 | 10.25.85                    |                       |                        |
|  |   |   |   |   |   |  |     | TEMPERATURE SENSOR              | 10.25.85                    |                       |                        |
|  |   |   |   |   |   |  |     | MASTER AIR VALVE ASSY. DROP BOX | 10.25.85                    |                       |                        |
|  |   |   |   |   |   |  |     |                                 |                             |                       |                        |
| <b>COMPILED BY:</b> <b>Peter B. Dowden</b>   |   |   |   |   |   |  |     | <b>DATE:</b><br><b>10.25.85</b> | <b>NO.</b><br><b>A35926</b> |                       | <b>REV</b><br><b>-</b> |

ASSEMBLY TITLE: CONTROL STATION ASSEMBLY  
 DRAWING NO: D35927

| DRAWING NO.                  |   |   |   |   |   | REV      | TITLE                      | RELEASE<br>DATE |
|------------------------------|---|---|---|---|---|----------|----------------------------|-----------------|
| 1                            | 2 | 3 | 4 | 5 | 6 |          |                            |                 |
| D35927                       |   |   |   |   |   |          | CONTROL STATION ASSEMBLY   | 10.25.85        |
| D36158                       |   |   |   |   |   |          | CONTROL CONSOLE STAND      | 10.25.85        |
| D36621                       |   |   |   |   |   |          | OPERATOR'S PLATFORM        | 10.25.85        |
| D36620                       |   |   |   |   |   |          | LAMP HOOD                  | 10.25.85        |
| A36617                       |   |   |   |   |   |          | OPERATOR'S SEAT            | 10.25.85        |
| A36619                       |   |   |   |   |   |          | PEDESTAL - OPERATOR'S SEAT | 10.25.85        |
| A36618                       |   |   |   |   |   |          | LIGHT FIXTURE              | 10.25.85        |
| COMPILED BY: Peter B. Dowden |   |   |   |   |   | DATE:    | NO.                        | REV             |
|                              |   |   |   |   |   | 10.25.85 | A35926                     | -               |

**SHEET 19 OF 28**

DRAWING NO.

**MUCK TUBE - DRIVER**

**DRAWING NO: D36662**

REV

**TITLE**

RELEASE  
DATE

|   |   |   |   |   |   |
|---|---|---|---|---|---|
| 1 | 2 | 3 | 4 | 5 | 6 |
|---|---|---|---|---|---|

**D36662**

**MUCK TUBE - DRIVER**

10.25.85

**B36114**

**FLANGE - FEMALE**

**10.25.85**

**B36115**

**FLANGE - MALE**

10.25.85

**A36109**

## WHEEL BRACKET

**10.25.85**

**A36108**

**WHEEL**

10.25.85

**B36137**

## CABLE SUPPORT BRACKET

**10.25.85**

**D36664**

### DRIVE PLATE

**10.25.85**

**COMPILED BY:**

**Peter B. Dowden**

**DATE:**

**10.25.85**

NO.

**A35926**

REV

•

ASSEMBLY TITLE: MUCK TUBE ASSEMBLY  
DRAWING NO: D36136

| DRAWING NO. |   |   |   |   |   |  | REV | TITLE                 | RELEASE<br>DATE |
|-------------|---|---|---|---|---|--|-----|-----------------------|-----------------|
| 1           | 2 | 3 | 4 | 5 | 6 |  |     |                       |                 |
| D36136      |   |   |   |   |   |  |     | MUCK TUBE ASSEMBLY    | 10.25.85        |
| B36114      |   |   |   |   |   |  |     | FLANGE - FEMALE       | 10.25.85        |
| B36115      |   |   |   |   |   |  |     | FLANGE - MALE         | 10.25.85        |
| A36109      |   |   |   |   |   |  |     | WHEEL BRACKET         | 10.25.85        |
| A36108      |   |   |   |   |   |  |     | WHEEL                 | 10.25.85        |
| B36137      |   |   |   |   |   |  |     | CABLE SUPPORT BRACKET | 10.25.85        |
|             |   |   |   |   |   |  |     |                       |                 |
|             |   |   |   |   |   |  |     |                       |                 |
|             |   |   |   |   |   |  |     |                       |                 |
|             |   |   |   |   |   |  |     |                       |                 |
|             |   |   |   |   |   |  |     |                       |                 |
|             |   |   |   |   |   |  |     |                       |                 |
|             |   |   |   |   |   |  |     |                       |                 |
|             |   |   |   |   |   |  |     |                       |                 |
|             |   |   |   |   |   |  |     |                       |                 |
|             |   |   |   |   |   |  |     |                       |                 |
|             |   |   |   |   |   |  |     |                       |                 |
|             |   |   |   |   |   |  |     |                       |                 |
|             |   |   |   |   |   |  |     |                       |                 |
|             |   |   |   |   |   |  |     |                       |                 |
|             |   |   |   |   |   |  |     |                       |                 |
|             |   |   |   |   |   |  |     |                       |                 |
|             |   |   |   |   |   |  |     |                       |                 |
|             |   |   |   |   |   |  |     |                       |                 |
|             |   |   |   |   |   |  |     |                       |                 |
|             |   |   |   |   |   |  |     |                       |                 |
|             |   |   |   |   |   |  |     |                       |                 |
|             |   |   |   |   |   |  |     |                       |                 |
|             |   |   |   |   |   |  |     |                       |                 |
|             |   |   |   |   |   |  |     |                       |                 |
|             |   |   |   |   |   |  |     |                       |                 |
|             |   |   |   |   |   |  |     |                       |                 |
|             |   |   |   |   |   |  |     |                       |                 |
|             |   |   |   |   |   |  |     |                       |                 |
|             |   |   |   |   |   |  |     |                       |                 |
|             |   |   |   |   |   |  |     |                       |                 |
|             |   |   |   |   |   |  |     |                       |                 |
|             |   |   |   |   |   |  |     |                       |                 |
|             |   |   |   |   |   |  |     |                       |                 |
|             |   |   |   |   |   |  |     |                       |                 |
|             |   |   |   |   |   |  |     |                       |                 |
|             |   |   |   |   |   |  |     |                       |                 |
|             |   |   |   |   |   |  |     |                       |                 |
|             |   |   |   |   |   |  |     |                       |                 |
|             |   |   |   |   |   |  |     |                       |                 |
|             |   |   |   |   |   |  |     |                       |                 |
|             |   |   |   |   |   |  |     |                       |                 |
|             |   |   |   |   |   |  |     |                       |                 |
|             |   |   |   |   |   |  |     |                       |                 |
|             |   |   |   |   |   |  |     |                       |                 |
|             |   |   |   |   |   |  |     |                       |                 |
|             |   |   |   |   |   |  |     |                       |                 |
|             |   |   |   |   |   |  |     |                       |                 |
|             |   |   |   |   |   |  |     |                       |                 |
|             |   |   |   |   |   |  |     |                       |                 |
|             |   |   |   |   |   |  |     |                       |                 |
|             |   |   |   |   |   |  |     |                       |                 |
|             |   |   |   |   |   |  |     |                       |                 |
|             |   |   |   |   |   |  |     |                       |                 |
|             |   |   |   |   |   |  |     |                       |                 |
|             |   |   |   |   |   |  |     |                       |                 |
|             |   |   |   |   |   |  |     |                       |                 |
|             |   |   |   |   |   |  |     |                       |                 |
|             |   |   |   |   |   |  |     |                       |                 |
|             |   |   |   |   |   |  |     |                       |                 |
|             |   |   |   |   |   |  |     |                       |                 |
|             |   |   |   |   |   |  |     |                       |                 |
|             |   |   |   |   |   |  |     |                       |                 |
|             |   |   |   |   |   |  |     |                       |                 |
|             |   |   |   |   |   |  |     |                       |                 |
|             |   |   |   |   |   |  |     |                       |                 |
|             |   |   |   |   |   |  |     |                       |                 |
|             |   |   |   |   |   |  |     |                       |                 |
|             |   |   |   |   |   |  |     |                       |                 |
|             |   |   |   |   |   |  |     |                       |                 |
|             |   |   |   |   |   |  |     |                       |                 |
|             |   |   |   |   |   |  |     |                       |                 |
|             |   |   |   |   |   |  |     |                       |                 |
|             |   |   |   |   |   |  |     |                       |                 |
|             |   |   |   |   |   |  |     |                       |                 |
|             |   |   |   |   |   |  |     |                       |                 |
|             |   |   |   |   |   |  |     |                       |                 |
|             |   |   |   |   |   |  |     |                       |                 |
|             |   |   |   |   |   |  |     |                       |                 |
|             |   |   |   |   |   |  |     |                       |                 |
|             |   |   |   |   |   |  |     |                       |                 |
|             |   |   |   |   |   |  |     |                       |                 |
|             |   |   |   |   |   |  |     |                       |                 |
|             |   |   |   |   |   |  |     |                       |                 |
|             |   |   |   |   |   |  |     |                       |                 |
|             |   |   |   |   |   |  |     |                       |                 |
|             |   |   |   |   |   |  |     |                       |                 |
|             |   |   |   |   |   |  |     |                       |                 |
|             |   |   |   |   |   |  |     |                       |                 |
|             |   |   |   |   |   |  |     |                       |                 |
|             |   |   |   |   |   |  |     |                       |                 |
|             |   |   |   |   |   |  |     |                       |                 |
|             |   |   |   |   |   |  |     |                       |                 |
|             |   |   |   |   |   |  |     |                       |                 |
|             |   |   |   |   |   |  |     |                       |                 |
|             |   |   |   |   |   |  |     |                       |                 |
|             |   |   |   |   |   |  |     |                       |                 |
|             |   |   |   |   |   |  |     |                       |                 |
|             |   |   |   |   |   |  |     |                       |                 |
|             |   |   |   |   |   |  |     |                       |                 |
|             |   |   |   |   |   |  |     |                       |                 |
|             |   |   |   |   |   |  |     |                       |                 |
|             |   |   |   |   |   |  |     |                       |                 |
|             |   |   |   |   |   |  |     |                       |                 |
|             |   |   |   |   |   |  |     |                       |                 |
|             |   |   |   |   |   |  |     |                       |                 |
|             |   |   |   |   |   |  |     |                       |                 |
|             |   |   |   |   |   |  |     |                       |                 |
|             |   |   |   |   |   |  |     |                       |                 |
|             |   |   |   |   |   |  |     |                       |                 |
|             |   |   |   |   |   |  |     |                       |                 |
|             |   |   |   |   |   |  |     |                       |                 |
|             |   |   |   |   |   |  |     |                       |                 |
|             |   |   |   |   |   |  |     |                       |                 |
|             |   |   |   |   |   |  |     |                       |                 |
|             |   |   |   |   |   |  |     |                       |                 |
|             |   |   |   |   |   |  |     |                       |                 |
|             |   |   |   |   |   |  |     |                       |                 |
|             |   |   |   |   |   |  |     |                       |                 |
|             |   |   |   |   |   |  |     |                       |                 |
|             |   |   |   |   |   |  |     |                       |                 |
|             |   |   |   |   |   |  |     |                       |                 |
|             |   |   |   |   |   |  |     |                       |                 |
|             |   |   |   |   |   |  |     |                       |                 |
|             |   |   |   |   |   |  |     |                       |                 |
|             |   |   |   |   |   |  |     |                       |                 |
|             |   |   |   |   |   |  |     |                       |                 |
|             |   |   |   |   |   |  |     |                       |                 |
|             |   |   |   |   |   |  |     |                       |                 |
|             |   |   |   |   |   |  |     |                       |                 |
|             |   |   |   |   |   |  |     |                       |                 |
|             |   |   |   |   |   |  |     |                       |                 |
|             |   |   |   |   |   |  |     |                       |                 |
|             |   |   |   |   |   |  |     |                       |                 |
|             |   |   |   |   |   |  |     |                       |                 |
|             |   |   |   |   |   |  |     |                       |                 |
|             |   |   |   |   |   |  |     |                       |                 |
|             |   |   |   |   |   |  |     |                       |                 |
|             |   |   |   |   |   |  |     |                       |                 |
|             |   |   |   |   |   |  |     |                       |                 |
|             |   |   |   |   |   |  |     |                       |                 |
|             |   |   |   |   |   |  |     |                       |                 |
|             |   |   |   |   |   |  |     |                       |                 |
|             |   |   |   |   |   |  |     |                       |                 |
|             |   |   |   |   |   |  |     |                       |                 |
|             |   |   |   |   |   |  |     |                       |                 |
|             |   |   |   |   |   |  |     |                       |                 |
|             |   |   |   |   |   |  |     |                       |                 |
|             |   |   |   |   |   |  |     |                       |                 |
|             |   |   |   |   |   |  |     |                       |                 |
|             |   |   |   |   |   |  |     |                       |                 |
|             |   |   |   |   |   |  |     |                       |                 |
|             |   |   |   |   |   |  |     |                       |                 |
|             |   |   |   |   |   |  |     |                       |                 |
|             |   |   |   |   |   |  |     |                       |                 |
|             |   |   |   |   |   |  |     |                       |                 |
|             |   |   |   |   |   |  |     |                       |                 |
|             |   |   |   |   |   |  |     |                       |                 |
|             |   |   |   |   |   |  |     |                       |                 |
|             |   |   |   |   |   |  |     |                       |                 |
|             |   |   |   |   |   |  |     |                       |                 |
|             |   |   |   |   |   |  |     |                       |                 |
|             |   |   |   |   |   |  |     |                       |                 |
|             |   |   |   |   |   |  |     |                       |                 |
|             |   |   |   |   |   |  |     |                       |                 |
|             |   |   |   |   |   |  |     |                       |                 |
|             |   |   |   |   |   |  |     |                       |                 |
|             |   |   |   |   |   |  |     |                       |                 |
|             |   |   |   |   |   |  |     |                       |                 |
|             |   |   |   |   |   |  |     |                       |                 |
|             |   |   |   |   |   |  |     |                       |                 |
|             |   |   |   |   |   |  |     |                       |                 |
|             |   |   |   |   |   |  |     |                       |                 |
|             |   |   |   |   |   |  |     |                       |                 |
|             |   |   |   |   |   |  |     |                       |                 |
|             |   |   |   |   |   |  |     |                       |                 |
|             |   |   |   |   |   |  |     |                       |                 |
|             |   |   |   |   |   |  |     |                       |                 |
|             |   |   |   |   |   |  |     |                       |                 |
|             |   |   |   |   |   |  |     |                       |                 |
|             |   |   |   |   |   |  |     |                       |                 |
|             |   |   |   |   |   |  |     |                       |                 |
|             |   |   |   |   |   |  |     |                       |                 |
|             |   |   |   |   |   |  |     |                       |                 |
|             |   |   |   |   |   |  |     |                       |                 |
|             |   |   |   |   |   |  |     |                       |                 |
|             |   |   |   |   |   |  |     |                       |                 |
|             |   |   |   |   |   |  |     |                       |                 |
|             |   |   |   |   |   |  |     |                       |                 |
|             |   |   |   |   |   |  |     |                       |                 |
|             |   |   |   |   |   |  |     |                       |                 |
|             |   |   |   |   |   |  |     |                       |                 |
|             |   |   |   |   |   |  |     |                       |                 |
|             |   |   |   |   |   |  |     |                       |                 |
|             |   |   |   |   |   |  |     |                       |                 |
|             |   |   |   |   |   |  |     |                       |                 |
|             |   |   |   |   |   |  |     |                       |                 |
|             |   |   |   |   |   |  |     |                       |                 |
|             |   |   |   |   |   |  |     |                       |                 |
|             |   |   |   |   |   |  |     |                       |                 |
|             |   |   |   |   |   |  |     |                       |                 |
|             |   |   |   |   |   |  |     |                       |                 |
|             |   |   |   |   |   |  |     |                       |                 |
|             |   |   |   |   |   |  |     |                       |                 |
|             |   |   |   |   |   |  |     |                       |                 |
|             |   |   |   |   |   |  |     |                       |                 |
|             |   |   |   |   |   |  |     |                       |                 |
|             |   |   |   |   |   |  |     |                       |                 |
|             |   |   |   |   |   |  |     |                       |                 |
|             |   |   |   |   |   |  |     |                       |                 |
|             |   |   |   |   |   |  |     |                       |                 |
|             |   |   |   |   |   |  |     |                       |                 |
|             |   |   |   |   |   |  |     |                       |                 |
|             |   |   |   |   |   |  |     |                       |                 |
|             |   |   |   |   |   |  |     |                       |                 |
|             |   |   |   |   |   |  |     |                       |                 |
|             |   |   |   |   |   |  |     |                       |                 |
|             |   |   |   |   |   |  |     |                       |                 |
|             |   |   |   |   |   |  |     |                       |                 |
|             |   |   |   |   |   |  |     |                       |                 |
|             |   |   |   |   |   |  |     |                       |                 |
|             |   |   |   |   |   |  |     |                       |                 |
|             |   |   |   |   |   |  |     |                       |                 |
|             |   |   |   |   |   |  |     |                       |                 |
|             |   |   |   |   |   |  |     |                       |                 |
|             |   |   |   |   |   |  |     |                       |                 |
|             |   |   |   |   |   |  |     |                       |                 |
|             |   |   |   |   |   |  |     |                       |                 |
|             |   |   |   |   |   |  |     |                       |                 |
|             |   |   |   |   |   |  |     |                       |                 |
|             |   |   |   |   |   |  |     |                       |                 |
|             |   |   |   |   |   |  |     |                       |                 |
|             |   |   |   |   |   |  |     |                       |                 |
|             |   |   |   |   |   |  |     |                       |                 |
|             |   |   |   |   |   |  |     |                       |                 |
|             |   |   |   |   |   |  |     |                       |                 |
|             |   |   |   |   |   |  |     |                       |                 |
|             |   |   |   |   |   |  |     |                       |                 |
|             |   |   |   |   |   |  |     |                       |                 |
|             |   |   |   |   |   |  |     |                       |                 |
|             |   |   |   |   |   |  |     |                       |                 |
|             |   |   |   |   |   |  |     |                       |                 |
|             |   |   |   |   |   |  |     |                       |                 |
|             |   |   |   |   |   |  |     |                       |                 |
|             |   |   |   |   |   |  |     |                       |                 |
|             |   |   |   |   |   |  |     |                       |                 |
|             |   |   |   |   |   |  |     |                       |                 |
|             |   |   |   |   |   |  |     |                       |                 |

| SANDIA DPBM - MASTER DRAWING LIST                   |   |   |   |   |   |     |                               |              |     | SHEET 21 OF 28 |  |
|---|---|---|---|---|---|-----|-------------------------------|--------------|-----|----------------|--|
| ASSEMBLY TITLE:           HYDRAULIC SYSTEM ASSEMBLY |   |   |   |   |   |     |                               |              |     |                |  |
| DRAWING NO:       D35914                            |   |   |   |   |   |     |                               |              |     |                |  |
| DRAWING NO.   |   |   |   |   |   | REV | TITLE                         | RELEASE DATE |     |                |  |
| 1   | 2 | 3 | 4 | 5 | 6 |     |                               |              |     |                |  |
| D35914  |   |   |   |   |   |     | HYDRAULIC SYSTEM ASSEMBLY     | 10.25.85     |     |                |  |
| D35924  |   |   |   |   |   |     | IN-HOLE DRILL INSTALLATION    | 10.25.85     |     |                |  |
| D36135  |   |   |   |   |   |     | POWER UNIT ASSEMBLY - IN-HOLE | 10.25.85     |     |                |  |
| D36073  |   |   |   |   |   |     | HYDRAULIC RESERVOIR           | 10.25.85     |     |                |  |
| B36131  |   |   |   |   |   |     | MANIFOLD BLOCK                | 10.25.85     |     |                |  |
| D36122  |   |   |   |   |   |     | RETURN HEADER                 | 10.25.85     |     |                |  |
| D36104  |   |   |   |   |   |     | MANIFOLD ASSEMBLY             | 10.25.85     |     |                |  |
| A36649  |   |   |   |   |   |     | DIRECTIONAL VALVE             | 10.25.85     |     |                |  |
| A36652  |   |   |   |   |   |     | COUNTERBALANCE VALVE          | 10.25.85     |     |                |  |
| A36663  |   |   |   |   |   |     | MANIFOLD                      | 10.25.85     |     |                |  |
| D36116  |   |   |   |   |   |     | MANIFOLD ASSEMBLY             | 10.25.85     |     |                |  |
| A36649  |   |   |   |   |   |     | DIRECTIONAL VALVE             | 10.25.85     |     |                |  |
| A36654  |   |   |   |   |   |     | CHECK VALVE                   | 10.25.85     |     |                |  |
| A36662  |   |   |   |   |   |     | MANIFOLD                      | 10.25.85     |     |                |  |
| A36651  |   |   |   |   |   |     | RELIEF VALVE                  | 10.25.85     |     |                |  |
| D36156  |   |   |   |   |   |     | MANIFOLD ASSEMBLY             | 10.25.85     |     |                |  |
| D36110  |   |   |   |   |   |     | MANIFOLD                      | 10.25.85     |     |                |  |
| A36650  |   |   |   |   |   |     | RELIEF VALVE                  | 10.25.85     |     |                |  |
| A36648  |   |   |   |   |   |     | DIRECTIONAL VALVE             | 10.25.85     |     |                |  |
| A36655  |   |   |   |   |   |     | RELIEF VALVE                  | 10.25.85     |     |                |  |
| A36653  |   |   |   |   |   |     | CHECK VALVE                   | 10.25.85     |     |                |  |
| D36132  |   |   |   |   |   |     | MANIFOLD - BULKHEAD           | 10.25.85     |     |                |  |
| B36151  |   |   |   |   |   |     | PUMP/MOTOR ADAPTER            | 10.25.85     |     |                |  |
| B36152  |   |   |   |   |   |     | COUPLING                      | 10.25.85     |     |                |  |
| COMPILED BY:  |   |   |   |   |   |     | DATE:                         | NO.          | REV |                |  |
| Peter B. Dowden                                     |   |   |   |   |   |     | 10.25.85                      | A35926       | -   |                |  |

| SANDIA DPBM - MASTER DRAWING LIST         |   |   |   |   |   |     |        |                                  |          | SHEET 22 OF 28 |  |
|---|---|---|---|---|---|-----|--------|----------------------------------|----------|----------------|--|
| ASSEMBLY TITLE: HYDRAULIC SYSTEM ASSEMBLY |   |   |   |   |   |     |        |                                  |          | (CON'T)        |  |
| DRAWING NO: D35914                        |   |   |   |   |   |     |        |                                  |          |                |  |
| DRAWING NO.                               |   |   |   |   |   | REV | TITLE  | RELEASE DATE                     |          |                |  |
| 1   | 2 | 3 | 4 | 5 | 6 |     |        |                                  |          |                |  |
|   |   |   |   |   |   |     | B36153 | COVER PLATE                      | 10.25.85 |                |  |
|   |   |   |   |   |   |     | B36154 | GASKET                           | 10.25.85 |                |  |
|   |   |   |   |   |   |     | B36140 | LEVEL SWITCH ADAPTER             | 10.25.85 |                |  |
|   |   |   |   |   |   |     | B36141 | LEVEL GAGE                       | 10.25.85 |                |  |
|   |   |   |   |   |   |     | A36728 | ELECTRIC MOTOR, 5 H.P., 1800 RPM | 10.25.85 |                |  |
|   |   |   |   |   |   |     | A36623 | RADIAL PISTON PUMP               | 10.25.85 |                |  |
|   |   |   |   |   |   |     | A36658 | SUCTION STRAINER                 | 10.25.85 |                |  |
|   |   |   |   |   |   |     | A36659 | RETURN FILTER                    | 10.25.85 |                |  |
|   |   |   |   |   |   |     | A36660 | AIR BREATHER                     | 10.25.85 |                |  |
|   |   |   |   |   |   |     | A36668 | SAMPLE VALVE                     | 10.25.85 |                |  |
|   |   |   |   |   |   |     | A36609 | THERMOMETER                      | 10.25.85 |                |  |
|   |   |   |   |   |   |     | A36661 | THERMO SWITCH                    | 10.25.85 |                |  |
|   |   |   |   |   |   |     | A36610 | LEVEL SWITCH                     | 10.25.85 |                |  |
|   |   |   |   |   |   |     | A36723 | SUCTION FITTING                  | 10.25.85 |                |  |
|   |   |   |   |   |   |     | A36670 | MINI-CHECK COUPLING              | 10.25.85 |                |  |
|   |   |   |   |   |   |     | A36612 | PRESSURE TRANSDUCER              | 10.25.85 |                |  |
|   |   |   |   |   |   |     | A36657 | QUICK DISCONNECT                 | 10.25.85 |                |  |
|   |   |   |   |   |   |     | A36155 | MALE CONNECTOR - MODIFIED        | 10.25.85 |                |  |
|   |   |   |   |   |   |     | A36611 | PRESSURE SWITCH                  | 10.25.85 |                |  |
|   |   |   |   |   |   |     | A36656 | QUICK DISCONNECT                 | 10.25.85 |                |  |
|   |   |   |   |   |   |     | A36108 | WHEEL                            | 10.25.85 |                |  |
|   |   |   |   |   |   |     | A36670 | MINI-CHECK COUPLING              | 10.25.85 |                |  |
|   |   |   |   |   |   |     | D35925 | INSTALLATION DERRICK POWER UNIT  | 10.25.85 |                |  |
|   |   |   |   |   |   |     | D35976 | POWER UNIT FRAME                 | 10.25.85 |                |  |

|                 |  |          |        |     |
|-----------------|--|----------|--------|-----|
| COMPILED BY:    |  | DATE:    | NO.    | REV |
| Peter B. Dowden |  | 10.25.85 | A35926 | -   |

| SANDIA DPBM - MASTER DRAWING LIST                   |   |   |   |   |   |  |          |                          |              | SHEET 23 OF 28 |     |
|---|---|---|---|---|---|--|----------|--------------------------|--------------|----------------|-----|
| ASSEMBLY TITLE:           HYDRAULIC SYSTEM ASSEMBLY |   |   |   |   |   |  |          |                          |              | (CON'T)        |     |
| DRAWING NO:     D35914                              |   |   |   |   |   |  |          |                          |              |                |     |
| DRAWING NO.   |   |   |   |   |   |  | REV      | TITLE                    | RELEASE DATE |                |     |
| 1   | 2 | 3 | 4 | 5 | 6 |  |          |                          |              |                |     |
|   |   |   |   |   |   |  |          | BOLT RING - INTERNAL     | 10.25.85     |                |     |
|   |   |   |   |   |   |  |          | BOLT RING                | 10.25.85     |                |     |
|   |   |   |   |   |   |  |          | BOLT RING                | 10.25.85     |                |     |
|   |   |   |   |   |   |  |          | BAFFEL PLATE             | 10.25.85     |                |     |
|   |   |   |   |   |   |  |          | MANIFOLD ASSEMBLY        | 10.25.85     |                |     |
|   |   |   |   |   |   |  |          | RELIEF VALVE             | 10.25.85     |                |     |
|   |   |   |   |   |   |  |          | RELIEF VALVE             | 10.25.85     |                |     |
|   |   |   |   |   |   |  |          | PRESSURE REDUCING VALVE  | 10.25.85     |                |     |
|   |   |   |   |   |   |  |          | CHECK VALVE              | 10.25.85     |                |     |
|   |   |   |   |   |   |  |          | CHECK VALVE              | 10.25.85     |                |     |
|   |   |   |   |   |   |  |          | MANIFOLD - PUMP CONTROL  | 10.25.85     |                |     |
|   |   |   |   |   |   |  |          | HOUSING - COUPLING       | 10.25.85     |                |     |
|   |   |   |   |   |   |  |          | HOUSING - COUPLING       | 10.25.85     |                |     |
|   |   |   |   |   |   |  |          | COVER - HOUSING          | 10.25.85     |                |     |
|   |   |   |   |   |   |  |          | MANIFOLD SUPPORT BRACKET | 10.25.85     |                |     |
|   |   |   |   |   |   |  |          | SUCTION ADAPTOR FLANGE   | 10.25.85     |                |     |
|   |   |   |   |   |   |  |          | COVER PLATE              | 10.25.85     |                |     |
|   |   |   |   |   |   |  |          | GASKET                   | 10.25.85     |                |     |
|   |   |   |   |   |   |  |          | TAP BAR                  | 10.25.85     |                |     |
|   |   |   |   |   |   |  |          | FILTER BRACKET           | 10.25.85     |                |     |
|   |   |   |   |   |   |  |          | GASKET                   | 10.25.85     |                |     |
|   |   |   |   |   |   |  |          | COVER PLATE              | 10.25.85     |                |     |
|   |   |   |   |   |   |  |          | FILTER BRACKET           | 10.25.85     |                |     |
|   |   |   |   |   |   |  |          | LEVEL SWITCH ADAPTER     | 10.25.85     |                |     |
| COMPILED BY:  |   |   |   |   |   |  | DATE:    |                          | NO.          |                | REV |
| Peter B. Dowden                                     |   |   |   |   |   |  | 10.25.85 |                          | A35926       |                | -   |

| SANDIA DPBM - MASTER DRAWING LIST   |   |   |   |   |   |     |                                    |              |  | SHEET 24 OF 28 |  |
|---|---|---|---|---|---|-----|------------------------------------|--------------|--|----------------|--|
| ASSEMBLY TITLE: <b>HYDRAULIC SYSTEM ASSEMBLY</b> (CON'T)<br>DRAWING NO: <b>D35914</b> |   |   |   |   |   |     |                                    |              |  |                |  |
| DRAWING NO.   |   |   |   |   |   | REV | TITLE                              | RELEASE DATE |  |                |  |
| 1   | 2 | 3 | 4 | 5 | 6 |     |                                    |              |  |                |  |
|   |   |   |   |   |   |     | COUPLING                           | 10.25.85     |  |                |  |
|   |   |   |   |   |   |     | COUPLING                           | 10.25.85     |  |                |  |
|   |   |   |   |   |   |     | LEVEL GAGE                         | 10.25.85     |  |                |  |
|   |   |   |   |   |   |     | ELECTRIC MOTOR - 75 H.P., 1200 RPM | 10.25.85     |  |                |  |
|   |   |   |   |   |   |     | PISTON PUMP "REXROTH" A7V250LV     | 10.25.85     |  |                |  |
|   |   |   |   |   |   |     | VAR. VOL. PUMP "REXROTH" A7V40DR   | 10.25.85     |  |                |  |
|   |   |   |   |   |   |     | SUCTION STRAINER                   | 10.25.85     |  |                |  |
|   |   |   |   |   |   |     | H.P. FILTER                        | 10.25.85     |  |                |  |
|   |   |   |   |   |   |     | H.P. FILTER                        | 10.25.85     |  |                |  |
|   |   |   |   |   |   |     | QUICK DISCONNECT                   | 10.25.85     |  |                |  |
|   |   |   |   |   |   |     | RETURN FILTER                      | 10.25.85     |  |                |  |
|   |   |   |   |   |   |     | QUICK DISCONNECT                   | 10.25.85     |  |                |  |
|   |   |   |   |   |   |     | LEVEL SWITCH                       | 10.25.85     |  |                |  |
|   |   |   |   |   |   |     | THERMOMETER                        | 10.25.85     |  |                |  |
|   |   |   |   |   |   |     | AIR BREATHER                       | 10.25.85     |  |                |  |
|   |   |   |   |   |   |     | PRESSURE TRANSDUCER                | 10.25.85     |  |                |  |
|   |   |   |   |   |   |     | NEEDLE VALVE                       | 10.25.85     |  |                |  |
|   |   |   |   |   |   |     | BALL VALVE                         | 10.25.85     |  |                |  |
|   |   |   |   |   |   |     | FLOW CONTROL VALVE                 | 10.25.85     |  |                |  |
|   |   |   |   |   |   |     | CHECK VALVE                        | 10.25.85     |  |                |  |
|   |   |   |   |   |   |     | MINI-CHECK COUPLING                | 10.25.85     |  |                |  |
|   |   |   |   |   |   |     | MAGNETIC PIPE PLUG                 | 10.25.85     |  |                |  |
|   |   |   |   |   |   |     | PRESSURE GAGE (0-3000 PSI)         | 10.25.85     |  |                |  |
|   |   |   |   |   |   |     | PRESSURE GAGE (0-6000 PSI)         | 10.25.85     |  |                |  |

|                                     |  |                       |                   |              |
|-------------------------------------|--|-----------------------|-------------------|--------------|
| COMPILED BY: <b>Peter B. Dowden</b> |  | DATE: <b>10.25.85</b> | NO. <b>A35926</b> | REV <b>-</b> |
|-------------------------------------|--|-----------------------|-------------------|--------------|



ASSEMBLY TITLE:

HYDRAULIC SYSTEM ASSEMBLY

(CON'T)

DRAWING NO:

D35914

| DRAWING NO.     |   |   |   |   |   |  | REV | TITLE    | RELEASE DATE                   |          |
|-----------------|---|---|---|---|---|--|-----|----------|--------------------------------|----------|
| 1               | 2 | 3 | 4 | 5 | 6 |  |     |          |                                |          |
|                 |   |   |   |   |   |  |     | A36603   | GAGE SNUBBER                   | 10.25.85 |
|                 |   |   |   |   |   |  |     | A36517   | SUCTION HOSE FITTING           | 10.25.85 |
|                 |   |   |   |   |   |  |     | A36518   | 90 DEGREE ELBOW FLANGE         | 10.25.85 |
|                 |   |   |   |   |   |  |     | A36519   | 4-BOLT FLANGE - REDUCING       | 10.25.85 |
|                 |   |   |   |   |   |  |     | A36727   | NAMEPLATE                      | 10.25.85 |
|                 |   |   |   |   |   |  |     | A37155   | QUICK DISCONNECT               | 10.25.85 |
|                 |   |   |   |   |   |  |     | A37157   | QUICK DISCONNECT               | 10.25.85 |
|                 |   |   |   |   |   |  |     | A37159   | QUICK DISCONNECT               | 10.25.85 |
|                 |   |   |   |   |   |  |     | A36155   | MALE CONNECTOR - MODIFIED      | 10.25.85 |
|                 |   |   |   |   |   |  |     | D35923   | HYDRAULIC INSTALLATION DERRICK | 10.25.85 |
|                 |   |   |   |   |   |  |     | D36730   | MANIFOLD ASSEMBLY              | 10.25.85 |
|                 |   |   |   |   |   |  |     | A36581   | DIRECTIONAL VALVE              | 10.25.85 |
|                 |   |   |   |   |   |  |     | A36582   | DIRECTIONAL VALVE              | 10.25.85 |
|                 |   |   |   |   |   |  |     | A36591   | CHECK VALVE                    | 10.25.85 |
|                 |   |   |   |   |   |  |     | A36616   | MANIFOLD                       | 10.25.85 |
|                 |   |   |   |   |   |  |     | D36731   | MANIFOLD ASSEMBLY              | 10.25.85 |
|                 |   |   |   |   |   |  |     | A36583   | DIRECTIONAL VALVE              | 10.25.85 |
|                 |   |   |   |   |   |  |     | A36587   | PRESSURE REDUCING VALVE        | 10.25.85 |
|                 |   |   |   |   |   |  |     | A36615   | MANIFOLD                       | 10.25.85 |
|                 |   |   |   |   |   |  |     | A36613   | MANIFOLD                       | 10.25.85 |
|                 |   |   |   |   |   |  |     | D36134   | MANIFOLD ASSEMBLY              | 10.25.85 |
|                 |   |   |   |   |   |  |     | D36133   | MANIFOLD                       | 10.25.85 |
|                 |   |   |   |   |   |  |     | A37214   | PRESSURE CONTROL VALVE         | 10.25.85 |
|                 |   |   |   |   |   |  |     | A36578   | DIRECTIONAL VALVE              | 10.25.85 |
| COMPILED BY:    |   |   |   |   |   |  |     | DATE:    | NO.                            | REV      |
| Peter B. Dowden |   |   |   |   |   |  |     | 10.25.85 | A35926                         | -        |

| SANDIA DPBM - MASTER DRAWING LIST   |   |   |   |   |   |     |                                  |              |  | SHEET 26 OF 28 |  |
|---|---|---|---|---|---|-----|----------------------------------|--------------|--|----------------|--|
| ASSEMBLY TITLE:           HYDRAULIC SYSTEM ASSEMBLY                                   (CON'T) |   |   |   |   |   |     |                                  |              |  |                |  |
| DRAWING NO:           D35914  |   |   |   |   |   |     |                                  |              |  |                |  |
| DRAWING NO.   |   |   |   |   |   | REV | TITLE                            | RELEASE DATE |  |                |  |
| 1   | 2 | 3 | 4 | 5 | 6 |     |                                  |              |  |                |  |
| A36579  |   |   |   |   |   |     | DIRECTIONAL VALVE                | 10.25.85     |  |                |  |
| D36734  |   |   |   |   |   |     | MANIFOLD - TANK RETURN           | 10.25.85     |  |                |  |
| D36735  |   |   |   |   |   |     | MANIFOLD - DRAIN RETURN          | 10.25.85     |  |                |  |
| D36736  |   |   |   |   |   |     | BULKHEAD MANIFOLD - CRAWLER      | 10.25.85     |  |                |  |
| D36738  |   |   |   |   |   |     | MOUNTING BRACKET - MANIFOLD      | 10.25.85     |  |                |  |
| D36737  |   |   |   |   |   |     | BULKHEAD PLATE                   | 10.25.85     |  |                |  |
| A36583  |   |   |   |   |   |     | DIRECTIONAL VALVE                | 10.25.85     |  |                |  |
| A36588  |   |   |   |   |   |     | PRESSURE REDUCING VALVE          | 10.25.85     |  |                |  |
| A36592  |   |   |   |   |   |     | CHECK VALVE                      | 10.25.85     |  |                |  |
| A36595  |   |   |   |   |   |     | FLOW CONTROL VALVE               | 10.25.85     |  |                |  |
| A36600  |   |   |   |   |   |     | PRESSURE GAGE                    | 10.25.85     |  |                |  |
| A36602  |   |   |   |   |   |     | PRESSURE GAGE                    | 10.25.85     |  |                |  |
| A36603  |   |   |   |   |   |     | GAGE SNUBBER                     | 10.25.85     |  |                |  |
| A36611  |   |   |   |   |   |     | PRESSURE SWITCH                  | 10.25.85     |  |                |  |
| A36612  |   |   |   |   |   |     | PRESSURE TRANSDUCER              | 10.25.85     |  |                |  |
| A36614  |   |   |   |   |   |     | SUB-PLATE                        | 10.25.85     |  |                |  |
| A36155  |   |   |   |   |   |     | MALE CONNECTOR - MODIFIED        | 10.25.85     |  |                |  |
| A36670  |   |   |   |   |   |     | MINI-CHECK COUPLING              | 10.25.85     |  |                |  |
| A37155  |   |   |   |   |   |     | QUICK DISCONNECT - NIPPLE        | 10.25.85     |  |                |  |
| A37157  |   |   |   |   |   |     | QUICK DISCONNECT - NIPPLE        | 10.25.85     |  |                |  |
| A37159  |   |   |   |   |   |     | QUICK DISCONNECT - NIPPLE        | 10.25.85     |  |                |  |
| A37161  |   |   |   |   |   |     | QUICK DISCONNECT - NIPPLE        | 10.25.85     |  |                |  |
| A37163  |   |   |   |   |   |     | QUICK DISCONNECT - NIPPLE        | 10.25.85     |  |                |  |
| D35922  |   |   |   |   |   |     | HYDRAULIC INSTALLATION - CRAWLER | 10.25.85     |  |                |  |

|                 |  |          |        |     |
|-----------------|--|----------|--------|-----|
| COMPILED BY:    |  | DATE:    | NO.    | REV |
| Peter B. Dowden |  | 10.25.85 | A35926 | -   |

| SANDIA DPBM - MASTER DRAWING LIST                   |   |   |   |   |   |     |                                  |                      |  | SHEET 27 OF 28  |  |
|---|---|---|---|---|---|-----|----------------------------------|----------------------|--|-----------------|--|
| ASSEMBLY TITLE:           HYDRAULIC SYSTEM ASSEMBLY |   |   |   |   |   |     |                                  |                      |  | (CON'T)         |  |
| DRAWING NO:       D35914                            |   |   |   |   |   |     |                                  |                      |  |                 |  |
| DRAWING NO.   |   |   |   |   |   | REV | TITLE                            |                      |  | RELEASE DATE    |  |
| 1   | 2 | 3 | 4 | 5 | 6 |     |                                  |                      |  |                 |  |
|   |   |   |   |   |   |     | MANIFOLD BLOCK                   |                      |  | 10.25.85        |  |
|   |   |   |   |   |   |     | ANGLE BRACKET                    |                      |  | 10.25.85        |  |
|   |   |   |   |   |   |     | DIRECTIONAL VALVE                |                      |  | 10.25.85        |  |
|   |   |   |   |   |   |     | SHUTTLE VALVE                    |                      |  | 10.25.85        |  |
|   |   |   |   |   |   |     | HYDRAULIC INSTALLATION - CONSOLE |                      |  | 10.25.85        |  |
|   |   |   |   |   |   |     | MOUNTING BRACKET - VALVE         |                      |  | 10.25.85        |  |
|   |   |   |   |   |   |     | FLOW CONTROL VALVE               |                      |  | 10.25.85        |  |
|   |   |   |   |   |   |     | SUBPLATE                         |                      |  | 10.25.85        |  |
|   |   |   |   |   |   |     | HOSE ASSEMBLY                    |                      |  | 10.25.85        |  |
|   |   |   |   |   |   |     | QUICK DISCONNECT - COUPLER       |                      |  | 10.25.85        |  |
|   |   |   |   |   |   |     | HOSE ASSEMBLY                    |                      |  | 10.25.85        |  |
|   |   |   |   |   |   |     | QUICK DISCONNECT - COUPLER       |                      |  | 10.25.85        |  |
|   |   |   |   |   |   |     | HOSE ASSEMBLY                    |                      |  | 10.25.85        |  |
|   |   |   |   |   |   |     | QUICK DISCONNECT - COUPLER       |                      |  | 10.25.85        |  |
|   |   |   |   |   |   |     | HOSE ASSEMBLY                    |                      |  | 10.25.85        |  |
|   |   |   |   |   |   |     | QUICK DISCONNECT - COUPLING      |                      |  | 10.25.85        |  |
|   |   |   |   |   |   |     | HOSE ASSEMBLY                    |                      |  | 10.25.85        |  |
|   |   |   |   |   |   |     | QUICK DISCONNECT - COUPLING      |                      |  | 10.25.85        |  |
|   |   |   |   |   |   |     | HYDRAULIC SCHEMATIC - IN HOLE    |                      |  | 10.25.85        |  |
|   |   |   |   |   |   |     | HYDRAULIC SCHEMATIC - DERRICK    |                      |  | 10.25.85        |  |
|   |   |   |   |   |   |     | HOSE ASSEMBLY                    |                      |  |                 |  |
|   |   |   |   |   |   |     | PRESSURE TESTING KIT             |                      |  |                 |  |
| COMPILED BY:           Peter B. Dowden              |   |   |   |   |   |     | DATE:           10.25.85         | NO.           A35926 |  | REV           - |  |

ASSEMBLY TITLE: ELECTRICAL SYSTEM ASSEMBLY  
 DRAWING NO: D35915


| DRAWING NO.                  |   |   |   |   |   |  | REV | TITLE                               | RELEASE DATE |
|------------------------------|---|---|---|---|---|--|-----|-------------------------------------|--------------|
| 1                            | 2 | 3 | 4 | 5 | 6 |  |     |                                     |              |
| D35915                       |   |   |   |   |   |  |     | ELECTRICAL SYSTEM ASSEMBLY          | 10.25.85     |
| D36725                       |   |   |   |   |   |  |     | ELECTRICAL INSTALLATION - IN HOLE   | 10.25.85     |
| D36667                       |   |   |   |   |   |  |     | ELECTRICAL PANEL                    | 10.25.85     |
| A36507                       |   |   |   |   |   |  |     | CYLINDER POSITION INDICATING SYSTEM | 10.25.85     |
| B35930                       |   |   |   |   |   |  |     | CONNECTING CABLE                    | 10.25.85     |
| D35626                       |   |   |   |   |   |  |     | IN-HOLE CABLING                     | 10.25.85     |
| D35928                       |   |   |   |   |   |  |     | CONTROL CONSOLE ASSEMBLY            | 10.25.85     |
| D36138                       |   |   |   |   |   |  |     | CONTROL CONSOLE BOX                 | 10.25.85     |
| A36168                       |   |   |   |   |   |  |     | MILLIAMMETER                        | 10.25.85     |
| A36505                       |   |   |   |   |   |  |     | MILLIAMMETER                        | 10.25.85     |
| A36506                       |   |   |   |   |   |  |     | DIGITAL METER                       | 10.25.85     |
| A36169                       |   |   |   |   |   |  |     | METER RELAY                         | 10.25.85     |
| A36526                       |   |   |   |   |   |  |     | MILLIAMMETER                        | 10.25.85     |
| A36504                       |   |   |   |   |   |  |     | MILLIAMMETER                        | 10.25.85     |
| B35930                       |   |   |   |   |   |  |     | ZED UNIT                            | 10.25.85     |
| D36119                       |   |   |   |   |   |  |     | NAMEPLATE                           | 10.25.85     |
| D36098                       |   |   |   |   |   |  |     | ELECTRICAL CABINET ASSEMBLY         | 10.25.85     |
| D36097                       |   |   |   |   |   |  |     | ELECTRICAL ENCLOSURE                | 10.25.85     |
| B36527                       |   |   |   |   |   |  |     | CABLE ASSEMBLY                      | 10.25.85     |
| B36740                       |   |   |   |   |   |  |     | CRAWLER CONTROL                     | 10.25.85     |
| D36739                       |   |   |   |   |   |  |     | ENCLOSURE                           | 10.25.85     |
| A36732                       |   |   |   |   |   |  |     | SINGLE AXIS CONTROLLER              | 10.25.85     |
| D35917                       |   |   |   |   |   |  |     | ELECTRICAL SCHEMATIC                | 10.25.85     |
| COMPILED BY: Peter B. Dowden |   |   |   |   |   |  |     | DATE: 10.25.85                      | NO. A35926   |
|                              |   |   |   |   |   |  |     |                                     | REV -        |

**APPENDIX B**

**to**

**DESIGN OF A MACHINE TO BORE AND LINE  
A LONG HORIZONTAL HOLE IN TUFF**

**DPBM ASSEMBLY DRAWINGS**



| Q   | Q#      | DESCRIPTION                      | QTY |
|-----|---------|----------------------------------|-----|
|     | 0559411 | REAR END ASSEMBLY                |     |
| 1   | 0562311 | IRON PLATE                       |     |
| 1   | 05625   | STEERING ARM - STEERING ASSEMBLY | 1   |
| 1   | 05630   | LEFT FRONT SHOCK                 |     |
| 1   | 05636   | SMALL ENGINE MOUNT ASSEMBLY      |     |
| 1   | 05638   | WHEEL CYLINDER                   |     |
| REF | 060974  | MACHINED METAL PLATE             |     |
| QTY | 061729  | ELECTRICAL RAYLON                |     |
| 1   | 062666  | CRANK PLATE                      |     |
| 1   | 063635  | BLACK TUBE                       | 3   |
| 1   | 063672  | BLACK TUBE (DRIVER)              |     |
| REF | 063746  | LINER                            |     |
| 1   | A57333  | STOP                             |     |
| 2   | 065100  | WHEEL AND TIRE ASSEMBLY          | 2   |

[illegible]

WEIGHTS

DRY SHIELD 10750 LB  
HYD. POWER UN 450 LB  
COMPLETE ASSY 20470 LB

AUG 1964

SANDIA NATIONAL LABORATORIES


THE SANDIA CO. GROUP CO.

SANDIA CO. GROUP CO.

SANDIA CO. GROUP CO.

SANDIA CO. GROUP CO.

B-5








# NOTES:

1. TORQUE FASTENERS PER DRAWING L-56572

- ▲ DETERMINE CENTER OF GRAVITY OF DERRICK ASSY.
- DETERMINE CENTER OF GRAVITY OF CRAWLER ASSY.
- POSITION DERRICK ASSY WITH ITS CENTER OF GRAVITY CONCURRENT WITH THAT OF THE CRAWLER ASSY. LOCATE P. 4 & DRILL AT ASSY.


OVERALL LENGTH 17'-10" (LESS IN-HOLE ASSY)  
 OVERALL HEIGHT 8'-6"  
 OVERALL WIDTH 6'-10"  
 WEIGHT 41000 LB (LESS IN-HOLE ASSY)

| NO. | REV. | DESCRIPTION                      | DATE |
|-----|------|----------------------------------|------|
| 1   | 1    | FRAME A - 1 PLY                  |      |
| 1   | 1    | DERRICK B - 1 PLY                |      |
| 1   | 1    | CRAWLER FRAME ASSEMBLY           |      |
| 1   | 1    | PLATE 8" x 4" x 1/2"             |      |
| 1   | 1    | BOLT 1/2" DIA. x 11 1/2" L       |      |
| 1   | 1    | WASHER 1/2" DIA.                 |      |
| 1   | 1    | HYDRAULIC INSTALLATION - DERRICK |      |
| 1   | 1    | HYDRAULIC INSTALLATION - CRAWLER |      |
| 1   | 1    | ELECTRICAL INSTALLATION          |      |



SECTION A-A  
 SCALE 1/4"  
 TYP 4 PLACES

HEIGHT 1.65" ABOVE FLOOR



SCALE 1/4"

| NO. | REV. | DESCRIPTION                      | DATE |
|-----|------|----------------------------------|------|
| 1   | 1    | FRAME A - 1 PLY                  |      |
| 1   | 1    | DERRICK B - 1 PLY                |      |
| 1   | 1    | CRAWLER FRAME ASSEMBLY           |      |
| 1   | 1    | PLATE 8" x 4" x 1/2"             |      |
| 1   | 1    | BOLT 1/2" DIA. x 11 1/2" L       |      |
| 1   | 1    | WASHER 1/2" DIA.                 |      |
| 1   | 1    | HYDRAULIC INSTALLATION - DERRICK |      |
| 1   | 1    | HYDRAULIC INSTALLATION - CRAWLER |      |
| 1   | 1    | ELECTRICAL INSTALLATION          |      |

SAFARI NATIONAL LABORATORIES

THE ENGINE OF THE 21ST CENTURY

MOBILE DERRICK ASSEMBLY

SECTION 1


DATE 10/1/72

BY 10/1/72

**SANDIA NATIONAL LABORATORIES**

One Operating Div., Mail, Box 166, Santa Barbara, California, U.S.A.

B-9




[illegible]

B-11



DETAIL I  
SCALE: 1/1



DETAIL I

DETAIL II



DETAIL II  
SCALE: 1/1

| QTY | PART NO.   | DESCRIPTION             | REVISION      | DATE |
|-----|------------|-------------------------|---------------|------|
|     | B36514 - 1 | LINER                   |               |      |
| 1   | - 2        | 36.00 Ø PIPE X .38 WALL | SEC<br>NOTE 1 |      |

- NOTES:
1. MATERIAL: API SPEC 5LX-52 (52 KSI YIELD)
  2. SEAM TO BE LONGITUDINAL
  3. OUT OF ROUNDNESS TOLERANCE 0.10

WEIGHT = 1140 LBS

| REVISION | APPROVED |
|----------|----------|
| A        |          |
| JUN      |          |
| JUL      |          |

|      |        |        |
|------|--------|--------|
| DP&M | B36514 | 22-110 |
| REV  | REV    | REV    |

|  |                 |                   |               |             |     |      |      |
|--|-----------------|-------------------|---------------|-------------|-----|------|------|
| REV DATE   |                 | ISSUE DESCRIPTION |               | BY          | CHK | SUPV | P.E. |
| <p>PROPERTY OF<br/> <b>SANDIA NATIONAL LABORATORIES</b><br/>         DEVELOPED BY<br/>         THE ROBBINS CO., KENT, WA.<br/>         DRL CONTRACT NO. 47-5795-13 (MATERIALS REQUIRED)<br/>         PRIOR APPROVAL OF THE PRE-CURING AGENCY</p> |                 |                   |               |             |     |      |      |
| TITLE: LINER   |                 | SCALE: 1/16       |               |             |     |      |      |
| DRAWN BY: J. J. SANTI  | CHECKED: PBD    | APPROVED: BOWDEN  | DATE: 9-12-55 | SIZE: 6     |     |      |      |
| ROBBINS JOB NO. 050018   | DWG. CLASS. UNC | REV. 1            | DATE: 10-1-55 | PAGE 1 OF 1 |     |      |      |
| ROBBINS DWG. NO. B36514  | REV.            | DWG. DWG. NO.     | REV           | CAT.        |     |      |      |

| QTY | Part    | Desc                              | ECN | REV  | QTY | REV |
|-----|---------|-----------------------------------|-----|------|-----|-----|
| 8   | 601-177 | WEL HD CAPSCREW .75-10UNC x 2.0L  |     |      | GR5 | 81  |
| 4   | 601-176 | WEL HD CAPSCREW .75-10UNC x 1.5L  |     |      | GR5 | 82  |
| 16  | 601-151 | WEL HD CAPSCREW .81-10UNC x 1.50L |     |      | GR5 | 83  |
| 13  | 601-103 | WEL HD CAPSCREW .50-13UNC x 1.50L |     |      | GR5 | 84  |
| 4   | 601-108 | WEL HD CAPSCREW .50-13UNC x 1.75L |     |      | GR5 | 85  |
| 4   | 601-82  | WEL HD CAPSCREW .30-16UNC x 1.50L |     |      | GR5 | 86  |
| 4   | 601-061 | WEL HD CAPSCREW .30-16UNC x 1.50L |     |      | GR5 | 87  |
| 36  | 601-027 | WEL HD CAPSCREW .31-16UNC x 1.50L |     |      | GR5 | 88  |
| 10  | 601-078 | WEL HD CAPSCREW .31-16UNC x 1.50L |     |      | GR5 | 89  |
| 4   | 625-003 | WEL NUT .50-13 UNC                |     |      |     |     |
| 4   | 625-005 | WEL NUT .50-13 UNC                |     |      |     |     |
| 4   | 675-015 | LOCKWASHER .75 (M60)              |     |      |     |     |
|     |         |                                   |     |      |     |     |
| 1/8 |         | 2 1/2" PIPE                       |     | SCRB | GR5 | 95  |
| 2   |         | 2" - 90° ELBOW (SCRB)             |     | GR5  | 96  |     |
| 1   | 653-905 | 2" - 90° ELBOW (SCRB)             |     | GR5  | 97  |     |
| 1   | 653-906 | 2" - 90° ELBOW (SCRB)             |     | GR5  | 98  |     |
|     |         | 2" PIPE NIPPLE = 5' LG            |     | GR5  | 99  |     |
| 1   | 653-957 | 2" PIPE NIPPLE = 5.5 LG           |     | GR5  | 100 |     |
| 1   | 653-954 | 1" PIPE PLUG                      |     |      |     |     |
| 1   | 653-960 | 2 1/2" PIPE PLUG                  |     |      |     |     |
|     |         |                                   |     |      |     |     |
| 1   |         | 2 1/2" TEE - ANGLE                |     | GR5  | 101 |     |
| 1   |         | 2" TEE - ANGLE                    |     | GR5  | 102 |     |
| 1   |         | 2" TEE - ANGLE                    |     | GR5  | 103 |     |
| 1   |         | 2" TEE - ANGLE                    |     | GR5  | 104 |     |
| 1   |         | 2" TEE - ANGLE                    |     | GR5  | 105 |     |
| 2   | 657-073 | 1/2" STREET ELBOW (SCRB)          |     | GR5  | 106 |     |
| 1   | 657-571 | 1/2" STREET ELBOW (SCRB)          |     | GR5  | 107 |     |
| 2   | 650-931 | 1/2" MALE PIPE ELBOW (SCRB)       |     | GR5  | 108 |     |
| 1/8 |         | 1/2" PIPE                         |     | GR5  | 109 |     |
| 2   |         | 1/2" PIPE COUPLING                |     | GR5  | 110 |     |
| 2   |         | 1/2" PIPE COUPLING                |     | GR5  | 111 |     |
| 1   |         | 1/2" - 45° ELBOW                  |     | GR5  | 112 |     |
| 2   |         | 1/2" - 90° ELBOW                  |     | GR5  | 113 |     |
| 1   |         | 1/2" CLOSE NIPPLE 1/2x 3/4        |     | GR5  | 114 |     |
| 1   |         | 1/2" TEE - ANGLE                  |     | GR5  | 115 |     |
| 1   |         | 1/2" TEE - ANGLE                  |     | GR5  | 116 |     |
| 1   |         | 1/2" TEE - ANGLE                  |     | GR5  | 117 |     |
| 1   |         | 1/2" TEE - ANGLE                  |     | GR5  | 118 |     |
| 1   |         | 1/2" TEE - ANGLE                  |     | GR5  | 119 |     |
| 1   |         | 1/2" TEE - ANGLE                  |     | GR5  | 120 |     |
| 1   |         | 1/2" TEE - ANGLE                  |     | GR5  | 121 |     |
| 1   |         | 1/2" TEE - ANGLE                  |     | GR5  | 122 |     |
| 1   |         | 1/2" TEE - ANGLE                  |     | GR5  | 123 |     |
| 1   |         | 1/2" TEE - ANGLE                  |     | GR5  | 124 |     |
| 1   |         | 1/2" TEE - ANGLE                  |     | GR5  | 125 |     |
| 1   |         | 1/2" TEE - ANGLE                  |     | GR5  | 126 |     |
| 1   |         | 1/2" TEE - ANGLE                  |     | GR5  | 127 |     |
| 1   |         | 1/2" TEE - ANGLE                  |     | GR5  | 128 |     |
| 1   |         | 1/2" TEE - ANGLE                  |     | GR5  | 129 |     |
| 1   |         | 1/2" TEE - ANGLE                  |     | GR5  | 130 |     |
| 1   |         | 1/2" TEE - ANGLE                  |     | GR5  | 131 |     |
| 1   |         | 1/2" TEE - ANGLE                  |     | GR5  | 132 |     |
| 1   |         | 1/2" TEE - ANGLE                  |     | GR5  | 133 |     |
| 1   |         | 1/2" TEE - ANGLE                  |     | GR5  | 134 |     |
| 1   |         | 1/2" TEE - ANGLE                  |     | GR5  | 135 |     |
| 1   |         | 1/2" TEE - ANGLE                  |     | GR5  | 136 |     |
| 1   |         | 1/2" TEE - ANGLE                  |     | GR5  | 137 |     |
| 1   |         | 1/2" TEE - ANGLE                  |     | GR5  | 138 |     |
| 1   |         | 1/2" TEE - ANGLE                  |     | GR5  | 139 |     |
| 1   |         | 1/2" TEE - ANGLE                  |     | GR5  | 140 |     |
| 1   |         | 1/2" TEE - ANGLE                  |     | GR5  | 141 |     |
| 1   |         | 1/2" TEE - ANGLE                  |     | GR5  | 142 |     |
| 1   |         | 1/2" TEE - ANGLE                  |     | GR5  | 143 |     |
| 1   |         | 1/2" TEE - ANGLE                  |     | GR5  | 144 |     |
| 1   |         | 1/2" TEE - ANGLE                  |     | GR5  | 145 |     |
| 1   |         | 1/2" TEE - ANGLE                  |     | GR5  | 146 |     |
| 1   |         | 1/2" TEE - ANGLE                  |     | GR5  | 147 |     |
| 1   |         | 1/2" TEE - ANGLE                  |     | GR5  | 148 |     |
| 1   |         | 1/2" TEE - ANGLE                  |     | GR5  | 149 |     |
| 1   |         | 1/2" TEE - ANGLE                  |     | GR5  | 150 |     |
|     |         |                                   |     |      |     |     |
| 3   | AS465-3 | MALE CONNECTOR - MODIFIED         |     |      |     |     |
| 1   | AS465-4 | MALE CONNECTOR - MODIFIED         |     |      |     |     |
| 1   | AS465-5 | MALE CONNECTOR - MODIFIED         |     |      |     |     |
|     |         |                                   |     |      |     |     |
|     |         |                                   |     |      |     |     |
|     |         |                                   |     |      |     |     |
|     |         |                                   |     |      |     |     |
|     |         |                                   |     |      |     |     |
|     |         |                                   |     |      |     |     |
|     |         |                                   |     |      |     |     |
|     |         |                                   |     |      |     |     |
|     |         |                                   |     |      |     |     |
|     |         |                                   |     |      |     |     |
|     |         |                                   |     |      |     |     |
|     |         |                                   |     |      |     |     |
|     |         |                                   |     |      |     |     |
|     |         |                                   |     |      |     |     |
|     |         |                                   |     |      |     |     |
|     |         |                                   |     |      |     |     |
|     |         |                                   |     |      |     |     |
|     |         |                                   |     |      |     |     |
|     |         |                                   |     |      |     |     |
|     |         |                                   |     |      |     |     |
|     |         |                                   |     |      |     |     |
|     |         |                                   |     |      |     |     |
|     |         |                                   |     |      |     |     |
|     |         |                                   |     |      |     |     |
|     |         |                                   |     |      |     |     |
|     |         |                                   |     |      |     |     |
|     |         |                                   |     |      |     |     |
|     |         |                                   |     |      |     |     |
|     |         |                                   |     |      |     |     |
|     |         |                                   |     |      |     |     |
|     |         |                                   |     |      |     |     |
|     |         |                                   |     |      |     |     |
|     |         |                                   |     |      |     |     |
|     |         |                                   |     |      |     |     |
|     |         |                                   |     |      |     |     |
|     |         |                                   |     |      |     |     |
|     |         |                                   |     |      |     |     |
|     |         |                                   |     |      |     |     |
|     |         |                                   |     |      |     |     |
|     |         |                                   |     |      |     |     |
|     |         |                                   |     |      |     |     |
|     |         |                                   |     |      |     |     |
|     |         |                                   |     |      |     |     |
|     |         |                                   |     |      |     |     |
|     |         |                                   |     |      |     |     |
|     |         |                                   |     |      |     |     |
|     |         |                                   |     |      |     |     |
|     |         |                                   |     |      |     |     |
|     |         |                                   |     |      |     |     |
|     |         |                                   |     |      |     |     |
|     |         |                                   |     |      |     |     |
|     |         |                                   |     |      |     |     |
|     |         |                                   |     |      |     |     |
|     |         |                                   |     |      |     |     |
|     |         |                                   |     |      |     |     |
|     |         |                                   |     |      |     |     |
|     |         |                                   |     |      |     |     |
|     |         |                                   |     |      |     |     |
|     |         |                                   |     |      |     |     |
|     |         |                                   |     |      |     |     |
|     |         |                                   |     |      |     |     |
|     |         |                                   |     |      |     |     |
|     |         |                                   |     |      |     |     |
|     |         |                                   |     |      |     |     |
|     |         |                                   |     |      |     |     |
|     |         |                                   |     |      |     |     |
|     |         |                                   |     |      | </  |     |

| Qty | Pc-01    | Q000 | DESCRIPTION                              | Q000    | Q000 |
|-----|----------|------|--|---------|------|
| 1   | A36590-1 |      | NEEDLE VALVE                             | (5 NPT) | 41   |
| 1   | A36590-1 |      | BALL VALVE                               |         | 41   |
| 1   | A36591-1 |      | FLANG                                    |         | 43   |
| 1   | A36591-1 |      | SPRING VALVE                             |         | 43   |
| 1   | A36591-1 |      | CHECK VALVE                              |         | 44   |
| 2   | A36620-2 |      | 1/2 IN. CHECK COUPLING                   |         | 45   |
|     |          |      |  |         | 46   |
| 3   | A36649-1 |      | MAGNETIC PIPE PLUG                       |         | 47   |
| 1   | A36649-1 |      | PRESS GAGE (0-1000 PSI)                  |         | 48   |
| 2   | A36649-1 |      | PRESS GAGE (0-6000 PSI)                  |         | 49   |
| 3   | A36649-1 |      | GAGE WHUBBER                             |         | 50   |
| 1   | A36649-1 |      | SUCTION HOSE FITTING                     |         | 51   |
| 1   | A36649-1 |      | 90° ELBOW FLANGE                         |         | 52   |
| 1   | A36649-1 |      | 4-BOLT FLANGE - REDUCING                 |         | 53   |
| 1   | A36717-1 |      | NAME PLATE                               |         | 54   |
| 1   | A36717-1 |      | NAME PLATE                               |         | 55   |
| 1   | A36717-1 |      | NAME PLATE                               |         | 56   |
| 3   | A37055-1 |      | QUICK DISCONNECT - NIPPLE (1/4")         |         | 57   |
| 1   | A37055-1 |      | QUICK DISCONNECT - NIPPLE (1/4")         |         | 58   |
| 1   | A37055-1 |      | QUICK DISCONNECT - NIPPLE (1/4")         |         | 59   |
| NR  | 651-540  |      | NR. MOSE (1/4") - AQUIN FC 270A - 8      |         | 60   |
| NR  | 651-541  |      | NR. MOSE (1/4") - AQUIN FC 270A - 8      |         | 61   |
| NR  | 651-540  |      | NR. MOSE (1/4") - AQUIN FC 250A - 8      |         | 62   |
| NR  | 651-501  |      | NR. MOSE (1/4") - AQUIN FC 250A - 12     |         | 63   |
| NR  | 651-502  |      | NR. MOSE (1/4") - AQUIN FC 250A - 16     |         | 64   |
| NR  |          |      | NR. MOSE (1/4") - AQUIN FC 273J - 10     |         | 65   |
| NR  | 651-544  |      | SUCTION HOSE (1/4") - AQUIN FC 264A - 12 |         | 67   |
| NR  | 651-525  |      | SUCTION HOSE (1/4") - AQUIN FC 264A - 10 |         | 68   |
| NR  |          |      |  |         | 69   |
| NR  |          |      | MOSE END (1/4") - AQUIN FC 27000A - 8    |         | 70   |
| NR  |          |      | MOSE END (1/4") - AQUIN FC 27000A - 8    |         | 71   |
| NR  |          |      | MOSE END (1/4") - AQUIN FC 27000A - 8    |         | 72   |
| NR  |          |      | MOSE END (1/4") - AQUIN FC 27000A - 8    |         | 73   |
| NR  |          |      | MOSE END (1/4") - AQUIN FC 27000A - 8    |         | 74   |
| NR  |          |      | MOSE END (1/4") - AQUIN FC 27000A - 8    |         | 75   |
| NR  |          |      |  |         | 76   |
| NR  |          |      |  |         | 77   |
| NR  |          |      | MOSE CLAMP (1/4") - AQUIN FC 27000A - 8  |         | 78   |
| NR  | 651-755  |      | MOSE CLAMP (1/4") - AQUIN FC 27000A - 8  |         | 79   |


NOTES:

- [illegible]

| QTY | ITEM     | DESCRIPTION                       | REMARKS |
|-----|----------|-----------------------------------|---------|
| -   | 035325-1 | HYDRAULIC ISOLATION POOR UNIT     |         |
| 1   | 035361-1 | POWER UNIT FRAME DEBRIS WASH JOIR |         |
| 1   | 035362-1 | HOUSING COUPLING                  |         |
| 1   | 036051-1 | HOUSING COUPLING                  |         |
| 2   | 036050-1 | COVER HOUSING                     |         |
| 2   | 036050-2 | COVER HOUSING                     |         |
| 1   | 036068-1 | MANIFOLD SUPPORT BRACKET          |         |
| 1   | 036067-1 | SUCTION ADAPTER FLANGE            |         |
| 1   | 036774-1 | MANIFOLD ASSEMBLY 035377-1        |         |
| 3   | 035565-1 | COVER PLATE (11500)               |         |
| 1   | 035566-1 | GASKET (11500)                    |         |
| 2   | 035567-1 | TAP BAR                           |         |
| 1   | 035568-1 | FILTER BRACKET                    |         |
| 1   | 035571-1 | GASKET (10000)                    |         |
| 2   | 035572-1 | COVER PLATE (10000)               |         |
| 1   | 035573-1 | FILTER BRACKET                    |         |
| 1   | 036101-1 | LEVEL SWITCH ADAPTER              |         |
| 1   | 036102-1 | COUPLING - FALK (60710)           |         |
| 1   | 036102-1 | COUPLING - FALK (60710)           |         |
| 1   | 036141-2 | LEVEL GAGE                        |         |
| 1   | A37101-1 | QUICK DISCONNECT - NIPPLE (10)    |         |
| 1   | A37103-1 | QUICK DISCONNECT - NIPPLE (10)    |         |
| 1   | A36119-1 | ELECTRIC MOTOR - 75HP 120C - 3PH  |         |
| 1   | A3651-1  | Piston Pump Reservoir - 415012V   |         |
| 1   | A36511-1 | VAR VOL PUMP RESERVOIR - 415012V  |         |
| 2   | A3666-1  | SUCTION STRAINER                  |         |
| 1   | A36608-1 | BP FILTER                         |         |
| 1   | A36609-1 | HP FILTER                         |         |
| 1   | A36607-1 | RETURN FILTER                     |         |
| 1   | A36610-1 | LEVEL SWITCH                      |         |
| 1   | A36609-1 | THELBOMETER                       |         |
| 1   | A36608-1 | AIR BREATHER                      |         |
| 2   | A36612-1 | PRESSURE TRANSDUCER               |         |



[illegible]

B-13





B-14



| DATE     | BY       | CHKD | APP'D |
|----------|----------|------|-------|
| 12/24/54 | W. J. H. |      |       |
| 12/24/54 | W. J. H. |      |       |
| 12/24/54 | W. J. H. |      |       |

|                                   |           |
|-----------------------------------|-----------|
| AVIATION                          |           |
| SANDIA NATIONAL LABORATORIES      |           |
| HYDRAULIC INSTALLATION POWER UNIT |           |
| 1. LANCE                          | 2. 550018 |
| 3. 355018                         | 4. 355018 |

[illegible]

7 MATCH LINE 7/8 DIA HOLE THRU  
 8 MATCH LINE 7/8 DIA HOLE THRU  
 9 DRILL 7/8 DIA HOLE THRU ON 80° CENTER  
 10 DRILL 7/8 DIA HOLE THRU


[illegible]


1. USE THE IMAGE PLATE (PIECE 9A) AS A TEMPLATE FOR LOCATING THE CENTER POINTS OF THE COMPONENTS.

2 MATERIAL .0315 X 2.00 5-FT SCREW,  
BUSHING AND FILLED WITH BLACK BARNEL.  
ADHESIVE TO BE APPLIED TO EACH,  
ATTACH WITH (2) #4-60000 X 2.00 SCREW.

18.0 IS THE CLEARANCE OPENING IN THE CONTROL  
CABLE STAND FOR THE ELECTRICAL DISCONNECTING  
AND HYDRAULIC LINES. R.F. LEMMON DRAWN

[illegible]





**APPENDIX C**

**to**

**DESIGN OF A MACHINE TO BORE AND LINE  
A LONG HORIZONTAL HOLE IN TUFF**

**THRUST REQUIREMENT ANALYSIS**

## THRUST REQUIREMENT

Total thrust requirement is the sum of the:

- (a) Cutterhead force.
- (b) Frictional force between liner and bore due to dead weight.
- (c) Frictional force due to stabilizer loading.
- (d) Rock shearing force at shield leading edge.
- (e) Gradient component force.
- (f) Liner binding force in deviated bore.

(a) Cutterhead Force

Based on a penetration of .06 inch/revolution, in 20 ksi rock, total axial cutter force requirement is 150,000 lbs.

150,000 lbs

(b) Dead Weight Friction

|                                 |              |
|---------------------------------|--------------|
| Weight of drill                 | 20,450 lbs   |
| 74 liner lengths (.50 in. wall) | 112,100      |
| 74 muck tubes                   | 31,450       |
| Cabling                         | <u>3,600</u> |

Assuming friction coefficient of .8 134,080 lbs

(c) Stabilizer Friction

|   |             |
|---|-------------|
| Force on upper and lower shoes (each)<br>(based on stabilizing force = 3 x<br>cutter side load) | 120,000 lbs |
|---|-------------|

Total force assuming friction  
coefficient of 0.8 192,000 lbs

(d) Rock Shearing Force

Assume the bore is undercut by .25 inch over one third of the circumference during a steering maneuver. Area of rock "shoulder" =  $37 \times \sin 60^\circ \times .25 = 8$  sq. in.

Assume rock resistance = unconfined compressive stress = 20 ksi

Shearing force =  $20,000 \times 8 =$  160,000 lbs

(e) Gradient Component

Assume worst angle of  $3^\circ$

$$\text{Force} = 225,000 \times \sin 3^\circ \qquad \underline{11,800 \text{ lbs}}$$

(f) Binding in Bore

Assume a lateral deviation of the bore of 2 inches in each 100 ft. length. See Figure C-1. Assume the bore is .5 in. larger than liner outside diameter (allowing for part worn cutters) resulting in a net deviation of 1.5 in. Shape of deflected liner can be considered equivalent to a series of 50 ft. span simply supported uniformly loaded beams. See Figure 1B.

For 36 in. O.D.      .50 in. wall

$$I = 8790 \text{ in}^4$$

$$E = 30 \times 10^6 \text{ lb/in}^2$$

$$\text{Deflection} = .75 = \frac{5 F(50 \times 12)^3}{384 \times 30 \times 10^6 \times 8790}$$

$$F = \text{total force} = 70,320 \text{ lb.}$$

Total force over 600 ft. length


$$= 12 \times 70,320 = 843,840 \text{ lb.}$$

$$\begin{aligned} \text{Sliding friction force} &= \\ (\text{assuming friction coefficient of } 0.8) &\qquad \underline{675,072 \text{ lbs}} \end{aligned}$$


$$\text{Total force required (sum of (a) - (f))} = \underline{1,356,952 \text{ lbs}}$$

A nominal force of  $1.5 \times 10^6 \text{ lb.}$  has been chosen, based on the estimates. This is in line with forces used on existing pipe jacking equipment for approximately the same size pipe.





(A) OVERALL BORE



(B) EQUIVALENT BEAM LOADING

Figure C-1 Bore Deviation and Liner Forces

**APPENDIX D**

**to**

**DESIGN OF A MACHINE TO BORE AND LINE  
A LONG HORIZONTAL HOLE IN TUFF**

**LINER BUCKLING STUDY**

## LINER BUCKLING STUDY

The derrick is to be provided with 1.5 million lb. thrust. The majority of this thrust is required to overcome potential binding forces on the liner due to faulty ground or hole misalignment. There is also provision for cutterhead thrust and sliding friction. Even with a perfect bore, a thrust of approximately 0.5 million lbs. will be needed at a hole length of 600 ft.

Consideration must be given to the structural behavior of the liner. In the compressive mode, buckling failure must be studied. There are two types of buckling, column and local shell buckling.

a. Column Buckling

For this to occur, there must be unimpeded lateral movement. This clearly cannot happen in a confined hole. Maximum lateral movement is one inch.

b. Shell Buckling

If the liner wall is thin in relationship to its diameter, a potential exists for local crumpling of the wall. According to the technical literature, true "thin" shells are those having a radius/thickness (R/t) ratio of at least 100, and generally in the region of 200-400. If a minimum liner thickness of 0.38 in. is considered, it has a ratio of 48. The ratio for a 0.5 in. wall is 36. These low ratios provide an extra margin of safety over the buckling forces predicted by "thin" shell theory.

1. Buckling of Cylindrical Shell Under Uniform Axial Load.

Roark (fifth edition) has the following formula for the limiting stress prior to buckling:

$$\sigma = \frac{E}{\sqrt{3} \cdot \sqrt{1 - \nu^2}} \cdot \frac{t}{R}$$

Where  $\sigma$  = critical stress :

E = Young's Modulus (30 x 10<sup>6</sup> psi)

$\nu$  = Poisson's Ratio (.27)

t = wall thickness (inch)

R = cylinder radius = 18 in.

$$\sigma_c = \frac{0.6 \cdot 30 \cdot 10^6}{\sqrt{3} \cdot \sqrt{1 - 27^2}} \cdot \frac{t}{18}$$

Roark recommends multiplying by a factor of 0.4 to 0.6 to account for actual experience as opposed to theory. Tennyson (Reference 1) shows a graph showing that the factor approaches 0.6 as R/t decreases to 100. This factor is used, though it will in fact be higher at ratios less than 50.

For wall thicknesses of .38, 0.5, and .75

$$\sigma_t = .38 = 228 \text{ ksi (6.5 yield)}$$

$$\sigma_t = 0.5 = 300 \text{ ksi (8.5 yield)}$$

$$\sigma_t = .75 = 450 \text{ ksi (12.9 x yield)}$$

In all cases, material will yield before buckling. Shell thickness for buckling just at yield (35 ksi) is 0.6 in.

Figure D-1 shows the buckling load plotted as a function of wall thickness, based on the calculated buckling stress over the pipe cross-section.

## 2. Direct Stresses

$$\text{Area (.38)} = 42 \text{ in}^2$$

$$\text{Area (0.5)} = 55.8 \text{ in}^2$$

$$\text{Area (.75)} = 83 \text{ in}^2$$

Assuming axially applied load of  $1.5 \times 10^6$  lbf.

$$\sigma_t = (.38) = 35714 \text{ psi}$$

$$\sigma_t = (0.5) = 26881 \text{ psi}$$

$$\sigma_t = (.75) = 18072 \text{ psi}$$

Figure D-2 shows the direct stress plotted as a function of wall thickness.

## 36 in. O.D. STEEL PIPE




Figure D-1 Direct Stress at  $1.5 \times 10^6$  lb. Axial Load vs. Wall Thickness

## 36 in. O.D. STEEL PIPE




Figure D-2 Buckling Load vs. Wall Thickness

### 3. Stress Under Eccentric Loading

The thrusting collar surface will be aligned square to the line of thrust, and the liner and surfaces machined symmetrically to the liner axis within .03 in. Additionally, the collar may incorporate a flexible backing pad or be mounted on a swiveling arrangement to minimize eccentric loading.

Even if eccentric loading is applied to the extent that the yield stress is reached, structural failure is unlikely. Yielding will take place until axial deformation redistributes the stress levels as the neutral axis is allowed to shift. A state of equilibrium is generally reached due to the confinement of the hole.

The successive axial yielding together with displacement presents an indeterminate problem for the calculation of actual stresses. The purpose of this analysis is to support the selection of a wall thickness, as opposed to calculating an actual stress state. In contrast to the compressive state, the tensile situation generates a reduction in wall thickness with a corresponding higher stress level and possibly ultimate failure. A liner pull system is therefore inherently less reliable.

Shell buckling as a function of elastic behavior, not strength properties of the materials, will not occur in the eccentric mode as the stresses will not be able to approach the levels calculated in b(2). To improve the understanding of liner stress influence, it is proposed that strain gages be installed on selected liners to monitor the stress state during the NTS tests. Linear strain data, together with associated thrust load levels, should provide useful information in understanding liner behavior, together with the operating characteristics of the DPBM.

#### c. "Dimpling" of Liner

In faulted ground, the possibility of rock being wedged between the liner and the bore is unlikely as the friction between liner and rock is less than between two rock surfaces. If a wedge situation occurs, dimpling of the liner is possible. The question has been raised as to the effect of the cross sectional change on buckling. Again, column type buckling cannot occur because of the side restraint. Shell buckling stresses will not be reached, though if the dimpling is severe (greater than one quarter of the circumference) compressive yielding could occur across the entire cross section of a 0.5 in. wall. This assumes that the dimpled section provides no resistance. This amount of dimpling is so severe, however, that the available axial forces could probably

not move the liner in any case. The problem would be equally severe if the liner were being pulled instead of pushed. Repair work would be required from inside the liner in order to proceed.

d. General Considerations: Pushing vs. Pulling

1. Compression loading is inherently safer structurally providing buckling is not possible. Tensile loading above yield leads to thinning of the section, stress increase and ultimately fracture. Excess compression leads to distortion, which is acceptable in this case, providing that no fracture occurs. Welds in compression are therefore superior.
2. With liner thrust (pipe jacking), the maximum loads are applied at the work station. In the event of failure, it will be easy to replace a broken section. In the original pull-in scheme, maximum loads are at the drilling machine. A failure will be in-hole and difficult to repair.

CONCLUSION

The liner configurations considered will not be subject to buckling problems because they have an  $R/t$  ratio outside the critical range. However, the direct stresses (which are the same for push or pull) are too high for a 0.38 wall liner made from mild steel (35 ksi). A higher strength liner (50-65 ksi) could be used. Extra cost will necessarily be incurred either in the use of a superior material or a thicker wall.

Reference<sup>1</sup> - R. C. Tennyson, "Buckling Modes of Cylindrical Shells Under Axial Compression," AIAA Journal, Vol. 7, Aug. 1969, pp. 1481-7.



APPENDIX E

to

DESIGN OF A MACHINE TO BORE AND LINE  
A LONG HORIZONTAL HOLE IN TUFF

VACUUM SYSTEM COMPUTATIONS

## VACUUM SYSTEM COMPUTATIONS

An analysis of the airflow through the muck handling system is complicated by the fact that the hole boring machine may be tested in at least three locations. The locations are at different elevations with variations in air temperature and relative humidity, resulting in a concomitant variation in the density of air and barometric pressure. The testing is expected to be as follows:

1. Initial testing in a rock quarry near Seattle (no analysis required.)
2. Proof of concept testing with the hole boring machine in U12G tunnel complex at the Nevada Test Site at the 6300 ft. elevation and air temperature of 75°F.
3. Hole boring in a proposed repository at 1200 ft. elevation and 80° F ambient air.

For a fixed muck throughput, pipe length has the greatest effect on power consumption by the vacuum pump. High altitudes cause a derating of the vacuum pump because of the reduced air density. Consequently, a dual set of calculations is required for the two cases. For convenience, the cases will be referred to as Test Tunnel and Repository Tunnel.

#### GENERAL DESCRIPTION OF THE VACUUM MUCKING SYSTEM

|     |                                       |                 |
|-----|---------------------------------------|-----------------|
| 1.  | Diameter of borehole                  | 37 in.          |
| 2.  | Area of face                          | 7.47 sq. ft.    |
| 3.  | Controlled advance rate               | 2 in/min.       |
| 4.  | Volume solids extracted               | 1.25 cu.ft/min. |
| 5.  | Specific weight of rock               | 150 lb/cu.ft.   |
| 6.  | Weight of rock drilled                | 187.5 lb/min.   |
| 7.  | Length of borehole lining per section | 8 ft.           |
| 8.  | Solid volume per lining section       | 59.76 cu. ft.   |
| 9.  | Swell factor                          | 1.6             |
| 10. | Total drop box volume required        | 95.6 cu. ft.    |
| 11. | Muck production                       | 5.6 tph         |
| 12. | Heat transfer in borehole             | 5300 btu/min.   |
| 13. | Temperature rise in muck              | 70°F            |
| 14. | Borehole lithology                    | welded tuff     |

#### DESIGN ASSUMPTIONS

1. The air drawn from the main haulage tunnel is free from dust and available in adequate quantity from the ventilation system. The test tunnel is 6,300 ft. above sea level with a temperature of 75°F and the repository tunnel is at 1,200 ft. altitude and 80°F.
2. The borehole is lined with a smooth steel liner.
3. The unobstructed area in the borehole is 3 sq. ft.
4. The minimum area around the muck plate for the passage of the air is approximately 0.5 sq. ft.
5. The sum of the areas normal to the airflow around the cutter is approximately 2 sq. ft.
6. The maximum length of the borehole is 600 ft.

7. The maximum length of the muck handling system in the main haulage way is approximately 100 ft.
8. The borehole is at right angles to the main tunnel.

#### DESCRIPTION OF THE AIRFLOW

The air required at the borehole face will be drawn into the borehole from the main tunnel by the pressure differential between the face and atmospheric pressure in the main tunnel. As the air passes over the motor and gearbox it will gain heat and volumetric flow rate, but lose density.

The air will be drawn into the face around the muck plate. The small area for entry will increase the velocity of the air to a point where dust will not be able to enter the main tunnel from the borehole.

The air velocity across the face will carry small dust particles and respirable dust back to the intake. Heavy particles, falling freely from the cutters, will be deflected towards the intake orifice.

The heavy particles resting on the invert will gradually move towards the intake orifice as the drill advances into the face. In addition, a sweep or plough blade set at an angle of  $45^{\circ}$  will sweep the muck towards the intake, imparting an initial velocity and maintaining a dynamic condition that will assist the air stream in propelling the muck into the intake. Once in the muck pipe, the air velocity increases as the pressure decreases (increasing vacuum) until the muck reaches the drop boxes. In the boxes the cross-sectional area of flow is increased sharply, resulting in quickly reduced airflow velocities.

## 1. TEST TUNNEL

### PRESSURE DROP FOR AIRFLOW INTO BOREHOLE:

Assume that particle pick up velocity is 6000 ft/min.

Area through muck hole plate is 0.2 sq. ft.

Minimum airflow must be  $6000 \times 0.2 = 1200$  cfm.

Borehole collar elevation is 6300 ft.

Specific weight of air is 0.0588 lb/cu. ft. at 75°F.

Barometric pressure (equivalent) is 23.71 in Hg absolute.

Borehole diameter at collar restricted by thrust collar, muck pipe, and two thrust jacks. Assume unrestricted area is  $6.305 - 1.354 = 4.95$  sq. ft.

Velocity at entrance is  $1200/4.95 = 242$  ft/min. = 4.04 ft/s.

Entrance loss,  $V \times V/4g$  expressed as a pressure drop is  $4.04 \times 4.04 \times 0.0588/(4 \times 32.2 \times 144) = 0.00005175$  psi \*\*\*

### PRESSURE DROP FOR AIRFLOW IN BOREHOLE:

Maximum length of test borehole is 271 ft. less 21.5 ft. length of drill or about 250 ft.

However, this area is reduced by electric cables, cable holders on the muck pipe, and a pair of caster mounts on the mid-point of each muck pipe section for positioning the muck pipe as each section is inserted in the borehole. Assume that the reduced area is 900 sq. in., but that the wetted perimeter is unaffected.

Cross section is circular less area of muck pipe.

Hydraulic radius =  $R_h = A/P = 900/(138.2 \times 12) = 0.543$  ft.

Wall roughness of steel liner approximately 0.00015 ft. =  $k$

Relative wall roughness =  $k/4R_h = 0.000069$

Dynamic viscosity of air =  $3.86 \times 10E-7$  lb. - s/sq. ft.

Reynolds No. of airflow =  $4.04 \times 4 \times 0.543 \times 0.0588/(3.86 \times 10E-7 \times 32.2) = 41,516$

Stanton-Moody friction factor (D'Arcy-Weisbach) = 0.0221

PRESSURE DROP DUE TO WALL FRICTION:

$$0.0588 \times 0.0221 \times 250.5 \times 4.04 \times 4.04 / (4 \times 0.543 \times 64.4 \times 144) = 0.00026377 \text{ psi} ***$$

ANALYSIS OF TEMPERATURE RISE AROUND THE MACHINE

Installed power - 125 hp = 93.25 kw

Equivalent heat energy -  $93.25 \times 3420 = 318,915 \text{ btu/hr.} = 5303 \text{ btu/min.}$

Ambient temperature -  $75^{\circ}\text{F}$

Table of Losses:

To ground assume 15% - 795 btu/min.

To watercooling 5% - 265 btu/min.

To additional steel liner, airflow and cut rock 80% - 4243 btu/min.

Weight of liner and thrust tube - 81 lbs/ft.

Weight of rock removed - 187.5 lbs/min.

Weight of air ( $1200 \times 0.0588$ ) - 70.6 lbs/min.

Specific heat of steel - 0.113

Specific heat of rock - 0.191

Specific heat of air - 0.237

Combined specific heats:

$$\begin{array}{l} 81 \times 0.113 = 9.153 \\ 187.5 \times 0.191 = 35.8125 \\ \underline{70.6 \times 0.237 = 16.7322} \end{array}$$

$$\begin{array}{lll} 339.1 & 61.6977 & 61.6977/339.1 = \\ & & 0.1819 \text{ Sp.heat} \end{array}$$

$$\text{Temperature rise} = 4252/61.6977 = 68.77^{\circ}\text{F}$$

From this, it is deduced that the steady running temperature around the machine will be in the order of  $75 + 69 = 144^{\circ}\text{F}$ .

### PRESSURE DROP FOR AIRFLOW THROUGH DRILL MACHINE

The density of the air in the borehole will decrease and its volumetric flow rate increase as the temperature rises near the drill machine.

The increase in volumetric flow rate is:

$$T_2 P_1 V_1 / T_1 P_2 = 604 \times 11.6489639 \times 1200 / (535 \times 11.6486484) = 1355 \text{ cfm}$$

$$\text{where } T_2 = 144\text{F}; T_1 = 75\text{F}; P_1 = 23.71 \text{ in Hg} = 11.6489639 \text{ psia}$$

The weighted cross-sectional area of the in-hole drill machine blocking the airflow is estimated to be that of an 18 in. diameter cylinder. The cross-sectional area of free airflow is 763 sq. in. and the wetted perimeter is 170 in., giving a hydraulic radius,  $R_h = 0.375 \text{ ft}$ .

Across the drill machine use average airflow and temperature to obtain  $(1200 + 1355)/2 = 1278 \text{ cfm}$  and 110F.

$$\text{Average velocity is } 1278 \times 144 / 763 = 241 \text{ ft/min. or } 4 \text{ ft/s.}$$

$$\text{Reynolds No.} = 4 \times 4 \times 0.375 \times 0.0588 / (3.97 \times 10^{-7} \times 32.2) = 27,725$$

Assume a roughness of 0.0002 ft. and relative roughness becomes  $0.0002 / (4 \times 0.375) = 0.0001$ .

The friction factor is 0.0244 and the pressure drop due to wall friction is  $0.0588 \times 0.0244 \times 21.5 \times 16 / (64.4 \times 144 \times 4 \times 0.375) = 0.00003548 \text{ psi}$  \*\*\*

$$\text{Velocity past muck plate} = Q/A = 1355/0.5 = 2710 \text{ fpm} = 45.16 \text{ ft/s}$$

$$\text{Velocity head expressed as pressure drop through muck plate} = 45.16 \times 45.16 \times 0.0588 / (64.4 \times 144) = 0.01293496 \text{ psi} \text{ ***}$$

### ANALYSIS OF AIRFLOW AROUND FRONT OF DRILL MACHINE

$$\text{Air to intake} = 1355 \text{ cfm}$$

$$\text{Velocity past cutters} = Q/A = 1355/2 = 677.5 \text{ ft/min.} = 11.29 \text{ ft/s.}$$

$$\begin{aligned} \text{Velocity head expressed as} \\ \text{pressure drop past cutters} &= 11.29 \times 11.29 \times 0.0588 / (64.4 \times 144) = \\ &0.00080820 \text{ psi} \text{ ***} \end{aligned}$$

The airflow is obstructed by the cutters. The flow is bounded by a complex structure and has a wetted perimeter of about 18 ft.

The cross-sectional area is about 2 sq. ft. The hydraulic radius is

therefore 0.1111 ft. and the path length is 3.5 ft. Reynolds No. =  $11.29 \times 0.444 \times 0.0588 / (3.97 \times 10^{-7} \times 32.2) = 23,078$   
Relative wall roughness is 0.0003375; friction factor = 0.0258

#### PRESSURE DROP AROUND FRONT OF DRILL MACHINE

=  $0.0588 \times 0.258 \times 3.5 \times 11.29 \times 11.29 / (64.4 \times 144 \times 4 \times 0.1111) = 0.00016422$  psi \*\*\*

#### ANALYSIS OF AIRFLOW INTO INTAKE AND TRANSITION MUCK PIPE

Airflow available is 1357 cfm corrected for pressure reduction

Area of intake,  $A_i = 0.2$  sq. ft.; Area of pipe,  $A_p = 0.196$  sq. ft.

Intake velocity =  $1357 / 0.2 = 6785$  ft/min.

Velocity in pipe =  $1357 / 0.196 = 6923$  ft/min.

Average velocity =  $(6785 + 6923) / 2 = 6854$  ft/min. = 114 ft/s.

Wetted perimeter of intake,  $P_i = 2.5$  ft.

Wetted perimeter of pipe,  $P_p = 1.55$  ft.

Hydraulic radius of intake,  $R_{hi} = 0.2 / 2.5 = 0.08$  ft.

Hydraulic radius of pipe,  $R_{hp} = 0.196 / 1.55 = 0.126$  ft.

Average hydraulic radius =  $(0.08 + 0.126) / 2 = 0.1032$  ft.

Entrance loss,  $V \times V / 4g$  expressed as a pressure drop is  $114 \times 114 \times 0.0588 / (4 \times 32.2 \times 144) = 0.0413728$  psi

Reynolds No. of airflow =  $114 \times 4 \times 0.1032 \times 0.0588 / (3.97 \times 10^{-7} \times 32.2) = 216,459$

Relative wall roughness =  $k / 4R_h = 0.00015 / (4 \times 0.1032) = 0.00036$

Stanton-Moody friction factor = 0.0181

Pressure drop due to wall friction in 12 ft. transition pipe =  $0.0588 \times 0.0181 \times 12 \times 114 \times 114 / (4 \times 0.1032 \times 64.4 \times 144) = 0.04335696$  psi

Correct for density change from air to air plus muck for both entrance and wall losses;

Airflow weight rate is  $1357$  cfm  $\times 0.0588$  lb/cu.ft. = 79.8 lb/min.

Rock flow weight is 187.5 lb/min. (1.25 cu. ft/min.)



Total weight rate is 267.3 lb/min.

Specific weight of mixture is  $267.3/1358.25 = 0.1968$  lb/cu. ft.

Corrected entrance pressure drop is  $0.0413728 \times 0.1968/0.0588 = 0.13846601$  psi

Corrected wall friction pressure drop is  $0.04335696 \times 0.1968/0.0588 = 0.14511309$  psi

Total pressure drop at intake = 0.2835791 psi \*\*\*

#### ANALYSIS OF AIRFLOW IN MUCK PIPE IN BOREHOLE

Length of 7 in. I.D. pipe is 250 ft. plus elbow length (5 ft.) = 255 ft.

Expanded air volume rate is  $1357 \times 11.65/11.28 = 1400$  cfm

Air V =  $Q/A = 1400/0.26725 = 5244$  ft/min. = 87 ft/s.

Assume 1.5 psi drop due to wall friction. Air expands to  $1400 \times 11.28/(11.28 - 1.5) = 1615$  cfm

Average airflow is  $(1400 + 1615)/2 = 1507$  cfm

Average air velocity is 94 ft/s.

Reynolds No. of airflow is  $94 \times 7 \times 0.0588/(3.97 \times 10^{-7} \times 32.2 \times 12) = 252,230$

Relative wall roughness =  $0.00015 \times 12/7 = 0.00026$

Stanton-Moody friction factor = 0.0171

New mixture specific weight is  $((1615 \times 0.0588) + 187.5)/1616.25 = 0.1748$  lb/cu. ft.

Pressure drop due to wall friction and corrected for mixture specific weight:

$-0.1748 \times 0.0171 \times 255 \times 94 \times 94 \times 12/(7 \times 64.4 \times 144) = 1.24473911$  psi  
\*\*\* (close enough to estimated 1.5 psi, ok)

#### ANALYSIS OF AIRFLOW IN MUCK PIPE IN MAIN TUNNEL

Pipe diameter is 7.625 in. inside. Flow rate is 1615 cfm

Velocity of air is  $1615/0.317 = 5093$  ft/min. = 85 ft/s.

Reynolds No. of airflow is  $85 \times 7.625 \times 0.0588/(3.97 \times 10^{-7} \times 32.2 \times 12) = 248,087$

Relative wall roughness =  $0.00015 \times 12/7.625 = 0.000236$

Stanton-Moody friction factor = 0.0170

Length of pipe to drop boxes including equivalent lengths of fittings assumed to be 200 ft.

Pressure drop due to wall friction and corrected for mixture density =  $0.1748 \times 0.0170 \times 200 \times 85 \times 85 \times 12/(7.625 \times 144) = 0.72870415$  psi

Pressure drop considered significant for increasing airflow intake rate.

Airflow correction is  $1615 \times 10.04/9.31 = 1742$  cfm

Average airflow is  $(1742 + 1615)/2 = 1678$  cfm

Average velocity is  $1678/0.317 = 5294$  ft/min. = 88 ft/s.

Corrected pressure drop is  $0.72870414 \times 88 \times 88/(85 \times 85) = 0.78530796$  psi  
\*\*\*

#### ANALYSIS OF AIRFLOW INTO DROP BOXES

Flow rate is 1742 cfm. Head loss into box is due to sudden enlargement from 8 in. pipe to 12 in. pipe. Velocity difference is  $(91.6 - 37.0)$  ft/s. and enlargement loss expressed as pressure drop is  $46.33 \times 0.0588/144 = 0.01891636$  psi.

Correcting the specific weight of the mixture gives  $((1742 \times 0.0588) + 187.5)/1743.25 = 0.1663$  lb/cu. ft. and the corrected enlargement pressure drop is 0.05349985 psi \*\*\*

The airflow through the muck boxes is difficult to analyze because in each box a slot 7 ft. long by 6 in. wide permits the coarser solids to drop out of the airstream. The airflow, now containing mostly dust and small particles, must come up around the exterior of the 12 in. diameter pipe, pass through the screen, and enter the discharge plenum along the top of the muck boxes.

Consider the exit losses through the slots as follows:

Expanded airflow is now  $1742 \times 9.31/9.26 = 1751$  cfm. Slot opening is  $2 \times 7 \times 6/12 = 7$  sq. ft. Velocity leaving slot is  $1751/7 = 250$  ft/min. or 4.2 ft/s. The exit loss expressed as a pressure drop is  $4.2 \times 4.2 \times 0.1663/(2 \times 32.2 \times 144) = 0.00031183$  psi \*\*\*

Note that the specific weight of the mixture is used here. The pressure drop for wall friction in the slotted pipe is considered negligible.

#### ANALYSIS OF AIRFLOW THROUGH SCREEN

Expanded flow rate is approximately 1762 cfm. Surface area of screen is 24 sq. ft. For an initial trial consider an 80 mesh with 80 wires to the inch and square openings of 0.0069 in. This is an effective area of 52% or about 12 sq. ft. If the screen openings are too small, the screen will restrict the airflow. Pressure drops are unknown across the screens, so 1/2 psi will be allowed.

#### ANALYSIS OF AIRFLOW INTO PLENUM

Expanded airflow is 1865 cfm

Slotted intake area is 1.76 sq. ft.

Velocity is  $1865/1.76 = 1055$  ft/min. = 17.6 ft/s.

Assume entrance loss only, expressed as a pressure drop, giving  $17.6 \times 17.6 \times 0.0588/(4 \times 32.2 \times 144) = 0.00097933$  psi \*\*\*

Along the plenum the length is 14.3 ft.,  $A = 0.75$  sq. ft. and the wetted perimeter is 5 ft., giving a hydraulic radius of 0.15 ft.

$V = 1865/0.75 = 2487$  ft/min. = 41 ft/s.

Reynolds No. of airflow =  $41 \times 4 \times 0.15 \times 0.0588/(3.97 \times 10E-7 \times 32.2) = 114,380$

Relative wall roughness =  $0.00015/(4 \times 0.15) = 0.00025$

Stanton-Moody friction factor = 0.0191

Pressure drop due to wall friction (assuming a mixture specific weight of 0.08 lb/cu. ft.) is  $0.08 \times 0.0191 \times 14.3 \times 41 \times 41/(4 \times 0.15 \times 64.4 \times 144) = 0.00660127$  psi \*\*\*

#### ANALYSIS OF AIRFLOW THROUGH FILTER

The maximum pressure drop through the two filter units is expected to be of the order of 3 in water gage or 0.11 psi \*\*\*

From the secondary filter the airflow enters the 14 in. diameter vacuum pump inlet through two feet of piping. The vacuum pump discharges through a 12 in. diameter opening into a plenum 4 ft. x 4 ft. x 20 in. before entering the 8 in. diameter intake to the silencer. The pressure drop is assumed to decrease another 0.5 psi \*\*\*

A summary of the losses in the test tunnel is tabulated.

## 2. REPOSITORY TUNNEL

The same procedure is followed as above but with the changes noted below:

Borehole collar elevation is 1200 ft.

Specific weight of air is 0.0706 lb/cu. ft. at 80°F.

Equivalent barometric pressure is 28.71 is Hg absolute.

Maximum length of borehole is 578.5 ft.

A summary of the losses in the repository is tabulated.

SUMMARY OF LOSSES IN TEST TUNNEL

| <u>LOCATION</u>             | <u>PRESSURE DROP</u><br>psi | <u>SUMMATION</u><br>psi |
|-----------------------------|-----------------------------|-------------------------|
| Into Borehole               | 0.00005175                  | 0.00005175              |
| In Borehole                 | 0.00026377                  | 0.00031552              |
| Through Drill Machine       | 0.01297044                  | 0.01328596              |
| Into Front of Drill Machine | 0.00097242                  | 0.01425838              |
| Into Intake                 | 0.13846601                  | 0.15272439              |
| Transition Muck Pipe        | 0.14511309                  | 0.29783748              |
| Borehole Muck Pipe          | 1.2447391                   | 1.54257658              |
| Pipe in Main Tunnel         | 0.78530796                  | 2.32788454              |
| Drop Box Intake             | 0.0534999                   | 2.38138444              |
| Drop Box Slot Exit          | 0.00031183                  | 2.38169627              |
| Through Screen              | 0.5                         | 2.88169627              |
| Plenum Entry                | 0.00097933                  | 2.8826756               |
| Plenum Length               | 0.00660127                  | 2.88927687              |
| Filter Unit                 | 0.11                        | 2.99927687              |
| Pump Inlet/Silencer         | 0.5                         | 3.49927687              |

or 7.12 in. Hg vac

Air volume rate to vacuum pump is approximately 1900 cfm. Referring to the Gardner-Denver curves for the 11CDL23 rotary blower: 1900 cfm at 8 in. Hg vac. and 975 rpm requires 45 bhp.

SUMMARY OF LOSSES IN REPOSITORY TUNNEL

| <u>LOCATION</u>             | <u>PRESSURE DROP</u><br>psi | <u>SUMMATION</u><br>psi |
|-----------------------------|-----------------------------|-------------------------|
| Into Borehole               | 0.00006213                  | 0.00006213              |
| In Borehole                 | 0.00069830                  | 0.00076043              |
| Through Drill Machine       | 0.01557108                  | 0.01633151              |
| Into Front of Drill Machine | 0.00116833                  | 0.01749984              |
| Into Intake                 | 0.14677493                  | 0.16427477              |
| Transition Muck Pipe        | 0.15126457                  | 0.31553934              |
| Borehole Muck Pipe          | 3.31748066                  | 3.63302000              |
| Pipe in Main Tunnel         | 1.10905518                  | 4.74207518              |
| Drop Box Intake             | 0.10022235                  | 4.84229753              |
| Drop Box Slot Exit          | 0.00041819                  | 4.84271571              |
| Through Screen              | 0.5                         | 5.34271571              |
| Plenum Entry                | 0.00161855                  | 5.34433426              |
| Plenum Length               | 0.00876574                  | 5.35310000              |
| Filter Unit                 | 0.11                        | 5.46310000              |
| Pump Inlet/Silencer         | 0.5                         | 5.96310000              |

or 12.13 in. Hg vac.

Air volume rate to vacuum pump is approximately 2400 cfm. Referring to the Gardner-Denver curves for the 11CDL23 rotary blower: 2400 cfm at 12 in. Hg vac. and 1300 rpm requires 85 bhp.

APPENDIX F

to

DESIGN OF MACHINE TO BORE AND LINE  
A LONG HORIZONTAL HOLE IN TUFF

RIB AND SEPDB

This report contains no data taken from or that should be included in the Reference Information Base (RIB) and/or the Site and Engineer Properties Data Base (SEPDB).

# DISTRIBUTION LIST

B. C. Rusche (RW-1)  
Director  
Office of Civilian Radioactive  
Waste Management  
U.S. Department of Energy  
Forrestal Building  
Washington, DC 20585

Ralph Stein (RW-23)  
Office of Civilian Radioactive  
Waste Management  
U.S. Department of Energy  
Forrestal Building  
Washington, DC 20585

J. J. Fiore (RW-221)  
Office of Civilian Radioactive  
Waste Management  
U.S. Department of Energy  
Forrestal Building  
Washington, DC 20585

M.W. Frei (RW-231)  
Office of Civilian Radioactive  
Waste Management  
U.S. Department of Energy  
Forrestal Building  
Washington, DC 20585

Carl P. Gertz, Project Manager (4)  
Waste Management Project Office  
U.S. Department of Energy  
Post Office Box 98518  
Las Vegas, NV 89193-8518

Chief, Repository Projects Branch  
Division of Waste Management  
U.S. Nuclear Regulatory Commission  
Washington, DC 20555

NTS Section Leader  
Repository Project Branch  
Division of Waste Management  
U.S. Nuclear Regulatory Commission  
Washington, DC 20555

B. G. Gale (RW-223)  
Office of Civilian Radioactive  
Waste Management  
U.S. Department of Energy  
Forrestal Building  
Washington, DC 20585

R. W. Gale (RW-40)  
Office of Civilian Radioactive  
Waste Management  
U.S. Department of Energy  
Forrestal Building  
Washington, DC 20585

J. O. Neff, Manager  
Salt Repository Project Office  
U.S. Department of Energy  
110 North 25 Mile Avenue  
Hereford, TX 79045

V. J. Cassella (RW-222)  
Office of Civilian Radioactive  
Waste Management  
U.S. Department of Energy  
Forrestal Building  
Washington, DC 20585

S. A. Mann, Manager  
Crystalline Rock Project Office  
U.S. Department of Energy  
9800 South Cass Avenue  
Argonne, IL 60439

K. Street, Jr.  
Lawrence Livermore National  
Laboratory  
Post Office Box 808  
Mail Stop L-209  
Livermore, CA 94550

L. D. Ramspott (3)  
Technical Project Officer for NNWSI  
Lawrence Livermore National  
Laboratory  
P.O. Box 808  
Mail Stop L-204  
Livermore, CA 94550



Document Control Center  
Division of Waste Management  
U.S. Nuclear Regulatory Commission  
Washington, DC 20555

V. M. Glanzman  
U.S. Geological Survey  
Post Office Box 25046  
913 Federal Center  
Denver, CO 80225

P. T. Prestholt  
NRC Site Representative  
1050 East Flamingo Road  
Suite 319  
Las Vegas, NV 89109

M. E. Spaeth  
Technical Project Officer for NNWSI  
Science Applications  
International Corporation  
Suite 407  
101 Convention Center Drive  
Las Vegas, NV 89109

SAIC-T&MSS Library (2)  
Science Applications  
International Corporation  
Suite 407  
101 Convention Center Drive  
Las Vegas, NV 89109

W. S. Twenhofel, Consultant  
Science Applications  
International Corporation  
820 Estes Street  
Lakewood, CO 89215

A. E. Gurrola  
General Manager  
Energy Support Division  
Holmes & Narver, Inc.  
Mail Stop 580  
Post Office Box 93838  
Las Vegas, NV 89193-3838

D. T. Oakley (4)  
Technical Project Officer for NNWSI  
Los Alamos National Laboratory  
N-5, Mail Stop J521  
P.O. Box 1663  
Los Alamos, NM 87545

L. R. Hayes (6)  
Technical Project Officer for NNWSI  
U.S. Geological Survey  
Post Office Box 25046  
421 Federal Center  
Denver, CO 80225

C. H. Johnson, Technical  
Program Manager  
Nuclear Waste Project Office  
State of Nevada  
Evergreen Center, Suite 252  
1802 North Carson Street  
Carson City, NV 89701

ONWI Library  
Battelle Columbus Laboratory  
Office of Nuclear Waste Isolation  
505 King Avenue  
Columbus, OH 43201

W. M. Hewitt, Program Manager  
Roy F. Weston, Inc.  
955 L'Enfant Plaza, Southwest,  
Suite 800  
Washington, DC 20024

H. D. Cunningham  
General Manager  
Reynolds Electrical &  
Engineering Co., Inc.  
Post Office Box 14400  
Mail Stop 555  
Las Vegas, NV 89114

T. Hay, Executive Assistant  
Office of the Governor  
State of Nevada  
Capitol Complex  
Carson City, NV 89710

J. A. Cross, Manager  
Las Vegas Branch  
Fenix & Scisson, Inc.  
Mail Stop 514  
Post Office Box 93265  
Las Vegas, NV 89193-3265

John Fordham  
Desert Research Institute  
Water Resources Center  
Post Office Box 60220  
Reno, NV 89506

Department of Comprehensive  
Planning  
Clark County  
225 Bridger Avenue, 7th Floor  
Las Vegas, NV 89155

Lincoln County Commission  
Lincoln County  
Post Office Box 90  
Pioche, NV 89043

Community Planning and  
Development  
City of North Las Vegas  
Post Office Box 4086  
North Las Vegas, NV 89030

City Manager  
City of Henderson  
Henderson, NV 89015

Timothy G. Barbour  
Science Applications  
International Corporation  
1626 Cole Boulevard, Suite 270  
Golden, CO 80401

E. P. Binnall  
Field Systems Group Leader  
Building 50B/4235  
Lawrence Berkeley Laboratory  
Berkeley, CA 94720

R.R. Loux, Jr., Executive Director (3)  
Nuclear Waste Project Office  
State of Nevada  
Evergreen Center, Suite 252  
1802 North Carson Street  
Carson City, NV 89701

Dr. Martin Mifflin  
Desert Research Institute  
Water Resources Center  
Suite 1  
2505 Chandler Avenue  
Las Vegas, NV 89120

Planning Department  
Nye County  
Post Office Box 153  
Tonopah, NV 89049

Economic Development  
Department  
City of Las Vegas  
400 East Stewart Avenue  
Las Vegas, NV 89101

Director of Community  
Planning  
City of Boulder City  
Post Office Box 367  
Boulder City, NV 89005

Commission of the  
European Communities  
200 Rue de la Loi  
B-1049 Brussels  
BELGIUM

Technical Information Center  
Roy F. Weston, Inc.  
955 L'Enfant Plaza, Southwest,  
Suite 800  
Washington, DC 20024

Gerald Parker (RW-241)  
Office of Civilian Radioactive  
Waste Management  
U.S. Department of Energy  
Forrestal Building  
Washington, DC 20585

T. H. Isaacs (RW-20)  
Office of Civilian Radioactive  
Waste Management  
U.S. Department of Energy  
Forrestal Building  
Washington, DC 20585

D. H. Alexander (RW-232)  
Office of Civilian Radioactive  
Waste Management  
U.S. Department of Energy  
Forrestal Building  
Washington, DC 20585

B. J. King, Librarian (2)  
Basalt Waste Isolation Project  
Library  
Rockwell Hanford Operations  
Post Office Box 800  
Richland, WA 99352

D. L. Fraser, General Manager  
Reynolds Electrical & Engineering  
Co., Inc.  
Mail Stop 555  
Post Office Box 98521  
Las Vegas, NV 89193-8521

J. P. Pedalino  
Technical Project Officer for NNWSI  
Holmes & Narver, Inc.  
101 Convention Center Drive,  
Suite 860  
Las Vegas, NV 89109

Eric Anderson  
Mountain West Research-  
Southwest, Inc.  
Phoenix Gateway Center  
432 North 44 Street  
Suite #400  
Phoenix, AZ 85008-6572

Judy Foremaster (5)  
City of Caliente  
Post Office Box 158  
Caliente, NV 89008

J. P. Knight (RW-24)  
Office of Civilian Radioactive  
Waste Management  
U.S. Department of Energy  
Forrestal Building  
Washington, DC 20585

Allen Jelacic (RW-233)  
Office of Civilian Radioactive  
Waste Management  
U.S. Department of Energy  
Forrestal Building  
Washington, DC 20585

J. R. Rollo  
Deputy Assistant Director  
for Engineering Geology  
U.S. Geological Survey  
106 National Center  
12201 Sunrise Valley Drive  
Reston, VA 22092

Vincent Gong  
Technical Project Officer for NNWSI  
Reynolds Electrical & Engineering  
Co., Inc.  
Mail Stop 615  
Post Office Box 98521  
Las Vegas, NV 89193-8521

S. D. Murphy  
Technical Project Officer for NNWSI  
Fenix & Scisson, Inc.  
Mail Stop 514  
Post Office Box 15408  
Las Vegas, NV 89114

S. H. Kale (RW-20)  
Office of Civilian Radioactive  
Waste Management  
U.S. Department of Energy  
Forrestal Building  
Washington, DC 20585

J. H. Antonnen, Deputy Assistant  
Manager for Commercial  
Nuclear Waste  
Basalt Waste Isolation Project  
Office  
U.S. Department of Energy  
P.O. Box 550  
Richland, WA 99352

J. C. Bresee (RW-22)  
Office of Civilian Radioactive  
Waste Management  
U.S. Department of Energy  
Forrestal Building  
Washington, DC 20585

J. L. Fogg (12)  
Technical Information Office  
Nevada Operations Office  
U.S. Department of Energy  
P.O. Box 98518  
Las Vegas, NV 89193-8518

R. L. Bullock  
Technical Project Officer for NNWSI  
Fenix & Scisson, Inc.  
Mail Stop 514  
P.O. Box 93265  
Las Vegas, NV 89193-3265

6300 R. W. Lynch  
6310 T. O. Hunter  
6310 22/124221/47-2295  
6310 NNWSI CF  
6311 A. L. Stevens  
6311 C. Mora  
6311 C. Horne (2)  
6312 F. W. Bingham  
6313 T. E. Blejwas  
6314 J. R. Tillerson  
6314 K. D. Young (10)  
6315 S. Sinnock  
6316 R. B. Pope  
6332 WMT Library (20)  
6430 N. R. Ortiz  
3141 S. A. Landenberger (5)  
3151 W. L. Garner (3)  
8024 P. W. Dean  
3154-3 C. H. Dalin (28)  
for DOE/OSTI

Dr. Roger Kasperson  
CENTED  
Clark University  
950 Main Street  
Worcester, MA 01610

C. L. West, Acting Director  
Office of External Affairs  
Nevada Operations Office  
U.S. Department of Energy  
P.O. Box 98518  
Las Vegas, NV 89193-8518

P. K. Fitzsimmons, Director  
Health Physics and Environmental  
Division  
Nevada Operations Office  
U.S. Department of Energy  
P.O. Box 98518  
Las Vegas, NV 89193-8518

Prof. S. W. Dickson  
Department of Geological Sciences  
Mackay School of Mines  
University of Nevada, Reno  
Reno, NV 89557

Elaine Ezra  
NNWSI GIS Project Manager  
EG&G Energy Measurements, Inc.  
P.O. Box 1912  
Mail Stop H-02  
Las Vegas, NV 89125

A. T. Tamura  
Science and Technology Division  
Office of Scientific and Technical  
Information  
U.S. Department of Energy  
P.O. Box 62  
Oak Ridge, TN 37831

L. Jardine  
Project Manager  
Bechtel National Inc.  
P.O. Box 3965  
San Francisco, CA 94119

R. Harig  
Parsons Brinckerhoff Quade &  
Douglas  
1625 Van Ness Ave.  
San Francisco, CA 94109-3679