

HYDRA-II: A Hydrothermal Analysis Computer Code

Volume II

User's Manual



September 1987

Prepared for the U.S. Department of Energy under Contract DE-AC06-76RLO 1830

Pacific Northwest Laboratory Operated for the U.S. Department of Energy by Battelle Memorial Institute



8902090143 PDR ORG

88121 EUSD

'nC

PNL-6206 Vol. 11

DISCLAIMER

This report was prepared as an account of work sponsored by an agency of the United States Government. Neither the United States Government nor any agency thereof, nor Battelle Memorial Institute, nor any of their employees, makes any warranty, expressed or implied, or assumes any legal liability or responsibility for the accuracy, completeness, or usefulness of any information, apparatus, product, or process disclosed, or represents that its use would not infringe privately owned rights. Reference herein to any specific commercial product, process, or service by trade name, trademark, manufacturer, or otherwise, does not necessarily constitute or imply its endorsement, recommendation, or favoring by the United States Government of any agency thereof, or Battelle Memorial Institute. The views and opinions of authors expressed herein do not necessarily state or reflect those of the United States Government or any agency thereof, or Battelle Memorial Institute.

PACIFIC NORTHWEST LABORATORY operated by BATTELLE MEMORIAL INSTITUTE for the UNITED STATES DEPARTMENT OF ENERGY under Contract DE-AC06-76RLO 1830

Printed in the United States of America Available from National Technical Information Service United States Department of Commerce 5285 Port Royal Road Springfield, Virginia 22161

NTIS Price Codes Microfiche A01

Printed Copy

	Price
Pages	Codes
001-025	A02
026-050	A03
051-075	A04
076-100	A05
101-125	A06
126-150	A07
151-175	A08
176-200	A09
201-225	A010
226-250	A011
251-275	A012
276-300	A013

SUMMARY

HYDRA-II is a hydrothermal computer code capable of three-dimensional analysis of coupled conduction, convection, and thermal radiation problems. This code is especially appropriate for simulating the steady-state performance of spent fuel storage systems. The code has been evaluated for this application for the U.S. Department of Energy's Commercial Spent Fuel Management Program.

HYDRA-II provides a finite-difference solution in cartesian coordinates to the equations governing the conservation of mass, momentum, and energy. A cylindrical coordinate system may also be used to enclose the cartesian coordinate system. This exterior coordinate system is useful for modeling cylindrical cask bodies.

The difference equations for conservation of momentum incorporate directional porosities and permeabilities that are available to model solid structures whose dimensions may be smaller than the computational mesh. The equation for conservation of energy permits modeling of orthotropic physical properties and film resistances. Several automated methods are available to model radiation transfer within enclosures and from fuel rod to fuel rod.

The documentation of HYDRA-II is presented in three separate volumes. <u>Volume I - Equations and Numerics</u> describes the basic differential equations, illustrates how the difference equations are formulated, and gives the solution procedures employed. This volume, <u>Volume II - User's Manual</u>, contains code flow charts, discusses the code structure, provides detailed instructions for preparing an input file, and illustrates the operation of the code by means of a sample problem. The final volume, <u>Volume III - Verification/Validation</u> <u>Assessments</u>, provides a comparison between the analytical solution and the numerical simulation for problems with a known solution. This volume also documents comparisons between the results of simulations of single- and multiassembly storage systems and actual experimental data.

iii

. . . .

ACKNOWLEDGMENTS

The authors express their appreciation to the U.S. Department of Energy for sponsoring this work. Appreciation is extended also to G. H. Beeman, D. R. Oden, Jr., and D. F. Newman of the Commercial Spent Fuel Management Program Office at Pacific Northwest Laboratory for their support of this activity. Project management was provided by J. M. Creer. A. J. Currie and T. S. Ceckiewicz provided technical editing support. The text of this document was initially processed by E. C. Darby. Final text processing was done under supervision of S. E. Kesterson.

CONTENTS

SUMMA	RY	• • • • • • • • • • • • • • • • • • • •	iii
ACKNO	WLEDG	MENTS '	iv
1.0	INTR	ODUCTION	1.1
2.0	CODE	OVERVIEW	2.1
	2.1	CODE STRUCTURE AND SOLUTION SEQUENCE	2.1
	2.2	CODE CONVENTIONS	2.8
	2.3	SUBROUTINE DESCRIPTIONS	2.9
3.0	PROG	RAM MAIN	3.1
	3.1	PARAMETER STATEMENT INFORMATION	3.1
	3.2	INPUT FORMAT	3.1
		3.2.1 Descriptive Text for the Application	3.1
		3.2.2 Run Control Information	3.3
		3.2.3 Print Plane Options	3.6
		3.2.4 Specification of Output	3.7
4.0	SUBR	OUTINE GRID	4.1
	4.1	GRID FUNCTIONS	4.1
		4.1.1 Choosing the Grid	4.5
		4.1.2 Simulations Using Only a Rectangular Grid	4.14
	4.2	PARAMETER STATEMENT INFORMATION	4.14
	4.3	INPUT FORMAT	4.16
		4.3.1 Overview	4.16
		4.3.2 Symmetry and Interface Regions. Input Block 1	4.17
		4.3.3 Rectangular Grid Computational Region Definition Grid. Input Block 2	4.18

		4.3.4	Cartesian and Radial Mesh Spacings.	
			Input Block 3	4.23
5.0	SUBR	OUTINE	PROP	5.1
	5.1	PROP I	FUNCTIONS	5.1
		5.1.1	Simple Isotropic or Orthotropic Conduction Model	5.13
		5.1.2	Parallel Conduction Model	5.13
		5.1.3	Series Conduction Model	5.14
		5.1.4	Array of Cylinders or Fuel Assembly Model	5.14
		5.1.5	Conduction Through Films	5.15
		5.1.6	Cask End Convection and Radiation	5.16
	5.2	PARAMI	ETER STATEMENT INFORMATION	5.20
	5.3	INPUT	FORMAT	5.21
		5.3.1	[,] Overview	5.21
		5.3.2	Thermal Resistance Print Specifications. PROP Input Block 1	5.21
		5.3.3	Cartesian Cask End Convection Specifications	5.22
		5.3.4	Material Conductivity Polynomial Coefficient Sets. PROP Input Block 3	5.24
		5.3.5	Parallel, Isotropic, and Orthotropic Conduction Models. PROP Input Block 4	5.26
		5.3.6	Series Conduction Models. PROP Input Block 5	5.30
		5.3.7	Fuel Assembly Conduction-Radiation Models. PROP Input Block 6	5.34
		5.3.8	Assignment of Resistance to Cell Locations. PROP Input Block 7	5.35
6.0	SUBR	OUTINE	THERM	6.1
	6.1	THERM	FUNCTIONS	6.1
		6.1.1	Numerical Procedure	6.2

		6.1.2 Heat Source	6.2
		6.1.3 Setting or Resetting Temperature	6.3
	6.2	PARAMETER STATEMENT INFORMATION	6.6
	6.3	INPUT FORMAT	6.6
		6.3.1 Overview	6.6
		6.3.2 Numerical Procedure and Printout Options	6.6
		6.3.3 Heat Source Specifications	6.9
		6.3.4 Initial Temperatures on the Rectangular Grid	6.12
		6.3.5 Temperature Modification Specifications	6.15
7.0	SUBR	OUTINE REBT	7.1
	7.1	REBT FUNCTIONS	7.1
	7.2	PARAMETER STATEMENT INFORMATION	7.5
	7.3	INPUT FORMAT	7.6
		7.3.1 Overview	7.6
		7.3.2 REBT Options Input Block	7.6
8.0	SUBR	OUTINE PROPS	8.1
	8.1	PROPS FUNCTIONS	8.1
	8.2	PARAMETER STATEMENT INFORMATION	8.2
	8.3	INPUT FORMAT	8.3
		8.3.1 Overview	8.3
		8.3.2 Thermal Resistance Print Specifications. PROPS Input Block 1	8.4
		8.3.3 Convection Specifications for Cask Side and Cylindrical Grid End Regions. PROPS Input Block 2	8.5
		8.3.4 Materials Conductivity Polynomial Coefficient Sets. PROPS Input Block 3	8.6

	8.3.5 Parallel, Isotropic, and Orthotropic Conduction Models. PROPS Input Block 4	8.7
	8.3.6 Series Conduction Models. PROPS Input Block 5	8.10
	8.3.7 Assignment of Resistance to Cell Locations. PROPS Input Block 6	8.12
9.0	SUBROUTINE TSIDE	9.1
	9.1 TSIDE FUNCTIONS	9.1
	9.2 PARAMETER STATEMENT INFORMATION	9.2
	9.3 INPUT FORMAT	9.2
	9.3.1 Overview	9.2
	9.3.2 TSIDE Input Block	9.2
10.0	SUBROUTINE TBND	10.1
	10.1 PARAMETER STATEMENT INFORMATION	10.1
	10.2 INPUT FORMAT	10.1
11.0	SUBROUTINE RADC	11.1
	11.1 PARAMETER STATEMENT INFORMATION	11.3
	11.2 INPUT FORMAT	11.4
	11.2.1 Overview	11.4
	11.2.2 Set INFO Switch	11.4
	11.2.3 Define Regions	11.7
	11.2.4 K-Cell Identifiers	11.10
	11.2.5 I-Cell Identifiers	11.11
	11.2.6 J-Cell Identifiers	11.12
	11.2.7 H Array	11.14
	11.2.8 Input Example When RADC Is Not Used	11.19
12.0	SUBROUTINE RADP	12.1

	12.1	PARAMETER STATEMENT INFORMATION	12.2
	12.2	INPUT FORMAT	12.2
		12.2.1 Overview	12.2
		12.2.2 I-Direction Radiation Heat Transfer Mode	12.4
		12.2.3 J-Direction Radiation Heat Transfer Mode	12.4
		12.2.4 K-Direction Radiation Heat Transfer Mode	12.8
		12.2.5 Input Example When RADP Is Not Used	12.9
13.0	SUBRO	DUTINE RADR	13.1
	13.1	PARAMETER STATEMENT INFORMATION	13.3
	13.2	INPUT FORMAT	13.4
		13.2.1 Overview	13.4
		13.2.2 Descriptive, Introductory Text Input	13.4
		13.2.3 H Array Input	13.5
		13.2.4 LREG Array Input Section	13.12
		13.2.5 LT4 Array Input	13.17
		13.2.6 Discussion of Input Example	13.19
		13.2.7 Input Example When RADR Is Not Used	13.20
14.0	SUBRO	UTINE REBA	14,1
	14.1	REBA FUNCTIONS	14.1
	14.2	PARAMETER STATEMENT INFORMATION	14.2
	14.3	INPUT FORMAT	14.2
		14.3.1 Overview	14.2
		14.3.2 REBA Input Block	14.2
15.0	SUBRO	UTINE QINFO	15.1
16.0	SUBRO	UTINE HYDRO	16.1

	16.1	PARAMETER STATEMENT INFORMATION	16.2
	16.2	INPUT FORMAT	16.3
		16.2.1 Run Control Information	16.3
		16.2.2 Monitor Cells for Mass Flux	16.6
		16.2.3 Viscosity Specifications	16.8
17.0	SUBRO	UTINE PINIT	17.1
	17.1	PARAMETER STATEMENT INFORMATION	17.2
	17.2	INPUT FORMAT	17.2
18.0	SUBRO	UTINE PROPM	18.1
	18.1	PARAMETER STATEMENT INFORMATION	18.6
	18.2	INPUT FORMAT	18.6
		18.2.1 Overview	18.6
		18.2.2 "Global" Setting of PERMX, PERMY, and PERMZ	18.6
		18.2.3 Block Loading Arrays AX, AY, AZ, AXI, AYI, AZI, POR, PERMX, PERMY, and PERMZ	18.7
19.0	SUBRO	UTINES MOMX, MOMY, AND MOMZ	19.1
	19.1	PARAMETER STATEMENT INFORMATION	19.1
	19.2	INPUT FORMAT	19.1
20.0	SUBRO	UTINE PDG	20.1
	20.1	PARAMETER STATEMENT INFORMATION	20.2
	20.2	INPUT FORMAT	20.2
		20.2.1 Overview	20.2
21.0	SUBRO	UTINE PITER	21.1
	21.1	PARAMETER STATEMENT INFORMATION	21.3
	21.2	INPUT FORMAT	21.3
		21.2.1 Overview	21.3

22.0	SUBRO	DUTINE PILES	22.1
	22.1	PARAMETER STATEMENT INFORMATION	22.2
	22.2	INPUT FORMAT	22.2
		22.2.1 Overview	22.2
23.0	SUBRO	DUTINE REBS	23.1
	23.1	REBS FUNCTIONS	23.1
	23.2	PARAMETER STATEMENT INFORMATION	23.1
	23.3	INPUT FORMAT	23.1
24.0	SUBRO	DUTINE REBQ	24.1
	24.1	REBQ FUNCTIONS	24.1
	24.2	PARAMETER STATEMENT INFORMATION	24.4
	24.3	INPUT FORMAT	24.5
		24.3.1 Overview	24.5
		24.3.2 Printout and Execution Options	24.6
		24.3.3 KREG Partition Specifications	24.7
		24.3.4 JREG Partition Specifications	24.13
		24.3.5 IREG Partition Specifications	24.18
25.0	SUBRO	DUTINE CROUT	25.1
	25.1	PARAMETER STATEMENT INFORMATION	25.1
	25.2	INPUT FORMAT	25.1
26.0	SUBRO	DUTINE AF	26.1
	26.1	PARAMETER STATEMENT INFORMATION	26.1
	26.2	INPUT FORMAT	26.1
		26.2.1 Overview	26.1
27.0	SUBRO	UTINE AVG	27.1
	27.1	PARAMETER STATEMENT INFORMATION	27.1

	27.2	INPUT F	ORMAT	27.1
		27.2.1	Overview	27.1
28.0	SUBRO	UTINE PR	INTL	28.1
	28.1	PARAMET	ER STATEMENT INFORMATION	28.1
	28.2	INPUT FO	ORMAT	28.1
29.0	SAMPL	E PROBLE	4	29.1
	29.1	CONFIGU	RATION	29.1
	29.2	COMPUTA	TIONAL MODEL	29.7
	29.3	COMPUTE	R SIMULATIONS	29.12
		29.3.1	Base Case Run	29.12
		29.3.2	Base-Case Run Extension	29.21
		29.3.3	Invoke REBA	29.21
		29.3.4	Invoke REBT	29.22
		29.3.5	Timing Runs	29.24
REFERI	ENCES	••••	• • • • • • • • • • • • • • • • • • • •	R.1
APPEN	DIX A	- SAMPLE	PROBLEM INPUT	A.1
APPENI	DIX B	- SAMPLE	PROBLEM OUTPUT	B.1

FIGURES

~

2.1	HYDRA-II Overall Structure	2.3
2.2	Outer Loop for Energy and Momentum Equation Solution	2.4
2.3	Energy Equation Solution Loop	2.5
2.4	Momentum and Continuity Equation Solution Loop	2.7
4.1	Alignment of Mesh and Physical Features and Proper Interfacing of Cartesian and Cylindrical Grid Regions	4.2
4.2	Mesh Orientation and Interfacing Principles	4.3
4.3	Rectangular and Cylindrical Grid Regions for Cask Simulation, Showing Possible Stepped Variations in Outer Cask Radius	4.4
4.4	Potential Modeling Region for Rectangular-Grid-Only Simulation	4.5
4.5	Some Nodalization Principles and Available Models	4.8
4.6	Series and Parallel Conduction Models	4.10
4.7	Subroutine GRID Input Blocks 1 and 2 for Mesh Shown in Figure 4.2c	4.12
4.8	Ranges of Axial Indices in Energy Momentum Equations for Sample Cask Nodalization with KP = 31, KBP = 2, and KTP = 3	4.13
4.9	Nodalization in X-Y Plane on a Region Treatable in Rectangular-Grid-Only Simulation	4.15
4.10	Sample Input for Rectangular-Grid-Only Simulation for Mesh of Figure 4.9	4.16
5.1	Heat Transfer Model Schematics	5.7
5.2	Parallel and Series Heat Transfer Examples	5.12
6.1	Regions Where Temperature is Set or Reset by Input to THERM	6.5
7.1	Qualitative Plot of Maximum Divergence Error in a K-Layer Versus Number of Iterations in REBT	7.3

7.2	Schematic Behavior of Maximum Temperature Change &T Per Time-Step Before and After REBT Call	7.4
7.3	Schematic Behavior of Maximum Temperature Change &T Per Time-Step for Varying XDTIME Values in a REBT Call	7.5
11.1	RADC Regions Superimposed on the Transverse Computational Mesh	11.5
11.2	Axial Computational Mesh and Alignment of Mesh with Physical Cask Features	11.6
11.3	RADC Enclosure 4 Blow-up Showing Modeled and Image Sections	11.20
12.1	Typical RADP "Floating Region" Simulating Radiation Heat Transfer in the K-Direction	12.5
12.2	Transverse Computational Mesh and Alignment of Mesh with Physical Cask Features - RADP Regions Shown	12.6
12.3	Axial Computational Mesh and Alignment of Mesh with Physical Cask Features - RADP KBEG and KEND Indices Shown	12.7
13.1	Placement of I and J Grid-Lines for HYDRA-II Cells When Spent Fuel Rods Are Modeled	13.2
13.2	RADR Example Grid	13.2
13.3	RADR Heat Transfer Coefficient Notation	13.9
13.4	Transverse Computational Mesh Illustrating I-Cell and J-Cell Levels of the RADR Model	13.15
13.5	Axial Computational Mesh Illustrating K-Cell Levels of the RADR Model	13.16
18.1	Cellular Locations for No-Slip Boundary Conditions	18.3
18.2	Obstructed Flow Path	18.4
24.1	Coarse Mesh for a K-Plane	24.2
24.2	Coarse Mesh for a J-Plane	24.3
29.1	Sample Problem Computational Mesh - Plan View	29.2
29.2	Sample Problem Computational Mesh - Elevation View	29.3
29.3	Sample Problem Computational Mesh - Elevation View	29.4

29.4	Cask Lid-to-Body Interface	29.5
29.5	Relative Axial Activity Profile	29.6
29.6	Basket Support Configuration	29.7
29.7	REBQ Model - KREG	29.13
29.8	REBQ Model - JREG	29.14
29.9	REBQ Model - IREG	29.15
29.10	Sample Problem Energy Flow Paths	29.19

TABLES

2.1	Input Data Units	2.9
5.1	Summary of PROP Input Blocks, Operations, and Indices	5.3
5.2	Thermal Parameter Set Construction for Heat Transfer Models	5.6
5.3	Values, Components Affected, and Actions Requested for the Parameter ID	5.10

~

,

1.0 INTRODUCTION

Implementation of spent fuel dry storage systems is required in the late 1980s because several at-reactor storage basins will attain maximum capacity (DOE 1986). The Nuclear Waste Policy Act of 1982 (NWPA) assigns the U.S. Department of Energy (DOE) the responsibility for assisting utilities with their spent fuel storage problems. One of the provisions of the NWPA is that DOE shall provide generic research and development of alternative spent fuel storage systems to assist utilities in their licensing activities.

One of the important requirements for storage systems is that they dissipate heat while maintaining the temperature of the stored materials below established limits. The thermal performance of a storage system can be assessed by a comprehensive testing program. Such testing programs are typically time-consuming and expensive. Analysis tools (e.g., computer codes), while not intended to entirely supplant testing methods, can perform a valuable service. Appropriately qualified computer codes can provide predictions of thermal performance as a function of system design and operating conditions. Moreover, when tests are to be performed, computer codes can help select test conditions, spent fuel decay heat generation rates, and instrumentation placements, as well as aid in interpreting test data.

HYDRA-II, developed by the Pacific Northwest Laboratory (PNL), is a computer code for heat transfer and fluid flow analysis. An enhanced version of HYDRA-I (McCann 1980), it is a member of the HYDRA family of general purpose codes collectively capable of transient three-dimensional analysis of coupled conduction, convection, and radiation problems. This current version is especially appropriate for simulating the steady-state performance of spent fuel storage systems of current interest. A specialized version was deemed appropriate for two reasons: 1) it provides a reasonable level of generality for most potential users without the unwelcome burden of excess complexity and cost, and 2) it permits public availability of the code in a timely fashion.

The documentation of HYDRA-II is presented in three separate volumes. <u>Volume I - Equations and Numerics</u> describes the basic differential equations, illustrates how the difference equations are formulated, and gives the solution

procedures employed. This volume, <u>Volume II - User's Manual</u>, contains code flow charts, discusses the code structure, provides detailed instructions for preparing an input file, and illustrates the operation of the code by means of a model problem. The final volume, <u>Volume III - Verification/Validation</u> <u>Assessments</u>, provides a comparison between the analytical solution and the numerical simulation for problems with a known solution. This volume also documents comparisons between the results of simulations of single- and multiassembly storage systems and actual experimental data.

A detailed overview of the HYDRA-II code is presented in Chapter 2.0. The code structure and solution sequence are described and illustrated with flow charts. General guidance on conventions to be followed in preparing the input file is also provided. Chapters 3.0 through 28.0 present specific descriptions of the code's individual subroutines. Each of these chapters contains the FORTRAN PARAMETERS and information needed to prepare the input file relevant to a specific subroutine. Chapter 29.0 contains a sample problem illustrating many characteristics of a typical spent fuel cask. The complete input file is included in Appendix A, and selected output is described in Appendix B. Code setup and operation, as well as output interpretation, are explained and illustrated using the sample problem.

2.0 CODE OVERVIEW

HYDRA-II provides a finite-difference solution in cartesian coordinates to the equations governing the conservation of mass, momentum, and energy. A cylindrical coordinate system may also be used to enclose the cartesian coordinate system. This exterior coordinate system is useful for modeling cylindrical cask bodies. When both coordinate systems are invoked, the code will automatically align the two systems and enforce conservation of energy at their interface.

The difference equations for conservation of momentum are enhanced by the incorporation of directional porosities and permeabilities that aid in modeling solid structures whose dimensions may be smaller than the computational mesh. The specification of inflow and outflow boundary conditions has been eliminated as appropriate for sealed storage systems. The equation for conservation of energy permits modeling of orthotropic physical properties and film resistances. Several automated procedures are available to model radiation transfer within enclosures and from fuel rod to fuel rod. An implicit solution algorithm is used for both the momentum and energy equations to ease time-step limitations and stability requirements.

HYDRA-II has been designed to provide a user-oriented input interface, which eliminates the need for internal code changes. Any application for which the code is an appropriate choice can be completely described through the construction of an input file. The user may optionally request a formatted echo of the input file to confirm that the intended parameters are actually those used by the code. A selectable commentary monitoring the progress of the code toward a steady-state solution is available, as is a summary of energy balances. Finally, a tape may be written at the conclusion of a run if the user wishes to restart the solution from its most recent point.

2.1 CODE STRUCTURE AND SOLUTION SEQUENCE

HYDRA-II is intended for steady-state applications. The method used by the code to approach steady state is similar to a transient simulation that ultimately converges to the steady-state condition. Starting from specified

initial conditions, the solution will evolve through time using automatically selected time-steps for both the energy and the momentum equations. Because only a steady-state solution is desired, the time-dependent terms for the energy, momentum, and continuity equations have been modified to accelerate convergence. Therefore, before it reaches steady state, the evolving solution will not correspond exactly to an actual transient solution, and the numerical values of the time-steps do not represent real time.

The overall structure of HYDRA-II is shown in Figure 2.1. If the run is to be restarted based on the results of a previous run, then the code will read a restart file. This file contains the thermal and momentum time-steps, temperatures, mass fluxes, densities, and pressures. If no restart file is present, the code will prescribe initial values for the above variables and proceed to initialize all subroutines in accordance with instructions read from the input file. The initial temperature field(s) may be printed, if desired, at this time.

Next, the outer loop for solution of the energy and momentum equations begins. The flow chart shown in Figure 2.2 illustrates the computational sequence. The appropriate subroutines are called in the correct order to determine a solution for either the energy equation(s) or the momentum equations or both. If a solution to both energy and momentum equations is desired, then the sequence is to solve for new-time temperatures using old-time mass fluxes and then solve the momentum equations using updated (temperaturedependent) density and viscosity. The solution is advanced by incrementing time by a thermal and momentum time-step. The magnitude of the two time-steps need not be the same because only the steady-state solution is desired. After the prescribed number of time-steps is reached, the code will exit this outer loop.

The final phase of the run consists of printing user-selected energy balances and field variables. A restart file is also written if desired.

A more detailed explanation of the energy and momentum solution sequences is now given. Figure 2.3 shows the flow chart for solution of the energy equation(s). If thermal radiation is present on the cartesian coordinate system, then, according to input file instructions, the selected subroutines embodying



.

FIGURE 2.1. HYDRA-II Overall Structure

2.3

~



FIGURE 2.2. Outer Loop for Energy and Momentum Equation Solution

appropriate radiation models will be called to calculate source terms. Thermal resistivities are then computed using old-time temperatures. The new-time temperatures are calculated for one time-step based on resistivities, heat sources, old-time mass fluxes, and boundary conditions for the cartesian mesh.

If a solution to the energy equation on the cylindrical coordinate system is not desired, then the energy phase of the solution sequence is complete. However, if temperatures are required for the cylindrical mesh (e.g., a cask body), then cartesian thermal radiation source terms are updated using new-time temperatures. Heat flow between the cartesian and cylindrical coordinate system is computed using the updated radiation field. Thermal resistivities for the cylindrical mesh are calculated using old-time temperatures. New-time temperatures for the cylindrical coordinate system are computed for one thermal



FIGURE 2.3. Energy Equation Solution Loop

time-step, based on resistivities and boundary conditions. One boundary condition is the prescribed energy exchange between the two coordinate systems; the other boundary condition is the ambient temperature. The temperatures on the interface between the two coordinate systems are updated as a final step to ensure continuous temperatures and enforce conservation of energy.

The solution sequence for the momentum and continuity equations is illustrated by the flow chart shown in Figure 2.4. The sequence begins by updating fluid density and viscosity using new-time temperatures. The three linear momentum equations are then solved for the tentative or tilde mass fluxes. The tilde mass fluxes will not, in general, satisfy continuity because the continuity equation has not yet been included in the solution process.

The finite-difference form of the continuity equation is now constructed for solution of a pressure correction field. This pressure correction field will be used to update old-time pressure and to modify tilde mass fluxes so that they do satisfy continuity.

Several algorithms are available for determining the pressure correction field. The subroutine names and algorithms are:

- PILES line successive relaxation
- REBS an approximate solver on a coarse mesh
- REBQ an approximate solver on a coarse mesh that is more elaborate and more effective than REBS
- AF an approximate factorization scheme.

Subroutine PILES must always be used, but the other three are optional; one or more may be called at the user's discretion.

After the pressure correction field is determined, the average pressure is adjusted to maintain a fixed amount of mass within the system or a specified average pressure. The magnitude of the next momentum time-step is computed such that either a specified tilde mass flux divergence error is maintained or the computational effort required to determine the pressure correction field is held constant. Finally, new-time pressures and new-time mass fluxes are computed using the pressure correction field.





2.2 CODE CONVENTIONS

This section contains some general information about the HYDRA-II source, as well as conventions to be observed in preparing the input file.

The source for HYDRA-II is written in ANSI FORTRAN 77. Extensions that might be installation-specific have been avoided. The code has been run on CDC-7600, VAX 11/780, and CRAY machines, and verified to produce essentially the same results (minor changes relating to word length on the VAX were needed). Because the code version anticipated for public release has been run extensively on CRAY machines, the internal coding has been structured to favor vector machines.

The source uses FORTRAN PARAMETER statements to dimension arrays. Each new application will require redimensioning. This is easily accomplished with a line editor. Redimensioning is required because certain economies in computer memory are more easily achieved and are commonly necessary for largescale simulations.

Almost every subroutine reads some information from the input file during initialization, even if that subroutine may not be subsequently used. The information read by a particular subroutine is most relevant to the function of the respective subroutine. Certain data of global use are read by a few subroutines and then propagated by means of COMMON blocks.

List-directed reads are used almost exclusively in the source. The few formatted reads in HYDRA-II read only some descriptive text for echoing to the output file. The physical input file is separated into logical sections, each dealing with a particular subroutine or special activity within a subroutine. The section boundaries begin with an integer and then a slash followed by identifying text. For example,

1/HYDRO/MONITOR/MX

The first integer, which will be either 0 or 1, acts as a flag to either echo succeeding input lines to the output file (1) or not (0). The slash terminates reading of the record. The text (in this example) identifies the lines to

follow as being read by subroutine HYDRO and related to monitoring selected mass fluxes in the x-direction. The text is very helpful in searching for a desired section of input with the aid of a line editor.

The code runs internally using a metric system of units. The input file must be prepared using the same units. Table 2.1 lists the system of consistent units that is to be used.

All echoing of the input file to the output file is done without conversion. Computed temperatures, however, are converted to degrees centigrade when printing is requested.

2.3 SUBROUTINE DESCRIPTIONS

Each chapter in the remainder of this volume deals with a single subroutine. The function of the subroutine is discussed, and general guidance is given for preparing an input file. PARAMETER statement information is provided. Next, the general input format is given with a description of the individual variables whose values are to appear on the file. Finally, an input file example of an actual application is shown, to lend concreteness to the description for general input.

Quantity	Units	
Length	centimeter (cm)	
Mass	gram (g)	
Time	second (s)	
Force	dyne (dyn)	
Power	watt (W)	
Temperature	degree Kelvin (°K)	
Density	g/cm ³	
Pressure	dyn/cm ²	
Mass flux	g/cm ² -s	
Viscosity	Poise (dyn-s/cm ²)	
Specific heat	W-s/g-°K	
Thermal conductivity	W/cm-°K	

TABLE 2.1. Input Data Units

3.0 PROGRAM MAIN

Program MAIN functions primarily as an executive that calls appropriate subroutines as they are needed according to the requirements of the application. Program MAIN also reads and writes restart tapes (if required) and controls many of the printing options.

3.1 PARAMETER STATEMENT INFORMATION

Program MAIN requires the specification of parameters IP, JP, KP, ISP, JSP, KBP, and KTP. These parameters define the overall computational mesh and are described in Chapter 4.0, Subroutine GRID. Two additional parameters are required for specification of printing options:

- NPLA1P Most three-dimensional arrays may be printed in their entirety (the default condition). It may be desirable, at times, that only selected k-planes be printed, to reduce the amount of output. NPLA1P-1 is the maximum number of k-planes that can be selected for any printing option. If no options are desired (other than the default), then NPLA1P should be set to 1.
- NPLA2P This parameter designates the maximum number of printing options. The default printing condition does not constitute an option. If no options are desired, then NPLA2P should be set to 1.

3.2 INPUT FORMAT

3.2.1 Descriptive Text for the Application

A user may optionally insert text to be printed on the output file that describes the application.

General Input Format

NECHO LINES TEXT . . TEXT General Input Description NECHO - Echoing switch for this section of input. If input is to be echoed, then NECHO = 1; otherwise, 0. LINES - The number of lines of text that follow and that are ۲ to be read from the input file. TEXT - Text that the user wishes to have printed on the out-۲ put file. Each line of text may be up to 48 characters long. Input File Example 1 1/main 2 15 3 4 5 6 7 8 9 10 11 so they chop and change, and each fresh move is inly a fresh mistake. 12 13 robert service 14 15 input for castor-v/21 6/6/85 16 source is cv15v, input file is cinv15v6 17 1/2 symmetry, vertical, he, 28.09kw, case 6

Echoed Input File Example

1 1	
2	
3	
4	
5	
6	
7	
8	
9	
10	so they chon and change and each fresh move
11	is inly a fresh mistake.
12	robert service
13	
14	input for castor-v/21 6/6/85
15	SOURCE IS CV15V, Input file is clov15v6
16	1/2 symmetry, vertical, be 28.09km case 6
17	the example of the field of the

NECHO is set to 1 on line 1. LINES on line 2 indicates that 15 lines of text are to follow. Note that a line of text may consist entirely of spaces.

3.2.2 Run Control Information

The next section of input is used to provide some of the information needed for general code operation. This information includes the number of time-steps to be allowed, reading or writing restart tapes, and the selection of certain subroutines to be called.

General Input Format

NRUN, NSTEP, NSINFO NREAD, NWRITE, NDUMP STEADY, NOBODY, NOTEMP, NOVEL NEWTA NDTIME, DTIMEN DTIMAX, DTIMIN RADCON, RADPON, RADRON REBAON, NREB, NREBN

General Input Description

- NRUN This constant indicates the run number for identification only.
- NSTEP The number of time-steps for this run.

- NSINFO This constant controls the printing frequency of diagnostic information and monitored variables. For example, if NSINFO = 20, then information will be printed for time-steps 1, 21, 41, etc. Information is always printed for the first and last time-steps of a run.
- NREAD If a restart tape is to be read at the start of a run, then NREAD = 1; otherwise, 0.
- NWRITE If a restart tape is to be written at the end of a run, then NWRITE = 1; otherwise, 0.
- NDUMP If NWRITE = 1, then a restart tape is written every NDUMP time-steps. This feature is useful for a long run where a crash may occur before the conclusion of the run.
- STEADY Used to distinguish between a transient and a steadystate simulation. Because HYDRA-II is intended only for steady-state simulation, STEADY should always have the value of 1.0.
- NOBODY If the simulation does not include a cask body, then NOBODY = 1; otherwise, 0.
- NOTEMP If NOTEMP = 1, then the temperature field(s) will not be updated during this run; otherwise, 0.
- NOVEL If NOVEL = 1, then the flow field will not be updated during the run; otherwise, 0.
- NEWTA If new ambient temperatures are desired, then NEWTA =
 1; otherwise, 0. New ambient temperatures are read
 from subroutines THERM and TSIDE.
- NDTIME If a new initial time-step is desired for the solution of the energy equation, the NDTIME = 1; otherwise, 0. This new time-step is applied to the first time-step of the run, and must be given if the run is not restarted from a tape.

- DTIMEN The value of the initial thermal time-step at the start of a run. Subsequent thermal time-steps are computed automatically within the code. The thermal time-steps may be different from the time-steps used in the solution of the momentum equations for a steady-state application.
- DTIMAX The maximum value of the thermal time-step. A value of 1.0 or less is recommended for the steady-state mode of operation.
- DTIMIN The minimum value of the thermal time-step.
- RADCON If the radiation model embodied in subroutine RADC is to be invoked for the application, then RADCON = 1.0; otherwise, 0.0.
- RADPON If the radiation model embodied in subroutine RADP is to be invoked for the application, then RADPON = 1.0; otherwise, 0.0.
- RADRON If the radiation model embodied in subroutine RADR is to be invoked for the application, then RADRON = 1.0; otherwise, 0.0.
- REBAON, Subroutine REBA provides a numerical method for NREB, NREBN accelerating the thermal solution toward a steady state. If this subroutine is to be called, then REBAON = 1.0; otherwise, 0.0. The subroutine will be called at the beginning of a time-step, NS, when the relationship MOD(NS,NREB) .EQ. NREBN is satisfied. Subroutine REBA should be called only if both subroutines THERM and TSIDE are being used.

Input File Example

```
18 10,4,1
19 1,1,100
20 1.0,0,0,0
21 0
22 0,0.1,1.0,0.01
23 1.0,1.0,0.0
24 1.0,100,1
```

Echoed Input File Example

18		run number 10
19		
20	maln	nrun≠10 nstep≈ 4 nsinfo≠ 1
21	maln	nread=1 nwrite=1 ndump= 100
22	maln	steady=1.0 nobody=0 notemp=0 novel=0
23	main	newta=0
24	main	ndtime=0 dtimen=0.100e+00 dtimax=0.100e+01 dtimin=0.100e-01
25	main	radcon=1.0 radpon=1.0 radron=0.0
26	main	rebaon=1.0 nreb=100 nrebn= 1

There is a one-to-one correspondence between each line of input and its respective echo. For example, the sequence of integers 10,4,1, on line 18 of the input file corresponds to line 20 of the echoed input file where NRUN = 10, NSTEP = 4, and NSINFO = 1.

3.2.3 Print Plane Options

The amount of information that could be sent to the output file can be almost overwhelming for most large-scale simulations. The print plane options allow the user to print selected k-planes of most three-dimensional arrays. The default option is that the entire array is printed.

General Input Format

NECHO NPLA2 NPLA1, KPLANE, KPLANE, ... KPLANE ... NPLA1, KPLANE, KPLANE, ... KPLANE <u>General Input Description</u> • NECHO - Echoing switch for this section of input. If input is to be echoed, then NECHO = 1; otherwise, 0.

- NPLA2 The number of sets of k-planes available (the number of lines to follow).
- NPLA1 The number of k-planes to be specified for this set of k-planes.
- KPLANE The k-plane to be printed in a given set. When more than one KPLANE is specified for a given set, the kplanes are printed in the order listed.

Input File Example

25 1/main/print plane sets 26 2 27 1,18 28 2,25,2

Echoed Input File

28mainprint plane sets are2 maximum allowed is4 with5 planes per set29option1:1830option2:252

The input file shows that the echoing switch, NECHO, is on and that two k-plane sets are to be defined. Line 27 indicates that one k-plane, namely k = 18, will be printed for the first set. The second set shown on line 28 indicates that two k-planes are to be printed, namely k = 25 and k = 2, in that order.

The echoed input file shows on line 28 that two print plane sets are available, and that a total of four could have been defined. Also, each set could specify up to five planes.

3.2.4 Specification of Output

Most of the arrays that hold variables of interest (e.g., temperature, pressure, mass fluxes) may be printed at the discretion of the user. The arrays can be quite large and, even if the user wishes to print some variable, not all of the arrays may be needed. This section of the input file allows the user to specify what arrays to print and which print plane options are to be selected.

General Input Format

NECHO PRINT, NOPTION/PTI PRINT, NOPTION/PTSI PRINT, NOPTION/PQI PRINT, NOPTION/PQI PRINT, NOPTION/PQRAD PRINT, NOPTION/PTS PRINT, NOPTION/PTS PRINT, NOPTION/PMX PRINT, NOPTION/PMX PRINT, NOPTION/PMZ PRINT, NOPTION/PMZ PRINT, NOPTION/PDF PRINT, NOPTION/PPF

General Input Description

•	NECHO	 Echoing switch for this section of input. If input is to be echoed, then NECHO = 1; otherwise, 0.
•	PRINT	 If the array or information is to be printed, then PRINT = 1.0; otherwise, 0.0.
•	NOPTION	 This integer specifies the number of the print plane option selected (0 indicates the default option of

printing the entire array).

The following definitions are used to indicate variables or information to be printed. A slash precedes each character string in the input file; therefore, the character string is not used in the code.

- PTI, PTSI Temperatures in the inside and side of the cask, respectively. These temperatures are those that exist prior to the first time-step of a run.
- PQBND Provides a summary of useful heat transfer information. Net heat transfer rates to, from, and within various regions of the cask are displayed. This information is not contained in an array; therefore, no print plane option is needed.
- PQI Heat fluxes within the cask cavity.

- PQRAD Radiation heat transfer to each cell within the cask cavity. This is a summary of radiation source strength computed by subroutines RADC, RADP, and/or RADR.
- PTS1 Heat flow into each cell of the side of the cask from the inside.
- PT, PTS Temperature in the inside and side of the cask, respectively.
- PMX, PMY, Mass fluxes in the x-, y-, and z-directions, PMZ respectively.
- PDPF The change in the pressure field for the last timeistep.
- PPF The pressure field.

Input File Example

29 1/main/print arrays or info 30 0.0,0/pti 31 0.0,0/ptsi 32 1.0/pqbnd 33 1.0,1/pqi 34 0.0,0/pqrad 35 0.0,0/pts1 36 1.0,0/pt 37 1.0,0/pts 38 1.0,2/pmx 39 0.0,0/pmy 40 1.0,0/pmz 41 0.0,0/pdpf 42 0.0,0/ppf

Echoed Input File Example

32	main	print arrays or info
33		pti=0.0 npti= 0
34		ptsi=0.0 nptsi= 0
35		pqbnd=1.0
36		pql=1.0 npql= 1
37		pgrad=0.0 npgrad= 0
38		pts1=0.0 npts1= 0
39		pt=1.0
40		pts=1.0 npts= 0
41		pmx≠1.0 npmx= 2
42		pmy≏0.0 npmy=0
43		pmz=1.0 npmz= 0
44		pdpf=0.0 npdpf= 0
45		ppf≠0₀0 nppf= 0

Line 29 on the input file shows that NECHO has been set to 1; therefore, the echoed input file is printed as shown. Line 30 on the input file shows that PRINT is set to 0.0 for PTI, so initial temperatures inside the cask are not to be printed. Line 32 on the input file shows that PRINT is set to 1.0 for PQBND; hence, a summary of heat transfer information will be printed. Line 38 shows that PRINT is set to 1.0 and that print plane option 2 is desired for PMX (mass fluxes in the x-direction). This specification results in printing of k-planes 25 and 2 in this order.
4.0 SUBROUTINE GRID

Subroutine GRID allows the user to set up the computational grid for a HYDRA-II application.

4.1 GRID FUNCTIONS

A full hydrothermal model with conduction, radiation, and single-phase fluid flow on a rectangular grid for a three-dimensional region is available. In addition, a coupled calculation of the temperature field is optionally available on a cylindrical grid in a region enclosing the rectangular grid. The two grid types have a cylindrical interface surface where coded connection techniques impose some constraints on user grids. This hybrid grid configuration and computational model is useful for modeling an interior rectangular array of fuel rods and supporting structure within a cylindrical cask body. Quarter-plane and half-plane symmetry can be treated. Computations can also be performed on a rectangular grid alone without a surrounding cylindrical grid.

Figure 4.1a shows a typical cross-section of a spent fuel cask. The fuel assemblies are stored within the cask in configurations most readily described in rectangular coordinates. Figure 4.1b shows a realistic hybrid nodalization of the cask of Figure 4.1a. Figure 4.2 illustrates some of the grid interfacing principles of the nodalization of the two grid regions in a simpler geometry. Rectangular grid indices in the x-y plane are I and J, with nodalization 1<IS<ISP. The radial grid index is JS, with nodalization 1<JS<JSP.

Two features are assumed for the full hybrid rectangular-cylindrical grid model as currently coded: 1) there is no computed flow in the cylindrical grid region, and 2) the inner surface of the cylindrical grid region is a circular cylinder. The interface conditions between rectangular and cylindrical grid regions assume that heat flow from the rectangular region enters the cylindrical region at the inner radius of the second radial cell in the azimuthal sectors. Consistent coding of this energy flow imposes constraints on both the cylindrical and the rectangular grids. A rectangular grid interface cell (I,J) must have a unique connection to an azimuthal sector, as illustrated in











b. Nonallowed Orientation for Quarter-Plane Symmetry





Figure 4.2. If a hybrid grid is used, the rectangular grid region must extend with uniform cross section for the entire axial extent of the model. The outer radius of the cylindrical grid region can vary stepwise in the z-direction, as shown in Figure 4.3.

A simulation using a rectangular grid only is also an option. It offers somewhat greater flexibility in the shape of the computational region and the location of grid lines. The computational region geometry that can be accommodated is shown schematically in Figure 4.4. The X-Y section can extend from the y-axis outward in the positive x-direction with no re-entry by an



FIGURE 4.3. Rectangular and Cylindrical Grid Regions for Cask Simulation, Showing Possible Stepped Variations in Outer Cask Radius



FIGURE 4.4. Potential Modeling Region for Rectangular-Grid-Only Simulation

x-direction grid line, and y-direction grid lines can enter the computation region only once and leave it once. The cross section modeled in an X-Y plane is invariant in the z-direction.

4.1.1 Choosing the Grid

To set up a computational grid, users should obtain cross sections in the x-y plane of the system to be simulated, as shown in Figure 4.1a. They should select a cylindrical surface outside of which there is no modeled flow and

which lends itself to the transition to cylindrical mesh. The active computational cells (as opposed to phantom cells) for the rectangular mesh will all lie inside this interface surface. The computational cells are those on which the field variable is computed in the solution algorithm for that grid type. The phantom cells are those used to supply boundary conditions for the solution on that grid type.

Although phantom cells experience no change in their field variables in executing the solution procedure on their own grid type, the temperature variable for phantom cells at the rectangular-cylindrical grid region interface will be altered in solving the energy equation alternately on the rectangular and cylindrical grid regions while advancing the solution through a time-step. The conditions imposed are continuity of temperature and conservation of energy. The coded method of achieving these conditions sets specific requirements on the setup of the grid, the specification of the rectangular grid computation region, and the designation of the interface cells, as will be explained here.

There are typically three types of geometric regions in the boundary between a satisfactory rectangular and cylindrical grid: 1) a "flat spot" at constant y, 2) a "flat spot" at constant x, and 3) a curved region in which

every x-direction grid line must intersect a y-direction grid line on the cylindrical interface. These three region types on the boundary can be seen in Figure 4.1b. They can also be seen in the grid layout of Figure 4.2, which shows the allowed orientations for quarter-plane and half-plane symmetry simulations. This arrangement of "flats" and curves recognizes two requirements: 1) some accommodation is necessary to join a rectangular grid to a cylindrical grid, and 2) each azimuthal sector should give or receive an appropriate share of the total heat transfer with respect to the rectangular grid.

In a representative x-y plane cross section, the user must superimpose on the interior region a tentative orthogonal network or grid. An early step is to select the flat parts of the boundary of the rectangular computational grid, using some discretion about the amount of gap that can be tolerated between the rectangular grid and the cylindrical interface. Grid lines that penetrate perpendicularly through these flat side boundaries can be chosen primarily to optimize resolution of physical detail. By contrast, grid lines (x- or y-direction) that intersect the cylinder interface without intersecting a flat boundary must intersect a perpendicular grid line (y or x) at the interface cylinder, and this imposes some constraints on their location. For example, the right boundary of the grid columns I = 2 or I = 3 in Figure 4.2 can be chosen to optimize resolution in the x-direction in the region 2 < I < 4, whereas the grid boundary between I = 5 and I = 6 must meet an x-direction grid line at the interface, like the one between J = 2 and J = 3.

Grid lines should pass along the major material boundaries. In choosing them, the user should keep in mind the models available to describe the heat transfer phenomena: flow in the available open spaces, radiative transfer from cell to cell by rods, radiative exchange among cells facing interior enclosures, conduction from cell to cell through homogeneous materials and laminar composites, and inhibition of conduction from cell to cell by film resistances. Grid lines should be inserted as needed to represent the physical phenomena. Some nodalization principles and models are illustrated in Figure 4.5. Those grid lines that do not intersect a flat side boundary will generate an orthogonal grid line from their point of intersection with the cylinder interface.



Grid Lines Chosen to Follow Material Boundaries

a. Grid Lines Chosen to Follow Material Boundaries



c. Two-Dimensional Radiation Enclosure (Infinite in Z-Direction)



b. Radiation Across Narrow Gap Modeled with Inter-Cell Film Resistance



d. Array of Cylinders Modeled as Orthotropic Continuum



FIGURE 4.5. Some Nodalization Principles and Available Models

Cell Column in Z-Direction

Users should insert the obvious choices of grid lines following material boundaries and draw in the requisite orthogonal grid lines intersecting them on the cylindrical interface for those not intersecting the flat boundary regions. The grid may then be excessively detailed for available memory or desired computational speed. A reduction in the number of grid lines may be possible without serious loss of accuracy if composite models are used for conduction and partial-flow blockage models are used for flow. These techniques may lead to local reduction of spatial resolution without significant loss of accuracy on a larger scale.

The series and parallel laminar composite conduction models for heat flow allow some opportunity to economize on grid cells. Consider an interface between material 1 and material 2 as shown in Figure 4.6. One would prefer to make a cell boundary coincide with the material interface, as shown in Figure 4.6a. The desirability of fitting cell boundaries to a material interface in the y-direction, the requirement that x and y grid lines intersect on the cylindrical interface on the curved part of the rectangular grid boundary, and a need to reduce the number of computational cells may require grid lines as shown in Figure 4.6b. A medium-straddling cell such as the (I,J) cell of Figure 4.6b can be considered as having series conduction through layers in the x-direction and parallel conduction in the y-direction as shown in Figure 4.6c. The approximate laminar composite model is shown schematically in Figure 4.6d. The input for laminar composite conduction is described in Chapter 5.0, but its availability is described here to aid nodalization. If one of two media within a computational cell contains a fluid, some use of directional permeabilities, directional surface porosities, directional velocity-dependent drag coefficients, and altered viscosities may be appropriate to model flow effects.

The preceding discussion and Figure 4.2 should indicate both the reasons and the method for assigning IEEND, JEBEG, JEEND, ICART, and JCART values. Specifically, the rules for assigning IEEND(J) values are:



a. Preferred Nodalization at a Material Medium Interface

Qx



b. Compromise Nodalization



c. Series Paths for Heat Flow Qx and Parallel Paths for Heat Flow Qy in Medium-Straddling Cell from b

Q,

d. Orthotropic Laminar Composite Approximation to the Cell in c

FIGURE 4.6. Series and Parallel Conduction Models

• J = 1 - IEEND(1) = 1

 J = 2 to JFLATM, i.e., along curved boundary - Set IEEND(J) to one less than the I index of the cell bisected by the interface curve.

- J = JFLATM to JFLATP Set IEEND(J) to one less than the I value of the cells that extend from the "flat" boundary there to the cylindrical interface curve.
- J = JFLATP+1 to JP-1 Set IEEND(J) to one less than the I index of the cell bisected by the interface curve.

• J = JP - IEEND(JP) = 1.

JEBEG and JEEND(I) values should be assigned according to:

• I = 1 to IFLATM - JEBEG(I) = 2

- I = 1 to IFLATP JEEND(I) = the J value of layer below "flat" upper boundary, that is JEEND(I) = JP-1
- I = IFLATM+1 to I = the I index just left of the "flat" right boundary
 - JEBEG(I) = one more than the J value of the cell bisected by the interface curve
 - JEEND(I) = one less than the J value of the cell bisected by the interface curve.

In the most correct nodalization, the I index just left of the flat right boundary will be IP-1.

The ICART(JS) and JCART(JS) values are the I and J indices, respectively, of the phantom cell to which the JS azimuthal sector connects. The lowest active computational sector is JS = 2, and it should be connected to the cell (I,J) = (ICART(2), JCART(2)) = 2,1. The subsequent ICART and JCART values can be read directly from a user diagram analogous to Figure 4.2. Figure 4.7 shows input data appropriate to Figure 4.2.

The limits of the computational region for the momentum equations are set in the arrays IMEND, JMBEG, and JMEND, and they are related to the choices for the energy equation. The momentum equations apply only to the rectangular

```
2.0,4,4,5,9
1/grid/ieend ends of energy eq. comp. reg. in x-direction
1,4,5,6,5*7,6,5,4,1
l/grid/jebeg beginning of energy eq. comp. reg. in y-direction
4*2,3,4,5
1/grid/jeend
             ends of energy eq. comp. reg. in y-direction
4*12,11,10,9
1/grid/imend ends of mom. eq. comp. reg. in x-direction
4,5,6,7,5*8,7,6,5,4
l/grid/jmbeg beginning of mom. eq. comp. reg. in y-direction
4*2,2,3,4
1/grid/jmend ends of mom. eq. comp. reg. in y-direction
4*12,12,11,10
1/grid/icart i indices for hookup to azimuth reg. js=2 thru js=18
2,3,4,5,6,7,5*8,7,6,5,4,3,2
1/grid/jcart j indices for hookup to azimuth reg. js=2 thru js=18
3*1,2,3,4,5,6,7,8,9,10,11,12,3*13
1/grid/isend is indices of radial comp. reg. limits (for kp=10)
10*4
```

FIGURE 4.7. Subroutine GRID Input Blocks 1 and 2 for Mesh Shown in Figure 4.2c

grid. One should extend the momentum equation computation to include the curved part of the rectangular grid boundary.

Users must identify the z-direction region for which the momentum equations are solved. This is done with parameters KBP (K bottom parameter) and KTP (K top parameter), which are set by a parameter statement defined in Chapter 6.0. KBP and KTP are the number of active computational cells which are used for the energy equation at the bottom and at the top of the cask nodalization, respectively, which are not used as active computational cells for the momentum equations. The K-indices in arrays used exclusively for the momentum equation solution (and not used for the energy equation) will have a restricted range. A z-direction index K in an array used exclusively in the

momentum equations will apply to the same cell as an index K+KBP in an array used in the energy equation. While no specific input in GRID is for the "offset" or reduced range arrays, the user should keep this in mind in choosing the z-direction nodalization. Figure 4.8 shows this restricted range and



K-offset for a real cask nodalization. The K-nodalization and KBP and KTP parameters for the cask shown in Figure 4.8 were chosen to model the conduction at the solid cask ends without a meaningless fluid flow calculation there.

4.1.2 <u>Simulations Using Only a Rectangular Grid</u>

Computations in a cylindrical grid region can be bypassed by setting NOBODY = 1 in the input to MAIN. For a simulation with no cylindrical region, nodalization for radial regions can be minimal, say ISP = 3. The boundary of the rectangular grid, however, still determines the number of azimuthal nodes required.

Figure 4.9 illustrates an X-Y nodalization for a geometry allowed in a rectangular-grid-only computation. The active computational region, shown by the dark outline in Figure 4.4, is defined in input using the arrays IEEND, JEBEG, JEEND, IMEND, JMBEG, and JMEND. Cells bounding the active computation region have a boundary condition or phantom cell role. The indices JS of the fictitious azimuthal sectors connecting to the boundary cells are shown circled. For a rectangular-grid-only simulation (NOBODY = 1), it is appropriate to set the dimensioning parameter JSP (number of azimuthal sectors, including phantoms) to two more than the number of phantom boundary cells in one X-Y plane to the right of the cell layer I = 1. Figure 4.10 illustrates a possible set of input for GRID Input Blocks 1 and 2 for the geometry of Figure 4.9.

A rectangular-grid-only simulation offers somewhat greater freedom in the choice of grid lines than does a hybrid grid. Code input does not currently allow a completely arbitrary specification of initial temperatures for a rectangular grid alone. If that is needed, it can be provided by fairly simple supplementary coding.

4.2 PARAMETER STATEMENT INFORMATION

Subroutine GRID requires the specification of the following parameters:



FIGURE 4.9. Nodalization in X-Y Plane of a Region Treatable in Rectangular-Grid-Only Simulation

 IP,JP,KP - Number of mesh planes in the x-, y-, and z-directions of the rectangular mesh, respectively, including those cell layers that are used for imposing boundary conditions or for interfacing: layers 1 and IP in the x-direction, layers 1 and JP in the y-direction, and layers 1 and KP in the z-direction.

1/GRID INPUT FOR RECTANGULAR-GRID-ONLY EXAMPLE IN FIGURE 4.9 4.0,3,4,7,9 /SYMTRY, IFLATM, IFLATP, JFLATM, JFLATP 1/GRID/IEEND(J),J=1,JP ENDS OF ENERGY EQ. COMP. REG. IN X-DIRECTION 1,3,3*6,2*5,2*4,1 1/GRID/JEBEG(I), I=1, IP-1BEGINNINGS OF ENERGY EQ. COMP. REG. IN Y-DIRECTION 3*2,3*3 1/GRID/JEEND(I), I=1, IP-1 ENDS OF ENERGY EQ. COMP. REG. IN Y-DIRECTION 3*9,5,6 1/GRID/IMEND(J), J=1, JPENDS OF MOM. EQ. COMP. REG. IN X-DIRECTION 1,3,3*6,2*5,2*4,1 1/GRID/JMBEG(I), I=1, IP-1BEGINNINGS OF MOM. EQ. COMP. REG. IN Y-DIRECTION 3*2,3*3 1/GRID/JMEND(I), I=1, IP-1 ENDS OF MOM. EQ. COMP. REG. IN Y-DIRECTION 3*9,5,6 1/GRID/ICART(JS), JS=2, JSP-1 I-INDICES FOR HOOKUP TO JS SECTORS 2,3,4,5,6,3*7,2*6,2*5,4,3,2 1/GRID/JCART(JS), JS=2, JSP-1 J-INDICES FOR HOOKUP TO JS SECTORS 2*1,3*2,3,4,5,6,7,8,9,3*10 1/GRID/ISEND(K),K=1,KP 12*2 /RADIAL LIMITS OF UNUSED CYLINDRICAL REGION

FIGURE 4.10. Sample Input for Rectangular-Grid-Only Simulation for Mesh of Figure 4.9

- ISP,JSP Number of radial annuli and azimuthal sectors, respectively, in the cylindrical grid, including radial layers

 and ISP and azimuthal sectors 1 and JSP that are used
 in imposing boundary conditions.
- NEFAP Dimension of a scratch array used for both grids and which should satisfy NEFAP = MAX(IP-1,JP-1,KP-1, ISP-1,JSP-1).

4.3 INPUT FORMAT

4.3.1 Overview

The input to subroutine GRID consists of 1) general specifications on the symmetry of the simulation and the region types in the rectangular-cylindrical grid interface; 2) integer arrays defining the computational mesh of the rectangular region for the energy and the momentum equation, and arrays specifying

the rectangular grid cells that interface with cylindrical grid sectors; and 3) arrays of mesh spacings for the rectangular and cylindrical meshes.

4.3.2 Symmetry and Interface Regions. Input Block 1

General Input Format

NECHO SYMTRY, IFLATM, IFLATP, JFLATM, JFLATP

General Input Description

- NECHO Echoing switch for this section of input. If input is to be echoed, then NECHO = 1; otherwise 0.
- SYMTRY Number of quadrants in modeled region: 1.0 for quarterplane symmetry, and 2.0 for half-plane symmetry.
- IFLATM The value of the highest I index in the rectangular grid for the flat part of the rectangular computational grid boundary at the lower constant y-value. See Figure 4.2.
- IFLATP The value of the highest I index in the rectangular grid for the flat part of the rectangular computational grid boundary at the higher constant y-value. See Figure 4.2.
- JFLATM The value of the lowest J index in the rectangular grid for the flat part of the rectangular computational grid boundary at constant x-value. See Figure 4.2.
- JFLATP The value of the highest J index in the rectangular grid for the flat part of the rectangular computational grid boundary at constant x-value. See Figure 4.2.
- Note: The grid shown in Figure 4.1 has IP = 25, JP = 48, ISP = 8, and JSP = 64, with the x-direction layer at I = 1 and the radial layer IS = 8 not shown. The phantom azimuthal sectors JS = 1 and JS = JSP = 64 are also not shown. This example also has IFLATM = 9, IFLATP = 9, JFLATM = 17, and JFLATP = 32. Because of the amount of detail and the fineness of the mesh in places, it is useful to also examine the grid shown in

Figure 4.2c, which has IP = 8, JP = 13, ISP = 5 (with radial section IS = ISP = 5 not shown), JSP = 19, IFLATM = 4, IFLATP = 4, JFLATM = 5, and JFLATP = 9. Input File Example 43 1/grid 44 2.0,9,9,17,32 Echoed Input File Example 46 47 grid symtry=2.0 iflatm=9 Iflatp=9 jflatm=17 jflatp=32

SYMTRY is set to 2.0 for the half-plane symmetry model shown in Figure 4.1. This simulation has IP = 25, JP = 48, KP = 31, ISP = 8, JSP = 64. IFLATM is set to 9, because I = 9 is the highest included I plane in the flat cartesian grid boundary between J = 1 and J = 2. IFLATP is similarly set to 9 for the flat part of the cartesian grid boundary between J = 47 and J = 48 = JP. JFLATM and JFLATP are set to 17 and 32, respectively, for the upper and lower J indices of the flat part of the rectangular grid boundary between I = 24 and I = 25 = IP.

4.3.3 <u>Rectangular Grid Computational Region Definition Grid</u>. Input Block 2

General Input Format

```
NECHO
IEEND(J),J=1,JP
INCO
JEBEG(I), I=1, IP-1
INCO
JEEND(I), I=1, IP-1
INCO
IMEND(J),J=1,JP
INCO
JMBEG(I), I=1, IP-1
INCO
JMEND(I), I=1, IP-1
INCO
ICART(JS),JS=2,JSP-1
INCO
JCART(JS), JS=2, JSP-1
INCO
ISEND(K),K=1,KP
```

General Input Definition

- NECHO Echoing switch for this section of input. If input is to be echoed, then NECHO = 1; otherwise, 0.
- IEEND(J) The highest I index of a computational cell as a function of J for which the energy equation is solved on the rectangular grid. Phantom cells are not included.
- INCO Integer variable used to update NECHO according to NECHO = MAX(NECHO,INCO), and which also serves as a line-holder for user comments in the input file.
- JEBEG(I) The lowest J index of a computational cell (as opposed to phantom cells) for layer I in the rectangular grid for the energy equation.
- JEEND(I) The highest J index of a computational cell in the I layer in the rectangular grid for the energy equation.
- IMEND(J) The highest I index of a computational cell in layer J in the solution of the momentum equations on the rectangular grid.
- JMBEG(I) The lowest J index of a computational cell for layer I in the solution of the momentum equations on the rectangular grid.
- JEND(I) The highest J index of a computational cell for layer I in the solution of the momentum equations on the rectangular grid.
- ICART(JS) The I index of the rectangular grid phantom cell that has an interface with azimuthal sector JS at the inner radius of the cylindrical annulus IS = 2. See Figures 4.1 and 4.2.
- JCART(JS) The J index of the rectangular grid phantom cell that has an interface with azimuthal sector JS at the inner radius of the cylindrical annulus IS = 2.

ISEND(K) - The highest IS index (cylindrical region radial index) of computational cells in the energy equation in the cylindrical grid at plane K. See Figure 4.3 for an example of a variable radial region. The outer cylindrical surface of a cell with IS = ISEND(K) at a given K-plane can be a radiating surface. If the outer surface is a single cylinder, then ISEND(K) = ISP-1 for all K.

The computational cells in the rectangular grid extend for the energy equation from I = 2 to I = IEEND(J) for a given J, and from J = JEBEG(I) to J = JEEND(I) for a given I. This is true for all K values. Phantom cells adjacent to computational cells are used in imposing interface conditions between rectangular and cylindrical grid regions. The arrays ICART and JCART specify the linkup of the two grids, but the grids and their interface must be set up as shown in Figures 4.1 and 4.2, with the previously discussed constraints imposed.

Input File Example

```
45 1/grid/ieend
46 1,9,10,11,12,13,14,15,16,17,18,19,20,21,22,23,16*24,
47 23,22,21,20,19,18,17,16,15,14,13,12,11,10,9,1
48 1/grid/jebeg
49 9*2,3,4,5,6,7,8,9,10,11,12,13,14,15,16,17
50 1/grid/jeend
51 9*47,46,45,44,43,42,41,40,39,38,37,36,35,34,33,32
52 1/grid/imend
53 9,10,11,12,13,14,15,16,17,18,19,20,21,22,23,18*24,
54 23,22,21,20,19,18,17,16,15,14,13,12,11,10,9
55 1/grid/jmbeg
56 10*2,3,4,5,6,7,8,9,10,11,12,13,14,15,16
57 1/grid/jmend
58 10*47,46,45,44,43,42,41,40,39,38,37,36,35,34,33
59 1/grid/icart
60 2,3,4,5,6,7,8,9,
61 10,11,12,13,14,15,16,17,18,19,20,21,22,23,24,16*25,
62 24,23,22,21,20,19,18,17,16,15,14,13,12,11,10,
63 9,8,7,6,5,4,3,2 64 1/grid/jcart
65 8*1,2,3,4,5,6,7,8,9,10,11,12,13,14,15,16,17,18,19,20,
66 21,22,23,24,25,26,27,28,29,30,31,32,33,34,35,36,
67 37, 38, 39, 40, 41, 42, 43, 44, 45, 46, 47, 8*48
68 1/grid/isend
69 31<del>*</del>7
```

Note: This input applies to Figure 4.1.

Output File Example

49	erid	Feend())	(i)pedel]#end(1)	imend(j)	jmbeg(1)	_imend(1)	lcart(js)	jcart(js)	isend(k)
50	• •	1	2	47	9	2	47	**	**	7
51	2	9	2	47	10	2	47	2	1	7
52	3	10	2	47	11	2	47	3	1	7
53	4	11	2	47	12	2	47	4	1	7
54	5	12	2	47	13	2	47	5	1	7
55	6	13	2	47	14	2	47	6	1	7
56	7	14	2	47	15	2	47	7	1	7
57	8	15	2	47	16	2	47	8	1	7
56	9	16	2	47	17	2	47	9	1	7
59	10	17	3	46	18	2	47	10	2	7
60	- 11	18	4	45	19	3	46	11	3	1
61	12	19	5	44	20	4	45	12	4	7
62	13	20	6	45	21	5	44	13	5	7
63	14	21	7	42	22	6	43	14	6	7
64	15	22	8	41	23	7	42	15	7	7
65	16	23	9	40	24	8	41	16	8	7
66	17	24	10	39	24	9	40	17	9	7
67	18	24	11	38	24	10	39	18	10	7
68	19	24	12	37	24	- 11	38	19	11	7
69	20	24	13	36	24	12	37	20	12	7
70	21	24	14	35	24	13	36	21	13	7
71	22	24	15	34	24	14	35	22	14	7
72	23	24	16	35	24	15	34	23	15	7
73	24	24	17	32	24	16	33	24	16	7
74	25	24	88	**	24	**	**	25	17	1
75	26	24	**	**	24		**	25	18	7
76	27	24	**	**	24	**	**	25	19	7
77	28	24	**	**	24	**	**	25	20	7
78	- 29	24	**		24	# #	**	25	21	7
79	30	24	**	**	24	**	**	25	22	7
80	· 31	24	**	**	24	**	**	25	23	7
81	32	24	48		24		**	25	24	**
82	33	23	**	**	24			25	25	
83	34	22	**		23	**	**	25	26	**
84	35	21	**	44	22		••	25	27	
65	36	20	**	**	21	**	**	25	28	
86	37	19			20	**	**	25	29	
87	38	18			19	**		25	30	
68	39	17			18	**		25	31	
89	40	16			17			25	32	
90	41	15	**		16			24	35	
91	42	14			15			23	54	
92	. 43	13		**	14			22	37	
93	44	12			13			21	20	
94	45				12			20	3/	
95	46	10	~~	**	11			19	50	
96	47	9	~*		10			61	24	
97	48	1	**	-	y	**	**	17	40	
98	49	**	-					16	41	
99	50							15	42	
100	51							14	•5	
101	52							15	44	
102	53	-	-				45	12	47	**
103	24	-	**					11	40	
104	22			**				10	40	**
205	20						**	, , , , , , , , , , , , , , , , , , ,	40	
106	5/		**	**				5	40	**
107	26							2	40	**
106	29								40	**
109	00					**		,	40	
110	01				**					
111	92							2	40	
114	زه							4		

The input shown corresponds to Figure 4.1, for which IP = 25, JP = 48, KP = 31, ISP = 8, JSP = 64. The 48 (=JP) entries for IEEND mark the limits of the computational region in the x-direction. The IEEND(1) and IEEND(JP) values are not significant, as they lie within J planes that are intrinsically phantom cells. In counting I-direction layers of cells in Figure 4.1, note that I = 3

corresponds to an extremely thin layer. Note IEEND(2) is set to 9, making the cell (I,J) = (10,2) a phantom cell. This is appropriate because the cell (I,J) = (10,2) is bisected by the cylinder and is appropriate for interfacing with the azimuthal sector JS = 10. The energy computations in the rectangular grid for J = 2 through J = 16 stop one short of a bisected interface cell in the I-direction. Energy computations for J = 17 through J = 32 stop at I = 24, leaving the cells at I = 25 in the region between this flat part of the rectangular grid boundary and the cylinder interface as phantom cells connecting to the azimuthal sectors JS = 25 through JS = 40.

The JEBEG and JEEND arrays give upper and lower J indices for the rectangular grid computational region, leaving the interface cell at either end (upper and lower) for interfaces. The IP-1 entries in either of these two arrays (for I = 1 to IP-1) specify these limits, whose correspondence to Figure 4.1 should be noted.

The computational limits for the momentum equation are similarly defined in IMEND, JMBEG, and JMEND. Note that the choices make the momentum equation computational region somewhat larger. The cells on the curved part of the interface boundary can be treated as having a partial flow area, with a zero flow condition on the next outward computational cell.

The ISEND(K) are set to 7 (=ISP-1) for all K indices, indicating that all radial regions in the cylindrical grid out to the phantom layer at IS = ISP = 8 are to be included, and that the cask exterior is a cylinder.

The echoed output of these arrays uses a running multipurpose integer index in a column on the left, i.e., the integer is I, J, JS, or K as needed, followed by columns to report IEEND(J), JEBEG(I), JEEND(I), IMEND(J), JMBEG(I), JMEND(I), ICART(JS), JCART(JS), or ISEND(K).

For convenience to users in seeing the region definitions and interface hookup input, a possible set of input for GRID Input Blocks 1 and 2 for the mesh shown in Figure 4.2c is presented in Figure 4.7.

4.3.4 Cartesian and Radial Mesh Spacings. Input Block_3

```
General Input Format
```

```
NECHO
DX(I),I=1,IP
INCO
DY(J),J=1,JP
INCO
DZ(K),K=1,JP
INCO
DR(IS),IS=1,ISP
```

General Input Definition

- NECHO Echoing switch for this section of input. If input is be echoed, then NECHO = 1; otherwise, 0.
- DX(I) The width of the Ith layer of cells in the x-direction.
- INCO Integer variable used to update NECHO according to NECHO = MAX(NECHO,INCO), and which also serves as a lineholder for user comments in the input file.
- DY(J) The width of the Jth layer of cells in the y-direction.

DZ(K) - The width of the Kth layer of cells in the z-direction.

 DR(IS) - The mesh spacing for the ISth radial cell. DR(1) should be set to the radius of the cylindrical interface with the cartesian grid.

Input File Example

70 1/grid/dx 71 1.0,5.0,0.5,5.5,2.0,4.02422514,1.0,3.97577486,1.0, 72 2*8.51211257,1.0,3.97577486,1.0,2.59636862,1.0, 73 6.93008731,0.8619833,2.10139183,0.75998222,2.77441184, 74 0.63974744,4.61506347,3.31733259,1.0 75 1/grid/dy 76 1.0,3.31733259,4.61506347,0.63974744,2.77441184, 77 0.75998222,2.10139183,0.8619833,6.93008731,1.0, 78 2.59636862,1.0,3.97577486,1.0,2*8.51211257,1.0, 79 3.97577486,1.0,4.02422514,2.0,5.5,0.5,2*5.0,0.5, 80 5.5,2.0,4.02422514,1.0,3.97577486,1.0,2*8.51211257, 81 1.0,3.97577486,1.0,2.59636862,1.0,6.93008731, 82 0.8619833,2.10139183,0.75998222,2.77441184, 83 0.63974744,4.61506347,3.31733259,1.0 84 1/grid/dz 85 1.0,18.0,14.0,3.0,7.0,10.0,12.5,15.0,17.5,20.0, 86 22.5,25.0,27.0,27.3,27.4,27.3,27.0,25.0,22.5,20.0, 87 17.5,15.0,12.5,9.5,9.0,9.0,6.5,5.5,23.5,9.3,1.0 88 1/grid/dr 89 75.2,1.0,10.0,3.2,2*10.0,4.8,1.0

Output File Example

113							
114	grid		dxt1)	dy(j)	dz (k)	dr(ls)	dtheta()s)
115		1	0.10000000#+01	0.100000000+01	0.100000000+01	0.75200000e+02	0,381237231+01
116		2	0.500000000+01	0.331733259+01	0,180000000+02	0.10000000e+01	0.381237231+01
117		3	0,50000000+00	0.461506547+01	0,140000000+02	0.10000000e+02	0.381888490+00
118		4	0.550000000+01	0,639747440+00	0,30000000+01	0,32000000e+01	0.421695021e+01
119		5	0,2000000000+01	0,277441184+01	0,700000000+01	0.10000000e+02	0.154365417e+01
120		6	0,402422514#+01	0.7599822200+00	0.100000000+02	0,10000000e+02	0,312952654e+01
121		1	0.1000000000000	0,2101391830+01	0.125000000+02	0.480000000+01	0,7854896680+00
122			0.1000000000000	0.601008731+00	0.175000000000000	0,100000000+01	0.709400400+00
124		10	0.851211257.001	0 10000000000000	0.2000000000000000000000000000000000000	************	0.696487587-00
125		11	0.851211257#+01	0.259636862+01	0.2250000000+02	*************	0.738747825e+01
126		12	0.1000000000+01	0.10000000000000	0.2500000000+02	**************	0.904497665+00
127		13	0,397577486+01	0.397577486+01	0.270000000+02	*************	0,369447113e+01
128		14	0,100000000+01	0.10000000+01	0,273000000+02	***************	0,956983767+00
129		15	0.259636862+01	0,851211257e+01	0,274000000e+02	*************	0.254515233+01
130		16	0.10000000e+01	0.851211257#+01	0,273000000+02	*************	0,100591424+01
131		17	0.693008731+01	0.10000000+01	0,270000000+02	***********	0.747250705+01
132		18	0.861983300e+00	0.397577486e+01	0,250000000+02	*************	0,100591424+01
133		19	0.210139183e+01	0.10000000+01	0.225000000+02	**********	0.254515234e+01
124		20	0.7599822200+00	0.4024225140+01	0.20000000000000	*************	0.9269837608+00
135		21	0.610747440.400	0.8500000000+01	0.150000000000000	************	0.904471736701
137		23	0.461506347e+01	0.5000000000+00	0.125000000e+02	*************	0.738747826e+01
138		24	0.331733259=+01	0.500000000+01	0.950000000+01	************	0.696487582+01
139		25	0,100000000+01	0.500000000+01	0.90000000e+01	**********	0,798499400e+00
140		26	**************	0,500000000+00	0.90000000+01	*************	0.314299247+01
141		27	*************	0,550000000+01	0.650000000+01	************	0.783489668+00
142		28	************	0.200000000+01	0,550000000+01	********	0.312952654e+01
143		29	************	0.402422514e+01	0.235000000e+02	*************	0.154365417e+01
144		30	*******	0.100000000e+01	0_950000000+01	***********	0.421695021+01
145		31 .	***********	0.397577486+01	0.100000000+01		0.381888490+00
146		32		0,10000000+01	*************	***********	0.381237231+01
147		35		0.8512112578+01	**************	************	0.3812372310+01
149		34	************	0.0000000000000000000000000000000000000	************	*************	0.3010004700100
150		36	*************	0.397577486+01	*************	************	0.154365417+01
151		37	*************	0.100000000+01	************	**************	0.512952654+01
152		38	*************	0.259636862+01	***********	*************	0.783489668+00
153		39	***********	0,10000000+01	**********	*************	0.314299247+01
154		40	************	0.693008731++01	***********	*************	0.798499400+00
155		41	*************	0,861983300e+00	*************	******	0,696487582e+01
156		42	*************	0.210139183e+01	**********	************	0.738247826+01
157		43	************	0.759982220+00	*************	*************	0.904497667+00
128		44		0.2774411840+01	************	***********	0.00944/1150+01
160		45		0.461506347+40	***********	************	0.254515234+01
161		47		0.331733259+01	*************	*************	0.100591424+01
162		48	*************	0,100000000+01	************	*************	0.747250705+01
163		49	************	************	***********	************	0.100591424+01
164	•	50	*************	**************	*************	************	0.254515233e+01
165		51	*************	******	*************	*************	0.956983767e+00
166		52	*************	**************	************	**************	0,369447113+01
167		53	************	***********		*************	0,904497665e+00
168		54	**************		*************		0,738247825+01
109		22		****************		****************	0.6964875810+01
170		20	**************	**************		****************	0.1984994000+00
171		50	*************			*************	0.39142992470101
178		50 50		*************	***************		0 312052654
174		60	*************	*************	*************	*************	0.154355417+401
175		61	************	*******	*************	***************	0.421695021#+01
176		62	************	*************	************	*************	0.381888490+00
177		63	***********	************	************	************	0.381237251+01
178		64	************	*******	************	************	0.381237231+01
179							0,180000000e+03

 \sim

The rectangular and cylindrical mesh spacings are both specified by this set of input. The azimuthal mesh is determined by the rectangular mesh and by the linkup prescribed by the ICART and JCART arrays and the mesh parameters IFLATM, IFLATP, JFLATM, and JFLATP, as can be seen in Figures 4.1 and 4.2. Although the thicknesses of the phantom cell layers set by DX(1), DZ(1), DZ(KP), DR(ISP), etc., are not critical for the boundary conditions usually imposed, they are not completely arbitrary, either. For example, if insulated boundary conditions are desired to impose symmetry about the constant x-plane between the I = 1 and I = 2 layers, then the product of the x-direction resistivity and the half-thickness of the I = 1 layer should be orders of magnitude greater than that for real conduction paths.

The echoed output of these arrays of mesh spacing information uses a running multipurpose integer index in a column on the left; i.e., the integer is I, J, K, IS, or JS as needed, followed by columns with DX(I), DY(J), DZ(K) DR(IS), and DTHETA(JS). The angular mesh spacing array, DTHETA(JS), is reported in degrees.

5.0 SUBROUTINE PROP

Subroutine PROP sets resistances to heat transfer in the rectangular grid region.

5.1 PROP FUNCTIONS

PROP treats heat transfer that is mathematically equivalent to conduction on a finite mesh. Emission and reabsorption of radiation over short distances within and between cells, as well as temperature dependence of true conduction, can be incorporated into thermal resistances by PROP using effective thermal conductivity polynomials. Explicit radiation models, like that among several surfaces facing an enclosure or among fuel pins treated discretely, are treated elsewhere in radiation routines RADC, RADP, and RADR.

At each time-step, PROP updates the resistances to heat transfer using current temperatures and previously stored sets of numbers referred to here as thermal parameter sets. These thermal parameter sets contain numbers that specify some features of the heat transfer model. For most models, these features include the temperature-dependence of the thermal conductivity of a comprising material or composite.

Heat transfer models available in PROP include:

- conduction in isotropic or orthotropic substances
- conduction through layered composites offering parallel conduction paths
- conduction through layered composites offering series conduction paths
- conduction and radiation among arrays of cylinders having axes in the z-direction (treated as a continuum)
- normal conduction through single or series films between cells, including gaps with combined radiation and conduction
- parallel heat transfer by radiation and by forced or natural convection from cask ends.

Input to PROP sets thermal properties of the system. On initiation or restart of a simulation, PROP reads:

- substance thermal conductivity information
- information specifying the heat transfer models
- information to assign thermal resistance parameters on the computational grid.

The substance thermal conductivity information comprises sets of coefficients for the thermal conductivity λ of material MAT expressed as a polynomial in absolute temperature:

 λ (MAT) = CCONO(MAT) + CCON1(MAT)*T + CCON3(MAT)*T³

The sets of (CCONO(MAT), CCON1(MAT), CCON3(MAT)) are read in PROP Input Block 3. The index MAT indicates a set for a particular material, and the name MAT is used in labeling this information in the echoed input.

The specification of the heat transfer models is done partly in PROP Input Blocks 4, 5, and 6, which direct the construction of thermal parameter sets (of set index MT). The specification of the heat transfer models is completed in PROP Input Block 7, in which I,J,K index ranges for thermal resistance assignment are followed by sets of (ID,MT) pairs. The composite identifier ID indicates the composite thermal model type (orthotropic and parallel conduction, series conduction, continuum fuel assembly conduction and radiation, cask-end convection) and the resistance component affected. The index MT specifies the thermal parameter set to use.

This sequence of operations in setting the thermal resistances from input is summarized in Table 5.1.

The effects of these models are included during the numerical solution only through the resistivity arrays RESX, RESY, and RESZ, and the film resistance arrays RESFX, RESFY, and RESFZ. In conduction, RESX(I,J,K) is the reciprocal of the effective thermal conductivity for heat flow in the x-direction within the (I,J,K) cell. In conduction, RESFX(I,J,K) is the film

PROP Input Block	Information Category	Arrays or Variable Sets Sets Read or Constructed	Identifying Name of Set Index
1	Thermal resistance specifications		
2	Rectangular grid cask-end convection specifications	Convection parameter sets (TOPH, TOPL, TOPV, TOPC, TOPN) and (BOTH, BOTL, BOTV, BOTC, BOTN) for the cask-end 51 group (ID = 51 or 52)	
3	Materials conductivity polynomial coefficient sets	(CCONO(MAT), CCON1(MAT), CCON3(MAT)), MAT = 1, MATS	MAT
4	Parallel, isotropic, and orthotropic conduction models	Thermal parameter sets for the isotropic 01 group (ID = 01, 02, 03, or 04) or the parallel conduction 11 group (ID = 11, 12, 13, 14, 15, or 16)	MT
5	Series conduction models	Thermal parameter sets for the cell-centered series conduction 21 group (ID = 21, 22, or 23) or the intercell film 41 group (ID = 41, 42, or 43)	MT
6	Fuel assembly conduction-radiation models	Thermal parameter sets for the fuel assembly conduction-radiation group 31 (ID = 31)	MT
7	Assignment of thermal resistance to cell locations	Mesh ranges and (ID,MT) pairs for assigning thermal resistances	

TABLE 5.1. Summary of PROP Input Blocks, Operations, and Indices

thickness divided by its conductivity for heat flow at the interface between cell (I,J,K) and cell (I+1,J,K). Similar definitions apply for y- and z-direction heat flow.

The user will get insight for the use of the models and the RES and RESF arrays by considering how they are used in the finite-difference equations.

HYDRA-II assumes a total heat transfer rate $Q_{K \rightarrow K+1}$ from cell (I,J,K) to cell (I,J,K+1) to have the form

$$Q_{K + K + 1} = (CK)_{K} T_{K} - (AK)_{K} T_{K + 1} + (SK)_{K}$$
 (5.1)

where CK_K , AK_K , and SK_K are functions of conductivity, flow velocity, properties of flowing material, cell size, and heat source. Indices I and J are suppressed in Equation (5.1). Specializing to no flow and no volumetric heat source simplifies the expressions of Equation (5.1) to

$$Q_{K+K+1} = \frac{\Delta x \Delta y}{\left(\frac{\Delta z}{2\lambda}\right)_{K} + \frac{1}{h_{K}} + \left(\frac{\Delta z}{2\lambda}\right)_{K+1}} (T_{K} - T_{K+1})$$
(5.2)

$$= \frac{\Delta x \Delta y}{\frac{1}{2} \Delta z_{K}^{*RESZ} + RESFZ_{K} + \frac{1}{2} \Delta z_{K+1}^{*RESZ} + (T_{K} - T_{K+1})$$
(5.3)

Here, λ is the thermal conductivity and 1/h is the film resistance. Equation (5.3) shows the additive nature of resistances to heat flow from the parts of the series path from the midplane of cell K to the film, through the film, and to the midplane of cell K+1.

A few observations follow from inspection of Equation (5.3):

1. If either the film resistance or the volumetric resistivity for heat conduction into a cell in a given direction is infinite, then no conductive heat flow will occur. This provides two ways of imposing an insulated boundary condition or zero heat flow condition required for symmetry, namely setting either the normal resistivity or the normal film resistance effectively infinite. If high phantom cell resistivity is used to impose insulated boundary conditions, the phantom cell thickness in the normal direction must not be infinitesimal but must have a resistivity times thickness that is relatively large.

- 2. If the effective resistivity within a cell for conduction in a particular direction is zero, the effect is equivalent to moving the cell center temperature to the cell boundary in that direction. This should be used in setting a temperature boundary condition at the edge of the computation region; i.e., set the resistivity in the phantom cell to zero and the phantom cell temperature to the value desired at the edge of the adjacent computational cell.
- Resistances to heat transfer by processes other than conduction can be modeled by appropriate temperature-dependent choices of resistivity and/or film resistance parameters, as we will show for specific cases.

The process of setting the RESX, RESY, RESZ, RESFX, RESFY, and RESFZ variables in subroutine PROP occurs in phases for these models. Descriptive input for these models is read in PROP in a series of input blocks. PROP Input Block 2 specifies some parameters needed for the cask end convection models. Input Block 3 specifies a number of sets of polynomial coefficients for conductivity of substances, the sets CCONO(MAT), CCON1(MAT), and CCON3(MAT) for MAT = 1 to MATS. Subsequent input blocks 4, 5, and 6 specify the construction of thermal parameter sets for use in the heat transfer models. These thermal parameters include the arrays CO(MT), C1(MT), C3(MT), and selected others for the specific models. Most commonly, the set CO(MT), C1(MT), and C3(MT) is a set of polynomial coefficients for a conduction-related variable. A final block of input to PROP gives final specifications for the construction of the resistance-related arrays according to these models, including the mesh locations at which they apply. The actual setting of resistance arrays is done at each time-step, using the latest temperatures, the constructed thermal parameter sets, and the resistance assignment directive sets.

Table 5.2 provides summary information for construction of the thermal parameter sets needed in the thermal models. It should be referred to in the following discussions of models and of input data. Figure 5.1 shows schematic

TABLE 5.2. Thermal Parameter Set Construction for Heat Transfer Models

Model	Nature of CO, C1, and C3 Arrays	I <u>Whe</u>	nput Bl <u>re Spec</u>	ock ified	_	Other Thermal Parameters of Model
Single isotropic or orthotopic conduction	Polynomial for effective conductivity in the L coordinate direction in the form $\lambda_{L}(MT) = CO(MT)+C1(MT)+T+C3(MT)+T^{3}$	PROP	Input	Block ·	4	None
Conduction through layers offering parallel paths to heat flow in a coor- dinate direction	Polynomial for $\Sigma_i \lambda_i \delta W_i$ for the composite in the form $\Sigma_i \lambda_i \delta W_i = CO(MT)+C1(MT)+T+C3(MT)+T^3$ = $(\Sigma_{MAT}CCONO(MAT)+\delta W_{MAT})$ + $(\Sigma_{MAT}CCON1(MAT)+\delta W_{MAT})+T$ + $(\Sigma_{MAT}CCON3(MAT)+\delta W_{MAT})+T^3$	PROP	Input	Block ·	4	None
Conduction through layers offering series paths to heat flow in a coor- dinate direction	Polynomial for $\lambda/\delta L$ for one material in the series: $(\lambda/\delta L)_{MT} = CO(MT)+C1(MT)*T+C3(MT)*T^3$ C3(MT) is optionally set from a gap radiation model as C3(MT) = 4.* $\sigma/(1/\epsilon_1 + 1/\epsilon_2 - 1)$	PROP	Input	Block	5	None
Array of cylinders or fuel assembly conduction- radiation model	C1(MT) and C2(MT) are polynomial coefficients for conductivity of intervening gas. C3(MT) can be coefficient of T^3 in radiation contribution to transverse conduction. All are used with other parameters (pitch, diameters, and conductivities) in model	PROP	Input	Block	6	CFUEL(MT), CCLAD(MT)
Conduction through cell interface	Polynomial for $\lambda/\delta L$ for one film layer type: $(\lambda/\delta L)_{MT} = CO(MT)+C1(MT)*T+C3(MT)*T^3$ C3(MT) is optionally set from a gap radiation model as C3(MT) = 4.* $\sigma/(1/\epsilon_1 + 1/\epsilon_2 - 1)$	PROP	Input	Block	5	TWF (MT)
Cask end radiation and convection	No set constructed for this model. C3(MT) from a set constructed for conduction through a film or a series layer should be referenced in INDEX in PROP Input Block 7	PROP	Input	Block 🕻	2	TOPV, BOTV, TOPC, BOTC, TOPL, BOTL, TOPN, BOTN, TWF(MT)



a. Simple Conduction



b. Conduction Through Parallel Layers



c. Conduction Through Series Layers <u>FIGURE 5.1</u>. Heat Transfer Model Schematics



d. Conduction and Radiation in Fuel Assembly



e. Conduction Through Cell Interface Films





geometry for the heat transfer models. The amount of model detail specified in intermediate blocks varies somewhat according to each model. For example, the parallel conduction model has a set of coefficients for the quantity $\Sigma_i \lambda_i \delta W_i$ formed at the intermediate stage and stored in (CO(MT), C1(MT), C3(MT)), and has the specified RESX, RESY, or RESZ value replaced by a new one in the final stage of applying the parallel conduction model to the prescribed range. By contrast, the series and film conduction models have coefficients for only single $\lambda/\delta L$ variables constructed at the intermediate stage and stored in (CO(MT), C1(MT), C3(MT)), and have the specified RESX, RESY, RESZ, RESFX, RESFY, or RESFZ altered by adding to the RESL new values of $(\lambda/\delta L)^{-1}/DXL$ or to existing values of RESFL new values of $(\lambda/\delta L)^{-1}$ in turn at the final stage of applying the series conduction model to the prescribed range. The action requested as a final step assigning resistances according to various models on prescribed ranges is determined by the variable ID and the specified intermediate parameter set MT in PROP Input Block 7. Table 5.3 summarizes the ID values and the action they request on resistance arrays.

The parallel and series conduction models could be used for exotic laminated materials, but they have an important function for modeling more routinely encountered materials. These models can be applied to cells that contain more than one material type, as required to maintain an acceptable number of rectangular mesh cells while also suitably interfacing with the cylindrical grid. Figure 5.2a shows an example in which the analyst has accepted a grid boundary between the I-1 and I layers of grid cells that does not coincide with a material boundary. The heat flow through the (I,J) cell in the x-direction resembles heat flow through two layers in series, as shown in Figure 5.2b; heat flow in the y-direction resembles heat flow through two layers in parallel. The series conduction model allows calculation of the resistivity RESX for heat flow in the x-direction as if the (I,J) cell were filled as in Figure 5.2c. Similarly, the parallel conduction model allows calculation of the resistivity RESY as if the (I,J) cell were filled as in Figure 5.2c. Judicious use of these models can give reasonable global heat flow results with reduction of resolution on the scale of a single cell. The anisotropy of the material resistivity from such models may be a consequence of

TABLE 5.3.	Values,	Components	Affected,	and	Actions	Requested	for	the	Parameter	ID	
									•		

ID Value	Component(s) Affected	Model	Action Requested
1	RESX - resistivity in the x coordinate direction	Conduction, x-direction	Reset RESX(I,J,K) to (CO(MT) + C1(MT)*T(I,J,K) + C3(MT)*T(I,J,K)**3)**(-1)
2	RESY - resistivity in the y coordinate direction	Conduction, y-direction	Reset RESY(I,J,K) to (CO(MT) + C1(MT)*T(I,J,K) + C3(MT)*T(I,J,K)**3)**(-1)
3	RESZ - resistivity in the z coordinate direction	Conduction, z-direction	Reset RESZ(I,J,K) to (CO(MT) + C1(MT)*T(I,J,K) + C3(MT)*T(I,J,K)**3)**(-1)
4	RESX,RESY, and RESZ - resistivities in all 3 coordinate directions	Isotropic conduction, x-, y-, and z-directions	Reset RESX(I,J,K), RESY(I,J,K), and RESZ(I,J,K) to (CO(MT) + C1(MT)*T(I,J,K) + C3(MT)*T(I,J,K) **3)**(-1)
11	RESX - resistivity in the x coordinate direction	Parallel conduction in the x-direction in layers lying in x-y planes	Reset RESX(I,J,K) to DZ(K)/(CO(MT) + C1(MT)*T(I,J,K) + C3(MT)*T(I,J,K)**3)
12	RESX - resistivity in the x coordinate direction	Parallel conduction in the x-direction in layers lying in x-z planes	Reset RESX(I,J,K) to DY(J)/(CO(MT) + C1(MT)*T(I,J,K) + C3(MT)*T(I,J,K)**3)
13	RESY - resistivity in the y coordinate direction	Parallel conduction in the y-direction in layers lying in x-y planes	Reset RESY(I,J,K) to DZ(K)/(CO(MT) + C1(MT)*T(I,J,K) + C3(MT)*T(I,J,K)**3)
14	RESY - resistivity in the y coordinate direction	Parallel conduction in the y-direction in layers lying in y-z planes	Reset RESY(I,J,K) to DX(I)/(CO(MT) + C1(MT)*T(I,J,K) + C3(MT)*T(I,J,K)**3)
15	RESZ - resistivity in the z coordinate direction	Parallel conduction in the z-direction in layers lying in x-z planes	Reset RESZ(I,J,K) to DY(J)/(CO(MT) + C1(MT)*T(I,J,K) + C3(MT)*T(I,J,K)**3)
16	RESZ - resistivity in the z coordinate direction	Parallel conduction in the z-direction in layers lying in y-z planes	Reset RESZ(I,J,K) to DX(I)/(CO(MT) + C1(MT)*T(I,J,K) + C3(MT)*T(I,J,K)**3)

TABLE 5.3. (contd)

ID Value	Component(s) Affected	Model	Action Requested
21	RESX - resistivity in the x coordinate direction	Series conduction in the x-direction through layers lying in y-z planes	Add to RESX(I,J,K) the effect of another layer: 1./((CO(MT) + C1(MT)*T(I,J,K) + C3(MT)*T(I,J,K) **3)*DX(I))
22	RESY - resistivity in the y coordinate direction	Series conduction in the y-direction through layers lying in x-z planes	Add to RESY(I,J,K) the effect of another layer: 1./((CO(MT) + C1(MT)*T(I,J,K) + C3(MT)*T(I,J,K) **3)*DY(J))
23	RESZ - resistivity in the z coordinate direction	Series conduction in the z-direction through layers lying in x-y planes	Add to RESZ(I,J,K) the effect of another layer: 1./((CO(MT) + C1(MT)*T(I,J,K) + C3(MT)*T(I,J,K) **3)*DZ(K))
31	RESX, RESY and RESZ - resistivities in all three coordinate directions	Conduction in a square array of cylinders with axes in the z-direction. Radiative and conductive transfer between cylinders.	Set RESX, RESY, and RESZ(I,J,K) according to model.
41	RESFX - film resistance (thickness times resistivity) to conduction in the x direction	Resistive layer in y-z plane between cell (I,J,K) and (I+1,J,K)	Add to RESFX(I,J,K) the effect of another layer: 1./(CO(MT) + C1(MT)*TB + C3(MT)*TB**3) where TB = TWF(MT)*T(I,J,K) + (1TWF(MT))*T(I+1,J,K)
42	RESFY - film resistance (thickness times resistivity) to conduction in the y direction	Resistive layer in x-z plane between cell (I,J,K) and (I,J+1,K)	Add to RESFY(I,J,K) the effect of another layer: 1./(CO(MT) + C1(MT)*TB + C3(MT)*TB**3) where TB = TWF(MT)*T(I,J,K) + (1TWF(MT))*T(I,J+1,K)
43	RESFZ — film resistance (thickness times resistivity) to conduction in the z direction	Resistive layer in x-y plane between cell (I,J,K) and (I,J,K+1)	Add to RESFZ(I,J,K) the effect of another layer: 1./(CO(MT) + C1(MT)*TB + C3(MT)*TB**3) where TB = TWF(MT)*T(I,J,K) + (1TWF(MT))*T(I,J,K+1)
51	RESFZ(I,J,KP-1)	Top end convection and radiation	Add to RESFZ(I,J,K) a contribution from the parallel heat transfer processes of convection and radiation
52	RESFZ(I,J,1)	Bottom end convection and radiation	Add to RESFZ(I,J,K) a contribution from the parallel processes of convection and radiation(a)

(a) The user should ensure that the K range (KBEG, KEND) is (KP-1, KP-1) for cask top, and (1,1) for cask bottom in the range specifications.

.

(


FIGURE 5.2. Parallel and Series Heat Transfer Examples

the noncoincidence of material and cell interfaces, not of intrinsic material structure, but it is useful for optimizing resolution when the number of cells is limited.

5.1.1 Simple Isotropic or Orthotropic Conduction Model

Subroutine PROP reads sets of polynomial coefficients CCONO, CCON1, and CCON3 for calculating conductivity λ of substance MAT at temperature T from

$$\lambda(MAT) = CCONO(MAT) + CCON1(MAT) + T + CCON3(MAT) + T^{3}$$
 (5.4)

These CCON type substance conductivity coefficient sets are read in PROP Input Block 3. These substance conductivity coefficients can subsequently be used to set arrays of coefficients CO(MT), C1(MT), and C3(MT) for polynomials that give either conduction-related parameters with a similar three-term polynomial or some other set of information used in setting RES or RESF type arrays. For simple isotropic or orthotropic conduction in material MT, the values (CO(MT), C1(MT), C3(MT)) will be set directly to (CCONO(MAT), CCON1(MAT), CCON3(MAT)), where MAT is a designated index for the thermal parameter set MT.

5.1.2 Parallel Conduction Model

For a set of layers that offer parallel paths for conduction in the L direction, the effective resistivity $R_{\rm I}$ is

$$R_{j} = W/(\Sigma_{j}\lambda_{j}\delta W_{j})$$
 (5.5)

where λ_i is the conductivity of the ith material in the composite and δW_i is its width. W is the width of the cell in the direction normal to the parallel planes of the composite. It is usually the case that

$$W = \Sigma_{i} \delta W_{i}$$
 (5.6)

The polynomial coefficient sets for the λ_i are input in PROP Input Block 3 in the CCONO, CCON1, and CCON3 arrays and subsequently used in setting the polynomial coefficients CO, C1, and C3 for $\Sigma\lambda_i\delta W_i$. The variables δW_i are input as WIDTH in PROP Input Block 4, along with the list of material property sets determining the λ_i to use in the $\Sigma\lambda_i\delta W_i$ sum. PROP Input Block 4 directs the construction of polynomial coefficients for $\Sigma\lambda_i\delta W_i$.

5.1.3 Series Conduction Model

For a set of layers offering series conduction paths in the L-direction through a computational cell, the effective resistivity in the L-direction is

$$R_{L} = \left(\Sigma_{i} \frac{1}{(\lambda_{i}/\delta L_{i})}\right) DXL$$
 (5.7)

where DXL is the computational cell length in the L-direction, λ_i is the conductivity of the ith material in the composite, and δL_i is the path length per computational cell supplied by the ith material. The variables δL_i for series layers are read as WIDTH in PROP Input Block 5, along with the index of the set of coefficients for the λ_i previously read in PROP Input Block 3. PROP Input Block 5 directs construction of polynomial coefficients for the guantities $\lambda_i/\delta L_i$. The direction of conduction and the orientation of the slabs is specified later by the variable ID read in the array INDEX in PROP Input Block 7. The coefficient sets for quantities of the form $\lambda_i/\delta L_i$ can also be used in the construction of film resistances for interfaces between cells. An option is available for construction of the cubic term in the series for $\lambda_i/\delta L_i$ according to a radiation model (see discussion of conduction through films).

5.1.4 Array of Cylinders or Fuel Assembly Model

The fuel assembly model constructs effective resistivities RESX, RESY, and RESZ for an array of cylinders having axes in the z-direction stored in a square pattern in the x-y plane. The cylinders are assumed to be composed of a circular cylinder core and annular clad, each region having its own characteristic conductivity. Resistivity RESZ is computed on the assumption of parallel conduction paths in the cylinder core, cladding, and intervening gas. Transverse resistivities RESX and RESY are computed on the basis of a twodimensional model that includes conduction in the cylinder core, cladding, and gas, as well as radiative heat transfer among the cylinders.

It should be noted that the radiative heat transfer among an array of fuel cylinders may, under special conditions, be treated by a more precise model (subroutine RADR) elsewhere in the code. For most practical purposes, RADR will require a region of the Cartesian mesh with one cylinder per cell column

in the z-direction. The user who can and wishes to use the RADR model can specify ignoring the radiative part of the transverse heat transfer in the fuel assembly model by setting either rod emissivity EROD or gap emissivity EGAP to zero in PROP Input Block 6.

5.1.5 Conduction Through Films

Films or gaps whose thicknesses are small compared with computational cells can have a significant effect on heat transfer. The effect as modeled in HYDRA-II can be seen for the case of no flow in Equation (5.3). HYDRA-II allows input of sets of polynomial coefficients for a number of materials in PROP Input Block 3. Subsequent input in PROP Input Block 5 allows construction of polynomial coefficients for series layer type quantities $\lambda/\delta L$, as described for the series conduction model. Coefficients of the $\lambda/\delta L$ type can also be used to construct film resistances singly or in series for the interfaces between grid cells.

A special feature allows construction of a film resistance for a narrow gap across which radiation occurs. RESFX, RESFY, and RESFZ are essentially reciprocals of heat transfer coefficients for the interface film between cell (I,J,K) and cell (I+1,J,K), (I,J+1,K), or (I,J,K+1), respectively. Radiation and conduction across a gas-filled gap are essentially parallel processes. Hence, the total heat transfer rate across a gap of width δL and area A will be

$$Q = \frac{\lambda'}{\delta L} A (T_1 - T_2) + A\sigma \frac{1}{\frac{1}{\epsilon_1} + \frac{1}{\epsilon_2} - 1} (T_1^4 - T_2^4)$$
(5.8)

where σ is the Stefan-Boltzman constant, ε_1 and ε_2 are emittances of the two surfaces facing the narrow gap, λ' is the thermal conductivity, and T_1 and T_2 are absolute temperatures on the two sides. If the absolute temperature difference in Equation (5.8) is not excessive, one can approximate Equation (5.8) by

$$Q = \frac{\lambda'}{\delta L} A (T_1 - T_2) + 4A\sigma \frac{1}{\frac{1}{\epsilon_1} + \frac{1}{\epsilon_2} - 1} T_B^3 (T_1 - T_2)$$
(5.9)

where T_B is some temperature between T_1 and T_2 . Noting that Q/A should be $(T_1 - T_2)^*(\lambda/\delta L)$ for an equivalent $\lambda/\delta L$, we can express Equation (5.9) in terms of an effective $\lambda/\delta L$:

$$\frac{\lambda}{\delta L} = \frac{\lambda'}{\delta L} + \frac{4\sigma}{\frac{1}{\varepsilon_1} + \frac{1}{\varepsilon_2} - 1} T_B^3$$
(5.10)

In constructing polynomial coefficients for the $\lambda/\delta L$ type quantities, HYDRA-II permits the coefficient of the cubic term, C3(MT), to be constructed either directly from a gap radiation model as $4\sigma/(1/\epsilon_1 + 1/\epsilon_2 - 1)$ with ϵ_1 and ϵ_2 as input emittances, or from the specified substance input variable set MAT as C3(MT) = CCON3(MAT)/ δL . The constructed polynomial coefficient set can thus optionally model conduction and radiation as parallel processes across the gap in the effective $\lambda/\delta L$, and the implied film or layer resistance can be placed in series with other layer resistances either within or between cells. Film resistance sets can be used in setting boundary conditions for cask ends.

The resistance to heat flow of the phantom cell between the flat parts of the rectangular grid boundary and the cylindrical grid interface can be accurately represented using the film resistance model. The volumetric resistivity for heat flow into these cells from the adjacent rectangular grid computational cell should be set to a low value. The film resistance, however, should be set to a value equal to the resistivity of the material there multiplied by the distance from the outside edge of the adjacent grid computational cell to the cylindrical grid interface. One can set up the $\lambda/\delta L$ polynomial coefficient values in PROP Input Block 5 for which $(\lambda/\delta L)^{-1}$ will give the desired resistivity multiplied by heat flow distance.

5.1.6 Cask End Convection and Radiation

Cask end boundary conditions are imposed using the resistance RESZ entries for K = 1 and K = KP, the film resistance RESFZ entries for K = 1 and K = KP-1, and the phantom cell temperature entries for K = 1 and K = KP. The physical phenomena modeled for cask ends are radiation and convection, and equivalent film resistance for these processes in parallel being added to whatever other film resistance the user specifies to be present. Convection and radiation from the ends are modeled as parallel processes with additive heat transfer coefficients. The reciprocal of the sum of the heat transfer coefficients for these processes is added to the film resistance RESFZ(I,J,1) or RESFZ(I,J,KP-1) as directed by entries in PROP Input Block 7. Options for the end conditions are set in PROP Input Block 2. Some entries needed for the radiation model can be set in PROP Input Block 5 as $\lambda/\delta L$ type film information.

The heat transfer coefficient for radiation is calculated as $C3(MT)*T_B^3$, where T_B is a boundary temperature and C3(MT) is a polynomial coefficient stored for the intermediate material properties set MT. In the specified set MT of intermediate material properties, the value of C3(MT) should have been appropriately set either as some $CCON3(MAT)/\delta L$, or from a gap radiation model in which $C3(MT) = 4\sigma/(1/E1 + 1/E2 - 1)$. This radiation model option for setting C3(MT) is available in setting the $\lambda/\delta L$ type polynomial coefficients in PROP Input Block 5. The boundary temperature T_B for radiation is a weighted average of the temperature in the edge computational cell and the phantom cell:

$$T_B = TWF(MT) * T(I,J,KBEG) + (1.-TWF(MT)) * T(I,J,KBEG+1)$$
 (5.11)

Here, KBEG is an entry in PROP Input Block 7 and should be set to 1 for setting bottom boundary conditions and KP-1 for top. TWF(MT) should have been set with the other series layer information in PROP Input Block 5.

The heat transfer coefficient for convection from cask ends can be set according to either natural or forced convection models. The models available are based on parameterized dimensionless correlations, but are specialized to air at atmospheric pressure as the medium and use linear approximations for the temperature dependence of its thermal conductivity and viscosity. The models are summarized below.

Forced Convection

Dimensionless Correlation

$$\frac{hL}{k} = C \left(\frac{\rho VL}{\mu}\right)^n \tag{5.12}$$

Coded Expression

$$h = (0.688 \times 10^{-4} + 0.635 \times 10^{-6} T_B) \frac{C}{L} \left(\frac{0.35296 VL}{T_B 0.608 \times 10^{-4} + 0.4 \times 10^{-6} T_B} \right)^n (5.13)$$

.

User-Selected Parameters

C,n,L,V

Assumptions

$$\rho = (\rho_0 T_0)/T$$

Linear approximations shown for $\boldsymbol{\mu}$ and \boldsymbol{k}_{\bullet}

Natural Convection

Dimensionless Correlation

$$\frac{hL}{k} = C \left[\frac{L^3 \rho^2 g_{\beta \Delta T}}{\mu^2} \left(\frac{C_p \mu}{k} \right) \right]^n$$
(5.14)

Coded Expression

$$h = (0.688 \times 10^{-4} + 0.634 \times 10^{-6} T_B) \frac{C}{L} * \left[\frac{87.9638 (L/T_B)^3 \Delta T}{(0.608 \times 10^{-4} + 0.4 \times 10^{-6} T_B)^2} \right]^n$$
(5.15)

User-Selected Parameters

C,n,L

Assumptions

$$\beta = \frac{1}{\rho} \left(\frac{\partial \rho}{\partial T} \right)_{\rho} = \frac{1}{T_{B}}$$

 $\rho = (\rho_0 T_0)/T$

$$(\rho_0 T_0)^2 g \frac{C_p \mu}{k} = 87.9638 \left(\frac{gm^* K}{cm^3}\right)^2 cm/sec^2$$

Linear approximations shown for μ and k. Definitions in the above forced and natural convection expressions are

h = convective heat transfer coefficient
k = thermal conductivity of gas medium in the boundary layer

- ρ = gas medium density
- V = forced convection flow velocity
- μ = viscosity of the gas medium
- T_B = boundary layer Kelvin temperature
- $\Delta T = |T_{ambient} T_{material}|$

L = length parameter representative of convecting surface

g = acceleration of gravity.

The boundary layer temperature T_B is calculated in the code as the average of the end layer (K = 2 for bottom, K = KP-1 for top) temperature in the Cartesian grid region and the respective ambient temperatures.

5.2 PARAMETER STATEMENT INFORMATION

The following array-dimensioning parameters have the same significance and should have the same value as in subroutine GRID (Chapter 4.0):

IP, JP, KP, ISP, JSP

Additional parameters appearing in subroutine PROP are:

- NMATP An array-dimensioning parameter greater than or equal to the number of substance conductivity polynomial coefficient sets read in PROP Input Block 3.
- MTP An array-dimensioning parameter greater than or equal to the largest value of MT for the intermediate variable sets (in arrays CO, C1, C3, TWF, CFUEL, CCLAD, etc.) for heat transfer models constructed from directives in PROP Input Blocks 4, 5, and 6.
- NSPECP Dimension of the array SPECS used in PROP Input Blocks 4, 5, and 6 to read in end-to-end all the intermediate heat transfer model specifications in each of the blocks. The SPECS array is overwritten by each of those input blocks in turn, but it must be long enough to accommodate the longest of the three blocks.
- NREGP,NPAIRP Two parameters used in setting length of the INDEX array (to INDEXP = 7*NREGP+2*NPAIRP) containing directives for assigning resistivity and film resistance values to cell locations (in PROP Input Block 7). NREGP is the maximum allowed number of region (range)

specifications for resistance assignment. NPAIRP is the sum over all the region specifications of the number of (ID,MT) pairs, where ID is an identifier of the resistance parameter affected and the model used, and MT is an identifier of the intermediate heat transfer variable set to use for that model. Each region directive set may request implementation of one or several changes in the resistance arrays for that region by including one or several (ID,MT) pairs.

5.3 INPUT FORMAT

5.3.1 Overview

The input to Subroutine PROP can be broken into seven blocks:

- 1. thermal resistance print specifications
- 2. rectangular grid cask end convection specifications
- 3. materials conductivity polynomial coefficient sets
- 4. parallel, isotropic, and orthotropic conduction models
- 5. series conduction models
- 6. fuel assembly conduction-radiation models
- 7. assignment of resistance to cell locations.

Detailed input will be described for these blocks.

5.3.2 Thermal Resistance Print Specifications. PROP Input Block 1

General Input Format

NECHO

NSX,NSFX,NSY,NSFY,NSZ,NSFZ,INFO

General Input Definition

- NECHO Echoing switch for this section of input. If input is to be echoed, then NECHO = 1; otherwise, 0.
- NSX,NSFX,NSY,NSFY,NSZ,NSFZ The number of the time-step at which to print the RESX, RESFX, RESY, RESFY, RESZ, and RESFZ

arrays, respectively. A negative entry suppresses printing of that array.

 INFO - Integer flag variable that, if equal to 1, requests printing of each resistivity or film resistivity array at its designated (by NSX, NSFX, etc.) time-step. No printing occurs if INFO = 0.

Input File Example

90 1/prop 91 -1,-1,-1,-1,-1,0

Echoed Input File Example

180 prop nsx= -1 nsfx= -1 nsfy= -1 nsz= -1 nsfz= -1 Info= 0

The echoing of input is requested by setting NECHO = 1; the remainder of the input line serves for comment. The printout of the RESL and RESFL (with L = x, y, or z) has been doubly suppressed, with INFO = 0 and NSX, NSFX, NSY, etc., set to -1. The user is advised to obtain these resistance array printouts (INFO = 1, NSX = 1, etc.) at least once in an early execution, to verify correctness of thermal model geometry and input.

5.3.3 Cartesian Cask End Convection Specifications

General Input Format

TOPH, TOPL, TOPV, TOPC, TOPN BOTH, BOTL, BOTV, BOTC, BOTN

General Input Definition

- TOPH Floating point flag variable that, if equal to 1.0, indicates a top end convective model is forthcoming. (Note: The line should contain five entries, even if TOPH = 0.0.)
- TOPL Length L to use in the forced convection [Equation (5.12)] or the natural convection [Equation (5.14)] heat transfer correlations for the cask top.

- TOPV Velocity to use in forced convection heat transfer correlation for top cask end. Setting TOPV = 0.0 with TOPH = 1.0 invokes the natural rather than forced convection model.
- TOPC Constant C to use for the top cask end heat transfer correlation in either forced convection [Equation (5.12), TOPV > 0.0] or natural convection [Equation (5.14), TOPV = 0.0].
- TOPN Exponent n to use for the top cask end heat transfer correlation in either forced convection [Equation (5.12), TOPV > 0.0] or natural convection [Equation (5.14), TOPV = 0.0].
- BOTH,BOTL,BOTV,BOTC,BOTN Values of convection flag, L, V, C, and n, respectively, for the cask bottom, analogous to TOPH, TOPL, TOPV, TOPC, and TOPN, respectively, for the cask top.

The complete specification of cask end thermal conditions will require entries elsewhere in PROP, such as radiation parameters or surface film resistances in Input Block 5 and resistance assignments in Input Block 7.

Input File Example

92 1.0,220.0,0.0,0.14,0.333 93 1.0,220.0,0.0,0.27,0.25

Echoed Input File Example

182						
183	prop	toph=1.0	top1=0.220e+03	topv≈0.000e+00	topc=0.140e+00	topn=0.333e+00
184	prop	both=1.0	bot1=0.220e+03	botv≈0,000e+00	botc=0,270e+00	botn≠0 . 250e+00

This input specifies that convection models are to be used on both the top and the bottom surfaces, because both TOPH and BOTH are set to 1.0. The length parameter in the convection correlation is set to 220 cm, on the order of the cask diameter. Setting velocity parameters TOPV and BOTV to zero specifies that the convection is natural, not forced. The coefficient C and the power n in the natural convection correlation, Equation (5.15), are specified as (TOPC = 0.14, TOPN = 0.333) for the top and (BOTC = 0.27, BOTN = 0.25) for the bottom. Values for C and n should be taken from the heat transfer literature.

5.3.4 <u>Material Conductivity Polynomial Coefficient Sets.</u> PROP Input Block 3

General Input Format

NECHO NMAT TEXT CCONO(1), CCON1(1)CCON3(1)TEXT CCONO(2), CCON1(2), CCON3(2)TEXT CCONO(NMAT),CCON1(NMAT),CCON3(NMAT) General Input Definition - Echoing switch for this section of input. If input is NECHO to be echoed, then NECHO = 1; otherwise, 0. NMAT - Number of sets of substance effective conductivity polynomial coefficients forthcoming. TEXT - Up to 40 characters of labeling information (5A8) for the next polynomial coefficient set. CCONO(MAT),CCON1(MAT),CCON3(MAT) - The MATth set of polynomial coefficients for representing an effective substance thermal conductivity $\lambda(MAT)$ as $\lambda(MAT) = CCONO(MAT) + CCON1(MAT) + T + CCON3(MAT) + T^3$.

These substance property sets are stored temporarily and are available to construct intermediate property sets (CO(MT), C1(MT), C3(MT)) for repeated use in setting resistance variables on the mesh according to the heat transfer models. The CO(MT), C1(MT), C3(MT) sets are saved and used for updating resistance variables as temperature changes.

Input File Example

94 1/prop/ccon0,ccon1,ccon3

95 9

```
96 low conductivity
97 0.1e-20,0.0,0.0
98 high conductivity
99 0.1e+20,0.0,0.0
100 helium (backfill gas)
101 0.52e-3,0.32e-5,0.0
102 sst
103 0.09215,0.1465e-3,0.0
104 boron steel (radionox)
105 0.079,0.21e-3,0.0
106 nodular cast iron
107 0.5162,-0.3205e-3,0.0
108 epoxy (not used)
109 0.15e-2,0.0,0.0
110 nitrogen (not used)
111 0.075e-3,0.6167e-6,0.0
112 air (not used)
113 0.6880e-4,0.6340e-6,0.0
```

Echoed Input File Example

186	prop	nmat= 9 maximum cur	rent dimension for nmat is 20	
187	prop	ccon0,ccon1,ccon3	material thermal conductivity, W/cm-k	
188		k (mat	<pre>ccon0(mat)+ ccon1(mat)*t+ ccon3(mat)*t*t*t</pre>	
189		t	(0,1000e-20)+(0,0000e+00)*t+(0,0000e+00)*t*t*t	low conductivity
190		2	(0.1000e+20)+(0.0000e+00)*t+(0.0000e+00)*t*t*t	high conductivity
191		3	(0,5200e-03)+(0,3200e-05)*++(0,0000e+00)*+*+*+	hellum (backfill gas)
192		4	(0.9215e-01)+(0.1465e-03)*++(0.0000e+00)*+*+*+	sst
193		5	(0,7900e-01)+(0,2100e-03)*++(0,0000e+00)*+*+*+	boron steel (radionox)
194		6	(0.5162e+00)+(3205e-03)*++(0.0000e+00)*+*+*+	nodular cast iron
195		7	(0,1500e-02)+(0,0000e+00)*++(0,0000e+00)*+*+*+	epoxy (not used)
196		8	(0,7500e-04)+(0,6167e-06)*++(0,0000e+00)*+*+*+	nltrogen (not used)
197		9	{0,6880e-04}+(0,6340e-06}*++(0,0000e+00)*+***	air (not used)

The input requests echoing of the nine material conductivity polynomial coefficient sets forthcoming. First descriptive text, then the list of three coefficients, appears for each of the nine sets. Note that some input sets may not be subsequently referenced.

The echoed input specifies the number of such sets NMAT, and also gives the current number, NMATP, of such sets that can be accommodated. The coefficient sets are printed out in a form that suggests their use, followed by the labeling text for that set.

5.3.5 <u>Parallel, Isotropic, and Orthotropic Conduction Models.</u> PROP Input Block 4

General Input Format

NECHO NTMAX SPECS(I),I=1,NSPECP

The entire dimensioned SPECS array is read. The user should construct it with MTMAX sets of entries, the sets being read end-to-end. It is recommended that each set of entries occupy one or more lines of input as needed, but that no lines contain entries for more than one of the sets. The form for a set for simple isotropic or orthotropic conduction or parallel conduction is

MT, MATS, MAT₁, WIDTH₁, MAT₂, WIDTH₂, ... MAT_{MATS}, WIDTH_{MATS}, MTMAX such sets

Unused locations of the NSPECP locations in SPECS should be set to zero. The entries in SPECS are in floating point form, but MT, MATS, MAT_1 , ... MAT_{MATS} are integer-type information after conversion.

General Input Definition

•	NECHO	-	Echoing switch for this section of input. If input is to be echoed, then NECHO = 1; otherwise, O.
•	МТМАХ	-	The number of specification sets forthcoming for the construction of thermal parameter property sets (CO(MT),C1(MT),C3(MT)) of the simple or parallel conduction types.
•	МТ	-	Index of a thermal parameter set for setting resistivity or film resistivity arrays.
•	MATS	-	The number of pairs of substance property index MAT and thickness WIDTH for use in setting the MTth intermediate parameters set.
•	MAT ₁ ,WIDTH ₁	,MA	T ₂ ,WIDTH ₂ - The substance property set indices MAT and the corresponding laminar layer thickness per cell

 δW = WIDTH for slabs offering parallel conduction

paths. See Equation (5.5). For simple substance conduction (as opposed to parallel laminar composite conduction), MATS will be 1 and WIDTH₁ should be set to 1.0.

The reading of the data in PROP Input Block 4 will direct construction of MTMAX thermal parameter set coefficients (CO(MT),C1(MT),C3(MT), with those for which MATS was 1 and WIDTH was 1.0 being polynomial coefficients for simple material conduction, and the others being for $\Sigma_i \lambda_i \delta W_i$ for parallel laminar composites. The simple substance sets with MATS = 1 and WIDTH = 1.0 are intended for use with ID = 1,2,3, or 4 in PROP Input Block 7. Those with MATS > 1 or WIDTH \neq 1.0 are intended for use with ID = 11,12,13,14,15 or 16 in PROP Input Block 7.

Input File Example

114 1/prop/specs def. 01 isotropic and 11 parallel 115 27 116 1.0,1.0,1.0,1.0, 117 2.0,1.0,2.0,1.0, 118 3.0,1.0,3.0,1.0, 119 4.0,1.0,4.0,1.0, 120 5.0,1.0,5.0,1.0, 121 6.0,2.0,3.0,1.0, 122 5.0,1.0, 123 7.0,1.0,5.0,0.7816, 124 8.0,2.0,3.0,0.5, 5.0,0.5, 125 126 9.0,1.0,3.0,2.0, 127 10.0,1.0,3.0,0.5, 128 11.0,1.0,5.0,2.0, 129 12.0,1.0,5.0,0.5, 130 13.0,2.0,3.0,0.6444, 4.0,0.3556, 131 132 14.0,1.0,3.0,1.552, 133 15.0,2.0,3.0,1.289, 134 4.0,0.7112, 135 16.0,2.0,3.0,0.3222, 4.0,0.1778, 136 137 17.0,1.0,3.0,3.104, 138 18.0,1.0,3.0,3.190, 139 19.0,1.0,3.0,1.431, 140 20.0,2.0,3.0,0.7221, 141 4.0,0.2779, 142 21.0,2.0,3.0,0.8222, 143 4.0,1.778,

144 22.0,1.0,3.0,1.355, 145 23.0,1.0,3.0,1.276, 146 24.0,2.0,3.0,4.669, 4.0,1.143, 147 148 25.0,2.0,3.0,7.366, 4.0,0.7366, 149 150 26.0,1.0,6.0,1.0, 151 27.0,1.0,4.0,8.0, 152 24*0.0

100

Echoed Input File Example

190							
199			maximum numbe	er of ma	terial	types is currently 45	
200			maximum array	dimens	lon of	specs is currently 150)
201							
202			***composite def	Inition	01 is	otropic and 11 parallel	***
203	prop	mtmax= 27					
204	prop	specs	m	mats	mat	width	
205	• •		1	1	1	0.1000+01	
206				: 1	2	0.1000+01	
207			3	1	3	0.1000+01	
208				1	4	0.1000+01	
209			4	1	5	0.10000+01	
210			e	2	3	0.1000e+01	
211					5	0.1000+01	
212			7	1	5	0.7816e+00	
213			8	2	3	0,5000+00	
214				-	5	0.5000+00	
215			g	1	3	0.2000e+01	
216			10	1	3	0.5000e+00	
217			11	1	5	0.2000e+01	
218			12	. 1	5	0.50000+00	
219			13	2	3	0.6446+00	
220			12	-	Ā	0.3556e+00	
221			14	1	3	0-1552e+01	
222			1	. 2	3	0.1289e+01	
223			1.	-	Á	0.71120+00	
224			16	2	3	0.32220+00	
225				-	á	0.1778e+00	
226			17	1	3	0.3104e+01	
227			18	. i	3	0.3190+01	
229			10		ž	0 14319+01	
220			20		2	0 7221 == 00	
230			20		ر ۸	0 2779	
231			21	2	7	0 92220+00	
237			21	2	ر ۸	0 1779 0101	
232			22			0.1355-01	
233			24	. 1	2	0.1276.001	
224			21	י ו י	2		
233			24	2	2		
230			26	2	4	0.71660+01	
231			25	2	د		
230					4		
239			26		0		
240			21	1	4	0.80000+01	
241					• •	•	
242			computed	coeffi	cients	trom specs array	

243	mt	c 0	ct	c3
244	1	0.1000e-20	0.0000e+00	0.0000e+00
245	2	0.1000e+20	0.0000e+00	0.0000e+00
246	3	0.5200e-03	0,3200e-05	0.0000e+00
247	4	0.9215e-01	0.1465e-03	0.0000e+00
248	5	0.7900e-01	0.2100e-03	0.0000e+00
249	6	0.7952e-01	0.2132e-03	0.0000e+00
250	7	0.6175e-01	0.1641e-03	0.0000e+00
251	8	0.3976e-01	0.1066e-03	0.0000e+00
252	9	0.1040e-02	0.6400e-05	0.0000e+00
253	10	0.2600e-03	0.1600e-05	0.0000e+00
254	11	0.1580e+00	0.4200e-03	0.0000e+00
255	12	0.3950e-01	0.1050e-03	0.0000e+00
256	13	0,3310e-01	0.5416e-04	0.0000e+00
257	14	0.8070e-03	0.4966e-05	0.0000e+00
258	15	0.6621e-01	0.1083e-03	0.0000e+00
259	16	0.1655e-01	0.2708e-04	0.0000e+00
260	17	0.1614e-02	0.9933e-05	0.0000e+00
261	18	0.1659e-02	0.1021e-04	0.0000e+00
262	19	0.7441e-03	0.4579e-05	0.0000e+00
263	20	0.2598e-01	0.4302e-04	0.0000e+00
264	21	0.1643e+00	0.26310-03	0.0000e+00
265	22	0.7046e-03	0.4336e-05	0.0000e+00
266	23	0.6635e-03	0.4083e-05	0.0000e+00
267	24	0.1078e+00	0.1824e-03	0.0000e+00
268	25	0.7171e-01	0.1315e-03	0.0000e+00
269	26	0.5162e+00	-0.3205e-03	0.0000e+00
270	27	0.7372e+00	0.1172e-02	0.0000e+00
271				

The initial line of the input data for this block asks for echoing of input (NECHO = 1) and contains a user comment as a reminder that the thermal parameter sets constructed here will be used either with the isotropic or orthotropic simple conduction 01 group (ID = 01,02,03, or 04), in which the constructed polynomial coefficients are for an effective conductivity λ (MT), or with the parallel laminar conduction 11 group (ID = 11,12,13,14,15, or 16), in which the polynomial coefficients are for a sum $\Sigma_i \lambda_i \delta W_i$. Explanations of the ID values used in PROP Input Block 7 will be discussed later and are summarized in Table 5.2.

The data specifies MTMAX = 27 sets of parallel and isotropic conduction model specifications. The SPECS entries are all floating point, with conversion to integers occurring in deconvoluting the end-to-end thermal parameter specification sets. The sets MT = 1 through MT = 5 in the example shown are simple substance sets with WIDTH = 1.0. By contrast, sets MT = 6 and MT = 8 are both parallel composites with two materials present. The set MT = 6 (lines 121 and 122) could be applied to cells having one slab of thickness 1 cm of material MAT = 3, and a second slab of thickness 1 cm of material MAT = 5. The set MT = 8 has the same two materials (MAT = 3 and MAT = 5), but would be applied to cells with 0.5-cm-thick slabs of each material offering parallel paths. The set MT = 7 (line 123) is of the parallel type, as indicated by WIDTH = 0.7816 rather than 1.0, but it has only one material present. The user is neglecting the contribution to total effective conductivity from other members (lower conductivity) of the set of parallel slabs. Referring to the data for PROP Input Block 3, we see that MT = 6 describes a composite of helium (MAT = 3) and boron steel (MAT = 5). Such composites are very useful when grid lines cannot be conveniently assigned for all material interfaces.

Note that the input data for this block ends with 24 zero values to fill out the SPECS array, which was dimensioned for this simulation to NSPECP = 150.

The echoed output is preceded by a reminder that the largest number, MT, of a thermal parameter set allowed by dimensioning is MTP and the length of the SPECS array used in PROP Input Blocks 4, 5, and 6.

The echoed input presents the MTMAX thermal parameter specification sets of this type, using MATS lines per set. The multiple-material sets thus stand out. The constructed thermal properties polynomial coefficients CO(MT), C1(MT), C3(MT) are presented. For MT sets for which MATS = 1 and WIDTH = 1.0, these sets will be the same as for the specified set MAT of substance conductivity polynomial coefficients read in PROP Input Block 3. These thermal parameter sets will be retained, however, after the substance coefficients are overwritten. Additional thermal parameter specification sets for other heat transfer models will be added in PROP Input Blocks 5 and 6.

5.3.6 Series Conduction Models. PROP Input Block 5

General Input Format

NECHO MTMAX SPECS(I),I=1,NSPECP

The entire dimensioned SPECS array is read. The user should construct it with MTMAX sets of entries, the sets being read end-to-end. It is recommended that

each set occupy one or more lines of input as needed, but that no lines contain entries for more than one of the sets. The input form for a laminar series conduction set is

MT,MAT,WIDTH,E1,E2,TWF(MT)

General Input Definitions

- NECHO Echoing switch for this section of input. If input is to be echoed, then NECHO = 1; otherwise, 0.
- MTMAX The number of specification sets forthcoming for the construction of thermal parameter sets (CO(MT), C1(MT),C3(MT),TWF(MT)) of the laminar series conduction type.
- MT Index of a thermal parameter set for setting resistivity or film resistivity arrays. Note: specifying an index already used for other thermal parameter sets of the same or other heat model type will cause overwriting.
- MAT,WIDTH The substance property set index MAT and the corresponding series path thickness δL = WIDTH per cell or film, for the construction of the thermal parameter set polynomial coefficients for the quantity $(\lambda/\delta L)_{\rm MT} = \lambda({\rm MAT})/{\rm WIDTH}.$
- E1,E2 Emittances of the two surfaces facing each other across a planar gap, if a radiation model is to be used in setting C3(MT) to 4σ/(1/E1 + 1/E2-1). If either E1 or E2 is zero, C3(MT) is instead set as C3(MT) = CCON3(MAT)/WIDTH.
- TWF(MT) If thermal parameter set MT is used for a film resistance, TWF(MT) is the relative weighting of the

lower-index cell temperature in computing an interface film temperature for the polynomial for $\lambda/\delta L$. For example, for RESFX(I,J,K): $T_B = TWF(MT)*T(I,J,K) + [1.-TWF(MT)]*T(I+1,J,K)$ RESFX(I,J,K) = 1./(CO(MT) + C1(MT)*T_B + C3(MT)*T_B³)

The reading of the data in PROP Input Block 5 will direct the construction of MTMAX more thermal parameter sets, each set comprising CO(MT), C1(MT), C3(MT), and TWF(MT). TWF(MT) is used for films between computational cells but not for series lamina within cells. The polynomial coefficients for the series model are for $\lambda/\delta L$ for single substance films.

Input File Example

```
153 1/prop/specs def. 21 series

154 11

155 32.0,3.0,1.0,0.0,0.0,0.5,

156 33.0,3.0,0.5,0.0,0.0,0.5,

157 34.0,4.0,4.572,0.0,0.0,0.0,

158 35.0,3.0,4.669,0.0,0.0,0.0,

159 36.0,4.0,2.946,0.0,0.0,0.0,

160 37.0,3.0,7.366,0.0,0.0,0.0,

161 38.0,3.0,0.3,0.2,0.2,0.5,

162 39.0,1.0,1.0,0.2,1.0,0.5,

163 40.0,3.0,0.35,0.83,0.45,0.0,

164 41.0,3.0,0.35,0.83,0.45,1.0,

165 42.0,1.0,1.0,0.8,1.0,0.5,

166 84*0.0
```

Echoed Input File

272						***composite	definition	21 series**	*
273	prop	mtmax≖	11						
274	prop	specs		mt	mat	width	e1	ə2	twf
275				32	3	0.1000 0+ 01	0.0000e+00	0.0000e+00	0.5000e+00
276				33	3	0.5000e+00	0.0000e+00	0.0000e+00	0.5000e+00
277				34	4	0.4572e+01	0.0000e+00	0.00000+00	0.0000 e+ 00
278				35	3	0.4669e+01	0.0000e+00	0.0000a+00	0.0000e+00
279				36	4	0.2946 0+ 01	0.0000a+00	0.00000+00	0.0000e+00
280				37	3	0.73660+01	0.0000a+00	0.0000e+00	0.0000e+00
281				38	3	0.3000e+00	0,2000e+00	0.2000e+00	0.5000e+00
282				39	1	0.1000 01 01	0.2000e+00	0.1000e+01	0.5000e+00
283				40	3	0.3500a+00	0.8300e+00	0.45000+00	0.0000e+00
284				41	3	0.3500e+00	0.8300e+00	0.4500e+00	0.1000a+01
285				42	1	0.1000e+01	0.8000e+00	0.1000e+01	0.5000e+00
286									
287					0	omputed coef	ficients fr	omspecs arra	y

288	mt	c 0	c1	c3
289	32	0.5200e-03	0.3200e-05	0,0000e+00
290	33	0.1040e-02	0.6400e-05	0.0000e+00
291	34	0.2016e-01	0.3204e-04	0,0000e+00
292	35	0.1114e-03	0.68540-06	0.0000e+00
293	36	0 .3128e- 01	0.4973e-04	0,0000e+00
294	37	0.7059e-04	0.4344e-06	0.00000+00
295	38	0.1733e-02	0.1067e-04	0.2520e-11
296	39	0.1000e-20	0.0000e+00	0.4536e-11
297	40	0.1486e-02	0.9143e-05	0.9345e-11
298	41	0.1486e-02	0 .9143e- 05	0.9345e-11
299	42	0 .1000e-2 0	0.0000e+00	0 . 1814 e -10

After the entry NECHO = 1 requesting echoing of input, the first line of this input has a user comment as a reminder that the thermal parameter sets constructed here will be used in the series conduction group 21 (ID = 21,22, or 23) or other groups having the series conduction character, like the film resistance group 41 (ID = 41,42, or 43) or the cask end group 51 (ID = 51 or 52). See PROP Input Block 7 and Table 5.2 for explanations of ID.

The data in this example specifies construction of MTMAX = 11 intermediate property sets of the series conduction type, with indices MT = 32 through 42. Note that the last index MT used for the isotropic and parallel conduction thermal parameter sets was at MT = 27, so a few blank locations are being left for future expansion. Line 156 has for MT = 33 the specifications MAT = 3 (for helium, as seen in PROP Input Block 3), WIDTH = 0.5 (for a 0.5-cm path in the conduction direction), E1 = E2 = 0.0 (for bypassing a gap radiation model), and TWF(33) = 0.5 (for equal weighting of temperatures on either side in calculating the film temperature for the $\lambda/\delta L$ polynomial). Line 162 has for MT = 39 a specification MAT = 1 (for a fictitious extremely low-conductivity material, as seen from PROP Input Block 3), WIDTH = 1.0 (for a 1.0-cm path in the conduction direction), emittances of 0.2 and 1.0 for the surfaces facing the gap, and TWF(39) = 0.5 (for equal forward and backward temperature weighting). One might expect MT = 39 to be a satisfactory set for a cask end radiation treatment for use with a convection model.

The 11 specification sets require 66 entries, leaving 84 of the 150 locations in SPECS to be filled with zeros in the last line of this input block.

The input variables of these specification sets and the resulting computed polynomial coefficients are echoed in the output in the form shown.

5.3.7 Fuel Assembly Conduction-Radiation Models. PROP Input Block 6

General Input Format

NECHO MTMAX SPECS(I),I=1,NSPECP

The entire dimensioned array SPECS is read. SPECS comprises MTMAX sets of entries making up the fuel assembly thermal parameter sets construction directives and having the form (after conversion from floating point to integer form as needed):

MT, MTA, FUELOD, CLADOD, PITCH, CFUEL, CCLAD, EROD, EGAP

General Input Definition

•	NECHO		Integer flag variable that, if positive, directs echoing of forthcoming input in the output.
•	МТМАХ	-	Number of specification sets forthcoming for construction of thermal parameter sets (CO(MT),C1(MT),C3(MT), X1(MT),X2(MT), Z1(MT),Z2(MT),Z3(MT)) of the fuel assembly type.
•	MT	-	Index of the thermal property set being constructed.
•	MTA	-	Index of a previously set thermal parameter set of the simple conduction type for calculating conductivity of the gas between the square array of cylinders. [CO(MT) gets set to CO(MTA), C1(MT) to C1(MTA)].
•	FUELOD	-	Outside diameter of the fuel pellets.
•	CLADOD	-	Outside diameter of the fuel cladding.
•	РІТСН	-	Distance between corresponding points on adjacent fuel rods in the array.
•	CFUEL	-	Thermal conductivity of the fuel.

• CCLAD - Thermal conductivity of the cladding.

- EROD Emittance of the fuel rods.
- EGAP Emittance of the gap between fuel rods when treating a single rectangular array of pins as a radiation enclosure (set to a value near 0.95).

Input File Example

```
167 1/prop/specs def. 31 fuel assembly
168 1
169 45.0,3.0,0.9484,1.072,1.430,0.0209,0.1150,0.8,0.95,
170 141*0.0
```

Echoed Input File Example

300												
301					***com	posite defi	nition 31	fuel assem	nbly###			
302	prop	stmax=	1									
303	prop	specs	mt	mta fue	lod cla	adod p	itch	cfuel	cclad	erod	egap	
304			45	3 0,948	4e+00 0.10	72+01 0.1	430+01 0.	2090-01	0.1150e+00	0.8000e+00	0.9500+00	
305												
306					COR	puted coeff	icients fr	om specs a	erray			
307			mt.	c 0	c1	c3	×t	x2	21	22	2 z	3
308			45	0,5200 - 03	0.3200-05	0.8052e-1	1 0,1130e	+01 0,1701	1++01 0.345	5e+00 0.959	91e-01 0.55	86e+00
100												

Following the request (NECHO = 1) for echoing of input, a user comment indicates that the resulting parameter set will go with ID = 31 in the assignment of resistance parameters to cells in PROP Input Block 7. The input example directs construction of a single thermal parameter set for a rectangular array fuel assembly heat transfer model. Index MT = 45 again allows a few spaces from the last previously used MT value, MT = 42. Thermal parameter sets for similar heat transfer models are grouped only for convenience. The data on line 169 directs use of the thermal parameter index MTA = 3 (assigned in Input Block 4 from the helium data in Input Block 3) for conductivity of the gas. Fuel core and cladding outside diameters are set at 0.9484 and 1.072 cm, respectively. The pitch of the square array is 1.430 cm. Thermal conductivity of the fuel and clad are set to 0.0209 and 0.1150 watts/cm°K), respectively. The emittances of rod and gap are set to 0.8 and 0.95, respectively.

5.3.8 Assignment of Resistance to Cell Locations. PROP Input Block 7

General Input Format

NECHO NREG,NPAIR INDEX(I),I=1,INDEXP The entire array INDEX is read. The NREG sets of region resistance assignment directives stored end-to-end in INDEX have the form:

IBEG, IEND, JBEG, JEND, KBEG, KEND, NPAIR, ID1, MT1, ID2, MT2, ... IDNPAIR, MTNPAIR

General Input Definitions

- NECHO Echoing switch for this section of input. If input is to be echoed, then NECHO = 1; otherwise, 0.
- NREG,NPAIR Number of region resistance assignment directive sets forthcoming in INDEX and the total number NPAIR of (ID,MT) pairs included in all of them.
- IBEG,IEND,JBEG,JEND,KBEG,KEND The beginning and ending mesh indices in the I, J, and K directions in turn for the current region resistance specification set.
- NPAIR (Redefined for the current resistance assignment directive set). Number of (ID,MT) pairs of resistance assignment directives in the current region resistance assignment directive set. Actions requested by (ID,MT) pairs are implemented in turn.
- ID,MT A pair of directives for modifying the thermal resistance arrays in the current region. ID specifies the heat transfer model type, structure orientation, and the action to be taken on one of RESX, RESY, RESZ, RESFX, RESFY, or RESFZ. MT is the index of the intermediate parameter set to use in this resistance parameter change. The changes specified by ID can be either replacement or addition to the resistance array variable for each I,J,K in the range set by IBEG < I < IEND, JBEG < J < JEND, KBEG < K < KEND. ID values are defined in Table 5.3.

Input File Example

171 1/prop/index 172 158,332

```
173 1,1,2,47,2,30,1,1,1,

174 2,24,2,47,1,1,1,52,42,

175 2,24,2,47,30,30,3,51,39,1,1,2,1,

176 2,24,2,47,4,27,1,4,3,

177 5,5,2,47,5,26,1,4,5,

178 2,24,21,21,5,26,1,4,5,

180 2,4,21,21,5,26,2,12,6,15,6,

181 2,4,28,28,5,26,2,12,6,15,6,

182 5,5,22,27,5,26,2,14,6,16,6,

183 2,2,20,20,5,26,1,42,32,

184 4,4,20,20,5,26,1,42,32,

185 2,2,28,28,5,26,1,42,32,

186 4,4,28,28,5,26,1,42,32,

187 5,5,22,22,5,26,1,41,32,

325 13,21,30,30,5,26,1,42,41,

326 13,21,34,34,5,26,1,41,41,

328 12,12,31,34,5,26,1,41,41,

329 21,21,15,18,5,26,1,41,40,

330 21,21,31,34,5,26,1,41,40,
```

331 65*0

Echoed Input File Example

310								**ava	ilable compo	osite	defi	nition:	3***						
311							gro	up		10								•	
312						()1 iso	tropi	c	1	resx								
313										2	resy								
314										3	resz								
315										- 4	resx.	,resy ,	*#5Z						
316						1	ll par	ailei		11	resx,	X-Y P	lane						
317										12	resx	x-z p	lane						
318										13	resy	x-y p	lane						
319										14	resy.	Y-Z P	lane						
320										15	resz,	x-z p	lane						
321										16	resz,	y-z p	lane						
322						2	ll ser	ies		21	resx								
323										22	resy								
324										23	resz								
325						3	il fue	l ass	embly	31	resx,	resy ,i	esz fo	or rod	array				
326						- 4	1 411	m res	Istance	41	resta								
327										42	resty	1							
328										43	resta	2							
329						5	il ext	erior	convection	51	resta	t for 1	top of	cask					
330							and	radia	ation	52	resta	t for l	notton	of cas	sk				
331																			
332	prop	nreg=	158	npal	ir= 3	32 🖷	nax i mu	m curi	rent dimens	ions	for nr	eg and	i npalı	r are	165	340			
333	prop	Index		ં લ	all le	ocatio	n					-							
334			Ibeg	lend	jbeg	jend	kbeg	kend	npair	Id	A T	ld	m†	10	at .	Id	R†	Id	#t
335			1	1	2	47	2	30	1	1	1								
336			2	24	2	47	1	1	1	52	42								
337			2	24	2	47	30	30	3	51	39	t	1	2	1				
338			2	24	2	47	4	27	1	4	3								

339				5	5	2	47	5	26	1	4	5		
340				2	24	21	21	5	26	i	, i	ŝ		
341				2	24	28	28	5	26					
342				2	1	21	21		26			2		
343				-		29	20	í	20	-	14		19	
344				-	- 2	20	20	2	20	4	12	0	15	6
146				, ,	2	~~~	21	2	20	2	14	6	16	6
343				2	2	20	20	5	26	1	42	32		
240				4	4	20	20	5	26	1	42	32		
347				2	2	28	28	5	26	1	42	32		
348				4	4	28	28	5	26	1	42	32		
349				5	5	22	22	5	26	1	41	32		
	•	•	•											
	•	٠	•											
	•	•	•											
487				13	21	30	30	5	26	1	42	4 1		
488				13	21	34	34	5	26	i	42	40		
489				12	12	15	18	í.	26		41	40		
490				12	12		7.4		20					
401				12	12	21	24	2	20		41	41		
+71				21	21	15	18	2	26	1	41	40		
49Z				21	21	31	34	5	26	T	41	40		
493														

After requesting echoing of input with NECHO = 1 on line 171 of the input file, the input states on line 172 that 158 region resistance assignment sets are forthcoming (NREG = 158) and that for these 158 regions there are 332(ID,MT) pairs directing action on specific resistance arrays and telling which intermediate parameter set MT to use. The default values of RESX, RESY, RESZ, RESFX, RESFY, and RESFZ is 0.0. Action is required only if nonzero values are required. The first such set (line 173) specifies that, on a region defined by $(1 \le I \le 1, 2 \le J \le 47, 2 \le K \le 30)$, one set (ID,MT) is to be imposed, namely (ID = 1, MT = 1). The value ID = 1 specifies that the array to be changed is the RESX array. See Table 5.3 and the summary at the start of the echoed input for ID value significances. The intermediate parameter set used, MT = 1, was constructed as directed by PROP Input Block 4 (line 116 of the input data example there), which, in turn, referenced the input material conductivity parameter set MAT = 1, which was input in PROP Input Block 3 (lines 96 and 97 of the input file example). From the fact that the thermal parameter set used was for low-conductivity material, we conclude that the user is setting the layer I = 1 to be effectively infinitely resistive, thus giving an insulated boundary condition or plane of symmetry there.

Line 174 of the input file example requests implementation of a cask bottom model with ID = 52, requesting that thermal parameter set of MT = 42 be used. Thermal parameter set MT = 42 was constructed from directives in PROP Input Block 5, line 165 of the input example.

Line 175 of the input file example requests implementation of two (ID,MT) resistance assignment pairs on its range (2 < I < 24, 2 < J < 47, 30 < K < 30), namely (ID,MT) = (1,1) and (ID,MT) = (2,1). Thus, both RESX and RESY are set to large values on this range.

The echoed input summarizes this information.

6.0 SUBROUTINE THERM

Subroutine THERM solves the energy equation on the rectangular grid.

6.1 THERM FUNCTIONS

THERM reads input specifying initial temperatures, heat sources, and numerical procedure options during initiation or restart of a simulation. If solution of the energy equation on the rectangular grid is requested, THERM is called at each time-step to advance the temperature solution.

The actions performed by THERM in the solution sequence include the following:

- THERM sets the connector arrays for the energy equation. These are the coefficients that relate temperature to heat flow rates, mass fluxes, and heat sources.
- 2. THERM executes an algorithm that advances the temperatures on the rectangular computational grid through a time-step.
- If requested, THERM prints monitoring information, including the location and amount of the largest temperature change in each timestep and the temperature in cells designated for temperature printout.
- THERM makes tentative adjustments in the time-step by comparing the maximum temperature change and a user-specified maximum target temperature change.

The algorithm used in THERM for advancing the temperature through a timestep is discussed in <u>Volume I - Equations and Numerics</u> (McCann 1987). To carry on this and its other functions in solving the energy equation on the rectangular grid, THERM is called at initialization or restart to read input to guide the solution and to set or reset temperatures.

Actions performed by THERM in the initialization or restart operation include:

1. THERM reads certain options for numerical procedures and printouts.

- 2. THERM reads specifications for heat sources.
- THERM reads specifications for initial temperatures on the rectangular grid region and the rectangular-cylindrical grid interface, including ambient temperatures at cask top and bottom.
- 4. THERM modifies or resets the temperature distribution according to user input, as may be desired in a restart.

6.1.1 Numerical Procedures

If a solution for both temperatures and flows is requested, calls from MAIN to the flow-solving routines are interspersed with the calls to the energy equation-solving routines (such as THERM and REBT for the rectangular grid, TSIDE for the cylindrical grid, and TBND or REBA for their connection). The algorithm in REBT solves the energy equation on slab partitions of the rectangular grid region, and its calling sequence is specified in input to THERM. The use of REBA, a solver of the energy equations on both grids, is specified in MAIN. The periodic use of REBT and REBA in the solution of the energy equations accelerates convergence, particularly as steady state is approached. See the guidance for the use of REBT in Chapter 7.0 and for REBA in Chapter 14.0.

6.1.2 Heat Sources

The technique for specifying heat sources has been designed especially for heat generating spent fuel assemblies. As a result, the input specifications are relatively simple. Three items of information are required: the toal heat generation rate of a fuel assembly; the locations of reduced heat generation within a fuel assembly, such as instrumentation tubes; and the relative axial activity of the fuel assembly. The longitudinal axis of each fuel assembly is in the z-direction.

The total heat being generated in a single column of cells, assumed to extend in the z-direction from K = 2 to K = KP-1, can be expressed as

$$Q^{C}(I,J) = Q^{g} \frac{W(I,J)DX(I)DY(J)}{\Sigma_{g} W(I,J)DX(I)DY(J)}$$
(6.1)

where $Q^{C}(I,J)$ is the total heat generation in a column I,J

Q^g is the total heat generation in the fuel assembly (group power) W(I,J) is a relative weighting factor for heat generation within the fuel assembly (group).

Different group powers and weighting factors may be specified for each fuel assembly. The weighting factor is automatically halved for phantom cells on the curved boundary.

The axial distribution of heat generation is determined from the relative activity curve for a spent fuel assembly. The heat generation sources used in the code are computed as

$$QGEN(I,J,K) = Q^{C}(I,J) \frac{RA(K)DZ(K)}{\Sigma_{k} RA(K)DZ(K)}$$
(6.2)

where QGEN(I,J,K) is the total heat generation in cell I,J,K RA(K) is the relative activity as a function of K.

The code assigns the same relative activity curve to all fuel assemblies. The relative activity data specified on the input file need not be normalized; the code does this automatically.

It can be seen from the preceding discussion that a completely arbitrary distribution of heat sources cannot be specified in this version of the code. The basic restriction is that heat generation sources be expressed in the form

$$Q(I,J,K) = FXY(I,J) * FZ(K)$$
(6.3)

6.1.3 <u>Setting or Resetting Temperatures</u>

Subroutine THERM can set the initial temperature on the rectangular grid and its interface with the cylindrical grid in a new simulation, or it can alter or reset them in a restart.

To set or reset the temperature distribution with input, the user supplies temperatures TS1(JS,K) on the cylindrical interface between rectangular and cylindrical grid regions, where JS is the azimuthal sector index and K is the

axial plane index. An array of temperatures, TCEN(K), on a user-specified axial "center line" in the rectangular grid is also read. An array, TCAN(K), of azimuthal average interface temperatures is calculated as

These arrays can be used to reset temperatures in three regions as indicated in Figure 6.1 according to options as follows:

1. NEWT = 1. Set an initial temperature distribution in the rectangular grid computational region (but not the phantom cells) according to

$$T(I,J,K) = TCEN(K) + (TCAN(K) - TCEN(K))*(FAC/FACMX)$$

where $FAC = (REAL(I) - 1.5)^{2} + (REAL(J) - CENJ)^{2}$

and FACMX is the largest value of FAC in the rectangular grid computational region.

 NEWTC = 1. Reset temperatures in the rectangular grid phantom cells at the cylindrical grid interface as

$$T(ICART(JS), JCART(JS), K) = TS1(JS, K)$$

for azimuthal indices JS in the range $2 \le JS \le JSP-1$ and axial indices K in the range $2 \le K \le KP-1$.

 NEWTA = 1. Reset cask end ambient temperatures in the rectangular grid region as

$$T(I,J,1) = TCAN(1)$$
$$T(I,J,KP) = TCAN(KP)$$

The azimuthal average value TCAN(1) of TS1(JS,1) becomes the cask bottom ambient temperature, and the average value TCAN(KP) of TS1(JS,KP) becomes the cask top ambient temperature.

These temperatures will be altered in the subsequent calculations with two exceptions:

 The cask end ambient temperatures T(I,J,1) and T(I,J,KP) will be held constant.



FIGURE 6.1. Regions Where Temperature is Set or Reset by Input to THERM

 If the calculation involves the rectangular grid only (as indicated by NOBODY = 1), the temperatures will be constant on the boundary cells of the rectangular grid.

6.2 PARAMETER STATEMENT INFORMATION

Dimensioning parameters required by THERM include IP, JP, KP, ISP, JSP, NEFAP. These were discussed in Chapter 4.0. Also needed by THERM are:

- KBP,KTP The number of K-planes at cask bottom and top, respectively, which are active computational cells for the energy equation but not for the flow equations. See Figure 4.8.
- MONTP Dimensioning parameter that must equal or exceed the number of computational cells for which temperature is to be monitored.

6.3 INPUT FORMAT

6.3.1 Overview

The input for THERM is discussed in four sections: 1) numerical procedure and printout options, 2) heat source specifications, 3) initial temperature specifications, and 4) temperature modifications or reset specifications.

6.3.2 Numerical Procedure and Printout Options

General Input Format

NECHO THETA, SPHTF, DTEMAX REBON, NREB, NREBN NECHO MONT IMONT(M), JMONT(M), KMONT(M) Lines for M=1 through MONT+1, (with IMONT(MONT+1)=0

General Input Description

 NECHO - Echoing switch for this section of input. If input is to be echoed, then NECHO = 1; otherwise, 0.

- THETA Temporal weighting for the energy equation. THETA should be chosen in the range 0.5 < THETA < 1.0. A value 0.5 has been proven satisfactory for steadystate applications.
- SPHTF The specified heat of fluid in joules/(gm°C).
- DTEMAX Target value of the maximum magnitude temperature change per time-step on the rectangular grid. A new tentative time-step DTIMEI is set as

DTIMEI = 1.1*DTIME if ABS(DTMAX)<DTEMAX or

DTIMEI = DTEMAX*DTIME/ABS(DTMAX) if ABS(DTMAX)>DTEMAX

where DTIME is the current time-step and DTMAX is the largest temperature increase on the grid in the current time-step.

- REBON, NREB, NREBN Criteria for the use of slab rebalance in Subroutine REBT during time-stepping. If STEADY = 1.0 and REBON = 1.0, then REBT is called for time-step NS when MOD(NS,NREB) = NREBN, where MOD is the FORTRAN modulo or remaindering function. Preferred values of NREB and NREBN are simulation-dependent. See Chapter 7.0, Subroutine REBT, for an expanded discussion.
- MONT Number of computational cells for which temperature monitoring is requested.
- IMONT(M), JMONT(M), KMONT(M) The (I,J,K) indices of the Mth cell for which temperature monitoring is requested.

Input File Example

332 1/therm 333 0.5,5.234,0.5 334 1.0,100,50 335 1/therm/monitor/t 336 12 337 2,24,7 338 2,24,11 339 2,24,15 340 2,24,16 341 2,24,18 342 2,24,22 343 2,41,7 344 2,41,11 345 2,41,15 346 2,41,16 347 2,41,18 348 2,41,22 349 0,0,0

Echoed Input File Example

494	therm	theta=0.5	sphtf	=0,5234e+	01 dt	emax=0.	500	ə+0()		
495	therm	rebon=1.0	nreb=	100 nre	bn= 50						
496											
497	therm	monitor ce	IIs=12	maximum	number	current	Hy	al	lowed	İs	12
498						m	i	J	k		
499						1	2	24	7		
500						2	2	24	11		
501						3	2	24	15		
502						4	2	24	16		
503						5	2	24	18		
504						6	2	24	22		
505						7	2	41	7		
506						8	2	41	11		
507						9	2	41	15		
508						10	2	41	16		
509						11	2	41	18		
510						12	2	41	22		
511											

Echoed input is requested with NECHO = 1 on line 332 of the input. THETA, SPHTF, and DTEMAX are set to 0.5, 5.234, and 0.5, respectively. One of the requirements for use of a coarse mesh rebalance of the energy equation, REBON = 1.0, is met. The input specifies rebalancing at time-steps NS = 50, 150, 250, etc. Monitoring of the temperature in the list of 12 cells is requested. Line 349 has a zero first entry, indicating the end of the list of cells for monitoring.

The echoed output confirms these numbers, and also compares the numbers MONT of cells requested for temperature printouts with the number currently allowed by dimensions.
6.3.3 <u>Heat Source Specifications</u>

General Input Format

```
NECHO
QWTFAC,IBEG,IEND,JBEG,JEND - Repeated until IBEG = 0 is encountered
NECHO
GRPPOW,IBEG,IEND,JBEG,JEND - Repeated until IBEG = 0 is encountered
NECHO
RELACT(K),K=2,KP-1
NECHO
PQGEN
```

General Input Description

• NECHO -	Echoing switch for this section of input. If input is to be echoed, then NECHO = 1; otherwise, 0 .
• QWTFAC –	The relative weighting factor per unit area for each heat source in the range JBEG < J < JEND IBEG < I < MIN(IEND,IMEND(J)) The range is thus restricted to the computational and phantom cells for the energy equation. QWTFAC is automatically reduced by one half if the cell is a phantom cell on the curved part of the Cartesian boun- dary. The default value of QWTFAC is zero.
IBEG,IEND,JBEG,JEND	<pre>- Range specifications of the form JBEG < J < JEND IBEG < I < MIN(IEND,IMEND(J))</pre>
● GRPPOW –	Total power in watts for the heat source in the region defined by the range specification on the same line and in the K direction by $2 \le K \le KP-1$. The default value of GRPPOW is zero.
• RELACT(K) -	The relative activity at each K-plane. Normalization is arbitrary.
• PQGEN -	Floating point flag variable that, if equal to 1.0, requests printout of the heat source array QGEN(I,J,K). No printing occurs if PQGEN = 0.0.

Input File Example

350 1/therm/q weighting factor 351 1.0,2,4,2,9 352 1.0,2,4,13,16 353 1.0,2,4,22,27 354 1.0,2,4,33,36 355 1.0,2,4,40,47 356 1.0,8,11,5,13 357 1.0,8,11,15,18 358 1.0,8,11,31,34 359 1.0,8,11,36,44 360 1.0,10,13,22,27 361 1.0,17,24,22,27 362 1.0.13,21,15,18 363 1.0,13,21,31,34 364 0.0,4*0 365 1/therm/group power 366 552.5,2,4,2,9 367 552.5,2,4,13,16 368 505.0,2,4,22,27 369 552.5,2,4,33,36 370 552.5,2,4,40,47 371 1783.0,8,11,5,13 372 993.0,8,11,15,18 373 993.0,8,11,31,34 374 1783.0,8,11,36,44 375 1105.0,10,13,22,27 376 1105.0,17,24,22,27 377 1783.0,13,21,15,18 378 1783.0,13,21,31,34 379 0.0,4*0 380 1/therm/relact 381 4*0.0,0.5,0.72,0.94,1.12,1.19,1.23,5*1.24, 382 1.23,1.21,1.16,1.03,0.83,0.61,0.44,0.26,6*0.0 383 1/therm/pggen 384 0.0

Echoed Input File Example

512	therm	q weighting		cell	locat	lon
513		factor	ibeg	lend	jbeg	jend
514		0.1000e+01	2	4	2	9
515		0.1000e+01	2	4	13	16
516		0.1000e+01	2	4	22	27
517		0.1000e+01	2	4	33	36
518		0.1000 0+ 01	2	4	40	47
519		0.1000e+01	8	11	5	13
520		0.1000e+01	8	11	15	18
521		0.1000e+01	8	11	- 31	34
522		0.1000e+01	8	11	36	44
523		0.1000 01 01	10	13	22	27

524				0.1000e+0	11	17	24	22	27	
525				0.1000e+0)1	13	21	15	18	
526				0.1000et()1	13	21	31	34	
527						12	- 1			
528	therm			acoup			cell	locat	Ion	
529				gi oup		i har	lond	iheg	iend	
530				0 55250+0	13	2	A	J009	J0/10	
531				0 55250+0	3	2	~	13	16	
532				0.50500+0	13	2	7	22	27	
533				0 55250+0	13	2		33	36	
534				0 55250+0		2	4	20	47	
535				0 1703-+0		2 0	11	40	47	
536)4) T	0	11	15	19	
537				0.0030+0	3	0		13	10	
530				0.1797-10		0	11	21	34	
530				0,1705810	J4	••	11	20	44 07	
229				0.11050+0	14	10	15	22	27	
540				0.11050+0	14	17	24	22	27	
541				0,1785e+0	14	15	21	12	18	
542				0.1783e+0)4	13	21	31	34	
543										
544	Therm		ĸ	relact(
545			2	0.0000e+0	0					
546			3	0.0000e+0	0					
547			4	0.000e+0	0					
548			5	0.0000e+0	0					
549			6	0 . 5000e+0	10					
550			7	0 . 7200e+0	0					
551			8	0 . 9400e+0	0					
552			9	0.1120e+0	1					
553			10	0.1190e+0	1					
554			11	0.1230e+0	1					
555			12	0 . 1240e+0	1					
556			13	0 . 1240e+0)1					
557			14	0 .1240e+ 0	1					
558			15	0.1240e+0	1					
559			16	0,1240e+0	1					
560			17	0,1230e+0	1					
561			18	0.1210e+0	1					
562			19	0,1160e+0	1					
563			20	0,1030e+0	1					
564			21	0.8300e+0	0					
565			22	0.6100e+0	0					
566			23	0.4400e+0	0					
567			24	0,2600e+0	0					
568			25	0,0000e+0	0					
569			26	0.0000e+0	0					
570			27	0.0000e+0	0					
571			28	0,0000e+0	0					
572			29	0.0000e+0	0					
573			30	0.0000e+0	0					
574										
575				total	generated	power	= 0.	28086	50e+05_ 1	watts
576							- 1			
577										
578	therm	0_0_omeopo								

The Q weighting factor is equal to 1.0 for 13 regions in the rectangular grid. These regions correspond to the fuel assembly regions in Figure 4.1. In this example, group powers for the entire axial extent of the 13 fuel assemblies of Figure 4.1 are set to values varying from 505 watts to 1783 watts. The relative activities at axial positions from K = 2 to K = KP-1 = 30 are set in the RELACT(K) array. Normalization of the input for RELACT(K) is arbitrary. In this example, non-negligible heat sources are from the axial positions K = 6 to K = 24.

The echoed input shows the Q weighting factors by region, the group powers by region, and the relative activity by position in the Z-direction. The total power shown is calculated for the entire cask (i.e., four quadrants), and not just the modeled region. Because PQGEN was set to zero, the final QGEN (I,J,K) heat source per cell was not printed.

6.3.4 Initial Temperatures on the Rectangular Grid

General Input Format

NECHO NEWT, CENJ TCEN(K), K=2, KP-1 NECHO NEWTC, INFO [TS1(JS,K),JS=2,JSP-1],K=1,KP

General Input Description

٠	NECHO	• Echoing switch for this section of input. If input is
		to be echoed, then NECHO = 1; otherwise, O.
•	NEWT	An integer variable that, if equal to 1, requests
		setting of temperatures on the rectangular grid based

- setting of temperatures on the rectangular grid based on input temperatures TS1(JS,K) on the cylindrical interface and TCEN(K) on the cask centerline. If NEWT = 0, then temperatures are not reset.
- CENJ A floating point number for the J index along which "cask center line" temperatures TCEN(K) are specified. The floating point number for the I index is at I = 1.5.

- TCEN(K) The initial temperature (°K) for each K-plane along the cask center line. No value for ambient (K = 1 or K = KP) is included.
- NEWTC An integer variable that, if equal to 1, requests setting a temperatures on the rectangular grid phantom cells at the cylindrical grid interface from the TS1 data. If NEWTC = 0, temperatures of the rectangular grid interface phantom cells are not reset.
- INFO An integer flag variable that, if equal to 1, requests printing of the interface temperatures. If INFO equals 0, then no printing occurs.
- TS1(JS,K) An input temperature array for the JS azimuthal sector at the Kth plane of the rectangular-cylindrical grid interface. Its uses are defined by flag variables: NEWT = 1 - Set T(I,J,K) for computational cells of the rectangular grid.
 - NEWTC = 1 Set T(ICART(JS),JCART(JS),K) for K = 2
 to KP-1, i.e., temperatures at rectangular
 grid phantom cells at the grid interface.
 - NEWTA = 1 Set cask end ambient temperatures T(I,J,1) and T(I,J,KP) from TCAN(1) and TCAN(KP), which are averages over JS of TS1(JS,1) and TS1(JS,KP), respectively. NEWTA is set in the input to MAIN.

If a run is started without using a restart tape, then all temperatures must be defined. If a restart tape is used, then only those temperatures that need to be changed are to be reset.

Input File Example

385 1/therm/tcen 386 0,24.5 387 380.0,385.0,395.0,410.0,430.0,470.0,505.0,545.0,575.0, 388 610.0,640.0,660.0,5*673.0,655.0,635.0,600.0,570.0, 389 535.0,510.0,475.0,445.0,415.0,395.0,385.0,380.0 390 1/therm/ts1 391 0,0 392 62*297.0,1798*373.0,62*297.0

Echoed Input File Example

580	therm	newt=0	cenj=24.5	k	tcən(k)				
581			_	2	0 . 380 0+03				
582				3	0 . 385e+03				
583				4	0,395e+03				
584				5	0.410 0+ 03				
585				6	0.430e+03				
586				7	0.470 0+ 03				
587				8	0,505 a+ 03				
588				9	0.545 0+ 03				
589				10	0.575e+03				
590				11	0.610e+03				
591				12	0.640 0+03				
592				13	0.660e+03				
593				14	0.673e+03				
594				15	0.673e+03				
595				16	0.6730+03				
596				17	0.673e+03				
597				18	0.673e+03				
598				19	0.655e+03				
599				20	0.6350+03				
600				21	0.600 0+03				
601				22	0,570e+03				
602				23	0.535e+03				
603				24	0,510a+03				
604				25	0.475e+03				
605				26	0.445e+03				
606				27	0.415e+03				
607				28	0.395e+03				
608				29	0,3850+03				
609				30	0.380e+03				
610									
611	therm	newtc=0	info=0		* * *	Initial	Interface	temperatur	es, *K * *

NECHO is set to 1 in input line 385. NEWT is set to zero on line 386, indicating that the temperatures on the rectangular grid are not to be reset. No reset will usually be the desired option on a restart. CENJ is set to 24.5 as the J value for the "cask center line". The pseudo-mesh location (I,J) =(1.5, 24.5) can be seen in Figure 4.1 to be the appropriate cask center line. The model for setting initial cask temperatures is approximate. The NEWTC and INFO entries (line 391) are both zero, indicating that new temperatures are not be set on the rectangular-cylindrical grid interface and that the grid interface temperatures are not to be printed. Nevertheless, 1922 entries (62+1798+62) are read for the TS1(JS,K) array for 2 < JS < JSP-1 and 1 < K < KP. For this simulation, JSP is 64 and KP is 31.

6.3.5 Temperature Modification Specifications

General Input Format

NECHO NDELTA IBEG,IEND,JBEG,JEND DELTA(K), K=2, KP-1

General Input Description

•	NECHO	-	Integer flag echoing of fo	variable that, if positive, requests orthcoming input in the output.
•	NDELTA	-	A flag whose NDELTA = 0 -	values indicate the following actions: Do not add user-prescribed temperature increments in the rectangular grid or grid interface region.
			NDELTA = 1 -	Add temperature increment DELTA(K) to temperature T(I,J,K) in the rectangular grid. The range is JBEG < J < JEND IBEG <i<min(iend,ieend(j)) 2 < K < KP-1</i<min(iend,ieend(j))
			NDELTA = 2 -	Add temperature increment DELTA(K) to rectangular-cylindrical grid interface cells according to T(ICART(JS),JCART(JS),K) = T(ICART(JS), JCART(JS),K) + DELTA(K) for 2 < K < KP-1 and 2 < JS < JSP-1.
			NDELTA = 3 -	Perform the actions described for both $NDELTA = 1$ and $NDELTA = 2$.
•	IBEG,IEND,JE	3EG	"JEND – A set range accordi JBEG(3) <j<j IBEG<i<min(< th=""><th>of mesh indices that describe an (I,J) ng to IEND IEEND(J),IEND</th></i<min(<></j<j 	of mesh indices that describe an (I,J) ng to IEND IEEND(J),IEND
•	DELTA(K)	-	Increment to plane for the	be added to all temperatures at the Kth (I,J) range.

393 1/therm/delta 394 0 395 2,18,2,34 396 29*0.0

Echoed Input File Example

613	therm	ndelta=0			
614	therm	Ibeg= 2	lend=18	.ibeq=	2 end=34
615		-		ĸ	delta(k)
616				2	0.000a+00
617				3	0.000a+00
618				4	0.000+00
619				5	0.000+00
620				6	0.000e+00
621				7	0.000 . 000
622				8	0.000+00
623				9	0.000e+00
624				10	0.000+00
625				11	0.000a+00
626				12	0.000e+00
627				13	0.000e+00
628				14	0.000e+00
629				15	0.000 . 00
630				16	0.000e+00
631				17	0,000e+00
632				18	0 . 000 . 00
633				19	0,000 s+ 00
634				20	0.000e+00
635				21	0.000e+00
636				22	0.000e+00
637				23	0 . 000a+00
638				24	0.000e+00
639				25	0.000e+00
640				26	0.000 0 +00
641				27	0.000a+00
642				28	0 .000e+00
643				29	0 . 000 . 00
644				30	0.000e+00

This input requests echoing (NECHO = 1) on line 393. Line 394 requests no adjustments of temperatures in the rectangular grid region (NDELTA = 0). The IBEG, IEND, JBEG, JEND, and DELTA(K) are read, nevertheless. The echoed input reflects these entries.

7.0 SUBROUTINE REBT

Subroutine REBT provides an optional numerical procedure intended to accelerate convergence of the solution of the energy equation toward steady state on the rectangular grid.

7.1 REBT FUNCTIONS

REBT solves the energy equation on a coarser mesh, specifically, on three slab partitions of the rectangular grid region. REBT is made available because the algorithm used in THERM reduces small long-range errors slowly as steady state is approached. Long-range errors are departures from the exact solution over distances much larger than the mesh spacing.

The prescription for calling REBT is provided by the user in the input to subroutine THERM. Additional minimal but rather important input for this convergence acceleration scheme is read by subroutine REBT during an initiation or restart. To use REBT judiciously, it is helpful to review some of the features of the solution for the physical system and of the energy equation in subroutine THERM.

HYDRA-II is set up to find steady-state conditions, using time-stepping to generate the approach to steady state. The finite-difference formulation in HYDRA-II discussed in Volume I (McCann 1987) presents the energy equation in a form relating temperature change $\delta T(I,J,K)$ in the (I,J,K) cell during time-step δt to the net energy flow into the (I,J,K) cell and energy sources there. Subroutine REBT, by contrast, solves a comparable energy equation on a coarser mesh for some time increment, $\delta t = XDTIME$, adding the temperature change δT found for a coarse region to the T(I,J,K) for all the (I,J,K) points within the region. REBT actually uses three coarse meshes, each a set of slabs. In the first coarse mesh, there is a slab for each I value. Each temperature increment $\delta T(I)$ found in this coarse mesh solution is added to all the T(I,J,K) for that I value. A similar procedure is followed in a coarse mesh with a slab for each K value.

Because the user is seeking only a steady-state solution for the coupled system of heat and mass flow, the time-step in REBT need not be the same as

that being used in THERM. Nor does it matter that the energy and flow equations are not advanced in near-synchronous fashion, so long as the steady-state solution is economically obtained. Although the algorithm in REBT allows arbitrarily large time-steps in the linearized energy equation, nonlinearities will limit the preferred time-step size. Nonlinearities arise because the radiation rates, the material properties, and the flow rates are dependent on the temperature. The choice of input to REBT (and the pattern of calling REBT set in THERM) should be based primarily on these considerations. The procedure within REBT is applicable only if a steady state is desired, as the user should indicate by setting STEADY = 1.0 in the input to Program MAIN.

The use of the coarser mesh solution in REBT will usually introduce shortrange error (departures from the true solution over distances of a few cell lengths) while reducing the long-wavelength error. The user should expect this in evaluating the effectiveness of REBT.

It is recommended that the user follow this procedure to use REBT effectively:

- Perform one or more HYDRA-II runs in which the solution for the composite system is allowed to proceed through enough time-steps that the temperature change per time-step becomes small before applying REBT. The velocities and material properties should have attained some measure of realism, but convergence will probably not have been reached, as indicated by heat balance information printed by QINFO. Create a restart file at this point.
- 2. Set the time-step $\delta t = XDTIME$ in REBT to some value in the approximate range 100 to 10^8 . Select a trial number NMAX of times to execute the three directions of slab solutions in REBT at each call, say NMAX~15. Run a restart case through a time-step in which REBT is called. The pattern of calls to REBT is set in THERM by input variables NREB and NREBN. INFO should be set to 1 or 2 in REBT for this restart, to get printout of the maximum divergence error total for a slab (labeled DIMAX, DJMAX, or DKMAX) following the I-, J-, or K-slab coarse solutions. Plot one or more of DIMAX, DJMAX, or DKMAX as a function of iteration number in REBT. Choose a value of NMAX for

subsequent use at a point of diminishing effectiveness in reducing this divergence error. A schematic plot of DKMAX versus iteration number in REBT is shown in Figure 7.1, showing diminishing effectiveness.

3. With number NMAX of iterations in REBT fixed, run a number of restarts (from the same restart file) in which REBT is called with various values of time-step $\delta t = XDTIME$, say 100, 10^4 , and 10^6 or some comparable set. Follow the REBT call for these restarts by some number (on the order of 50 to 100) of time-steps with the energy equation solved on the rectangular grid by the algorithm in THERM. For economy, turn the momentum solution off with NOVEL = 1 in MAIN. Set NSINFO to 1 in the input to MAIN to obtain printouts of δT from THERM at every time-step for this test.



FIGURE 7.1. Qualitative Plot of Maximum Divergence Error in a K-Layer Versus Number of Iterations in REBT

- 4. Tentatively identify the preferred value of XDTIME as the one from Step 3 that offers the best improvement in energy balance as printed by QINFO. The energy balance information is printed at the end of a run, so the values from Step 3 to compare will be those after the prescribed number of time-steps (using the algorithm in THERM to solve the energy equation on the rectangular grid) after use of REBT.
- 5. Choose the number of time-steps in THERM for subsequent use between calls to REBT as follows. Plot $|\delta T|_{max}$ values versus time-step number printed by THERM in the run from Step 3 with the best XDTIME value. Include some of the final δT values from step 1 on the plot. The plot should resemble the qualitative one in Figure 7.2. Pick the number of time-steps between calls to REBT as the number of time-steps between calls to REBT as the number of time-of time-of time-steps after the REBT call at which the $|\delta T|_{max}$ values have leveled out.



Time Step Number

FIGURE 7.2. Schematic Behavior of Maximum Temperature Change [ST] Per Time-Step Before and After REBT Call

6. If desired, confirm the choice of XDTIME in step 4 by constructing plots of $|\delta T|_{max}$ versus time-step number for other XDTIME values. The qualitative features to expect are shown in Figure 7.3.

The NMAX and XDTIME values and the frequency of calls to REBT selected by the foregoing procedure should tentatively be chosen for further converging the simulation toward steady state, and the diagnostic printouts can be switched off. For difficult cases, the user may need to re-examine choices later.

The user should remember that the effect of REBT is only on the rate of convergence, not on the final solution given by the model. On simulations characterized by rapid convergence, there may be no need to use REBT at all.

7.2 PARAMETER STATEMENT INFORMATION

Subroutine REBT requires specification of the following parameters to the same values and with the same significance as described in Chapter 4.0 for Sub-routine GRID:



Time Step Number

FIGURE 7.3. Schematic Behavior of Maximum Temperature Change |&T| Per Time-Step for Varying XDTIME Values in a REBT Call

• IP, JP, KP, NEFAP

The following parameters required by REBT were discussed in Chapter 4.0, Subroutine GRID, and defined in Chapter 6.0, Subroutine THERM:

• KBP,KTP

7.3 INPUT FORMAT

7.3.1 Overview

The input to REBT is minimal, but good choices for the key variables XDTIME and NMAX should be based on previous experience or on systematic studies described in Section 7.1. If REBT is to be used, set STEADY = 1.0 in MAIN and REBON = 1.0 in THERM. The pattern of calls to the REBT procedure is set by variables NREB and NREBN in THERM.

7.3.2 REBT Options Input Block

General Input Format

```
NECHO
XDTIME,NMAX,INFO
```

General Input Description

9	NECHO	 Echoing switch for this section of input. If input is to be echoed, then NECHO = 1; otherwise, 0.
•	XDTIME	 The time-step to be used in the solution of the energy equation on the three slab partitions of the rectangular grid region.
•	NMAX	 The number of three-direction sweeps used in solving the slab representation of the energy equation on the rec- tangular grid on a call to REBT.
•	INFO	 Input variable to control the level of printout at each of the NMAX iterations in a call to REBT. INFO = 0 No divergence error printout
		INFO = 1 Print the maximum sum of divergence errors encountered for a slab in each of

the slab orientations and the index of the slab. Print after all three slab solutions are done. Labels will be (DIMAX,ID), (DJMAX,JD) and (DKMAX,KD) for the three slab orientations. INFO = 2 Print the maximum sum of divergence errors for any slab after the temperature adjustment based on the slab solution has been made, and the slab location at which it occurred. Print immediately after each slab solution is done.

Input File Example

397 1/rebt 398 1.0e+5,12,1

Echoed Input File Example

645 646 rebt xdtime=0.100e+06 nmax=12 info=1

In this example, echo of input is requested on line 397 of the input file with NECHO = 1. A time-step XDTIME = 1.0E+5 is set on input line 398, and NMAX = 12 slab iterations is requested. Printout at one time of maximum divergence error encountered and its location during the three slab solutions is requested with INFO = 1. The output echoes these values.

8.0 SUBROUTINE PROPS

Subroutine PROPS sets heat transfer properties for the simulation in the cylindrical grid region, much as Subroutine PROP does for the rectangular grid.

8.1 PROPS FUNCTIONS

The effects of heat transfer models used by PROPS are imposed exclusively through the three thermal resistivity arrays RESX, RESY, and RESZ, and the three film resistance arrays RESFX, RESFY, and RESFZ. These X-, Y-, and Z-labeled arrays now apply to the r, θ , and z directions and have meanings for the cylindrical grid as follows:

- RESX R-direction resistivity
- RESY θ-direction resistivity
- RESZ Z-direction resistivity
- RESFX R-direction film resistance
- RESFY θ -direction film resistance
- RESFZ Z-direction film resistance.

Subroutine PROPS reads input and sets up intermediate parameter sets related to heat transfer models for the cylindrical grid. It reads mesh location information assigning resistance array values on the cylindrical grid according to these models. The actual assignment of values to resistance arrays is done during each time-step using the latest temperatures for temperature-dependent properties.

The heat transfer models available in PROPS include 1) simple isotropic or orthotropic conduction in substances, 2) conduction through layered composites offering parallel paths, 3) conduction through layered composites offering series paths, 4) normal conduction through single or series films between cells, and 5) parallel heat transfer by radiation and by forced or natural convection from cask ends and sides. The model for conduction through a film at a cell interface can include a contribution equivalent to radiation across a gap. For an understanding of the models, see Chapter 5.0. The changes in the definitions and relationships from those of Chapter 5.0 for the conversion to cylindrical coordinates need not generally concern the user in supplying input. Consistent interfacing of the cylindrical and rectangular grid regions requires that the radial resistivity in the first radial phantom cell, RESX(IS = 1,JS,K), be set to a large number.

The user should also know that any resistivity or film resistance component not defined for a mesh location will have the default value of zero.

8.2 PARAMETER STATEMENT INFORMATION

The following dimension-setting parameters have the same significance and should have the same value as in Subroutine GRID (Chapter 4.0):

IP, JP, KP, ISP, JSP

The following dimension-setting parameters play an analogous role to parameters of the same name used in PROP for the rectangular grid, but their numerical values should be set in PROPS according to the need there:

- NMATP An array-dimensioning parameter greater than or equal to the number of substance conductivity polynomial coefficient sets read in PROPS Input Block 3.
- MTP An array-dimensioning parameter greater than or equal to the largest value of MT for the intermediate variable sets (in arrays CO, C1, C3, TWF, CFUEL, CCLAD, etc.) for heat transfer models constructed from directives in PROPS Input Blocks 4 and 5.
- NSPECP Dimension of the array SPECS used in PROPS Input Blocks 4 and 5 to read end-to-end all the intermediate heat transfer model specifications in each of the blocks. The SPECS array is overwritten by each of those input blocks in turn, so it must be long enough to accommodate the longer of them.
- NREGP,NPAIRP Two parameters used in setting length of the INDEX array (to INDEXP = 7*NREGP+2*NPAIRP) containing directives for assigning resistivity and film resistance

values to cell locations in the cylindrical grid. NREGP is the maximum allowed number of region (range) specifications. NPAIRP is the sum over all regions of the number of (ID,MT) pairs, where ID is an identifier of the resistance parameter affected and the model used, and MT is an identifier of the intermediate heat transfer variable to use for that model. Each region directive set may request implementation of one or several changes in the resistance arrays by including one or several (ID,MT) pairs.

8.3 INPUT FORMAT

8.3.1 Overview

The input to Subroutine PROPS separates into six blocks:

- 1. thermal resistance print specifications for the cylindrical grid
- convection specifications for cask side and for cylindrical grid parts of top and bottom
- 3. materials conductivity polynomial coefficient sets
- 4. parallel, isotropic, and orthotropic conduction models
- 5. series conduction models
- 6. assignment of resistance to cell locations.

The material conductivity polynomial coefficients read in Input Block 3 are overwritten after their use in setting up intermediate parameter sets in Input Blocks 4 and 5. The intermediate parameter sets constructed in response to Input Blocks 4 and 5 are retained as local variables for use in assigning resistances to cell locations at each time-step with most recent temperatures, as directed in PROPS Input Block 6.

8.3.2 Thermal Resistance Print Specifications. PROPS Input Block 1

General Input Format

NECHO

NSX,NSFX,NSY,NSFY,NSZ,NSFZ,INFO

General Input Description

- NECHO Echoing switch for this section of input. If input is to be echoed, then NECHO = 1; otherwise, 0.
- NSX,NSFX,NSY,NSFY,NSZ,NSFZ The number of the time-step at which to print respectively the RESX, RESFX, RESY,

RESFY, RESZ, and RESFZ arrays.

 INFO - Integer flag variable that, if equal to 1, requests printing of each resistivity or film resistance array at its designated (by NSX, NSFX, etc.) time-step. No printing occurs if INFO = 0.

Input File Example

```
399 1/props
400 -1,-1,-1,-1,-1,-1,0
```

Echoed Input File Example

647 648 props nsx= -1 nsfx= -1 nsv= -1 nsfv= -1 nsz= -1 nsfz=-1

Echoing of input is requested with NECHO = 1, but printout of the six resistance arrays on the cylindrical grid is doubly suppressed, with INFO = 0 and with NSX = -1, NSFX = -1, etc. The user should set INFO = 1 and the resistance array printout flags to a non-negative time-step number in some early execution to obtain a printout of the resistance arrays to verify the . correctness of the input.

Info=0

8.3.3 <u>Convection Specifications for Cask Side and Cylindrical Grid End</u> <u>Regions. PROPS Input Block 2</u>

General Input Format

TOPH, TOPL, TOPV, TOPC, TOPN BOTH, BOTL, BOTV, BOTC, BOTN SIDEH, SIDEL, SIDEV, SIDEC, SIDEN

General Input Description

- TOPH,BOTH,SIDEH Floating point flag variables that, if equal to
 1.0, indicate a convection model is forthcoming for
 cask top, bottom, or side, respectively. The five
 entries on a line must be supplied, even if the flag
 variable is 0.
- TOPL,TOPV,TOPC,TOPN Length L, velocity V, multiplier C, and exponent n in the forced or natural convection models for the cylindrical grid region of the cask top. The convection models were described in Chapter 5.0 for the rectangular grid. TOPV > 0.0 requests a forced convection model, while TOPV = 0.0 requests a natural convection model.
- BOTL,BOTV,BOTC,BOTN Length L, velocity V, multiplier C, and exponent n for the cask bottom convection model, analogous to TOPL, TOPV, TOPC, and TOPN.
- SIDEL,SIDEV,SIDEC,SIDEN Length L, velocity V, multiplier C, and exponent n for the cask side convection model.

Input File Example

401 1.0,220.0,0.0,0.14,0.333 402 1.0,220.0,0.0,0.27,0.25 403 1.0,3.5,0.0,0.45,0.25

Echoed Input File Example

649						
650	props	toph=1.0	top1=0,220e+03	topv=0.000e+00	topc=0.140e+00	topn=0.333e+00
651	props	both=1.0	bot1=0,220e+03	botv=0,000e+00	botc=0,270e+00	botn=0.250e+00
652	props	sideh=1.0	side1=0.350e+01	sidev=0.000e+00	sidec=0.450e+	00 siden=0.250e+00

Flags that convection models are forthcoming are set by the first entries on three lines of input: TOPH = 1.0 on line 401, BOTH = 1.0 on line 402, and SIDEH = 1.0 on line 403. Natural convection models are requested in this input with TOPV = 0.0, BOTV = 0.0, SIDEV = 0.0. The multiplier C and the power n for the natural convection are set for each of the three models to values from the convection heat transfer literature. The values for the side correlation are appropriate to a fin model.

8.3.4 <u>Materials Conductivity Polynomial Coefficient Sets. PROPS Input</u> Block 3

General Input Format

CCONO(NMAT),CCON1(NMAT),CCON3(NMAT)

General Input Description

These quantities are exactly as defined in Input Block 3 of PROP (Chapter 5.0) for use on the rectangular grid, but they form a separate and independent set of information for use by PROPS on the cylindrical grid.

Input File Example

```
404 1/props/ccon0,ccon1,ccon3
405 8
406 low conductivity
407 0.1e-20,0.0,0.0
408 high conductivity
409 0.1e+20,0.0,0.0
410 helium
411 0.52e-3,0.32e-5,0.0
412 sst
413 0.09215,0.1465e-3,0.0
414 nodular cast iron
415 0.5162,-0.3205e-3,0.0
416 air
417 0.688e-4,0.634e-6,0.0
```

```
418 epoxy (not used)
419 0.15e-2,0.0,0.0
420 nitrogen (not used)
421 0.075e-3,0.6167e-6,0.0
```

Echoed Input File Example

654	props	nmat= 8 maximum current dimension for nmat is 20
655	props	ccon0,ccon1,ccon3 material thermal conductivity, W/cm-k
656		k(mat) = ccon0(mat) + ccon1(mat) + t + ccon3(mat) + + + + + + + + + + + + + + + + + + +
657		1 (0,1000e-20)+(0,0000e+00)#t+(0,0000e+00)#t*t*t low conductivity
658		2 (0,1000e+20)+{0,0000e+00}*++{0,0000e+00}*+#t*t high conductivity
659		3 {0_5200e-03}+{0_3200e-05}*t+{0_0000e+00}*t*t hellum
660		4 (0,9215e-01)+(0,1465e-03)*++(0,0000e+00)*+*+* sst
661		5 (0,5162e+00)+(-,3205e-03)*++(0,0000e+00)*+*+*+ nodular cast iron
662		6 (0,6880e-04)+(0,6340e-06)*++(0,0000e+00)*+*+*+ air
663		7 (0,1500e-02)+(0,0000e+00)*++(0,0000e+00)*+*+*+ epoxy (not used)
664		8 (0,7500e-04)+(0,6167e-06)#t+(0,0000e+00)#t#t#t nitrogen (not used)

Line 404 of the input file example sets NECHO to 1 to request echoing input, provides comments indicating that the forthcoming block is for Subroutine PROPS and the sets of conductivity polynomial coefficient arrays CCONO, CCON1, and CCON3. Line 405 of the input indicates that 8 (NMAT) properties sets are forthcoming. The subsequent line gives 40 characters of material labeling information, followed by a line with the three polynomial coefficients for the thermal conductivity of that material. Not all thermal conductivity property sets need be subsequently referenced. The fictitious high conductivity and low conductivity sets may be useful in setting fixed temperature or insulated surface boundary conditions, respectively. The polynomial assumes temperatures in degrees Kelvin.

The echoed input gives NMAT and the maximum value of NMAT currently allowed by dimensions (NMATP), followed by information on the conductivity polynomials and their labeling text in an informative form.

8.3.5 <u>Parallel, Isotropic, and Orthotropic Conduction Models.</u> PROPS Input Block 4

General Input Format

NECHO MTMAX SPECS(I),I=1,NSPECP The entire dimensioned array SPECS is read. The user should construct it with MTMAX sets of entries, the sets being read end-to-end. Each set directs construction of an intermediate parameter set of index MT for subsequent referencing (in PROPS Input Block 6) in setting resistivities and film resistances on the cylindrical mesh. The form for a set for simple isotropic or orthotropic conduction or for parallel conduction is:

MT, MATS, MAT1, WIDTH1, MAT2, WIDTH2...MATMATS, WIDTHMATS,

Unused entries in the SPECS array should be filled with zeros in the input.

General Input Description

These quantities are exactly as defined in Input Block 4 of PROP (Chapter 5.0) for use on the rectangular grid, but they form an independent set of information for use by PROPS on the cylindrical grid. Each intermediate parameter set constructed here has labeling index MT and includes three coefficients for a polynomial in Kelvin temperature for conductivity λ or a sum $\Sigma_i \lambda_i \delta W_i$.

Input File Example

422 1/props/specs def. 01 isotropic and 11 parallel 423 9 424 1.0,1.0,1.0,1.0, 425 2.0,1.0,2.0,1.0, 426 3.0,1.0,3.0,1.0, 427 4.0,1.0,4.0,1.0, 428 5.0,1.0,5.0,1.0, 429 6.0,1.0,6.0,1.0, 430 7.0,1.0,5.0,0.2259, 431 8.0,1.0,5.0,0.310, 432 9.0,1.0,5.0,0.5172, 433 64*0.0

Echoed Input File Example

665				
666				maximum number of material types is currently 30
667				maximum array dimension of specs is currently 100
668				
669				***composite definition O1 isotropic and 11 parallel***
670	props	mtmax=	9	
671	props	specs		mt mats mat width
672		•		1 1 1 0,1000e+01
673				2 1 2 0.1000e+01
674				3 1 3 0 . 1000e+01
675				4 1 4 0,1000e+01
676				5 1 5 0,1000e+01
677				6 1 6 0 . 1000 01 01
678				7 1 5 0,2259e+00
679				8 1 5 0 , 3100e+00
680				9 1 5 0 .5172e+0 0
681				
682				computed coefficients from specs array
683				mt c0 c1 c3
684				1 0,1000e-20 0,0000e+00 0,0000e+00
685				2 0,1000e+20 0,0000e+00 0,0000e+00
686				3 0,5200e-03 0,3200e-05 0,0000e+00
687				4 0,9215e-01 0,1465e-03 0,0000e+00
688				5 0.5162e+00 -0.3205e-03 0.0000e+00
689				6 0.6880e-04 0.6340e-06 0.0000e+00
690				7 0.1166e+00 -0.7240e-04 0.0000e+00
691				8 0,1600e+00 -0,9936e-04 0,0000e+00
692				9 0,2670e+00 -0,1658e~03 0,0000e+00

Line 422 of the input file example requests echoing of input with NECHO = 1, then gives user comments indicating that the data is for Subroutine PROPS and directs construction of intermediate parameter sets for the simple conduction group 01 (ID = 01,02,03, or 04) or for the parallel conduction composite group 11 (ID = 11,12,13,14,15, or 16). Line 423 of the input says MTMAX = 9 directive sets for construction of intermediate parameter sets of the isotropic, orthotropic, or parallel conduction type are forthcoming. Lines 424 through 432 give the directive sets, each of which leads to the construction of polynomial coefficients for quantities of the form

 $\Sigma \lambda_i \delta W_i$ or $\Sigma_{MAT} \lambda(MAT) * WIDTH(MAT)$

as described in Chapter 5.0. In the nine sets shown here, the number MATS of terms included in the sum is one for each case. The index MAT refers to sets of conductivity polynomial coefficients supplied in PROPS Input Block 3. Line 433 of the input fills out the unused entries in the SPECS array, which was dimensioned in this case to NSPECP = 100.

The echoed input first prints out a reminder that the largest value of MT is MTP, and that the length of the SPECS array for holding the directives for their construction is NSPECP. The sets of directives are themselves then printed, followed by the constructed polynomial coefficients CO(MT), C1(MT), and C3(MT) of degree 0, 1, and 3 in Kelvin temperature in response to those directive sets.

8.3.6 Series Conduction Models. PROPS Input Block 5

General Input Format

NECHO MTMAX SPECS(I),I=1,NSPECP

The entire dimensioned SPECS array is read. The user should construct it with MTMAX sets of entries, with the sets being read end-to-end. The entries are in floating point form, with some of them converted to integers. The input form for a series conduction set is:

MT,MAT,WIDTH,E1,E2,TWF(MT)

General Input Description

The definition and purpose of these input variables are the same as for the rectangular mesh. See Chapter 5.0, PROP Input Block 5.

Input File Example

434 1/props/specs def. 21 series 435 10 436 20.0,3.0,0.1,0.2,0.25,0.5, 437 21.0,3.0,0.15,0.2,0.25,0.5, 438 22.0,3.0,0.3,0.2,0.2,0.5, 439 23.0,3.0,5.0,0.2,0.2,0.5, 440 24.0,1.0,1.0,0.2,1.0,0.5, 441 25.0,6.0,0.1,0.2,0.25,0.5, 442 26.0,1.0,1.0,0.3,1.0,0.5, 443 27.0,1.0,1.0,0.96,1.0,0.5, 444 28.0,1.0,1.0,0.8,1.0,0.5, 445 29.0,3.0,0.001,0.2,0.25,0.5, 446 40*0.0

Echoed Input File Example

603

							21 contoc##	
694					***composite	Gerinition	21 Sectos	
695	props	mtma×≃ 10	_		• • • •		-2	+
696	props	specs	mt	mat	WIGTH	61	62	1#1
697			20	3	0 . 1000e+00	0,2000e+00	0,2500e+00	0.50008+00
698			21	3	0.1500e+00	0 . 2000e+00	0.2500e+00	0,50000+00
699			22	3	0.3000e+00	0.2000e+00	0.2000e+00	0,5000e+00
700			23	3	0.5000e+01	0.2000e+00	0.2000e+00	0 . 5000e+00
701			24	1	0.1000e+01	0,2000e+00	0.1000e+01	0 . 5000a+00
702			25	6	0.1000e+00	0.2000e+00	0.2500e+00	0.5000e+00
703			26	1	0_1000e+01	0.3000e+00	0.1000e+01	0,5000e+00
704			27	1	0.1000e+01	0,9600e+00	0.1000e+01	0,5000e+00
704			28	1	0.1000e+01	0.8000e+00	0.1000e+01	0.5000e+00
705			29	3	0,10000-02	0.2000e+00	0.2500e+00	0.50000+00
700				-	•••••	•		
707				c	amputed coef	ficients fr	om specs arr	ay
700				m	nt c0	c1	c3	
709				2	0 0.5200e-0	2 0.3200e-	04 0_2835e-	-11
710				2	1 0 3467e-0	2 0.21330-	04 0.2835e-	-11
/11				2	2 0 1733 = 0	2 0.1067	04 0.2520e-	-11
712				2	3 0 1040-0	3 0 64000-	06 0.25208-	-11
715				2			00 0.4536e-	-11
714				2			05 0 28356-	.11
715				2			00 0 68040	-11
716				2				-10
717				2				-10
718				2	8 0.1000e-2		00 0.10148'	-10
719				2	9 0.5200e+0	0 0,5200e-	UZ U.28339	•11
720								

The MTMAX = 10 forthcoming sets of series type intermediate parameter set construction directives indicated on input example line 435 appear on lines 436 through 445. The remaining 40 entries of the NSPECP = 100 locations in SPECS are filled with zeros on line 446 of the input example. Line 436 directs construction of intermediate parameter set MT = 20 using the coefficient set MAT = 3, which was supplied on lines 410 and 411 of the input file example of PROPS Input Block 3. The thickness δL = WIDTH in the heat flow direction for the series layer is specified as 0.1 cm by the third entry on line 436. A radiation model for construction of C3(20) is requested by the next two entries of line 436 by the emittance values E1 = 0.2, E2 = 0.25. If the set MT = 20 is

used for a film resistance rather than as part of series layers for resistivity within a cell, the temperatures in the cells on the two sides of the interface will be equally weighted in forming a boundary temperature T_B at which to evaluate the polynomial for $\lambda/\delta L$, because TWF(20) is set to 0.5.

The other nine sets direct construction of additional $\lambda/\delta L$ polynomial (in Kelvin temperature) coefficient sets.

The echoed input repeats these specification sets and displays the polynomial coefficients actually constructed.

8.3.7 Assignment of Resistance to Cell Locations. PROPS Input Block 6

General Input Format

NECHO NREG,NPAIR INDEX(I),I=1,INDEXP

The entire array INDEX is read. The NREG sets of region resistance assignment directives stored end-to-end in index have the form:

IBEG, IEND, JBEG, JEND, KBEG, KEND, NPAIR, ID, MT, ID, MT, ID, MT, ... ID, NPAIR, MT, NPAIR

The resistance assignments here on the cylindrical grid are analogous to those in PROP Input Block 7 for the rectangular grid, but the ranges apply to indices IS, JS, and K in the cylindrical grid, and the (ID,MT) pairs are those constructed in PROPS for the cylindrical grid rather than those constructed in PROP for the rectangular grid.

General Input Description

The definitions of the variables for assignment of resistances in the cylindrical grid are analogous to those in Subroutine PROP Input Block 7 for the rectangular grid (Chapter 5.0). Items to remember are:

```
    IBEG,IEND,JBEG,JEND,KBEG,KEND - Region limits for radial, azimuthal,
and axial cell indices are, respectively,
IBEG < IS < IEND
JBEG < JS < JEND
KBEG < K < KEND</li>
```

- ID,MT A pair of directives for modifying the thermal resistance arrays (refer to Chapter 5.0, PROP Input Block 7). The indices MT here refer to intermediate parameter sets set in PROPS, and the RESX, RESY, and RESZ (and corresponding RESFX, RESFY, and RESFZ) arrays refer to conduction in the R, θ, and Z directions. Table 5.3 still defines the actions requested for defined ID values, but one new value is added:

Input File Example

```
447 1/props/index
448 21,30
449 1,1,2,63,2,30,1,1,1,
450 2,7,1,1,2,30,1,2,1,
451 2,7,64,64,2,30,1,2,1,
452 2,7,2,63,1,1,1,52,28,
453 2,2,2,63,2,3,1,4,5,
454 2,2,2,63,4,5,1,4,3,
455 2,2,2,63,6,24,2,4,4,41,29,
456 2,2,2,63,25,27,1,4,3,
457 2,2,2,63,28,28,2,4,4,41,20,
458 2,3,2,63,29,29,1,4,4,
459 4,7,2,63,27,29,1,4,5,
460 4,4,2,63,29,29,3,4,4,41,21,43,23,
461 3,3,2,63,2,28,1,4,5,
462 4,5,2,63,2,26,3,1,7,2,8,3,9,
463 6,7,2,63,2,26,1,4,5,
464 2,5,2,63,30,30,3,1,1,2,1,51,24,
465 5,5,2,63,30,30,1,41,25,
466 6,7,2,63,30,30,2,4,5,51,26,
467 7,7,2,63,2,5,1,53,26,
468 7,7,2,63,6,27,1,53,27,
469 7,7,2,63,28,30,1,53,26,
470 48*0
```

Echoe	ed Inj	out_	File	Ex	amp 1	le												
							**aval	lable comp	osite	defi	nition	s###						
						gro	up		id									
					1	01 İsc	tropic	8	1	resx								
									2	resy								
									3	resz								
									4	resx	,resy,	resz						
						11 par	allel		11	resx	,×-y p	lane						
									12	resx	,x-z p	lane						
									13	resy	,×−y p	lane						
									14	resy,	,y−z p	lane						
									15	resz,	,×-z p	lane						
									16	resz,	,y−z p	lane						
						ZI ser	ies		21	resx								
									22	rasy								
									25	resz								
					•	•• ••	m resi	stance	41	rest)	K.							
									42	resty								
						51 ave	ecion	convection				+4	anak					
						hoe	cadia		52	F0314		hottom	Cask	.				
						9110	10010		53	ract	c for	side o	f cack	3K				
										10317		3108 0	i cask					
props	nred≈	21	npai	r= .	30 r	na xi mu	m curr	ent dimens	lons	for n	neo an	d noal	r are	25	40			
props	Index		Ċ		ocatio	n												
		i beg	lend	jbeg	jend	kbag	kend	npair	id	πt	10	mt	id	πt	id	πt	Id	mt
		1	1	2	63	2	30	1	1	1								
		2	7	1	1	2	30	1	2	1								
		2	7	64	64	2	30	1	2	1								
		2	7	2	63	1	1	1	52	28								
		2	2	2	63	2	3	1	4	5								
		2	2	2	63	4	5	1	4	3								
		2	2	2	63	6	24	2	4	- 4	41	29						
		2	2	2	63	25	27	1	- 4	3								
		2	2	2	63	28	28	2	4	4	41	20						
		2	3	2	63	29	29	1	4	4								
		4	7	2	63	27	29	1	4	5								
		4	4	2	63	29	29	3	4	4	41	21	43	23				
		3	3	2	63	2	28	1	4	5								
		4	5	2	63	2	26	3	1	7	2	8	- 3	9				
		6	7	2	63	2	26	1	4	5								
		2	5	2	63	30	30	3	1	1	2	1	51	24				
		5	5	2	63	30	30	1	41	25								
		6	7	2	63	30	30	2	4	5	51	26						
		7	7	2	63	2	5	1	53	26								
		7	7	2	63	6	27	1	53	27								
		7	7	2	61	20	30	•	81	26								

The input file example asks for echoing of input on line 447 with NECHO = 1, then specifies 21 resistance assignment directive sets holding 30 (ID,MT) pairs on line 448. Lines 449 through 469 contain these resistance assignment directive sets.

Line 449 of the input file example sets radial resistivities (as indicated by ID = 1) to a large number (as indicated by MT = 1) on the inner radial cells (as indicated by the range 1 < IS < 1, 2 < JS < 63, 2 < K < 30). That MT = 1will get high resistivity can be seen by noting that the intermediate parameter set MT = 1 was constructed in PROPS Input Block 4, where the directive set on input file example line 424 referenced the input conductivity coefficient set

MAT = 1, which was for low conductivity. The set MAT = 1 was input on lines 406 and 407 of the input file example for PROPS Input Block 3. A high radial resistivity for IS = 1 is needed for proper communication between rectangular and cylindrical grid regions. The ID values are defined in Table 5.3.

Line 460 of the input file example specifies a region for its resistance array changes as (4 < IS < 4, 2 < JS < 63, 29 < K < 29). It requests implementation of resistance arrays changes there with three (ID,MT) pairs:

- (4,4) Replace RESX, RESY, and RESZ in that region with values derived from intermediate parameter set 4.
- (41,21) Add to radial film resistance RESFX the reciprocal of the $\lambda/\delta L$ determined from intermediate parameter set 21, which was set in PROPS Input Block 5. Parameter set MT = 21 specified a helium material with a gap radiation transfer model for setting C3.
- (43,23) Add to axial film resistance RESFZ the reciprocal of the $\lambda/\delta L$ calculated from the intermediate parameter set MT = 23 set in PROPS Input Block 5 input file example line 439. The set MT = 23 described a 5-cm-wide helium filled gap with wall emittances 0.2 on both sides, with equal weighting of temperatures on either side requested [by TWF(23) = 0.5] in calculating a film temperature for properties evaluation.

The other resistance-assignment directive sets similarly implement one or more (ID,MT) pairs in filling out the resistance arrays. Unused locations in INDEX are set to zero values on line 470 of the input example. INDEX has INDEXP = 7*NREGP+2*NPAIRP dimensioned locations.

The echoed input first gives a summary table of the ID values and their requested actions. It then repeats the number NREG of region specifications forthcoming and the number NPAIR of (ID,MT) resistance-setting pairs they contain, and gives for user convenience the current dimension limits NREGP and NPAIRP for NREG and NPAIR, respectively. The echoed input gives a table of resistance assignment directives.

9.0 SUBROUTINE TSIDE

Subroutine TSIDE is used to solve the energy equation on the cylindrical grid region.

9.1 TSIDE FUNCTIONS

TSIDE reads input specifying initial temperatures, boundary temperatures, numerical procedure options, and printout options during initiation or restart of a simulation. If solution of the energy equation in the cylindrical grid region is requested, TSIDE is called at each time-step to advance the temperature solution.

The actions by TSIDE in the solution sequence include:

- TSIDE sets the connector arrays for the energy equation on the cylindrical grid. These are the coefficients that relate heat flows to temperatures and heat sources.
- TSIDE executes an algorithm that advances the temperature on the cylindrical grid through a time-step.
- 3. If requested, TSIDE prints monitoring information, including the location and magnitude of the greatest temperature change on the cylindrical grid for the current time-step, and also the temperatures in cells specified by the user for monitoring.
- 4. TSIDE makes a tentative adjustment in the time-step by comparing the maximum temperature change and a user-specified target maximum temperature change.

The algorithm used in TSIDE for advancing the temperature on the cylindrical grid through a time-step is discussed in <u>Volume I - Equations and Numerics</u> (McCann 1987). The imposition of continuity conditions between the rectangular and cylindrical grid regions, achieved with subroutine TBND supplementing TSIDE and THERM, is discussed in Chapter 2.0, Code Overview.

TSIDE is called at setup or restart to read input to guide the solution and to set or reset temperatures. Actions by TSIDE during setup or restart include:

- reading certain numerical procedure options, printout options, and temperature monitoring options
- 2. reading and implementing options for setting or altering the initial temperature distribution and ambient temperature.

9.2 PARAMETER STATEMENT INFORMATION

Subroutine TSIDE requires specification of the following parameters, which were discussed in Chapter 4.0, Subroutine GRID:

IP, JP, KP, ISP, JSP, NEFAP, KBP, KTP

Subroutine TSIDE also requires specification of the parameter

 MONTSP - Number of cells in the cylindrical grid that can be specified by the user for monitoring the temperature during time-stepping.

9.3 INPUT FORMAT

9.3.1 Overview

The input read by TSIDE will be described in Section 9.3.2. Other input available to TSIDE includes the initial temperature for the cylindrical grid that was read in THERM.

9.3.2 TSIDE Input Block

General Input Format

NECHO NEWTS,TSAMB,DTEMAX NECHO MONTS IMONTS(M),JMONTS(M),KMONTS(M) {Repeated for M=1 to MONTS+1, with IMONTS(M),JMONTS(M),KMONTS(M) { NECHO NDELTA DELTA(K),K=2,KP-1

General Input Description

- NECHO Echoing switch for this section of input. If input is to be echoed, then NECHO = 1; otherwise, 0.
- NEWTS An integer flag for initializing or resetting side (cask body or cylindrical grid) temperatures. If NEWTS = 1, cylindrical grid temperatures TS are set to the initial interface temperatures read in THERM. If NEWTS = 0, cylindrical grid temperatures are not reset.
- TSAMB The cask-side ambient temperature. If resetting side ambient temperature is requested by NEWTA = 1 (set in MAIN) or NEWTS = 1, the cask-side ambient temperatures are set as:

TS(IS,JS,K) = TSAMB for the cells defined by the ranges 2<JS<JSP-1 ISEND(K)+1<IS<ISP 2<K<KP-1 This is the region radially beyond the active

 DTEMAX - The target maximum temperature change per time-step for the cylindrical grid. A tentative new time-step DTIMES is set as: DTIMES = 1.1*DTIME if DTMAX < DTEMAX DTIMES = DTIME*DTEMAX/DTMAX if DTMAX>DTEMAX DTIME is the current time-step, and DTMAX is the magnitude of the largest temperature change in the

computational cells.

 MONTS - The number of cells in the cylindrical grid region for which temperature monitoring is requested.

cylindrical grid in the current time-step.

•	IMONTS(M),JMONTS(M),KMONTS(M) - The radial, azimuthal and axial mesh
	indices IS, JS, and K, respectively, of the mth cell
	in the cylindrical grid for which temperature printout
	is desired during the time-stepping. IMONTS(MONTS+1)
	should be set = 0 to terminate the list.

 NDELTA - An integer flag for adding a K-plane dependent increment to the temperatures for the cylindrical grid interior cells. If NDELTA = 1, add DELTA(K) to the TS(IS,JS,K) for cells in the range 2<K<KP-1 2<JS<JSP-1 2<IS<ISP-1 If NDELTA = 0, no DELTA increment is added. If ISEND(K) < ISP-2 and NDELTA = 1, the increment

DELTA(K) will be added to the ambient temperature for that K-layer. In this case, reset the side ambient temperatures using NEWTA.

 DELTA(K) - Temperature increment to optionally add to the active computational cells of the kth plane of the cylindrical grid, either initially or in a restart. The DELTA array is read even if NDELTA = 0.

Input File Example

471 1/tside 472 0,297.0,1.0 473 1/tside/monitor/ts 474 4 475 7,63,6 476 7,63,15 477 7,63,18 478 7,63,26 479 0,0,0 480 1/tside/delta 481 0 482 29*0.0

ŝ

Echoed Input File Example

768 769	tside	newts=0	tsamb=0.	297e+03	dtemax=0.1000+01								
709	te ide	monitor (A zello	mavimum	number	CUE	rení	Hu	a f	Iowed	ie	A	
771	13100		wins= 4	BUATBU	11011001	Cui	m	1	1	k	1.3		
772							1	7	63	6			
773							2	7	63	15			
774							3	7	63	18			
775							á	7	63	26			
776							•	•	02	20			
770	tside	ndelta=0		k	delta	(k)							
778				2	0.000e1	юо							
779				3	0.000e	ю							
780				4	0.00004	юл							
781				5	0.0000	100							
782				6	0.000e1	юо							
783				7	0.000et	100							
784				8	0.000el	юо							
785				9	0.000et	100							
786				10	0.000e+	юо							
787				11	0.000e+	-00							
788				12	0.000e+	юо							
789				13	0,000e+	-00							
790				14	0.000e+	Ю0							
791				15	0,000e+	-00							
792				16	0.000e+	60							
793				17	0.000e+	-00							
794				18	0.000e+	ю0							
795				19	0.000e+	-00							
796				20	0.000e+	60							
797				21	0,000e+	-00							
798				22	0.000e+	00							
799				23	0,000e+	-00							
800				24	0.000e+	00							
801				25	0,000e+	-00							
802				26	0.000e+	00							
803				21	0.00000	-00							
004 805				28	0.000-	00							
806				29	0.00004	-00							
807				00	0.00081	00							
~~~													

The input file example requests echoing of input with NECHO = 1 on line 471. On line 472, the input file example sets NEWTS = 0, indicating that no new side (cask body) temperature is to be set. The ambient temperature for the cask side is to be set to 297°K or 24°C if such a resetting of side temperatures (cylindrical grid region) occurs. Line 472 sets target maximum temperature change per time-step for the cask body DTEMAX to 1.0°C. Line 473 resets NECHO, and serves to carry the user comments on what is forthcoming, which is

the list of cells to be monitored for the cask body. Line 474 specifies that monitoring of four temperatures is requested, and they are listed by their indices in lines 475 through 478. Line 479 terminates this list of monitored cells with its leading zero. Line 480 resets NECHO. Lines 481 and 482 set NDELTA to 0, then set the 29 entries (for K = 2 through 30 in a simulation with KP = 31) for DELTA(K) to zero, doubly indicating that no manual increment of the temperatures in the active computational cells of the cylindrical grid region is desired.

The output example echoes this input and also provides a reminder on line 770 of the number of monitor cells in the cylindrical grid region currently allowed by dimensioning.
#### 10.0 SUBROUTINE TBND

Subroutine TBND provides the means to couple the solution of the energy equation within the interior of a cask to that of the exterior side of the cask body. A cartesian coordinate system is used for the interior of a cask and a cylindrical coordinate system is used for the side portion of the cask body. A cross section of a cask and the corresponding computational mesh is illustrated in Figure 4.1. Although the temperatures are determined implicitly within each region, the coupling between the two regions is explicit. This explicit coupling is done within subroutine TBND in such a way that temperature is continuous across the boundary and energy is conserved.

New-time temperatures are determined in the interior region using old-time boundary temperatures. Heat fluxes from the interior to the boundary are then determined. These heat fluxes are used as a boundary condition to calculate new-time exterior side temperatures. Finally, the temperatures on the boundary between the interior and exterior regions are updated to satisfy conservation of energy across the boundary. If there is no body to the cask, then neither subroutine TSIDE nor subroutine TBND is called.

#### 10.1 PARAMETER STATEMENT INFORMATION

Subroutine TBND requires the specification of parameter IP, JP, KP, ISP, JSP, NEFAP, KBP, and KTP. These parameters define the overall computational mesh and are described in Chapter 4.0, Subroutine GRID. No additional parameters are needed for Subroutine TBND.

# 10.2 INPUT FORMAT

The operation of subroutine TBND is automatic, and input file specifications are not required.

#### 11.0 SUBROUTINE RADC

HYDRA-II provides the user with three subroutines for use in modeling radiation heat transfer - RADC, RADP, and RADR. Subroutine RADC is described in this chapter. Subroutine RADP provides the user with a model for plateto-plate radiation heat transfer. RADP is described in Chapter 12.0. The remaining subroutine, RADR, is described in Chapter 13.0 and is intended to model radiation heat transfer between the fuel rods of an assembly. The radiation heat transfer distribution computed in RADC is cumulative with that computed by the other radiation heat transfer routines, RADP and RADR.

Subroutine RADC allows simulation of radiation heat transfer between the cell surfaces making up an enclosure in the computational grid. Each surface is associated with a cell of the grid by using the cell's (I,J,K) index. For RADC, the surfaces of an enclosure must have the same K index. Therefore, RADC allows communication between only the surfaces of an enclosure that are on the same K-plane. Communication between surfaces at differing K-planes must be handled in RADP. Enclosures having the same configuration (i.e., the same set of (I,J) indices defining the surfaces, as well as the same heat transfer coefficients between those surfaces), but residing on different K-planes, form regions in RADC terminology.

The radiation heat transfer between surfaces of an enclosure is computed as:

$$\begin{bmatrix} q_{1} \\ q_{2} \\ \vdots \\ q_{m} \\ q_{m} \end{bmatrix} = DZ(K) \begin{bmatrix} H_{1,1} & H_{1,2} & H_{1,3} & \cdots & H_{1,N} \\ H_{2,1} & H_{2,2} & H_{2,3} & \cdots & H_{2,N} \\ \vdots & \vdots & \vdots & \vdots \\ H_{m,1} & H_{m,2} & H_{m,3} & \cdots & H_{m,N} \\ \vdots & \vdots & \vdots & \vdots \\ H_{N,1} & H_{N,2} & H_{N,3} & H_{N,N} \end{bmatrix} \begin{bmatrix} T_{1}^{4} \\ T_{2}^{4} \\ \vdots \\ \vdots \\ T_{m}^{4} \\ T_{N}^{4} \end{bmatrix}$$

The radiation heat transfer received by the mth surface of the enclosure is represented by  $q_m$ . Each surface of the enclosure is assigned an index. These indices range sequentially from 1 to N. The correlation between these indices and the corresponding (I,J,K) indices of the computational cell is made in the input to RADC. The format for providing this information is discussed in Sections 11.2.3, 11.2.4, and 11.2.5.

DZ(K) represents the local DZ length segment which is common to all surfaces of this enclosure. It makes up half of the information necessary to compute the effective area of each of the surfaces. The other length segment is embedded in the radiation heat transfer coefficient, H.

The radiation heat transfer coefficients,  $H_{m,n}$ , are generated by the user and provided as input to RADC as discussed in Section 11.2.6. The constituent H's must include the effect of surface emissivity, shape factor, and Stefan-Boltzmann constant ( $\sigma = 5.67e-12 \text{ W/cm}^2 \cdot \text{K}^4$ ), in addition to carrying the other length segment representing the surface area. Since each enclosure of a RADC region has the same set of radiation heat transfer coefficients, there must be as many H matrices as there are regions in the RADC model. Each H matrix must be symmetric to ensure conservation of energy (i.e.,  $H_{m,n} = H_{n,m}$ ). The diagonal elements of these matrices account for reradiation from the receiving surface to the other surfaces of the region. Therefore, they must equal the negative of the sum of the off-diagonal row-element H's. More compactly stated,

> N H_{m,m} = − Σ H_{m,n} n=1 n≠m

As a general note, the information required to construct the H arrays can be very lengthy and dominates the RADC input section. Therefore, the user should configure the regions of the RADC model to take maximum advantage of any symmetries present in the geometry in an effort to reduce the number of H

arrays required. The effect of symmetries resulting from the application of boundary conditions requires special consideration. This is discussed in Section 11.2.7.

The temperatures used to represent the surfaces in the RADC computation are those of the corresponding (I,J,K) cells. These temperatures are actually located at the center of the cell. Therefore, the user must reference a cell surface to the cell that best represents the temperature of that surface. RADC is intended to model radiation heat transfer between solid surfaces, however. Consequently, the user must choose a cell that is consistent with both of these considerations.

#### 11.1 PARAMETER STATEMENT INFORMATION

Aside from the overall grid specification information IP, JP, KP, KBP, and KTP (described in Chapter 4.0), RADC requires information pertaining to the limiting number of surfaces and regions in the model. The required data are as follows:

٠	NREGP	-	An array	/ dimen	sion	grea	ater tha	n or	equa	l to	the
			maximum	number	of I	RADC	regions	in	the m	odel.	

- KCELLP An array dimension greater than or equal to the maximum number of K indices in a K-plane identifier.
- IDKP An array dimension greater than or equal to the maximum number of K-plane identifiers in the model.
- NSURFP An array dimension greater than or equal to the maximum number of surfaces in any region.
- IDIP An array dimension greater than or equal to the maximum number of I-cell identifiers.
- IDJP An array dimension greater than or equal to the maximum number of J-cell identifiers.
- IDHP An array dimension greater than or equal to the maximum number of H identifiers.

Each of these parameters must be set, as a minimum, to a value of 1 (even when RADC is not used).

# 11.2 INPUT FORMAT

# 11.2.1 Overview

Generally speaking, the input to subroutine RADC can be divided into six subsections:

- set info switch
- define regions
- load K-plane identifiers
- load I-cell identifiers
- load J-cell identifiers
- load H array.

A detailed discussion of the input requirements for each of these subsections is provided in the following text. This discussion references the RADC radiation model for the sample problem presented previously in Chapter 4.0. The plan and elevation views illustrating the computational mesh and RADC regions are presented in Figures 11.1 and 11.2, respectively. The input for Region 4 will be discussed in detail. Therefore, an enlarged view of this region is provided in Figure 11.1.

## 11.2.2 Set INFO Switch

General Input Format

#### NECHO INFO

# General Input Description

 NECHO - Echoing switch for this section of input. If
 NECHO = 1, an echo of the input for this section will be provided in the output; if NECHO = 0, this echoing will not be provided.



FIGURE 11.1. RADC Regions Superimposed on the Transverse Computational Mesh



FIGURE 11.2. Axial Computational Mesh and Alignment of Mesh with Physical Cask Features

 INFO - With INFO = 1, the code will monitor all enclosures and indicate the one experiencing the largest (in magnitude) net radiation heat transfer. This is discussed further in the following echoed-input file example. Setting INFO = 0 bypasses this monitoring process. With INFO = 1, RADC will override all settings of NECHO < INFO in the input file for this subroutine.

Input File Example

483 1/radc 484 0

Echoed-Input File Example

808 radc info=0 809

NECHO and INFO are input on lines 483 and 484, respectively. The corresponding echoed-input stream is presented as line 808. Setting INFO = 1 will allow the routine to monitor the net radiation heat transfer within an enclosure. In this case, RADC will print the net radiation heat transfer in the enclosure, the corresponding region number, and K-plane for the enclosure in which the maximum net radiation heat transfer has occurred. Note that the net radiation heat transfer in an enclosure should be 0. Therefore, this output provides a measure of sensitivity to truncation error as well as to inaccuracies in input data. When INFO = 1, all RADC input will be echoed in the output, regardless of the value of NECHO provided in the input. Setting INFO = 0 inhibits this echoing in the output.

11.2.3 Define Regions

General Input Format

NECHO NREGS NKCELL,IDK,NSURFS,IDI,IDJ,IDH

repeated for each of the NREGS regions of the model

# General Input Description

•	NECHO	-	Echoing switch for this section of input. If NECHO = 1, an echo of the input for this section will be provided in the output; if NECHO = 0, this echoing will not be provided.
•	NREGS	-	Number of regions in the RADC model (0 < NREGS < NREGP).
•	NKCELL	-	Number of K-planes (enclosures) in this region.
•	IDK	-	K-plane identifier for this region (1 < IDK < IDKP). This value will link with an IDK value input in Section 11.2.4.
•	NSURFS	-	Number of radiating surfaces in an enclosure (1 < NSURFS < NSURFP).
•	IDI	-	I-cell identifier for this region (1 < IDI < IDIP). This value will link with an IDI value input in Section 11.2.5.
•	IDJ	-	J-cell identifier for this region (1 < IDJ < IDJP). This value will link with an IDJ value input in Section 11.2.6.
•	IDH	-	H identifier for this region (1 < IDH < IDHP). This value will link with an IDH value input in Section 11.2.7.
	T	-	

Input File Example

485 1/radc/index 486 18 487 22,1,12,1,1,1 488 22,1,12,1,2,1 489 22,1,18,2,3,2 490 22,1,8,3,4,3 491 22,1,8,3,5,3 492 22,1,14,4,6,4 493 22,1,24,5,7,5 494 22,1,24,5,8,5 495 22,1,26,6,9,6

496	22,1	,26,	,7,	10,6	
497	22,1	,26,	7,	11,6	
<b>49</b> 8	22,1	26	6,	12,6	
499	22,1	10	8.	13,7	
500	22,1	10	9	14,7	
501	22,1	10	9	15,7	
502	22,1	10	8.	16.7	
503	22,1	27	10	,17,8	
504	22.1	27	10	18.8	

<u>`__</u>

# Echoed-Input_File_Example

810	radc	nregs= 18	maximum curr	ent dimension	for areas l	s 18			
811	radc	Index	region	number of	k-cel l	number of	i-cel i	i-cel l	h
812			number	k cells	Identifier	surfaces	Identifier	Identifier	Identifier
813			1	22	1	12	1	1	1
814			2	22	i	12	1	2	1
815			3	22	1	18	2	3	2
816			4	22	1	8	3	Å	ī
817			5	22	1	8	3	5	š
818			6	22	1	14	Ā	6	, j
819			7	22	i	24	5	7	5
820			8	22	1	24	. 5	8	ś
821			9	22	1	26	6	9	6
822			10	22	1	26	7	10	6
823			11	22	i	26	,	11	ĸ
824			12	22	1	26	6	12	š
825			13	22	i	10	8	13	7
826			14	22	1	10	9	14	7
827			15	22	1	10	9	15	7
828			16	22	1	10	8	16	7
829			17	22	1	27	10	17	Ŕ
830			18	22	1	27	10	18	8
831					•	_,	.0		U

Input lines 485 through 504 reflect the RADC input for the regional decomposition of the mesh. The corresponding echoed-input stream is presented in lines 810 through 830. NECHO is set to 1 on line 485 of this input section. As indicated in line 486 of the input and line 810 of the echoed-input, there are 18 RADC regions for this application. Further information for each of the 18 regions is provided in input lines 487 through 504 and echoed in output lines 811 through 830. The number of K-planes and surfaces present in each region are provided here, as are the I-cell, J-cell, K-plane, and H identifiers associated with each of these regions. The value of these identifiers provides the link between the surfaces of the region and the corresponding cell indices associated with each surface. In addition, the

value of the H identifier associates a matrix of radiation heat transfer coefficients with the surfaces of this region. These links are completed with the input from the following four sections, 11.2.4 through 11.2.7.

#### 11.2.4 K-Cell Identifiers

General Input Format

NECHO KCELLS	,KCELL(	1,IDK	),KCELL(2,IDK),	,KCELL(KCELLS,IDK)	repeated for
	•	•	•		each K-plane
	•	٠	•	)	laentifier
	•	•	•		

# General Input Description

•	NECHO	-	Echoing switch for this section of input. If
			NECHO = 1, an echo of the input for this section will
			be provided in the output; if NECHO = 0, this echoing
			will not be provided.

- KCELLS Number of K-planes in this set (1 < KCELLS < KCELLP).
- KCELL List of K-plane indices.
- IDK K-plane identifier for this set (1 < IDK < IDKP). This value will link with an IDK value input in Section 11.2.3.

Input File Example

505 1/radc/kcell 506 22,5,6,7,8,9,10,11,12,13,14,15,16,17,18,19,20,21,22,23,24,25,26

Echoed-Input File Example

 832
 rade
 kcell
 idk
 k-cells:

 833
 1
 22
 :
 5
 6
 7
 8
 9
 10
 11
 12
 13
 14
 15
 16
 17
 18
 19
 20
 21
 22
 23
 24
 25
 26

NECHO is set to one on line 505 of the input stream. The number and value of the K indices from the computational mesh are provided in input line 506. Since there is only one K-plane set in this model, the radiation heat transfer between the enclosure surfaces for the 18 regions will be computed for each of the 22 K-planes. These 22 K-planes span the range of K indices 5 through 26. Figure 11.2 illustrates their location in the model.

## 11.2.5 I-Cell Identifiers

General Input Format

NECHO NSURFS,	ICELL(	1,IDI	),ICELL	.(2,IDI), .	,ICELL(1	NSURFS,IDI)	repeated for
	٠	•	•			1	each I-cell
	•	•	•			J	Identifier
	٠	•	•				

General Input Description

- NECHO Echoing switch for this section of input. If
   NECHO = 1, an echo of the input for this section will be provided in the output; if NECHO = 0, this echoing will not be provided.
- NSURFS Number of surfaces in this set (1 < NSURFS < NSURFP).</li>
- ICELL List of I-cell indices.
- IDI I-cell identifier for this set (1 < IDI < IDIP). This value will link with an IDI value input in Section 11.2.3.</li>

Input File Example

507 1/radc/icell 508 12,2,3,4,3*5,4,3,2,3*1 509 18,6,7,8,6*9,8,7,6,6*5 510 8,2,3,4,5,4,3,2,1 511 14,15,6*16,15,6*14 512 24,6,6*7,8,9,10,11,12,11,10,9,8,7,6,6*5 513 26,6,12*7,6,12*5 514 26,25,24,23,22,21,20,19,18,17,16,15,14,13,12,13,14,15,16,17,18,19,20,21, 515 22,23,24 516 10,8,9,10,11,11,10,9,8,7,7 517 10,2*25,24,23,4*22,23,24 518 27,13,14,15,16,17,18,19,20,21,21,20,19,18,17,16,15,14,13,9*12

Echoed-Input File Example

835	radc	icell	Idi	i-cell	s:																								
836			1	12	:	2	- 3	- 4	5	5	- 5	- 4	- 3	2	1	1	1												
837			2	18	:	6	7	8	9	9	9	9	9	9	8	7	6	5	5	5	5	5	5						
838			3	8	:	2	3	- 4	- 5	4	3	2	1																
8 39			4	14	:	15	16	16	16	16	16	16	15	14	14	-14	14	14	- 14										
840			5	24	:	б	7	7	1	7	7	7	6	9	10	11	12	11	10	9	8	7	6	5	5	5	- 5	5	5

841	6	26	:	6	7	7	7	7	7	7	7	7	7	7	7	7	б	5	5	5	5	5	5	5	5	5	5	5	5	
842	7	26	:	25	24	23	22	21	20	19	18	17	16	15	14	13	12	13	14	15	16	17	18	19	20	21	22	23	24	
843	8	10	:	8	9	10	11	11	10	9	8	7	7																	
844	9	10	:	25	25	24	23	22	22	22	22	23	24																	
845	 10	27	:	13	14	15	16	17	18	19	20	21	21	20	19	18	17	16	15	14	13	12	12	12	12	12	12	12	12	12
846																														

The information for each I-cell identifier is provided next in input lines 507 through 518. NECHO has again been set to 1 on line 507. The number of surfaces and mesh indices are provided for each of the 10 I-cell identifier sets (IDI) in lines 508 through 518. The echoed-input stream for this data is presented in lines 835 through 845. The number of surfaces represented in this I-cell set is presented first in a line of input (e.g., 8 surfaces will be represented by I-cell set 3 on input line 510). This is followed by the I-cell indices associated with each of the surfaces of the set (e.g., I = 2,3,4,... for I-cell set 3 on input line 510). Note that the IDI values for the I-cell groups are not explicitly provided in the input. HYDRA-II loads the value of NSURFS and each of the corresponding NSURFS I-cell indices into one IDI group before incrementing IDI and beginning to load the next IDI group.

11.2.6 J-Cell Identifiers

General Input Format

NECHO NSURFS,JCELL(1,IDJ),JCELL(2,IDJ), ...,JCELL(NSURFS,IDJ) each J-cell identifier

## General Input Description

- NECHO Echoing switch for this section of input. If
   NECHO = 1, an echo of the input for this section will be provided in the output; if NECHO = 0, this echoing will not be provided.
- NSURFS Number of surfaces in this set (1 < NSURFS < NSURFP).</li>
- JCELL List of J-cell indices.

IDJ

J-cell identifier for this set (1 < IDJ < IDJP). This value will link with an IDJ value input in Section 11.2.3.</li>

Input File Example

519 1/radc/jcell 520 12,3*17,18,19,20,3*21,20,19,18 521 12,3*32,31,30,29,3*28,29,30,31 522 18,3*21,22,23,24,25,26,27,3*28,27,26,25,24,23,22 523 8,3*10,11,3*12,11 524 8,3*39,38,3*37,38 525 14,21,22,23,24,25,26,27,28,27,26,25,24,23,22 526 24,14,15,16,17,18,6*19,20,6*21,20,19,18,17,16,15 527 24,35,34,33,32,31,6*30,29,6*28,29,30,31,32,33,34 528 26,1,2,3,4,5,6,7,8,9,10,11,12,13,14,13,12,11,10,9,8,7,6,5,4,3,2 529 26,20,12*19,20,12*21 530 26,29,12*30,29,12*28 531 26,48,47,46,45,44,43,42,41,40,39,38,37,36,35,36,37,38,39,40,41,42,43,44, 45,46,47 532 533 10,1,1,2,3,4*4,3,2 534 10,18,17,16,15,15,16,17,18,19,19 535 10,31,32,33,34,34,33,32,31,30,30 536 10,48,48,47,46,4*45,46,47 537 27,5,6,7,8,9,10,11,12,13,9*14,13,12,11,10,9,8,7,6,5 538 27,44,43,42,41,40,39,38,37,36,9*35,36,37,38,39,40,41,42,43,44

Echoed-Input File Example

847	radc	jcell	idj	j-cel	is:																											
848			i i	12	:	17	t7	17	18	19	20	21	21	21	20	19	18															
849			2	12	: :	32	32	32	31	30	29	28	28	28	29	30	31															
850			3	18	: 2	1 1	21	21	22	23	24	25	26	27	28	28	28	27	26	25	24	23	22									
851		•	4	8	: '	0	10	10	11	12	12	12	11																			
852			5	8	: :	9	39	39	38	37	37	37	38																			
853			6	14	: 2	21 2	22	23	24	25	26	27	28	27	26	25	24	23	22													
854			7	24	: 1	4 1	15	16	17	18	19	19	19	19	19	19	20	21	21	21	21	21	21	20	19	18	17	16	15			
855			8	24	: 3	5 3	54	33	32	31	30	30	30	30	30	30	29	28	28	28	28	28	28	29	30	31	32	33	34			
856			9	26	:	1	2	3	4	5	6	7	8	9	10	11	12	13	14	13	12	11	10	9	8	7	6	5	4	5	2	
857			10	26	: 2	0	19	19	19	19	19	19	19	19	19	19	19	19	20	21	21	21	21	21	21	21	21	21	21	21	21	
858			11	26	: 2	9 3	50	30	30	30	30	30	30	30	30	30	30	30	29	28	28	28	28	28	28	28	28	28	28	28	28	
859			12	26	: 4	8 4	17	46	45	44	43	42	41	40	39	38	37	36	35	36	37	38	39	40	41	42	43	44	45	46	47	
860			13	10	:	1	1	2	3	4	4	4	4	3	2																	
861			14	10	: 1	8 1	17	16	15	15	16	17	18	19	19																	
862			15	10	: 3	13	32	33	34	34	33	32	31	30	30																	
863			16	10	: 4	8 4	18	47	46	45	45	45	45	46	47																	
864			17	27	:	5	6	7	8	9	10	11	12	13	14	14	14	14	14	14	14	14	14	13	12	11	10	9	8	7	6	5
865			18	27	: 4	4.4	13 4	42	41	40	39	38	37	36	35	35	35	35	35	35	35	35	35	36	37	38	30	á	41	42	43	
866			-																						2.	20					~2	

The J-cell identifier information is provided next in input lines 519 through 538. The format for this input is the same as that for the I-cell identifiers. That is, line 519 indicates NECHO has been set to a value of 1. Information for each of the 18 J-cell identifiers is provided next in input lines 520 through 538 and has been echoed in output lines 848 through 865. The number of surfaces and their corresponding J-cell indices are provided for each J-cell set in this input stream. For example, J-cell set 4 represents eight surfaces with J indices 10, 11, and 12. As with IDI in the previous section, the IDJ group identifier numbers are assigned internally in HYDRA-II.

At this point, the code has all the necessary index information to associate an (I,J,K) cell index with each of the surfaces modeled. For example, the (I,J,K) indices associated with the eight surfaces of region 4 are (2,10,K), (3,10,K), (4,10,K), (5,11,K), (4,12,K), (3,12,K), (2,12,K), and (1,11,K). As specified by the K-plane set provided on input line 506, K takes on the values 5 through 26 in this RADC model.

It remains to associate a radiation heat transfer coefficient with each of the interacting surface pairs of the model. This information is provided next.

11.2.7 H Array

General Input Format

NE NS H(	CHO URFS 1,1,IDH)	,H(1,2,IDH), ,H(1,NSURFS,IDH),	repeated for
		• • • • • •	each H-identifier set
H(	NSURFS,1 <u>General</u>	,IDH),H(NSURFS,2,IDH),,H(NSURFS, Input Description	NSURFS,IDH)
•	NECHO	<ul> <li>Echoing switch for this section</li> <li>NECHO = 1, an echo of the input</li> <li>be provided in the output; if</li> </ul>	on of input. If ut for this section will NECHO = O, this echoing

 NSURFS - Number of surfaces represented in this H identifier set (1 < NSURFS < NSURFP).</li>

will not be provided.

• H

-	Matrix of	radiation	heat	transfer	coefficients	for
	this set.					

# • IDH - H identifier for this H matrix (1 < IDH < IDHP).

Input File Example

539	0/radc/h
540	12
541	967992423084
542	.13372162059
543	.21348096540
544	0.
C / C	144646000611

541	967992423084620e-11	144545280611220e-12	144593159843263e-11.
542	.133721620597627e-11	.389548549669991e-12	.154380651783190e-11.
543	.213480965409158e-11	. 230612866749674e-12	
544	0.	.0.	.0.
545	144545280611221e-12	112005588613371e-11	.145114180107132e-12.
546	.140265349851777e-12	415585794368260e-13	.158065316055406e-12.
547	236030481944205e-12	238408757658562e-13	.230635822361273e-12.
548	0.	.0.	.0.
549	144593159843263e-11	.145114180107131e-12	108314180956411e-10.
550	.223448481096404e-11	. 436015483685137e-12	.152690761027124e-11.
551	.267210659730428e-11	. 236019678319556e-12	213483813655713e-11.
552	0.	.0.	.0.
553	.133721620597628e-11	.140265349851777e-12	. 223448481096404e-11.
554	804166888540504e-11	. 236067219282889e-12	.906119342226106e-12.
555	.150656347927900e-11	.156049296512796e-12	.152490318131222e-11.
556	0.	.0.	.0.
557	.389548549669995e-12	415585794368262e-13	436015483685141e-12.
558	.236067219282891e-12	220784085075826e-11	.238802877733071e-12.
559	.434383953042135e-12	. 415548020670205e-13	.389909385841205e-12.
560	0.	.0.	.0.
561	.154380651783191e-11	.158065316055405e-12	.152690761027126e-11.
562	.906119342226099e-12	238802877733070e-12	812834382046880e-11.
563	.225641498023646e-11	.142280625220507e-12	.135594655089405e-11.
564	0.	.0.	.0.
565	.213480965409158e-11	236030481944201e-12	.267210659730428e-11,
566	.150656347927900e-11	434383953042134e-12	.225641498023646e-11,
567	108318769033387e-10	.145123763252704e-12	.144644399418830e-11,
568	0.	,0.	,0. ,
569	.230612866749678e-12	, .238408757658560e-13	.236019678319558e-12,
570	.156049296512798e-12	, .415548020670205e-13,	.142280625220508e-12,
571	.145123763252704e-12	,112005839117282e-11	.144576483284708e-12,
572	0.	,0.	,0. ,
573	.245345355748303e-11	, .230635822361273e-12,	.213483813655713e-11,
574	.152490318131222e-11	, .389909385841205e-12,	.135594655089406e-11,
575	.144644399418831e-11	, .144576483284708e-12,	,968070711192182e-11,
576	0.	,0.	,0. ,
577	0.	,0.	,0. ,
578	0.	,0.	,0. ,
579	0.	,0.	,0. ,
580	0.	,0.	,0. ,
581	0.	<b>,0.</b>	,0, ,

582	0.	,0.	,0	•	•
583	0.	,0.	,0	•	•
584	0.	,0.	,0	•	,
585	0.	,0,	,0	•	,
586	0.	,0.	,0	•	
587	0.	,0,	,0	•	,
588	0.	,0.	,0	•	,
			-		-
		•	•	•	
		•	•	•	
		•	•	•	
698	8				
699	87730874863427	5e-11, .1855111	43726041e-12,	<b>.</b> 133538878723581€	2-11,
700	.76124386376475	5e-12, .1635689	22689131e-11,	<b>.</b> 305931782435861€	e-12,
701	.45493226822889	05e-11,0.	,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,		
/02	.185511143/2604	3e-12,1115446	/0514/29e-11,	.1/812183/4515356	2-12,
703	.92/5/141345236	4e-13, .2989146	95/28965e-12,	.5421010445964166	2-13,
704	.305931/8243585	08e-12,0.	,	10000101000011	10
/05	.1335388/8/235/	9e-11, .1/81218	3/4515320-12,-	.1000849449209116	2-10,
705	.18425890462170	08e-11, .4/1//90	89856585e-11,	.298914695/289656	9-12,
707	•10350892208912 76124206276476	(90-11,0. (5, 12, 0075714)	12452260- 12	104250004621760	. 11
700	./01243003/04/3	000-12, .92/0/14 06, 11 10/2500	134323008-13, 04621760, 11	104230904021/000 027571812852268	2-11,
709	00901020000	000-11, 1042009	04021/000-11,	.92/3/14134323046	2-13,
710	./01243003/04/4	10 11 20001/6	05720062- 12	171770000056505	. 11
712	•10330092200913 19425900462176	320-11 - 1000940	<i>4</i> /020012 <u>0</u> -12,	4/1//90090000000	. 12
712	.10423090402170	20-11,1000049	449209128-10,	•1/012103/4515556	:-12,
717	-1353567672557	$0e^{-11}, 0$	115061160-13	208014605728066	-12
714	027571/12/5236	36-12, 0.0421010	374515346-12 =	111544670514720	-12,
716	18551114372604	10-12	5/4515546-12,-	•1113440/0314/236	-11,
717	45493226822880	12-12,0. 15a-11 3059317	824358580-12	1635680226801314	-11
718	76124386376474	$9_{-12}$ 1335388	787235790-11	1855111437260414	-12
719	- 87730874863427	50-12, 1000000	/0/200/00-11,	•1000111407200410	
720	0.	0.	ູ້ດ		
721	0.	<b>,</b> 0,	<b>,</b> 0	-	,
722	0.	,0,	,.		,
	••	,	,		
		•	•		
		•	•		
		•		•	
		-	-	-	
****	******	************** NOT	E *********	*****	****
*					*
*	Only part of the	H input file (fo	or H identifie	r = 1 and 3)	*
*	is shown for brev	vity		-	*
*		-			*
*****	*****************	******	***********	***************	***

Part of the input file for the radiation heat transfer coefficients is provided in lines 539 through 588 and lines 698 through 722. This input is typically quite lengthy for enclosures having many surfaces. Therefore, only portions of it are presented here. Input line 539 indicates the setting of NECHO to zero for this section. Input lines 540 through 588 correspond to the data provided for the first H set (H identifier, IDH = 1). This array of radiation heat transfer coefficients represents a region composed of 12 surfaces (ref., input line 540). Therefore, there are 144 elements in this H array (12 x 12). The array is loaded by rows (i.e., updating the second index most rapidly). Consequently, the radiation heat transfer coefficients from the first through twelfth surfaces to the first surface are loaded first. Those from the first through twelfth surfaces to the second surface are loaded next, and so on. The H identifiers on input lines 487 and 488 (and in the echoedinput lines 813 and 814) indicate that this H array is used for regions 1 and 2 of the RADC model.

The regional input provided in lines 487 through 504 above indicated that there are eight such H arrays in this RADC model. Therefore, the input to this section must have eight corresponding sets of data similar in format to that provided in input lines 540 through 588.

Data for the third H array (H identifier, IDH = 3) are presented in input lines 698 through 722. Input line 698 indicates that this array represents the radiation heat transfer coefficients between eight surfaces. Therefore, this array contains 64 elements (8 x 8). As with the first H array, this array is loaded by rows.

The format for the H array input, as well as the connection between this input and the information provided for I-cell, J-cell, and K-plane specifications, is best illustrated by an example. Therefore, the following discussion pertains to region 4 of the model. The computational mesh associated with this region is illustrated in the detail of Figure 11.1.

Region 4 represents an eight-surface enclosure at each of the 22 K-planes corresponding to K indices 5 through 26. At each of these K-planes, radiation heat transfer will be computed between the eight surfaces represented by the I-cell and J-cell identifiers 3 and 4, respectively. The (I,J) pairs defining

the cells of this enclosure are identified by association with these I-cell and J-cell identifiers as (2,10), (3,10), (4,10), (5,11), (4,12), (3,12), (2,12), and (1,11). The H identifier is 3 for this region. Therefore, the corresponding radiation heat transfer coefficients for this region are provided in the third array of H data provided (input lines 698 through 722). The radiation heat transfer coefficient for reradiation from the surface associated with cell (2,10,K) to the seven other surfaces of this enclosure is input first. The radiation heat transfer coefficient for energy received by (2,10,K) from the surface associated with cell (3,10,K) is presented next in the input file, followed by that for (4,10,K) to (2,10,K), and so on. As indicated by the K index, these values are used for radiation heat transfer in this enclosure at each of the 22 K-planes of the model. The code internally scales these coefficients by the appropriate DZ(K). The other length scale of the area element must be incorporated in the radiation heat transfer coefficient.

To further illustrate the structure of the input file format, consider the specific interaction between nodes (5,11,K) and (3,10,K). The radiation heat transfer coefficient used for the energy radiated by the surface at (3,10,K) to the surface at (5,11,K) has the value 0.92757...e-13. Cell (5,11,K) represents the fourth surface element of an enclosure in region 4. Cell (3,10,K) represents the second surface element of an enclosure in region 4. Therefore, the radiation heat transfer coefficient for energy received by (5,11,K) from (3,10,K) is stored in H_{4.2} (i.e., the second element of the fourth row in this H array). Since the array is loaded by rows, this corresponds to the twentysixth entry to the array (viz., the second entry on input line 708). To illustrate the symmetry required of the matrix of radiation heat transfer coefficients, this value must equal that representing transfer from (5,11,K) to (3,10,K). The value is stored in element  $H_{2,4}$ , the fourth element in the second row. This is the twelfth value entered in the H array, viz., the first entry on input line 703. Comparison of these two values indicates that they are equal. The radiation heat transfer coefficient used to model reradiation from (5,11,K) to the adjoining surfaces of the enclosure has the value -0.53931...e-11 (the diagonal element on the fourth row of this array,  $H_{4,4}$ ). This value equals the negative of the sum of the other radiation heat transfer

coefficients from (5,11,K). These same coefficients are used for each of the 22 K-planes, 5 through 26 (with the appropriate rescaling by DZ(K)).

Frequently, symmetries are present in the problem configuration. The presence of these symmetries should be exploited in the model to reduce the amount of input and execution time required by the simulation. However, when invoking these symmetries, the user must be certain to include the effects of image cells (i.e., the reflection of model cells about a line of symmetry) when generating the input. In particular, the RADC radiation heat transfer coefficients must reflect the presence of these symmetries. A typical situation exhibiting this is illustrated in Figure 11.3. In this figure, the modeled section is represented on the right of the line-of-symmetry, and its image is to the left of the line-of-symmetry. The participating surfaces of the RADC enclosure and their images are indicated by the boxed numbers. To properly model the radiation heat transfer in this enclosure, the user must generate radiation heat transfer coefficients that include the presence of the image section. For example, the radiation heat transfer coefficient between surfaces 1 and 7 should also include the effect of radiation from the image of surface 7 (surface 7') to surface 1. Similarly, the interaction between surfaces 3 and 4 should include that between surfaces 3' and 4' also. Surfaces 1' through 7' are not, of course, explicitly included in the RADC model. Their effect is lumped into the surface in the modeled section and its corresponding radiation heat transfer coefficients.

#### 11.2.8 Input Example When RADC Is Not Used

If routine RADC is not used in the simulation, then only lines 483 through 486, 505, 507, 519, and 539 need be provided in the input stream. The input might look like the following in this case:

483 1/radc 484 0 485 1/radc/index 486 0 505 0/radc/kcell 507 0/radc/icell 519 0/radc/jcell 539 0/radc/h



FIGURE 11.3. RADC Enclosure 4 Blow-up Showing Modeled and Image Sections (RADC Surfaces are Denoted by Boxed Numbers)

#### 12.0 SUBROUTINE RADP

HYDRA-II provides the user with three subroutines for radiation heat transfer - RADC, RADP, and RADR. Subroutine RADC is described in Chapter 11.0. RADC allows the user to simulate radiation heat transfer between the surfaces of an enclosure in the computational domain. The cells associated with these surfaces must share the same K index for RADC to be applicable. Subroutine RADP is described in this chapter. The remaining subroutine, RADR, is described in Chapter 13.0 and is intended to model radiation heat transfer between the fuel rods of an assembly. The radiation heat transfer distribution computed in RADP is cumulative with that computed by the other radiation heat transfer routines, RADC and RADR.

RADP computes the radiative heat transfer received by the mth cell surface from the nth cell surface using

$$q_{RADP}(m,n) = \frac{\sigma A_m [T_n^4 - T_m^4]}{[(1/\epsilon_2) - 1 + (1/\epsilon_1)]}$$

where  $\varepsilon_1$  and  $\varepsilon_2$  are the emissivities of the two communicating cell surfaces,  $\sigma$  is the Stefan-Boltzmann constant (= 5.67e-12 W/cm²·K⁴), and A_m is the appropriate surface area of cell m. A shape factor of 1.0 is assumed between the two surfaces. Therefore, the radiation heat transfer is equivalent to that between two essentially infinite parallel planes.

RADP is designed to compute the radiation heat transfer between the cells on two computational mesh planes. These planes may be separated in any one of the three coordinate directions (viz., I, J, or K). Two of the three cell indices must be the same for any pair of communicating cells. Therefore, the transfer of energy is either between the cells associated with indices (I,J,K) and (L,J,K), between (I,J,K) and (I,M,K), or between (I,J,K) and (I,J,N). RADP will sweep over a user-specified range of the two variable indices, computing the radiation heat transfer between each pair of communicating cells in that range. The range of indices constitutes a region of the computational domain. Radiation heat transfer is between two cell surfaces. Any one cell surface is shared by either of two cells. In addition, the temperatures  $T_n^4$  and  $T_n^4$  in the above relationship are those associated with the center of cells m and n. Therefore, care must be exercised when assigning cell indices to the surfaces exchanging energy. When the RADP model is set up, the participating cells should be chosen to accurately represent both the temperature and thermal properties of the interacting surfaces.

#### 12.1 PARAMETER STATEMENT INFORMATION

Aside from the overall computational mesh specification information IP, JP, and KP, and the bottom- and top-side mesh information KBP and KTP (described in Chapter 4.0), RADP requires information pertaining to the limiting number of regions in the model. The required data are as follows:

- IREGP An array dimension greater than or equal to the maximum number of IREG regions (see Section 12.2.2).
- JREGP An array dimension greater than or equal to the maximum number of JREG regions (see Section 12.2.3).
- KREGP An array dimension greater than or equal to the maximum number of KREG regions (see Section 12.2.4).

IREGP, JREGP, and KREGP must, as a minimum, be set to a value of one (even when RADP is not used).

### 12.2 INPUT FORMAT

#### 12.2.1 Overview

Generally speaking, the input to subroutine RADP can be divided into three subsections:

- load arrays for heat transfer between cells separated in the I-direction
- load arrays for heat transfer between cells separated in the J-direction

• load arrays for heat transfer between cells separated in the K-direction.

A detailed discussion of the input requirements for each of these subsections is provided in the following text.

General Input Format

The general format for input to this routine is as follows:

input line n : NECHO input line (n+1) : NREGS input line (n+2) :  $\varepsilon_1$ ,  $\varepsilon_2$ , IBEG, IEND, JBEG, JEND, KBEG, KEND input line (n+2+NREGS-1):  $\varepsilon_1$ ,  $\varepsilon_2$ , IBEG, IEND, JBEG, JEND, KBEG, KEND. General Input Description

- NECHO Echoing switch for this section of input. If
   NECHO = 1, an echo of the input for this section will be provided in the output; if NECHO = 0, this echoing will not be provided.
- NREGS The number of regions modeled in this subsection.
- $\varepsilon_1$  and  $\varepsilon_2$  Emissivities of the communicating surfaces.
- IBEG Beginning value for the I index range.
- IEND Ending value for the I index range.
- JBEG Beginning value for the J index range.
- JEND Ending value for the J index range.
- KBEG Beginning value for the K index range.
- KEND Ending value for the K index range.

The pairs (IBEG,IEND), (JBEG,JEND), and (KBEG,KEND) represent the index ranges for the surfaces of this region. RADP will loop (in the FORTRAN sense) over any two of the three pairs of indices to compute the radiation heat transferred between the third pair of indices. The index for one cell is composed from the two running indices and the "BEG" value of the third index. The index for the second cell of the pair is composed from the same two running indices and the "END" value of the third index. For example, consider two cells separated in the K-direction. Each cell has running indices I and J where IBEG  $\leq$  I  $\leq$  IEND and JBEG  $\leq$  J  $\leq$  JEND. Each pair of interacting cells will then have indices (I,J,KBEG) and (I,J,KEND). This configuration is illustrated in Figure 12.1.

This routine is perhaps best understood by means of an example problem. Therefore, the use of RADP in modeling the sample problem presented in Chapter 4.0 is discussed in Sections 12.2.2 through 12.2.4. Figures 12.2 and 12.3 illustrate the location of the regions modeled in the following input. The input line numbers are used to call out the location of the corresponding region on Figure 12.2.

12.2.2 I-Direction Radiation Heat Transfer Mode

Input File Example 1507 1/radp/iregs 1508 0

Echoed-Input File Example

867 radp iregs≠ 0 maximum current dimension for iregs is 1 868

Those regions of the computational mesh for which the RADP surfaces are separated in the I-direction are input first. The corresponding input for the sample problem is shown here as input lines 1507 and 1508. On input line 1507, the value of NECHO is set to 1. Input line 1508 provides the value of the number of IREG regions in the RADP model. For this model, there are none, so O is entered. The echoed-input lines for this section are shown here as output lines 867 and 868.

12.2.3 J-Direction Radiation Heat Transfer Mode

Input File Example

1509 1/radp/jregs 1510 0



FIGURE 12.1. Typical RADP "Floating Region" Simulating Radiation Heat Transfer in the K-Direction



FIGURE 12.2. Transverse Computational Mesh and Alignment of Mesh with Physical Cask Features - RADP Regions Shown



FIGURE 12.3. Axial Computational Mesh and Alignment of Mesh with Physical Cask Features - RADP KBEG and KEND Indices Shown

#### Echoed-Input File Example

869 radp jregs= 0 maximum current dimension for jregs is 1 870

Those regions of the computational mesh for which the RADP surfaces are separated in the J-direction are input next. The corresponding input for the sample problem is shown here as input lines 1509 and 1510. On input line 1509, the value of NECHO is set to 1. Input line 1510 provides the value of the number of JREG regions in the RADP model. For this model, there are none, so O is entered. The echoed-input lines for this section are shown here as output lines 869 and 870.

## 12.2.4 K-Direction Radiation Heat Transfer Mode

Input File Example

1511 1/radp/kregs 1512 68 1513 0.4,0.25,5,5,2,47,26,28

• •

1517 0.4,0.25,2,24,21,21,26,28

•	٠	•
•	٠	•
•	٠	•

1580 0.8,0.25,17,24,22,27,3,5

#### Echoed-Input File Example

871 872	radp radp	kregs≖ 68	maximum cur region	rent dimer emitt	nslon for k ances	rəgsis (	58 Ce	)   c	ocatio	n	
873 874			- 1	0.400	0,250	i bəg 5	lend 5	jbəg 2	jend 47	kbəg 26	kend 28
			•		- 				•		
878			• 5	0,400	0,250	2	24	21	21	26	28
			•	•	, ,			•	1 1		
941			68	0,800	0,250	17	24	22	27	3	5

Finally, those regions of the computational mesh for which the RADP surfaces are separated in the K-direction are input. The corresponding input for the example problem is shown as input lines 1511 through 1580. On input line 1511 the value of NECHO is set to 1. Input line 1512 indicates that there are 68 KREG regions in the RADP model. Input line 1580 is typical of the input lines in this routine. Here,  $\epsilon_1$  and  $\epsilon_2$  are set to a value of 0.8 and 0.25, respectively. Since this input is in the third subsection of input provided to this routine, the routine will sweep over the I and J index ranges, computing the radiation heat transfer between the surface pairs at (I,J,3) and (I,J,5) for each I and J in the ranges 17 < I < 24 and 22 < J < 27. The surface area, A, will be computed as DX(I)*DY(J). The echoed-input lines for these lines are shown in lines 871 through 874, line 878, and line 941.

# 12.2.5 Input Example When RADP Is Not Used

If routine RADP is not used in the simulation, the following input must still be provided:

1507 1/radp/iregs 1508 0 1509 1/radp/jregs 1510 0 1511 1/radp/kregs 1512 0

## 13.0 SUBROUTINE RADR

HYDRA-II provides the user with three subroutines for use in modeling radiation heat transfer - RADC, RADP, and RADR. Subroutine RADC is described in Chapter 11.0. RADC allows the user to simulate radiation heat transfer between the surfaces of an enclosure in the computational domain. The cells associated with these surfaces must share the same K index for RADC to be applicable. Subroutine RADP provides the user with a model for plate-to-plate radiation heat transfer. RADP is described in Chapter 12.0. Subroutine RADR is described in this chapter. The radiation heat transfer computed in RADR is cumulative with that computed by the other radiation heat transfer routines, RADC and RADP.

RADR provides the user with a method for computing rod-to-rod radiation heat transfer in a fuel assembly. Each computational cell of the RADR model contains only one spent fuel rod. The cell surfaces on any K-plane are configured so as not to "cut" the spent fuel rod boundaries; hence, the cellto-cell nature of the radiation heat transfer mode in this routine (contrasted with the surface-to-surface structure of RADC). This idea is illustrated in Figure 13.1.

The routine is structured to compute the radiation heat transfer between the cell associated with index (I,J,K) and any of its 24 neighboring cells in the range  $I\pm 2$  and  $J\pm 2$ . This region-of-influence is shown schematically in Figure 13.2. The center cell [index (I,J,K)] is the receiver cell. The "generic" cell in this region-of-influence is identified by the roman indices (I,J,K) to differentiate it from the center cell (I,J,K). The surrounding 24 cells of this region are the transmitter cells "seen" by the center cell. The region-of-influence "floats" over the range of cells specified in the RADR model. In addition, RADR computes the radiation heat transfer between these cells for a user-specified range of K-planes. As in the RADC subroutine, RADR does not allow radiation heat transfer between cells having different K-plane indices. This mode of exchange may be modeled using subroutine RADP.

In general, the proper computation of radiation heat transfer coefficients can get very involved. This is particularly true in cases where there are many









interacting surfaces that can absorb, re-emit, and reflect radiation. The necessary radiation heat transfer coefficients have been tabulated for a variety of fuel rod assemblies by Cox (1977).

The radiation heat transfer from cell n to cell m is computed as

$$q_{RADR}$$
 (m,n) =  $\sigma H_{m,n} (T_n^4 - T_m^4) DZ(K)$ 

The computational-cell index associated with the receiver cell m is (I,J,K); that for the transmitting cell is (I-2 < I < I+2, J-2 < J < J+2, K) [excluding the combination (I,J,K)]. Note that the above definition for  $q_{RADR}$  (m,n) has the DZ(K) portion of the area element explicitly included in the equation. The other length segment making up the surface area has been included in the specification of the radiation heat transfer coefficient,  $H_{m,n}$ . Note further that the Stefan-Boltzmann constant,  $\sigma$  (= 5.67e-12 W/cm²·K⁴), has been extracted from the radiation heat transfer coefficient in this expression. Therefore, the user must account for this when computing the radiation heat transfer coefficients for input to RADR.

#### 13.1 PARAMETER STATEMENT INFORMATION

Aside from the overall grid specification information IP, JP, KP, KBP, and KTP (described in Chapter 4.0), RADR requires information pertaining to the limiting number of cells and radiation heat transfer coefficients in the model. The required data are as follows:

- NHP An array dimension greater than or equal to the maximum number of RADR radiation heat transfer coefficient groups in the model.
- NREGP An array dimension greater than or equal to the maximum number of computational cell regions in the model.

 NT4P - An array dimension greater than or equal to the maximum number of LT4 regions (to be defined in Section 13.2.5) in the model.

Each of these parameters must be set to a value of 1 as a minimum (even when RADR is not used).

# 13.2 INPUT FORMAT

# 13.2.1 Overview

Generally speaking, the input to subroutine RADR can be divided into four subsections:

- descriptive, introductory text
- the radiation heat transfer coefficient array, H
- regional description array, LREG
- array LT4 containing the T⁴ values for the affected computational cells.

A detailed discussion of the input requirements for each of these subsections is provided in the following text.

# 13.2.2 Descriptive, Introductory Text Input

#### General Input Description

- NECHO Echoing switch for this section of input. If
   NECHO = 1, an echo of the input for this section will be provided in the output; if NECHO = 0, this echoing will not be provided.
- NLINES The number of lines of descriptive information to be read (NLINES > 0).
- TEXT A line of descriptive information containing up to 48 characters.

Input File Example

```
324 1/radr/notes
325 2
326 emmitance of rods is 0.8
327 connectors confined to assembly
```

#### Echoed-Input File Example

555radremittance of rods is 0.8556radrconnectors confined to assembly

Input variables NECHO and NLINES are provided on lines 324 and 325, respectively. This is followed by NLINES lines of descriptive text (herein provided on lines 326 and 327). The corresponding echoed-input file is presented as lines 555 through 556. NECHO is set to 1 here to generate an echo of the input. NLINES is set to 2 indicating there are two lines of text to follow. If no descriptive text is desired, set NLINES = 0.

13.2.3 <u>H Array Input</u>

#### General Input Format

IDH, H(1,IDH), H(2,IDH), ..., H(23,IDH), H(24,IDH) ..., H(23,IDH), H(24,IDH) NH-1, H(1,NH-1), H(2,NH-1), ..., H(23,NH-1), H(24,NH-1) NH, H(1,NH), H(2,NH), ..., H(23,NH), H(24,NH)

General Input Description

- NECHO Echoing switch for this section of input. If
   NECHO = 1, an echo of the input for this section will be provided in the output; if NECHO = 0, this echoing will not be provided.
- NH Number of sets of radiation heat transfer coefficients (0 < NH < NHP).</li>
- IDH Identifier for this radiation heat transfer coefficient set (1 < IDH < NH).</li>
  - Array containing the radiation heat transfer coefficients. The first argument refers to the particular cell-to-cell connection. The second argument refers to the coefficient set identifier, IDH. Each coefficient refers to the communication between the cell at location (I,J,K) and one of its 24 neighboring cells. The input sequence follows a specific order indicating the indices of the transmitting cell as follows:

H(1,IDH)	=>	( <i>I</i> +1, <i>J</i> , <i>K</i> ) or h2e
H(2,IDH)	=>	( <i>I,J</i> +1, <i>K</i> ) or h2n
H(3,IDH)	=>	( <i>I</i> -1, <i>J</i> , <i>K</i> ) or h2w
H(4,IDH)	=>	( <i>I,J-</i> 1, <i>K</i> ) or h2s
H(5,IDH)	=>	( <i>I</i> +1, <i>J</i> +1, <i>K</i> ) or h3ne
H(6,IDH)	=>	( <i>I</i> -1, <i>J</i> +1, <i>K</i> ) or h3nw
H(7,IDH)	=>	( <i>I</i> -1, <i>J</i> -1, <i>K</i> ) or h3sw
H(8,IDH)	=>	( <i>I</i> +1, <i>J</i> -1, <i>K</i> ) or h3se
H(9,IDH)	=>	( <i>I</i> +2, <i>J</i> , <i>K</i> ) or h4e
H(10,IDH)	=>	( <i>I,J</i> +2, <i>K</i> ) or h4n
H(11,IDH)	=>	( <i>I-2,J,K</i> ) or h4w
H(12,IDH)	=>	( <i>I,J-2,K</i> ) or h4s
-----------	----	-------------------------------------------------
H(13,IDH)	=>	( <i>I</i> +2,J+1, <i>K</i> ) or h5ene
H(14,IDH)	=>	( <i>I</i> +1, <i>J</i> +2, <i>K</i> ) or h5nne
H(15,IDH)	=>	( <i>I</i> -1, <i>J</i> +2, <i>K</i> ) or h5nnw
H(16,IDH)	=>	( <i>I-2,J+1,K</i> ) or h5wnw
H(17,IDH)	=>	( <i>I</i> -2, <i>J</i> -1, <i>K</i> ) or h5wsw
H(18,IDH)	=>	( <i>I</i> -1, <i>J</i> -2, <i>K</i> ) or h5ssw
H(19,IDH)	=>	( <i>I</i> +1, <i>J</i> -2, <i>K</i> ) or h5sse
H(20,IDH)	=>	( <i>I</i> +2, <i>J</i> -1, <i>K</i> ) or h5ese
H(21,IDH)	=>	( <i>I</i> +2, <i>J</i> +2, <i>K</i> ) or h6ne
H(22,IDH)	=>	( <i>I-</i> 2, <i>J</i> +2, <i>K</i> ) or h6nw
H(23,IDH)	=>	( <i>I-</i> 2, <i>J-</i> 2, <i>K</i> ) or h6sw
H(24,IDH)	=>	( <i>I</i> +2, <i>J</i> -2, <i>K</i> ) or h6se

All 24 radiation heat transfer coefficients <u>must</u> be provided for <u>each</u> coefficient set. If they are not used, the value should be set to 0. The units of H should be cm. RADR cells that connect with phantomcells (e.g., those cells with I or J index of 1) and pseudo-cells (e.g., those cells with I or J index of 0) should have 0 entered for the radiation heat transfer coefficient between them. The modeler must ensure that transmission from image cells is accounted for when symmetry is exploited in a computational model to reduce the number of cells considered in the model. Further discussion of these subtleties is provided below in the example simulation.

The 24 coefficients are organized into five subsets labeled as h2x, h3x, h4x, h5x, and h6x. Compass positions [relative to the cell at (I,J,K)] are used to further identify the coefficient and, in so doing, define the neighboring cell to which this coefficient is related. The compass position (e.g., e, n, ene, ssw) is provided in the "x" suffix of the subset

name. The subset and relative position of each coefficient is illustrated in Figure 13.3. As an example, the radiation heat transfer coefficient between cells (I,J,K) and (I+1,J-2,K) is represented by the entry h5sse. The input sequence given in its general form above, can also be represented by the following sequence for each group:

IDH,h2e,h2n,h2w,h2s,

h3ne,h3nw,h3sw,h3se,

h4e,h4n,h4w,h4s,

h5ene,h5nne,h5nnw,h5wnw,h5wsw,h5ssw,h5sse,h5ese, h6ne,h6nw,h6sw,h6se.

IDH (1 < IDH < NH) identifies the coefficient set. This data is provided, in its entirety, for each of the NH coefficient sets of the model.

### Input File Example

- 328 1/radr/h
- 329 25
- 330 1.0,2*0.171,2*0.0,0.208,3*0.0,2*0.005,2*0.0,2*0.046,6*0.0,4*0.0,
- 331 2.0,0.171,0.388,0.171,0.0,2*0.208,2*0.0,0.005,0.010,2*0.0,3*0.046,5*0.0, 332 4*0.0.
- 333 3.0,0.388,0.171,0.0,0.171,0.208,2*0.0,0.208,0.010,0.005,2*0.0,2*0.046,
- 334 5*0.0,0.046,4*0.0,
- 335 4.0,0.171,0.342,0.171,0.0,2*0.208,2*0.0,0.005,0.010,0.005,0.0,4*0.046,
- 336 4*0.0,4*0.0,
- 337 5.0,0.342,0.171,0.0,0.171,0.208,2*0.0,0.208,0.010,0.005,0.0,0.005,2*0.046, 338 4*0.0,2*0.046,4*0.0,
- 339 6.0,0.171,0.342,0.171,0.0,2*0.208,2*0.0,0.0,0.010,0.005,0.0,0.0,3*0.046,
- 340 4*0.0,4*0.0,
- 341 7.0,0.342,0.171,0.0,0.171,0.208,2*0.0,0.208,0.010,2*0.0,0.005,0.046,5*0.0, 342 2*0.046,4*0.0,
- 343 8.0,0.0,0.342,0.171,0.0,0.0,0.208,2*0.0,0.0,0.010,0.005,0.0,2*0.0,2*0.046, 344 4*0.0,4*0.0,
- 345 9.0,0.342,2*0.0,0.171,3*0.0,0.208,0.010,2*0.0,0.005,6*0.0,2*0.046,4*0.0,
- 346 10.0,4*0.388,4*0.208,2*0.010,2*0.0,3*0.046,4*0.0,0.046,4*0.0,
- 347 11.0,0.388,0.342,0.388,0.342,4*0.208,3*0.010,0.0,5*0.046,2*0.0,0.046,4*0.0,
- 348 12.0,0.342,0.388,0.342,0.388,4*0.208,2*0.010,0.0,0.010,3*0.046,2*0.0,

k	J+2	6/NW	5/NNW	4/N	5/NNE	6/NE	
	J+1	5/WNW	3/NW	2/N	3/NE	5/ENE	
- N -	J	4/W	2/W	•	2/E	4/E	
Â	J-1	5/WSW	3/SW	2/S	3/SE	5/ESE	
	J-2	6/SW	5/SSW	4/S	5/SSE	6/SE	
		I-2	I-1	1	l+1	l+2	

FIGURE 13.3. RADR Heat Transfer Coefficient Notation

349 3*0.046,4*0.0,

350 13.0,0.388,0.342,0.388,0.342,4*0.208,0.0,2*0.010,0.0,0.0,4*0.046,3*0.0,

351 4*0.0,

352 14.0,0.342,0.388,0.342,0.388,4*0.208,0.010,2*0.0,0.010,0.046,4*0.0,3*0.046, 353 4*0.0,

354 15.0,0.0,0.342,0.388,0.342,0.0,2*0.208,0.0,0.0,2*0.010,0.0,2*0.0,3*0.046, 355 3*0.0,4*0.0,

356 16.0,0.342,0.0,0.342,0.388,2*0.0,2*0.208,0.010,2*0.0,0.010,5*0.0,3*0.046, 357 4*0.0,

358 17.0,4*0.342,4*0.208,4*0.010,8*0.046,4*0.0,

359 18.0,4*0.342,4*0.208,0.0,3*0.010,0.0,6*0.046,0.0,4*0.0,

361 20.0,4*0.342,4*0.208,2*0.0,2*0.010,3*0.0,4*0.046,0.0,4*0.0,

```
362 21.0,0.0,3*0.342,0.0,2*0.208,0.0,0.0,3*0.010,2*0.0,4*0.046,2*0.0,4*0.0,
363 22.0,0.342,0.0,2*0.342,2*0.0,2*0.208,0.010,0.0,2*0.010,4*0.0,4*0.046,4*0.0,
364 23.0,0.0,3*0.342,0.0,2*0.208,0.0,2*0.0,2*0.010,3*0.0,3*0.046,2*0.0,4*0.0,
365 24.0,0.342,0.0,2*0.342,2*0.0,2*0.208,2*0.0,2*0.010,4*0.0,3*0.046,0.0,4*0.0,
366 25.0,2*0.0,2*0.342,2*0.0,0.208,0.0,2*0.010,4*0.0,2*0.046,2*0.0,4*0.0,
```

# Echoed-Input File Example

558	radr	oh= 2	25 r	maximum cur	rent dimens	lon for nh	ls 25				
559	radr	h									
560			nh	h2e(nh)	h2n(nh)	h2w(nh)	h2s(nh)	h3ne(nh)	h3ow(ob)	h3sw(nh)	h3se(nh)
561			1	0.1710+00	0.1710+00	0.0000+00	0.0000+00	0.2080a+00	0.0000+00	0.0000+00	0.0000e+00
562			2	0.1710e+00	0.3880e+00	0.1710+00	0.0000e+00	0.2080++00	0 2080+00	0.00000+00	0.00000+00
563				0.3880e+00	0.1710a+00	0.0000+00	0 1710+00	0 2080+00	0.0000+00	0.00000+00	0.2090e+00
564			Á	0 1710e+00	0 3420a+00	0 1710+00	0.00000+00	0 2080-+00	0.20800+00	0.00000+00	0.20000+00
565			5	0 3420+00	0.1710-+00	0.0000+00	0.1710-+00	0.20000+00	0.20000+00	0.00000+00	0.000000000
565				0.17100+00	0.1/100-00	0.1710-+00	0.17100+00	0.20000+00	0.00000+00	0.00008400	0.20000+00
500				0.1/100+00	0.34200+00	0.17108+00	0.0000000000	0.20509700	0.20808+00	0.0000e+00	0.00006+00
501				0.34208100	0.1/108+00	0.00008+00	0.17106+00	0,20500+00	0.0000000000	0.0000e+00	0,20800+00
200			8	0.00000+00	0.34208+00	0.1/100+00	0.00000+00	0.00000+00	0.2080e+00	0,0000e+00	0.0000e+00
709			9	0.54208+00	0.00000+00	0.0000e+00	0.17100+00	0.00000+00	0.0000e+00	0.0000e+00	0.2080.+00
570			10	0.38800+00	0.3880e+00	0.3880e+00	0,3880e+00	0.2080e+00	0.2080e+00	0.2080e+00	0.2080e+00
571			11	0,3880e+00	0,3420e+00	0,3880e+00	0.34200+00	0.2080e+00	0.2080e+00	0.20800+00	0.2080e+00
572			12	0.3420e+00	0,3880e+00	0.3420e+00	0.3880e+00	0,2080+00	0.2080e+00	0.2080e+00	0.2080e+00
573			13	0.38800+00	0.34200+00	0,3880e+00	0.34200+00	0.2080e+00	0.2080e+00	0.2080e+00	0.2080e+00
574			- 14	0.3420+00	0.3880+00	0.3420e+00	0.3880e+00	0.2080e+00	0.20800+00	0.2080e+00	0.20800+00
575			15	0.00000+00	0.3420e+00	0,38800+00	0.3420e+00	0.0000e+00	0.2080e+00	0.2080+00	0.0000e+00
576			16	0.3420+00	0.0000a+00	0,3420+00	0,3880+00	0.0000e+00	0.0000e+00	0.2080+00	0.2080e+00
577			17	0.3420+00	0.3420+00	0.34200+00	0,3420+00	0.2080+00	0.2080+00	0.2080+00	0.2080a+00
578			18	0.3420+00	0.3420+00	0.3420e+00	0.3420+00	0.2080+00	0.2080+00	0.2080+00	0.2080a+00
579			19	0.3420+00	0.3420+00	0.3420+00	0.3420+00	0.2080+00	0.2080e+00	0.2080a+00	0.2080e+00
580			20	0.3420e+00	0.3420e+00	0.3420+00	0.3420+00	0.2080a+00	0.2080e+00	0.2080a+00	0.2080a+00
581			21	0.0000e+00	0.3420+00	0.3420+00	0.3420e+00	0.0000e+00	0.2080++00	0.2080++00	0.0000a+00
582			22	0.3420e+00	0.0000+00	0.3420e+00	0 34200+00	0.00000+00	0.0000+00	0 2080++00	0 20800+00
583			23	0.00000+00	0.34200+00	0.34200+00	0 \$4200+00	0.000000000	0.200000100	0.20000-00	0.20000+00
584			24	0.3420e+00	0.0000+00	0.34200+00	0.34200+00	0.00000+00	0.20000-100	0.20000+00	0.0000000000
585			25	0.0000+00	0.00000+00	0.34200+00	0.34200+00	0.000000000	0.00008+00	0.20000-100	0.20800+00
596			25	0.0000000000	0.0000000000	0.34208400	0.34208+00	0.0000000000	0.00008+00	0.20808+00	0.000000+00
597				bd. a ( a b )	b4= (-b)	h4 . ( - h )					
500				0 5000- 02	040(00)	04W(00)	n45(//n/)				
500				0.50000-02	0.50008-02	0.00000+00	0.00000+00				
509			2	0.50008-02	0.10008-01	0.0000e+00	0.0000e+00				
590			2	0.10008-01	0.50008-02	0.0000e+00	0.0000e+00				
591			4	0.50008-02	0,1000e-01	0,5000e-02	0.0000e+00				
592			5	0.1000e-01	0.50000-02	0.0000e+00	0.50000-02				
593			6	0.0000e+00	0.1000e-01	0,5000e-02	0.0000e+00				
594			7	0.1000 <del>0-</del> 01	0.0000e+00	0.0000e+00	0.5000e-02				
595			8	0.0000e+00	0.1000a-01	0.50000-02	0.0000e+00				
596			9	0.1000 <del>a-</del> 01	0.0000e+00	0.0000e+00	0.50008-02				
597			10	0.1000e-01	0.1000e-01	0.0000e+00	0.0000e+00				
598			11	0.1000a-01	0.1000e-01	0.1000e-01	0.0000e+00				
599			12	0.1000e-01	0.1000e-01	0.0000e+00	0.10008-01				
600			13	0.0000e+00	0.1000e-01	0.10008-01	0.0000e+00				
601			14	0.10000-01	0.0000+00	0.0000+00	0.1000e-01				
602			15	0.0000e+00	0.1000-01	0.1000-01	0.0000e+00				
603			16	0.1000e-01	0.0000+00	0.0000+00	0.10008-01				
604			17	0.1000-01	0.10008-01	0.1000=-01	0.1000e-01				
605			18	0_0000e+00	0.1000a-01	0.1000a-01	0.1000e-01				
606			19	0.10008-01	0.0000e+00	0.10008-01	0.1000e-01				
607			20	0_0000e+00	0.0000e+00	0.10008-01	0 1000e-01				
608			21	0.0000+00	0 10000-01	0 10000-01	0 10000-01				
609			22	0 1000-01	0.00000+00	0.1000-01	0.10000-01				
610			22	0.0000-01	0.00000+00	0.10008-01	0.10000-01				
611			23	0.000000000	0.00008700	0.10009-01	0.10008-01				
511			24	0.0000000000	0.00008+00	0.10008-01	0.10008-01				
012			25	0.000000+00	0.00000+00	0.10008-01	0.1000e-01				
013											
514			nh	h5ene(nh)	h5nne(nh)	h5nnw(nh)	h5wnw(nh)	h5wsw(nh)	h5ssw(nh)	h5sse(nh)	h5ese(nh)
615			1	0.4600e-01	0.4600e-01	0.0000e+00	0.0000a+00	0.0000e+00	0.0000+00	0.00000+00	0 <b>.</b> 0000 <del>.</del> 0
516			2	0.4600e-01	0.4600e-01	0.46000-01	0.000e+00	0.0000e+00	0.0000e+00	0.0000e+00	0.0000 <del>.</del> 00
617			3	0.46000-01	0.4600e-01	0.0000+000	0.00000+00	0.0000e+00	00+e0000.0	0.0000e+00	0.4600a-01
618			4	0.4600e-01	0.4600e-01	0.46000-01	0.4600e-01	0.0000e+00	0.0000e+00	0.00000+00	0.0000e+00
6 19			5	0.4600e-01	0.4600e-01	0.0000e+00	0.0000e+00	0.0000e+00	0.0000e+00	0.4600e-01	0_4600e-01
620			6	0.0000e+00	0.46000-01	0.46000-01	0.4600e-01	0.0000e+00	0.0000e+00	0.0000+00	0.0000e+00
521			7	0.4600e-01	0.0000e+00	0.0000e+00	0.0000e+00	0.0000e+00	0.0000e+00	0.4600 <del>e-01</del>	0.4600a-01
622			8	0.0000e+00	0.0000e+00	0.46000-01	0.46000-01	0.0000e+00	0.00000+00	0.00000+00	0.0000e+00
623			9	0.0000e+00	0.0000e+00	0.0000+00	0.0000e+00	0.0000e+00	0.00000+00	0.46000-01	0.46008-01
624			10	0.4600e-01	0.46000-01	0.46000-01	0.0000e+00	0.00000+00	0.0000e+00	0.0000e+00	0.4600e-01
625			11	0.46000-01	0.4600e-01	0.4600e-01	0.4600-01	0.4600e-01	0.0000e+00	0.0000e+00	0.4600e-01

526 1	2 0.46000-01	0.4600e-01	0.4600e-01	0_0000e+00	0_0000+00	0_4600e-01	0_4600e-01	0.46009-01
627 1	3 0.00000+00	0.46000-01	0.46008-01	0.4500e-01	0.4600e-01	0.0000e+00	0.00000+00	0.0000+00
628 1	4 0.46000-01	0.0000e+00	0.0000+00	0.0000e+00	0.0000e+00	0.4600e-01	0.46009-01	0.4600e-01
629 I	5 0.00000+00	0.0000e+00	0.46000-01	0.4600e-01	0.46009-01	0.00000+00	0.0000e+00	0.0000e+00
530 1	5 0.0000e+00	0.0000e+00	0.00000+00	0.0000+00	0.00000+00	0.4600e-01	0.46009-01	0.4600e-01
631 1	7 0.46000-01	0.46000-01	0.46009-01	0.46008-01	0.46000-01	0.4600e-01	0.4600e-01	0.4600e-01
632 1	3 0.0000e+00	0.4600e-01	0.46000-01	0.4600e-01	0.46000-01	0.4600e-01	0.46000-01	0.0000e+00
633 1	0.4600e-01	0_0000e+00	0.00000+00	0,46000-01	0.46008-01	0.46000-01	0.46000-01	0.46000-01
634 2	0.0000e+00	0.0000e+00	0.00000+00	0.46000-01	0.46000-01	0.4600e-01	0.46000-01	0.0000e+00
635 2	0.00000+00	0.0000e+00	0.4600e-01	0.4600e-01	0.4600e-01	0.4600e-01	0.00000+00	0.0000e+00
636 22	0.00000+00	0.0000e+00	0.0000e+00	0.0000e+00	0.46000-01	0.46000-01	0.4600e~01	0.4600e-01
637 2	0.0000e+00	0.0000e+00	0.0000e+00	0.4600e-01	0.46009-01	0.4600e-01	0.0000e+00	0.0000e+00
638 24	0.0000+00	0.0000e+00	0.0000e+00	0.0000e+00	0.46000-01	0.4600e-01	0.46009-01	0.0000e+00
639 25	0.0000e+00	0.0000e+00	0.0000e+00	0.0000e+00	0.46000-01	0.4600e-01	0.0000e+00	0.0000 <del>0</del> +00
640								
641 ni	i h6ne(nh)	h6nw(nh)	h6sw(nh)	h6se(nh)				
642	0.0000a+00	0.0000e+00	0.0000+00	0.00000+00				
643	00+e0000e+00	0.0000e+00	0.0000e+00	0.0000e+00				
544	0.00000+00	0.0000e+00	0.0000e+00	0.0000e+00				
645	0,0000e+00	0.0000e+00	0.0000e+00	0.0000e+00				
646	0.00000+00	0.00000+00	0.0000e+00	0.0000e+00				
647	5 0.0000e+00	0.0000e+00	0.0000e+00	0.0000e+00				
648	0,0000+00	0.0000e+00	0.0000e+00	0.0000e+00				
649	3 0 <b>.</b> 0000 <del>0</del> +00	0.0000e+00	0.0000e+00	0.0000e+00				
650	0.00000+00	0.0000e+00	0.00000+00	0.0000e+00				
651 10	0.00000+00	0.0000+00	0.00000+00	0.0000e+00				
652 1	0.00000+00	0.00000+00	0.00000+00	0.0000e+00				
653 I	0 <b>.0000e+00</b>	0.0000e+00	0.00000+00	0.0000e+00				
654 13	0.0000e+00	0.0000e+00	0.0000e+00	0.0000e+00				
655 14	0.00000+00	0.0000e+00	0.0000e+00	0.0000e+00				
656 1	0.0000e+00	0.00000+00	0.0000e+00	0.0000e+00				
657 10	0.00000+00	0,0000e+00	0.00000+00	0.0000e+00				
658 1	0.0000e+00	0,00000+00	0.00000+00	0.0000e+00				
659 16	0.0000e+00	0.0000e+00	0.00009+00	0.0000e+00				
660 19	0.0000e+00	0.0000e+00	0.0000e+00	0.0000e+00				
661 20	0.0000e+00	0.0000e+00	0.0000e+00	0.0000e+00				
662 2	0.0000e+00	0.0000e+00	0.00000+00	0.00000+00				
663 22	2 0.0000+00	0.0000e+00	0.0000e+00	0.0000e+00				
664 21	0.0000e+00	0.0000e+00	0.00000+00	0.0000e+00				
665 24	0.0000e+00	0.0000e+00	0.00000+00	0.00000+00				
666 21	0.0000e+00	0,0000e+00	0.0000e+00	0.00000+00				

Radiation heat transfer coefficient information is provided next in the input file. In this model, NECHO is set to 1 on input line 328. Thus, the input to this section will be echoed in the output listing.

The radiation heat transfer coefficient information is divided into sets of 24 coefficients corresponding to the 24 neighboring cells. The number of sets provided in the model, NH (0 < NH < NHP), is entered next in the input. For this model, input line 329 indicates that there are 25 such sets. The echoed input is provided in line 558 of the output listing.

Each set represents the exchange between a typical computational cell location identified by indices (I,J,K) and its 24 neighboring cells located

within the range (I-2 < I < I+2, J-2 < J < J+2, K). In this way, several regions of the model can reference the same set of heat transfer coefficients without having to be retyped as input.

Radiation heat transfer coefficients representing communication of a computational cell with phantom and/or pseudo cells should be assigned a zero value. This situation is typically encountered in those cells residing within a distance of two cells from a symmetry condition or computational-mesh boundary. The temperature associated with these phantom and pseudo cells may be fictitious. Consequently, these cells must be effectively excluded from the computation. In models exploiting a symmetry condition of the problem, the RADR radiation heat transfer coefficients must include the effect of heat transfer with the image cells residing outside the computational domain. This same concern is discussed in detail in Section 11.2.7.

Lines 330 through 366 of the input present the radiation heat transfer coefficient information for this model. The echoed input generated is presented in output lines 559 through 666.

# 13.2.4 LREG Array Input Section

General Input Format

- IDH Radiation heat transfer coefficient set identifier (1 < IDH < NH).</li>
- IBEG Beginning I index of the region for which IDH applies.
- IEND Ending I index of the region for which IDH applies.
- JBEG Beginning J index of the region for which IDH applies.
- JEND Ending J index of the region for which IDH applies.
- KBEG Beginning K index of the plane.
- KEND Ending K index of the plane.

# Input File Example

367 1/radr/lreg 368 25 369 1,1,2,2,2,2,2,23, 370 2,2,3,3,2,2,2,23, 371 3,3,2,2,3,3,2,23, 372 4,4,4,7,2,2,2,23, 373 5,5,2,2,4,7,2,23, 374 6,6,8,8,2,2,2,23, 375 7,7,2,2,8,8,2,23, 376 8,8,9,9,2,2,2,2,3, 377 9,9,2,2,9,9,2,23, 378 10,10,3,3,3,3,2,23, 379 11,11,4,7,3,3,2,23, 380 12,12,3,3,4,7,2,23, 381 13,13,8,8,3,3,2,23, 382 14,14,3,3,8,8,2,23, 383 15,15,9,9,3,3,2,23, 384 16,16,3,3,9,9,2,23, 385 17,17,4,7,4,7,2,23, 386 18,18,8,8,4,7,2,23, 387 19,19,4,7,8,8,2,23, 388 20,20,8,8,8,8,2,23, 389 21,21,9,9,4,7,2,23, 390 22,22,4,7,9,9,2,23, 391 23,23,9,9,8,8,2,23, 392 24,24,8,8,9,9,2,23, 393 25,25,9,9,9,9,2,23

### Echoed-Input File Example

668	radr	nreg= 25	maximum cu	irrent dimension	for nre	sg is	25			
669	radr	lreg	region	radiation		c	el I le	ocatio	ก	
670			number	type (nh)	ibeg	iend	jbeg	jend	kbəg	kend
671			1	1	2	2	2	2	2	23
672			2	2	3	3	2	2	. 2	23
673			3	3	2	2	3	3	2	23
674			4	4	4	7	2	2	2	23
675			5	5	2	2	4	7	2	23
676			6	б	8	8	2	2	2	23
677			7	7	2	2	8	8	2	23
678			8	8	9	9	2	2	2	23
679			9	9	2	2	9	9	2	23
680			10	10	3	3	3	3	2	23
681			11	11	4	7	3	3	2	23
682			12	12	3	3	4	7	2	23
683			13	13	8	8	3	3	2	23
684			14	14	3	3	8	8	2	23
685			15	15	9	9	3	3	2	23
686			16	16	3	3	9	9	2	23
687			17	17	4	7	4	7	2	23
688			18	18	8	8	4	7	2	23
689			19	19	4	7	8	8	2	23
690			20	20	8	8	8	8	2	23
691			21	21	9	9	4	7	2	23
692			22	22	4	7	9	9	2	23
693			23	23	9	9	8	8	2	23
694			24	24	8	8	9	9	2	23
695			25	25	9	9	9	9	2	23

The portions of the model over which RADR radiation heat transfer is simulated are segregated into regions. Each region is assigned a number, NREG  $(1 \le NREG \le NREGP)$ , as well as an identifier for the set of heat transfer coefficients IDH  $(1 \le IDH \le NHP)$ . In addition, an index range is provided in this input file to identify the indices I, J, and K to which the coefficient set associated with IDH applies. For each K-plane in the specified K-range, RADR will sweep (in the FORTRAN sense) over the I and J index ranges using the radiation heat transfer coefficients in set IDH to compute the radiation energy transferred between each (I,J,K) cell and its 24 neighboring cells. The regions and participating cells of this model are illustrated in Figures 13.4 and 13.5.

The input required by RADR to effect this result is provided in this section. An example of this input is provided in Section 13.2.3 as input lines





FIGURE 13.4. Transverse Computational Mesh Illustrating I-Cell and J-Cell Levels of the RADR Model (Encircled numbers indicate model region numbers)





FIGURE 13.5. Axial Computational Mesh Illustrating K-Cell Levels of the RADR Model

367 through 393. The input to this section is initiated by assigning a value to NECHO. For the input file example, this is done on input line 367.

The number of regions in the model, NREG (0 < NREG < NREGP), is provided next in the input file (input line 368 for this example). As indicated, the remaining input to this section follows the general format:

#### IREG, NH, IBEG, IEND, JBEG, JEND, KBEG, KEND.

Input variable IREG identifies the region number (1 < IREG < NREG). The cells assigned to this region of the RADR model will use the radiation heat transfer coefficients identified in coefficient set NH. The I, J, and K ranges are next provided as indicated above. Note that, since RADR sweeps over the cells in this range in the FORTRAN sense, radiation heat transfer will be computed for every cell in this range.

### 13.2.5 LT4 Array Input

For computational reasons, subroutine RADR computes the  $T^4$  terms for all participating cells in the radiation model. As with the input of the preceeding section, the participating cells are divided into regions. The cell indices associated with these regions are loaded into the LT4 array. The cells of a region in this input section are not constrained to share a common set of radiation heat transfer coefficients. Therefore, the number of cells in an LT4 region can be greatly increased. This reduces the amount of input required. The cells identified in this input must, however, "cover" every participating cell of the RADR model.

### General Input Format

NECHO NT4 1,IT4BEG,IT4END,JT4BEG,JT4END,KT4BEG,KT4END 2,IT4BEG,IT4END,JT4BEG,JT4END,KT4BEG,KT4END IT4,IT4BEG,IT4END,JT4BEG,JT4END,KT4BEG,KT4END

# NT4-1, IT4BEG, IT4END, JT4BEG, JT4END, KT4BEG, KT4END NT4, IT4BEG, IT4END, JT4BEG, JT4END, KT4BEG, KT4END

# General Input Description

•	NT4	-	Number of T4 regions in the model (0 < NT4 < NT4P).
٠	IT4	-	T4 region identifier (1 < IT4 < NT4).
٠	IT4BEG	-	Beginning I index of the T4 region.
٠	IT4END	-	Ending I index of the T4 region.
٠	JT4BEG	-	Beginning J index of the T4 region.
٠	JT4END	-	Ending J index of the T4 region.
•	KT4BEG	-	Beginning K index of the T4 region.
٠	KT4END	-	Ending K index of the T4 region.
	Input File	Exar	nple
394 305	1/radr/lt4		
396	1,2,9,2,9,2,	,23	
	Echoed-Inpu	it F	ile Example
697 698 699 700	radr nt4 radr 1t4	1= 1 1	maximum current dimension for nt4 is 1 region cell location number ibeg iend jbeg jend kbeg kend 1 2 9 2 9 2 23

NECHO is set to a value of 1 on input line 394. The index ranges for the participating cells of the RADR model are stored in array LT4. NT4, the number of regions into which the RADR model is subdivided for loading LT4, is provided next in the input file. For this model, NT4 is set to 1 on input line 395. This is reflected in the echoed input on output line 697.

As indicated above, the remaining input to this section has the general form

IT4, IBEG, IEND, JBEG, JEND, KBEG, KEND.

IT4 (1 < IT4 < NT4) is the region number for this set of indices comprising the computational cells (I,J,K) where IBEG < I < IEND, JBEG < J < JEND, and KBEG < K < KEND. This input is presented in input line 396 for the model discussed herein. The corresponding echoed input is presented in output lines 698 through 700.

# 13.2.6 Discussion of Input Example

To aid understanding of the interconnection between the input sections of this routine, consider LREG region number 1 in Figure 13.4. This region represents a portion of the computational domain swept-out by cells (2,2,2 <K < 23) - essentially a pencil of cells located at (I = 2, J = 2) and covering K planes 2 through 23. RADR will compute the radiation heat transfer between each of the neighboring 24 cells in the range (0 < I < 4, 0 < J < 4, K) and the cell at (2,2,K) for each of the 22 K-planes. The radiation heat transfer coefficients used in these computations are carried in the first coefficient set (NH = 1). Thus, for example, the radiation heat transfer coefficient used for communication between cells  $(2,4,\kappa)$  and  $(2,2,\kappa)$  is identified as h4n(1) =0.005; that between cells (4,4,K) and (2,2,K) is hone = 0. Initialization of the T⁴ temperatures for the participating cells of this region are "covered" in LT4 region number 1. Note that the phantom cells (index I or J = 1) and some pseudo-cells (index I or J = 0) are included in the LREG region. These cells are not "covered" by the LT4 region. The "temperature" for each of these cells is therefore set to zero by the initialization procedure. However, their effect is excluded from the RADR model by the zero entries in the radiation heat transfer coefficients  $h_{2w}(1)$ ,  $h_{2s}(1)$ ,  $h_{3nw}(1)$ ,  $h_{3sw}(1)$ ,  $h_{3se}(1)$ ,  $h_{4w}(1)$ , h4s(1), h5nnw(1), h5wnw(1), h5wsw(1), h5ssw(1), h5sse(1), h5ese(1), h6nw(1), h6sw(1), and h6se(1). Due to the quarter symmetry exploited in this problem, some of these cell locations do coincide with image cells. For example, coefficient h3ne(1) must include the effect of the communication between cell (3,3,K) and (2,2,K) and its image energy-flow path, (1,1,K) and (2,2,K).

As in subroutine RADC, the matrix of heat transfer coefficients must be symmetric to ensure energy conservation. For example, the radiation heat transfer coefficient used in computing the energy received by the cell at

(8,8,K) from the cell at (7,6,K) [h5ssw(20) = 0.046] must equal that used in computing the energy received by cell (7,6,K) from cell (8,8,K) [h5nne(17) = 0.046].

# 13.2.7 Input Example When RADR Is Not Used

If subroutine RADR is not used in the simulation, then only the following lines of input are required:

1/radr
0
1/radr/h
0
1/radr/lreg
0
1/radr/lt4
0

#### 14.0 SUBROUTINE REBA

Subroutine REBA provides an optional procedure for acceleration of the energy equation solution when a steady state is sought.

#### 14.1 REBA FUNCTIONS

REBA solves steady-state energy balance equations on a coarse mesh made up of three regions in each of the KP-2 active computational K-planes. The three regions at a given K-plane are the rectangular grid region, the interface cells, and the cylindrical grid region.

The merits and constraints of a coarse-mesh solution of the energy equation in accelerating progress toward steady state were discussed in Chapter 7.0, Subroutine REBT. Some admonitions there are also applicable to use of REBA. Use of REBA should be deferred until enough time-steps are taken that properties and flows have "settled down" somewhat to near-physical values. The axially coupled three-radial-region solutions in REBA are sufficiently effective, however, in achieving a rough temperature distribution that its use is recommended for simulations that use both the rectangular and cylindrical grid features.

The pattern of calls to REBA is set in Program MAIN by input variables REBAON, NREB, and NREBN. The user may find it advantageous to monitor the progress toward the steady-state solution before and after use of REBA by looking at the maximum temperature change per time-step, and also by looking at power balance information that can be calculated and printed by Subroutine QINFO. See Chapters 15.0 and 29.0 for the QINFO features.

A feature provided in REBA to avoid potential overcompensation is a maximum allowable magnitude for the temperature change from the REBA coarse-mesh solution. If in a given K-plane a temperature change  $\delta T'$  is calculated for one of the three regions, the amount of temperature change  $\delta T$  added to the evolving temperatures for that region is

 $\delta T = SIGN(MIN(ABS(\delta T'), DTMAX), \delta T')$ 

where the FORTRAN SIGN function gives the algebraic sign of the second argument ( $\delta T'$  in this case) to the magnitude of the first argument (the smaller of  $|\delta T'|$  and DTMAX, in this case).

A printout option in REBA allows displaying "divergence error" quantities. In REBA, a divergence error for a cell is calculated by net heat flow into the cell, which should be zero in steady state. The divergence error quantities printable in REBA are the sums of divergence errors over the regions (rectangular, boundary, and cylindrical) of a K-plane. The largest sum for any K-plane for each region can be printed.

# 14.2 PARAMETER STATEMENT INFORMATION

Parameters appearing in subroutine REBA that were discussed in Chapter 4.0, Subroutine GRID, include:

# IP, JP, KP, ISP, JSP, KBP, KTP

Additional dimensioning parameters in subroutine REBA that are discussed in Chapter 25.0, Subroutine CROUT, include:

# ICRP, JCRP

### 14.3 INPUT FORMAT

# 14.3.1 Overview

The schedule for calls to REBA is set in Program MAIN. The input here sets a maximum allowable temperature change from the coarse grid solution, and also sets the level of printout desired.

# 14.3.2 REBA Input Block

General Input Format

NECHO DTMAX,INFO

#### General Input Description

- NECHO Echoing switch for this section of input. If input is to be echoed, then NECHO = 1; otherwise, 0.
- DTMAX The upper bound on the magnitude of the temperature change to add for any of the three regions at a K-plane from the coarse-mesh solution.
- INFO An integer flag variable for printout of results. If INFO = 1, REBA will report the K-plane at which the divergence error sum is largest for each of the three regions (rectangular grid, interface cells, cylindrical grid) and the value of that divergence error sum. Note that calculating this information takes some (though not major) effort, so it should be done only as needed. If INFO = 0, this information is not reported.

Input File Example

1591 1/reba 1592 20.0,1

Echoed Input File Example

949 950 reba dtmax=0.200e+02 info=1 951

The input file asks for echoing (line 1591), sets maximum temperature change in a region to  $20^{\circ}$ C (line 1592), and asks for a printout of divergence error information with INFO = 1 on line 1592. A typical line of divergence error information printed in response to INFO = 1 on a call to REBA is:

reba info=1 dimax=-0.371e-01 dimax= 0.402e-01 ki=30 dbmax=0.133e-01 kb=15 dsmax= 0.386e-08 ks= 3

This REBA printout line gives the maximum temperature change DTMAX that actually occurred in the current call to REBA, the maximum divergence error DIMAX for the interior (rectangular grid) region, the K-plane KI = 30 where it occurred, the maximum divergence error DBMAX for the boundary or interface region, the K-plane KB = 15 where it occurred, the maximum divergence DSMAX on the side or cylindrical grid region, and the K-plane KS = 3 where it occurred.

# 15.0 SUBROUTINE QINFO

At the conclusion of a run, a user may optionally print net heat flows to various portions of the cask and heat fluxes in the inside of the cask. Subroutine QINFO implements the process of determining heat flows using geometrical information and current temperatures and thermal resistances.

### 15.1 PARAMETER STATEMENT INFORMATION

Subroutine QINFO requires the specification of parameters IP, JP, KP, KBP, and KTP. These parameters define the overall computational mesh and are described in Chapter 4.0, Subroutine GRID. No additional parameters are needed in Subroutine QINFO.

# 15.2 INPUT FORMAT

Subroutine QINFO does not read information from the input file. No user attention is required other than selecting appropriate input file options as described in Chapter 3.0, Program MAIN.

#### 16.0 SUBBROUTINE HYDRO

This subroutine serves as a gateway to all other subroutines required for the solution of the fluid momentum and continuity equations. Subroutine HYDRO is always called in the initialization phase of a run to set a number of constants and arrays. If a momentum solution is desired, then this subroutine is called once each time-step to update temperature-dependent properties, call other subroutines, and provide diagnostic information.

The first operation undertaken in this subroutine is to read the input file. The information contained on the input file includes:

- minimum and maximum allowed values of the momentum time-step
- reference pressure, temperature, and density for the gas within the cask
- gravitational vector orientation with respect to the cask
- temperature dependence of gas viscosity
- viscosity specifications to account for fluid flow obstructions and free-slip boundary conditions
- provision to monitor selected mass fluxes during a run.

The above information must be on the input file even if a momentum solution is not desired, to satisfy list-directed read requirements. If no momentum solution is desired, such as for a conduction-only application, then the information on the input file need not represent a physically realizable system.

There are certain other control parameters on the input file that relate to simulating transient applications. This documented version of the code is, however, intended for only steady-state applications. To allow for potential future extension of the code and its documentation, input specifications relating to a transient mode of operation have been retained. In the general input descriptions in this chapter, parameters related to the transient mode are identified, a brief indication of the function given, and the appropriate value to be used is provided.

If a solution to the momentum and continuity equations is desired (enabled by setting NOVEL = 0 in Program MAIN), then subroutine HYDRO will call the appropriate subroutines once each time-step. The calling sequence is:

- subroutine MOMX, MOMY, and MOMZ (Chapter 19.0) for solution of tilde mass fluxes - Tilde mass fluxes are tentative mass fluxes that do not yet satisfy continuity because they are based on old-time pressures.
- subroutine PDG (Chapter 20.0) for computation of the divergence error of the tilde mass fluxes and construction of the discrete form of the continuity equation
- subroutine PITER (Chapter 21.0), which directs the solution of the continuity equation expressed in terms of pressure changes.

After satisfaction of the pressure (continuity) equation, the pressure changes are returned to subroutine HYDRO to update the tilde mass fluxes so that they satisfy conservation of mass. The next momentum time-step is computed automatically based on the current time-step, the tilde mass-flux continuity error, and the computational effort required to satisfy the pressure (continuity) equation. The new time-step may be adjusted up or down to meet the specified optimum tilde mass-flux continuity error and specified optimum computational cycles for the pressure equation. Finally, those mass fluxes designated for monitoring are sent to the output file.

#### 16.1 PARAMETER STATEMENT INFORMATION

Subroutine HYDRO requires the specification of parameters IP, JP, KP, KBP, and KTP. These parameters define the overall computational mesh and are described in Chapter 4.0, Subroutine GRID. Four additional parameters, local to this subroutine, are required for specification of fluid viscosities and printing options:

 NREGP - This parameter is used to dimension an array that holds information about regions of computational cells requiring special treatment of viscosity. The details of this special treatment are given in Section 16.2.3. NREGP should be greater than or equal

to the number of regions. If no special regions are required, then NREGP should equal 1.

 MONMXP, - Three parameters, each greater than or equal to 1, MONMYP, that allow storage for mass fluxes mx, my, and/or mz to be monitored at designated computational cells. For example, if MONMXP = 4, then it is possible to print mass fluxes in the x-direction every time-step at up to four different locations. See Section 16.2.2 for further details.

### 16.2 INPUT FORMAT

#### 16.2.1 Run Control Information

This section of input provides some of the information needed for operation of the momentum solution. Basic gas properties and gravitational vector orientation are also specified here. The input file must be constructed as shown, to satisfy list-directed read requirements--even if no momentum solution is required.

General Input Format

NECHO CONVEK,EPSCON,MITMAX,THETAM,WM,ESTPF NDTYME,DTYMEN,DTYMAX NEWGAS,NEWVEL,EXTRAV PFREF,TFREF,DFREF GX,GY,GZ CVISA,CVISB

General Input Description

- NECHO Echoing switch for this section of input. If input is to be echoed, then NECHO = 1; otherwise, 0.
- CONVEK The convection of momentum terms may be deleted from the linear momentum equations if desired. The terms deleted are ∇・(求前) where 求 is the velocity and 南 is

the mass flux. The terms are included if CONVEK = 1.0; they are deleted if CONVEK = 0.0.

- EPSCON The maximum allowable continuity error to be permitted if both momentum and continuity equations are to be satisfied each time-step. This option is intended for transient applications; therefore, EPSCON should be set equal to 0.0.
- MITMAX The maximum number of solution cycles permitted to satisfy both momentum and continuity equations each time-step. This option is intended for transient applications; therefore, MITMAX should be set equal to 0.
- THETAM New-time tilde mass fluxes may be computed based on a mixture of old-time mass fluxes and new-time tilde mass fluxes. THETAM sets the relative weighting and should have the value of 0.5 for steady-state applications.
- WM A weighting factor in the momentum equations intended for switching between transient and steady-state modes of operation. A value of 1.0 is to be used for the steady-state mode.
- ESTPF This constant is used to estimate new-time pressures according to the expression

$$p = p + estpf * \frac{\delta t}{\delta t_{old}} (p - p_{old})$$

The momentum equations and the continuity (pressure) equation are not solved simultaneously; thus, the coupling is explicit. Slight underrelaxation is, at times, beneficial for stability. The value shown on the input file example for estpf, -0.05, is usually satisfactory. A best value is application-specific, and, if necessary, is determined by trial.

- NDTYME If a new momentum time-step is desired at the start of a run, then ndtyme = 1; otherwise, ndtyme = 0. If the run is started without a restart tape, then ndtyme = 1.
- DTYMEN The value of the new initial momentum time-step.
- DTYMAX The maximum value of the momentum time-step. DTYMAX will normally not exceed 1.0, and may be less for steady-state applications.
- NEWGAS A switch that enables changing gas properties at the start of a run for transient applications. NEWGAS should be set to 0 for steady-state applications.
- NEWVEL This constant, if equal to 1, will set all mass fluxes to zero at the start of any run. No action is taken if NEWVEL equals 0.
- EXTRAV If EXTRAV has a value different from 1.0, then all mass fluxes are reset at the start of any run according to the expression m = EXTRAV * m. The new mass fluxes still satisfy continuity.
- PFREF, Reference pressure, temperature, and density for TFREF, the gas, used in the code to compute density according DFREF to an equation of state,

$$\rho = \left(\frac{\rho T}{p}\right) \frac{p}{ref}$$

- GX, GY, GZ The components (direction cosines) of the gravitational vector along the three cartesian coordinate axes. The cartesian coordinate system is fixed relative to the cask body.
- CVISA, CVISB The constants in the temperature-dependent equation for the viscosity of the gas,

 $\mu$  = CVISA + CVISB * T

Input File Example

1593 1/hydro 1594 1.0,0.2e-7,0,0.5,1.0,-0.05 1595 0,0.1e-3,0.1 1596 0,0,1.0 1597 0.65e+6,483.0,0.6472e-4 1598 0.0,0.0,-1.0 1599 0.7e-4,0.4e-6

Echoed Input File Example

952	hydro	convek=1.0 epscon=0.200e-07 mitmax= 0 thetam=0.5 wm=1.0 estpt=500e-01
953	hydro	ndtyme=0
954	hydro	nawgas=0 nawvel=0 extrav∞0,100e+01
955	hydro	pfref=0.6500000e+06
956	hydro	gx= 0.000000 gy= 0.000000 gz=-1.000000
957	hydro	cvisa=0,700e-04

### 16.2.2 Monitor Cells for Mass Flux

Mass fluxes at selected I,J,K locations may be written to the output file while the run is in progress. Printing a few carefully chosen mass fluxes periodically may aid in monitoring the performance of the code toward a steadystate solution.

General Input Format

NECHO MONMX I,J,K

0,0, NECH MONM I,J, I,J, 0,0, NECH	0 10 17 K 0 0	
I,J,	K	
•		
I,J, 0,0,	К 0	
	<u>General Inpu</u>	t Description
٠	NECHO	<ul> <li>Echoing switch for this section of input. If input is to be echoed, then NECHO = 1; otherwise, 0.</li> </ul>
•	MONMX , MONMY MONMZ	<ul> <li>The number of monitor cells for mass fluxes in the x-,</li> <li>y-, and z-directions, respectively.</li> </ul>
•	I,J,K	- The I,J,K location of each cell.
٠	0,0,0	- The I,J,K sequence for MONMX, MONMY, and MONMZ must terminate with 0,0,0.
	Input File E	xample
1600 1601 1602 1603 1604 1605 1606 1607 1608 1609 1610 1611 1612 1613 1614 1615 1616	1/hydro/monif 4 12,13,2 12,20,2 5,20,2 9,20,25 0,0,0 1/hydro/monif 0 0,0,0 1/hydro/monif 4 2,20,16 8,20,16 23,20,16 2,24,16 0,0,0	tor/mx tor/my tor/mz

-----

16.7

### Echoed Input File Example

959	hydro	monitor	mx	cells=	4	maximum	number	cur	rent	Hy	allowed	is	4
960								m	, T	J	ĸ		
961								1	12	13	2		
962								2	12	20	2		
963								3	5	20	2		
964								4	9	20	25		
965													
966	hydro	monitor	mγ	cells=	0	maximum	number	cur	rent	tly.	allowed	ls	4
967													
968	hydro	monitor	mz	cells=	4	maximum	number	cur	rent	tly	allowed	is	4
969								តា	I.	J	k		
970		•						1	2	20	16		
971								2	8	20	16		
972								3	23	20	16		
973		·						4	2	24	16		

In the example shown, four cells were selected for mass fluxes in the xdirection, none in the y-direction, and four in the z-direction. These mass fluxes will be written to the output file while the run is in progress.

### 16.2.3 <u>Viscosity Specifications</u>

The viscosity is specified automatically for those cells that contain a fluid. However, certain boundary (phantom) cells and those internal cells not containing a fluid need to be identified on the input file. A single cell or a region of contiguous cells forming a rectangular parallelpiped may be identified by a single specification. In either case, the cell or region of cells is indicated by an I,J,K range: IBEG, IEND, JBEG, JEND, KBEG, and KEND.

The most common flow boundary condition is a no-slip condition. Consequently, the viscosity in all cells is initialized to a large value (1.0e+20). The input file then identifies those boundary cells (regions) requiring a different viscosity.

Some internal cells may be occupied by a solid material. These cells may be conveniently identified by a large viscosity.

#### General Input Format

NECHO/HYDRO/SPECS VIS BOUNDARY NREG VIS,IBEG,IEND,JBEG,JEND,KBEG,KEND

- • •
- •

NECHO/HYDRO/SPECS VIS INSIDE NREG XVIS,IBEG,IEND,JBEG,JEND,KBEG,KEND

- •
  - •
- • •

# General Input Description

- NECHO Echoing switch for this section of input. If input is to be echoed, then NECHO = 1; otherwise, 0.
- NREG The number of regions specified in the section of input that follows (either boundary or inside cells).
- VIS Viscosity in boundary (phantom) cells. A very low value would indicate a free-slip condition.
- XVIS A number that multiplies the normal fluid viscosity for interior cells. A solid obstruction would be represented by multiplying the fluid viscosity by a large XVIS for those cells.
- IBEG,IEND, The beginning and ending I,J,K indices for a JBEG,JEND, parallelpiped. If a single cell is to be identified, KBEG,KEND then IBEG = IEND, etc. IBEG,...KEND are input as real numbers.

Input File Example

```
1617 1/hydro/specs vis boundary
1618 1
1619 0.1e-19,1.0,1.0,2.0,47.0,2.0,25.0,
1620 189*0.0
1621 1/hydro/specs vis inside
1622 27
1623 0.1e+10,2.0,4.0,10.0,10.0,3.0,24.0,
1624 0.1e+10,2.0,4.0,17.0,17.0,3.0,24.0,
1625 0.1e+10,2.0,4.0,32.0,32.0,3.0,24.0,
1626 0.1e+10,2.0,4.0,32.0,32.0,3.0,24.0,
1645 0.1e+10,14.0,14.0,22.0,27.0,3.0,24.0,
```

1646 0.1e+10,16.0,16.0,22.0,27.0,3.0,24.0, 1647 0.1e+10,2.0,3.0,10.0,12.0,2.0,2.0, 1648 0.1e+10,2.0,3.0,37.0,39.0,2.0,2.0, 1649 0.1e+10,14.0,16.0,23.0,26.0,2.0,2.0, 1650 7*0.0

Echoed Input File Example

074

7/4											
975	hydro	nreg≖	1	maximum current	dimension for nreg	Is 28	8				
976	hydro	specs		region	viscosity		C	<b>ell</b> la	ocatio	in l	
977	-			-		ibeg	lend	jbəg	jend	kbeg	kend
978				t	0.100e-19	1	t	2	47	2	25
979											
980	hydro	nreg≖	27	maximum current	dimension for nreg	is 2	8				
981	hydro	specs		region	viscosity		C	ell la	ocatio	in in	
982	-				multiplier	ibəg	lend	jbeg	jend	kbeg	kənd
983				1	0,100e+10	2	4	10	10	3	24
984				2	0.1000+10	2	4	12	12	3	24
985				3	0.100e+10	2	4	17	17	3	24
986				4	0.100 <del>0+</del> 10	2	4	32	32	3	24
1005	• • •			23	0.100e+10	14	14	22	27	3	24
1006				24	0.1000+10	16	16	22	27	3	24
1007				25	0.100e+10	2	3	10	12	2	2
1008				26	0.100e+10	2	3	37	39	2	2
1009				27	0.100e+10	14	16	23	26	2	2

For the example shown on the input file, there is one boundary region (line 1618) that includes the J-K plane with I equal to 1 (line 1619) that has a viscosity of 0.1e-19 (a free-slip condition). The array that holds the above information is, in this example, dimensioned to 196 (28 regions * 7 items/region) therefore 189 additional items of the list are provided (line 1620) but are not used in the code. The echoed input file example reflects this information on lines 975 through 978.

For the example shown on the input file, there are 27 internal regions (line 1622). The following 27 lines (lines 1623 to 1649) each contain a viscosity multiplier and the six constants specifying the I,J,K range of the region. The viscosity multiplier (0.1e+10 in the example) shown on each line is used to multiply the regular fluid viscosity in the indicated range of cells. The array that holds the above information is the same one used for boundary viscosity information and is dimensioned for 28 regions. Line 1650 provides the additional dummy items of the list.

#### 17.0 SUBROUTINE PINIT

Subroutine PINIT initializes the pressure field assuming a static (zero velocity) flow field within the domain. Consequently, the equation for the pressure (obtained by setting each of the velocity component terms in the momentum equations to zero), is solved initially. This equation is

$$-\nabla \rho + \rho \dot{g} = 0 \tag{17.1}$$

.

PINIT sets up the matrix and vector components for the discrete form of this equation. The actual solution for the pressure is performed in subroutines PITER and PILES. Typically, HYDRA-II computes the gas properties using an equation of state to relate pressure, density, and temperature. However, for the purposes of the pressure initialization process in this routine only, the fluid density is assumed constant.

HYDRA-II provides two options for setting the average pressure:

- 1. Set the desired average pressure directly.
- 2. Set the fluid mass in the domain.

Option 1 uses the reference fluid density, DFREF, specified as input to subroutine HYDRO in the computation for the pressure field. After Equation (17.1)is solved, each nodal pressure is adjusted by a constant amount so that the average pressure over the field equals FIXEDP if a value FIXEDP > 0.0 is input to subroutine AVG. If the mass of the system is set as the constraint (option 2 above - invoked when FIXEDM > 0.0 is input to subroutine AVG), the cell density is adjusted to produce this specified mass. The cell pressures are subsequently adjusted to be consistent with this density and the specified initial temperature. In this case, the presence of any porous media, which have been specified by the user to occupy some or all of the fluid cells (through the input to subroutine PROPM), is accounted for to reduce the effective volume of the domain.

The pressure field resulting from this initialization process is a function of, among other things, the orientation of the gravitational field vector,

 $\hat{g}$ , relative to the computational domain's coordinate system. The direction cosines defining the orientation of the gravitational field vector are GX, GY, and GZ. These direction cosines are provided by the user as input to sub-routine HYDRO. Vector  $\hat{g}$  is then defined as

$$\dot{\mathbf{f}} = (\mathbf{GX} \ \hat{i} + \mathbf{GY} \ \hat{j} + \mathbf{GZ} \ \hat{k}) |\dot{\mathbf{f}}|$$
 (17.2)

where  $\hat{i}$ ,  $\hat{j}$ , and  $\hat{k}$  are the unit vectors in the x-, y-, and z-directions of the coordinate system, respectively, and  $|\hat{g}|$  is the magnitude of the acceleration due to gravity (= 980.665 cm/sec² in HYDRA-II).

Subroutine PINIT is not accessed in the event of:

1. a restart run (NREAD = 1 as input to MAIN)

2. no momentum-equation solution desired (NOVEL = 1 as input to MAIN).

In the first event, the pressure field is obtained from restart data. The pressure field is irrelevant for the second event.

#### 17.1 PARAMETER STATEMENT INFORMATION

Subroutine PINIT requires the specification of parameters IP, JP, KP, KBP, and KTP. These data define the overall computational mesh and are described in Chapter 4.0.

#### 17.2 INPUT FORMAT

Subroutine PINIT does not require input data.

#### 18.0 SUBROUTINE PROPM

The grid information has been provided in subroutine GRID, and much of the thermo-fluid property information obtained through input to subroutine HYDRO. Therefore, solution of the momentum equations in HYDRA-II requires only some additional input regarding embedded flow obstructions. This information per-tains to area blockages, cell porosities, and cell permeabilities. Two models are available to the user for representing subgrid scale flow obstructions. Flow paths in which a permeable substance is present may be modeled using a Darcy-flow relationship. This Darcy-flow model may be used to represent the entire range of permeability, from virtually unobstructed to essentially plugged paths. For those flow paths occupied in part by an impermeable obstruction, HYDRA-II allows the user to reduce the effective flow area to simulate an orifice-induced pressure gradient.

Flow through porous media can be modeled by using any one of the PERMO, PERMX, PERMY, and/or PERMZ input options provided in this routine. The pressure gradient experienced from cell-to-cell as a result of the presence of this porous media is modeled using the Darcy-flow relationship,

$$\nabla p = \frac{-\mu}{\rho^* PERMI} \stackrel{*}{m}$$
(18.1)

where p,  $\mu$ , and  $\rho$  are the pressure, viscosity, and density of the fluid in the cell, respectively,  $\hbar$  is the mass flux vector, and PERMI is the permeability coefficient (with I = X, Y, or Z representing pressure gradients in the x-, y-, or z-direction, respectively). Orthotropic permeability can be modeled by specifying different values for the PERMX, PERMY, and PERMZ coefficients associated with a given cell. The permeability for each physical cell of the computational mesh is initialized to the input value PERMO. This value applies to PERMX, PERMY, and PERMZ. Therefore, each cell is initially isotropic. The prescribed permeability may then be overwritten with input to PERMX, PERMY, and/or PERMZ as desired, to introduce directional preference in the model. An impermeable cell is represented by a very small permeability coefficient. Conversely, a very porous cell is represented by a large permeability coefficient.

The appropriate value to be assigned to PERMI at input may be estimated from an order-of-magnitude analysis of the affected terms in the momentum equations. For example, an order-of-magnitude study of the ratio of Darcy-flow induced pressure gradient to the viscous shear-stress gradient indicates that these two terms will be of comparable importance if the permeability, PERMI, is on the order of the square of the mesh size. Mathematically stated,

$$\mathsf{PERMI} \sim \delta^2 \tag{18.2}$$

where  $\delta$  is the characteristic cell size. Therefore, for cases in which Darcyflow modeling is desired, the permeability coefficient, PERMI, should be set to a value on the order of the square of the local mesh size. To model both virtually-impermeable and very permeable cells with this Darcy-flow model, PERMI should be represented as follows:

- PERMI <<  $\delta^2$  (or <<  $(\delta|_{min})^2$  in the global case) for virtually impermeable cells.
- PERMI >>  $\delta^2$  for permeable cells (or >>  $(\delta|_{max})^2$  for globally very permeable cells.

"Plugging" of cells may be instituted either by the above process (i.e., specifying PERMI <<  $\delta^2$ ) or by setting the cell viscosity to a relatively large value. There is a subtle, but important, difference in these two approaches. When using the cell viscosity to "plug" a cell, the blockage is assumed to occur over the entire cell. The no-slip condition will then be effectively applied at the cell faces. On the other hand, using the permeability coefficient to "plug" a cell results in an induced drag that affects the mass flow rates across the cell interfaces. The "no-slip" condition is therefore effectively applied at the location of the mass flow rates, and is centered on the surface of the cell interfaces. This amounts to adding an additional half-a-cell width to the location of the "no-slip" condition. These ideas are illustrated in Figure 18.1. PERMI may be used to "plug" a cell in any or all of the coordinate directions independently. On the other hand, using viscosity to "plug" a cell precludes flow through the cell in any direction.





FIGURE 18.1. Cellular Locations for No-Slip Boundary Conditions

Area blockages at the interface between two cells (e.g., orifice plates or sudden expansions and contractions) are modeled with input to arrays AXI, AYI, and/or AZI. The entries to these arrays represent the effective cross-sectional area fraction between communicating cells available for fluid flow. Input variables AXI, AYI, and AZI represent effective fractional flow areas in the x-, y-, and z-directions, respectively. Those elements of the arrays corresponding to faces of the physical cells in the computational mesh are initialized to 1.0, representing no flow obstruction. Therefore, only the interfaces in which an obstruction is present need to be modified via the input to this subroutine. Array element AXI(I,J,K) represents a flow obstruction for the flow path between cells (I,J,K) and (I+1,J,K). Similarly, array element AYI(I,J,K) and (I,J+1,K), as does AZI(I,J,K) for flow between cells (I,J,K) and (I,J,K) and (I,J,K).

The loss coefficient associated with these obstructions is modeled as  $(1 - A^2)/A^2$ , where A is the effective flow area fraction for this flow path. This produces an additional pressure gradient across the flow path. The pressure gradient is included in the appropriate component of the momentum equation as

$$\nabla P = -\frac{1}{2\rho} \left[ \left( \frac{1 - AXI^2}{AXI^2} \frac{|mx|mx}{\Delta x} \right) \hat{i} + \left( \frac{1 - AYI^2}{AYI^2} \frac{|my|my}{\Delta y} \right) \hat{j} + \left( \frac{1 - AZI^2}{AZI^2} \frac{|mz|mz}{\Delta z} \right) \hat{k} \right] (18.3)$$

where  $\vec{m}$  (= mx  $\hat{i}$  + my  $\hat{j}$  + mz  $\hat{k}$ ) is the mass flux across this flow path ( $\hat{i}$ ,  $\hat{j}$  and  $\hat{k}$  are the unit vectors in the x-, y-, and z-directions, respectively).

The user may effectively block a flow path by providing a relatively small value of AXI, AYI, and/or AZI. An estimate of the necessary magnitude for the effective area required to close off a flow path may be obtained from a comparison of the pressure gradient terms in the momentum equations. In a manner similar to that provided for estimating the appropriate value of PERMI, the ratio of the orifice-induced pressure gradient and viscous shear-stress gradient implies that a flow path may be effectively blocked if the effective flow area (e.g., AXI) satisfies

$$AXI^2 << Re_{\delta}/(1+Re_{\delta})$$
(18.4)

where  $\text{Re}_{\delta}$  is an estimate of the cell Reynolds number ( $\text{Re}_{\delta} = \rho u \delta / \mu$ ). This ignores the difference in scales associated with the pressure and viscous shear-stress gradients, but does provide a rough estimate.

A typical situation in which non-unity AXI is required to simulate the flow obstruction is depicted in Figure 18.2. Here, obstructions are present between the cells at (I,J) = (2,1) and (3,1), and between (2,2) and (3,2).



These obstructions reduce the effective flow area by 100% and 60%, respectively. The corresponding input would be  $10^{-6}$  (an entry of 0.0 would produce a division-by-zero error) for the AXI associated with the path (2,1)  $\leftrightarrow$  (3,1), and 0.4 for the AXI associated with the path (2,2)  $\leftrightarrow$  (3,2).

With regard to the input variables AXI, AYI, and AZI, the presence of a flow obstruction implies that:

- a restriction to flow exists in one or more of the coordinate directions
- a no-slip condition be imposed for flow in directions parallel to the obstruction surface.

The first item is addressed by specifying values for AXI, AYI, and/or AZI that are in the range 0 < AXI, AYI, AZI < 1. The second item is addressed in the coding of HYDRA-II. The momentum equation viscous-stress terms representing drag to the flow in directions parallel to the obstruction surface are scaled in the code to represent the no-slip condition imposed by the obstruction. For example, when AXI  $\neq$  1.0, the flow rates in the y- and z-directions will experience an additional drag at the cell interface due to the presence of this obstruction.

The free-volume fraction of a cell can be modified from its default value with the input to array POR. Values of 0.0 < POR(I,J,K) < 1.0 indicate that the effective free volume of the cell associated with index (I,J,K) is

$$VOL(I,J,K) = POR(I,J,K)*DX(I)*DY(J)*DZ(K)$$
 (18.5)

where DX, DY, and DZ are the mesh sizes for the cell. For steady-state applications, the volume influences the results for only those cases in which a fixed mass is specified for the computational domain (FIXEDM > 0 as input to subroutine AVG). When the average pressure is specified for the computational domain (FIXEDP > 0 as input to subroutine AVG), POR has no effect on the computation. Array POR is initialized to 0.0 for those cells outside the hydrodynamic portion of the computational domain, to 0.5 for those cells lying on the interface between the cartesian and cylindrical meshes (to simulate the
cells whose volumes are partially occupied by the domain enclosure), and to 1.0 for those cells located entirely within the hydrodynamic portion of the computational domain.

As a final note, the effective loss coefficient for pressure-drop calculations is independent of flow speed (or, equivalently, flow rate) in the porousmedia model. On the other hand, the effective loss coefficient in modeling flow obstructions with AXI, for example, is linearly dependent on the flow speed. Therefore, by judiciously combining the two models and their coefficients, the user may simulate a segment of the drag curve for flow around a body (e.g., cylinder or sphere). Attempts can then be made to match the coefficients to produce the experimentally observed drag coefficient variation in the Reynolds number range of interest.

## 18.1 PARAMETER STATEMENT INFORMATION

Only the overall grid specification information IP, JP, KP, KBP, and KTP (described in Chapter 4.0) is required as PARAMETER information in PROPM.

## 18.2 INPUT FORMAT

#### 18.2.1 Overview

Generally speaking, the input to subroutine PROPM can be divided into two subsections:

- "global" setting of the PERMX, PERMY, and PERMZ arrays
- loading of arrays AX, AY, AZ, AXI, AYI, AZI, and POR, as well as the resetting of arrays PERMX, PERMY, and PERMZ by mesh blocks.

The input requirements for each of these subsections is provided in Section 18.2.2.

## 18.2.2 "Global" Setting of PERMX, PERMY, and PERMZ

#### General Input Format

NECHO PERMO

## General Input Description

- NECHO Echoing switch for this section of input. If
   NECHO = 1, an echo of the input for this section will be provided in the output; if NECHO = 0, this echoing will not be provided.
- PERMO Value to which the elements of arrays PERMX, PERMY, and PERMZ will be set. A value <u>must</u> be provided for the input.

Input File Example

1651 1/propm 1652 10.0

#### Echoed Input File Example

1011 propm perm0=0.100e+02 1012

NECHO is set to 1 on input line 1651. The value of PERMO is set to 10.0 on input line 1652. This is reflected in the output as line 1011. As a result, PERMX, PERMY, and PERMZ are set to 10.0 for every element of the arrays associated with a "physical" cell of the computational domain (i.e., those cells of the computational mesh which are neither phantom nor pseudo-cells).

18.2.3 <u>Block Loading Arrays AX, AY, AZ, AXI, AYI, AZI, POR, PERMX,</u> PERMY, and PERMZ

General Input Format

NECHO INFO VALUE, IBEG, IEND, JBEG, JEND, KBEG, KEND

• • • • •

VALUE, IBEG, IEND, JBEG, JEND, KBEG, KEND -1.0, 6*0

## General Input Description

- NECHO Echoing switch for this section of input. If
   NECHO = 1, an echo of the input for this section will be provided in the output; if NECHO = 0, this echoing will not be provided.
- INFO Switch to print the output file for the <u>entire</u> contents of the array associated with this input section (e.g., AXI or PERMY). Setting INFO = 1 will generate this output listing; INFO = 0 will not.
- Quantity to be loaded into this block of AX, AY, AZ, VALUE AXI, AYI, AZI, POR, PERMX, PERMY, or PERMZ. A block is defined as those cells covered by a sweep through the I, J, and K index ranges. Loading is terminated for a set of blocks with the sequence -1.0, 6*0. Up to 1000 blocks may be loaded in each set. The AX set of blocks is loaded first, followed by the AY, AZ, AXI, AYI, AZI, POR, PERMX, PERMY, and PERMZ sets. Loading in this order is essential. Input to arrays AX, AY, and AZ has no significance to the steady-state solution obtained by HYDRA-II. Therefore, no input is provided to these arrays. As indicated in the sample input presented in this section, only the terminator sequence is provided as input to these arrays. The input variable "VALUE" corresponds to a multiplier when loading array POR. The affected elements of array POR are set equal to the product of the input value of POR multiplied by the cell volume

POR(I,J,K) = VALUE*DX(I)*DY(J)*DZ(K).

The volumes of those hydrodynamic cells lying on the interface between cartesian and cylindrical meshes are halved to account for the cell bisection produced by this interface.

- IBEG Beginning I index of the block.
- IEND Ending I index of the block.
- JBEG Beginning J index of the block.
- JEND Ending J index of the block.
- KBEG Beginning K index of the block. The values specified for these K indices refer to the momentum equation grid. This distinction was discussed in Section 4.1.
- KEND Ending K index of the block. The values specified for these K indices refer to the momentum equation grid. This distinction was discussed in Section 4.1.

Input File Example

1653 1/propm/ax 1654 0 1655 -1.0,6*0 1656 1/propm/ay 1657 0 1658 -1.0,6*0 1659 1/propm/az 1660 0 1661 -1.0,6*0 1662 1/propm/axi 1663 0 1664 0.67,1,23,2,47,2,2 1665 0.62,1,23,2,47,25,25 1666 0.65,2,3,11,11,3,24 1667 0.65,2,3,18,20,3,24 1668 0.65,2,3,29,31,3,24 1669 0.65,2,3,38,38,3,24 1670 0.65,8,9,20,20,3,24 1671 0.65,8,9,29,29,3,24 1672 0.65,21,22,20,20,3,24 1673 0.65,21,22,29,29,3,24 1674 -1.0,6*0 1675 1/propm/ayi 1676 0 1677 0.67,2,23,2,46,2,2 1678 0.62,2,23,2,46,25,25 1679 0.65,6,6,3,4,3,24 1680 0.65,6,6,16,17,3,24 1681 0.65,6,6,31,32,3,24 1682 0.65,6,6,44,45,3,24 1683 0.65,6,8,22,23,3,24

```
1684 0.65,6,8,25,26,3,24
 1685 0.65,15,15,22,23,3,24
 1686 0.65,15,15,25,26,3,24
 1687 -1.0,6*0
 1688 1/propm/azi
 1689 0
 1690 0.1e-6,2,4,9,13,2,2
 1691 0.1e-6,2,4,36,40,2,2
 1692 0.1e-6,13,17,22,27,2,2
1693 0.1e-6,2,4,2,2,2,2,
1694 0.1e-6,2,4,47,47,2,2
1695 0.1e-6,24,24,22,27,2,2
1696 0.1e-6,2,4,16,16,2,2
1697 0.1e-6,2,4,33,33,2,2
1698 0.1e-6,10,10,22,27,2,2
1699 0.1e-4,2,4,22,22,2,2
1700 0.1e-4,2,4,27,27,2,2
     .
1755 0.45,8,10,20,20,3,24
1756 0.45,8,10,29,29,3,24
1757 0.4,6,6,3,7,3,24
1758 0.4,6,6,42,46,3,24
1759 0.4, 19, 23, 20, 20, 3, 24
1760 0.4, 19, 23, 29, 29, 3, 24
1761 -1.0,6*0
1762 1/propm/por
1763 0
1764 -1.0.6*0
1765 1/propm/permx
1766 0
1767 0.5e-2,2,4,2,9,4,23
1768 0.5e-2,2,4,13,16,4,23
1769 0.5e-2,2,4,22,27,4,23
1770 0.5e-2,2,4,33,36,4,23
1771 0.5e-2,2,4,40,47,4,23
1772 0.5e-2,8,11,5,13,4,23
1773 0.5e-2,8,11,15,18,4,23
1774 0.5e-2,8,11,31,34,4,23
1775 0.5e-2,8,11,36,44,4,23
1776 0.5e-2,13,21,15,18,4,23
1777 0.5e-2,13,21,31,34,4,23
1778 0.5e-2,10,13,22,27,4,23
1779 0.5e-2,17,24,22,27,4,23
1780 -1.0,6*0
1781 1/propm/permy
1782 0
1783 0.5e-2,2,4,2,9,4,23
```

1784 0.5e-2,2,4,13,16,4,23 1785 0.5e-2,2,4,22,27,4,23 1786 0.5e-2,2,4,33,36,4,23 1787 0.5e-2,2,4,40,47,4,23 1788 0.5e-2,8,11,5,13,4,23 1789 0.5e-2,8,11,15,18,4,23 1790 0.5e-2,8,11,31,34,4,23 1791 0.5e-2,8,11,36,44,4,23 1792 0.5e-2,13,21,15,18,4,23 1793 0.5e-2,13,21,31,34,4,23 1794 0.5e-2,10,13,22,27,4,23 1795 0.5e-2,17,24,22,27,4,23 1796 -1.0,6*0 1797 1/propm/permz 1798 0 1799 0.1e-1,2,4,2,9,4,23 1800 0.1e-1,2,4,13,16,4,23 1801 0.1e-1,2,4,22,27,4,23 1802 0.1e-1,2,4,33,36,4,23 1803 0.1e-1,2,4,40,47,4,23 1804 0.1e-1,8,11,5,13,4,23

> · · · · · ·

1825 0.1e-4,22,22,29,29,3,24 1826 0.1e-4,15,15,23,23,3,24 1827 0.1e-4,15,15,26,26,3,24 1828 -1.0,6*0

## Echoed Input File Example

1013	propm	info=0	region	ax	cell location				n		
1014					ibeg	lend	jbeg	jend	kbeg	ikend	
1015					-			•	-		
1016	propm	info=0	region	ay	cell location						
1017					i beg	iend	jbeg	jend	kbeg	<b>jkend</b>	
1018											
1019	propm	info=0	region	az	cell locatio			on			
1020					ibeg lend jbeg jo			jend	jend kbegkend		
1021											
1022	propm	info=0	region	axi		C	ell k	ocatio	n		
1023					Ibeg	lend	Jbeg	jend	kbeg	kend	
1024			1	0.670000e+00	1	23	2	47	2	2	
1025			2	0.620000e+00	1	23	2	47	25	25	
1026			3	0.650000e+00	2	3	11	11	3	24	
1027			4	0.650000e+00	2	3	18	20	3	24	
1028			5	0.650000e+00	2	3	29	31	3	24	
1029			6	0.650000e+00	2	3	38	38	3	24	
1030			7	0.650000e+00	8	9	20	20	3	24	
1031			8	0.650000e+00	8	9	29	29	3	24	
1032			9	0.650000e+00	21	22	20	20	3	24	
1033			10	0.650000e+00	21	22	29	29	3	24	
1034											

1035	oroom	in fo=0	reaion	ayi	cell location						
1036	PP			,	i beg	lend	jbeg	jend	kbøg	kend	
1037			1	0.670000e+00	2ັ	23	2	46	2	2	
1038			2	0.620000a+00	2	23	2	46	25	25	
1039			3	0.650000e+00	6	6	3	4	3	24	
1040			Δ	0.650000e+00	6	6	16	17	3	24	
1040			5	0.650000e+00	6	6	31	32	3	24	
1042			ĥ	0.6500000+00	6	6	44	45	3	24	
1042			7	0.6500000+00	6	8	22	23	3	24	
1043			Ŕ	0.6500000+00	6	8	25	26	3	24	
1044			å	0.6500000+00	15	15	22	23	3	24	
1045			10	0.6500000+00	15	15	25	26	3	24	
1040			10	0.000008100			~ >	20	-		
1047		1-60						ocatic	<b>1</b> 0		
1048	ргорт	1010-0	region	921	thee	land		lond	"' khao	kand	
1049			•	0 100000-06	100g	19110	Jueg	13	2	2	
1050			1	0,100000-00	2	-	7	40	2	2	
1051			2	0.100000-06	17	4	20	40	2	2	
1052			2	0,100000-06	21	17	~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~	21	2	2	
1053			4	0,100000-06	2	4	2	47	2	2	
1054			5	0.10000e-06	2	4	4/	4/	2	2	
1055			6	0.100000e-06	24	24	22	21	2	2	
1056			7	0,10000e-06	2	4	16	16	2	2	
1057			8	0 <b>.</b> 100000e-06	2	4	33	33	2	2	
1058			9	0 <b>.</b> 100000 <del>e</del> -06	10	10	22	27	2	2	
1059			10	0.100000e-04	2	4	22	22	2	2	
1060			11	0 <b>.</b> 100000e-04	2	4	27	27	2	2	
	•			•					•		
	•			•					•		
	•			•					•		
							•••	~~			
1115			66	0,450000e+00	8	10	20	20	2	24	
1116			67	0,450000e+00	8	10	29	29	د	24	
1117			68	0,400000e+00	6	6	3	1	د	24	
1118			69	0 <b>,</b> 400000e+00	6	6	42	46	3	24	
1119			70	0,400000e+00	19	23	20	20	3	24	
1120			71	0 <b>.</b> 400000e+00	19	23	29	29	3	24	
1121										•	
1122	propm	info=0	region	por		C	sett te	ocatio	ก		
1123					i beg	lend	jbeg	jend	kbeg	kend	
1124											
1125	propm	info=0	region	permx		Ċ	:011 10	ocatio	n		
1126			-		i beg	iend	jbeg	jend	kbeg	kend	
1127			1	0,500000e-02	2	4	2	9	4	23	
1128			2	0,500000e-02	2	4	13	16	4	23	
1129			3	0.500000e-02	2	4	22	27	4	23	
1130			4	0,500000e-02	2	4	33	36	4	23	
1131			5	0,500000e-02	2	4	40	47	4	23	
1132			6	0.500000a-02	8	11	5	13	4	23	
1133			7	0.500000e-02	8	11	15	18	4	23	
1134			8	0.500000e-02	8	11	31	34	4	23	
1135			9	0.500000-02	8	11	36	44	4	23	
1136			10	0.500000-02	13	21	15	18	4	23	
1137			11	0.500000-02	13	21	31	34	4	23	
1138			12	0.5000000-02	10	13	22	27	4	23	
1139			13	0.500000-02	17	24	22	27	4	23	
1140			<i></i>	Ja >000000-02	•••	~~	÷ 6	- '	-		
1140											

•

 $\sim$ 

1141	ргорт	info=0	region	permy		c	ell location			
1142					ibeg lend jbeg jend k				kbeg	kend
1143			1	0,500000e-02	2	4	2	9	4	23
1144			2	0.500000e-02	2	4	13	16	4	23
1145			3	0,500000e-02	2	4	22	27	4	23
1146			4	0.500000e-02	2	4	33	36	4	23
1147			5	0,500000e-02	2	4	40	47	4	23
1148			6	0.500000e-02	8	11	5	13	4	23
1149			7	0,500000e-02	8	11	15	18	4	23
1150			8	0.500000e-02	8	11	31	34	4	23
1151			9	0 <b>.</b> 500000e-02	8	11	36	44	4	23
1152			10	0,500000e-02	13	21	15	18	4	23
1153			11	0,500000e-02	13	21	31	34	4	23
1154			12	0,500000e-02	10	13	22	27	4	23
1155			13	0,500000e-02	17	24	22	27	4	23
1156										
1157	propm	info=0	region	permz		c	ell le	ocatio	n	
1158					l beg	lend	jbeg	jend	kbeg	kend
1159			1	0.100000e-01	2	4	2	9	4	23
1160			2	0.100000e-01	2	4	13	16	4	23
1161			3	0.100000e-01	2	4	22	27	4	23
1162			4	0.100000e-01	2	4	33	36	4	23
1163			5	0.100000e-01	2	4	40	47	4	23
1164										23
			6	0.100000e-01	8	11	5	13	4	25
			б	0.100000e-01	8	11	5	13	4	25
	٠		6	0.100000e-01	8	11	5	13	•	23
	•		6	0.100000e-01 • •	8	11	5	13	4 • •	23
	• •		6	0.100000e-01 • •	8	11	5	13	4 • •	25
1185	• •		6 27	0.100000e-01	8	11	5 29	13	4	24
1185 1186	• •		6 27 28	0.10000e-01 • • • • • • • • • • • • • • • • • • •	8 22 15	11 22 15	5 29 23	13 29 23	4 • • 3 3	23 24 24

NECHO is set to 1 on input line 1653; INFO is set to 0 on line 1654. Arrays AX, AY, and AZ have no significance to the steady-state solution produced by HYDRA-II. Therefore, their input sections are effectively bypassed by providing only the terminator line of input. Consequently, the array elements are loaded with the default value 1.0.

Ten blocks of array AXI are loaded with the input from lines 1664 through 1673. The input follows the standard format. For example, input line 1668 results in the array elements of AXI(I,J,K) for 2 < I < 3, 29 < J < 31, and 3 < K < 24 being loaded with the value 0.65. This particular input is echoed in line 1028 of the output. Input to array AXI is terminated by the input on line 1674. The echoed input for the complete section is provided in output lines 1022 through 1033. Those "physical" cells not explicitly loaded will contain the default value 1.0. The elements of AXI associated with the remaining cells outside of the hydrodynamic region will contain the default value

0.0. Ten blocks of array AYI are loaded with the input from lines 1677 through 1686. Input to this array is terminated with the information provided on line 1687. The echoed input for this section is provided in lines 1035 through 1046. The same defaults apply here as for array AXI.

Seventy-one blocks of array AZI are loaded with the input from lines 1690 through 1761. The corresponding echoed-input is provided in lines 1048 through 1120. Again, the same default values apply here as for array AXI. The POR array multiplier is loaded next in the sequence. However, in this example the default values are sufficient (defaults to 1.0). Therefore, only the section terminator line is provided, input line 1764.

PERMX, PERMY, and PERMZ are loaded next. Input lines 1765 through 1828 reflect the values specified for each block. For example, the array elements PERMX(I,J,K) for 10 < I < 13, 22 < J < 27, and 4 < K < 23 are loaded with the value 0.005 on line 1778 of the input. Those "physical" cells not covered in the input to these sections are defaulted to PERMO.

#### 19.0 SUBROUTINES MOMX, MOMY, AND MOMZ

The terms of the momentum equations are evaluated in subroutines MOMX, MOMY, and MOMZ using the methods discussed in <u>Volume I - Equations and Numerics</u> (McCann 1987). Subroutine MOMX evaluates the terms of the x-component momentum equation; MOMY, the y-component; and MOMZ the z-component. The x-, y-, and zmomentum equation terms are evaluated using pressures obtained from the previous time-step. Consequently, the momentum subroutines produce a mass-flux field that will not, in general, satisfy continuity. For this reason, these mass fluxes are tentative and are denoted by a tilde, m̃. This part of the calculation is thus termed the "tilde phase." Mass conservation is enforced by subsequently modifying the pressure field using the tilde-phase mass-flux field. The final mass fluxes for this time-step are then computed using the tilde-phase mass fluxes and the modified pressure field.

## **19.1 PARAMETER STATEMENT INFORMATION**

Subroutines MOMX, MOMY, and MOMZ require the specification of parameters IP, JP, KP, KBP, KTP, and NEFAP. These data define the overall computational mesh and are described in the discussion of subroutine GRID in Chapter 4.0. No additional parameters are needed for these three subroutines.

## 19.2 INPUT FORMAT

Subroutines MOMX, MOMY, and MOMZ do not require input data.

#### 20.0 SUBROUTINE PDG

Subroutine PDG performs two functions. First, PDG sets up the coefficient matrix required to obtain a solution for the pressure-correction field. The elements comprising this coefficient matrix are identified in Chapter 9.0 of <u>Volume I - Equations and Numerics</u> (McCann 1987). This matrix is used in obtaining a first-pass solution in PDG. It is also employed in subroutines PILES, REBS, REBQ, and AF to obtain a solution to the pressure-correction field. The first-pass solution is generated in PDG using a variant of the Douglas and Gunn algorithm (1964). The modification to this algorithm employs a user-supplied weighting parameter, WP. This parameter is used to artificially weight the diagonal elements of the coefficient matrix. The effect of this weighting is to enhance the convergence properties of the algorithm.

Subroutine PDG also allows the user to monitor the cell mass imbalance during the solution process. Monitoring is controlled by switch NSINFO (set in MAIN). This constant controls the printing frequency of diagnostic information and monitored variables. For example, if NSINFO = 20, then information will be printed for time-steps 1, 21, 41, etc. Information is always printed for the first and last time-steps of a run. The output provided in this process is:

- the time-step number
- the momentum time-step
- the I, J, and K indices of the cell experiencing the largest tildephase mass imbalance
- the tilde-phase mass imbalance for this cell.

In addition, the largest component mass-flux corrections and their corresponding computational-mesh indices are provided in the output.

The magnitude of the largest continuity error is used to suggest a momentum time-step adjustment to subroutine HYDRO. This is done in an effort to maintain the optimum tilde-phase continuity error for the next time-step.

## 20.1 PARAMETER STATEMENT INFORMATION

Subroutine PDG requires the specification of parameters, IP, JP, KP, KBP, KTP, and NEFAP. These data define the overall computational mesh and are described in the discussion of subroutine GRID in Chapter 4.0.

## 20.2 INPUT FORMAT

## 20.2.1 Overview

Very little input is required by subroutine PDG. Only three variables are read: NECHO, WP, and OPTCON. The input sequence and definition are provided below.

## General Input Description

- NECHO Echoing switch for this section of input. If
   NECHO = 1, an echo of the input for this section will be provided in the output; if NECHO = 0, this echoing will not be provided.
- WP A weight parameter used to weight the diagonal elements of the coefficient matrix. The appropriate value depends on the nature of the desired solution, i.e., time-dependent or steady state. For steady-state solutions, set WP = 0.8.
- OPTCON A weight factor allowing the user a measure of control in achieving the "optimum continuity" error. Subroutine PDG will suggest scaling the new momentum timestep using

 $\Delta t_{m} = (1.5 - 0.5* | ERRCON | / OPTCON) * \Delta t$ 

where the subscript m refers to the suggested momentum time-step and ERRCON is the largest cell mass imbalance.

General Input Format

NECHO WP,OPTCON

Input File Example

1829 1/pdg 1830 0.8,0.5e-5

# Echoed-Input File Example

1189 pdg wp=0.80 optcon=0.500e-05 1190

NECHO has been set to 1 on input line 1829. Input line 1830 indicates that WP has been set to a value of 0.8 and OPTCON to a value of 0.5e-5.

## 21.0 SUBROUTINE PITER

Subroutine PITER serves as a traffic control routine directing program flow to the various methods available for solving the Poisson equation for the pressure-correction field. HYDRA-II provides the user with a number of approaches to generate the solution to the Poisson equation:

- Coarse-mesh subroutines REBS and REBQ adjust the interim pressurecorrection field solution to reduce long-wavelength errors. These routines are discussed in Chapters 23.0 and 24.0.
- Subroutine AF uses an approximate-factorization technique. AF is discussed in Chapter 26.0.
- Subroutine PILES performs line successive relaxation iterations. PILES is discussed in Chapter 22.0.

Subroutine PITER allows the user to tailor the solution scheme to suit the requirements of the specific problem at hand. PITER starts with the pressurecorrection field estimate obtained in subroutine PDG. An optimum sequence for solving the pressure equation cannot be prescribed a priori for a particular simulation. The user can cautiously try using REBQ along with PILES, and possibly AF or REBS in a sequence found workable for similar problems. The use of REBQ, REBS, or AF should be interspersed with the use of PILES with, at least initially, setting the printout option INFO = 1 in PILES. The divergence error, DMAX, for each direction of line-successive-relaxation sweeps in PILES should be examined, and the maximum number of three-direction line-successive-relaxation sweeps (NMAX) in PILES should be set to ensure that:

- the short wavelength error is being reduced sufficiently in PILES so that the divergence error is smaller than it was before the call to REBQ or to a combination of REBQ, AF, and REBS
- the iterations within PILES are not continuing past a point of diminishing returns (i.e., the divergence error is no longer being removed effectively).

In some cases it may be desirable to systematically explore the efficacy of REBS, REBQ, and AF patterns, with PILES in the pressure correction solution. This can be done with a sequence as follows:

- Run HYDRA-II through some number of time-steps, possibly using only PILES or some previously successful combination of PILES, REBS, REBQ, and AF, but terminating with PILES. Create a restart file.
- 2. Run a succession of restart cases from this restart file in which one of the routines REBS, REBQ, or AF is called, followed by a call to PILES with a fairly high number of inner iterations (NMAX) and with INFO = 1 to get divergence error printouts. Consider the pattern of divergence errors (printed in PILES), noting which of the routines preceding the call to PILES are effective in reducing the divergence error. Note that some routines (particularly REBS and REBQ) may initially increase the divergence error by increasing short wavelength error while reducing long wavelength error. PILES is effective for reducing short wavelength error.
- 3. Select some of the more promising routines from among REBS, REBQ, and AF, based on the tests in Step 2. Use them in combinations, with or without calls to PILES between them, and do further comparisons of divergence error patterns. PILES should be called in the sequence, of course, since only it, and possibly AF, can produce converged solutions on the fine mesh. Always note the number of iterations in PILES needed to show a net improvement in the divergence error, paying particular attention to the diminishing returns phenomenon. Select a pattern of calls to PILES, REBS, REBQ, and AF for further use in seeking convergence, along with a number of iterations in PILES (NMAX).
- 4. With the sequence (specified in NORDER in the input to PITER) chosen by this procedure, and with the selected number of inner iterations in PILES (NMAX), advance the simulation through additional timesteps, stopping and restarting as appropriate. Reduce the level of printout when confidence is gained that the sequence of procedures is effective.

The number of techniques employed to obtain the interim solutions are completely specified by the user with input variable NORDA. The sequence in which each technique is employed in the process is specified by the user with input to array NORDER(I) for I = 1, 2, ..., NORDA. The following is a list of allowable NORDER settings and the corresponding routines invoked:

NORDER(I)	Routine Invoked
1	line successive relaxation - PILES
2	coarse-mesh solver - REBS
3	coarse-mesh solver - REBQ
4	approximate factorization - AF

Subroutine PITER sweeps through the first NORDA elements of array NORDER; therefore, the solution technique associated with the value of NORDER(1) will be employed first. This is followed by invocation of the scheme associated with NORDER(2), and so on up to NORDER(NORDA).

Convergence is not necessarily assured with one passage through the <u>set</u> of schemes invoked by NORDER. Therefore, PITER allows the user to specify, via the input variable NMAX, the number of times this <u>set</u> of schemes will be called by subroutine PITER during each pass through PITER.

## 21.1 PARAMETER STATEMENT INFORMATION

Subroutine PITER requires the specification of one parameter, NORDAP. This parameter sets the maximum number of elements which can be contained in array NORDER. The elements of NORDER specify which methods are employed in the calling sequence of subroutine PITER.

## 21.2 INPUT FORMAT

## 21.2.1 Overview

The input to subroutine PITER serves primarily to direct the calling sequence to the various solution algorithms available.

## General Input Format

NECHO NOPT,NMAX REBSON,REBQON,AFON NECHO NORDA NORDER(1),NORDER(2), ..., NORDER(NORDA)

## General Input Description

- NECHO Echoing switch for this section of input. If
   NECHO = 1, an echo of the input for this section will be provided in the output; if NECHO = 0, this echoing will not be provided.
- NOPT The desired optimum number of passes through subroutine PITER. Subroutine PITER will suggest appropriate scaling of the momentum time-step to the calling routine, HYDRO, based on the convergence history of the pressure solution. The scaling is based on the number of PITER passes required for convergence, ITER. ITER is set to the value NMAX if no convergence is obtained in this pass through subroutine PITER. The suggested time-step is computed as

 $\Delta t_{p} = MAX(1.5 - 0.5*REAL(ITER)/REAL(NOPT), 0.1)*\Delta t$ 

NOPT should be set to a value less than or equal to NMAX. Therefore, the suggested time-step scaling can range from 0.1 for difficult convergence situations to an asymptote of 1.5.

- NMAX Maximum iterations allowed in each pass through PITER.
- REBSON, Initialization switches for subroutines REBS, REBQ, REBQON and AF, respectively. If any of these routines are AFON to be employed in the set of iteration schemes, the

corresponding switch for that routine should be set to 1.0. Otherwise, set the switch to 0.0.

- NORDA Total number of routines employed in each pass through PITER. If one routine is used more than once in the set, it should be counted as many times as it is invoked.
- NORDER Array containing the identification numbers for the solution schemes. Their storage order corresponds to the sequence in which the routines will be invoked in the iteration. The identification number for the various routines is provided in the above text. There must be NORDAP entries provided in the input even if NORDA < NORDAP. NORDER(I) for I = NORDA+1, NORDA+2, ..., NORDAP may be set to any value.</li>

Input File Example

1831 1/piter 1832 4,20 1833 0.0,1.0,1.0 1834 1/piter/norder 1835 3 1836 3,4,1,0

## Echoed-Input File Example

1191 piter nopt=4 nmax#20 1192 piter rebson=0.0 rebgon=1.0 afon=1.0 1193 1194 plter norda= 3 maximum current dimension for norda is 4 1195 piter norder 3 4 1 0

NECHO has been set to 1 on input line 1831. On input line 1832, NOPT is set to 4 and NMAX is set to 20. Therefore, there will be a maximum of 20 iterations allowed in each pass through PITER.

Input line 1833 indicates that, of the three switchable schemes, only REBQ and AF will be employed in this set. Subroutine PILES will be the last subroutine invoked in this set of schemes. NECHO has been set to 1 on input line 1834. Input line 1835 indicates that there will be three schemes employed in the set; therefore, each scheme (viz., REBQ, AF, and PILES) will be invoked only once per iteration. The sequence in which these schemes are employed is provided on input line 1836. This line indicates that REBQ will be invoked first, followed by AF and PILES. Note that four entries are provided for array NORDER, even though only three are non-zero. With NORDAP = 4 and NORDA = 3, four entries are required for input, but only the first three are used. The remaining one is ignored.

This input sequence has been echoed in output lines 1191 through 1195.

#### 22.0 SUBROUTINE PILES

Subroutine PILES solves the Poisson equation for the pressure correction field using a line-successive-relaxation iteration scheme. This Poisson equation is obtained by seeking the pressure-field correction that will produce a mass balance for each cell of the computational mesh.

The line-successive-relaxation iteration is performed in three passes-one corresponding to each of the three coordinate directions. If the user-specified value for INFO is > 1, the routine searches for the largest solution residual (in magnitude) and its (I,J,K) index location at the beginning of the first two of the three passes. PILES always searches for these values at the beginning of the third step, regardless of the value of INFO. If INFO is set to a value greater than 0, PILES will print the iteration count, together with the largest residual and its (I,J,K) index location at the first and second passes in the iteration. The time-step number (NS, updated in MAIN) and switch NSINFO (also set in MAIN) control whether or not this printout is produced at the end of the third pass. For example, if NSINFO = 20, then information will be printed at time-steps 1, 21, 41, etc. Information is always printed for the first and last time-steps of a run, NS = 1 and NSTEP, respectively.

Convergence is tested at the conclusion of the third pass in each iteration. When the largest residual (in magnitude) is less than the userspecified convergence criterion, EPSD, the algorithm has converged. PILES will then return to subroutine PITER. If no convergence is obtained after NMAX iterations have been performed, PILES will set a flag before returning to PITER. This flag indicates to subroutine PITER, the lack of convergence in PILES. HYDRA-II uses this information to determine whether momentum time-step adjustment is required.

The iteration scheme requires the user to specify a relaxation parameter, OMEGA. This relaxation parameter may assume a value in the range

0 < OMEGA < 2

OMEGA < 1 corresponds to underrelaxation; OMEGA > 1 corresponds to overrelaxation. As with the familiar successive overrelaxation (SOR) methods, there exists a value for OMEGA which will produce the largest asymptotic reduction in error. Unfortunately, the exact value for this optimal OMEGA is very problem-specific and is usually determined by numerical experiment in most simulations.

## 22.1 PARAMETER STATEMENT INFORMATION

Subroutine PILES requires the specification of parameters IP, JP, KP, KBP, KTP, and NEFAP. These data define the overall computational mesh and are described in the discussion of subroutine GRID in Chapter 4.0.

## 22.2 INPUT FORMAT

# 22.2.1 Overview

The input to subroutine PILES sets the parameters of the line successiverelaxation scheme. Specifically, the convergence criterion (EPSD), relaxation factor (OMEGA), and number of iterations per pass through PILES (NMAX), are defined by the user through the input to this routine.

General Input Format

NECHO EPSD, OMEGA, NMAX, INFO

## General Input Description

- NECHO Echoing switch for this section of input. If
   NECHO = 1, an echo of the input for this section will be provided in output; if NECHO = 0, this echoing will not be provided.
- EPSD Convergence criterion. The appropriate value to use is problem-dependent. A "loose" convergence criterion effectively produces sources and sinks of mass in the problem. These mass sources and sinks are amplified

by the enthalpy terms in the energy equation and are, therefore, commonly manifested as spurious trends in the temperature field.

- OMEGA Relaxation parameter. OMEGA is constrained to a value in the range 0 < OMEGA < 2. Values of OMEGA < 1 correspond to underrelaxation; OMEGA > 1 corresponds to overrelaxation. The optimal value for OMEGA is problem-dependent. This value must be determined from numerical test cases. Problems that are "stiff" in the numerical sense (e.g., problems in which the gas region is represented by a disparate range of mesh sizes) typically require a relaxation parameter close to 1 (e.g., OMEGA = 1.1). Conversely, those problems that are not "stiff" will allow greater over-relaxation (e.g., OMEGA = 1.8).
- NMAX The maximum number of line-successive-relaxation iterations to be performed in each pass through subroutine PILES.
- INFO Residual-monitor and print flag.

Input File Example

1837 1/piles 1838 0.2e-8,1.1,4,0

#### Echoed-Input File Example

1197 piles epsd=0.200e-08 omega=1.10 nmax= 4 Info=0 1198

NECHO has been set to 1 on input line 1837. Convergence will be achieved if the absolute value of the largest residual is less than the specified value of EPSD, 0.2E-8. The second entry on input line 1838 indicates that an over-relaxation factor of 1.1 will be used in this simulation for each of the maximum of four iterations per pass through PILES. The last entry on input line 1838 specifies INFO = 0.

## 23.0 SUBROUTINE REBS

Subroutine REBS is one member of the set of subroutines (PILES, REBS, REBQ, and AF) that can be called upon by subroutine PITER to solve a Poisson equation for the pressure correction field.

#### 23.1 REBS FUNCTIONS

If requested for use, REBS solves the Poisson equation three times on slab representations of the rectangular grid, for slabs lying in planes of constant I, J, and K in turn. The  $\delta P(I)$  calculated for the I-slab case is applied to computational cells in that I-plane, and similarly for the J-plane and K-plane solutions.

REBS does not read input, and it executes rapidly. It is used without user control in setting up the static pressure field when initiating a simulation. REBS is effective for numerically-easy problems. Its effectiveness in the pressure-correction equation solution sequence can be monitored by noting the divergence error for the pressure equation as printed by PILES before and after REBS application. REBS will generally introduce some short-wavelength error (which PILES is effective in removing) while reducing long-wavelength error. Allow enough line-successive-relaxation sweeps in PILES between REBS calls to ensure that the short-wavelength error is reduced and net progress toward a solution is made.

#### 23.2 PARAMETER STATEMENT INFORMATION

Dimensioning parameters set in REBS include IP,JP,KP. These were defined in Chapter 4.0, subroutine GRID, and have the same meanings and should have the same values here. Also set are KBP,KTP which were discussed in Chapter 4.0 and defined in Chapter 6.0, subroutine THERM.

## 23.3 INPUT FORMAT

Subroutine REBS does not read input.

## 24.0 SUBROUTINE REBQ

Subroutine REBQ is another member of the set of subroutines (PILES, REBS, REBQ, and AF) that can be called by subroutine PITER to aid in solving a Poisson equation for the pressure correction field.

## 24.1 REBQ FUNCTIONS

REBQ solves the pressure correction equation on three different userdefined coarse partitions of the rectangular grid. These coarse mesh solutions are used to improve the estimate of the pressure correction field on the fine mesh. REBQ has proved an effective tool for expediting convergence in the pressure correction field, even for difficult simulations with intricate flow patterns. It is effective in removing long-wavelength error, and it should be interspersed with techniques like those of subroutine PILES or AF that are effective against short-wavelength error.

REBQ is noteworthy for the flexibility and ease with which the coarse mesh can be defined. For the first of the three coarse meshes (the KREG mesh), the X-Y boundaries are defined identically for each K-plane. The coarse mesh can be a fairly arbitrary set of rectangles bounded by X- and Y-grid lines. Such a set is shown in Figure 24.1. The user must define the X-Y bounds of the cells. The flow computational region with phantom planes extends from K = 1 to K = KP-KBP-KTP.

The second of the three coarse meshes (the JREG mesh) is defined identically for each J-plane. The coarse cells within a J-plane are a fairly arbitrary set of rectangles bounded by X- and Z-grid lines, with the user defining the bounds and interfaces. An example of a partition of a J-plane is shown in Figure 24.2. Similarly, for the third or IREG simulation, each coarse cell defined within a single I-plane is bounded by Y- and Z-grid lines.

The specification of any of these three coarse meshes requires identifying:

- 1. the bounds of the coarse cells within a single plane
- 2. the other coarse cells with which each one has an interface







 $\smile$ 

FIGURE 24.2. Coarse Mesh for a J-Plane

3. the orientation of the interface between any two contacting cells. The code limits the coarse computational cells to the computational region of the rectangular grid. The user can define these cells with rectangular grid index ranges, allowing the HYDRA-II coding to restrict the defined coarse cells to the rectangular grid flow region along the curved parts of the boundary.

It is practical to use on the order of 30 or 40 computational cells in each plane for each of the three coarse meshes. It is suggested that the coarse cells be chosen to give a fair representation of the physical phenomena occurring. Experience to date indicates that this selection is not critical, as benefits from REBQ can be obtained with a variety of coarse meshes.

#### 24.2 PARAMETER STATEMENT INFORMATION

The following array-dimensioning parameters have the same significance and should have the same value as in Chapter 4.0 (subroutine GRID):

• IP, JP, KP, NEFAP

The following array dimensioning parameters were discussed in Chapter 4.0 (subroutine GRID) and were defined in Section 6.2 (subroutine THERM):

• KBP, KTP

The following array dimensioning parameters are defined in Chapter 25.0 (subroutine CROUT):

• ICRP, JCRP

Additional dimensioning parameters required are:

- KREGP Maximum value of KREG allowed by dimensioning, where KREG is the number of coarse cells in a K-plane for the first coarse mesh pressure correction solution (the KREG solution).
- JREGP Maximum value of JREG allowed by dimensioning, where JREG is the number of cells in a J-plane for the second coarse mesh pressure correction solution (the JREG solution).

- IREGP Maximum value of IREG allowed by dimensioning, where IREG is the number of cells in an I-plane for the third coarse mesh pressure correction solution (the IREG solution).
- KBIDAP The length of the array KBID, used to store the cell interface information for the KREG partition. The KBID array stores, for each coarse cell of the KREG mesh, a list of pairs of numbers for interfaces with other coarse cells not already specified. The pair for an interface comprises the neighbor cell number and a number specifying the orientation of their interface plane.
- JBIDAP The length of the array JBID, used to store the cell interface information for the JREG partition, analogous to KBIDAP for the KREG partition.
- IBIDAP The length of the array IBID, used to store the cell interface information for the IREG partition, analogous to KBIDAP for the KREG partition.

## 24.3 INPUT FORMAT

# 24.3.1 Overview

The REBQ input can be considered in four blocks:

- specifications on the level of printout and execution options for the pressure correction solutions on the REBQ type partitions of the flow region
- cell geometry and interfaces in the I-J planes (planes of constant K) for the KREG partition
- 3. cell geometry and interfaces in the I-K planes (planes of constant J) for the JREG partition
- cell geometry and interfaces in the J-K planes (planes of constant I) for the IREG partition.

## 24.3.2 Printout and Execution Options

General Input Format

NECHO NMAX, INFO KBOUND, JBOUND, IBOUND AKKMIN, AJJMIN, AIIMIN

#### General Input Description

- NECHO Echoing switch for this section of input. If input is to be echoed, then NECHO = 1; otherwise, 0.
- NMAX Number of times to cycle through the approximate solution on the three coarse region partitions on a call to REBQ. The preferred value is simulation-dependent, and should be chosen by setting NMAX initially to 3 with INFO set to 1. Observe the printed divergence error and adjust the value of NMAX if necessary to an observed point of diminishing returns on the divergence error reduction.
- INFO Flag for the level of printout desired. If INFO = 1, print divergence error maxima and location before each of the three coarse partition solutions at each of the NMAX iterations. If INFO = 2, print divergence error maxima and location before and after each of these coarse partition solutions at each of the NMAX iterations. If INFO = 3, print also the coefficient matrices for the coarse partitions. If INFO = 0, bypass printing. After choosing and verifying a satisfactory value of NMAX, it is desirable to set INFO = 0.
- KBOUND, JBOUND IBOUND Index of a phantom (boundary) plane related to inflow and outflow conditions. This version of HYDRA-II is restricted to no-flow boundaries; therefore, KBOUND, JBOUND, and IBOUND should each be equal to 1.

 AKKMIN, AJJMIN, AIIMIN - Minimum values of the coarse mesh coefficient matrix related to inflow and outflow conditions. This version of HYDRA-II is restricted to noflow boundaries; therefore, AKKMIN, AJJMIN, and AIIMIN should each have the value of 0.1E-20.

Input File Example

```
1849 1/rebq
1850 3,0
1851 1,1,1
1852 0.1e-20,0.1e-20,0.1e-20
```

Echoed Input File Example

```
1216 rebq nmax=3 info=0

1217 rebq kbound= 1 jbound≈ 1 ibound= 1

1218 rebq akkmin=0.100e-20 ajjmin=0.100e-20 alimin=0.100e-20

1219
```

The input file example requests echoing on line 1849 with NECHO = 1, sets number of solutions on the three partitions to NMAX = 3 on line 1850, and suppresses diagnostic printout with INFO = 0. A value NMAX = 3 was set (for this application) after inspection of patterns of divergence error, so INFO = 0 is appropriate to obtain no further divergence error information from the calls to REBQ.

24.3.3 KREG Partition Specifications

General Input Format

NECHO KREG KRID(L), L = 1, KRIDAP NECHO KBIDA KBID(L), L = 1, KBIDAP

The array KRID contains KREG sets of X-Y region specifications end-to-end, each set having six entries in the form:

KREGNO, NBND, IBEG, IEND, JBEG, JEND

The array KBID contains data sets stored end-to-end, each set having the form:

KREGA, KREGB₁, MBTYP₁, KREGB₂, MBTYP₂, ..., KREGB_{NBND}(KREGA), MBTYP_{NBND}(KREGA)

Each set in KBID has as a leading entry a region number KREGA that was one of the regions KREGNO specified in KRID. This is followed by NBND(KREGA) pairs of integers, where NBND(KREGA) was the second entry for set KREGA in KRID. Each pair (KREGB_i, MBTYP_i) of these integers has as first entry a number KREGB of another region in the X-Y plane that adjoins region KREGA, and as second entry a number MBTYP (-1, +1, -2, or +2) that tells whether region KREGB is in the -X (MBTYP = -1), +X (MBTYP = +1), -Y (MBTYP = -2), or +Y (MBTYP = +2) direction from region KREGA. An interface should be specified only once. If region KREGB is specified as adjoining region KREGA, then KREGA should not be included in the list of regions adjoining KREGB.

General Input Description

•	NECHO	<ul> <li>Echoing switch for this section of input. If input is to be echoed, then NECHO = 1; otherwise, 0.</li> </ul>
•	KREG	<ul> <li>Number of coarse computational cells in an X-Y plane at each K-plane.</li> </ul>
•	KRID	<ul> <li>Array defining the coarse cells in the X-Y plane for each K-plane. The data entries for the regions follow each other end-to-end, the six entries for each region being: KREGNO, NBND, IBEG, IEND, JBEG, JEND</li> </ul>
•	KREGNO	<ul> <li>Number of a region in the X-Y plane for the KREG computation. The region numbers and their accompanying six-entry data sets must appear consecutively with indices KREGNO running 1 through KREG without omissions.</li> </ul>

- NBND Number of interfaces in the I-J plane for cell KREGNO not previously specified for some other cell. See forthcoming discussion for (KREGB, MBTYP) pairs.
- IBEG, IEND, JBEG, JEND The beginning and end in the I-direction, followed by the beginning and end in the J-direction, of the included fine mesh cells for cell KREGNO in the coarse KREG partition of the X-Y plane. The KREG coarse cells are further restricted to the active computational region for the momentum equations defined the IMEND, JMBEG, and JMEND arrays.
- KBIDA The number of active entries (individual numbers) forthcoming in the KBID array (which is dimensioned to KBIDAP).
- KBID The array of sets of information on the interfaces of the cells of the KREG partition, stored end-to-end as previously indicated, each set having the form: KREGA, KREGB₁, MBTYP₁, KREGB₂, MBTYP₂, ..., KREGB_{NBND}(KREGA), MBTYP_{NBND}(KREGA)
- KREGB, MBTYP The index of a cell having an interface with cell KREGA, and a specification of its relative position. The values of MBTYP and their meanings are:

MBTYP	Direction of	of KREGB	From KREGA	Interface	Plane
-1		-X		Y-Z	
+1		+X		Y-Z	
-2		-Y		X-Z	
+2		+Y		X-Z	

The interface between two regions should be specified only once in the KBID array, which is achieved if the region index KREGB is always greater than KREGA in the sets in KBID.

1853 1/rebq/krid 1854 35 1855 1,2,2,4,2,9, 1856 2,5,5,7,2,13, 1857 3,1,8,12,2,4, 1858 4,1,2,4,10,12, 1859 5,2,8,12,5,13, 1860 6,1,13,21,5,13, 1861 7,2,2,4,13,16, 1862 8,3,5,7,14,18, 1863 9,2,8,12,14,18, 1864 10,2,13,21,14,18, 1865 11,1,22,24,14,18, 1866 12,2,2,4,17,21, 1867 13,2,5,7,19,21, 1868 14,3,8,12,19,21, 1869 15,3,13,24,19,21, 1870 16,2,2,4,22,27, 1871 17,3,5,9,22,27, 1872 18,3,10,13,22,27, 1873 19,2,14,16,22,27, 1874 20,1,17,24,22,27, 1875 21,3,2,4,28,32, 1876 22,2,5,7,28,30, 1877 23,2,8,12,28,30, 1878 24,2,13,24,28,30, 1879 25,3,2,4,33,36, 1880 26,2,5,7,31,35, 1881 27,2,8,12,31,35, 1882 28,2,13,21,31,35, 1883 29,0,22,24,31,35, 1884 30,2,2,4,37,39, 1885 31,3,8,12,36,44, 1886 32,0,13,21,36,44, 1887 33,1,2,4,40,47, 1888 34,1,5,7,36,47, 1889 35,0,8,12,45,47 1890 1/rebg/kbid 1891 168 1892 1,2,1,4,2, 1893 2,3,1,4,-1,5,1,7,-1,8,2, 1894 3,5,2, 1895 4,7,2, 1896 5,6,1,9,2, 1897 6,10,2, 1898 7,8,1,12,2, 1899 8,9,1,12,-1,13,2, 1900 9,10,1,14,2, 1901 10,11,1,15,2,

1902	11,15,2,
1903	12,13,1,16,2,
1904	13,14,1,17,2,
1905	14,15,1,17,2,18,2,
1906	15,18,2,19,2,20,2,
1907	16,17,1,21,2,
1908	17,18,1,22,2,23,2,
1909	18,19,1,23,2,24,2,
1910	19,20,1,24,2,
1911	20,24,2,
1912	21,22,1,25,2,26,1,
1913	22,23,1,26,2,
1914	23,24,1,27,2,
1915	24,28,2,29,2,
1916	25,26,1,30,2,34,1,
1917	26,27,1,34,2,
1918	27,28,1,31,2,
1919	28,29,1,32,2,
1920	30,33,2,34,1,
1921	31,32,1,34,-1,35,2,
1922	33,34,1,
1923	34,35,1

# Echoed Input File Example

1220	rebg	kreg= 35	maximum curr	ent dimension	for kreg	ls	35			
1221	rebq	krid	kreg	boundary			c	ellic	ocati (	D <b>N</b>
1222			-	surfaces			l beg	lend	jbeg	jend
1223			1	2			2	4	2	9
1224			2	5			5	7	2	13
1225			3	1			8	12	2	4
1226			4	1			2	4	10	12
1227			5	2			8	12	5	13
1228			6	1			13	21	5	13
1229			7	2			2	4	13	16
1230			8	3			5	7	14	18
1231			9	2			8	12	14	18
1232			10	2			13	21	14	18
1233			11	1			22	24	14	18
1234			12	2			2	4	17	21
1235			13	2			5	7	19	21
1236			14	3			8	12	19	21
1237			15	3			13	24	19	21
1238			16	2			2	4	22	27
1239			17	3			5	9	22	27
1240			18	3			10	13	22	27
1241			19	2			14	16	22	27
1242			20	1			17	24	22	27
1243			21	3			2	4	28	32
1244			22	. 2			5	7	28	30
1245			23	2			8	12	28	30
1246			24	2			13	24	28	30
1247			25	3			2	4	33	36
1248			26	2			5	7	31	- 35
1249			27	2			8	12	31	35
1250			28	2			13	21	31	35
1251			29	0			22 -	24	31	35
1252			30	2			2	4	37	39

•

1253			31	3			8	12	36	44				
1254			32	0			13	21	36	44				
1255			33	1			2	4	40	47				
1256			34	1			5	7	36	47				
1257			35	0			8	12	45	47				
1258														
1259	rebq	kbida=168	maximum current	dime	nsion fo	or kbio	ia is 16	58						
1260	rebq	kbid	kreg	50 <b>05</b>	plane	sees	plane	sees	plane	588 <b>5</b>	plane	50 <b>8</b> 5	plane	
1261				kr eg	type	kreg	type	kreg	type	kreg	type	kreg	type .	
1262 \			1	2	1	4	2				•			
1263			2	3	1	4	-1	5	1	7	-1	8	2	
_1264			3	5	2					-				
1265			4	7	2				·					
1266			5	6	1	9	2							
1267			6	10	2									
1268			7	8	1	12	2							
1269			8	9	1	12	-1	13	2					
1270			9	10.	1	14	2							
1271			10	11	1	15	2							
1272			11	15	2									
1273			12	13	-1	16	2							
1274			13	14	· 1	17	2	-			•			
1275			14	15	1	17	2	18	2					
1276			15	18	2	19	2	20	2					
1277			16	17	1	21	2							
1278			17	18	1	22	2	23	. 2					
1279			18	19	1	23	2	24	2					
1280			19	20	1	24	2							
1281			20	24	2									
- 1282			21	22	1	25	2	26	1					
1283			22	23	1	26	2							
1284			23	24	1.	27	2							
1285			24	28	2	29	2							
1286			25	26	1	30	2	34	1					
1287			26	27	1_	34	2							
1288			27	28	1	31	2							
1289			28	29	1	32	2							
1290			30	33	2	34	1							
1291			31	32	1	34	-1	35	2					
1292			33	34	1									
1293			34	35	1									

This input file example requests the partition shown in Figure 24.1 for the KREG coarse region computation.

The input file example requests echoing on line 1853 with NECHO = 1, then states on line 1854 that 35 (KREG) regions in each K-plane will be used. Lines 1855 through 1889 specify those 35 regions. For example, line 1855 indicates that region 1 (first entry) has two specified interfaces in the X-Y plane, and has X-Y extent 2 < I < 4, 2 < J < 9. Line 1856 indicates that region 2 has five not previously specified interfaces in the X-Y plane (the interface with region 1 not being included in this list). Line 1890 of the input example introduces the forthcoming KBID array data by again setting NECHO to 1 with accompanying comments. Line 1891 promises 168 forthcoming numbers to specify the interfaces between the KREG type cells, and these 168 entries in the KBID array appear in lines 1892 through 1923. Line 1892 indicates that cell 1 (first number) sees cell 2 (second number) on its positive X side (as specified by the third number, 1), and sees cell 4 (fourth number) on its +Y side (as specified by the fifth number, 2). Recall that two pairs of bounding cells for cell 1 had been specified by the second entry NBND = 2 for cell 1 on line 1855. Line 1893 gives five new interfaces for cell 2, but does not give the 1-2 interface, which was specified on line 1892. No trailing zeros appear in this KBID array data because the array was dimensioned exactly to KBIDAP = 168.

The echoed input gives the KREG information in tabular form.

## 24.3.4 JREG Partition Specifications

General Input Format

```
NECHO
JREG
JRID(L), L = 1, JRIDAP
NECHO
JBIDA
JBID(L), L = 1, JBIDAP
  General Input Description
               - Echoing switch for this section of input, if input is
  NECHO
                 to be echoed, then NECHO = 1; otherwise, 0.
  JREG
               - Number of coarse computational cells in the X-Z plane
                  for each J-plane.
               - Array defining the coarse cells in the X-Z plane for
  JRID
                 each J-plane. The data entries for the regions follow
```

each region being

consecutively end-to-end, with the six entries for

JREGNO, NBND, IBEG, IEND, KBEG, KEND
- JREGNO Number of a region in the X-Z plane for the JREG computation. Region numbers run 1 through JREG consecutively.
- NBND Number of interfaces in the I-K plane for cell JREGNO not previously specified for some other cell. See forthcoming discussion for (JREGB, MBTYP) pairs.
- IBEG, IEND, KBEG, KEND The beginning and end in the I-direction, followed by the beginning and end in the K-direction, of the fine mesh cells included in the coarse mesh cell JREGNO. The JREG coarse cells are further restricted in the code to the active computational region for the momentum equations defined by the IMEND, JMBEG, and JMEND arrays.
- JBIDA The number of active entries (individual numbers) forthcoming in the JBID array (which is dimensioned to JBIDAP).
- JBID The array of sets of information on the interfaces of the cells of the JREG partition, stored end-to-end, with each set having the form: JREGA, JREGB1, MBTYP1, JREGB2, MBTYP2, ...JREGBNBND(JREGA), MBTYPNBND(JREGA)
- JREGB, MBTYP The index of a cell having an interface with cell JREGA, and a specification of their relative position. The values of MBTYP and their meanings are:

MBTYPDirection of KREGB From KREGAInterface Plane-1-XY-Z+1+XY-Z-3-ZX-Y+3+ZX-Y

Input File Example

1924 1/rebq/jrid 1925 30

1926 1,2,2,4,2,2
1927 2,2,5,7,2,2,
1928 3,2,8,12,2,2,
1929 4,2,13,21,2,2,
1930 5,1,22,24,2,2,
1931 6,2,2,4,3,9,
1932 7,2,5,7,3,9,
1933 8,2,8,12,3,9,
1934 9,2,13,21,3,9,
1935 10,1,22,24,3,9,
1936 11,2,2,4,10,13,
1937 12,2,5,7,10,13,
1938 13,2,8,12,10,13,
1939 14,2,13,21,10,13,
1940 15,1,22,24,10,13,
1941 16,2,2,4,14,17,
1942 1/,2,5,/,14,17,
1943 18,2,8,12,14,17,
1944 $19,2,13,21,14,17,$
1945 20,1,22,24,14,17,
1940 21,2,2,4,18,24,
1347 $22,2,3,7,10,24,1049$ $22,2,0,12,10,24$
1040 20, 20, 10, 10, 24, 100, 24, 100, 24, 20, 20, 100, 20, 20, 20, 100, 20, 20, 20, 100, 20, 20, 20, 20, 20, 20, 20, 20, 20,
1050 25 1 22 24 10 24
1950 25,1,22,24,10,24,
1952 27 1 5 7 25 25
1953 28.1.8.12.25.25.
1954 29.1.13.21.25.25.
1955 30.0.22.24.25.25
1956 1/reba/jbid
1957 127
1958 1,2,1,6,3,
1959 2,3,1,7,3,
1960 3,4,1,8,3,
1961 4,5,1,9,3,
1962 5,10,3,
1963 6,/,1,11,3,
1964 7,8,1,12,3,
1965 8,9,1,13,3,
1900 9,10,1,14,3,
1907 10, 15, 5, 1060 11 12 1 16 2
1900 11, 12, 1, 10, 3, 1060 12, 12, 1, 17, 2
1070 12 1/ 1 10 2
1971 14 15 1 10 3
1972 15.20 3
1973 16.17.1.21.3.
1974 17,18,1,22,3
1975 18,19,1,23,3.
1976 19,20,1,24,3.

1977	20,25,3,
1978	21,22,1,26,3,
1979	22,23,1,27,3,
1980	23,24,1,28,3,
1981	24,25,1,29,3,
1982	25,30,3,
1983	26,27,1,
1984	27,28,1,
1985	28,29,1,
1986	29,30,1
1985 1986	28,29,1, 29,30,1

## Echoed Input File Example

1294												
1295	rebq	jreg= 30	maximum curr	ent dimension	for jreg	is 30						
1295	rebq	jrid	jreg	boundary			cettt	ocatio	n			
1297				surfaces		Ibeg	lend	kbeg	kənd			
1298			1	2		2	4	2	2			
1299			2	2		5	7	2	2			
1300			3	2		8	12	2	2			
1301			4	2		13	21	2	2			
1302			5	1		22	24	2	2			
1303			6	2		. 2	4	3	9			
1304			7	2		5	7	3	9			
1305			8	2		8	12	3	9			
1306			9	2		13	21	3	9			
1307			10	1		22	24	3	9			
1308			11	2		2	4	10	13			
1309			12	<b>2</b> ·		5	7	10	13			
1310			13	2		8	12	10	13			
1311			14	2		13	21	10	13			
1312			15	1		22	24	10	13			
1313			16	2		2	4	14	17			
1314			17	2		5	7	14	17			
1315			18	2		8	12	14	17			
1316			19	2		13	21	14	17		·	
1317			20	1		22	24	14	17			
1318			21	2		2	4	18	24			
1319			22	2		5	7	18	24			
1320			23	2		8	12	18	24			
1321			24	2		13	21	18	24			
1322			25	1		22	24	18	24			
1323			26	1		2	4	25	25			
1324			27	1		5	7	25	25			
1325			28	1		8	12	25	25			
1326			29	1		13	21	25	25			
1327			30	0		22	24	25	25			
1328												
1329	rebo	jbida=127	maximum cur	rent dimension	for jbl	da is 12	7					
1330	rebq	jbid	jreg	sees plane	e sees	plane	sees	plane	Sees	plane	sees	plane
1331		•		jreg type	jreg	type	jrəg	type	jrøg	type '	jreg	type
1332			t	2 1	6	3						•
1333			2	31	7	3						
1334			3	4 1	8	3						
1335	-		4	51	9	3						
1336			5	10 3						•		
1337			· 6	71	11	3						
1338			7	8 1	12	3						
1339			8	9 1	13	3						
1340			9	10 1	14	3						

1341	10	15	3		
~1342	11	12	1	16	3
1343	12	13	1	17	3
1344	13	14	1	18	3
1345	14	15	1	19	3
1346	15	20	3		
-1347	16	17	1	21	3
1348	17	18	1	22	3
1349	18	19	1	23	3
1350	19	20	1	24	3
1351	20	25	3		
1352	21	22	1	26	3
1353	22	<b>23</b> ⁻	1	27	3
1354	23	24	1	28	3
1355	24	25	1	29	3
1356	25	30	3		
1357	26	27	1		
1358	27	28	1		
1359	28	29	1		
1360	29	30	1		

This example requests the partition shown in Figure 24.2 for the JREG coarse region computation. The section shown in Figure 24.2 is the plane of constant Y passing through the cask axis.

The input file example requests echoing on line 1924 with NECHO = 1, then indicates on line 1925 that 30 (JREG) regions in each J-plane will be used. Lines 1926 through 1955 specify those 30 regions. Line 1926 indicates that region 1 (first number) has two (second number) specified interfaces in the X-Z plane, and has a fine mesh extent 2 <I < 4, 2 < K < 2. Note that the K indices are in the momentum equations grid, whose indices in the K-direction are offset from those of the energy equation grid by KBP. Line 1927 indicates region 2 has two not-previously specified interfaces and has a fine mesh extent 5 < I < 7, 2 < K < 2.

Line 1956 of the input file example resets NECHO to 1 while serving to introduce with comments the specification of the interfaces for the JREG partition in the forthcoming JBID array. Line 1957 specifies that 127 data entries are forthcoming to specify those interfaces. Because the JBID array was dimensional to JBIDAP = 127 for this simulation, the 127 entries on lines 1958 through 1986 fill that array and no filling of unused locations with zeros is needed. Line 1958 specifies the two interfaces for region 1 (first entry) that were alluded to on line 1926, the interfaces being specified by the data pairs (2,1) and (6,3). The (2,1) pair states that region 2 is in the +X

direction from region 1, while the (6,3) pair states that region 6 is in the +Z direction from region 1 in the JREG partition.

Line 1959 of the input file example specifies the two not-previously specified interfaces of JREG cell 2. Cell 2 (first number) has an interface with cell 3 (second number) on its +X (third number, +1) side, and with cell 7 (fourth number) on its +Z (fifth number, +3) side.

The echoed input summarizes the information on the JREG partition and interfaces in tabular form.

24.3.5 IREG Partition Specifications

General Input Format

NECHO IREG IRID(L), L = 1, IRIDAP NECHO IBIDA IBID(L), L = 1, IBIDAP

General Input Description

•	NECHO	Echoing switch for this section of input. If input is to be echoed, then NECHO = 1; otherwise, O.
•	IREG	Number of coarse computational cells in a Y-Z plane at each I-plane.
•	IRID	Array defining the coarse cells in a Y-Z plane for each I-plane. The data entries for the regions follow consecutively end-to-end, the six entries for each region being: IREGNO, NBND, JBEG, JEND, KBEG, KEND
•	IREGNO	Number of a region in the Y-Z plane for the IREG computation. Region numbers run 1 through IREG consecutively.
•	NBND	Number of interfaces in the J-K plane for cell IREGNO not previously specified for some other cell. See

forthcoming discussion of (IREG, MBTYP) pairs.

- JBEG, JEND, KBEG, KEND The beginning and end in the J-direction, followed by the beginning and end in the K-direction, of the fine mesh cells to include in the coarse mesh cell IREGNO. The IREG coarse cells are further restricted in the code to the active computational region for the momentum equations defined by the IMEND, JMBEG, and JMEND arrays.
- IBIDA The number of active entries (individual numbers) forthcoming in the IBID array (which is dimensioned to IBIDAP).
- IBID The array of sets of information on the interfaces of the cells of the IREG partition, stored end-to-end, with each set having the form: IREGA, IREGB₁, MBTYP₁, IREGB₂, MBTYP₂, ...IREGB_{NBND}(IREGA), MBTYP_{NBND}(IREGA)

 IREGB, MBTYP - The index of an IREG type cell having an interface with cell IREGA, and a specification of its relative position. The values of MBTYP and their meanings are:
 MBTYP Direction of KREGB From KREGA Interface Plane

DITE	DITECTION OF KREAD FION KREAK	Incertace Fig
-2	-Y	X-Z
+2	+γ	X-Z
-3	-Z	X-Y
+3	+Z	X-Y

Input File Example

1987 1/rebq/irid 1988 35 1989 1,2,2,10,2,4, 1990 2,2,11,16,2,4, 1991 3,2,17,20,2,4, 1992 4,2,21,28,2,4, 1993 5,2,29,32,2,4, 1994 6,2,33,38,2,4, 1995 7,1,39,47,2,4, 1996 8,2,2,10,5,10, 1997 9,2,11,16,5,10, 1998 10,2,17,20,5,10,

1999 11,2,21,28,5,10, 2000 12,2,29,32,5,10, 2001 13,2,33,38,5,10, 2002 14,1,39,47,5,10, 2003 15,2,2,10,11,15, 2004 16,2,11,16,11,15, 2005 17,2,17,20,11,15, 2006 18,2,21,28,11,15, 2007 19,2,29,32,11,15, 2008 20,2,33,38,11,15, 2009 21,1,39,47,11,15, 2010 22,2,2,10,16,22, 2011 23,2,11,16,16,22, 2012 24,2,17,20,16,22, 2013 25,2,21,28,16,22, 2014 26,2,29,32,16,22, 2015 27,2,33,38,16,22, 2016 28,1,39,47,16,22, 2017 29,1,2,10,23,25, 2018 30,1,11,16,23,25, 2019 31,1,17,20,23,25, 2020 32,1,21,28,23,25, 2021 33,1,29,32,23,25, 2022 34,1,33,38,23,25, 2023 35,0,39,47,23,25 2024 1/rebg/ibid 2025 150 2026 1,2,2,8,3, 2027 2,3,2,9,3, 2028 3,4,2,10,3, 2029 4,5,2,11,3, 2030 5,6,2,12,3, 2031 6,7,2,13,3, 2032 7,14,3, 2033 8,9,2,15,3, 2034 9,10,2,16,3, 2035 10,11,2,17,3, 2036 11,12,2,18,3, 2037 12,13,2,19,3, 2038 13,14,2,20,3, 2039 14,21,3, 2040 15,16,2,22,3, 2041 16,17,2,23,3, 2042 17,18,2,24,3, 2043 18,19,2,25,3, 2044 19,20,2,26,3, 2045 20,21,2,27,3, 2046 21,28,3, 2047 22,23,2,29,3, 2048 23,24,2,30,3, 2049 24,25,2,31,3,

2050	25	,26	,2,	,32	.3.
2051	26	27	2	33	3,
2052	27	28	2	34	3
2053	28	35	3		
2054	29	30	2		
2055	30	31	2		
2056	31	32	2		
2057	32	33	2		
2058	33,	34,	2,		
2059	34,	35,	2		

# Echoed Input File Example

1362	rebq	lreg= 35	maximum current	dimens	sion for	Ireg	ls	35						
1363	rebq	1rid	ireg t	ounda	ry i			Ċ	cellic	ocatic	n			
1364				surface	BS			jbeg	jend	kbeg	kend			
1365			1	2				2	10	2	4			
1366			2	2				11	16	2	4			
1367			3	2				17	20	2	4			
1368			4	2				21	28	2	4			
1369			5	2				29	32	2	4			
1370			6	2				33	38	2	4			
1371			7	1				39	47	2	4			
1372			8	2				2	10	5	10			
1373			9	2				11	16	5	10			
1374			10	2				17	20	5	10			
1375			11	2	•			21	28	5	10			
1376			12	2	•			29	32	5	10			
1377			13	2				33	38	5	10			
1378			14	1				39	47	5	10			
1379			15	2				2	10	11	15			
1380			16	2				11	16	11	15			
1381			17	2				17	20	11	15			
1382			18	2				21	28	11	15			
1383			19	2				29	32	11	15			
1384			20	2				33	38	11	15			
1385			21	1				39	47	11	15			
1386			22	2				2	10	16	22			
1387			23	2				11	16	16	22			
1388			24	2				17	20	16	22			
1389			25	2				21	28	16	22			
1390			26	2				29	32	16	22			
1391			27	2				33	38	16	22			
1392			28	1				39	47	16	22			
1393			29	1				2	10	23	25			
1394			30	1				11	16	23	25			
1395			31	1				17	20	23	25			
1396			32	1				21	28	23	25			
1397			33	1				29	32	23	25			
1398			34	Ť				33	38	23	25			
1399			35	ò				39	47	23	25			•
1400				•					•••					
1401	rebo	lbida=150	maximum current	dimer	nsion fo	r ibia	da i	s 150	ר					
1402	rebo	ibid		CARC	niane	CRAC	nia.		SAAS	plane	5865	ensio	5885	plane
1403	1004		ii og	irea	type	Irea	tvn	A	Irea	type	Irea	type	Irea	type
1404			1	09	2	cg	- , , p - , , p	-		.,,,,,		.,		.,
1405			2	3	2	ğ	ر ۲				•			
1405				Á	2	10	ž							
1407			Ă	5	2	11	3							
1408			5	6.	2	12	- - 							
_ 1700			,	U	~	12	,							

•

1409	б	7	2	13	3
1410	7	14	3		-
1411	8	9	2	15	3
1412	9	10	2	16	3
_1413	10	11	2	17	3
1414	11	12	2	18	3
1415	12	13	2	19	3
1416	13	14	2	20	3
1417	14	21	3		•
1418	15	16	2	22	3.
1419	16	17.	2	23	3
1420	17	18	2	24	3
1421	18	19	2	25	3
1422	19	20	~2	26	3
1423	20	21	ž	27	5
1424	21	28	3		
1425	22	23	2	29	3
1426	23	24	2	30	3
1427	24	25	2	31	3
1428	25	26	. 2	32	3
1429	26	27	2	33	3
1430	27	28	. 2	34	3
1431	28	35	-3		
1432	29	30	2		
1433	30	31	2		
1434	- 31	32	2		
1435	32	33	2		
1436	33	34	2		
1437	34	35	2		

This input is quite analogous to that for the KREG partition and the JREG partition, defining the regions in a J-K layer in lines 1988 through 2023, then defining their interfaces in lines 2025 through 2059.

#### 25.0 SUBROUTINE CROUT

Subroutine CROUT employs a direct method for the solution of linear matrix equations associated with subroutines REBA and REBQ. The Crout method is used to solve matrix equations of the form

## AX = B

where A is an m by m square matrix and X and B each have m rows and n columns. A discussion of the Crout method may be found in Westlake (1968).

## 25.1 PARAMETER STATEMENT INFORMATION

The dimension of arrays A and B are specified by two parameters:

- ICRP Row and column dimension of A and rows of B. If subroutine REBA is used, then ICRP = 3. If subroutine REBQ is used, then ICRP = MAX(IREG,JREG,KREG). If both subroutines are used, then ICRP must equal the largest of the above two dimensions.
- JCRP Number of columns of B. If subroutine REBA is used, then JCRP = 4. If subroutine REBQ is used, then JCRP = ICRP. If both subroutines are used, then JCRP must equal the largest of the above two dimensions.

#### 25.2 INPUT FORMAT

Subroutine CROUT does not read the input file.

## 26.0 SUBROUTINE AF

Subroutine AF solves a Poisson equation (derived in <u>Volume I - Equations</u> <u>and Numerics</u>, Chapter 9.0) for the pressure-correction field. It is one of the set of subroutines (viz., PILES, REBS, REBQ, and AF) that can be called upon by subroutine PITER to produce this solution. The method employed in this routine is effectively an approximate factorization of the pressure-correction-field matrix operator. Since the factorization is approximate, the exact solution is not obtained in one pass through the algorithm. The user must specify the number of times the routine will cycle through the algorithm in each pass through the subroutine. This is done with input variable NMAX.

Subroutine AF also allows the user to monitor the convergence history of this algorithm. By setting input variable INFO = 1, AF will print the following information: iteration count, the value of the current pressure-correction at the (I,J,K) mesh location corresponding to the cell experiencing the largest right-hand-side residual (in absolute value), the right-hand-side residual at cell (I,J,K), and the I, J, and K cell indices for this "worst-case" cell. With INFO = 1, this information is provided after entering AF just prior to commencement of the iteration (for which case the iteration count and the largest right-hand-side residual are printed as having values of 0), and once again for each of the NMAX iterations. If this output is not desired, specify INFO = 0 in the input.

#### 26.1 PARAMETER STATEMENT INFORMATION

Subroutine AF requires the specification of parameters IP, JP, KP, KBP, and KTP. These data define the overall computational mesh and are described in the discussion of subroutine GRID in Chapter 4.0.

#### 26.2 INPUT FORMAT

#### 26.2.1 Overview

Very little input is required by subroutine AF. Only three variables are read--NECHO, NMAX, and INFO. The input sequence and definition is provided below.

## General Input Format

NECHO NMAX,INFO

## General Input Description

- NECHO Echoing switch for this section of input. If
  NECHO = 1, an echo of the input for this section will be provided in the output; if NECHO = 0, this echoing will not be provided.
- NMAX Maximum number of iterations per pass through subroutine AF. The appropriate setting for NMAX is very problem-specific if one wishes to optimally employ the pressure-iteration scheme in HYDRA-II. NMAX should be set in this routine after factoring in the convergence history of AF relative to that realized when subroutine PILES is employed. A more detailed discussion of this is provided in Chapter 21.0 of the User's Manual.
- INFO Convergence history print-out switch. INFO = 0 precludes output; INFO = 1 produces convergence history output as described in the above text. Scanning the pressure-correction field to locate the "worst-case" residual is a relatively expensive process. Therefore, this switch should be set to zero unless a resetting of NMAX is desired.

Input File Example

2060 1/af 2061 5,0

----

## Echoed-Input File Example

1439 af nmax= 5 info=0

NECHO is set to 1 on input line 2060. NMAX and INFO are set to 5 and 0, respectively, on input line 2061. With NECHO set to 1, these input data are echoed in the output on line 1439.

#### 27.0 SUBROUTINE AVG

Subroutine AVG computes the pressure adjustment required to satisfy the user-specified constraint of either fixed total fluid mass or fixed average pressure for the system. In either case, AVG takes advantage of the indeterminacy of the pressure field defined by the momentum equations. This indeterminacy allows the pressure field to be shifted by a spatially-uniform amount in every cell of the computational mesh to effect the desired mass or averagepressure constraint.

The choice of one or the other is determined by the user with a positive input for FIXEDM (for fixed total system mass) or FIXEDP (for fixed average system pressure). If either of the options is NOT desired, the corresponding input should be zero.

#### 27.1 PARAMETER STATEMENT INFORMATION

Subroutine AVG requires the specification of parameters IP, JP, KP, KBP, and KTP. These data define the overall computational mesh and are described in the discussion of subroutine GRID in Chapter 4.0.

#### 27.2 INPUT FORMAT

#### 27.2.1 Overview

Very little input is required by subroutine AVG. Only three variables are read--NECHO, FIXEDM, and FIXEDP. The input sequence and definition is provided below.

#### General Input Format

NECHO FIXEDM,FIXEDP

#### General Input Description

 NECHO - Echoing switch for this section of input. If
 NECHO = 1, an echo of the input for this section will be provided in the output; if NECHO = 0, this echoing will not be provided.

- FIXEDM Flag to indicate whether or not the system mass is fixed and, if so, at what value. If this option is not to be used, set FIXEDM = 0.0; otherwise, set FIXEDM = desired system mass in grams.
- FIXEDP Flag to indicate whether or not the system is operating at fixed average pressure. If this option is not to be used, set FIXEDP = 0.0; otherwise, set FIXEDP = desired average system pressure in dyn/cm².

Input File Example

2062 1/avg 2063 0.0.0.496e+6

Echoed-Input File Example

1441 avg fixedm=0,0000000e+00 fixedp=0,4960000e+06

NECHO is set to 1 on input line 2062. FIXEDM and FIXEDP have been set to 0 grams and 496000 dyn/cm², respectively. Therefore, this simulation will operate with a fixed average pressure.

## 28.0 SUBROUTINE PRINTL

Subroutine PRINTL is called from numerous locations to print array variables, according to user options or code defaults. PRINTL prints the triplydimensioned variable in its call list. No user attention to PRINTL is required except to the dimensioning parameters.

#### 28.1 PARAMETER STATEMENT INFORMATION

Subroutine PRINTL requires the specification of parameters IP and JP that define the computational mesh and are described in Chapter 4.0, Subroutine GRID. Two additional parameters, NPLA1P and NPLA2P, are required for specification of printing options. These are described in Chapter 3.0, Program MAIN.

## 28.2 INPUT FORMAT

Subroutine PRINTL does not read user input.

#### 29.0 SAMPLE PROBLEM

This chapter presents a relatively simple sample problem with many of the characteristics of a typical spent fuel cask. The configuration is still sufficiently detailed, however, so that many of the input options available in HYDRA-II can be exercised. General observations on code setup and operation, and on output interpretation, are made and illustrated by means of this sample problem. The complete input and output file obtained from the execution of this sample problem is provided in Appendixes A and B. This, together with the source code and restart tape available in the HYDRA-II package, should provide the necessary checkpoints for the user to get comfortable with the input to the code.

In this chapter, the physical characteristics of the sample problem are first presented. Having oriented the user to the configuration, the following sections of this chapter will discuss some of the salient points in the modeling of this sample problem and the corresponding HYDRA-II input. The model and corresponding results are not intended to be representative of an actual spent fuel cask configuration. Nor are the details of the model (e.g., nodalization) necessarily intended to represent those suitable for design and licensing purposes.

#### 29.1 CONFIGURATION

A cutaway view of the sample problem (Figure 29.1) illustrates the overall arrangement of the cask body and its internal components. Figures 29.2 and 29.3 present the corresponding elevation views of this cask. The overall dimensions of the cask are:

- outside height = 118 cm
- outside diameter = 29 cm
- inside diameter = 21 cm
- top lid thickness = 4 cm
- bottom lid thickness = 4 cm.



FIGURE 29.1. Sample Problem Computational Mesh - Plan View

The top and bottom lids are welded to the side of the cask, leaving a slight 1-mm gap between the lid and cask side, as shown in the detail drawing of Figure 29.4. The entire cask body is constructed of nodular cast iron.

Spent fuel rods are stored in a 9x9 square array within the cask. The physical parameters for this array are:

- rod diameter = 1.072 cm
- pitch-to-diameter ratio = 1.334
- rod height = 100 cm.

The modeled portion of the rod array generates 290 watts of decay heat. Therefore, the full rod array produces 1160 watts (4 x 290) of decay heat. The relative activity profile for each rod is presented in Figure 29.5. Several of











FIGURE 29.4. Cask Lid-to-Body Interface



FIGURE 29.5. Relative Axial Activity Profile

the rods present in the array generate no heat. The exact location of these rods is indicated by the cross-hatched rod segments in Figure 29.1. The rods are surrounded and supported by a stainless steel basket. Both the rods and basket rest on the bottom lid of the cask. The basket stands on its four corner legs in contact with the bottom lid of the cask. This support configuration is illustrated in the detail view presented in Figure 29.6. The basket thickness is 1 cm.

After it is loaded and sealed, the cask is backfilled with helium and maintained at an absolute pressure of 496,000 dyn/cm². The cask stands in a vertical orientation on an insulated foundation in this simulation. The outside surfaces of the cask are exposed to the ambient environment whose temperature is maintained at a constant temperature of 300 K.



FIGURE 29.6. Basket Support Configuration

## 29.2 COMPUTATIONAL MODEL

The computational mesh chosen to represent this cask is illustrated in the plan and elevation views of Figures 29.1 and 29.2, respectively. Symmetry should be exploited wherever appropriate to reduce the number of cells required to represent the problem. For this sample problem, only one quarter of the cask need be modeled; hence, the quarter symmetry of the computational grid presented in Figure 29.1. Each K-plane of the computational domain is divided into a 12x12 array of cells representing the I and J directions. In the fuel rod region of the domain, the cell size is chosen so that each cell contains only one rod segment per cell. The remaining cell boundaries are defined either by the interfaces present between regions of dissimilar materials (e.g., helium and stainless steel), or to provide sufficient nodalization to adequately represent the physics of the problem. Thus, regions where large gradients in either temperature or velocity are anticipated should be represented with many cells of a scale adequate to capture these gradients.

Because of the cartesian grid used to represent the interior of the cask and the cask's cylindrical configuration, not all of the cells in the 12x12 array are activated in the model. The column of cells represented by I = 1 and J = 1, 2, 3, ..., 12, and the row of cells at I = 2, 3, ..., 12 and J = 12 are phantom cells used to represent the symmetry boundary conditions. The extent of the active cells to be used in the model in obtaining a solution to the momentum and energy equations is represented, in the usual way, by specification of the "beg" and "end" values for the I and J indices of the active cells. This information is provided as input to subroutine GRID. The cell sizes (viz., DX(I) and DY(J)) are also provided as input to this subroutine. As noted in Figure 29.1 and in the input to subroutine GRID, a small portion of the cask interior represented by cells (I,J) = (2,1), (3,1), (12,10), and (12,11) is not explicitly represented by the active cells of the cartesian region. However, the influence of these regions is still incorporated in the model. This will be done in the input to subroutine PROP.

The azimuthal cell spacing in the cylindrical grid is set by the pointsof-intersection of the cartesian-region computational grid lines with the cask body inner surface. Phantom cells for this region of the model are represented by the row of cells at IS = 1 and JS = 1, 2, 3, ..., 14 as well as IS = 7, JS = 1, 2, 3, ..., 14. The fact that the outside of the cask has constant radius at all elevations is represented by the uniformity of input to array ISEND(K) for K= 1 through 30. As with the cartesian-grid information, this data is provided in the input to subroutine GRID.

The input pertaining to material properties of the cartesian region is provided as input to subroutine PROP. For the most part, this input is relatively straightforward and reflects the information necessary to set the thermal resistances represented by the cells. However, the thermal resistance of the regions represented by the cells at (I,J) = (2,1), (3,1), (12,10), and (12,11) are incorporated as equivalent film resistances in the input to this

subroutine. RESFY values are assigned to cells (2,1) and (3,1) to model the effective resistance represented by these regions for heat transfer between the active cells (I,J) = (2,2) and (3,2) of the cartesian region and cells (IS,JS) = (2,2) and (2,3) of the cylindrical region. While cartesian-region cells (2,1) and (3,1) are phantom cells, they may still have resistances assigned to them. The effective thermal resistance must be assigned to these cells because HYDRA-II assumes that RESFY(I,J,K) represents a resistance to heat flow between the cell at (I,J,K) and (I,J+1,K). The input to subroutine PROP indicates that these resistances are computed using the series-resistance properties assigned to MT = 41, 42, 43, or 44. MT = 41 and 43 are used to represent the thermal resistance of these cells in the bottom and top lids of the cask. The material making up these cells as well as the adjoining cells in the lids is nodular cast iron (MAT = 5 in the input). PROP has been directed to use the average of the temperature in cell (2,2,K) and that in (2,1,K) for RESFY(2,1,K) when K = 2, 3, 4, 27, 28, and 29. Similarly, HYDRA-II will use the average temperature of cell (3,2,K) and that of cell (3,1,K) in the computation of RESFY(3,1,K) for K = 2, 3, 4, 27, 28, and 29. This has been done by specifying TWF = 0.5 for MT = 41 and 43. For the cells at K = 5 through 26, however, the material making up the interior cells and the walls of the cask are dissimilar. The region excluded from the active cells of the cartesian region is backfill gas (in this case helium) and, for the sake of illustration, is assumed to be more closely represented by the temperature of the cell at either (I,J) = (2,2) or (3,2) rather than that at the cask inner wall. Therefore, by specifying TWF = 0 for MT = 42 and 44, RESFY will be computed using the temperature of the cell at either (I,J,K) = (2,2,K) or (3,2,K) for the cells at K = 5 through 26.

A similar approach has been employed in modeling the thermal resistance present in the communication between the cells at (I,J,K) = (11,10,K), (11,11,K) and the cask-body inner surface. However, since RESFX(I,J,K) represents a thermal resistance between the cells at (I,J,K) and (I+1,J,K), these RESFX's are assigned to the cells at (11,10,K) and (11,11,K). TWF has been set to 0.5 for the RESFX's located in the bottom and top lids (K = 2, 3, 4, 27, 28,and 29), and to 1.0 for the remaining cells (K = 5 through 26). Thus, HYDRA-II will use an average temperature to compute RESFX in the heads (MT = 41 or 43),

and the temperature at either of cells (11,10,K) or (11,11,K) for those cells representing a gas-to-solid film resistance (MT = 45 or 46).

Information pertaining to the heat load presented by the spent fuel rods is provided as part of the input to subroutine THERM. The weighting factors assigned to each rod or rod portion in the model are provided in the "q weighting factor" input section. Note that those cells containing half a rod (viz., along I = 2 and J = 11) have a weight factor of 0.5. The rods without heat generation are located in cells (I,J) = (2,11), (3,8), and (5,10). The corresponding q weighting factor assigned to these cells is 0.0. The remaining cells in which the spent fuel rods are located are assigned a unity q weighting factor. The q-weighting-factor array is initialized to zero for each column of cells of the computational mesh (representing 144 cells in this sample problem - 12x12). Therefore, inputting nonzero q weighting factors serves to "turn-on" power generation in that column. The input to this array illustrates the usage of the overwriting capabilities frequently available during the input to HYDRA-II. For example, note that the cells in the range  $3 \le I \le 6$  and  $7 \le 1$ J < 10 have been assigned a q weighting factor of one. These values are subsequently overwritten with a value of zero to identify those cells within this (I,J) index range for which there is no heat generation. The K-dependence of the rod's heat generation rate is provided next in the input. The values input here reflect the profile illustrated in Figure 29.5.

The next major input section involves that for subroutine PROPS. The thermal resistance represented by the 1-mm gap in the lid-to-side interfaces at both the top and bottom of the cask is represented by means of film resistances. Here, the gap is modeled as a film resistance between the cylindrical-region cells at (IS,JS,K) = (3,JS,K) and (4,JS,K) for JS = 2 through 13, and K = 3, 4, 27, and 28. The gap is specified in the input as having the properties associated with MT = 42. As such, the gap is assumed to be filled with helium gas at a temperature equal to the average of the two adjoining cylindrical-region cells (TWF = 0.5 will use IS = 3 and 4). Moreover, radiation across this gap is accounted for in this model, with both surfaces having emissivities of 0.4.

The symmetry conditions are imposed by specifying very small values for the fluid viscosity (e.g.,  $10^{-20}$ ) in the input to HYDRO. Conversely, very large values of viscosity (viz.  $10^{20}$ ) are used in this simulation to indicate the presence of solids. This input is also provided to subroutine HYDRO. Note that the K-values specified in the input to HYDRO correspond to those of the momentum-solution grid. That is, they are offset by KBP from the K-values used in the formation of the grid and illustrated in Figure 29.1.

Alternatively, very small values (e.g.,  $10^{-6}$ ) may be provided for the AXI, AYI, and/or AZI quantities in subroutine PROPM, to indicate the presence of the impermeable flow obstruction represented by the solid. This method was also used in this simulation and is provided in the input to PROPM. Specifying the presence of solids by both large viscosities and small area-fractions is redundant, however. It is done in this model for illustration only. Note that, in specifying a very small value for flow-path area-fraction,

- AXI(I,J,K) applies to flow between cells (I,J,K) and (I+1, J,K).
- AYI(I,J,K) applies to flow between cells (I,J,K) and (I,J+1,K).
- AZI(I,J,K) applies to flow between cells (I,J,K) and (I,J,K+1).

As in the input to HYDRO, the K-values specified here correspond to those of the momentum-solution grid.

This simulation reflects a FIXEDP > 0 condition (specified later by the input to subroutine AVG). Therefore, the values loaded in the POR array in the input to subroutine HYDRO will have no impact on the momentum solution. However, they are provided for consistency. Very small values (e.g.,  $10^{-6}$ ) are loaded into array POR to represent those cells entirely occupied by solids. On the other hand, cells partially occupied by solids have a corresponding free-volume fraction that is a significant fraction of 1. This is the case for the cells representing the fuel assembly region (i.e., 2 < I < 6, 7 < J < 11, and 2 < K < 19). Again, the K-values represented are those of the momentum-solution grid.

Flow through the fuel assemblies will be represented using the Darcy-flow model. Consequently, the permeabilities in each of the flow directions are

provided to arrays PERMX, PERMY, and PERMZ. As with the other input to subroutine PROPM, the K-values listed in this input reflect those of the momentumsolution grid.

Skipping down to the input to REBQ, the model employed for this mode of rebalance is illustrated in Figures 29.7, 29.8, and 29.9. These figures indicate the manner in which the cells of the cartesian-region portion of the model have been collected into coarse cells. The corresponding input follows directly from the information provided in these figures and the discussion of input provided in Chapter 24.0.

#### 29.3 COMPUTER SIMULATIONS

A HYDRA-II input file was generated to simulate this sample problem. A base-case run was first executed using this input. This case serves as a starting point for a series of parametric runs. The changes made in each of these parametric runs are discussed in the following subsections. The intent here is to assess the effectiveness of some routines in obtaining a converged solution.

## 29.3.1 Base Case Run

Appendix A presents the input file used in the base case run. The salient features of this simulation are as follows:

- no rebalance schemes employed in the energy equation solution
- the pressure iteration scheme employed utilizes REBQ, AF, and PILES, in that order
- run for time-steps 0 to 1000.

The results generated by this run are presented in the output listing provided in Appendix B. A walk-through of the output file follows.

Lines 1 through 839 present an echo of the input file. The results from the simulation are presented in the remainder of the output, lines 841 through 1868. The static pressure field is initialized as indicated in lines 841 through 846. The iteration count, together with the maximum residual and its corresponding (I,J,K) location, are provided in output lines 845 through 846.



The time-step number, thermal time-step, and maximum inside temperature change are presented next in the output (line 848). As indicated here, HYDRA-II starts with the thermal time-step set to value DTIMEN provided in the input. The maximum inside temperature change (here 1.38 degrees) must be considered in relation to this time-step. The ratio of the maximum inside temperature change to the thermal time-step provides one measure of convergence in the solution. This information is immediately followed by the cell temperatures at the locations requested in the monitoring information provided to subroutine THERM (echoed in lines 222 through 229 of the output). These locations should be chosen to indicate the temperature in particularly



sensitive cells or to illustrate symmetries which are in the model, and should be reflected in the results. For example, the sample problem considered here is symmetric both geometrically and physically (with respect to the energy and momentum equations) about a radial line at -45 degrees from the horizontal (J equal constant) line. Consequently, the cells chosen for temperature



monitoring in this simulation should exhibit this symmetry. The temperatures listed on lines 849 and 850 of the output do exhibit this symmetry [e.g., T(3,4,10) = T(9,10,10)].

The maximum temperature change in the cylindrical-grid region of the model is listed next in the output. The ratio of this value to the thermal time-step provides a measure of the convergence of the solution. The following line of the output lists the temperature in selected cells of the cylindrical-grid region. The cells chosen for monitoring are specified as part of the input to subroutine TSIDE (echoed in output lines 851 through 852). Results for the cylindrical-grid region should also be symmetric about the -45 degree radial line. Therefore, the temperatures obtained in the simulation should reflect this symmetry. The monitoring cells for the side temperatures were chosen to check the results for this symmetry. For example, the temperatures in cylindrical-region cells (2,5,10) and (2,10,10) should be equal. Referring to line 852 of the output indicates that this is the case.

Information pertaining to the momentum-equation solution is presented in the next few lines of output. The time-step number, momentum time-step, and tilde-phase continuity error are presented in line 853 of the output. As indicated here, HYDRA-II starts the run with a momentum time-step equal to that specified in the input to subroutine HYDRO as DTYMEN (here DTYMEN = 0.0001). For the remaining time-steps of the simulation, HYDRA-II chooses an appropriate time-step based on the convergence history of the pressure-field solution and the time-step bounds specified by the user as input to subroutine HYDRO. The tilde-phase continuity error represents a measure of the residual mass in the tilde phase of the momentum-equation solution. The following line of output lists the increment to the tilde-phase x-, y-, and z-component mass fluxes. When these values are of significant magnitude, any symmetries present in the model should be reflected in these mass-flux corrections. The values of DMX should be antisymmetric (or very nearly so) with those of DMY in this simulation.

INFO has been turned off for both PILES and AF in this run. Had they been turned on, however, a more detailed listing of the convergence history would have been provided in the output. For example, the expanded listing of the PILES convergence history presented in lines 873 through 876 in the output appears as follows:

206 maximum 207 piles residual i j k 208 n -0.2590-08 9 11 18 209 1 -0.4580-08 9 10 18 210 1 -0.3339-08 9 10 18 211 1 -0.2920-08 9 10 18 2 212

215	2	-0,308e-08 9	10 18	
214	2	-0,2650-08 9	9 18	
215	3	-0,239e-08 9	10 18	
216	3	-0.244e-08 9	10 18	
217	3	-0,228e-08 9	9 18	
218	4	-0.201e-08 9	10 18	
219	4	-0.203e-08 9	10 18	,
220	4	-0.209e-08 9	8 17	
Similarly,	when 1	INFO is set at	one in AF,	the detailed listing appears
35 34 35 af 36 37		pressure n correction 0 0.0000e+00 1 -0 2102e-03	maximum residual -0.1684e-04	i j k 7 7 20
38		2 = 0.5179e = 03		6 7 23
39		3 0.1057e-03	0.4336e-06	5 10 25 3 10 21
40		4 0.5252e-03	0.2126e-06	9 10 23
41		5 -0,1227e-03	-0.13520-06	A 5 10

as

Here, the iteration count is presented along with the pressure correction and (I,J,K) indices corresponding to the cell experiencing the maximum residual in the Poisson equation for the pressure correction field. The maximum residual is the appropriate item to key on with regard to the rate of convergence of the routine. In the listing for AF it appears we have reached the "point of diminishing returns" with regard to the convergence rate. That is, with NMAX= 5 in AF, the "payoff" in the last few iterations is diminishing. Therefore, some computer time may be saved by reducing the allowed number of iterations (NMAX).

Following the call to PILES (to obtain the final pressure correction field at this time-step) and its usual output, HYDRA-II lists the component mass fluxes at the cell locations specified in the input to subroutine HYDRO (this input has been echoed in lines 691 through 708 of the output). As with the temperatures, these locations should be chosen to exhibit the mass fluxes in particularly sensitive cells or to aid in verifying solution symmetry. Lines 861 and 862 indicate the antisymmetry expected in the solution (when the mass fluxes are of significant magnitude).

Finally, the average pressure (in atmospheres) and continuity error are presented. This average pressure should equal that specified as input to sub-routine AVG for the case when FIXEDP > 0 is desired. Otherwise, this value will reflect the average pressure required to obtain the desired FIXEDM

specified in the input to subroutine AVG. The continuity error presented in this line of output represents that of the final mass-flux field at this timestep. This value should be acceptably low, as not only does it represent the presence of a source or sink in the fluid mass, but its effect gets amplified in the solution of the energy equation due to the multiplicative enthalpy term. In fact, often times continuity errors will be manifest first as spurious temperatures, but are actually traceable to the fluid portion of the simulation.

The above output is provided at the first, last, and each of the specified intermediate time-steps of the simulation. Following this, when PQBND has been set to 1.0 in the input to MAIN, HYDRA-II will provide a summary output section in which the heat balances (or lack thereof) for the constituent portions of the model are presented. This section provides an excellent source of information for checking the convergence of the solution. For the most part, the descriptive text provided with each entry in this section is self-explanatory. Some key values in this output section are the "EXCESS POWER ...." entries. These values represent macro-balances on the cask cavity and body. In a converged solution, they should all be zero (or very nearly so). The first value (EXCESS POWER LEAVING CAVITY) represents the difference between the power supplied to the cavity via the decay-heat section of the input to subroutine THERM (echoed in output lines 231 through 274) and the sum of the thermal power from the cavity to the top, side, and bottom of the cask body (output lines 988 through 992). These thermal powers are based on the temperature distribution at the final time-step of this run. The remaining three macro-balances represent the difference between the "THERMAL POWER FROM CAVITY TO ..." and the "THERMAL POWER FROM ... TO AMBIENT (or SIDE)." Figure 29.10 illustrates the location and orientation of each of the energy flow paths listed in this section of the output.

The remainder of the output presents the cell heat fluxes, temperatures, mass fluxes, and pressure corrections at the locations specified by the input to MAIN (echoed in output lines 1020 through 1866). In this simulation, the Iand J-direction heat fluxes for the K = 8 plane (PQI = 1.0 and NPQI = 1 in the input to MAIN) are presented in output lines 1020 through 1050. These values



Index	Descriptor						
1	Thermal power from cavity to top						
2	Thermal power from cavity to side						
3	Thermal power from cavity to bottom						
4	Thermal power from top to ambient						
5	Thermal power from top to side						
6	Thermal power from bottom to side						
7	Thermal power from bottom to ambient						
8	Thermal power from top of side to ambient						
9	Thermal power from side to ambient						
10	Thermal power from bottom of side to ambient						

FIGURE 29.10. Sample Problem Energy Flow Paths

•

(

provide and excellent check of the symmetry properties that should result from this simulation. The I-component heat-flux matrix should be antisymmetric with the J-component heat-flux matrix in this simulation. Therefore, the I = 7 output column for the I-direction heat flux values should equal the negative of J = 5 output column for the J-direction heat flux values (recall that the heat flux in the ith column of output for the I-direction heat flux component represents the heat flux between the cells at I and I+1; those in the jth row of output for the J-direction heat flux component represent that between the cells at J and J+1). The K-direction heat fluxes for the K = 8 plane are provided next in the output (lines 1053 through 1066). These results should be symmetric. For example, the I = 9 column of results should equal the results presented in the J = 4 column.

The cartesian-region temperatures are presented next in the output (output lines 1069 through 1519). This results from setting PT = 1.0 in the input to MAIN. With NPT = 0, the cell temperatures (in degrees Centigrade) are printed for each (I,J,K) value in the cartesian-region grid. These results should also exhibit the symmetry inherent in the model [e.g., the ith column should equal the J = (13 - ith) row at any K-plane].

With PTS = 1.0 and NPTS= 0 set in MAIN, the temperatures (in degrees Centigrade) for each cell of the cylindrical-region grid are presented next in the output. As with the cartesian-region temperatures, these results should also exhibit the symmetry inherent in the model. The temperatures listed for the K = 1 and K = 30 planes represent those of the ambient (set with the initial interface temperature in the input to subroutine THERM). The temperatures listed in the jth column of entries should equal those of the (15 - jth) column for each K-plane.

The x- and z-component mass fluxes are presented next in the output file. With both NPMX and NPMY set to 2 in MAIN, these results will be listed for the K = 2 and 10 planes only. Without the y-component mass fluxes, only the z-component mass fluxes can be checked for symmetry here. As with the K-direction heat flux output, the ith column of data should equal the (13 ith) row of data for symmetry.
Finally, the pressure change results are presented. These values represent the amount of correction applied to the pressure field in the last time-step.

## 29.3.2 Base-Case Run Extension

The results from the preceeding base-case run indicated that convergence was not obtained in the first 1000 time-steps (EXCESS POWER LEAVING CAVITY = -78.7 watts). Therefore, for this case the same model and simulation parameters (e.g., no energy-equation rebalance routines invoked) were utilized to extend the run an additional 1000 time steps (i.e., time steps 1001 through 2000) using the restart tape generated by the base-case run. This involved changes to the following variables in the input file and the corresponding routine in which they appear:

*NREAD = 1 in MAIN
*NEWTA = 0 in MAIN
*NDTIME = 0 in MAIN
*NEWT = 0 in THERM
*NEWTC = 0 in THERM
*NEWTS = 0 in TSIDE
*NDTYME = 0 in HYDRO.

This simulation produced the following "EXCESS POWER" values:

٠	EXCESS	POWER	LEAVING	CAVITY	-0.507e+02
٠	EXCESS	POWER	LEAVING	ТОР	-0.353e+02
•	EXCESS	POWER	LEAVING	SIDE	-0.586e+03
•	EXCESS	POWER	LEAVING	BOTTOM	-0.558e+02.

Clearly, with this iteration scheme, the problem still has not converged.

#### 29.3.3 Invoke REBA

This simulation represents an extension to the base-case run for 1000 time-steps (i.e., time-steps 1001 through 2000) as was done for the preceeding case. However, in this simulation the REBA routine was invoked (by setting

REBAON = 1.0 in MAIN). With REBA switched on and INFO already set to one in the input to REBA, the simulation will produce the following information in the output every time REBA is invoked:

839 reba info=1 dtmax=0.200e+02 dimax=0.541e+01 ki=3 dbmax=0.934e+00 kb=15 dsmax=0.132e+02 ks=15

This line indicates the maximum temperature change was 20 degrees Centigrade. The maximum divergence error for the cartesian region was 5.41 occurring on the third K-plane, the maximum divergence error for the interface region was 0.934 and occurred on the fifteenth K-plane, and the maximum divergence error in the cylindrical region was 13.2 occurring, again, on the fifteenth K-plane.

The simulation produced the following "EXCESS POWER" values:

- EXCESS POWER LEAVING CAVITY
   EXCESS POWER LEAVING TOP
   EXCESS POWER LEAVING SIDE
   0.337e-02
   0.346e-02
- EXCESS POWER LEAVING BOTTOM -0.611e-01.

This solution appears to be very close to convergence. The "excess power" values are only one measure of convergence, however. One must also check to ensure that quantities such as the "maximum inside change," "maximum side change," and "continuity error" are sufficiently small.

REBA appears to have been very effective in producing a converged solution for this problem. Other problems may not be as responsive to the implementation of REBA. They may well require an entirely different rebalance scheme (e.g., REBT) to accelerate convergence. In any case, a sufficient number of time-steps should be executed before any rebalance scheme is invoked. This allows the solution to "settle-down" from that provided as the (assumed erroneous) initial guess and reduces the possibility for over-correction brought on by invoking a rebalance routine.

## 29.3.4 Invoke REBT

This simulation is similar to that presented in the preceeding section 29.3.3 except that REBT is invoked in place of REBA. This is effected by setting REBON = 1.0 in the input to THERM. NREB and NREBN have been set to 100 and 1, respectively, to facilitate comparison with the preceeding cases. The simulation is then extended 1000 time-steps from the base-case run (i.e., time-steps 1001 through 2000). With REBT turned on and INFO = 1 specified in the input to REBT, subroutine REBT produces the following output at specified intervals during the run:

76	rebt	info=1	n	dimax	ld	djmax	jd	dkmax	kd
77			1	0.437e+01	7	-0.633e+01	2	-0.251e+01	28
78			2	-0.432e+01	11	-0.448e+01	2	0.2350-01	26
79			3	-0.348e+01	11	-0.318e+01	2	0.1650-01	26
80			4	-0.260e+01	11	-0,228e+01	2	0.119e-01	26
81			5	-0.192e+01	11	-0.165e+01	2	0.8669-02	26
82			6	-0.140e+01	11	-0.120e+01	2	0,630e-02	26
83			7	-0.102e+01	11	-0.874e+00	2	0.459e-02	26
84			8	-0.744e+00	11	-0.636e+00	2	0.3340-02	26
85			9	-0.542e+00	11	-0.463e+00	2	0 <b>.243e-</b> 02	26
86			10	-0.395e+00	11	-0.337e+00	2	0 <b>.177e-</b> 02	26
87			11	-0.288e+00	11	-0.246e+00	2	0.1290-02	26
88			12	-0.210e+00	11	-0.179e+00	2	0,940e-03	26

These results indicate the iteration number, maximum divergence error in the I-, J-, and K-direction passes, and the corresponding planes on which this error occurred. It appears from these data that more iterations may be required because there is still a substantial reduction in divergence error obtained between the eleventh and twelfth iterations.

The simulation produced the following "EXCESS POWER" values:

٠	EXCESS	POWER	LEAVING	CAVITY	-0.194e+02
٠	EXCESS	POWER	LEAVING	ТОР	-0.283e+02
٠	EXCESS	POWER	LEAVING	SIDE	-0.618e+03
٠	EXCESS	POWER	LEAVING	BOTTOM	-0.470e+02.

These values indicate that the run is still far from convergence.

To test the effect of increasing the number of REBT iterations, an additional study was performed in which the above-discussed case was rerun with NMAX changed from 12 to 17. This simulation was again run using the restart tape from the base-case run and carrying the case out an additional 1000 timesteps. A typical REBT output produced by this run is as follows:

123	rebt	info=1	n	dimax	ld	djmax	jd	dkmax	kd
124			1	0.114e+02	7	-0.106e+02	2	-0.605e+01	28
125			2	-0.707e+01	11	-0.776e+01	2	0.435e-01	26
126			3	-0,600e+01	11	-0.550e+01	2	0,295e-01	26
127			4	-0.451e+01	11	-0.396e+01	2	0.214e-01	26
128			5	-0.332e+01	11	-0.287e+01	2	0,1560-01	26
129			6	-0.243e+01	11	-0.209e+01	2	0.113e-01	26
130			7	-0.178e+01	11	-0.152e+01	2	0.827e-02	26
131			8	-0.130e+01	11	-0.111e+01	2	0.603e-02	26
132			9	~0,946e+00	11	-0,808e+00	2	0.4390-02	26
133			10	-0.690e+00	11	-0.589e+00	2	0.320e-02	26

134 -0.503e+00 11 -0.430e+00 2 11 0.2349-02 26 135 -0.367e+00 11 -0.313e+00 2 0.170-02 26 12 -0.267e+00 11 -0.228e+00 2 136 0.1249-02 26 13 -0.167e+00 2 137 14 -0.195e+00 11 0.9069-03 26 138 15 -0.1420+00 11 -0.1219+00 2 0.6619-03 26 139 16 -0.1040+00 11 -0.886e-01 2 0.4829-03 26 140 -0.756e-01 11 17 -0.646e-01 2 0,3518-03 26 Extending the number of iterations by five appears to have reduced the diverg-

ence errors by roughly a factor of five. However, as the following "EXCESS POWER" values show, little improvement was realized in the overall energy balance.

•	EXCESS	POWER	LEAVING	CAVITY	-0.193e+02
٠	EXCESS	POWER	LEAVING	ТОР	-0.282e+02
•	EXCESS	POWER	LEAVING	SIDE	-0.619e+03
٠	EXCESS	POWER	LEAVING	BOTTOM	-0.469e+02.

# 29.3.5 Timing Runs

In an effort to assess the computational expense incurred when invoking any of the various energy-equation and pressure-field iterative schemes, the base-case run was extended for 10 time-steps. The CPU time spent in each of the various acceleration-scheme subroutines was computed. These times will vary from one machine to another, as well as from one simulation to another. The results presented here have been normalized in an effort to enable generalizing somewhat from the findings of this single simulation. However, the significance of these results will vary on a case-by-case basis. Keep in mind that, while some of the acceleration schemes appear relatively expensive and perhaps ineffective in producing a converged solution for this simulation, they may be very effective under different simulation conditions and, therefore, well worth the added computational expense.

In comparing the relative merits of using REBA or REBT, the results discussed in Section 29.3.3 obtained from invoking REBA are compared with a case in which REBT is invoked. This REBT case differs from that presented in Section 29.3.4 in that NMAX has been changed from 12 to 1. In this way, one can compare the cost per pass through either REBA or REBT. Normalizing on the REBA times, one pass through REBT requires ~25% of the computational time for one REBA pass. NREB and NREBN were set to 100 and 1, respectively, for both of these simulations. Rerunning the REBT simulation with NMAX = 12 results in each REBT pass costing ~1.6 times one REBA pass. Invoking REBA proved to be very effective in producing a converged solution in the above studies. Its added cost (relative to one REBT pass) was more than offset by the reduced number of total time-steps required to produce a converged solution.

Timings were also performed for the various pressure-field acceleration schemes to assess their relative costs. In this study, each of the four schemes (REBS, REBQ, AF, and PILES) was invoked once per pass with NMAX = 1 where appropriate. Normalizing on the sum of the time spent in each subroutine during one pass through the pressure-iteration scheme, REBS required ~6% of the total, REBQ (with the REBQ model presented in the base-case run) required ~46%, AF required ~14%, and PILES required 34%. INFO was switched off for each of these subroutine passes (and INFONS was less than one in PILES) so that no time was spent generating monitoring information. In the sample problem, the tildephase momentum solution had an inconsequential contribution to the total time. However, these timings are still valid and should provide some assistance to the user in setting up an iteration scheme for different simulations. Again however, the user may well encounter situations in which the relative expense of invoking REBQ, for example, may pay big dividends in reducing the number of iterations required to produce a convergent momentum-equation solution. Typically these situations are encountered in large-scale simulations with a high contrast among connectors and where the fluid is experiencing rather significant eddying motion.

29.25

# REFERENCES

- Cox, R. L. 1977. <u>Radioactive Heat Transfer in Arrays of Parallel Cylinders</u>. ORNL-5239, Oak Ridge National Laboratory, Oak Ridge, Tennessee.
- DOE. 1986. <u>Spent Fuel Storage Requirements</u>. DOE/RL-86-5, U.S. Department of Energy, Richland Operations Office, Richland, Washington.
- Douglas, J., and J. Gunn. 1964. "A General Formulation of Alternating Direction Methods." <u>I. Numer. Math.</u> 6:428.
- McCann, R. A. 1987. <u>HYDRA-II: A Hydrothermal Analysis Computer Code</u>, <u>Volume I - Equations and Numerics</u>. PNL-6206 Vol. I, Pacific Northwest Laboratory, Richland, Washington.
- McCann, R. A. 1980. <u>HYDRA-I: A Three Dimensional Finite Difference Code for</u> <u>Calculating the Thermohydraulic Performance of a Fuel Assembly Contained</u> <u>Within a Canister</u>. PNL-3367, Pacific Northwest Laboratory, Richland, Washington.
- Westlake, J. R. 1968. <u>A Handbook of Numerical Matrix Inversion and Solution</u> of Linear Equations. John Wiley & Sons, Inc., New York, New York.

APPENDIX A

SAMPLE PROBLEM INPUT

# APPENDIX A

# SAMPLE PROBLEM INPUT

```
1 1 /MAIN - necho
 23
 3 HYDRA User's Manual
 4 Appendix Problem Input
 5 Use quarter symmetry
 6 1,1000,200 /MAIN - nrun, nstep, nsinfo
 7 0,1,1000,0 /MAIN - nread, nwrite, ndump, ngraph
 8 1,0,0,0 /MAIN - steady,nobody,notemp,novel
 9 1 /MAIN - newta
10 1,0.1,1.0,0.01 /MAIN - ndtime,dtimen,dtimax,dtimin
11 1,1,1 /MAIN - radcon, radpon, radron
12 0,100,1 /MAIN - rebaon, nreb, nrebn
13 1 /MAIN - necho
14 2 /MAIN - npla2
15 1,8 /MAIN - plane 1 option
16 2,2,10,16 /MAIN - plane 2 option
17 1 /MAIN - necho
18 0,0 /MAIN - pti,npti
19 0,0 /MAIN - ptsi,nptsi
20 1 /MAIN - pqbnd
21 1,1 /MAIN - pqi,npqi
22 0,0 /MAIN - pqrad, npqrad
23 0,0 /MAIN - pts1, npts1
24 1,0 /MAIN - pt,npt
25 1,0 /MAIN - pts, npts
26 1,2 /MAIN - pmx, npmx
27 0,0 /MAIN - pmy, npmy
28 1,2 /MAIN - pmz,npmz
29 1,1 /MAIN - pdpf,npdpf
30 0,0 /MAIN - ppf,nppf
31 1 /GRID - necho
```

A.1

```
32 1,3,11,10,11 /GRID - symtry,iflatm,iflatp,jflatm,jflatp
33 1 /GRID - necho, ieend
34 1,3,4,5,6,7,8,9,10,11,11,11
35 1 /GRID - inco
36 2,2,2,3,4,5,6,7,8,9,10 /GRID - jebeg
37 1 /GRID - inco
38 11*11 /GRID - jeend
39 1 /GRID - inco
40 4,4,5,6,7,8,9,10,4*11 /GRID - imend
41 1 /GRID - inco
42 4*2,3,4,5,6,7,8,9 /GRID - jmbeg
43 1 /GRID - inco
44 11*11 /GRID - jmend
45 1 /GRID - inco
46 2,3,4,5,6,7,8,9,10,11,2*12 /GRID - icart
47 1 /GRID - inco
48 2*1,2,3,4,5,6,7,8,9,10,11 /GRID - jcart
49 1 /GRID - inco
50 30*6 /GRID - isend
51 1 /GRID - necho
52 1, 0.71501, 4*1.43002, 1, 0.8806025934102, 0.9314908108106,
      0.6412008982674, 0.4053017678801, 1 /GRID - dx
53
54 1 /GRID - inco
55 1, 0.4053017678801, 0.6412008982674, 0.9314908108106,
56 0.8806025934102, 1, 4*1.43002, 0.71501, 1 /GRID - dy
57 1 /GRID - inco
58 1, 1, 2, 1, 5*2.5, 3.25, 4.25, 5.5, 7.25, 9.5, 12.75, 12.75,
59 9.5, 7.25, 5.5, 4.25, 3.25, 5*2.5, 1, 2, 1, 1 /GRID - dz
60 1 /GRID - inco
61 10.51480511546, 0.5, 3*1, 0.5, 1 /GRID - dr
62 1 / PROP - necho
63 0, 0, 0, 0, 0, 0, 0 / PROP - nsx,nsfx,nsy,nsfy,nsz,nsfz,info
64 1, 26.1, 0, 0.14, 0.333 / PROP - toph,top1,topv,topc,topn
65 0, 26.1, 0, 0, 0.25 /PROP - both,botl,botv,botc,botn
```

```
66 1 /PROP - necho
67 6 / PROP - nmat
68 low conductivity
                                             /PROP - text
69 0.1e-20, 0, 0
                                             /PROP - ccon(0), ccon(1), ccon(3)
70 high conductivity
                                             /PROP - text
71 0.1e+20, 0, 0
                                             /PROP - ccon(0), ccon(1), ccon(3)
72 helium ( backfill gas )
                                             /PROP - text
73 0.52e-3, 0.32e-5, 0
                                             /PROP - ccon(0), ccon(1), ccon(3)
74 stainless steel
                                             /PROP - text
75 0.09215, 0.0001465, 0
                                             /PROP - ccon(0), ccon(1), ccon(3)
76 nodular cast iron
                                             /PROP - text
77 0.5162, -0.3205e-3, 0
                                             /PROP - ccon(0), ccon(1), ccon(3)
78 air ( not used )
                                             /PROP - text
79 0.6880e-4, 0.6340e-6, 0
                                             /PROP - ccon(0), ccon(1), ccon(3)
80 1 /PROP - necho ( specs def. 01 isotropic and 11 parallel )
81 5 / PROP - mtmax
82 1, 1, 1, 1,
83 2, 1, 2, 1,
84 3, 1, 3, 1,
85 4, 1, 4, 1,
86 5, 1, 5, 1,
87 30*0 / PROP - specs
88 1 / PROP - necho ( specs def. 21 series )
89 7 / PROP - mtmax
90 40, 1, 1, 0.2, 1, 0.5
91 41, 5, 0.016, 0, 0, 0.5
92 42, 3, 0.016, 0, 0, 0.0
93 43, 5, 0.107, 0, 0, 0.5
94 44, 3, 0.107, 0, 0, 0.0
95 45, 3, 0.016, 0, 0, 1
96 46, 3, 0.107, 0, 0, 1
97 4*0 / PROP - specs
98 1 /PROP - necho ( specs def. 31 fuel assembly )
99 1 / PROP - mtmax
```

100 47, 3, 0.9484, 1.072, 1.43002, 0.0209, 0.115, 0, 0 101 41*0 / PROP - specs 102 1 /PROP - necho 103 24, 24 / PROP - nreg, npair 104 1,1, 2,11, 2,29, 1,1,1, 105 2,11, 12,12, 2,29, 1,2,1, 106 2,11, 2,11, 5,26, 1,4,3, 107 2,7, 6,6, 5,22, 1,4,4, 108 7,7, 7,11, 5,22, 1,4,4, 109 2,5, 6,6, 5,8, 1,4,3, 110 7,7, 8,11, 5,8, 1,4,3, 111 2,6, 7,11, 5,22, 1,31,47, 112 2,11, 2,11, 2,4, 1,4,5, 113 2,11, 2,11, 27,29, 1,4,5, 114 2,11, 2,11, 1,1, 1,3,1, 115 2,11, 2,11, 29,29, 1,51,40, 116 2,2, 1,1, 2,4, 1,42,41 117 2,2, 1,1, 5,26, 1,42,42 118 2,2, 1,1, 27,29, 1,42,41 119 3,3, 1,1, 2,4, 1,42,43 120 3,3, 1,1, 5,26, 1,42,44 121 3,3, 1,1, 27,29, 1,42,43 122 11,11, 10,10, 2,4, 1,41,43 123 11,11, 10,10, 5,26, 1,41,46 124 11,11, 10,10, 27,29, 1,41,43 125 11,11, 11,11, 2,4, 1,41,41 126 11,11, 11,11, 5,26, 1,41,45 127 11,11, 11,11, 27,29, 1,41,41 128 791*0 /PROP - index 129 1 / THERM - necho 130 0.5, 5.234, 0.5 /THERM - theta, sphtf, dtemax 131 0, 100, 50 /THERM - rebon, nreb, nrebn 132 1 /THERM - necho 133 8 /THERM - mont

134 2,2,10 135 3,4,10 136 5,6,10 137 5,7,10 138 11,11,10 139 9,10,10 140 7,8,10 141 6,8,10 142 0,0,0 /THERM - (i,j,k) locations 143 1 /THERM - necho 144 0.5, 2,2,7,11 145 0.5, 3,6,11,11 146 1, 3,6,7,10 147 0, 2,2,11,11 148 0, 3,3,8,8 149 0, 5,5,10,10 150 0, 4*0 /THERM - q weighting factor, ibeg, iend, jbeg, jend 151 1 /THERM - necho 152 290., 2,6,7,11 153 0.,0,0,0,0 /THERM - group power, ibeg, iend, jbeg, jend 154 1 /THERM - necho 155 3*0, 29.5, 44.5, 57, 65, 71, 75, 78, 6*80, 156 78.5, 69, 55, 39, 24.5, 7*0 /THERM - relact(k) 157 1 /THERM - necho 158 0 / THERM - pagen 159 1 / THERM - necho 160 1,11.5 161 321, 323, 325, 356, 398, 433, 456, 473, 484, 492, 162 6*498, 494, 467, 428, 383, 342, 337, 332, 328, 163 324, 320, 315, 310 /THERM - newt,cenj,tcen(k) 164 1 /THERM - necho 165 1, 0 166 12*300, 336*320, 12*300 /THERM - newtc,cenj,ts1(j,k) 167 1 /THERM - necho

A.5

```
168 0 /THERM - ndelta
169 2,6,2,13 /THERM - loc
170 29*0 /THERM - delta
171 1 /REBT - necho
172 0.1e+6, 12, 1 /REBT - xdtime.nmax.info
173 1 / PROPS - necho
174 0, 0, 0, 0, 0, 0, 0 /PROPS - nsx,nsfx,nsy,nsfy,nsz,nsfz,info
175 1, 26.1, 0, 0.14, 0.333 /PROP - toph.topl.topv.topc.topn
176 0, 26.1, 0, 0, 0.25 /PROP - both,botl,botv,botc,botn
177 1, 118.0, 0, 0.10, 0.333 / PROPS - sideh, sidel, sidev, sidec, siden
178 1 /PROPS - necho
179 6 /PROPS - nmat
180 low conductivity
                                             /PROPS - text
181 0.1e-20, 0, 0
                                             /PROPS - ccon0,ccon1,ccon3
182 high conductivity
                                             /PROPS - text
183 0.1e+20, 0, 0
                                             /PROPS - ccon0,ccon1,ccon3
184 helium ( backfill gas )
                                             /PROPS - text
185 0.52e-3, 0.32e-5, 0
                                             /PROPS - ccon0,ccon1,ccon3
186 stainless steel
                                             /PROPS - text
187 0.09215, 0.0001465, 0
                                             /PROPS - ccon0,ccon1,ccon3
188 nodular cast iron
                                             /PROPS - text
189 0.5162, -0.3205e-3, 0
                                            /PROPS - ccon0,ccon1,ccon3
190 air ( not used )
                                             /PROPS - text
191 0.6880e-4, 0.6340e-6, 0
                                             /PROPS - ccon0,ccon1,ccon3
192 1 / PROPS - necho
193 5 / PROPS - mtmax ( specs def. 01 isotropic and 11 parallel )
194 1, 1, 1, 1,
195 2, 1, 2, 1,
196 3, 1, 3, 1,
197 4, 1, 4, 1,
198 5, 1, 5, 1,
199 80*0 /PROPS - specs
200 1 / PROPS - necho
201 2 / PROPS - mtmax ( specs def. 21 series )
```

```
202 41, 1, 1, 0.2, 1, 0.5
203 42, 3, 0.1, 0.4, 0.4, 0.5
204 88*0 /PROPS - specs
205 1 / PROPS - necho
206 9,9 /PROPS - nreg, npair
207 2,6, 2,13, 2,29, 1,4,5
208 1,1, 2,13, 2,29, 1,1,1
209 2,6, 1,1, 2,29, 1,2,1
210 2,6, 14,14, 2,29, 1,2,1
211 6,6, 2,13, 2,29, 1,53,41
212 2,6, 2,13, 1,1, 1,3,1
213 2,6, 2,13, 29,29, 1,51,41
214 3,3, 2,13, 27,28, 1,41,42
215 3,3, 2,13, 3,4, 1,41,42
216 174*0 /PROPS - index
217 1 /TSIDE - necho
218 1, 300, 5 /TSIDE - newts,tsamb,dtemax
219 1 /TSIDE - necho
220 4 /TSIDE - monts
221 2, 5, 10
222 2, 10, 10
223 4, 5, 10
224 4, 10, 10
225 0, 0, 0 /TSIDE - incol, inco2, inco3
226 1 /TSIDE - necho
227 0
228 28*0 /TSIDE - ndelta,delta
229 1 /RADC - necho
230 0 /RADC - info
231 1 /RADC - necho
232 2 /RADC - nregs
233 18,1,12,1,1,1
234 18,1,12,2,2,1 /RADC - nkcell, idk, nsurfs, idi, idj, idh
235 1 /RADC - necho
```

```
236 18, 5,6,7,8,9,10,11,12,13,14,15,16,17,18,19,20,21,22 /RADC - kcells,kcell,idk
237 1 /RADC - necho
238 12, 2,3,4,5,6,7,7,6,5,4,3,2 /RADC - nsurfs, icel1(*,1)
239 12, 6*7,8,9,10,11,2*12 /RADC - nsurfs,icell(*,2)
240 1 /RADC - necho
241 12, 6*6,5,4,3,2,2*1 /RADC - nsurfs,jcell(*,1)
242 12, 11,10,9,8,7,6,6,7,8,9,10,11 /RADC - nsurfs,jcell(*,2)
243 1 /RADC - necho
244 12 /RADC - nsurfs
245
     -1.9315045692589e-12,
                              1.7814174953191e-13,
                                                     1.4676974094935e-13,
246
      1.0922176415065e-13,
                              7.4006341878091e-14,
                                                     3.3356405994197e-14,
247
      5.0253274575751e-14,
                             1.2031398337844e-13,
                                                     1.9416884735737e-13,
248
       3.0864550228951e-13,
                              4.3775113556598e-13,
                                                     2.7887582358759e-13,
249
      1.7814174953191e-13, -3.7133637277021e-12,
                                                     2.962943649003e-13,
250
      2.3030898670503e-13,
                                                     6.9428148011471e-14,
                             1.5758935284123e-13,
251
      1.0569095369594e-13,
                              2.6880575245861e-13,
                                                     4.5921549645403e-13,
252
      6.9273903046315e-13,
                              8.1680503895927e-13,
                                                     4.3834485368104e-13,
253
      1.4676974094936e-13,
                              2,9629436490029e-13,
                                                    -3.7607747156819e-12,
254
       2.6124382424036e-13,
                              1.9084872556432e-13,
                                                     7.9638816576821e-14,
255
       1.2631628926698e-13,
                              3.9130616188361e-13,
                                                     6.8319780127815e-13,
256
      7.3024192016115e-13.
                              5.9565067832659e-13.
                                                     2.5926639253403e-13.
257
       1.0922176415065e-13,
                              2.3030898670502e-13.
                                                     2.6124382424036e-13,
258
      -3.7649985826716e-12,
                              2.6203843744515e-13,
                                                     1.0928846605724e-13,
259
      1.9581318305493e-13,
                              7.6226577648453e-13,
                                                     8.0621286265921e-13,
260
       5.0848068315119e-13,
                              3.6532275159017e-13,
                                                     1.5480184713297e-13,
261
       7.4006341878094e-14,
                              1.5758935284123e-13,
                                                     1.9084872556433e-13,
262
       2.6203843744515e-13,
                             -3.7138156110638e-12,
                                                     2.2620983572389e-13,
263
       6.0877889258035e-13,
                              1.1130978871075e-12,
                                                     4.7003581272239e-13,
264
       2.8037622095288e-13,
                              2.2970032442227e-13,
                                                     1.0113377982547e-13,
265
       3.33564059942e-14,
                              6.9428148011475e-14,
                                                     7.9638816576823e-14,
266
       1.0928846605724e-13,
                              2.2620983572389e-13,
                                                    -2.4867927816087e-12,
267
       1.2067655762691e-12,
                              3.2389558541632e-13,
                                                     1.5345365652446e-13,
268
       1.2136129618654e-13,
                              1.1243369400613e-13,
                                                     5.0961300842421e-14,
269
       5.0253274575752e-14,
                              1.0569095369594e-13,
                                                     1.2631628926699e-13,
```

 $\overline{\phantom{a}}$ 

270	1.9581318305493e-13,	6.0877889258036e-13,	1.2067655762691e-12,
271	-3.2096362674751e-12,	3.3513657881041e-13,	2.0146062162007e-13,
272	1.6159819783848e-13,	1.4787255007166e-13,	6.9950149691289e-14,
273	1.2031398337844e-13,	2.6880575245863e-13,	3.9130616188361e-13,
274	7.6226577648454e-13,	1.1130978871075e-12,	3.2389558541632e-13,
275	3.3513657881041e-13,	-4.33824795969e-12,	3.6672146643102e-13,
276	2.8727032822821e-13,	2.5147402795549e-13,	1.1796041153554e-13,
277	1.9416884735739e-13,	4.5921549645397e-13,	6.8319780127817e-13,
278	8.0621286265922e-13,	4.7003581272239e-13,	1.5345365652449e-13,
279	2.0146062162004e-13,	3.6672146643102e-13,	-4.086691328908e-12,
280	3.2052904844429e-13,	2.918754201466e-13,	1.3982029527023e-13,
281	3.0864550228951e-13,	6.9273903046317e-13,	7.3024192016117e-13,
282	5.084806831512e-13,	2.8037622095288e-13,	1.213612961865e-13,
283	1.6159819783847e-13,	2.8727032822825e-13,	3.2052904844429e-13,
284	-3.8909369156429e-12,	3.2164379379074e-13,	1.5805089413644e-13,
285	4.3775113556601e-13,	8.1680503895927e-13,	5.9565067832661e-13,
286	3.6532275159019e-13,	2.2970032442223e-13,	1.1243369400614e-13,
287	1.478725500717e-13,	2.5147402795551e-13,	2.9187542014654e-13,
288	3.2164379379077e-13,	-3.7377436677138e-12,	1.6721425287865e-13,
289	2.7887582358759e-13,	4.38344853681e-13,	2.59266392534e-13,
290	1.5480184713297e-13,	1.0113377982548e-13,	5.0961300842396e-14,
291	6.995014969128e-14,	1.179604115355e-13,	1.3982029527028e-13,
292	1.5805089413639e-13,	1.6721425287866e-13,	-1.9363800011156e-12
293 1	/RADP - necho		
294 2	2 /RADP - iregs		
295 (	.4, 0.25, 7,8, 6,6, 5,8		
296 (	).4, 0.25, 7,9, 7,7, 5,8		
297 1	/RADP - necho		
298 2	2 /RADP - jregs		
299 0	.25, 0.4, 6,6, 4,6, 5,8		
300 0	0.25, 0.4, 7,7, 5,6, 5,8		
301 1	/RADP - necho		
302 5	5 /RADP - kregs		
303 0	0.4, 0.25, 2,7, 6,6, 22,	27	

A.9

304	0.4, 0.25, 7,7,	7,11, 22,27								
305	5 0.8, 0.25, 2,6, 7,11, 22,27									
306	5 0.25, 0.4, 2,5, 6,6, 4,9									
307	7 0.25, 0.4, 7,7, 8,11, 4,9 /RADP - e1,e2,ibeg,iend,jbeg,jend,kbeg,kend									
308	1 /RADR - necho									
309	92									
310	D RADR Input Section									
311	Rod Emittance is	0.8								
312	1 /RADR - necho									
313	25 /RADR - nh, h									
314	1.000000	0.1710000	0.0000000E+00	0.0000000E+00	0.1710000					
315	0.0000000E+00	0.0000000E+00	0.0000000E+00	0.2080000	4.99999999E-03					
316	0.0000000E+00	0.0000000E+00	4.99999999E-03	0.0000000E+00	0.0000000E+00					
317	0.0000000E+00	0.0000000E+00	0.0000000E+00	0.0000000E+00	4.600000E-02					
318	4.6000000E-02	0.0000000E+00	0.0000000E+00	0.0000000E+00	0.0000000E+00					
319	2.000000	0.1710000	0.0000000E+00	0.1710000	0.3880000					
320	0.0000000E+00	0.000000E+00	0.2080000	0.2080000	4.99999998-03					
321	0.0000000E+00	0.0000000E+00	9.9999998E-03	0.0000000E+00	0.000000E+00					
322	0.000000E+00	0.0000000E+00	0.0000000E+00	4.600000E-02	4.600000E-02					
323	4.600000E-02	0.000000E+00	0.0000000E+00	0.0000000E+00	0.000000E+00					
324	3.000000	0.3880000	0.1710000	0.000000E+00	0.1710000					
325	0.2080000	0.0000000E+00	0.0000000E+00	0.2080000	9.9999998E-03					
326	0.0000000E+00	0.000000E+00	4.99999999E-03	4.600000E-02	0.0000000E+00					
327	0.0000000E+00	0.0000000E+00	0.0000000E+00	0.0000000E+00	4.600000E-02					
328	4.6000000E-02	0.0000000E+00	0.0000000E+00	0.0000000E+00	0.000000E+00					
329	4.000000	0.1710000	0.0000000E+00	0.1710000	0.3420000					
330	0.0000000E+00	0.0000000E+00	0.2080000	0.2080000	4.9999999E-03					
331	0.0000000E+00	4.99999999E-03	9.9999998E-03	0.000000E+00	0.000000E+00					
332	0.0000000E+00	0.0000000E+00	4.600000E-02	4.600000E-02	4.600000E-02					
333	4.600000E-02	0.0000000E+00	0.0000000E+00	0.0000000E+00	0.0000000E+00					
334	5.000000	0.3420000	0.1710000	0.0000000E+00	0.1710000					
335	0.2080000	0.0000000E+00	0.0000000E+00	0.2080000	9.9999998E-03					
336	4.9999999E-03	0.0000000E+00	4.99999998-03	4.6000000E-02	4.600000E-02					
337	0.0000000E+00	0.000000E+00	0.0000000E+00	0.0000000E+00	4.600000E-02					

338	4.6000000E-02	0.0000000E+00	0.0000000E+00	0.0000000E+00	0.0000000E+00
339	6.000000	0.1710000	0.0000000E+00	0.1710000	0.3420000
340	0.0000000E+00	0.0000000E+00	0.2080000	0.2080000	0.000000E+00
341	0.0000000E+00	4.99999998-03	9.9999998E-03	0.0000000E+00	0.0000000E+00
342	0.0000000E+00	0.0000000E+00	4.600000E-02	4.600000E-02	4.600000E-02
343	0.0000000E+00	0.000000E+00	0.0000000E+00	0.0000000E+00	0.0000000E+00
344	7.000000	0.3420000	0.1710000	0.000000E+00	0.1710000
345	0.2080000	0.0000000E+00	0.0000000E+00	0.2080000	9.9999998E-03
346	4.99999999E-03	0.0000000E+00	0.000000E+00	4.600000E-02	4.600000E-02
347	0.0000000E+00	0.0000000E+00	0.0000000E+00	0.0000000E+00	0.000000E+00
348	4.600000E-02	0.000000E+00	0.0000000E+00	0.0000000E+00	0.000000E+00
349	8.000000	0.0000000E+00	0.000000E+00	0.1710000	0.3420000
350	0.0000000E+00	0.0000000E+00	0.2080000	0.0000000E+00	0.000000E+00
351	0.0000000E+00	4.99999998-03	9.9999998E-03	0.0000000E+00	0.000000E+00
352	0.0000000E+00	0.0000000E+00	4.600000E-02	4.600000E-02	0.000000E+00
353	0.0000000E+00	0.0000000E+00	0.0000000E+00	0.0000000E+00	0.0000000E+00
354	9.000000	0.3420000	0.1710000	0.000000E+00	0.000000E+00
355	0.2080000	0.000000E+00	0.0000000E+00	0.0000000E+00	9.9999998E-03
356	4.99999998E-03	0.0000000E+00	0.0000000E+00	4.600000E-02	4.600000E-02
357	0.0000000E+00	0.0000000E+00	0.0000000E+00	0.000000E+00	0.000000E+00
358	0.000000E+00	0.000000E+00	0.000000E+00	0.000000E+00	0.000000E+00
359	10.00000	0.3880000	0.3880000	0.3880000	0.3880000
360	0.2080000	0.2080000	0.2080000	0.2080000	9.9999998E-03
361	0.000000E+00	0.000000E+00	9.9999998E-03	4.600000E-02	0.000000E+00
362	0.000000E+00	0.0000000E+00	0.0000000E+00	4.600000E-02	4.600000E-02
363	4.600000E-02	0.0000000E+00	0.000000E+00	0.000000E+00	0.000000E+00
364	11.00000	0.3880000	0.3420000	0.3880000	0.3420000
365	0.2080000	0.2080000	0.2080000	0.2080000	9.9999998E-03
366	0.000000E+00	9.9999998E-03	9.9999998E-03	4.600000E-02	0.000000E+00
367	0.000000E+00	4.600000E-02	4.600000E-02	4.600000E-02	4.600000E-02
368	4.6000000E-02	0.0000000E+00	0.0000000E+00	0.0000000E+00	0.000000E+00
369	12.00000	0.3420000	0.3880000	0.3420000	0.3880000
370	0.2080000	0.2080000	0.2080000	0.2080000	9.9999998E-03
371	9.9999998E-03	0.0000000E+00	9.9999998E-03	4.600000E-02	4.600000E-02

_

372	4.600000E-02	0.0000000E+00	0.0000000E+00	4.6000000E-02	4.600000E-02
373	4.600000E-02	0.0000000E+00	0.0000000E+00	0.0000000E+00	0.000000E+00
374	13.00000	0.3880000	0.3420000	0.3880000	0.3420000
375	0.2080000	0.2080000	0.2080000	0.2080000	0.0000000E+00
376	0.000000E+00	9.9999998E-03	9.9999998E-03	0.000000E+00	0.0000000E+00
377	0.0000000E+00	4.600000E-02	4.600000E-02	4.600000E-02	4.600000E-02
378	0.000000E+00	0.000000E+00	0.000000E+00	0.000000E+00	0.0000000E+00
379	14.00000	0.3420000	0.3880000	0.3420000	0.3880000
380	0.2080000	0.2080000	0.2080000	0.2080000	9.9999998E-03
381	9.9999998E-03	0.0000000E+00	0.000000E+00	4.600000E-02	4.600000E-02
382	4.600000E-02	0.000000E+00	0.000000E+00	0.0000000E+00	0.0000000E+00
383	4.600000E-02	0.0000000E+00	0.000000E+00	0.0000000E+00	0.0000000E+00
384	15.00000	0.0000000E+00	0.3420000	0.3880000	0.3420000
385	0.0000000E+00	0.2080000	0.2080000	0.0000000E+00	0.0000000E+00
386	0.000000E+00	9.9999998E-03	9.9999998E-03	0.000000E+00	0.0000000E+00
387	0.0000000E+00	4.600000E-02	4.600000E-02	4.600000E-02	0.0000000E+00
388	0.000000E+00	0.0000000E+00	0.000000E+00	0.0000000E+00	0.000000E+00
389	16.00000	0.3420000	0.3880000	0.3420000	0.000000E+00
390	0.2080000	0.2080000	0.0000000E+00	0.000000E+00	9.9999998E-03
391	9.9999998E-03	0.000000E+00	0.0000000E+00	4.600000E-02	4.600000E-02
392	4.600000E-02	0.0000000E+00	0.000000E+00	0.000000E+00	0.0000000E+00
393	0.000000E+00	0.0000000E+00	0.0000000E+00	0.0000000E+00	0.0000000E+00
394	17.00000	0.3420000	0.3420000	0.3420000	0.3420000
395	0.2080000	0.2080000	0.2080000	0.2080000	9.9999998E-03
396	9.9999998E-03	9.9999998E-03	9.9999998E-03	4.600000E-02	4.600000E-02
397	4.600000E-02	4.600000E-02	4.600000E-02	4.600000E-02	4.600000E-02
398	4.600000E-02	0.000000E+00	0.0000000E+00	0.000000E+00	0.0000000E+00
399	18.00000	0.3420000	0.3420000	0.3420000	0.3420000
400	0.2080000	0.2080000	0.2080000	0.2080000	0.000000E+00
401	9.9999998E-03	9.9999998E-03	9.9999998E-03	0.0000000E+00	4.600000E-02
402	4.600000E-02	4.600000E-02	4.600000E-02	4.600000E-02	4.600000E-02
403	0.000000E+00	0.000000E+00	0.000000E+00	0.000000E+00	0.000000E+00
404	19.00000	0.3420000	0.3420000	0.3420000	0.3420000
405	0.2080000	0.2080000	0.2080000	0.2080000	9.9999998E-03

406	9.9999998E-03	9.9999998E-03	0.0000000E+00	4.6000000E-02	4.600000E-02
407	4.600000E-02	4.600000E-02	4.600000E-02	0.0000000E+00	0.000000E+00
408	4.600000E-02	0.0000000E+00	0.0000000E+00	0.0000000E+00	0.000000E+00
409	20.00000	0.3420000	0.3420000	0.3420000	0.3420000
410	0.2080000	0.2080000	0.2080000	0.2080000	0.0000000E+00
411	9.9999998E-03	9.9999998E-03	0.000000E+00	0.0000000E+00	4.600000E-02
412	4.6000000E-02	4.600000E-02	4.600000E-02	0.000000E+00	0.0000000E+00
413	0.0000000E+00	0.000000E+00	0.000000E+00	0.0000000E+00	0.000000E+00
414	21.00000	0.000000E+00	0.3420000	0.3420000	0.3420000
415	0.0000000E+00	0.2080000	0.2080000	0.000000E+00	0.000000E+00
416	9.9999998E-03	9.9999998E-03	9.9999998E-03	0.000000E+00	0.000000E+00
417	4.600000E-02	4.600000E-02	4.600000E-02	4.600000E-02	0.000000E+00
418	0.0000000E+00	0.000000E+00	0.000000E+00	0.000000E+00	0.000000E+00
419	22.00000	0.3420000	0.3420000	0.3420000	0.000000E+00
420	0.2080000	0.2080000	0.0000000E+00	0.000000E+00	9.9999998E-03
421	9.9999998E-03	9.9999998E-03	0.0000000E+00	4.600000E-02	4.600000E-02
422	4.600000E-02	4.600000E-02	0.0000000E+00	0.000000E+00	0.000000E+00
423	0.0000000E+00	0.000000E+00	0.0000000E+00	0.000000E+00	0.000000E+00
424	23.00000	0.000000E+00	0.3420000	0.3420000	0.3420000
425	0.0000000E+00	0.2080000	0.2080000	0.000000E+00	0.000000E+00
426	9.9999998E-03	9.9999998E-03	0.000000E+00	0.0000000E+00	0.000000E+00
427	4.600000E-02	4.600000E-02	4.600000E-02	0.000000E+00	0.000000E+00
428	0.000000E+00	0.0000000E+00	0.000000E+00	0.0000000E+00	0.000000E+00
429	24.00000	0.3420000	0.3420000	0.3420000	0.000000E+00
430	0.2080000	0.2080000	0.000000E+00	0.000000E+00	0.000000E+00
431	9.9999998E-03	9.9999998E-03	0.000000E+00	0.0000000E+00	4.600000E-02
432	4.600000E-02	4.600000E-02	0.000000E+00	0.000000E+00	0.000000E+00
433	0.000000E+00	0.000000E+00	0.000000E+00	0.000000E+00	0.000000E+00
434	25.00000	0.000000E+00	0.3420000	0.3420000	0.000000E+00
435	0.0000000E+00	0.2080000	0.000000E+00	0.000000E+00	0.0000000E+00
436	9 <b>.</b> 9999998E-03	9.9999998E-03	0.000000E+00	0.000000E+00	0.000000E+00
437	4.600000E-02	4.600000E-02	0.000000E+00	0.000000E+00	0.000000E+00
438	0.0000000E+00	0.000000E+00	0.000000E+00	0.0000000E+00	0.000000E+00
439	1 /RADR - necho				

1

440 25 /RADR - nreg, lreg 441 1,1, 2,2, 11,11, 5,22 442 2,2, 3,3, 11,11, 5,22 443 3,3, 2,2, 10,10, 5,22 444 4,4, 4,4, 11,11, 5,22 445 5,5, 2,2, 9,9, 5,22 446 6,6, 5,5, 11,11, 5,22 447 7,7, 2,2, 8,8, 5,22 448 8,8, 6,6, 11,11, 5,22 449 9,9, 2,2, 7,7, 5,22 450 10,10, 3,3, 10,10, 5,22 451 11,11, 4,4, 10,10, 5,22 452 12,12, 3,3, 9,9, 5,22 453 13,13, 5,5, 10,10, 5,22 454 14,14, 3,3, 8,8, 5,22 455 15,15, 6,6, 10,10, 5,22 456 16,16, 3,3, 7,7, 5,22 457 17, 17, 4, 4, 9, 9, 5, 22 458 18,18, 5,5, 9,9, 5,22 459 19,19, 4,4, 8,8, 5,22 460 20,20, 5,5, 8,8, 5,22 461 21,21, 6,6, 9,9, 5,22 462 22,22, 4,4, 7,7, 5,22 463 23,23, 6,6, 8,8, 5,22 464 24,24, 5,5, 7,7, 5,22 465 25,25, 6,6, 7,7, 5,22 466 1 /RADR - necho 467 1 /RADR - nt4 468 1, 2,6, 7,11, 5,22 /RADR - 1t4 469 1 /REBA - necho 470 20, 1 /REBA - dtmax, info 471 1 /HYDR0 - necho 472 1,0,0,0.5,1,-0.5 /HYDRO - convek,epscon,mitmax,thetam,estpf 473 1,0.0001,0.1 /HYDR0 - ndtyme,dtymen,dtymax

```
474 0,0,1 /HYDRO - newgas, newvel, extrav
 475 0.65e+6, 483, 0.6472e-4 /HYDR0 - pfref,tfref,dfref
 476 0,0,-1 /HYDR0 - gx,gy,gz
 477 0.7e-4, 0.4e-6 /HYDR0 - cvisa, cvisb
 478 1 /HYDR0 - necho
 479 3 /HYDRO - monmx
 480 7,9,3 /HYDRO - i,j,k location for monitoring mx
 481 4,4,12
 482 9,9,12
 483 0,0,0
 484 1 /HYDRO - necho
 485 3 / HYDR0 - monmy
 486 4,5,3 /HYDRO - i,j,k location for monitoring my
 487 9,8,12
 488 4,3,12
 489 0,0,0
 490 1 /HYDRO - necho
 491 4 / HYDRO - monmz
 492 7,9,3 /HYDRO - i,j,k location for monitoring mz
 493 4,6,3
 494 4,4,12
 495 9,9,12
 496 0,0,0
 497 1 /HYDRO - necho
 498 2 /HYDR0 - nreg
499 0.1e-19, 1,1, 2,11, 2,23
 500 0.1e-19, 2,11, 12,12, 2,23
 501 28*0
 502 1 /HYDRO - necho
 503 4 /HYDR0 - nreg
 504 0.1e+21, 6,7, 6,6, 2,5
 505 0.1e+21, 2,7, 6,6, 6,19
 506 0.1e+21, 7,7, 7,7, 2,5
 507 0.1e+21, 7,7, 7,11, 6,19
```

```
A.15
```

```
508 14*0
509 1 / PROPM - necho
510 10 / PROPM - permO
511 1 / PROPM - necho
512 0 / PROPM - info
513 -1, 6*0 / PROPM - ax
514 1 / PROPM - necho
515 0 / PROPM - info
516 -1, 6*0 / PROPM - ay
517 1 / PROPM - necho
518 0 / PROPM - info
519 -1, 6*0 / PROPM - az
520 1 / PROPM - necho
521 0 / PROPM - info
522 0.1e-5, 6,7, 6,11, 6,19 / PROPM - axi, ibeg, iend, jbeg, jend, kbeg, kend
523 0.1e-5, 1,6, 6,6, 6,19
524 0.1e-5, 5,7, 6,6, 2,5
525 0.1e-5, 6,7, 7,7, 2,5
526 -1, 6*0
527 1 / PROPM - necho
528 0 / PROPM - info
529 0.1e-5, 2,7, 5,6, 6,19 / PROPM - ayi, ibeg, iend, jbeg, jend, kbeg, kend
530 0.1e-5, 7,7, 7,11, 6,19
531 0.1e-5, 6,7, 5,6, 2,5
532 0.1e-5, 7,7, 7,7, 2,5
533 -1, 6*0
534 1 / PROPM - necho
535 0 /PROPM - info
536 0.1e-5, 2,7, 6,6, 5,19 /PROPM - azi, ibeg, iend, jbeg, jend, kbeg, kend
537 0.1e-5, 7,7, 7,11, 5,19
538 0.1e-5, 6,7, 6,6, 2,5
539 0.1e-5, 7,7, 7,7, 2,5
540 -1, 6*0
541 1 / PROPM - necho
```

```
542 0 /PROPM - info
543 0.1e-5, 2,7, 6,6, 6,19 / PROPM - por, ibeg, iend, jbeg, jend, kbeg, kend
544 0.1e-5, 7,7, 7,11, 6,19
545 0.1e-5, 6,7, 6,6, 2,5
546 0.1e-5, 7,7, 7,7, 2,5
547 0.559, 2,6, 7,11, 2,19
548 -1, 6*0
549 1 / PROPM - necho
550 0 /PROPM - info
551 0.00466, 2,6, 7,11, 2,19 / PROPM - permx, ibeg, iend, jbeg, jend, kbeg, kend
552 -1, 6*0
553 1 / PROPM - necho
554 0 /PROPM - info
555 0.00466, 2,6, 7,11, 2,19 / PROPM - permy, ibeg, iend, jbeg, jend, kbeg, kend
556 -1, 6*0
557 1 / PROPM - necho
558 0 / PROPM - info
559 0.0098, 2,6, 7,11, 2,19 / PROPM - permz, ibeg, iend, jbeg, jend, kbeg, kend
560 -1, 6*0
561 1 / PDG - necho
562 0.8, 0.5e-5 /PDG - wp,optcon
563 1 /PITER - necho
564 4, 20 /PITER - nopt, nmax
565 0, 1, 1 /PITER - rebson, rebgon, afon
566 1 /PITER - necho
567 3 /PITER - norda
568 3,4,1,0 /PITER - norder
569 1 /PILES - necho
570 0.2e-8, 1.1, 4, 0 /PILES - epsd, omega, nmax, info
571 1 /REBQ - necho
572 2,0 /REBQ - nmax, info
573 1,1,1 /REBQ - kbound, jbound, ibound
574 0.1e-20, 0.1e-20, 0.1e-20 /REBQ - akkmin,ajjmin,aiimin
575 1 /REBQ - necho
```

```
576 3 /REBQ - kreg
577 1,1, 2,7, 2,5
578 2,1, 2,7, 6,11
579 3,0, 8,11, 6,11 /REBQ - krid
580 1 /REBQ - necho
581 6 /REBQ - kbida
582 1, 2,2
583 2, 3,1 /REBQ - kbid
584 1 /REBQ - necho
585 5 /REBQ - jreg
586 1,3, 2,7, 2,19
587 2,1, 8,11, 2,5
588 3,1, 8,11, 6,19
589 4,1, 8,11, 20,23
590 5,0, 2,7, 20,23 /REBQ - jrid
591 1 /REBQ - necho
592 16 /REBQ - jbida
593 1, 2,1, 3,1, 5,3
594 2, 3,3
595 3, 4,3
596 4, 5,-1 /REBQ - jbid
597 1 /REBQ - necho
598 5 /REBQ - ireg
599 1,3, 2,7, 2,19
600 2,1, 8,11, 2,5
601 3,1, 8,11, 6,19
602 4,1, 8,11, 20,23
603 5,0, 2,7, 20,23 /REBQ - irid
604 1 /REBQ - necho
605 16 /REBQ - ibida
606 1, 2,2, 3,2, 5,3
607 2, 3,3
608 3, 4,3
609 4, 5,-2
```

٩

610 1 /AF - necho
611 5,0 /AF - nmax,info
612 1 /AVG - necho
613 0, 0.496e+6 /AVG - fixedm,fixedp
*

APPENDIX B

# SAMPLE PROBLEM OUTPUT

.

# APPENDIX B

(

# SAMPLE PROBLEM OUTPUT

Use quarter symmetry run number         I           main         nrun=1         nstep=1000         nsinio=200           main         nread=0         nwrite=1         ndump=1000           main         nread=0         nwrite=1         ndump=100           main         rebaon=0,0         nreb=0         nov=0           main         rebaon=0,0         nreb=1         nov=0           main         rebaon=0,0         nreb=0         nov=0           pti=0,0         npti=0         pti=1,0         pti=1,0           pti=1,0         nptr=0,0         npti=1         pti=1,0           pti=1,0         nptr=0,0         npti=1         pti=1,0           pti=1,0         npt=2         npti=1,0         npti=1           ppf=0,0         npti=1         jittim=1         jittim=1           grid         symtry=1,0 <th>4</th> <th></th> <th></th> <th></th> <th>Арт</th> <th>endix Prob</th> <th>lem Input</th> <th></th> <th></th> <th></th> <th></th> <th></th>	4				Арт	endix Prob	lem Input					
run number 1 mein nrun=1 nstep=1000 nsifo= 200 mein nread=0 nwrita=1 ndump=1000 mein stedy=1.0 nobdy=0 nove!=0 netra=1 mein netra=1 mein ntime=1 dtime=0_100e+00 dtimex=0,100e+01 dtimin=0,100e=01 mein rebeon=0,0 nreb=10 nrebn= 1 mein rebeon=0,0 nreb=10 nrebn= 1 mein print plane options are 2 meximum allowed is 4 with 5 planes per option option 2: 2 10 mein print arrays or info pti=0,0 npti=0 pti=0,0 npti=0 pti=0,0 npti=0 pti=0,0 npti=0 pti=0,0 npti=0 pti=0,0 npti=0 pti=0,0 npti=0 pti=1,0 npti=0 pti=0,0 npti=0 pti=0,0 npti=0 pti=0,0 npti=0 pti=0,0 npti=0 grid symtry=1.0 fifatm=3 fifatm=11 jfiatm=10 grid ieend(j) jebeg(1) jeend(1) imend(j) jmeng(1) jmend(1) icart(js) jcart(js) isend(k) 1 1 2 11 4 2 11 et at 6 4 5 6 4 11 7 3 11 5 3 6 4 5 6 4 11 7 3 11 5 3 6 4 6 5 8 9 7 11 10 0 6 11 8 6 4 6 6 7 8 6 11 9 5 11 7 5 6 7 8 6 11 9 5 11 8 0 7 10 10 6 11 8 7 5 6 7 10 10 7 10 0 7 10 10 7 5 6 7 10 0 7 10 10 7 5 6 7 10 0 7 10 10 7 5 6 7 10 0 7 10 0 7 10 0 7 10 0 7 10 0 7 10 0 7 10 0 0 10 0 7 10 10 7 5 6 7 10 0 0 0 0 0 7 10 0 0 0 7 10 0 0 0 7 10 0 0 0 7 10	5				Use	quarter sy	mmetry					
7       mein       nrun=1       nstep=1000       nsinfo=200         9       mein       nread=0       nortmp=0       novel=0         10       mein       nesteal       nobody=0       nortmp=0       novel=0         11       mein       nest=1       nest=0       notemp=0       100e+01       dtimin=0,100e-01         12       mein       nethe=1       nest=0       nest=0       nest=0         12       mein       redeon=1,0       radon=1,0       radon=1,0       radon=1,0         13       mein       print plane options are 2       2       meximum allowed is 4 with 5 planes per option         14       mein       print arrays or info       pti=0,0       npti=0         14       pdnd=1,0       npdi=1       papid=0       pti=0,0       npti=0         15       papid=1,0       npti=0       pti=0,0       npti=0       pti=0,0       npti=0         15       papid=1,0       npti=0             16       pti=0,0       npti=0             16       pti=0,0       npti=0	6						run num	ber 1				
8       mein       mrun=1       nstmep=1000         10       mein       steedy=1.0       nobody=0       notemp=0       novei=0         11       mein       netra=1       num==0.100e+00       dtimex=0.100e+01       dtimin=0.100e+01         12       mein       netra=1       dtimex=0.100e+00       dtimex=0.100e+01       dtimin=0.100e+01         13       mein       redcon=1.0       redcon=1.0       redcon=1.0         14       mein       redcon=0.0       nredton=1.0       redcon=1.0         15       mein       redcon=1.0       redcon=1.0       redcon=1.0         16       nein       print plane options are       2 maximum allowed is       4 with       5 planes per option         17       option       2:       2 10	7											
9       meIn       nread-0       nurite=1       ndump=1000         10       meIn       steady=1.0       nobody=0       notemp=0       notemp=0         11       meIn       neth=1       time=1       dtimes=0.100e+00       dtimes=0.100e+01       dtimin=0.100e-01         12       meIn       radion=1.0       radion=1.0       radion=1.0       radion=1.0         14       meIn       rabson=0.0       nreb=10       nreb=1       nreb=1         15       meIn       radion=1.0       radion=1.0       radion=1.0         16       meIn       print plane options are 2 meximum allowed is 4 with 5 planes per option       option         17       option 2:       2 l0           18       option 0:       2 l1           19         prist_0.0       prist=0         21       prist_0.0       nprist=0           22       prist=0.0       prist_0.0       prist_0.0          23       pgtnd=0.0             24       pipt=0.0       prist_0.0       nprist_0.0           25       pist=0.0       nprist_0.0	8	mein	nrun= 1	nstep=1000	nsinfo=	200						
10       meIn       steady=1,0       notemp=0       nove1=0         11       meIn       net1me=1       dt1men=0,100e+00       dt1max=0,100e+01       dt1m1n=0,100e-01         13       meIn       notem=0,0       redon=1,0       redon=1,0         14       meIn       redon=1,0       redon=1,0         15       meIn       print plane options are 2 meximum allowed is 4 with 5 planes per option         16       meIn       print plane options are 2 meximum allowed is 4 with 5 planes per option         17       option 1: 8       option 2: 2 10         20       meIn       print arrays or info         21       pti=0,0       mpts=0         22       pti=0,0       npts=0         23       pqdnd=1,0       -         24       pql=1,0       npg=0         25       pqrad=0,0       npms=0         26       pts=1,0       npms=0         27       pt=1,0       npms=0         28       pfs=0,0       npms=0         29       pmx=1,0       npms=2         30       pmy=0,0       npp=1         31       ppf=0,0       npf=0         33       pdf=1,0       jmed(1)       imed(1)       imed(1) </td <td>9</td> <td>main</td> <td>nread=0</td> <td>nwrite=1</td> <td>ndump=1000</td> <td>)</td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td>	9	main	nread=0	nwrite=1	ndump=1000	)						
11       mein       newta=1         12       mein       netime=0,100s+00       dtimex=0,100s+01         13       mein       redecon=1,0       redpon=1,0         14       mein       redecon=0,0       nreb=100         14       mein       print piane options are 2 maximum allowed is 4 with 5 planes per option         16       mein       print piane options are 2 maximum allowed is 4 with 5 planes per option         17       option 1: 8       option 2: 2 l0         19       netime=0,0 mpti=0       pti=0,0 mpti=0         22       pti=0,0 mpti=0       pti=0,0 mpti=0         23       pdpd=1,0       pprad=0,0         24       pdi=1,0 mpti=0       pti=0,0 mpti=0         25       pprad=0,0 mpti=0       pti=0,0 mpti=0         26       pti=0,0 mpti=0       pti=0,0 mpti=0         27       pti=1,0 mpti=0       pti=0         28       ppto=0,0 mpti=0       pti=0         29       pmx=1,0 npmz=2       pupdi=1,0         29       pmx=1,0 iflatm=3 iflatp=11 jflatm=10 jflatp=11         39       1       1       2       1         39       2       3       2       1       4       1         39       2	10	main	steady=1.0	nobody =	0 notemp:	=0 novel=0	)					
12       mein       ndtime=1       dtimes=0,100s+00       dtimin=0,100s-01         13       mein       radcon=1,0       radcon=1,0         14       mein       redcon=0,0       neb=10         15       neb=100       neb=1         16       mein       print plane options are 2 meximum allowed is 4 with 5 planes per option         17       option 2: 2 10         18       option 2: 2 10         20       mein       print arrays or info         21       pti=0,0       npti=0         22       ptsi=0,0       npti=0         23       pqdmd=0       pris=0         24       pql=1,0       npti=0         25       pgrad=0,0       npti=0         26       pti=0,0       npti=0         27       pt=1,0       npti=0         28       ppts=0       psi=0         29       pmx=1,0       npmx= 2         30       pmy=0,0       npmx=1         31       pptf=1,0       nptf=1         35       grid       leend(j) jebe(i) jeend(i) immd(j) jmbe(i) jmend(i) icart(js) jcart(js) isend(k)         36       2       3       2       11       4         36       2	11	main	newta=1									
13       mein       radoon=1.0       radoon=1.0         14       mein       rebon=0.0       nreb=100       nreb= 1         15       mein       print plane options are       2 meximum allowed is       4 with       5 planes per option         16       mein       print plane options are       2 meximum allowed is       4 with       5 planes per option         17       option       1:       8       option       2:       1         18       option       2:       10	12	main	ndtime≠1	dtimen=0.	100 <del>a+</del> 00 d	ttimax=0,100	De+01 dtli	nin=0 <b>,</b> 100e-4	01			
14       mein       rebon=0.0       nreb=100       nreb=1         15       mein       print plane options are 2 maximum allowed is 4 with 5 planes per option       option         17       option 1: 8       option 2: 2 10       option 2: 2 10         18       option 0: 2: 2 10       option 0: 2: 2 10         20       mein       print arreys or info         21       pti=0.0       npti=0         22       pts=0.0       npts=0         23       pqdnd=1.0       option 2: 2         24       pql=1.0       npt=0         25       pqrad=0.0       optis=0         26       pts=0.0       npt=0         27       pts=1.0       npt=0         28       pts=1.0       npt=0         29       pmw=1.0       npt=1         29       pmy=0.0       npmz= 2         20       ppf=0.0       npf=1         37       ppf=0.0       npf=1         36       1       1       1       4         37       ppf=0.0       npt=1       jflatp=11         36       1       2       11       4       2       1         37       grid       semf(j) jebeg(i) jeend(i	13	main	radcon=1.0	radpon=	1.0 radro	on=1.0						
15       main       print plane options are 2 maximum allowed is 4 with 5 planes per option         16       option 1: 8         17       option 2: 2 10         18       option 2: 2 10         20       main         21       pti=0.0         22       pts=0.0         23       pqtmather.0         24       pql=1.0         25       pqtad=0.0         26       pts=0.0         27       pts=0.0         28       pts=1.0         29       pmx=1.0         29       pmx=2.0         20       ppf=0.0         21       pts=0.0         22       pdpf=1.0         23       ppf=0.0         24       ppf=0.0         25       pmx=1.0         26       pts=1.0         pmz=1.0       npmt=2         20       pmx=2.1         21       ppf=0.0         23       ppf=0.0         24       jpf=0.0         25       grid         1       1         25       grid         1       2         26       1         27	14	mein	rebaon=0.0	nreb=10	0 nrebn=	1						
16       main       print plane options are 2 meximum allowed is 4 with 5 planes per option         17       option 1: 8         18       option 2: 2 10         19       main         20       main         21       ptimover intervation of the intervation of the intervation of the intervation of the intervation of the intervation of the intervation of the intervation of the intervation of the intervation of the intervation of the intervation of the intervation of the intervation of the intervation of the intervation of the intervation of the intervation of the intervation of the intervation of the intervation of the intervation of the intervation of the intervation of the intervation of the intervation of the intervation of the intervation of the intervation of the intervation of the intervation of the intervation of the intervation of the intervation of the intervation of the intervation of the intervation of the intervation of the intervation of the intervation of the intervation of the intervation of the intervation of the intervation of the intervation of the intervation of the intervation of the intervation of the intervation of the intervation of the intervation of the intervation of the intervation of the intervation of the intervation of the intervation of the intervation of the intervation of the intervation of the intervation of the intervation of the intervation of the intervation of the intervation of the intervation of the intervation of the intervation of the intervation of the intervation of the intervation of the intervation of the intervation of the intervation of the intervation of the intervation of the intervation of the intervation of the intervation of the intervation of the intervation of the intervation of the intervation of the intervation of the intervation of the int	15											
17 option 1: 8 18 option 2: 2 10 19 20 main print arrays or info 21 pti=0,0 npti= 0 22 ptsi=0,0 nptsi= 0 23 pqbnd=1,0 24 pql=1,0 npt= 1 25 pqrad=0,0 nptsi= 0 26 ptsi=0,0 npts= 0 27 pt=1,0 npt= 0 28 pts=1,0 npt= 0 29 pmx=1,0 npmx= 2 30 pmy=0,0 npmx= 2 31 pmz=1,0 npmz= 2 32 pdpf=1,0 npmz= 2 33 pff=0,0 npf= 0 34 35 grid symtry=1,0 ifiatm=3 ifiatp=11 jfiatm=10 jfiatp=11 36 37 grid leend(j) jebeg(1) jeend(1) imend(j) jmbeg(1) jmend(1) icart(js) jcart(js) isend(k) 38 1 1 2 11 4 2 11 ** *** 6 39 2 3 2 11 4 2 11 2 1 6 40 3 4 2 11 5 2 11 3 1 6 41 4 5 3 11 6 2 11 4 2 6 41 4 5 3 11 6 2 11 4 2 6 41 4 5 3 11 6 2 11 4 2 6 41 4 5 3 11 6 4 6 41 4 5 3 11 6 4 6 41 7 8 6 11 9 5 11 7 5 6 44 7 8 6 11 9 5 11 7 5 6 45 8 9 7 7 11 10 6 11 8 4 6	16	main	print plan	e options	are 2 maxi	imum allowed	d is 4 with	h 5 planes	per option			
18       option 2: 210         19       mein       print arrays or info         21       pti=0,0       npti=0         22       ptsi=0,0       nptsi=0         23       pqdpati,0       npti=0         24       pq1=1,0       npts=0         25       pqrad=0,0       npts=0         26       ptsi=0,0       npts=1         27       pt=1,0       npt=0         28       pts=1,0       npt=2         29       pmx=1,0       npmz=2         30       ppf=0,0       nppf=0         31       ppf=0,0       nppf=0         34       35       grld       symtry=1.0       ifiatp=11         37       grld       ieend(j)       jeend(i)       imend(j)       jmend(i)       icart(js)       isend(k)         38       1       1       2       11       4       2       11       ***       6         36       2       3       2       11       4       2       11       ***       6         38       1       1       2       11       4       2       1       6         39       2       3       2	17		option 1:	8				·				
19       mein       print arreys or info         21       print arreys or info         22       ptsi=0,0       npti=0         23       pqdnd=1,0         24       pql=1,0       npqt=0         25       pqrad=0,0       nptsi=0         26       ptsi=0,0       npts=0         28       pts=1,0       npts=0         29       pmx=1,0       npmz=2         30       ppmg=0,0       npmz=2         31       pmz=1,0       npt=1         35       grid       symtry=1,0       ifiatp=11         36       jfiatp=1       jfiatp=11         37       grid       ifiatp=3       ifiatp=11         36       jfiatp=1       jfiatp=11         37       grid       ifiatp=1       jfiatp=11         36       npf=0,0       npf=0         37       grid       ifiatp=1       jfiatp=1         37       grid       ifiatp=1       jfiatp=1         36       1       2       11       4         37       grid       ifiatp=1       jfiatp=1         36       1       2       11       6         37       3	18		option 2:	2 10								
20       main       print arreys or info         21       pti=0,0       npti=0         22       ptsi=0,0       nptsi=0         23       pqdnd=1,0         24       pqi=1,0       nptsi=0         25       pqrad=0,0       nptsi=0         26       ptsi=0,0       nptsi=0         27       pt=1,0       npt=0         28       ptsi=0,0       npmx=2         30       pmy=0,0       npmz=2         31       pmz=1,0       npmz=2         32       pdpf=1,0       npdf=1         33       ppf=0,0       nppf=0         34            55       grid       symtry=1,0       ifiatp=11       jfiatp=11         56       1       2       11       4       2       11       ***       6         57       grid       ieend(j) jebeg(i) jeend(i) imend(j) jmbeg(i) jmend(i) icart(js) jcart(js) isend(k)       isend(k)         38       1       1       2       11       4       2       1       6         59       2       3       2       11       4       2       1       6         40       3	19		•									
21       pti=0.0       npti=0         22       ptsi=0.0       nptsi=0         23       pqbnd=1.0	20	maln	print arra	ys or Info								
22       ptsl=0.0       nptsl=0         23       pqtnd=1.0       npql=1.0         24       pql=1.0       npql=1         25       pqrad=0.0       nptsl=0         26       ptsl=0.0       nptsl=0         27       pt=1.0       npt=0         28       ptsl=0.0       npmx=2         30       pmy=0.0       npmx=2         31       pmz=1.0       npdpf=1         35       ppf=0.0       nppf=0         34       34       2       11       4       2       11       ***       6         35       grid       ieend(j)       jebg(i)       jeend(i)       imend(j)       jmbg(i)       jeend(i)       isend(k)         38       1       1       2       11       ***       6         36       2       3       2       11       4       1       1       6         39       2       3       2       11       4       2       11       5       1       6         40       3       4       2       11       5       3       1       6         41       4       5       3       11       <	21		p+1=0.0	npti= 0								
23 pqbnd=1.0 24 pq1=1.0 npq1=1 25 pqrad=0.0 npqrad= 0 26 pts1=0.0 npts = 0 27 pt=1.0 npt= 0 28 pts=1.0 npmx= 2 30 pmy=0.0 npmy= 0 31 pmz=1.0 npmz= 2 32 pdpf=1.0 npdpf= 1 33 ppf=0.0 npdf= 1 34 35 grld symtry=1.0 iflatm=3 iflatp=11 jflatm=10 jflatp=11 36 37 grld leend(j) jebeg(l) jeend(l) lmend(j) jmbeg(l) jmend(l) lcart(js) jcart(js) isend(k) 38 1 1 2 11 4 2 11 ** ** 6 39 2 3 2 11 4 2 11 ** ** 6 39 2 3 2 11 4 2 11 2 1 6 40 3 4 2 11 5 2 11 2 1 6 40 3 4 2 11 6 2 11 4 2 1 6 41 4 5 3 11 6 2 11 4 2 6 41 4 5 3 11 6 2 11 4 2 6 43 6 7 5 11 8 4 11 6 4 6 44 7 8 6 11 9 5 11 7 5 6 45 8 9 7 1 1 10 6 11 7 5 6	22		ptsi=0.0	nptsl= 0								
24       pql=l_0 npql=1         25       pqrad=0_0 nptr=0         26       pts=l_0 npts=0         27       pt=l_0 npts=0         28       pts=l_0 npmr=0         29       pmx=l_0 npmr=2         30       pmr=0_0 npmr=2         32       pdpf=l_0 npnr=2         32       pdf=l_0 npdf=1         34       pf=0_0 npf=0         34       35         35       grld         1       1         28       1         29       pts=l_0 npmz=2         32       pdpf=l_0 npdf=1         34       35         35       grld         36       1         37       grld         1       2         1       2         1       4         2       3         2       1         38       1         1       2         1       4         2       3         2       3         38       1         39       2         3       4         2       1         4       5	23		pabnd=1.0	·								
25       pqrad=0,0       nprad=0         26       pts=0,0       npts=0         27       pt=1,0       npt=0         28       pts=1,0       npts=0         29       pmx=1,0       npmx=2         30       pmy=0,0       npmz=1         31       pmz=1,0       npmz=2         32       pdpf=1,0       npdpf=1         33       ppf=0,0       nppf=0         34       35       grid       symtry=1,0       ifiatm=3         36       1       1       2       11       4       2       11       ***       6         36       1       1       2       11       4       2       11       ***       6         37       grid       ieend(j)       jebeg(i)       jeend(i)       imend(j)       jmbg(i)       jmend(i)       icart(js)       jcart(js)       isend(k)         38       1       1       2       11       4       2       11       ***       6         39       2       3       2       11       4       2       11       2       1       6         40       3       4       2       11       <	24		pqi=1.0	npgi= 1								
26       ptsl=0.0       nptsl=0         27       ptsl=0.0       npts=0         28       ptsl=0.0       npts=0         29       pmx=1.0       npms= 2         30       pmy=0.0       npmz=1.0         31       pmz=1.0       npmz= 2         32       pdf=1.0       npdf=1         34	25		pgrad=0.0	npgrad=	0							
$\begin{array}{cccccccccccccccccccccccccccccccccccc$	26		pts1=0.0	npts1= 0								
28       pts=1.0       npts=0         29       pmx=1.0       npmx=2         30       pmy=0.0       npmy=0         31       pmz=1.0       npmz=2         32       pdpf=1.0       npdpf=1         33       ppf=0.0       nppf=0         34         35       grld       symtry=1.0         36       1       1         37       grld       leend(j)         38       1       1         39       2       3         2       3       2         39       2       3         40       3       4         41       4       5         42       5       6         43       6       7         44       7       8         45       8       9         45       8       9         45       8       9         45       8       9         45       8       9         45       8       9         45       8       9         45       8       6         45       11       9	27		pt=1.0 n	pt= 0								
$\begin{array}{cccccccccccccccccccccccccccccccccccc$	28		pts=1.0	npts= 0								
$\begin{array}{cccccccccccccccccccccccccccccccccccc$	29		pmx=1.0	nomx= 2								
31       pmz=1.0       npmz=2         32       pdpf=1.0       npdpf=1         33       ppf=0.0       nppf=0         34       35       grid       symtry=1.0       iflatp=11       jflatp=11         36       37       grid       ieend(j)       jebeg(i)       jeend(i)       imend(j)       jmbeg(i)       jmend(i)       icart(js)       jcart(js)       isend(k)         38       1       1       2       11       4       2       11       ***       ***       6         39       2       3       2       11       4       2       11       2       1       6         40       3       4       2       11       5       2       11       3       1       6         41       4       5       3       11       6       2       11       4       2       6         42       5       6       4       11       7       3       11       5       3       6         42       5       6       4       11       7       3       11       5       3       6         43       6       7       5	30		pmy=0.0	npmy= 0								
$\begin{array}{cccccccccccccccccccccccccccccccccccc$	31		pmz=1.0	npmz= 2								
$\begin{array}{cccccccccccccccccccccccccccccccccccc$	32		pdp f =1.0	nodof= 1								
$\begin{array}{c ccccccccccccccccccccccccccccccccccc$	33		opf=0.0	noof= 0								
$\begin{array}{c ccccccccccccccccccccccccccccccccccc$	34		FF •									
$\begin{array}{c ccccccccccccccccccccccccccccccccccc$	35	arid	symtry=1.0	iflatm=	3 Iflate	o≖11 iflat	tm=10 ifla	ato=11				
$ \begin{array}{c ccccccccccccccccccccccccccccccccccc$	36	3, 12	-,,			<b>J</b>	<b>J</b>					
$\begin{array}{cccccccccccccccccccccccccccccccccccc$	37	arid		leend(i)	ie bea(i)	ieend(i)	imend(i)	imbea(i)	imend(i)	icart(is)	icart(is)	isend(k)
$\begin{array}{cccccccccccccccccccccccccccccccccccc$	38	<b>J</b>	1	1	2	11	4	2	11	**	**	6
40       3       4       2       11       5       2       11       3       1       6         41       4       5       3       11       6       2       11       4       2       6         42       5       6       4       11       7       3       11       5       3       6         43       6       7       5       11       8       4       11       6       4       6         44       7       8       6       11       9       5       11       7       5       6         45       8       9       7       11       10       6       11       8       6       6	39		2	3	2	11	4	2	11	2	1	6
41       4       5       3       11       6       2       11       4       2       6         42       5       6       4       11       7       3       11       5       3       6         43       6       7       5       11       8       4       11       6       4       6         44       7       8       6       11       9       5       11       7       5       6         45       8       9       7       11       10       6       11       8       6       6	40		3	4	2	11	5	2	11	3	1	6
42     5     6     4     11     7     3     11     5     3     6       43     6     7     5     11     8     4     11     6     4     6       44     7     8     6     11     9     5     11     7     5     6       45     8     9     7     11     10     6     11     8     6	41		4	5	3	11	6	2	11	4	2	6
43     6     7     5     11     8     4     11     6     4     6       44     7     8     6     11     9     5     11     7     5     6       45     8     9     7     11     10     6     11     8     6     6	42		5	6	4	11	7	-	11	5	3	6
44     7     8     6     11     9     5     11     7     5     6       45     8     9     7     11     10     6     11     8     6     6	43		6	2 7	5	11	8	4	11	6	4	6
	44		7	8	6	11	9	5	11	7	5	6
	45		. 8	ğ	7	11	10	6	11	, 8	6	6

46		9	10	8	11	11	7	11	9	7	6
47		10	11	9	11	11	8	11	10	8	6
48		11	11	10	11	11	9	11	11	Ğ	6
49		12	11	**	**	11	**	**	12	10	6
50		13	**	**	**	**	**	**	12	11	6
51		14	**	**	**	**	**	**	**	**	6
52		15	**	**	**	**	**	**	**	**	6
53		16	**	**	**	**	**	**	**	**	6
54		17	**	**	**	**	**	**	**	**	6
55		18	**	**	**	**	**	**	**	**	6
56		19	**	**	**	**	**	**	**	**	6
57		20	**	**	**	**	**	**	**	**	6
58		21	**	**	**	**	**	**	**	**	6
59		22	**	**	**	**	**	**	**	**	6
60		23	**	**	**	**	**	**	**	**	6
61		24	**	**	**	**	**	**	**	**	6
62		25	**	**	**	**	**	**	**	**	6
63		26	**	**	**	**	**	**	**	**	6
64		27	**	**	**	**	**	**	**	**	6
65		28	**	**	**	**	**	**	**	**	6
66		29	**	**	**	**	**	**	**	¥¥	6
67		30	**	**	**	**	**	**	**	**	6
68											v
69	grid		dx(1)	I.	dy (j )		dz (k)	c	Ir(is)	dtheta	(is)
70		1	0.10000000	le+01	0.10000000e+01	0.1	0000000a+01	0,1051	48051e+02	0, 38991 396	540+01
71		2	0,715010000	le+00	0.405301768e+00	0.1	00000000e+01	0.5000	00000e+00	0, 38991 390	540+01
72		3	0,143002000	le+01	0.641200898e+00	0.2	000000000000000000000000000000000000000	0.1000	00000a+01	0,78718809	3a+01
73		4	0.143002000	le+01	0.931490811e+00	0.1	0000000e+01	0,1000	00000e+01	0.8105947	72e+01
74		5	0,143002000	e+01	0 <b>.880602593e+00</b>	0.2	50000000e+01	0.1000	00000e+01	0.85476526	58e+01
75		6	0.143002000	le+01	0.100000000e+01	0.2	50000000e+01	0.5000	00000a+00	0.93098376	50e+01
76		7	0.10000000	e+01	0.143002000e+01	0.2	50000000 <del>e+0</del> 1	0,1000	00000e+01	0.72655414	3e+01
77		8	0.880602593	e+00	0.143002000e+01	0,2	5000000e+01	*****	*****	0.72655414	13e+01
78		9	0,931490811	e+00	0.143002000e+01	0,2	5000000 <del>0</del> +01	*****	*****	0.93098376	00+01
79		10	0.641200898	e+00	0.143002000e+01	0.3	25000000e+01	****	*******	0.85476526	58e+01
80		11	0.405301768	e+00	0.715010000e+00	0.4	25000000e+01	*****	*****	0.81059477	2e+01
81		12	0.10000000	e+01	0.10000000e+01	0.5	5000000 <del>0</del> +01	*****	*******	0.78718809	
82		13	*******	****	***********	0.7	25000000e+01	****	****	0,38991396	4e+01
83		14	********	****	*****	0.9	50000000e+01	****	*****	0.38991396	54e+01
84		15	*********	****	******	0.1	27500000e+02	****	*******	******	****
85		16	********	****	************	0.1	27500000 <del>o+</del> 02	****	*****	*******	*****
86		17	****	****	*****	0.9	5000000 <del>0</del> e+01	*****	*****	*******	****
87		18	*********	****	****	0.7	25000000e+01	*****	*****	******	*****
88		19	****	****	*****	0.5	5000000 <del>0</del> e+01	*****	*****	*******	****
89		20	********	****	***********	0.4	25000000 <del>0</del> +01	*****	*****	********	*****
90		21	******	****	**********	0.3	25000000 <del>o+</del> 01	*****	*******	*******	****
91		22	****	****	*****	0.2	50000000-+01	****	****	*******	*****

92		23	****	****	0,250000000e+01	*****	******
93		24	****	*****	0.250000000e+01	****	**********
94		25	*****	****	0,250000000e+01	****	******
95		26	*****	****	0.25000000e+01	****	**********
96		27	****	******	0,10000000e+01	******	*********
97		28	****	*****	0.200000000+01	****	*****
08		29	****	****	0.100000000+01	****	***********
00		30	****	****	0 100000000000000	*****	****
100		20			0.100000000.01		0 90000000-+02
100							0.900000000000
101					0 0 1	-0	
102	prop	nsx= ∪	nstx= 0 nsy= 0	/ nsty= 0 nsz=	0 nstz= 0 Into	-0	
105		+	+	+		0 3330+00	
104	prop	ropn-reu	1001-0.2010+02			0,250,400	
105	ргор	DOTN=0,0	DOTIEU.ZOIETUZ			0,200000	
100					- 10		
107	prop	nmat= o	maximum current d	limension for nmat i		I.	
108	ргор	cconu,cco	on i, ccon 3		mai conductivity, W/		
109			k(mat)= cc	conv(mat)+ cconi(ma	T) TT CCONS(Mat) TT		• •
110			1 (0,1	000e=20)+(0,0000e+0	10) *f + (0,0000e+00) *f *	TT IOW CONDUCTIV	іту
111			2 (0.1	000e+20)+(0,0000e+0)	00)*++(0,0000e+00)*+*	ter high conduction	VITY
112			3 (0.5	200e-03)+(0_3200e-0	)5)*++(0,0000e+00)*+*	ter hellum (back	fill gas )
113			4 (0,9	0215e-01)+(0.1465e-0	)3)*++(0,0000e+00)*+*	t*t stainless ste	el
114			5 (0,5	162e+00)+(-,3205e-0	)3)*++(0_0000+00)*+*	t*t nodular cast	Iron
115			6 (0,6	6880e-04)+(0.6340e-0	)6)*++(0 _• 0000e+00)*+*	t*t air (not use	d )
116							
117			π	naximum number of me	iterial types is curr	ently 50	
118			m	aximum array dimens	ion of specs is curr	ently 50	
1 19							
120			***c	composite definition	n 01 isotropic and 11	parallel***	
121	prop	mtmax≖ 5	5				
122	prop	specs		mt mets	s <del>ma</del> t width		
123				1 1	1 0,1000e+01		
124				2 1	2 0,1000e+01		
125				3 1	3 0,1000e+01		
126				4 1	4 0,1000e+01		
127				5 1	5 0,1000e+01		
128							
129				computed coeffi	cients from specs ar	rav	
130				mt c0	c1 c3	,	
131				1 0,1000e-20	0,0000+00 0,0000e	+00	
132				2 0.1000e+20	0.0000+00 0.0000	+00	
133				3 0.5200-03	0.3200e-05 0.0000e	+00	
134				4 0.9215-01	0.1465e=03 0.0000e	+00	
135				5 0 5162-400	-0.3205e-03 0.0000e	+00	
136				2 00201020100	**************************************		
137				*************	afinition 21 contact	**	
					101 111 1 101 41 301 103		

(

(

в.З

138	prop	mtma×≃	7								
139	ргор	specs		mt	mat	width	et	e2	twf		
140				40	1	0.1000e+01	0,2000e+00	0 <b>.</b> 1000e+01	0,5000e+00		
141				41	5	0.1600e-01	0.0000e+00	0.00000+00	0 <b>,</b> 5000e+00		
142				42	3	0.1600e-01	0.0000e+00	0,0000e+00	0.0000e+00		
143				43	5	0.1070e+00	0.0000e+00	0,0000e+00	0,5000e+00		
144				44	3	0.1070e+00	0.0000+00	0,0000e+00	0.0000e+00		
145				45	3	0.1600-01	0.0000+00	0,0000e+00	0,1000e+01		
146				46	3	0.1070e+00	0.0000+00	0.0000e+00	0.1000e+01		
147					-			••••	•		
148					0	mouted coef	ficients fro	m specs arra			
149							c1	c3			
150					4	0.1000e-2	0 0.0000+0	0 0.4536e-1	1		
151					4	0.3226e+0	7 -0.2003e-0	0.0000e+0	0		
152					4	2 0.3250e=0	1 0.20000	13 0.0000e+0	0		
153					4	5 0.4824e+0	1 -0.2995-0	0.0000e+0	0		
154					4			A 0.0000+0	0		
155					4	5 0 3250e-0			• 0		
156					4	5 0.4860a-0			0		
157					-				•		
158					***~	mocite def	inition 31 f	Fual accombly	***		
150		mt may =	1					1001 03300017			
160	prop		· 	men fucion		aladad	. Itah	ofuol	coled or	ed of	
100	prop	specs	m1	mia fuelou			pi i ch	CIUGI		00 898	P
					•	1072~401 0	1430-401 0	2000-01 0	1150-400 0.00	000400 0 000	0~+00
161			47	3 0.9484e+00	0.	10720+01 0.	1430e+01 0.	,2090e-01 0.	1150e+00 0.00	000000000000000000000000000000000000000	00 <del>o</del> +00
161			4/	3 0 <b>.</b> 9484e+00	0.	10720+01 0.	1430e+01 0.	,2090e-01 0.	1150e+00 0.00	0000+00 0.000	00e+00
161 162 163			47	3 0.9484e+00	0.	omputed coef	1430e+01 0. ficients fro	,2090e-01 0, om specs arra	1150e+00 0.00 y1	-2°	-3
161 162 163 164			47 mt	3 0.9484⊕+00 c0 c	0. c	omputed coef c3	1430e+01 0. ficients fro x1	2090e-01 0. om specs arra x2	1150e+00 0.00 y z1	22 0.0.959101	z3
161 162 163 164 165			47 mt 47	3 0.9484e+00 c0 c 0.5200e-03 0.32	0. c: 1 200e-1	1072e+01 0. omputed coef c3 05 0.0000e+	1430e+01 0. ficlents fro x1 00 0.1130e+	,2090e-01 0. xm specs arra x2 +01 0.1701e+	1150e+00 0.00 y z1 01 0.3455e+00	22 0.9591e-01	23 0₅5586⊕+00
161 162 163 164 165 166			47 mt 47	3 0,9484e+00 c0 c 0,5200e-03 0,32	0. 0. 1 00e-1	1072e+01 0. omputed coef c3 05 0.0000e+	1430e+01 0. flclents fro x1 00 0.1130e+	2090e-01 0. xm specs arra x2 H01 0.1701e+	1150e+00 0.00 y z1 01 0.3455e+00	00e+00 0.000 z2 0 0.9591e-01	23 0,5586⊕+00
161 162 163 164 165 166 167			47 mt 47	3 0,9484e+00 c0 c 0,5200e-03 0,32	0. c 1 200e-4	1072e+01 0. omputed coef c3 05 0.0000e+ **available	1430e+01 0. flclents fro x1 00 0.1130e+ composite de	2090e-01 0. xm specs arra x2 H01 0.1701e+ afinitions***	1150⊕+00 0,00 y 21 01 0,3455⊕+00	00⊕+00 0.000 z2 ) 0.9591⊖-01	23 0,5586⊕+00
161 162 163 164 165 166 167 168			47 mt 47	3 0,9484e+00 c0 c 0,5200e-03 0,32	0. c 1 00e- groi	1072e+01 0. omputed coef c3 05 0.0000e+ **available	1430e+01 0. flclents fro x1 00 0.1130e+ composite de Id	2090e-01 0. om specs arra x2 H01 0.1701e+ afinitions***	1150⊕+00 0.00 y 21 01 0.3455⊕+00	00⊕+00 0.000 z2 ) 0.9591⊖-01	23 23 0₅5586 <del>e</del> +00
161 162 163 164 165 166 167 168 169			47 mt 47	3 0,9484e+00 c0 c 0,5200e-03 0,32	0. c 1 00e- yrol iso	1072e+01 0. cmputed coef c3 05 0.0000e+ **available up tropic	1430e+01 0. flclents fro x1 00 0.1130e4 composite de Id 1 re	2090e-01 0. xm specs arra x2 H01 0.1701e+ afinitions***	1150⊕+00 0.00 y 21 01 0.3455⊕+00	000+00 0.000 z2 0 0.9591e-01	z3 0,5586⊕+00
161 162 163 164 165 166 167 168 169 170			47 mt 47	3 0,9484e+00 c0 c 0,5200e-03 0,32 01	0. c 1 00e- groi iso	1072e+01 0. cmputed coef c3 05 0.0000e+ **available up tropic	1430e+01 0. flclents fro x1 00 0.1130e4 composite de Id 1 re 2 re	2090e-01 0. xm specs arra x2 H01 0.1701e+ afinitions*** asy	1150⊕+00 0.00 y 21 01 0.3455⊕+00	00⊕+00 0.000 z2 0 0.9591⊖-01	z3 0,5586⊕+00
161 162 163 164 165 166 167 168 169 170 171			47 mt 47	3 0,9484e+00 c0 c 0,5200e-03 0,32 01	0. c 1 00e- groi iso	1072e+01 0. cmputed coef c3 05 0.0000e+ **available up tropic	1430e+01 0. flclents fro x1 00 0.1130e4 composite de Id 1 re 2 re 3 re	2090e-01 0. xm specs arra x2 H01 0.1701e+ afinitions*** asy asy asy	1150⊕+00 0.00 y 01 0.3455⊕+00	00⊕+00 0.000 z2 0 0.9591⊖-01	z3 0,5586⊕+00
161 162 163 164 165 166 167 168 169 170 171 172			47 mt 47	3 0,9484e+00 c0 c 0,5200e-03 0,32 01	0. c 1 200e- y grou iso	1072e+01 0. cmputed coef c3 05 0.0000e+ **available up tropic	1430e+01 0. flclents fro x1 00 0.1130e4 composite de Id 1 re 3 re 4 re	2090e-01 0. xc specs arra x2 H01 0.1701e+ afinitions*** asx asy asy asy asy, resy, resz	1150⊕+00 0.00 y z1 01 0.3455⊕+00	00⊕+00 0.000 z2 0 0.9591⊖-01	z3 0,5586⊕+00
161 162 163 164 165 166 167 168 169 170 171 172 173			47 mt 47	3 0.9484e+00 c0 c 0.5200e-03 0.32 01	0. c 1 200e- grou iso	1072e+01 0. cmputed coef c3 05 0.0000e++ **available up tropic	1430e+01 0. flclents fro x1 00 0.1130e4 1d 1 re 3 re 4 re 11 re	2090e-01 0. xx specs arra x2 HO1 0.1701e+ afinitions*** asx asx asy asz asx, resy,resz asx, x-y plan	1150⊕+00 0.00 y z1 01 0.3455⊕+00	22 22 0 0.9591e−01	z3 0,5586⊕+00
161 162 163 164 165 166 167 168 169 170 171 172 173 174			4 7 mt 4 7	3 0,9484e+00 c0 c 0,5200e-03 0,32 01	0. c 1 00e- groi iso	1072e+01 0. cmputed coef c3 05 0.0000e+ **available p tropic	1430e+01 0. flclents fro x1 00 0.1130e4 1d 1 re 3 re 4 re 11 re 12 re	2090e-01 0. xx specs arra x2 HO1 0.1701e+ afinitions*** asx asx asx asx asx asx asx asx	1150⊕+00 0.00 y z1 01 0.3455⊕+00 e	22 22 0 0.9591e−01	z3 0,5586⊕+00
161 162 163 164 165 166 167 168 169 170 171 172 173 174 175			4 7 mt 4 7	3 0,9484e+00 c0 c 0,5200e-03 0,32 01	0. c 1 200e-4 groi iso	1072e+01 0. cmputed coef c3 05 0.0000e++ **available up tropic	1430e+01 0. flclents fro x1 00 0.1130e4 10 1 re 1 re 3 re 4 re 11 re 12 re 13 re	2090e-01 0. x2 x2 x01 0.1701e+ afinitions*** asx asx asx asx asx, resy,resz asx, x-y plan asy, x-y plan	1150⊕+00 0.00 y z1 01 0.3455⊕+00 9 9 9	22 22 0 0.9591⊖-01	z3 0₅5586⊕+00
161 162 163 164 165 166 167 168 169 170 171 172 173 174 175 176			47 mt 47	3 0,9484e+00 c0 c 0,5200e-03 0,32 01	0. c 1 200e-4 groi iso	1072e+01 0. cmputed coef c3 05 0.0000e++ **available up tropic	1430e+01 0. flclents fro x1 00 0.1130e4 id 1 re 1 re 3 re 4 re 11 re 12 re 13 re 14 re	2090e-01 0. x2 x2 x01 0.1701e+ afinitions*** asx asx asx asx, resy,resz asx, x-y plan asy, x-y plan asy, y-z plan	1150e+00 0.00 y z1 01 0.3455e+00 e e	22 22 0 0.9591⊖-01	z3 0,5586⊕+00
161 162 163 164 165 166 167 168 169 170 171 172 173 174 175 176 177			47 mt 47	3 0,9484e+00 c0 c 0,5200e-03 0,32 01	0. c 1 200e-1 iso iso	1072e+01 0. cmputed coef c3 05 0.0000e++ **available up tropic	1430e+01 0. ficients fro x1 00 0.1130e4 composite de Id 1 re 2 re 3 re 1 re 12 re 13 re 14 re 15 re	2090e-01 0. cm specs arra x2 HO1 0.1701e+ afinitions*** asx asx asx, resy,resz asx, x-y plan asy, x-y plan asy, y-z plan asy, x-z plan	1150e+00 0.00 y z1 01 0.3455e+00 e e e	22 2000 € 000 22 000 000 000 000 000 000 000 00000000	z3 0,5586⊕+00
161 162 163 164 165 166 167 168 169 170 171 172 173 174 175 176 177 178			47 mt 47	3 0.9484e+00 c0 c 0.5200e-03 0.32 01 11	0, c: 1 000e iso par	1072e+01 0. omputed coef c3 05 0.0000e++ **available up tropic	1430e+01 0. flclents fro x1 00 0.1130e4 composite de Id 1 re 2 re 3 re 1 re 12 re 13 re 14 re 15 re 16 re 2	2090e-01 0. cm specs arra x2 HO1 0.1701e+ afinitions*** asx asx asx, resy,resz asx, r-y plan asy, x-y plan asy, y-z plan asz, x-z plan	1150e+00 0.00 y z1 01 0.3455e+00 e e e e	22 2000 € 0000 22 000 000 0000 000 000 0000000000	z3 0,5586+00
161 162 163 164 165 166 167 168 169 170 171 172 173 174 175 176 177 178 179			47 mt 47	3 0.9484e+00 c0 c 0.5200e-03 0.32 01 11	o. c 1 2 000e-4 iso iso part	1072e+01 0. omputed coef c3 05 0.0000e++ **available up tropic	1430e+01 0. flclents fro x1 00 0.1130e+ 10 0.1130e+ 10 110e 11 re 12 re 13 re 14 re 15 re 16 re 17 re	2090e-01 0. cm specs arra x2 HO1 0.1701e+ afinitions*** asx asx asx, resy,resz asx, r-y plan asy, x-y plan asy, y-z plan asz, y-z plan asz, y-z plan	1150e+00 0.00 y z1 01 0.3455e+00 e e e	22 2000 € 0000 22 000 000 0000 0000000000	z3 0,5586+00
161 162 163 164 165 166 167 168 169 170 171 172 173 174 175 176 177 178 179 180			47 mt 47	3 0.9484e+00 c0 c 0.5200e-03 0.32 01 11	o. c 1 2 000e-4 iso part ser	1072e+01 0. omputed coef c3 05 0.0000e++ **available up tropic	14300+01 0. ficients fro x1 00 0.11300+1 composite de Id 1 re 2 re 3 re 11 re 12 re 13 re 14 re 15 re 21 re 22 re 27 re	2090e-01 0. cm specs arra x2 HO1 0.1701e+ afinitions*** asx asx asx, resy,resz asx, r-y plan asy, x-y plan asy, y-z plan asz, y-z plan asz, y-z plan asx asy	1150e+00 0.00 y z1 01 0.3455e+00 e e e	22 2000 € 0000 22 000 000 0000 0000000000	23 0,5586+00
161 162 163 164 165 166 167 168 169 170 171 172 173 174 175 176 177 178 179 180 181			47 mt 47	3 0.9484e+00 c0 c 0.5200e-03 0.32 01 11 21	o. c 1 000e-4 iso par	1072e+01 0. omputed coef c3 05 0.0000e++ **available up tropic allel	14300+01 0. ficients fro x1 00 0.11300+1 composite de 1d 1 re 2 re 3 re 11 re 12 re 13 re 14 re 15 re 21 re 22 re 23 re	2090e-01 0. cm specs arra x2 HO1 0.1701e+ afinitions*** asx asx asy asx, resy,resz asx, x-y plan asy, x-y plan asy, y-z plan asz, y-z plan asz asy asy asz asy asy asy asy asy asy asy asy	1150e+00 0.00 y z1 01 0.3455e+00 e e e	22 20009+00 0.000 0.95919−01	23 0,5586+00
161 162 163 164 165 166 167 168 169 170 171 172 173 174 175 176 177 178 179 180 181 182			47 mt 47	3 0.9484e+00 c0 c 0.5200e-03 0.32 01 11 21 31	o. c 1 000e iso par	lo72e+01 0. omputed coef c3 05 0.0000e++ **available up tropic allel les l assembly	14300+01 0. ficients fro x1 00 0.11300+1 composite de 1d 1 re 3 re 4 re 11 re 13 re 14 re 15 re 21 re 22 re 23 re 31 re	2090e-01 0. cm specs arra x2 HO1 0.1701e+ afinitions*** asx asx asx, resy,resz asx, x-y plan asy, x-y plan asy, y-z plan asz, y-z plan asz, y-z plan asz asy asz asx asy asz asy asz asy asz asy asz asy asz asy asz asy asz asy asz asy asz asy asz asy asz asy asy asy asy asy asy asy asy	11500+00 0.00 y z1 01 0.34550+00 e e e e e for rod array	22 2000 − 0000 0.95910 − 01	z3 0,5586+00

**B.**4

184											4	2 resty	/							
185						_					4.	o restz	۲. ۲.							
186							ext	erior	conve	ctio	on 5	l restz	tor t	op of	cask					
187							and	radia	tion		52	2 restz	tor b	ottom	of cas	sk				
188																				
189	ргор	nreg= 2	24	npal	r=	24 m	aximui	n curr	ent d	limer	ns i ons	for nr	eg and	npal	r are	25	30			
190	prop	index		c	elli	ocatic	n.													
191		F1	bøg	lend	jbeg	jend	kbeg	kend	npa	ir.	id	mt	id	mt	id	mt	id	mt	id	mt
192			1	1	2	11	2	29		1	1	1								
193			2	11	12	12	2	29		1	2	1								
194			2	11	2	11	5	26		1	4	3								
195			2	7	6	6	5	22		1	4	4								
196			7	7	7	11	5	22		1	4	4								
197			2	5	6	6	5	8		1	4	3								
198			7	7	8	11	5	8		1	4	3								
199			2	6	7	11	5	22		1	31	47								
200			2	11	2	11	2	4		1	4	5								
201			2	11	2	11	27	29		1	4	5								
202			2	11	2	11	1	1		1	3	1								
203			2	11	2	11	29	29		1	51	40								
204			2	2	1	1	2	4		1	42	41								
205			2	2	1	1	5	26		1	42	42								
206			2	2	1	1	27	29		1	42	41								
207			3	3	1	1	2	4		1	42	43								
208			3	3	1	t	5	26		1	42	44								
209			3	3	1	1	27	29		1	42	43								
210		1	11	11	10	10	2	4		1	41	43								
211			11	11	10	10	5	26		1	41	46								
212			11	11	10	10	27	29		1	41	43								
213			11	11	11	11	2	4		1	41	41								
214			11	11	11	11	5	26		1	41	45								
215			11	11	11	11	27	29		1	41	41								
216																				
217	therm	theta=0.	5	sohtf	=0.52	34e+01	dt	emax≖0	, 500e	+00										
218	therm	rebon=0.	0	nreb=	100	nrebr	= 50		•	-										
219																				
220	therm	monitor	cells	s= 8	max	imum r	umber	airre	ontiv	alle	wed I	s 12								
221						•			n 1	1	k									
222								1	2	2	10									
223								2	2 3	4	10									
224								7	5 5	6	10									
225								4	5	7	10									
226									5 11	11	10									
227								Ē	5 9	10	10									
228								7	7	8	10									
220								، ع	, , ,	Ř	10									
/									- 0		. •									

(

B.5

<b>070</b>								
230	thorn			_				
232	1 nerm		q weighting	,	Cell	IOCATI	on	
233					beg lend	i jbeg 7	Jena	•
234			0.50000+00		2 2	11	11	
235			0.1000+00		J U Z S	7	10	
236					5 5 2 2	,,	10	
237			0.0000+00		2 2	11	•	
238			0.00000+00		5 5	10	10	
230			0.0000.00		, ,	10	10	
240	therm				no i i	Incoti	~~	
240			group	11	Cell bog lond	IOCATI	lon d	
242			0 2000-+03	•	2 6	i jbeg 7	Jena 11	
243			0.29008.09		2 0	'	• •	
242	thorm	4	rolact(k)					
245		2						
246		2	0.0000-+00					
240		ر ۸	0.00000+00					
248			0.2050-+02					
240		5	0.4450-+02					
250		7	0.5700-402					
251		/ Q	0.6500-402					
252		0	0.7100-+02					
253		9 10	0.7500-+02					
254		10	0.79000102					
255		11	0.9000-+02					
255		12						
257		13						
259		14						
250		15						
259		10						
261		17	0.7050.102					
201		10						
202		19	0.69000+02					
205		20	0.3000-102					
204		21	0.3450.102					
209		22	0.24300+02					
200		23						
207		24						
200		20	0.00000+00					
209 270		26	0.00000+00					
270		21						
271		28						
414 272		29	0.00000+00					
213					-			
214			total	generated	power=0	• 1 1600	Ue+04,	watts
2/2								

.

	276									
	277	therm	pqgen=0,	0						
	278		1.0							
	279	therm	newt=1	cen.j=11.5	k	tcen(k)				
	280			•	2	0,321e+03				
	281				3	0.323e+03				
	282				4	0.325e+03				
	283				5	0.356e+03				
	284				6	0.398e+03				
	285				7	0.433e+03				
	286				8	0.456e+03				
	287				9	0.473e+03				
	288				10	0.484e+03				
	289				11	0.492+03				
	290				12	0.498e+03				
	291				13	0.498e+03				
	292				14	0.498e+03				
	293				15	0.498e+03				
	294				16	0.498e+03				
	295				17	0.498+03				
	296				18	0.494+03				
	297				19	0-467e+03				
	298				20	0.428+03				
	299				21	0.383e+03				
B	300				22	0.342+03				
.7	301				23	0 337+03				
	302				24	0 332+03				
	303				25	0 328+03				
	304				25	0.3240+03				
	305				20	0 320-103				
	305				29	0.315.403				
	307				20					
	309				29	0.0108400				
	300	**		1-40		* * *		1	Tem	444
	309	Therm	new tc=I	ULLO-			1011101	Infertace	i emp., ,	oeg.
	310	<b></b>		<b>`</b>						
	211	Therm		) 1	••	0 1				
	512	Therm	Ibeg= 2	iend= o	Jbeg=	2 jend=15				
	515				ĸ	001TA(K)				
	514				2	0.0000+00				
	315				د	0.000e+00				
	316				4	0.000e+00				
	317				5	U_000e+00				
	318				6	0,000e+00				
	319				7	0.000e+00				
	320				8	0.000e+00				
	321				9	0,000e+00				

(

к * * *

322		10 0 ₀ 000e+00
323		11 0,000e+00
324		12 0,000+00
325		13 9-9999+199
326		14 9-9999=199
327		15 0-000+00
328		
329		
330		
331		
332		20 0,000e+00
333		
334		22 0.000e+00
335		23 0-000 <del>0+0</del> 0
336		24 0,000e+00
337		25 0-000e+00
338		26 0.000e+00
339		27 0,000e+00
340		28 0.000e+00
341		29 0_000e+00
342		
343	rebt	xdtime=0,100e+06
344		
345	props	nsx≖ 0 nsfx≈ 0 nsy≖ 0 nsfy≡ 0 nsz≖ 0 nsfz= 0 info=0
346		$\gamma$ .
347	props	toph=1,0 topl=0,261e+02 topv=0,000e+00 topc=0,140e+00 topn=0,333e+00
348	props	both=0,0
349	props	sideh=1.0
350		
351	props	nmat= 6 maximum current dimension for nmat is 20
352	props	ccon0,ccon1,ccon3 material thermal conductivity, w/cm-k
353		k(mat) = ccon0(mat) + ccon1(mat) + ccon3(mat) + + + + + + + + + + + + + + + + + + +
354		1 (0.1000e-20)+(0.0000e+00)*t+(0.0000e+00)*t*t*t low conductivity
355		2
356		3 (0.5200e-03)+(0.3200e-05)*t+(0.0000e+00)*t*t*t hellum ( backfill gas )
357		4 (0.9215e-01)+(0.1465e-03)*t+(0.0000e+00)*t*t*t stainless steel
358		5
359		6
360		
361		maximum number of material types is currently 30
362		maximum array dimension of specs is currently 100
363		
364		***composite definition 01 isotropic and 11 parallel***
365	props	mtmax= 5
366	props	specs mt mats mat width
367		1 1 1 0,1000e+01

B.8

368		2 1	2 0,1000e+01
369		3 1	3 0,1000e+01
370		4 1	4 0,1000e+01
371		5 1	5 0,1000e+01
372			
373		computed coefficier	its from specs array
374		mt c0	c1 c3
375		1 0,1000 <del>0</del> -20 0,0	000e+00 0,0000e+00
376		2 0.1000e+20 0.0	000e+00 0.0000e+00
377		3 0,5200 <del>0</del> -03 0,3	200e-05 0.0000e+00
378		4 0,9215e-01 0,1	465e-03 0.0000e+00
379		5 0,5162e+00 -0,3	205e-03 0.0000e+00
380			
381		***composite defin	nition 21 series***
382	props mtmax= 2		
383	props specs	mt met width ei	e2 twf
384		41 1 0 <b>.</b> 1000 <del>o</del> +01 0.200	00e+00 0.1000e+01 0.5000e+00
385		42 3 0 <b>.</b> 1000 <del>0</del> +00 0 <b>.</b> 400	00e+00 0.4000e+00 0.5000e+00
386			
387		computed coefficier	its from specs array
388		mt c0	cl c3
389		41 0.1000 <del>0</del> -20 0.0	000e+00 0,4536e-11
390		42 0.5200e-02 0.3	200e-04 0,5670e-11
391			
392		***available compos	ite definitions***
393		group	Id
394		01 Isotropic	1 resx
395			2 resy
396			3 resz
397		••	4 resx,resy,resz
398		11 parallel	11 resx, x-y plane
399			12 resx, x-z plane
400			13 resy, x-y plane
401			14 resy, y-z plane
402			15 resz, x-z plane
405			l6 resz, y-z plane
404		21 series	21 resx
405			22 resy
405			23 resz
407		41 film resistance	41 resfx
408			42 resfy
409			43 resf2
410		51 exterior convection	51 resfz for top of cask
411		and radiation	52 restz for bottom of cask
412			53 resfx for side of cask
413			

B.9
414	props	nreg=	9	npa i	r=	9	maximum	n cur	rent	din	nens	lons	for nre	eg and	i npai	r are	2	5	40			
415	props	i ndex		c	ell 10	cati	on															
416			l beg	i end	jbeg	jen	t kbeg	kend	n	palı	÷.	Īđ	mt	id	mt	id	A	t	ld	mt	١d	mt
417			2	6	2	13	2	29		1		4	5									
418			1	1	2	13	2	29		1		1	1									
419			2	6	1	1	2	29		1		2	1									
420			2	6	14	- 14	2	29		1		2	1									
421			6	6	2	13	2	29		1		53	41									
422			2	6	2	13	1	1		1		3	1									
423			2	6	2	13	29	29		1		51	41									
424			3	3	2	13	27	28		1		41	42									
425			3	3	2	13	3	4		1		41	42									
426																						
427	tside	newts=1	+	samb=0	.300e1	-03	dtema>	(=0.5	00e+	01												
428					-			-														
429	tside	monitor	· cel	ls≖ 4	maxi	mum	number	arr	entl	y al	low	ed is	4									
430								1	m	i .	l k											
431									1	2	5 10											
432								:	2	2 10	) 10											
433									3	4 5	5 10											
434									4	4 10	) 10											
435																						
436	tside	ndelta=	•0			k	delta	(k)														
437						2	0.000ef	100														
438						3	0.000ef	ю0														
439						4	0.000e+	Ю0														
440						5	0,000ef	Ю0														
441						6	0.000ef	ю0														
442						7	0.000e1	ю0														
443						8	0.000e1	Ю0														
444						9	0.000e	Ю0														
445					1	0	0.000et	Ю0														
446					1	1	0.000e	Ю0														
447					1	2	0.000e1	Ю0														
448					1	3	0.000e	Ю0														
449					1	4	0,000et	юо														
450					1	5	0.000et	Ю0														
451					1	6	0.000e1	ю0														
452					1	7	0.000e1	юо														
453					1	8	0.000et	ю0														
454					1	9	0.000e	юо														
455					2	0	0.000e	юо														
456					2	21	0,000e-	юо														
457					2	2	0.000e1	юо														
458					2	23	0.000e	ю0														
459					2	.4	0.000et	ю0														

460       25       0.000e+00         461       26       0.000e+00         462       .27       0.000e+00         463       28       0.000e+00         464       29       0.000e+00         465       .29       0.000e+00         466       radc       info=0         467	
461       26 0.000e+00         462       27 0.000e+00         463       28 0.000e+00         464       29 0.000e+00         465       29 0.000e+00         465       465         466       radc         1 nregs= 2       maximum current dimension for nregs is 2         469       radc         1 ndex       region	
462       .27       0.000e+00         463       .28       0.000e+00         464       .29       0.000e+00         465	
463       28 0,000e+00         464       29 0,000e+00         465         466         466         radc       info=0         467         468       radc       nregs≃ 2         469       radc       index         region       number of       i-cell         j-cell       h	
464 29 0,000e+00 465 466 radc info=0 467 468 radc nregs≅ 2 maximum current dimension for nregs is 2 469 radc index region number of k-cell number of i-cell j-cell h	
465 466 radc info=0 467 468 radc nregs≃ 2 maximum current dimension for nregs is 2 469 radc index region number of k-cell number of i-cell j-cell h	
466 radc info=0 467 468 radc nregs≃ 2 maximum current dimension for nregs is 2 469 radc index region number of k-cell number of i-cell j-cell h	
467 468 radc nregs≃ 2 maximum current dimension for nregs is 2 469 radc index region number of k-cell number of i—cell j-cell h	
468 rade nregs≃ 2 maximum current dimension for nregs is 2 469 rade index region number of k-cell number of i-cell j-cell h	
409 radic index region number of K-cell number of I-cell J-cell n	
470 sumbor k solis identičios sustanas identičios identičios identičios	
470 AUMDOR K COUS IGONTITION SUFTACOS IGONTITION IGONTITION A71 1 19 1 12 1 1 1 1	
472 2 18 1 12 2 2 1	
473	
474 radc kcell idk k-cells:	
475 1 18 : 5 6 7 8 9 10 11 12 13 14 15 16 17 18 19 20 21 22	
476	
477 rado iceli idi i-celis:	
478 1 12 : 2 3 4 5 6 7 7 6 5 4 3 2	
460 481 rado icellidi izcello:	
483 2 12 : 11 10 9 8 7 6 6 7 8 9 10 11	
484	
485 rado h	
486	
487 * * * idh= 1 nsurfs=12 * * *	
489 i -0,1951506-11 0,1781426-12 0,1407706-12 0,1092226-12 0,7400656-15 0,5555646-15 0,5025556-15 0,1205146-12 0,1941696 400 0 309646-12 0 437751-12 0 279976-12	e-12
490 0,000406-12 0,4077016-12 0,2700706-12 491 2 0 178142a-12 -0 371336a-11 0 206204a-12 0 230300a-12 0 157580a-12 0 604281a-13 0 105601a-12 0 268806a-12 0 4502154	-12
492 0.692739a=12 0.816805a=12 0.438345a=12	0-12
493 3 0,146770e-12 0,296294e-12 -0,376077e-11 0,261244e-12 0,190849e-12 0,796388e-13 0,126316e-12 0,391306e-12 0,6831986	ie-12
494 0,730242e-12 0,595651e-12 0,259266e-12	• · -
495 4 0,109222e-12 0,230309e-12 0,261244e-12 -0,376500e-11 0,262038e-12 0,109288e-12 0,195813e-12 0,762266e-12 0,806213e	<del>∕o</del> ~12
496 0,508481e-12 0,365323e-12 0,154802e-12	
497 5 0,740063e-13 0,157589e-12 0,190849e-12 0,262038e-12-0,371382e-11 0,226210e-12 0,608779e-12 0,111310e-11 0,470036e	<del>.e-</del> 12
498 0,280376e-12 0,229700e-12 0,101134e-12	
499 0 U.JJJJ048-15 U.694281e-15 U.795388e-15 U.109288e-12 U.226210e-12 -0.248679e-11 U.120677e-11 0.323896e-12 U.153454e	<del>e</del> -12
200 0,1212018-12 0,124248-12 0,2090128-12 501 7 0 502533-13 0 105601-12 0 126316-12 0 105813-12 0 609770-12 0 120677-11-0 320064-11 0 335137-12 0 201461-	0-12
502 0.161598a=12 0.147873a=12 0.699501a=13	0-12
503 8 0,120314e-12 0,268806e-12 0,391306e-12 0,762266e-12 0,111310e-11 0,323896e-12 0,335137e-12-0,433825e-11 0,3667216	e-12
504 0,287270e-12 0,251474e-12 0,117960e-12	. =
505 9 0,194169e-12 0,459215e-12 0,683198e-12 0,806213e-12 0,470036e-12 0,153454e-12 0,201461e-12 0,366721e-12 -0,4086696	

(

B.11

506		0.320	529-12	0.2	291875-12	0,139820	-12										
507	10	0.308	6460-12	0.6	592739e-12	0.7302428	-12 0.50	8481e-1	2	0.2803	576e-12	2 0.	121361	e-12	0,161598e-12	0.287270e-12	0.3205298-12
508		-0.3890	094-11	0.3	321644e-12	0.158051e	-12		-					• • •	••••••••		
500	11	0.437	751-12	0.8	316805-12	0.595651e	-12 0.36	5323e-1	2	0.2297	/00e=12	2 0.	112434	le-12	0.147873e-12	0-2514740-12	0.291875-12
510	••	0 3216	644o-12	-0.1	373774-11	0.167214	-12		-					••••	••••••••••••••		
511	12	0 278	8760-12	0.4	1383450-12	0.259266	-12 0.15	48020-1	2	0. 1011	340-12	2 0.	509613	ie-13	0.699501e-13	0.117960-12	0,139820-12
512	12	0 1580	051-12	0 1	67214-12	-0 1936380-	-11		-	•••••							0, 0, 0, 0, 0, 0, 0, 0, 0, 0, 0, 0, 0, 0
513		0.1300	0710-12	0.1	0/2148-12	-0.1750508-											
514		rado	i reas a	2	maximum c	urrent dimer	neion for	Ireas	le	2							
515		rado	11 <del>0</del> 95 -	-	region	emiti	ances	n ogs			ol In	catl	00				
516					region	Garri	ancos	1	bea	lend	ihea	iend	kbea	kend			
517					1	0.400	0.250	•	7	8	500g	6	5	8			
518					2	0.400	0.250		7	9	7	7	5	8			
519					-				•	•	•	•	-	•			
520		rado	ireas =	2	maximum c	urrent dimer	nsion for	ireas	is	2							
521		cado	Ji 095-	-	realon	emiti	tances	J. 095		- 0	ell lo	cati	on				
522		i u up			, ogi on	Gillitti	anoos	i	hea	lend	ibea	lend	kbea	kend			
523					1	0,250	0.400	•	6	6	4	6	5	8			
524					. 2	0.250	0.400		7	7	5	6	5	8			
525					~				•	•	-	•	-	-			
526		rado	kreas =	5	maximum c	urrent dimer	sion for	kreas	is	5							
527		rado	090	-	region	emit1	tances	ege		- c	elf lo	cati	on				
528		1 a op			. egi en	•		I	bea	lend	ibea	lend	kbea	ı kend			
529					1	0,400	0.250		2	7	6	6	22	27			
530					2	0.400	0.250		7	7	7	11	22	27			
531					3	0.800	0.250		2	6	7	11	22	27			
532					4	0.250	0.400		2	5	6	6	4	9			
533					5	0.250	0.400		7	7	8	11	4	9			
534						• • • •											
535		radr	RADR In	nout	Section												
536		radr	Rod Emi	ittan	ce is 0.8												
537																	
538		radr	nh= 25	me	ximum curr	ent dimensio	on for nh	is 25									
539		radr	h														
540				nh	h2e(nh)	h2n(nh)	h2w(nh)	h2s	(nh	) H	n3ne(nt	1)	h3nw (n	h)	h3sw(nh) h3	se(nh)	
541				1 0	, 1710e+00	0.00000+00 (	0.0000e+0	0 0.171	0e+	00 0.0	)000e+0	0 0.	0000e+	-00 0.	0000e+00 0 _• 20	80e+00	
542				2 (	0 <b>.1710⊕+</b> 00	0.0000e+00 (	0 <b>.1710e+0</b>	0 0,388	0e+	00 0.0	)000e+(	0 0.	0000e+	юо о.	2080e+00 0.20	00+e08	
543				3 (	, 3880e+00	0.1710+00 (	0,000e+0	0 0.171	0e+	00 0.2	2080e+0	0 0.	0000e+	HOO 0.	0000+00 0.20	80 <del>a+</del> 00	
544				4 (	) <b>.</b> 1710e+00	0.0000+00 (	0.1710e+0	0 0.342	0e+	00 0.0	) <del>1e000</del> (	0 0.	0000e+	юо о.	2080e+00 0,20	80e+00	
545				5 (	,3420e+00	0.1710e+00 (	).0000e+0	0 0.171	0e+	00 0.2	2080e+0	0 0.	0000 <del>a</del> +	HOO 0.	0000 <del>0</del> +00 0.20	80e+00	
546				6 (	),1710e+00	0.0000e+00 0	0 <b>.1710e+</b> 0	0 0.342	0e+	00 0.0	) <del>1000e+</del> (	0 0.	0000 <del>o</del> 1	юо о.	2080e+00 0.20	80e+00	
547				7 (	)•3420e+00	0.1710e+00 (	0.000 <del>0</del> +0	0 0.171	0e+	00 0.2	2080 <del>9</del> +0	0 0.	0000 <del>e</del> +	HOO 0.	0000e+00 0.20	80e+00	
548				8 (	0000e+00	0.0000e+00 (	0 <b>.1710e+0</b>	0 0.342	0e+	00 0.0	)+e000(	0 0.	0000 <del>e</del> 1	юо о.	2080e+00 0.00	00 <del>e</del> +00	
549				9 (	<b>3420e+00</b>	0.17100+00 (	0.000e+0	0 0.000	0e+	00 0.2	2080 <del>e+</del> 0	0 0.	0000e+	HOO 0.	0000e+00 0.00	00 <del>o</del> +00	
550				10 (	0 <b>,</b> 3880 <del>o+</del> 00	0.3880.000	0 <b>.</b> 3880e+0	0 0,388	0e+	00 0.2	2080 <del>o</del> +(	0 0.	2080 <del>e</del> 1	юо о.	2080e+00 0.20	80 <del>a</del> +00	
551				11 0	),3880e+00	0.34200+00 (	0 <b>.</b> 3880e+0	0 0.342	0e+	00 0.2	2080e+0	0 0.	2080 <del>o</del> 1	юо о.	2080e+00 0,20	80e+00	

552	12	0.34200+00	0.3880e+00	0.3420e+00	0.3880e+00	0.2080e+00	0.2080e+00	0.2080e+00	0.2080e+00
553	13	0.3880.+00	0.34200+00	0.3880e+00	0.3420e+00	0.2080e+00	0.2080e+00	0.2080e+00	0,2080e+00
554	14	0.3420e+00	0.3880e+00	0.3420+00	0.3880e+00	0.2080e+00	0.2080e+00	0,2080e+00	0,2080+00
555	15	0.0000e+00	0.3420e+00	0.3880e+00	0.3420e+00	0.0000e+00	0.2080+00	0.2080e+00	0,0000e+00
556	16	0.3420e+00	0.3880e+00	0.34200+00	0,000e+00	0.2080e+00	0.2080e+00	0.000e+00	0,0000e+00
557	17	0.3420e+00	0.3420e+00	0.3420e+00	0.3420e+00	0.2080e+00	0.2080e+00	0.2080e+00	0.2080e+00
558	18	0,3420e+00	0.34200+00	0.34200+00	0.3420e+00	0.2080e+00	0.2080e+00	0.2080e+00	0.2080e+00
559	19	0.34200+00	0.3420e+00	0.3420e+00	0.3420e+00	0.2080.+00	0.2080e+00	0.20800+00	0.2080e+00
560	20	0.3420e+00	0,3420+00	0.3420e+00	0.34200+00	0.2080.+00	0.2080e+00	0.2080e+00	0 <b>.</b> 2080e+00
561	21	0.0000+00	0.3420e+00	0.3420e+00	0.3420e+00	0.00000+00	0.2080e+00	0.2080e+00	0.0000e+00
562	22	0,3420e+00	0,3420e+00	0.34200+00	0,0000+00	0.2080.+00	0.2080e+00	0.0000e+00	0.0000+000
563	23	0.0000e+00	0,3420e+00	0.3420e+00	0,34200+00	0.0000e+00	0.2080e+00	0.20809+00	0.0000e+00
564	24	0.3420e+00	0,3420e+00	0,3420+00	0,0000+00	0,2080+00	0.2080e+00	0.0000e+00	0.0000e+00
565	25	0.0000e+00	0,3420e+00	0.3420e+00	0.0000e+00	0.0000+00	0.2080.+00	0.0000e+00	0.0000e+00
566									
567	nh	h4e(nh)	h4n(nh)	h4w(nh)	h4s(nh)				
568	1	0.5000e-02	0.0000e+00	0.0000e+00	0,5000e-02				
569	2	0.5000e-02	0,0000e+00	0.0000e+00	0,1000e-01				
570	3	0.1000e-01	0.0000+00	0.0000e+00	0,5000e-02				
571	4	0.5000e-02	0.000e+00	0.5000e-02	0.1000e-01			•	
572	5	0.1000e-01	0.5000e-02	0.0000e+00	0.5000e-02				
573	6	0.0000e+00	0.000e+00	0.5000e-02	0,1000-01				
574	7	0,1000e-01	0.5000e-02	0.000e+00	0.0000e+00				
575	8	0.0000e+00	0.0000+00	0.50000-02	0.1000e-01				
576	9	0.1000e-01	0.5000e-02	0.0000+00	0,0000+00				
577	10	0.1000e-01	0.000e+00	0.0000+00	0.1000e-01				
578	11	0.1000e-01	0.0000e+00	0,1000e-01	0.1000e-01				
579	12	0.1000e-01	0.1000e-01	0.0000+00	0.10000-01				
580	13	0.0000+00	0.0000e+00	0.1000e-01	0.1000e-01				
581	14	0.1000e-01	0.1000e-01	0.0000e+00	0.000e+00				
582	15	0.0000e+00	0,0000e+00	0.1000e-01	0.1000e-01				
583	16	0.1000e-01	0.1000e-01	0.0000e+00	0.000e+00				
584	17	0.1000e-01	0.1000e-01	0.1000e-01	0.1000e-01				
585	18	0.0000e+00	0.1000e-01	0.1000e-01	0.1000e-01				
586	19	0.1000e-01	0.1000e-01	0.1000e-01	0,0000e+00				
587	20	0.00000+00	0.1000-01	0.1000e-01	0.0000e+00				
588	21	0.0000+00	0.1000-01	0.1000e-01	0.1000e-01				
589	22	0.1000-01	0,1000-01	0.1000e-01	0.0000e+00				
590	23	0.0000e+00	0.1000-01	0.1000e-01	0.0000e+00				
591	24	0.0000+00	0.1000e-01	0.1000e-01	0.0000+00				
592	25	0.0000e+00	0,1000a-01	0.1000-01	0,0000+00				
593				/ ·					
594	nh	h5ene(nh)	h5nne(nh)	h5nnw (nh)	h5wnw (nh)	h5wsw (nh )	h5ssw(nh)	h5sse(nh)	h5ese(nh)
595	1	0.0000e+00	0.0000e+00	0.0000e+00	0,0000e+00	0.0000e+00	0.0000+00	0.4600e-01	0.4600e-01
596	2	0.0000e+00	0,0000+00	0.0000e+00	0.0000+00	0.0000+00	0.4600-01	0.4600e-01	0.4600e-01
597	3	0.4600e-01	0.0000e+00	0.0000+00	0.000e+00	0,000a+00	0.0000e+00	0.46000-01	0.4600e-01
									-

ſ

598	4	0.0000+00	0.0000e+00	0.0000+00	0.000e+00	0.4600e-01	0.4600e-01	0.46000-01	0.4600e-01
599	5	0.4600e-01	0.4600e-01	0.0000+00	0.0000e+00	0.0000+00	0.0000+00	0,4600-01	0.46000-01
600	6	0.000e+00	0.0000e+00	0.0000e+00	0.0000+00	0.4600e-01	0.4600e-01	0.4600-01	0.000e+00
601	7	0.4600e-01	0.4600e-01	0.0000e+00	0.0000e+00	0.0000+00	0.000e+00	0.000e+00	0.4600e-01
602	8	0.0000+00	0.000e+00	0.0000+00	0.0000+00	0.4600e-01	0.46000-01	0.0000e+00	0,0000e+00
603	9	0.4600e-01	0.4600e-01	0.000e+00	0,0000+00	0.0000e+00	0,0000e+00	0.0000+00	0.0000e+00
604	10	0.4600e-01	0.0000e+00	0.0000+00	0.0000+00	0.0000e+00	0.4600e-01	0.4600e-01	0.4600-01
605	11	0.4600e-01	0.0000e+00	0,0000e+00	0.4600e-01	0.4600e-01	0.4600-01	0.4600e-01	0.4600e-01
606	12	0.4600-01	0.4600e-01	0.4600e-01	0,0000+00	0.0000+00	0.4600e-01	0.4600e-01	0.4600-01
607	13	0.0000e+00	0.0000+00	0.0000e+00	0.4600e-01	0.4600e-01	0.4600e-01	0.4600-01	0.0000+00
608	14	0.4600e-01	0.4600e-01	0.4600e-01	0.0000+00	0.0000e+00	0.0000e+00	0,0000e+00	0.4600-01
609	15	0.0000e+00	0.0000+00	0.0000e+00	0.4600e-01	0.4600e~01	0.4600e-01	0.0000e+00	0,0000e+00
610	16	0.46000-01	0.4600e-01	0.4600e-01	0.0000+00	0.0000e+00	0.0000e+00	0.0000+00	0.0000e+00
611	17	0.4600e-01	0.4600e-01	0.4600e-01	0.4600-01	0.4600e-01	0.4600e-01	0.46000-01	0.4600e-01
612	18	0.0000e+00	0.46000-01	0.4600e-01	0.4600e-01	0.4600e-01	0.4600e-01	0.4600e-01	0.0000e+00
613	19	0.4600e-01	0.4600e-01	0.4600e-01	0.4600e-01	0.4600e-01	0.0000+00	0.0000e+00	0.460001
614	20	0.0000e+00	0.4600e-01	0.46000-01	0.4600e-01	0.4600e-01	0.0000e+00	0.0000e+00	0.0000e+00
615	21	0.0000e+00	0.0000+00	0.4600e-01	0.4600e-01	0.4600e-01	0.46000-01	0.0000e+00	0.0000e+00
616	22	0.4600e-01	0.4600e-01	0.4600e-01	0.4600e-01	0.0000e+00	0.0000e+00	0.0000e+00	0.0000e+00
617	23	0.0000e+00	0.0000+00	0.4600e-01	0.4600e-01	0.4600e-01	0,0000+00	0.00000+00	0,0000e+00
618	24	0.0000e+00	0.4600e-01	0.4600e-01	0.4600e-01	0.000e+00	0.0000e+00	0.0000+00	0.0000e+00
619	25	0.0000e+00	0.00000+00	0.4600e-01	0.4600e-01	0.0000+00	0.0000e+00	0.0000e+00	0.0000e+00
620									
621	nh	h6ne(nh)	h6nw (nh)	hósw (nh )	h6se(nh)				
621 622	nh 1	h6ne(nh) 0,0000e+00	hбnw (nh) 0.000ө+00	h6sw (nh ) 0.0000e+00	h6se(nh) 0.0000e+00				
621 622 623	nh 1 2	h6ne(nh) 0.0000e+00 0.0000e+00	h6nw (nh) 0.0000e+00 0.0000e+00	h6sw (nh) 0.0000e+00 0.0000e+00	h6se(nh) 0.0000e+00 0.0000e+00				
621 622 623 624	nh 1 2 3	h6ne(nh) 0.0000e+00 0.0000e+00 0.0000e+00	h6nw (nh) 0.0000e+00 0.0000e+00 0.0000e+00	h6sw(nh) 0.0000e+00 0.0000e+00 0.0000e+00	h6se(nh) 0.0000e+00 0.0000e+00 0.0000e+00				
621 622 623 624 625	nh 1 2 3 4	h6ne(nh) 0.0000e+00 0.0000e+00 0.0000e+00 0.0000e+00	h6nw (nh) 0.0000e+00 0.0000e+00 0.0000e+00 0.0000e+00	h6sw (nh) 0,0000e+00 0,0000e+00 0,0000e+00 0,0000e+00	h6se(nh) 0.0000e+00 0.0000e+00 0.0000e+00 0.0000e+00				
621 622 623 624 625 626	nh 1 2 3 4 5	h6ne(nh) 0.0000e+00 0.0000e+00 0.0000e+00 0.0000e+00 0.0000e+00	h6nw (nh) 0.0000e+00 0.0000e+00 0.0000e+00 0.0000e+00 0.0000e+00	h6sw (nh) 0.0000e+00 0.0000e+00 0.0000e+00 0.0000e+00 0.0000e+00	h6se(nh) 0.0000e+00 0.0000e+00 0.0000e+00 0.0000e+00 0.0000e+00				
621 622 623 624 625 626 626	nh 1 2 3 4 5 6	h6ne(nh) 0.0000e+00 0.0000e+00 0.0000e+00 0.0000e+00 0.0000e+00 0.0000e+00	h6nw (nh) 0.0000e+00 0.0000e+00 0.0000e+00 0.0000e+00 0.0000e+00 0.0000e+00	h6sw (nh) 0.0000e+00 0.0000e+00 0.0000e+00 0.0000e+00 0.0000e+00 0.0000e+00	h6se(nh) 0.0000e+00 0.0000e+00 0.0000e+00 0.0000e+00 0.0000e+00 0.0000e+00				
621 622 623 624 625 626 627 628	nh 1 2 3 4 5 6 7	h6ne(nh) 0.0000e+00 0.0000e+00 0.0000e+00 0.0000e+00 0.0000e+00 0.0000e+00 0.0000e+00	h6nw (nh) 0.0000e+00 0.0000e+00 0.0000e+00 0.0000e+00 0.0000e+00 0.0000e+00 0.0000e+00	h6sw (nh) 0.0000e+00 0.0000e+00 0.0000e+00 0.0000e+00 0.0000e+00 0.0000e+00 0.0000e+00	h6se(nh) 0.0000e+00 0.0000e+00 0.0000e+00 0.0000e+00 0.0000e+00 0.0000e+00 0.0000e+00				
621 622 623 624 625 626 627 628 629	nh 1 2 3 4 5 6 7 8	h6ne(nh) 0.0000e+00 0.0000e+00 0.0000e+00 0.0000e+00 0.0000e+00 0.0000e+00 0.0000e+00 0.0000e+00	h5nw (nh) 0.0000+00 0.0000+00 0.0000+00 0.0000+00 0.0000+00 0.0000+00 0.0000+00 0.0000+00	h6sw (nh) 0.0000e+00 0.0000e+00 0.0000e+00 0.0000e+00 0.0000e+00 0.0000e+00 0.0000e+00 0.0000e+00	h6se(nh) 0.0000e+00 0.0000e+00 0.0000e+00 0.0000e+00 0.0000e+00 0.0000e+00 0.0000e+00 0.0000e+00				
621 622 623 624 625 626 627 628 629 630	nh 1 2 3 4 5 6 7 8 9	h6ne(nh) 0.0000e+00 0.0000e+00 0.0000e+00 0.0000e+00 0.0000e+00 0.0000e+00 0.0000e+00 0.0000e+00 0.0000e+00	h5nw (nh) 0.0000+00 0.0000+00 0.0000+00 0.0000+00 0.0000+00 0.0000+00 0.0000+00 0.0000+00 0.0000+00	h6sw (nh) 0.0000e+00 0.0000e+00 0.0000e+00 0.0000e+00 0.0000e+00 0.0000e+00 0.0000e+00 0.0000e+00 0.0000e+00	h6se(nh) 0.0000e+00 0.0000e+00 0.0000e+00 0.0000e+00 0.0000e+00 0.0000e+00 0.0000e+00 0.0000e+00 0.0000e+00				
621 622 623 624 625 626 627 628 629 630 631	nh 1 2 3 4 5 6 7 8 9 10	h5ne(nh) 0.0000e+00 0.0000e+00 0.0000e+00 0.0000e+00 0.0000e+00 0.0000e+00 0.0000e+00 0.0000e+00 0.0000e+00 0.0000e+00	h5nw (nh) 0.0000+00 0.0000+00 0.0000+00 0.0000+00 0.0000+00 0.0000+00 0.0000+00 0.0000+00 0.0000+00 0.0000+00	h5sw (nh) 0.0000e+00 0.0000e+00 0.0000e+00 0.0000e+00 0.0000e+00 0.0000e+00 0.0000e+00 0.0000e+00 0.0000e+00 0.0000e+00	h6se(nh) 0.0000e+00 0.0000e+00 0.0000e+00 0.0000e+00 0.0000e+00 0.0000e+00 0.0000e+00 0.0000e+00 0.0000e+00 0.0000e+00				
621 622 623 624 625 626 627 628 629 630 631 632	nh 1 2 3 4 5 6 7 8 9 10 11	h5ne(nh) 0.0000e+00 0.0000e+00 0.0000e+00 0.0000e+00 0.0000e+00 0.0000e+00 0.0000e+00 0.0000e+00 0.0000e+00 0.0000e+00 0.0000e+00	h5nw (nh) 0.0000+00 0.0000+00 0.0000+00 0.0000+00 0.0000+00 0.0000+00 0.0000+00 0.0000+00 0.0000+00 0.0000+00 0.0000+00	h5sw (nh) 0.0000e+00 0.0000e+00 0.0000e+00 0.0000e+00 0.0000e+00 0.0000e+00 0.0000e+00 0.0000e+00 0.0000e+00 0.0000e+00	h6se(nh) 0.0000e+00 0.0000e+00 0.0000e+00 0.0000e+00 0.0000e+00 0.0000e+00 0.0000e+00 0.0000e+00 0.0000e+00 0.0000e+00 0.0000e+00				
621 622 623 624 625 626 627 628 629 630 631 632 633	nh 1 2 3 4 5 6 7 8 9 10 11	h5ne(nh) 0.0000e+00 0.0000e+00 0.0000e+00 0.0000e+00 0.0000e+00 0.0000e+00 0.0000e+00 0.0000e+00 0.0000e+00 0.0000e+00 0.0000e+00	h5nw (nh) 0.0000+00 0.0000+00 0.0000+00 0.0000+00 0.0000+00 0.0000+00 0.0000+00 0.0000+00 0.0000+00 0.0000+00 0.0000+00 0.0000+00	h5sw (nh) 0.0000e+00 0.0000e+00 0.0000e+00 0.0000e+00 0.0000e+00 0.0000e+00 0.0000e+00 0.0000e+00 0.0000e+00 0.0000e+00 0.0000e+00	h6se(nh) 0.0000e+00 0.0000e+00 0.0000e+00 0.0000e+00 0.0000e+00 0.0000e+00 0.0000e+00 0.0000e+00 0.0000e+00 0.0000e+00 0.0000e+00 0.0000e+00				
621 622 623 624 625 626 627 628 629 630 631 632 633 634	nh 1 2 3 4 5 6 7 8 9 10 11 12 13	h6ne(nh) 0.0000e+00 0.0000e+00 0.0000e+00 0.0000e+00 0.0000e+00 0.0000e+00 0.0000e+00 0.0000e+00 0.0000e+00 0.0000e+00 0.0000e+00 0.0000e+00	h5nw (nh) 0.0000+00 0.0000+00 0.0000+00 0.0000+00 0.0000+00 0.0000+00 0.0000+00 0.0000+00 0.0000+00 0.0000+00 0.0000+00 0.0000+00 0.0000+00	h5sw (nh) 0.0000+00 0.0000+00 0.0000+00 0.0000+00 0.0000+00 0.0000+00 0.0000+00 0.0000+00 0.0000+00 0.0000+00 0.0000+00 0.0000+00 0.0000+00	h6se(nh) 0.0000e+00 0.0000e+00 0.0000e+00 0.0000e+00 0.0000e+00 0.0000e+00 0.0000e+00 0.0000e+00 0.0000e+00 0.0000e+00 0.0000e+00 0.0000e+00				
621 622 623 624 625 626 627 628 629 630 631 632 633 634 635	nh 1 2 3 4 5 6 7 8 9 10 11 12 13	h6ne(nh) 0.0000e+00 0.0000e+00 0.0000e+00 0.0000e+00 0.0000e+00 0.0000e+00 0.0000e+00 0.0000e+00 0.0000e+00 0.0000e+00 0.0000e+00 0.0000e+00 0.0000e+00	h5nw (nh) 0.0000+00 0.0000+00 0.0000+00 0.0000+00 0.0000+00 0.0000+00 0.0000+00 0.0000+00 0.0000+00 0.0000+00 0.0000+00 0.0000+00 0.0000+00	h5sw (nh) 0,0000+00 0,0000+00 0,0000+00 0,0000+00 0,0000+00 0,0000+00 0,0000+00 0,0000+00 0,0000+00 0,0000+00 0,0000+00 0,0000+00 0,0000+00	h6se(nh) 0.0000e+00 0.0000e+00 0.0000e+00 0.0000e+00 0.0000e+00 0.0000e+00 0.0000e+00 0.0000e+00 0.0000e+00 0.0000e+00 0.0000e+00 0.0000e+00 0.0000e+00				
621 622 623 624 625 626 627 628 629 630 631 632 633 634 635 636	nh 1 2 3 4 5 6 7 8 9 10 11 12 13 14	h6ne(nh) 0.0000+00 0.0000+00 0.0000+00 0.0000+00 0.0000+00 0.0000+00 0.0000+00 0.0000+00 0.0000+00 0.0000+00 0.0000+00 0.0000+00 0.0000+00 0.0000+00 0.0000+00	h5nw (nh) 0.0000+00 0.0000+00 0.0000+00 0.0000+00 0.0000+00 0.0000+00 0.0000+00 0.0000+00 0.0000+00 0.0000+00 0.0000+00 0.0000+00 0.0000+00 0.0000+00	h5sw (nh) 0,0000+00 0,0000+00 0,0000+00 0,0000+00 0,0000+00 0,0000+00 0,0000+00 0,0000+00 0,0000+00 0,0000+00 0,0000+00 0,0000+00 0,0000+00 0,0000+00	h6se(nh) 0.0000e+00 0.0000e+00 0.0000e+00 0.0000e+00 0.0000e+00 0.0000e+00 0.0000e+00 0.0000e+00 0.0000e+00 0.0000e+00 0.0000e+00 0.0000e+00 0.0000e+00 0.0000e+00				
621 622 623 624 625 626 627 628 629 630 631 632 633 634 635 636 637	nh 1 2 3 4 5 6 7 8 9 10 11 12 13 14 15 16	h6ne(nh) 0.0000+00 0.0000+00 0.0000+00 0.0000+00 0.0000+00 0.0000+00 0.0000+00 0.0000+00 0.0000+00 0.0000+00 0.0000+00 0.0000+00 0.0000+00 0.0000+00 0.0000+00 0.0000+00	h5nw (nh) 0,0000+00 0,0000+00 0,0000+00 0,0000+00 0,0000+00 0,0000+00 0,0000+00 0,0000+00 0,0000+00 0,0000+00 0,0000+00 0,0000+00 0,0000+00 0,0000+00 0,0000+00	h5sw (nh) 0,0000+00 0,0000+00 0,0000+00 0,0000+00 0,0000+00 0,0000+00 0,0000+00 0,0000+00 0,0000+00 0,0000+00 0,0000+00 0,0000+00 0,0000+00 0,0000+00 0,0000+00	h6se(nh) 0.0000e+00 0.0000e+00 0.0000e+00 0.0000e+00 0.0000e+00 0.0000e+00 0.0000e+00 0.0000e+00 0.0000e+00 0.0000e+00 0.0000e+00 0.0000e+00 0.0000e+00 0.0000e+00 0.0000e+00				
621 622 623 624 625 626 627 628 629 630 631 632 633 634 635 636 637 638	nh 1 2 3 4 5 6 7 8 9 10 11 12 13 14 15 16 17	h6ne(nh) 0.0000+00 0.0000+00 0.0000+00 0.0000+00 0.0000+00 0.0000+00 0.0000+00 0.0000+00 0.0000+00 0.0000+00 0.0000+00 0.0000+00 0.0000+00 0.0000+00 0.0000+00 0.0000+00	h5nw (nh) 0,0000+00 0,0000+00 0,0000+00 0,0000+00 0,0000+00 0,0000+00 0,0000+00 0,0000+00 0,0000+00 0,0000+00 0,0000+00 0,0000+00 0,0000+00 0,0000+00 0,0000+00 0,0000+00	h5sw (nh) 0,0000+00 0,0000+00 0,0000+00 0,0000+00 0,0000+00 0,0000+00 0,0000+00 0,0000+00 0,0000+00 0,0000+00 0,0000+00 0,0000+00 0,0000+00 0,0000+00 0,0000+00 0,0000+00	h6se(nh) 0.0000e+00 0.0000e+00 0.0000e+00 0.0000e+00 0.0000e+00 0.0000e+00 0.0000e+00 0.0000e+00 0.0000e+00 0.0000e+00 0.0000e+00 0.0000e+00 0.0000e+00 0.0000e+00 0.0000e+00 0.0000e+00				
621 622 623 624 625 626 627 628 629 630 631 632 633 634 635 636 637 638 639	nh 1 2 3 4 5 6 7 8 9 10 11 12 13 14 15 16 17 18	h6ne(nh) 0.0000+00 0.0000+00 0.0000+00 0.0000+00 0.0000+00 0.0000+00 0.0000+00 0.0000+00 0.0000+00 0.0000+00 0.0000+00 0.0000+00 0.0000+00 0.0000+00 0.0000+00 0.0000+00 0.0000+00	h5nw (nh) 0,0000+00 0,0000+00 0,0000+00 0,0000+00 0,0000+00 0,0000+00 0,0000+00 0,0000+00 0,0000+00 0,0000+00 0,0000+00 0,0000+00 0,0000+00 0,0000+00 0,0000+00 0,0000+00 0,0000+00	h5sw (nh) 0,0000+00 0,0000+00 0,0000+00 0,0000+00 0,0000+00 0,0000+00 0,0000+00 0,0000+00 0,0000+00 0,0000+00 0,0000+00 0,0000+00 0,0000+00 0,0000+00 0,0000+00 0,0000+00 0,0000+00	h6se(nh) 0.0000e+00 0.0000e+00 0.0000e+00 0.0000e+00 0.0000e+00 0.0000e+00 0.0000e+00 0.0000e+00 0.0000e+00 0.0000e+00 0.0000e+00 0.0000e+00 0.0000e+00 0.0000e+00 0.0000e+00 0.0000e+00 0.0000e+00				
621 622 623 624 625 626 627 628 629 630 631 632 633 634 635 636 637 638 639 640	nh 1 2 3 4 5 6 7 8 9 10 11 12 13 14 15 16 17 18 19	h6ne(nh) 0.0000+00 0.0000+00 0.0000+00 0.0000+00 0.0000+00 0.0000+00 0.0000+00 0.0000+00 0.0000+00 0.0000+00 0.0000+00 0.0000+00 0.0000+00 0.0000+00 0.0000+00 0.0000+00 0.0000+00 0.0000+00	h5nw (nh) 0,0000+00 0,0000+00 0,0000+00 0,0000+00 0,0000+00 0,0000+00 0,0000+00 0,0000+00 0,0000+00 0,0000+00 0,0000+00 0,0000+00 0,0000+00 0,0000+00 0,0000+00 0,0000+00 0,0000+00	h5sw (nh) 0,0000+00 0,0000+00 0,0000+00 0,0000+00 0,0000+00 0,0000+00 0,0000+00 0,0000+00 0,0000+00 0,0000+00 0,0000+00 0,0000+00 0,0000+00 0,0000+00 0,0000+00 0,0000+00 0,0000+00	h6se(nh) 0.0000e+00 0.0000e+00 0.0000e+00 0.0000e+00 0.0000e+00 0.0000e+00 0.0000e+00 0.0000e+00 0.0000e+00 0.0000e+00 0.0000e+00 0.0000e+00 0.0000e+00 0.0000e+00 0.0000e+00 0.0000e+00 0.0000e+00 0.0000e+00				
621 622 623 624 625 626 627 628 629 630 631 632 633 634 635 636 637 638 639 640 641	nh 1 2 3 4 5 6 7 8 9 10 11 12 13 14 15 16 17 18 19 20	h6ne(nh) 0.000e+00 0.000e+00 0.000e+00 0.000e+00 0.000e+00 0.000e+00 0.000e+00 0.000e+00 0.000e+00 0.000e+00 0.000e+00 0.000e+00 0.000e+00 0.000e+00 0.000e+00 0.000e+00 0.000e+00 0.000e+00 0.000e+00 0.000e+00 0.000e+00	h5nw (nh) 0,0000+00 0,0000+00 0,0000+00 0,0000+00 0,0000+00 0,0000+00 0,0000+00 0,0000+00 0,0000+00 0,0000+00 0,0000+00 0,0000+00 0,0000+00 0,0000+00 0,0000+00 0,0000+00 0,0000+00 0,0000+00	h5sw (nh) 0,0000+00 0,0000+00 0,0000+00 0,0000+00 0,0000+00 0,0000+00 0,0000+00 0,0000+00 0,0000+00 0,0000+00 0,0000+00 0,0000+00 0,0000+00 0,0000+00 0,0000+00 0,0000+00 0,0000+00 0,0000+00	h6se(nh) 0.0000e+00 0.0000e+00 0.0000e+00 0.0000e+00 0.0000e+00 0.0000e+00 0.0000e+00 0.0000e+00 0.0000e+00 0.0000e+00 0.0000e+00 0.0000e+00 0.0000e+00 0.0000e+00 0.0000e+00 0.0000e+00 0.0000e+00 0.0000e+00 0.0000e+00 0.0000e+00 0.0000e+00				
621 622 623 624 625 626 627 628 629 630 631 632 633 634 635 636 637 638 639 640 641 642	nh 1 2 3 4 5 6 7 8 9 10 11 12 13 14 15 16 17 18 19 20 21	h6ne(nh) 0.000e+00 0.000e+00 0.000e+00 0.000e+00 0.000e+00 0.000e+00 0.000e+00 0.000e+00 0.000e+00 0.000e+00 0.000e+00 0.000e+00 0.000e+00 0.000e+00 0.000e+00 0.000e+00 0.000e+00 0.000e+00 0.000e+00 0.000e+00 0.000e+00 0.000e+00	h5nw (nh) 0,0000+00 0,0000+00 0,0000+00 0,0000+00 0,0000+00 0,0000+00 0,0000+00 0,0000+00 0,0000+00 0,0000+00 0,0000+00 0,0000+00 0,0000+00 0,0000+00 0,0000+00 0,0000+00 0,0000+00 0,0000+00 0,0000+00	h5sw (nh) 0,0000+00 0,0000+00 0,0000+00 0,0000+00 0,0000+00 0,0000+00 0,0000+00 0,0000+00 0,0000+00 0,0000+00 0,0000+00 0,0000+00 0,0000+00 0,0000+00 0,0000+00 0,0000+00 0,0000+00 0,0000+00 0,0000+00	h6se(nh) 0.0000e+00 0.0000e+00 0.0000e+00 0.0000e+00 0.0000e+00 0.0000e+00 0.0000e+00 0.0000e+00 0.0000e+00 0.0000e+00 0.0000e+00 0.0000e+00 0.0000e+00 0.0000e+00 0.0000e+00 0.0000e+00 0.0000e+00 0.0000e+00 0.0000e+00 0.0000e+00 0.0000e+00				

		_								
644		2	3 0,000e+00	0.00000+00 0.000	00e+00 0	0000	e+00			
645		2	4 0.0000e+00	0.0000e+00 0.000	)0e+00 0	,0000	e+00			
646		2	5 0.0000e+00	0.000e+00 0.000	00 <del>0+0</del> 00	.0000	e+00			
647										
648	radr	nr <del>o</del> g≃ 25	maximum cu	irrent dimension	for nre	sg is	25			
649	radr	lreg	region	radiation		c	ell ic	catio	n	
650			number	type (nh)	i beg	iend	jbeg	jend	kbeg	kend
651			1	1	2	2	11	11	5	22
652			2	2	3	3	11	11	5	22
653			3	3	2	2	10	10	5	22
654			4	4	4	4	11	11	5	22
655			5	5	2	2	9	9	5	22
656			6	6	5	5	11	11	5	22
657			7	7	2	2	8	8	5	22
658			8	8	6	6	11	11	5	22
659			9	9	2	2	7	7	5	22
660			10	10	3	3	10	10	5	22
661			11	11	4	4	10	10	5	22
662			12	12	3	3	9	9	5	22
663			13	13	5	5	10	10	5	22
664			14	14	3	3	8	8	5	22
665			15	15	6	6	10	10	5	22
666			16	16	ž	ž	7	7	5	22
667			17	17	Å	Ă	à	ó	5	22
668			18	18	5	5	ó	á	5	22
669			10	10	Á	Â	Â	é	5	22
670			20	20		-7 5	a a	6	5	22
671			20	20	5	5	0	0	5	22
672			21	21			7	ע ר	י ב	22
672			22	22	4	4	<i>'</i>		5	22
675			23	25	0		0	0 7		22
674			24	24	2	2	-	<u> </u>	2	22
675			25	20	0	D		'	2	22
0/0										
677	radr	nT4= 1	maximum cur	rent dimension 1	tor nt4	IS	1			
678	radr	174		region		c	ell lo	catio	n	
679				number	Ibeg	lend	jbeg	jend	kbeg	kend
680				1	2	6	7	11	5	22
681										
682	reba	dtmax=0.	200e+02 inf	·o=1						
683										
684	hydro	convek =1	.0 epscon=0	) <b>.</b> 000e+00 mitma	ax= 0	theta	m≈0.5	wm=	1.0	estpf=~,500e+00
685	hydro	ndtyme=1	dtymen=0.1	100e-03 dtymax	=0 <b>,</b> 100e+	Ю0				
686	hydro	newgas=0	newvel≕0	extrav=0.100e+	51					
687	hydro	pfref=0.	6500000 <del>a</del> +06	tfref=0,483e+03	5 dfre	of=0.6	4720e-	-04		
688	hydro	gx= 0,00	0000 gy= 0,	,000000 gz <b>≈</b> −1.0	000000					
689	hydro	cvisa=0.	700 <del>0-</del> 04 cvi	sb=0,400e-06						

(

(

B.15

690															
691	hydro	monitor	mx cells≖	∶3 maxi	mum number	curi	rent	ly.	all	owed	is	3			
692						m	i	j	k						
693						1	7	9	3						
694						2	4	4	12						
695						3	9	9	12						
696						-	-	-	• -						
697	hydro	monitor	my calle =	a mavi		~	ront	ł.	all	and	le	٦			
698	119 01 0			5 1000			1	• 7	- U - I	0400	13	2			
600						1		ן ד							
700						2	-	2	12						
700						4	у А	7	12						
701						2	4	2	12						
702	here a start and a start and a start a start a start a start a start a start a start a start a start a start a								- 1 1						
705	nyaro	MONITOR	MZ COLISª	4 maxi	mum number	curi	rent	IY.	an	CM 00	15	4			
704						m	-	ľ	ĸ						
705						1	7	9	3						
706						2	4	6	3						
707						3	4	4	12						
708						4	9	9	12						
709															
710	hydro	nreg=	2 maximu	m current	dimension	for	nre	g l	s	6					
711	hydro	specs	reg	ion	viscosit	ty		-			Ce	•11 Id	ocatic	n	
712			-			•			i be	g le	nd	bed	jend	kbeg	kend
713				1	0_100e-1	9			1	•	1	້ 2ັ	<b>1</b> 1	2	23
714				2	0.100-1	9			2	: 1	1	12	12	2	23
715				-		-			-					-	
716	hydro	nrea=	4 maximu	m current	dimension	for	ore	~ I	le	6					
717	hydro	SDACS	·		viscosit	107 N		э.		Ŭ	~		ocatio		
718		specs	. • • 9		mutioli	7 Ior			The	o to	nd .	iboa	land	"' khaa	kond
719				1	0 1000+2	21			6	y ie	7	- 100g	Jenu	2	5
720				2	0 100-12				2	r 1	י ד	6	۰ ۲	-	10
720				2	0,1009+2						7		7	2	19
721				2	0.1000+2	<u>.</u>				,	7			4	2
122				4	0.1000+2	: 1					1		11	0	19
725															
124	propm	perm0≖0,	100e+02												
725															
726	propm	info≖0	region	ax			Cel	1 1	loca	tion	I				
727					i beg	lenc	t j∣	beg	j je	nd	kbeç	g kend	t		
728															
729	propm	Info≖0	region	ay			Cel	1 1	loca	tion	I				
730			-	•	lbeg	lend	) j	bec	i je	nd	kbeç	, kend	t		
731					-			~				-			
732	propm	info=0	region	az			cel	1 1	oca	tion	I.				
733		-	<b>a</b> · - · ·		Ibea	lend	1 1	bec	ie	nd	kber	kend	ł		
734							J	3	, ,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,				-		
735	0000	Info=0	realor	avl			cel			tion					
	Pr op m		. og i on	941			001	• •							

.

776					****	1	1	Innd	khaa	kand
/ 30			•	0 100000 OF	i Deg	Iena	jbeg ∡	jena 11	KDØG	10
757			1	0.1000008-05	0	ć	o c	۱۱ ج	0 4	19
/38			2		1	7	e o	٥ د	2	19
759			2	0.1000008-05	2	<u>'</u>		7	2	5
/40			4	0,100000-05	D	/	'		2	2
741									_	
742	propm	into=0	region	ayı		с • • • • •		Catio	и - ма	lan d
/43				0 100000 OF	IDeg		Jbeg	Jeng	KDOG	Kena
744			1	0.1000000-05	2	4	2		o ¢	19
/45			2	0.1000008-05		4	/	- 11 - E	0	19
746			3	0.100000e-05	0		2	0	2	2
747			4	0,100000e-05	/	/	/	/	2	2
748										
749	propm	info=0	region	azi		C	:ell 10	DCatio	м	
750					Ibeg	lend	Jbeg	Jend	KDeg	Kend
751			1	0.100000-05	2	<u>′</u>	0		2	19
752			2	0,100000-05	1	/	1	11	2	19
753			3	0.100000-05	0	<u>′</u>	0	0	2	2
754			4	0.100000e-05	7	7	1	/	2	5
755										
756	propm	info=0	region	por	• •	, c		ocatio	on 	
757					Ibeg	lend	Jbeg	jend	kbeg	kend
758			1	0.10000e-05	2	7	6	6	6	19
759			2	0.10000e-05	7	7	7	11	6	19
760			3	0.10000e-05	6	7	6	6	2	5
761			4	0.10000e-05	7	7	7	7	2	5
762			5	0 <b>.</b> 559000e+00	2	6	7	11	2	19
763										
764	propm	info=0	region	permx		C	:ell 1	ocatio	on .	
765					Ibeg	iend	Jbeg	jend	kbeg	kend
766			1	0,4660000-02	2	6	7	11	2	19
767										
768	propm	info=0	region	permy		c	:e11 1	ocatio	on nc	
769					i beg	lend	jbeg	jend	kbeg	kend
770			1	0 <b>.</b> 466000 <del>0</del> -02	2	6	7	11	2	19
771										
772	propm	info=0	region	permz		c	ell l	ocatio	on	
773					i beg	i end	jbeg	jend	kbeg	kend
774			1	0 <b>.</b> 980000 <del>0</del> -02	2	6	7	11	2	19
775										
776	pdg	wp <b>=0.</b> 80	optcor	1≖0,500e-05						
777										
778	piter	nopt= 4	nmax=	20						
779	piter	rebson=(	).0 ret	oqon=1.0 afon	=1.0					
780										

(

•

781 piter norda= 3 maximum current dimension for norda is 4

B.17

piter norder piles epsd=0,200e-08 omega=1.10 nmax= 4 info=0 nmax= 2 info=0 rebq jbound= 1 ibound= 1 reba kbound= 1 rebq aiimin=0.100e-20 reba krea≖ 3 maximum current dimension for kreg is 3 rebq krid boundary kreg cell location surfaces ibeg lend jbeg jend б rebg kbida= 6 maximum current dimension for kbida is rebq kbld kreg sees plane sees plane sees plane sees plane sees plane kreg type kreg type kreg type kreg type kreg type rebq jreg= 5 maximum current dimension for jreg is reba jrid jreg boundary cell location surfaces ibeg lend kbeg kend maximum current dimension for jbida is 16 rebo jbida≈ 16 rebq jbid jreg sees plane sees plane sees plane sees plane sees plane jreg type jreg type jreg type jreg type ireg type 3 1 - 3 -1 ireg= 5 rebq maximum current dimension for ireg is 5 rebq irid ireg boundary cell location surfaces jbeg jend kbeg kend 

829 reba ibida= 16 maximum current dimension for ibida is 16 830 ibid rebg Ireq sees plane sees plane sees plane sees plane sees plane 831 Ireg type ireg type Ireg type ireg type Ireg type 832 Ł 2 2 3 2 5 3 2 3 3 833 834 3 3 4 -2 835 4 5 836 837 af nmax= 5 info=0 838 839 fixedm=0.000000e+00 flxedp=0.4960000e+06 avg 840 841 ***hydrostatic pressure initialization*** 842 843 maximum 844 piles residual 1 j k n 845 1 0.237e-11 2 9 14 846 1 0.2378-11 2 9 14 847 1 848 1 thermal time step=0.100e+00 maximum inside change( 3, 2,15)=0,138e+01 849 +( 2, 2, 10)=0, 512e+02 +( 3, 4,10)=0,107e+03 +( 5, 6, 10)=0, 136e+03 +( 5, 7,10)=0.154e+03 850 +(11,11,10)=0.512e+02+( 9,10,10)=0.107e+03 +( 7, 8,10)=0.136e+03 +(6, 8, 10)=0.154e+03851 maximum side change( 2, 7,29)=-.925e-01 852 ts(2,10,10)=0.470e+02 ts(4,5,10)=0.470e+02 ts(4,10,10)=0.470e+02 ts( 2, 5,10)≠0,470e+02 853 momentum time step=0.100e-03 tilde continuity error( 6, 7,23)=-.109e-06 1 dmx( 6, 7,23)=-.122e-17 dmy( 5, 4,23)=-.983e-18 dmz( 6, 7,22)=-.533e-07 854 855 856 maximum 857 residual i j k piles h 858 1 0.7946-09 9 10 18 859 1 0.794e-09 9 10 18 860 dmx(5, 5, 2) = -561e - 08 dmy(8, 7, 2) = 0.562e - 08dmz ( 6, 7,22)=0,530e-07 861 mx(7, 9, 3) = -.211e - 08mx(4, 4, 12) = -, 198e - 11mx( 9, 9,12)=-,521e-12 mx( my(9,8,12)=0.150e-11 862 my(4, 5, 3)=0.210e-08my(4, 3, 12)=0.459e-12my ( 863  $m_2(7, 9, 3)=0.128e-07$ mz(4,6,3)=0,128e-07  $m_{z}(4, 4, 12)=0.115e-08$  $m_{z}(9, 9, 12)=0.117e-08$ 864 avg. pressure=0.4895e+00 continuity error( 9,10,18)=0.414e-09 865 201 thermal time step=0.424e+00 maximum inside change( 2,11,26)=0,504e+00 866 +( 2, 2,10)=0.557e+02 +( 3, 4,10)=0.985e+02 +( 5, 6,10)=0.137e+03 +( 5, 7,10)=0,167e+03 867 +(11,11,10)=0,557e+02 +(9,10,10)=0.985e+02+( 7, 8,10)=0,137e+03 +( 6, 8,10)=0,167e+03 868 maximum side change( 2, 8,15)=0.258e-01 869 ts( 2,10,10)=0.481e+02 ts( 4, 5,10)=0.479e+02 ts( 4,10,10)=0.479e+02 ts( 2, 5,10)=0,481e+02 870 201 momentum time step=0.100e+00 tilde continuity error( 3,10,23)=0,214e-05 871 dmx(7,11,23)=0.455e-05 dmy(2,5,23)=-.455e-05 dmz(2,11,22)=0.139e-04 872 873 maximum 874 piles residual i j k n

```
875
                        -0.333e-08 9 10 18
                  1
                        -0.2090-08 9 8 17
876
                  4
877
878
                          maximum
879
                          residual i j k
         DILes
                  n
880
                  1
                         -0,772e-10 9 10 18
                  1
                         -0.772e-10 9 10 18
881
882
                                             dmx(3,10,23)=0.3310-06 dmy(3,9,23)=-.3310-06
                                                                                                  dmz(3,10,22)=-,470e-06
883
                                        mx(4, 4, 12)=0.194e-06
                                                                  mx(9, 9, 12)=0.668e-07
               m_x(7, 9, 3) = -862e - 04
                                                                                            mx(
884
                                         my(9, 8, 12) = -.194e - 06
                                                                  my(4, 3, 12) = -668e = 07
               my(4, 5, 3)=0.862e-04
                                                                                            my (
885
               m_z(7, 9, 3)=0.519e-03
                                         m_{z}(4, 6, 3)=0.519e-03
                                                                  mz(4, 4, 12) = -,151e - 04
                                                                                            mz( 9, 9,12)=-,151e-04
                                                          continuity error( 9,10,18)=-.409e-10
                   avg. pressure=0.4895e+00
886
                                                     maximum inside change( 2, 6,22)=0.833e-01
887
        401 thermal time step=0.100e+01
888
                +(2, 2, 10)=0.6020+02
                                          +(3, 4, 10)=0.104e+03
                                                                   +(5, 6, 10)=0.144+03
                                                                                             +( 5. 7.10)=0.174e+03
                +(11,11,10)=0.602e+02
                                          +(9,10,10)=0,104e+03
                                                                                             +( 6. 8,10)=0,174e+03
889
                                                                   +( 7, 8, 10)=0, 144e+03
890
                                                     maximum side change( 2, 7,15)=0.510e-01
891
               ts( 2, 5,10)=0,528e+02
                                        ts( 2,10,10)=0,528e+02 ts( 4, 5,10)=0,525e+02 ts( 4,10,10)=0,525e+02
892
              momentum time step=0.100e+00
                                                    tilde continuity error( 3,10,23)=0,188e-06
        401
893
                                             dmx(7,11,20) = -257e - 06 dmy(2,5,20) = 0.257e - 06
                                                                                                dmz(8,11,19)=0,437e-06
894
895
                          maximum
896
         Diles
                          residual i j k
                  n
897
                         -0.216e-09 10 10 23
                  1
898
                  1
                         -0.216e-09 10 10 23
899
                                             dmx( 5,10,23)=0,197e-07 dmy( 3, 7,23)=-,197e-07
                                                                                                  dmz(3,10,22)=-.622e-07
900
               mx(7, 9, 3) = -.840e - 04
                                         m_{x}(4, 4, 12) = 0.638 = -06
                                                                  m_{x}(9, 9, 12) = 0.228e = 06
                                                                                            mx(
901
               my(4, 5, 3)=0.840e-04
                                         my( 9, 8,12)=~.638e-06
                                                                  my(4, 3, 12) = -228e - 06
                                                                                            my (
                                                                  mz(4,4,12)=-.1020-04
902
               m_z(7, 9, 3)=0.513e-03
                                         m_z(4, 6, 3)=0.513e-03
                                                                                            mz(9, 9, 12)=-, 102e-04
903
                   avg. pressure=0.4895e+00
                                                          continuity error( 9,10,22)=-,119e-09
904
        601 thermal time step=0.100e+01
                                                     maximum inside change( 2, 6,15)=0.447e-01
905
                                                                   +( 5, 6,10)=0,150e+03
                                                                                             +( 5, 7,10)=0,180e+03
                (2, 2, 10) = 0.654 = +02
                                          +(3, 4, 10)=0.109e+03
906
                +(11,11,10)=0,654e+02
                                          +( 9,10,10)=0,109e+03
                                                                   +( 7, 8,10)=0.150e+03
                                                                                             +( 6, 8,10)=0,180+03
907
                                                     maximum side change( 2, 2,15)=0,446e-01
908
               ts( 2, 5,10)=0,579e+02
                                        ts(2,10,10)=0.579e+02 ts(4, 5,10)=0.576e+02 ts(4,10,10)=0.576e+02
909
                                                    tilde continuity error( 4.10,23)=0.820e-07
              momentum time step=0.100e+00
        601
910
                                             dmx(7, 9, 23) = 0.509e - 07 dmy(4, 5, 23) = -.509e - 07
                                                                                                  dmz(6, 4,11)=0.1720-06
911
912
                          maximum
913
         Diles
                          residual i j k
                  n
914
                  1
                         -0.182e-09 9 10 18
915
                  1
                        -0.1820-09 9 10 18
916
                                                                                                  dmz( 5, 4,12)=-,393e-07
                                             dmx(5,10,23)=0.613e-08
                                                                       dmy(3, 7, 23) = -.613e - 08
917
               mx(7, 9, 3) = -810e - 04
                                         mx(4, 4, 12)=0.692e-06
                                                                  m_{X}(9, 9, 12) = 0.244 = -06
                                                                                            mx(
918
                                                                  my(4, 3,12)=-.244e-06
               my(4, 5, 3)=0.810e-04
                                         my(9, 8, 12) = -692e - 06
                                                                                            my (
919
               m_z(7, 9, 3)=0.497e-03
                                         mz(4, 6, 3)=0.497e-03
                                                                  mz(4, 4, 12) = -1170 - 04
                                                                                            mz(9,9,12)=-,117e-04
920
                   avg. pressure=0.4895e+00
                                                          continuity error( 9,10,18)=-.989e-10
```

L

921 801 thermal time step=0.100e+01 maximum inside change( 2, 2,15)=0,387e-01 +( 5. 7.10)=0.1840+03 922 +(2, 2, 10)=0.706e+02+( 3, 4,10)=0,114e+03 +( 5, 6,10)=0,155e+03 +( 9,10,10)=0_114e+03 923 +(11,11,10)=0.706e+02+( 7, 8,10)=0,155e+03 +(6, 8, 10)=0.184e+03924 maximum side change( 2, 2,15)=0,391e-01 925 ts( 2. 5.10)=0.631e+02 ts( 2.10.10)=0.631e+02 ts( 4. 5.10)=0.628e+02 ts( 4.10.10)=0.628e+02 926 tilde continuity error( 6,10,20)=-,538e-07 801 momentum time step=0,100e+00 927  $dm_x(7,11,5) = -389e - 07$   $dm_y(2,5,5) = 0.389e - 07$ dmz(6,4,11)=0,147e-06 928 929 maximum 930 piles residual i j k n 931 -0.303e-09 9 10 18 1 932 1 -0.303e-09 9 10 18 933 dmx(7,10, 5) = -1990 - 08 dmy(3, 5, 5) = 0.1990 - 08dmz(5,4,12)=-,305e-07 934 mx(7, 9, 3) = -.779 = -.04mx(4, 4, 12)=0.660e-06mx(9, 9, 12)=0.232e-06mx( 935 my(4, 5, 3)=0.779=-04my(9, 8, 12) = -,660e - 06my(4, 3, 12) = -232e - 06my ( mz(4,6,3)=0,478e-03 mz(4,4,12)=-,136e-04 mz( 9, 9,12)=-,136e-04 936 mz( 7, 9, 3)≈0,478e-03 937 avg. pressure=0.4895e+00 continuity error( 9,10,18)=-,164e-09 938 maximum inside change( 2, 2,15)=0,339e-01 thermal time step=0.100e+01 1000 939 +( 2, 2, 10)=0,757e+02 +(3, 4, 10)=0.119e+03+( 5, 6, 10)=0, 160e+03 +( 5, 7,10)=0,189e+03 +( 7, 8,10)=0.160e+03 +( 6, 8,10)=0.189e+03 940 +(11,11,10)=0.757e+02 +(9,10,10)=0,119e+03941 maximum side change( 2, 2,15)=0.344e-01 942 ts( 2, 5,10)=0,682e+02 ts( 2,10,10)=0,682e+02 ts( 4, 5,10)=0,679e+02 ts( 4,10,10)=0,679e+02 943 tilde continuity error( 6, 7,20)=-,545e-07 1000 momentum time step=0,100e+00 944 dmx(7,11,5)=-,391e-07 dmy(2,5,5)=0,391e-07dmz(9,7,11)=0,123e-06 945 946 maximum 947 piles residual i j k n 948 1 -0.3630-09 9 10 18 949 1 -0.363e-09 9 10 18 dmx(7,10,5)=-.194e-08 dmy(3,5,5)=0.194e-08 dmz(6,7,20)=-.283e-07 950 951  $m_{X}(7, 9, 3) = -.749 = -.04$ mx( 4, 4, 12)=0,613e-06  $m_X(9, 9, 12)=0.216e-06$ mx( 952 my(4, 5, 3)=0.749e-04my(9, 8, 12) = -613e - 06my(4, 3, 12) = -216e - 06my ( 953 mz(7, 9, 3)=0.459e-03mz(4,6,3)=0,459e-03 mz(4,4,12)=-,152e-04 mz( 9, 9,12)=-.152e-04 954 continuity error( 9,10,18)=-,195e-09 avg. pressure=0.4895e+00 955 1 956 * * * thermal power balance summary, watts * * * 957 958 thermal power from inside to side at level k 959 29 -, 165139e+01 960 28 -.434836e+01 961 27 -.716536e+01 962 0.378800e+01 26 963 25 0.227392e+01 964 24 0.130187e+01 965 23 0.205785e+01 966 0.177996e+02 22

967	21	0,2479990+02
968	20	0,354332e+02
969	19	0.513323e+02
970	18	0.752517e+02
971	17	0,105157e+03
972	16	0.140924e+03
973	15	0.142044e+03
974	14	0,108947e+03
975	13	0.817615e+02
976	12	0.592768e+02
977	11	0.428461e+02
978	10	0.302628e+02
979	9	0.211010e+02
980	8	0.174653e+02
981	7	0.114181e+02
982	6	0.670351e+01
983	- <b>5</b>	0.251733e+01
984	4	0.788006+01
985	3	0.10340+02
986	2	0.6935090+01
987	-	0.0777070.01
988	thermal newer from caulty to ton	0 1982520+02
989		0.1902920.02
990	thermal nower from cavity to side	0.984463-+03
991		0,0000000000000000000000000000000000000
992	thermal nower from cavity to bottom	0.770241+02
993		0.7702410.02
400	thermal nower from cavity	0 1081316+04
995		0.1001218104
996	thormal nower from too to ambient	0 5151220+01
997		0.0101228.01
998	thermal nower from ton to side	- 1316516+02
999		
1000	thermal nower from bottom to side	0.251631e+02
1001		0.2710310101
1002	thermal nower from bottom to ambient	0.241767e=16
1003		
1004	thermal nower from top of side to ambient	0-462020+01
1005		0.4020200.01
1006	thermal power from side to ambient	0.252627e+03
1007		A87280510.43
1008	thermal power from bottom of side to ambient	0.210228-16
1009		-92.0240 IA
1010	thermal power from outside surface to ambient	0.2623999+03
1011		-1
1012	excess nower leaving cavity	7870+02
· - · -	heart rearring marries	

1013		
1014	excess power leaving top	<b>-</b> •278 <del>0</del> +02
1015		
1016	excess power leaving side	<b></b> 739e+03
1017		
1018	excess power leaving bottom	<b></b> 519e+02
1019 1		
1020	* * * inside he	at flux in i-direction, watts/sq. cm * * *
1021		
1022		plane k= 8
1023	j (= 1	
1024	11-0,426e-18-0,116e-01 0,149e-01 0,376e-01 0,381e	-01 0.749e-01 0.485e+00 0.429e+00 0.192e+00 0.770e-01 0.534e-01
1025	10-0,428e-18-0,129e-01 0,151e-01 0,509e-01 0,247e	-01 0.779e-01 0.473e+00 0.411e+00 0.179e+00 0.695e-01 0.442e-01
1026	9-0.417e-18-0.126e-01 0.673e-02 0.294e-01 0.435e	-01 0.802e-01 0.419e+00 0.334e+00 0.129e+00 0.566e-01 0.000e+00
1027	8-0,391e-18 0,522e-02-0,146e-01 0,238e-01 0,508e	-01 0.762e-01 0.303e+00 0.194e+00 0.648e-01 0.000e+00 0.000e+00
1028	7-0.362e-18-0.125e-01 0.441e-02 0.315e-01 0.803e	-01 0.149e+00 0.826e-01 0.507e-01 0.000e+00 0.000e+00
1029	6-0,293e-18 0,166e-01 0,581e-01 0,945e-01 0,350e	-01 0,206e+00 0,199e+00 0,000e+00 0,000e+00
1030	5-0,256e-18 0,149e-01 0,500e-01 0,912e-01 0,904e	-01 0.451e-01 0.000e+00 0.000e+00
1031	4-0,219e-18 0,121e-01 0,352e-01 0,589e-01 0,682e	-01 0.000e+00 0.000e+00
1032	3-0,176e-18 0,743e-02 0,215e-01 0,293e-01 0,000e	+00 0,000e+00
1033	2-0,143e-18 0,100e-02 0,132e-01 0,000e+00 0,000e	+00
1054		
1035 1	<b></b>	and the second second second second second second second second second second second second second second second
1020	* * * Inside he	at flux in j-direction, watts/sq. cm * * *
1057		
1028		plane K= 8
1039	j = 2	-10 0 20710 0 25510 0 21010 0 17510 0 14710
1040	10 0 116 - 01 0 120 - 01 0 126 - 01 0 522 - 02 0 125 - 01 0 522 - 02 0 125 - 01 0 126 - 01 0 126 - 01 0 126 - 01 0 126 - 01 0 126 - 01 0 126 - 01 0 126 - 01 0 126 - 01 0 126 - 01 0 126 - 01 0 126 - 01 0 126 - 01 0 126 - 01 0 126 - 01 0 126 - 01 0 126 - 01 0 126 - 01 0 126 - 01 0 126 - 01 0 126 - 01 0 126 - 01 0 126 - 01 0 126 - 01 0 126 - 01 0 126 - 01 0 126 - 01 0 126 - 01 0 126 - 01 0 126 - 01 0 126 - 01 0 126 - 01 0 126 - 01 0 126 - 01 0 126 - 01 0 126 - 01 0 126 - 01 0 126 - 01 0 126 - 01 0 126 - 01 0 126 - 01 0 126 - 01 0 126 - 01 0 126 - 01 0 126 - 01 0 126 - 01 0 126 - 01 0 126 - 01 0 126 - 01 0 126 - 01 0 126 - 01 0 126 - 01 0 126 - 01 0 126 - 01 0 126 - 01 0 126 - 01 0 126 - 01 0 126 - 01 0 126 - 01 0 126 - 01 0 126 - 01 0 126 - 01 0 126 - 01 0 126 - 01 0 126 - 01 0 126 - 01 0 126 - 01 0 126 - 01 0 126 - 01 0 126 - 01 0 126 - 01 0 126 - 01 0 126 - 01 0 126 - 01 0 126 - 01 0 126 - 01 0 126 - 01 0 126 - 01 0 126 - 01 0 126 - 01 0 126 - 01 0 126 - 01 0 126 - 01 0 126 - 01 0 126 - 01 0 126 - 01 0 126 - 01 0 126 - 01 0 126 - 01 0 126 - 01 0 126 - 01 0 126 - 01 0 126 - 01 0 126 - 01 0 126 - 01 0 126 - 01 0 126 - 01 0 126 - 01 0 126 - 01 0 126 - 01 0 126 - 01 0 126 - 01 0 126 - 01 0 126 - 01 0 126 - 01 0 126 - 01 0 126 - 01 0 126 - 01 0 126 - 01 0 126 - 01 0 126 - 01 0 126 - 01 0 126 - 01 0 126 - 01 0 126 - 01 0 126 - 01 0 126 - 01 0 126 - 01 0 126 - 01 0 126 - 01 0 126 - 01 0 126 - 01 0 126 - 01 0 126 - 01 0 126 - 01 0 126 - 01 0 126 - 01 0 126 - 01 0 126 - 01 0 126 - 01 0 126 - 01 0 126 - 01 0 126 - 01 0 126 - 01 0 126 - 01 0 126 - 01 0 126 - 01 0 126 - 01 0 126 - 01 0 126 - 01 0 126 - 01 0 126 - 01 0 126 - 01 0 126 - 01 0 126 - 01 0 126 - 01 0 126 - 01 0 126 - 01 0 126 - 01 0 126 - 01 0 0 126 - 01 0 126 - 01 0 126 - 01 0 126 - 01 0 126 - 01 0 126 - 01 0 126 - 01 0 126 - 01 0 126 - 01 0 126 - 01 0 126 - 01 0 126 - 01 0 126 - 01 0 126 - 01 0 126 - 01 0 126 - 01 0 126 - 01 0 126 - 01 0 126 - 01 0 126 - 01 0 126 - 01 0 126 - 01 0 126 - 01 0 126 - 01 0 126 - 01 0 126 - 01 0 126 - 01 0 126 - 01 0 126 - 01 0 12	-10 U_2938-10 U_2208-10 U_2198-10 U_1708-10 U_1428-10 -01-0 166a:01-0 140a-01-0 121a-01-0 743a-02-0 100a-02
1041		
1042	$9-0_{\bullet}$ 1499-01-0_{\bullet} 1918-01-0_{\bullet} 0758-02_0_{\bullet} 1408-01-0_{\bullet} 4418	
1045		
1045	6=0,749=-01=0,779=-01=0,802=-01=0,762=-01=0,149=-01=0,149=-01=0,149=-01=0,149=-01=0,149=-01=0,149=-01=0,149=-01=0,149=-01=0,149=-01=0,149=-01=0,149=-01=0,149=-01=0,149=-01=0,149=-01=0,149=-01=0,149=-01=0,149=-01=0,149=-01=0,149=-01=0,149=-01=0,149=-01=0,149=-01=0,149=-01=0,149=-01=0,149=-01=0,149=-01=0,149=-01=0,149=-01=0,149=-01=0,149=-01=0,149=-01=0,149=-01=0,149=-01=0,149=-01=0,149=-01=0,149=-01=0,149=-01=0,149=-01=0,149=-01=0,149=-01=0,149=-01=0,149=-01=0,149=-01=0,149=-01=0,149=-01=0,149=-01=0,149=-01=0,149=-01=0,149=-01=0,149=-01=0,149=-01=0,149=-01=0,149=-01=0,149=-01=0,149=-01=0,149=-01=0,149=-01=0,149=-01=0,149=-01=0,149=-01=0,149=-01=0,149=-01=0,149=-01=0,149=-01=0,149=-01=0,149=-01=0,149=-00,149=-00,149=-00,149=-00,149=-00,149=-00,149=-00,149=-00,149=-00,149=-00,149=-00,149=-00,149=-00,149=-00,149=-00,149=-00,149=-00,149=-00,149=-00,149=-00,149=-00,149=-00,149=-00,149=-00,149=-00,149=-00,149=-00,149=-00,149=-00,149=-00,149=-00,149=-00,149=-00,149=-00,149=-00,149=-00,149=-00,149=-0,149=-00,149=-00,149=-00,149=-00,149=-00,149=-00,149=-00,149=-00,149=-00,149=-00,149=-00,149=-00,149=-00,149=-00,149=-00,149=-00,149=-00,149=-00,149=-00,149=-00,149=-00,149=-00,149=-00,149=-00,149=-00,149=-00,149=-00,149=-00,149=-00,149=-00,149=-00,149=-00,149=-00,149=-00,149=-00,149=-00,149=-00,149=-00,149=-00,149=-00,149=-00,149=-00,149=-00,149=-00,149=-00,149=-00,149=-00,149=-00,149=-00,149=-00,149=-00,149=-00,149=-00,149=-00,149=-00,149=-00,149=-00,149=-00,149=-00,149=-00,149=-00,149=-00,149=-00,149=-00,149=-00,149=-00,149=-00,149=-00,149=-00,149=-00,149=-00,149=-00,149=-00,149=-00,149=-00,149=-00,149=-00,149=-00,149=-00,149=-00,149=-00,149=-00,149=-00,149=-00,149=-00,149=-00,149=-00,149=-00,149=-00,149=-00,149=-00,149=-00,149=-00,149=-00,149=-00,149=-00,149=-00,149=-00,149=-00,149=-00,149=-00,149=-00,149=-00,149=-00,149=-00,149=-00,149=-00,149=-00,149=-00,149=-00,149=-00,149=-00,149=-00,149=-00,149=-00,149=-00,149=-00,149=-00,149=-00,149=-00,149=-00,149=-00,149=-00,149=-00,149=-00,149=-00,149=-00,149=-00,149=-00,149=-	+00-0,2000+00-0,451e-01,0,000e+00
1045		
1040		
1048	3-0-192e+00-0.179e+00-0.129e+00-0.648e-01.0.000e	+00
1049	2-0,770e-01-0,695e-01-0,566e-01 0,000e+00	
1050	1-0.534e-01-0.442e-01.0.000e+00.0.000e+00	
1051		
1052 1		
1053	* * * incido ha	at flux in k-direction, watts/so, cm * * *
1054		ar traverile a controlly mutic/age and
1055		plane k= 8
1056	i i= 2	provide the second second second second second second second second second second second second second second s
1057	11-0, 1290+00-0, 1280+00-0, 1160+00-0, 9050-01-0, 2630	-01-0.229e-01 0.827e+00 0.376e+00-0.365e+00-0.316e+00
1058	10-0,128+00-0,128+00-0,116+00-0,873+01-0,254	-01-0,217e-01 0,788e+00 0,309e+00-0,400e+00-0,314e+00

(

B.23

1059	9-0.116e+00-0.1	116e+00-0.107e+00-0.861e-01-	0.2350-01-0	0.1998-01	0.5980+00-	-0.210e-01-	-0 <b>.</b> 569e+00-	-0.123e+00				
1060	8-0,905e-01-0,873e-01-0,861e-01-0,758e-01-0,375e-01-0,235e-01 0,252e+00-0,492e+00-0,203e+00 0,000e+00											
1061	7-0.263e-01-0.2	254-01-0.235-01-0.375-01-	0.105e+00-0	). 132e+01-	0.175e+00-	-0.282.+00	0.000a+00	-				
1062	6-0.229e-01-0.2	217e-01-0, 199e-01-0, 235e-01-	0.1320+01-0	)_121e+01-	0.149+00	0.000+00						
1063	5 0.827e+00 0.7	788e+00 0.598e+00 0.252e+00-	0.175e+00-0	).149e+00	0.000+00							
1064	4 0.376e+00 0.3	309e+00-0.211e-01-0.492e+00-	0.282+00 0	000e+00								
1065	3-0.365+00-0.4	400e+00-0.569e+00-0.203e+00	0.000e+00	•••••								
1066	2=0.316+00=0.3	314e+00-0,123e+00,0,000e+00										
1067												
1068 1												
1069			* * * ;	incido tom	oerature	~ * * *						
1070			•		perature,							
1071				nlan								
1072	1 1= 2			pran	10 K-JU							
1073	12 0.000+00.0.0	000+00 0.000+00 0.000+00	0.000+00.0	000-+00	0 0000+00	0 000-+00	0.000-+00	0.000-+00	0.000-+00			
1074		$270_{0}+02$ 0 $270_{0}+02$ 0 $270_{0}+02$	0 2700+02 0	270+02	0 270+02	0 270+02	0 2700+02	0 2700+02	0.0000+00			
1075	10 0 270+02 0 2	$270_{0}+02$ 0 $270_{0}+02$ 0 $270_{0}+02$	0 2700+02 0	2700+02	0 270-+02	0 270-+02	0 270-+02	0.270-+02	0.000-+00			
1076	9 0 270-+02 0 2	$270_{0} \pm 02$ 0 $270_{0} \pm 02$ 0 $270_{0} \pm 02$	0 270 +02 0	270-402	0 270-+02	0 270 +02	0 270 +02	0 270-+02	0.0000+00			
1077	8 0 270-402 0 2	$270_{0} \pm 02$ 0 $270_{0} \pm 02$ 0 $270_{0} \pm 02$	0.2700+02 0	2700+02	0 270 +02	0.2700+02	0 2700+02	0.000-+00	0.0000100			
1079		$270_{0}+02$ 0 $270_{0}+02$ 0 $270_{0}+02$	0,2700+02 0		0 270-+02	0,270,402		0.0000000				
1070		$270_{-4}02$ 0 $270_{-4}02$ 0 $270_{-4}02$	0.2700+02 0		0.270.00	0.000-+00	0.00000000					
1000	5 0 270-102 0-2	270-402 0.270-402 0.270-402	0,270,102 0	270-102		0.0000+00						
1000		2706402 0.2706402 0.2706402	0.2708402 0		0.0000+00							
1001	4 0.2709TUZ 0.2	270et02 0.270et02 0.270et02 270et02 0.270et02 0.270et02	0.2700+02 0	0000+00								
1002		2708402 0.2708402 0.2708402 0	0.0000+00									
1003												
1004	I U.UUU0+UU U.U											
1005					- 1-20							
1000				pian	I8 K=29							
1007	J I= 2	000-100 0 000-100 0 000-100	0.000.100.0	000.000	0.000.000	0 000 100	0.000.000	0.000.100	0 000 100			
1000	12 0.00000000000					0.0000000		0.0000+00	0.0008700			
1009	10 0 516 102 0 5	516e+02 0.516e+02 0.515e+02	0.5150402 0	0.0100+02	0.5146+02	0.5140+02	0.5140+02	0.5150+02	0.5150+02			
1090	10 0.510e+02 0.5		0.5150+02 0	0.0100+UZ	0,5156+02	0,0100+02	0,5150+02	0,5150+02	0,5150+02			
1091	9 0,5100+02 0,5	5100102 0.5100102 0.5100102 (	0.5150+02 0	.5150+02	0.5150+02	0.5150+02	0.5150+02	0.5160+02	0.000e+00			
1092	8 0.5150+02 0.5	5160+02 0.5160+02 0.5160+02	0,5160+02 0	0.516e+02	0.516e+02	0.5160+02	0.5168+02	0.000e+00				
1095	/ 0.5150+02 0.5	515e+02 0,515e+02 0,516e+02	0.515e+02 0	<b>516e+02</b>	0,516e+02	0,517e+02	0,000e+00					
1094	6 0,515e+02 0,5	515e+02 0,515e+02 0,516e+02	0,516e+02 0	516e+02	0.5176+02	0.000e+00						
1095	5 0,514e+02 0,5	515e+02 0,515e+02 0,516e+02	0.516e+02 0	•517e+02	0 <b>.000e+00</b>							
1096	4 0,514e+02 0,5	515e+02 0,515e+02 0,516e+02	0.517e+020	000 <del>e</del> +00								
1097	3 0,5140+02 0,5	515e+02 0,515e+02 0,516e+02	0 <b>.</b> 000e+00									
1098	2 0.515e+02 0.5	515e+02 0.516e+02 0.000e+00										
1099	1 0,515e+02 0,5	515e+02 0.000e+00 0.000e+00										
1100												
1101				plan	e k=28							
1102	j != 2											
1103	12 0.000e+00 0.0	000e+00 0.000e+00 0.000e+00	0 <b>.000e+00</b> 0	00 <del>0</del> 000.	0.000e+00	0.000e+00	0.000e+00	0.000e+00	0.000e+00			
1104	11 0,517e+02 0,5	517e+02 0.517e+02 0.516e+02 (	0,516e+02 0	•515e+02	0,515e+02	0.515e+02	0,515e+02	0,5160+02	0.516e+02			

8.24

1105 1106 9 0.517e+02 0.517e+02 0.517e+02 0.517e+02 0.516e+02 0.516e+02 0.516e+02 0.516e+02 0.516e+02 0.516e+02 0.517e+02 0.000e+00 1107 8 0.516e+02 0.517e+02 0.517e+02 0.517e+02 0.517e+02 0.516e+02 0.517e+02 0.517e+02 0.517e+02 0.000e+00 1108 7 0,516e+02 0,516e+02 0,516e+02 0,517e+02 0,517e+02 0,517e+02 0,517e+02 0,517e+02 0,518e+02 0,000e+00 1109 6 0,515e+02 0,516e+02 0,516e+02 0,516e+02 0,517e+02 0,517e+02 0,518e+02 0,000e+00 1110 5 0.515e+02 0.515e+02 0.516e+02 0.517e+02 0.517e+02 0.518e+02 0.000e+00 1111 4 0.515e+02 0.516e+02 0.516e+02 0.517e+02 0.518e+02 0.000e+00 1112 3 0,515e+02 0,516e+02 0,516e+02 0,517e+02 0,000e+00 1113 2 0.516e+02 0.516e+02 0.517e+02 0.000e+00 1114 1 0,516e+02 0,516e+02 0,000e+00 0,000e+00 1115 1116 plane k=27 1117 ] = 2 1118 12 0,000+00 0,000+00 0,000+00 0,000+00 0,000+00 0,000+00 0,000+00 0,000+00 0,000+00 0,000+00 0,000+00 0,000+00 1119 11 0.520e+02 0.520e+02 0.520e+02 0.519e+02 0.518e+02 0.517e+02 0.516e+02 0.516e+02 0.517e+02 0.518e+02 0.518e+02 10 0.520e+02 0.520e+02 0.520e+02 0.519e+02 0.518e+02 0.517e+02 0.517e+02 0.517e+02 0.517e+02 0.517e+02 0.518e+02 0.519e+02 1120 1121 9 0.520e+02 0.520e+02 0.519e+02 0.519e+02 0.518e+02 0.518e+02 0.517e+02 0.517e+02 0.518e+02 0.518e+02 0.000e+00 1122 8 0,519e+02 0,519e+02 0,519e+02 0,519e+02 0,518e+02 0,518e+02 0,518e+02 0,519e+02 0,520e+02 0,000e+00 1123 7 0.518e+02 0.518e+02 0.518e+02 0.518e+02 0.518e+02 0.518e+02 0.518e+02 0.519e+02 0.520e+02 0.000e+00 1124 6 0.517e+02 0.517e+02 0.518e+02 0.518e+02 0.518e+02 0.519e+02 0.520e+02 0.000e+00 1125 5 0.516e+02 0.517e+02 0.517e+02 0.518e+02 0.519e+02 0.520e+02 0.000e+00 1126 4 0,516e+02 0,517e+02 0,517e+02 0,519e+02 0,520e+02 0,000e+00 1127 3 0,517e+02 0,517e+02 0,518e+02 0,520e+02 0,000e+00 1128 2 0,518e+02 0,518e+02 0,519e+02 0,000e+00 1129 1 0,518e+02 0,519e+02 0,000e+00 0,000e+00 1130 1131 plane k=26 1132 1 1= 2 1133 12 0,000+00 0,000+00 0,000+00 0,000+00 0,000+00 0,000+00 0,000+00 0,000+00 0,000+00 0,000+00 0,000+00 0,000+00 1134 11 0,109e+03 0,107e+03 0,101e+03 0,938e+02 0,874e+02 0,830e+02 0,788e+02 0,724e+02 0,634e+02 0,560e+02 0,528e+02 1135 10 0,107e+03 0,105e+03 0,996e+02 0,929e+02 0,868e+02 0,825e+02 0,784e+02 0,719e+02 0,632e+02 0,565e+02 0,528e+02 1136 9 0,1010+03 0,9966+02 0,9490+02 0,8950+02 0,8450+02 0,8060+02 0,7630+02 0,6910+02 0,5970+02 0,5290+02 0,0000+00 1137 8 0.938+02 0.929+02 0.896+02 0.856+02 0.813+02 0.774+02 0.721+02 0.631+02 0.529+02 0.000+00 1138 7 0.874e+02 0.868e+02 0.845e+02 0.813e+02 0.772e+02 0.719e+02 0.639e+02 0.530e+02 0.000e+00 1139 6 0.830e+02 0.825e+02 0.806e+02 0.774e+02 0.719e+02 0.630e+02 0.530e+02 0.000e+00 1140 5 0,788e+02 0,784e+02 0,763e+02 0,721e+02 0,639e+02 0,530e+02 0,000e+00 1141 4 0,724e+02 0,719e+02 0,691e+02 0,631e+02 0,530e+02 0,000e+00 1142 3 0.634e+02 0.632e+02 0.597e+02 0.529e+02 0.000e+00 1143 2 0,560e+02 0,565e+02 0,529e+02 0,000e+00 1144 1 0.528e+02 0.528e+02 0.000e+00 0.000e+00 1145 1146 plane k=25 1147 j i= 2 1148 12 0,000+00 0,000+00 0,000+00 0,000+00 0,000+00 0,000+00 0,000+00 0,000+00 0,000+00 0,000+00 0,000+00 0,000+00 1149 11 0,123e+03 0,120e+03 0,109e+03 0,965e+02 0,866e+02 0,804e+02 0,749e+02 0,686e+02 0,613e+02 0,561e+02 0,539e+02 1150 10 0.120e+03 0.117e+03 0.106e+03 0.951e+02 0.859e+02 0.799e+02 0.745e+02 0.681e+02 0.612e+02 0.565e+02 0.540e+02

8.25

9 0,109e+03 0,106e+03 0,988e+02 0,904e+02 0,834e+02 0,778e+02 0,724e+02 0,657e+02 0,586e+02 0,540e+02 0,000e+00 1151 1152 8 0,965e+02 0,951e+02 0,904e+02 0,852e+02 0,798e+02 0,741e+02 0,682e+02 0,609e+02 0,541e+02 0,000e+00 7 0.866e+02 0.859e+02 0.834e+02 0.798e+02 0.745e+02 0.681e+02 0.615e+02 0.541e+02 0.000e+00 1153 1154 6 0_804e+02 0_799e+02 0_778e+02 0_741e+02 0_681e+02 0_607e+02 0_541e+02 0_000e+00 1155 5 0.749e+02 0.745e+02 0.724e+02 0.682e+02 0.615e+02 0.541e+02 0.000e+00 4 0,686e+02 0,681e+02 0,657e+02 0,609e+02 0,541e+02 0,000e+00 1156 1157 3 0.613e+02 0.612e+02 0.586e+02 0.541e+02 0.000e+00 1158 2 0.561e+02 0.565e+02 0.540e+02 0.000e+00 1159 1 0.539e+02 0.540e+02 0.000e+00 0.000e+00 1160 1161 plane k=24 1162 i i= 2 12 0.000e+00 0.000e+00 0.000e+00 0.000e+00 0.000e+00 0.000e+00 0.000e+00 0.000e+00 0.000e+00 0.000e+00 0.000e+00 1163 11 0,128e+03 0,123e+03 0,109e+03 0,938e+02 0,811e+02 0,730e+02 0,689e+02 0,646e+02 0,598e+02 0,566e+02 0,553e+02 1164 10 0.123a+03 0.119a+03 0.106a+03 0.916a+02 0.797a+02 0.724a+02 0.685a+02 0.643a+02 0.598a+02 0.569a+02 0.553a+02 1165 9 0,109e+03 0,106e+03 0,959e+02 0,849e+02 0,759e+02 0,706e+02 0,669e+02 0,626e+02 0,581e+02 0,554e+02 0,000e+00 1166 8 0,938e+02 0,916e+02 0,849e+02 0,779e+02 0,723e+02 0,680e+02 0,641e+02 0,595e+02 0,555e+02 0,000e+00 1167 7 0.811e+02 0.797e+02 0.759e+02 0.723e+02 0.686e+02 0.642e+02 0.598e+02 0.555e+02 0.000e+00 1168 6 0.730e+02 0.724e+02 0.706e+02 0.680e+02 0.642e+02 0.594e+02 0.556e+02 0.000e+00 1169 1170 5 0.689e+02 0.685e+02 0.669e+02 0.641e+02 0.598e+02 0.556e+02 0.000e+00 1171 4 0.646e+02 0.643e+02 0.626e+02 0.595e+02 0.555e+02 0.000e+00 1172 3 0.598e+02 0.598e+02 0.581e+02 0.555e+02 0.000e+00 1173 2 0.566e+02 0.569e+02 0.554e+02 0.000e+00 1174 1 0.553e+02 0.553e+02 0.000e+00 0.000e+00 1175 1176 plane k=23 1177 1 1= 2 1178 12 0.000e+00 0.000e+00 0.000e+00 0.000e+00 0.000e+00 0.000e+00 0.000e+00 0.000e+00 0.000e+00 0.000e+00 0.000e+00 11 0,139e+03 0,134e+03 0,122e+03 0,110e+03 0,991e+02 0,893e+02 0,831e+02 0,711e+02 0,632e+02 0,588e+02 0,570e+02 1179 1180 10 0.134e+03 0.130e+03 0.120e+03 0.108e+03 0.975e+02 0.878e+02 0.814e+02 0.700e+02 0.629e+02 0.591e+02 0.570e+02 1181 9 0.122e+03 0.120e+03 0.112e+03 0.103e+03 0.932e+02 0.832e+02 0.758e+02 0.662e+02 0.604e+02 0.571e+02 0.000e+00 1182 8 0,110e+03 0,108e+03 0,103e+03 0,966e+02 0,882e+02 0,788e+02 0,701e+02 0,622e+02 0,572e+02 0,000e+00 1183 7 0,991e+02 0,975e+02 0,932e+02 0,882e+02 0,821e+02 0,745e+02 0,646e+02 0,573e+02 0,000e+00 1184 6 0.893e+02 0.878e+02 0.832e+02 0.788e+02 0.745e+02 0.682e+02 0.574e+02 0.000e+00 1185 5 0.831e+02 0.814e+02 0.758e+02 0.701e+02 0.646e+02 0.574e+02 0.000e+00 1186 4 0,711e+02 0,700e+02 0,662e+02 0,622e+02 0,573e+02 0,000e+00 1187 3 0.632e+02 0.629e+02 0.604e+02 0.572e+02 0.000e+00 1188 2 0,588e+02 0,591e+02 0,571e+02 0,000e+00 1189 1 0.570e+02 0.570e+02 0.000e+00 0.000e+00 1 190 1191 plane k=22 1192 | |= 2 1193 12 0,000e+00 0,000e+00 0,000e+00 0,000e+00 0,000e+00 0,000e+00 0,000e+00 0,000e+00 0,000e+00 0,000e+00 0,000e+00 11 0.190e+03 0.189e+03 0.183e+03 0.171e+03 0.154e+03 0.140e+03 0.127e+03 0.101e+03 0.788e+02 0.650e+02 0.591e+02 1194 1195 10 0, 189e+03 0, 188e+03 0, 182e+03 0, 170e+03 0, 154e+03 0, 139e+03 0, 126e+03 0, 995e+02 0, 784e+02 0, 660e+02 0, 592e+02 1196 9 0.183e+03 0.182e+03 0.178e+03 0.168e+03 0.152e+03 0.138e+03 0.123e+03 0.935e+02 0.721e+02 0.593e+02 0.000e+00

1197 8 0,171e+03 0,170e+03 0,168e+03 0,161e+03 0,147e+03 0,135e+03 0,117e+03 0,826e+02 0,595e+02 0,000e+00 1198 7 0.154e+03 0.154e+03 0.152e+03 0.147e+03 0.139e+03 0.132e+03 0.103e+03 0.598e+02 0.000e+00 1199 6 0,140e+03 0,139e+03 0,138e+03 0,135e+03 0,132e+03 0,130e+03 0,602e+02 0,000e+00 1200 5 0.127e+03 0.126e+03 0.123e+03 0.117e+03 0.103e+03 0.602e+02 0.000e+00 1201 4 0.101e+03 0.995e+02 0.935e+02 0.826e+02 0.598e+02 0.000e+00 1202 3 0,788e+02 0,784e+02 0,721e+02 0,595e+02 0,000e+00 1203 2 0.650e+02 0.660e+02 0.593e+02 0.000e+00 1204 1 0,591e+02 0,592e+02 0,000e+00 0,000e+00 1205 1206 plane k=21 1207 i i= 2 1208 12 0.000e+00 0.000e+00 0.000e+00 0.000e+00 0.000e+00 0.000e+00 0.000e+00 0.000e+00 0.000e+00 0.000e+00 0.000e+00 1209 11 0,209e+03 0,208e+03 0,202e+03 0,187e+03 0,167e+03 0,145e+03 0,133e+03 0,107e+03 0,838e+02 0,682e+02 0,615e+02 1210 10 0.208e+03 0.207e+03 0.200e+03 0.186e+03 0.166e+03 0.145e+03 0.132e+03 0.106e+03 0.835e+02 0.694e+02 0.616e+02 1211 9 0.202e+03 0.200e+03 0.196e+03 0.184e+03 0.164e+03 0.143e+03 0.129e+03 0.100e+03 0.765e+02 0.617e+02 0.000e+00 1212 8 0,187e+03 0,186e+03 0,184e+03 0,176e+03 0,159e+03 0,140e+03 0,123e+03 0,881e+02 0,619e+02 0,000e+00 1213 7 0,167e+03 0,166e+03 0,164e+03 0,159e+03 0,148e+03 0,137e+03 0,108e+03 0,623e+02 0,000e+00 6 0.145e+03 0.145e+03 0.143e+03 0.140e+03 0.137e+03 0.135e+03 0.628e+02 0.000e+00 1214 1215 5 0,133e+03 0,132e+03 0,129e+03 0,123e+03 0,108e+03 0,628e+02 0,000e+00 1216 4 0,107e+03 0,106e+03 0,100e+03 0,881e+02 0,623e+02 0,000e+00 1217 3 0.838e+02 0.835e+02 0.765e+02 0.619e+02 0.000e+00 1218 2 0.682e+02 0.694e+02 0.617e+02 0.000e+00 1219 1 0.615e+02 0.616e+02 0.000e+00 0.000e+00 1220 1221 plane k=20 1222 1= 2 1223 12 0.000e+00 0.000e+00 0.000e+00 0.000e+00 0.000e+00 0.000e+00 0.000e+00 0.000e+00 0.000e+00 0.000e+00 0.000e+00 1224 11 0.233e+03 0.233e+03 0.225e+03 0.207e+03 0.182e+03 0.154e+03 0.142e+03 0.114e+03 0.888e+02 0.719e+02 0.647e+02 1225 10 0.233e+03 0.231e+03 0.223e+03 0.206e+03 0.181e+03 0.154e+03 0.141e+03 0.113e+03 0.885e+02 0.732e+02 0.648e+02 1226 9 0.225e+03 0.223e+03 0.218e+03 0.205e+03 0.180e+03 0.152e+03 0.137e+03 0.107e+03 0.809e+02 0.649e+02 0.000e+00 1227 8 0,207e+03 0,206e+03 0,205e+03 0,195e+03 0,173e+03 0,149e+03 0,130e+03 0,934e+02 0,652e+02 0,000e+00 1228 7 0,182e+03 0,181e+03 0,180e+03 0,173e+03 0,159e+03 0,146e+03 0,115e+03 0,656e+02 0,000e+00 1229 6 0,154e+03 0,154e+03 0,152e+03 0,149e+03 0,146e+03 0,143e+03 0,661e+02 0,000e+00 1230 5 0.142e+03 0.141e+03 0.137e+03 0.130e+03 0.115e+03 0.661e+02 0.000e+00 1231 4 0.114e+03 0.113e+03 0.107e+03 0.934e+02 0.656e+02 0.000e+00 1232 3 0.888e+02 0.885e+02 0.809e+02 0.652e+02 0.000e+00 1233 2 0.719e+02 0.732e+02 0.649e+02 0.000e+00 1234 1 0,647e+02 0,648e+02 0,000e+00 0,000e+00 1235 1236 plane k=19 1237 j i= 2 1238 12 0.000e+00 0.000e+00 0.000e+00 0.000e+00 0.000e+00 0.000e+00 0.000e+00 0.000e+00 0.000e+00 0.000e+00 0.000e+00 1239 11 0,259e+03 0,259e+03 0,250e+03 0,230e+03 0,200e+03 0,167e+03 0,153e+03 0,122e+03 0,951e+02 0,767e+02 0,688e+02 10 0.259e+03 0.257e+03 0.248e+03 0.228e+03 0.199e+03 0.166e+03 0.152e+03 0.121e+03 0.948e+02 0.781e+02 0.689e+02 1240 1241 9 0.250e+03 0.248e+03 0.242e+03 0.226e+03 0.197e+03 0.164e+03 0.148e+03 0.114e+03 0.866e+02 0.690e+02 0.000e+00 1242 8 0,230a+03 0,228a+03 0,226a+03 0,215a+03 0,190a+03 0,161a+03 0,141a+03 0,100a+03 0,693a+02 0,000a+00

1243 7 0.200e+03 0.199e+03 0.197e+03 0.190e+03 0.174e+03 0.157e+03 0.124e+03 0.697e+02 0.000e+00 1244 6 0.167e+03 0.166e+03 0.164e+03 0.161e+03 0.157e+03 0.154e+03 0.703e+02 0.000e+00 1245 5 0.153e+03 0.152e+03 0.148e+03 0.141e+03 0.124e+03 0.703e+02 0.000e+00 1246 4 0,122e+03 0,121e+03 0,114e+03 0,100e+03 0,697e+02 0,000e+00 1247 3 0.951e+02 0.948e+02 0.866e+02 0.693e+02 0.000e+00 1248 2 0.767e+02 0.781e+02 0.690e+02 0.000e+00 1249 1 0.688e+02 0.689e+02 0.000e+00 0.000e+00 1250 1251 plane k=18 1252 i i= 2 1253 12 0.000+00 0.000+00 0.000+00 0.000+00 0.000+00 0.000+00 0.000+00 0.000+00 0.000+00 0.000+00 0.000+00 0.000+00 1254 11 0.281e+03 0.280e+03 0.271e+03 0.249e+03 0.217e+03 0.180e+03 0.164e+03 0.131e+03 0.102e+03 0.823e+02 0.738e+02 1255 10 0.280e+03 0.278e+03 0.269e+03 0.248e+03 0.216e+03 0.179e+03 0.163e+03 0.130e+03 0.102e+03 0.839e+02 0.738e+02 1256 9 0.271e+03 0.269e+03 0.262e+03 0.245e+03 0.214e+03 0.177e+03 0.159e+03 0.123e+03 0.931e+02 0.740e+02 0.000e+00 1257 8 0.249e+03 0.248e+03 0.245e+03 0.233e+03 0.205e+03 0.174e+03 0.151e+03 0.108e+03 0.743e+02 0.000e+00 1258 7 0.217e+03 0.216e+03 0.214e+03 0.205e+03 0.188e+03 0.169e+03 0.133e+03 0.748e+02 0.000e+00 1259 6 0, 180e+03 0, 179e+03 0, 177e+03 0, 174e+03 0, 169e+03 0, 166e+03 0, 755e+02 0,000e+00 1260 5 0, 164e+03 0, 163e+03 0, 159e+03 0, 151e+03 0, 133e+03 0, 755e+02 0,000e+00 1261 4 0.1310+03 0.1300+03 0.1230+03 0.1080+03 0.7480+02 0.0000+00 1262 3 0,102e+03 0,102e+03 0,931e+02 0,743e+02 0,000e+00 1263 2 0.823e+02 0.839e+02 0.740e+02 0.000e+00 1264 1 0,738e+02 0,738e+02 0,000e+00 0,000e+00 1265 1266 plane k±17 1267 i i= 2 1268 12 0.000+00 0.000+00 0.000+00 0.000+00 0.000+00 0.000+00 0.000+00 0.000+00 0.000+00 0.000+00 0.000+00 0.000+00 1269 11 0.293e+03 0.293e+03 0.283e+03 0.261e+03 0.228e+03 0.190e+03 0.173e+03 0.139e+03 0.109e+03 0.881e+02 0.792e+02 1270 10 0,293e+03 0,290e+03 0,281e+03 0,259e+03 0,227e+03 0,189e+03 0,172e+03 0,138e+03 0,108e+03 0,897e+02 0,792e+02 1271 9 0.283e+03 0.281e+03 0.274e+03 0.257e+03 0.225e+03 0.187e+03 0.168e+03 0.130e+03 0.992e+02 0.795e+02 0.000e+00 1272 8 0.261e+03 0.259e+03 0.257e+03 0.244e+03 0.216e+03 0.183e+03 0.160e+03 0.115e+03 0.798e+02 0.000e+00 1273 7 0.228e+03 0.227e+03 0.225e+03 0.216e+03 0.198e+03 0.178e+03 0.141e+03 0.803e+02 0.000e+00 1274 6 0, 190e+03 0, 189e+03 0, 187e+03 0, 183e+03 0, 175e+03 0, 175e+03 0, 809e+02 0,000e+00 1275 5 0,173e+03 0,172e+03 0,168e+03 0,160e+03 0,141e+03 0,809e+02 0,000e+00 1276 4 0.139e+03 0.138e+03 0.130e+03 0.115e+03 0.803e+02 0.000e+00 1277 3 0.109e+03 0.108e+03 0.992e+02 0.798e+02 0.000e+00 1278 2 0.881e+02 0.897e+02 0.795e+02 0.000e+00 1279 1 0,792e+02 0,792e+02 0,000e+00 0,000e+00 1280 1281 plane k=16 1282 i= 2 1283 12 0.000e+00 0.000e+00 0.000e+00 0.000e+00 0.000e+00 0.000e+00 0.000e+00 0.000e+00 0.000e+00 0.000e+00 0.000e+00 1284 11 0.292e+03 0.291e+03 0.281e+03 0.260e+03 0.229e+03 0.192e+03 0.176e+03 0.142e+03 0.113e+03 0.925e+02 0.838e+02 1285 10 0,291e+03 0,288e+03 0,279e+03 0,259e+03 0,227e+03 0,192e+03 0,175e+03 0,141e+03 0,112e+03 0,941e+02 0,838e+02 1286 9 0.281e+03 0.279e+03 0.273e+03 0.256e+03 0.225e+03 0.190e+03 0.171e+03 0.134e+03 0.104e+03 0.840e+02 0.000e+00 1287 8 0.260e+03 0.259e+03 0.256e+03 0.244e+03 0.217e+03 0.186e+03 0.163e+03 0.119e+03 0.843e+02 0.000e+00 1288 7 0,229e+03 0,227e+03 0,225e+03 0,217e+03 0,199e+03 0,181e+03 0,144e+03 0,848e+02 0,000e+00

l

1289 6 0, 192e+03 0, 192e+03 0, 190e+03 0, 186e+03 0, 181e+03 0, 178e+03 0, 855e+02 0,000e+00 1290 5 0.176e+03 0.175e+03 0.171e+03 0.163e+03 0.144e+03 0.855e+02 0.000e+00 1291 4 0.142e+03 0.141e+03 0.134e+03 0.119e+03 0.848e+02 0.000e+00 1292 3 0.113e+03 0.112e+03 0.104e+03 0.843e+02 0.000e+00 1293 2 0,925e+02 0,941e+02 0,840e+02 0,000e+00 1294 1 0.838e+02 0.838e+02 0.000e+00 0.000e+00 1295 1296 plane k=15 1297 i= 2 1 1298 12 0.000e+00 0.000e+00 0.000e+00 0.000e+00 0.000e+00 0.000e+00 0.000e+00 0.000e+00 0.000e+00 0.000e+00 0.000e+00 1299 11 0.293e+03 0.292e+03 0.282e+03 0.261e+03 0.230e+03 0.193e+03 0.177e+03 0.143e+03 0.114e+03 0.935e+02 0.846e+02 1300 10 0.292e+03 0.289e+03 0.280e+03 0.260e+03 0.228e+03 0.193e+03 0.176e+03 0.142e+03 0.114e+03 0.951e+02 0.847e+02 1301 9 0.282e+03 0.280e+03 0.274e+03 0.257e+03 0.225e+03 0.191e+03 0.172e+03 0.135e+03 0.105e+03 0.849e+02 0.000e+00 1302 8 0.261e+03 0.260e+03 0.257e+03 0.245e+03 0.218e+03 0.187e+03 0.164e+03 0.120e+03 0.852e+02 0.000e+00 1303 7 0.230e+03 0.228e+03 0.226e+03 0.218e+03 0.200e+03 0.183e+03 0.146e+03 0.857e+02 0.000e+00 1304 6 0, 193e+03 0, 193e+03 0, 191e+03 0, 187e+03 0, 183e+03 0, 179e+03 0, 864e+02 0,000e+00 1305 5 0, 177e+03 0, 176e+03 0, 172e+03 0, 164e+03 0, 146e+03 0, 864e+02 0, 000e+00 1306 4 0.143e+03 0.142e+03 0.135e+03 0.120e+03 0.857e+02 0.000e+00 1307 3 0,114e+03 0,114e+03 0,105e+03 0,852e+02 0,000e+00 1308 2 0.935e+02 0.951e+02 0.849e+02 0.000e+00 1309 1 0,846e+02 0,847e+02 0,000e+00 0,000e+00 1310 1311 plane k=14 1312 i i= 2 1313 12 0.000e+00 0.000e+00 0.000e+00 0.000e+00 0.000e+00 0.000e+00 0.000e+00 0.000e+00 0.000e+00 0.000e+00 0.000e+00 1314 11 0.298e+03 0.297e+03 0.287e+03 0.265e+03 0.233e+03 0.194e+03 0.177e+03 0.142e+03 0.112e+03 0.909e+02 0.817e+02 1315 10 0.297e+03 0.295e+03 0.285e+03 0.264e+03 0.231e+03 0.194e+03 0.176e+03 0.141e+03 0.112e+03 0.925e+02 0.818e+02 1316 9 0.287e+03 0.285e+03 0.279e+03 0.261e+03 0.229e+03 0.191e+03 0.172e+03 0.134e+03 0.102e+03 0.820e+02 0.000e+00 1317 8 0.265e+03 0.264e+03 0.261e+03 0.249e+03 0.220e+03 0.187e+03 0.164e+03 0.118e+03 0.823e+02 0.000e+00 7 0.233e+03 0.231e+03 0.229e+03 0.220e+03 0.202e+03 0.183e+03 0.145e+03 0.828e+02 0.000e+00 1318 1319 6 0.194e+03 0.194e+03 0.191e+03 0.187e+03 0.183e+03 0.180e+03 0.835e+02 0.000e+00 1320 5 0,177e+03 0,176e+03 0,172e+03 0,164e+03 0,145e+03 0,835e+02 0,000e+00 1321 4 0,142e+03 0,141e+03 0,134e+03 0,118e+03 0,828e+02 0,000e+00 1322 3 0,112e+03 0,112e+03 0,102e+03 0,823e+02 0,000e+00 1323 2 0,909e+02 0,925e+02 0,820e+02 0,000e+00 1324 1 0.817e+02 0.818e+02 0.000e+00 0.000e+00 1325 1326 plane k=13 1327 1= 2 1328 12 0.000e+00 0.000e+00 0.000e+00 0.000e+00 0.000e+00 0.000e+00 0.000e+00 0.000e+00 0.000e+00 0.000e+00 0.000e+00 1329 11 0.293e+03 0.293e+03 0.283e+03 0.261e+03 0.228e+03 0.190e+03 0.172e+03 0.138e+03 0.108e+03 0.868e+02 0.776e+02 1330 10 0.293e+03 0.290e+03 0.281e+03 0.259e+03 0.227e+03 0.189e+03 0.172e+03 0.137e+03 0.107e+03 0.884e+02 0.777e+02 1331 9 0.283e+03 0.281e+03 0.274e+03 0.257e+03 0.225e+03 0.187e+03 0.168e+03 0.130e+03 0.983e+02 0.779e+02 0.000e+00 1332 8 0.261e+03 0.259e+03 0.257e+03 0.244e+03 0.216e+03 0.183e+03 0.159e+03 0.114e+03 0.783e+02 0.000e+00 1333 7 0.228e+03 0.227e+03 0.225e+03 0.216e+03 0.197e+03 0.178e+03 0.140e+03 0.788e+02 0.000e+00 1334 6 0, 190e+03 0, 189e+03 0, 187e+03 0, 183e+03 0, 178e+03 0, 175e+03 0, 795e+02 0,000e+00

1335 5 0,172e+03 0,172e+03 0,168e+03 0,159e+03 0,140e+03 0,795e+02 0,000e+00 1336 4 0,138e+03 0,137e+03 0,130e+03 0,114e+03 0,788e+02 0,000e+00 1337 3 0.108e+03 0.107e+03 0.983e+02 0.783e+02 0.000e+00 1338 2 0.868e+02 0.884e+02 0.779e+02 0.000e+00 1339 1 0.776e+02 0.777e+02 0.000e+00 0.000e+00 1340 1341 plane k=12 1342 1 1=2 1343 12 0.000e+00 0.000e+00 0.000e+00 0.000e+00 0.000e+00 0.000e+00 0.000e+00 0.000e+00 0.000e+00 0.000e+00 0.000e+00 1344 11 0.285e+03 0.284e+03 0.275e+03 0.253e+03 0.221e+03 0.182e+03 0.166e+03 0.132e+03 0.103e+03 0.825e+02 0.737e+02 1345 10 0,284e+03 0,282e+03 0,273e+03 0,251e+03 0,219e+03 0,182e+03 0,165e+03 0,131e+03 0,103e+03 0,842e+02 0,737e+02 1346 9 0.275e+03 0.273e+03 0.267e+03 0.249e+03 0.217e+03 0.180e+03 0.161e+03 0.124e+03 0.938e+02 0.740e+02 0.000e+00 1347 8 0.253e+03 0.251e+03 0.249e+03 0.237e+03 0.209e+03 0.176e+03 0.153e+03 0.109e+03 0.743e+02 0.000e+00 1348 7 0.221e+03 0.219e+03 0.217e+03 0.209e+03 0.190e+03 0.172e+03 0.135e+03 0.748e+02 0.000e+00 1349 6 0, 182e+03 0, 182e+03 0, 180e+03 0, 176e+03 0, 172e+03 0, 168e+03 0, 754e+02 0,000e+00 1350 5 0,166e+03 0,165e+03 0,161e+03 0,153e+03 0,135e+03 0,754e+02 0,000e+00 1351 4 0,132e+03 0,131e+03 0,124e+03 0,109e+03 0,748e+02 0,000e+00 1352 3 0,103e+03 0,103e+03 0,938e+02 0,743e+02 0,000e+00 1353 2 0.825e+02 0.842e+02 0.740e+02 0.000e+00 1354 1 0.737e+02 0.737e+02 0.000e+00 0.000e+00 1355 1356 plane k=11 1357 1 1=2 1358 12 0,000+00 0,000+00 0,000+00 0,000+00 0,000+00 0,000+00 0,000+00 0,000+00 0,000+00 0,000+00 0,000+00 0,000+00 1359 11 0.273e+03 0.272e+03 0.263e+03 0.242e+03 0.211e+03 0.174e+03 0.158e+03 0.126e+03 0.981e+02 0.788e+02 0.703e+02 10 0, 272e+03 0, 270e+03 0, 261e+03 0, 240e+03 0, 209e+03 0, 174e+03 0, 157e+03 0, 125e+03 0, 979e+02 0, 803e+02 0, 704e+02 1360 1361 9 0.263e+03 0.261e+03 0.255e+03 0.238e+03 0.207e+03 0.172e+03 0.154e+03 0.119e+03 0.895e+02 0.706e+02 0.000e+00 1362 8 0_242e+03 0_240e+03 0_238e+03 0_226e+03 0_199e+03 0_168e+03 0_146e+03 0_104e+03 0_709e+02 0_000e+00 1363 7 0.2116+03 0.2096+03 0.2076+03 0.1996+03 0.1826+03 0.1646+03 0.1286+03 0.7146+02 0.0006+00 1364 6 0, 174e+03 0, 174e+03 0, 172e+03 0, 168e+03 0, 164e+03 0, 161e+03 0, 720e+02 0,000e+00 1365 5 0.158e+03 0.157e+03 0.154e+03 0.146e+03 0.128e+03 0.720e+02 0.000e+00 1366 4 0.126e+03 0.125e+03 0.119e+03 0.104e+03 0.714e+02 0.000e+00 1367 3 0.981e+02 0.979e+02 0.895e+02 0.709e+02 0.000e+00 1368 2 0.788e+02 0.803e+02 0.706e+02 0.000e+00 1369 1 0.703e+02 0.704e+02 0.000e+00 0.000e+00 1370 1371 plane k=10 1372 j [= 2 1373 12 0_000e+00 0_000e+00 0_000e+00 0_000e+00 0_000e+00 0_000e+00 0_000e+00 0_000e+00 0_000e+00 0_000e+00 0_000e+00 1374 11 0,256e+03 0,256e+03 0,248e+03 0,228e+03 0,200e+03 0,167e+03 0,151e+03 0,120e+03 0,939e+02 0,757e+02 0,677e+02 1375 10 0,256e+03 0,254e+03 0,246e+03 0,227e+03 0,199e+03 0,166e+03 0,150e+03 0,119e+03 0,938e+02 0,772e+02 0,678e+02 1376 9 0.248e+03 0.246e+03 0.241e+03 0.226e+03 0.197e+03 0.164e+03 0.146e+03 0.113e+03 0.858e+02 0.680e+02 0.000e+00 1377 8 0,228e+03 0,227e+03 0,226e+03 0,215e+03 0,189e+03 0,160e+03 0,139e+03 0,994e+02 0,683e+02 0,000e+00 1378 7 0.200e+03 0.199e+03 0.197e+03 0.189e+03 0.172e+03 0.155e+03 0.122e+03 0.687e+02 0.000e+00 1379 6 0.167e+03 0.166e+03 0.164e+03 0.160e+03 0.155e+03 0.152e+03 0.692e+02 0.000e+00 1380 5 0.151e+03 0.150e+03 0.146e+03 0.139e+03 0.122e+03 0.692e+02 0.000e+00

1381 4 0.120e+03 0.119e+03 0.113e+03 0.994e+02 0.687e+02 0.000e+00 1382 3 0.939e+02 0.938e+02 0.858e+02 0.683e+02 0.000e+00 1383 2 0.757e+02 0.772e+02 0.680e+02 0.000e+00 1384 1 0.677e+02 0.678e+02 0.000e+00 0.000e+00 1385 1386 plane k= 9 1387 1 1= 2 12 0.000+00 0.000+00 0.000+00 0.000+00 0.000+00 0.000+00 0.000+00 0.000+00 0.000+00 0.000+00 0.000+00 0.000+00 1388 11 0_237e+03 0_237e+03 0_230e+03 0_213e+03 0_191e+03 0_162e+03 0_145e+03 0_115e+03 0_905e+02 0_733e+02 0_658e+02 1389 1390 10 0.237e+03 0.236e+03 0.229e+03 0.212e+03 0.189e+03 0.161e+03 0.144e+03 0.114e+03 0.904e+02 0.747e+02 0.659e+02 1391 9 0_230e+03 0_229e+03 0_225e+03 0_212e+03 0_188e+03 0_158e+03 0_140e+03 0_109e+03 0_828e+02 0_660e+02 0_000e+00 1392 8 0.213e+03 0.212e+03 0.212e+03 0.202e+03 0.179e+03 0.153e+03 0.132e+03 0.952e+02 0.663e+02 0.000e+00 1393 7 0.191e+03 0.189e+03 0.188e+03 0.179e+03 0.160e+03 0.144e+03 0.114e+03 0.666e+02 0.000e+00 1394 6 0, 162e+03 0, 161e+03 0, 158e+03 0, 153e+03 0, 144e+03 0, 141e+03 0, 671e+02 0,000e+00 1395 5 0,145e+03 0,144e+03 0,140e+03 0,132e+03 0,114e+03 0,671e+02 0,000e+00 1396 4 0.115e+03 0.114e+03 0.109e+03 0.952e+02 0.666e+02 0.000e+00 1397 3 0.905e+02 0.904e+02 0.828e+02 0.663e+02 0.000e+00 1398 2 0.733e+02 0.747e+02 0.660e+02 0.000e+00 1399 1 0.658e+02 0.659e+02 0.000e+00 0.000e+00 1400 1401 plane k= 8 1402 1 1= 2 12 0,000+00 0,000+00 0,000+00 0,000+00 0,000+00 0,000+00 0,000+00 0,000+00 0,000+00 0,000+00 0,000+00 0,000+00 1403 1404 11 0.213e+03 0.213e+03 0.208e+03 0.195e+03 0.180e+03 0.146e+03 0.128e+03 0.109e+03 0.878e+02 0.714e+02 0.642e+02 1405 10 0.213e+03 0.212e+03 0.207e+03 0.194e+03 0.179e+03 0.147e+03 0.128e+03 0.109e+03 0.875e+02 0.727e+02 0.643e+02 1406 9 0.208e+03 0.207e+03 0.204e+03 0.194e+03 0.178e+03 0.145e+03 0.124e+03 0.103e+03 0.800e+02 0.644e+02 0.000e+00 1407 8 0,195e+03 0,194e+03 0,194e+03 0,186e+03 0,168e+03 0,136e+03 0,115e+03 0,892e+02 0,646e+02 0,000e+00 1408 7 0.180e+03 0.179e+03 0.178e+03 0.168e+03 0.143e+03 0.122e+03 0.101e+03 0.649e+02 0.000e+00. 1409 6 0,146e+03 0,147e+03 0,145e+03 0,136e+03 0,122e+03 0,121e+03 0,653e+02 0,000e+00 1410 5 0,128e+03 0,128e+03 0,124e+03 0,115e+03 0,101e+03 0,653e+02 0,000e+00 1411 4 0.109e+03 0.109e+03 0.103e+03 0.892e+02 0.649e+02 0.000e+00 1412 3 0.878e+02 0.875e+02 0.800e+02 0.646e+02 0.000e+00 1413 2 0,714e+02 0,727e+02 0,644e+02 0,000e+00 1414 1 0.642e+02 0.643e+02 0.000e+00 0.000e+00 1415 1416 plane k= 7 1417 1 1= 2 1418 12 0,000+00 0,000+00 0,000+00 0,000+00 0,000+00 0,000+00 0,000+00 0,000+00 0,000+00 0,000+00 0,000+00 0,000+00 1419 11 0.181e+03 0.181e+03 0.178e+03 0.167e+03 0.156e+03 0.122e+03 0.103e+03 0.903e+02 0.774e+02 0.672e+02 0.628e+02 1420 10 0.181e+03 0.181e+03 0.177e+03 0.167e+03 0.156e+03 0.122e+03 0.103e+03 0.899e+02 0.773e+02 0.681e+02 0.628e+02 1421 9 0.178e+03 0.177e+03 0.175e+03 0.167e+03 0.155e+03 0.121e+03 0.101e+03 0.867e+02 0.727e+02 0.630e+02 0.000e+00 1422 8 0,167e+03 0,167e+03 0,167e+03 0,161e+03 0,146e+03 0,115e+03 0,959e+02 0,786e+02 0,631e+02 0,000e+00 1423 7 0,156e+03 0,156e+03 0,155e+03 0,146e+03 0,123e+03 0,104e+03 0,885e+02 0,634e+02 0,000e+00 1424 6 0.122e+03 0.122e+03 0.121e+03 0.115e+03 0.104e+03 0.103e+03 0.636e+02 0.000e+00 1425 5 0,103e+03 0,103e+03 0,101e+03 0,959e+02 0,885e+02 0,636e+02 0,000e+00 1426 4 0.903e+02 0.899e+02 0.867e+02 0.786e+02 0.634e+02 0.000e+00

1427 3 0,774e+02 0,773e+02 0,727e+02 0,631e+02 0,000e+00 1428 2 0.672e+02 0.681e+02 0.630e+02 0.000e+00 1429 1 0.628e+02 0.628e+02 0.000e+00 0.000e+00 1430 1431 plane k= 6 1432 i i= 2 1433 12 0.000e+00 0.000e+00 0.000e+00 0.000e+00 0.000e+00 0.000e+00 0.000e+00 0.000e+00 0.000e+00 0.000e+00 0.000e+00 11 0.141e+03 0.141e+03 0.139e+03 0.131e+03 0.124e+03 0.990e+02 0.856e+02 0.774e+02 0.698e+02 0.641e+02 0.616e+02 1434 1435 10 0,141e+03 0,141e+03 0,138e+03 0,131e+03 0,123e+03 0,993e+02 0,856e+02 0,772e+02 0,698e+02 0,646e+02 0,617e+02 1436 9 0,139e+03 0,138e+03 0,137e+03 0,132e+03 0,123e+03 0,987e+02 0,845e+02 0,754e+02 0,672e+02 0,618e+02 0,000e+00 1437 8 0,131e+03 0,131e+03 0,132e+03 0,128e+03 0,117e+03 0,949e+02 0,815e+02 0,708e+02 0,619e+02 0,000e+00 1438 7 0,124e+03 0,123e+03 0,123e+03 0,117e+03 0,101e+03 0,876e+02 0,776e+02 0,621e+02 0,000e+00 6 0,990e+02 0,993e+02 0,987e+02 0,949e+02 0,876e+02 0.868e+02 0.623e+02 0.000e+00 1439 5 0.856e+02 0.856e+02 0.845e+02 0.815e+02 0.776e+02 0.623e+02 0.000e+00 1440 1441 4 0.774e+02 0.772e+02 0.754e+02 0.708e+02 0.621e+02 0.000e+00 1442 3 0.698e+02 0.698e+02 0.672e+02 0.619e+02 0.000e+00 1443 2 0.641e+02 0.646e+02 0.618e+02 0.000e+00 1444 1 0.616e+02 0.617e+02 0.000e+00 0.000e+00 1445 1446 plane k= 5 1447 1 1= 2 1448 12 0.000e+00 0.000e+00 0.000e+00 0.000e+00 0.000e+00 0.000e+00 0.000e+00 0.000e+00 0.000e+00 0.000e+00 0.000e+00 1449 11 0.923e+02 0.927e+02 0.917e+02 0.885e+02 0.855e+02 0.756e+02 0.697e+02 0.665e+02 0.637e+02 0.617e+02 0.608e+02 1450 10 0.927e+02 0.924e+02 0.913e+02 0.885e+02 0.851e+02 0.758e+02 0.697e+02 0.665e+02 0.638e+02 0.619e+02 0.609e+02 9 0.9176+02 0.9136+02 0.9136+02 0.8896+02 0.8536+02 0.7576+02 0.6946+02 0.6596+02 0.6296+02 0.6106+02 0.0006+00 1451 1452 8 0.885e+02 0.885e+02 0.889e+02 0.873e+02 0.831e+02 0.743e+02 0.685e+02 0.643e+02 0.611e+02 0.000e+00 1453 7 0.855e+02 0.851e+02 0.853e+02 0.831e+02 0.764e+02 0.717e+02 0.675e+02 0.613e+02 0.000e+00 1454 6 0.756e+02 0.758e+02 0.757e+02 0.743e+02 0.717e+02 0.714e+02 0.614e+02 0.000e+00 1455 5 0.697e+02 0.697e+02 0.694e+02 0.685e+02 0.675e+02 0.614e+02 0.000e+00 1456 4 0.665e+02 0.665e+02 0.659e+02 0.643e+02 0.613e+02 0.000e+00 1457 3 0,637e+02 0,638e+02 0,629e+02 0,611e+02 0,000e+00 1458 2 0.617e+02 0.619e+02 0.610e+02 0.000e+00 1459 1 0,608e+02 0,609e+02 0,000e+00 0,000e+00 1460 1461 plane k= 4 1462 1 1=2 1463 12 0.000e+00 0.000e+00 0.000e+00 0.000e+00 0.000e+00 0.000e+00 0.000e+00 0.000e+00 0.000e+00 0.000e+00 0.000e+00 1464 11 0.653e+02 0.653e+02 0.650e+02 0.644e+02 0.635e+02 0.624e+02 0.618e+02 0.613e+02 0.610e+02 0.609e+02 0.608e+02 1465 10 0.653e+02 0.652e+02 0.650e+02 0.644e+02 0.636e+02 0.625e+02 0.618e+02 0.614e+02 0.611e+02 0.609e+02 0.609e+02 1466 9 0.650e+02 0.650e+02 0.647e+02 0.643e+02 0.635e+02 0.625e+02 0.618e+02 0.614e+02 0.611e+02 0.611e+02 0.000e+00 1467 8 0.644e+02 0.644e+02 0.643e+02 0.639e+02 0.633e+02 0.625e+02 0.619e+02 0.615e+02 0.612e+02 0.000e+00 1468 7 0.635e+02 0.636e+02 0.635e+02 0.633e+02 0.631e+02 0.630e+02 0.620e+02 0.615e+02 0.000e+00 1469 6 0.624e+02 0.625e+02 0.625e+02 0.625e+02 0.630e+02 0.627e+02 0.619e+02 0.000e+00 1470 5 0.618e+02 0.618e+02 0.618e+02 0.619e+02 0.620e+02 0.619e+02 0.000e+00 1471 4 0.613e+02 0.614e+02 0.614e+02 0.615e+02 0.615e+02 0.000e+00 1472 3 0.610e+02 0.611e+02 0.611e+02 0.612e+02 0.000e+00

B.32

- E

1473 2 0.609e+02 0.609e+02 0.610e+02 0.000e+00 . 1474 1 0.608e+02 0.609e+02 0.000e+00 0.000e+00 1475 1476 olane k= 3 1477 J I= 2 1478 12 0.000+00 0.000+00 0.000+00 0.000+00 0.000+00 0.000+00 0.000+00 0.000+00 0.000+00 0.000+00 0.000+00 0.000+00 1479 11 0.642e+02 0.642e+02 0.639e+02 0.634e+02 0.628e+02 0.621e+02 0.616e+02 0.612e+02 0.610e+02 0.608e+02 0.608e+02 1480 10 0.642e+02 0.641e+02 0.639e+02 0.634e+02 0.628e+02 0.621e+02 0.617e+02 0.613e+02 0.610e+02 0.609e+02 0.608e+02 1481 9 0.639e+02 0.639e+02 0.637e+02 0.633e+02 0.627e+02 0.621e+02 0.617e+02 0.613e+02 0.611e+02 0.610e+02 0.000e+00 1482 8 0.634e+02 0.634e+02 0.633e+02 0.630e+02 0.626e+02 0.621e+02 0.617e+02 0.613e+02 0.612e+02 0.000e+00 1483 7 0.628e+02 0.628e+02 0.627e+02 0.626e+02 0.623e+02 0.620e+02 0.616e+02 0.614e+02 0.000e+00 1484 6 0,621e+02 0,621e+02 0,621e+02 0,621e+02 0,620e+02 0,617e+02 0,615e+02 0,000e+00 1485 5 0.616e+02 0.617e+02 0.617e+02 0.617e+02 0.616e+02 0.615e+02 0.000e+00 1486 4 0,612e+02 0,613e+02 0,613e+02 0,613e+02 0,614e+02 0,000e+00 1487 3 0.610e+02 0.610e+02 0.611e+02 0.612e+02 0.000e+00 1488 2 0.608e+02 0.609e+02 0.610e+02 0.000e+00 1489 1 0,608e+02 0,608e+02 0,000e+00 0,000e+00 1490 1491 plane k= 2 1492 i 1= 2 1493 12 0,000+00 0,000+00 0,000+00 0,000+00 0,000+00 0,000+00 0,000+00 0,000+00 0,000+00 0,000+00 0,000+00 0,000+00 1494 11 0.638e+02 0.638e+02 0.635e+02 0.631e+02 0.625e+02 0.620e+02 0.615e+02 0.611e+02 0.609e+02 0.607e+02 0.606e+02 1495 10 0.638e+02 0.637e+02 0.635e+02 0.631e+02 0.625e+02 0.620e+02 0.616e+02 0.612e+02 0.609e+02 0.607e+02 0.607e+02 1496 9 0.635e+02 0.635e+02 0.633e+02 0.630e+02 0.625e+02 0.619e+02 0.616e+02 0.612e+02 0.610e+02 0.608e+02 0.000e+00 1497 8 0.631e+02 0.631e+02 0.630e+02 0.627e+02 0.623e+02 0.619e+02 0.615e+02 0.612e+02 0.610e+02 0.000e+00 1498 7 0,625e+02 0,625e+02 0,625e+02 0,623e+02 0,620e+02 0,617e+02 0,614e+02 0,612e+02 0,000e+00 1499 6 0.620e+02 0.620e+02 0.619e+02 0.619e+02 0.617e+02 0.614e+02 0.612e+02 0.000e+00 1500 5 0.615e+02 0.616e+02 0.616e+02 0.615e+02 0.614e+02 0.612e+02 0.000e+00 1501 4 0.611e+02 0.612e+02 0.612e+02 0.612e+02 0.612e+02 0.000e+00 1502 3 0.609e+02 0.609e+02 0.610e+02 0.610e+02 0.000e+00 1503 2 0.607e+02 0.607e+02 0.608e+02 0.000e+00 1504 1 0.606e+02 0.607e+02 0.000e+00 0.000e+00 1505 1506 plane k= 1 1507 | |= 2 1508 12 0.000e+00 0.000e+00 0.000e+00 0.000e+00 0.000e+00 0.000e+00 0.000e+00 0.000e+00 0.000e+00 0.000e+00 0.000e+00 1509 11 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.000e+00 1510 10 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.000e+00 1511 9 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.000e+00 1512 8 0,270e+02 0,270e+02 0,270e+02 0,270e+02 0,270e+02 0,270e+02 0,270e+02 0,270e+02 0,270e+02 0,000e+00 1513 7 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.000e+00 1514 6 0,270e+02 0,270e+02 0,270e+02 0,270e+02 0,270e+02 0,270e+02 0,270e+02 0,000e+00 1515 5 0,270e+02 0,270e+02 0,270e+02 0,270e+02 0,270e+02 0,270e+02 0,000e+00 4 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.000e+00 1516 1517 3 0,270e+02 0,270e+02 0,270e+02 0,270e+02 0,000e+00 1518 2 0,270e+02 0,270e+02 0,270e+02 0,000e+00

B.33

**(** →

1519	1 0.000e+00	0.000e+00	0.000e+00	0.0000+00								
1520												
1521 1												
1522					불 불 :	* side tem	perature,	c * * *				
1523							-					
1524						pla	ne k=30					
1525	i j= 2											
1526	2 0.2700+02	0,270e+02	0.270e+02	0.270e+02	0,270e+02	0.270e+02	0.270e+02	0.270e+02	0.270e+02	0.270e+02	0.270e+02	0 <b>.270e+02</b>
1527	3 0,270e+02	0.270.+02	0.270e+02	0.2700+02	0.270e+02	0.270e+02	0.270e+02	0.2700+02	0.270e+02	0.2700+02	0,270e+02	0.270e+02
1528	4 0,270e+02	0.270e+02	0.270e+02	0.270e+02	0.270e+02	0.270e+02	0.2700+02	0.270e+02	0.270e+02	0.270e+02	0.270e+02	0,270e+02
1529	5 0.270e+02	0,270e+02	0.270e+02	0.270e+02	0.270e+02	0.270e+02	0.2700+02	0,270e+02	0.270e+02	0,270e+02	0.2700+02	0,270e+02
1530	6 0.270e+02	0.270e+02	0.270e+02	0.270.+02	0.270e+02	0.270e+02	0,270e+02	0.270e+02	0.270e+02	0,2700+02	0.270+02	0.270e+02
1531	7 0.000e+00	0,000e+00	0.000e+00	0.000e+00	0.000e+00	0.000+00	0.000e+00	0.000e+00	0.000e+00	0.000e+00	0.000e+00	0.000e+00
1532											-	
1533						pla	ne k=29					
1534	i j= 2					-						
1535	2 0,515e+02	0,515e+02	0.516e+02	0,5160+02	0.517e+02	0.517e+02	0.517e+02	0,517e+02	0.516e+02	0,516e+02	0.515e+02	0.515e+02
1536	3 0 <b>.</b> 516e+02	0.516e+02	0,516e+02	0.517e+02	0.517e+02	0.517e+02	0,517e+02	0.517e+02	0.517e+02	0.516e+02	0.5160+02	0 <b>.</b> 516e+02
1537	4 0,5168+02	0.5170+02	0.5170+02	0.518e+02	0.518e+02	0.5180+02	0.518e+02	0.5180+02	0.518e+02	0.517e+02	0.517e+02	0,516e+02
1538	5 0.516e+02	0.517e+02	0.5170+02	0.518e+02	0.518e+02	0.518e+02	0.5180+02	0.518e+02	0.518e+02	0.517e+02	0.517e+02	0.516e+02
1539	6 0,516e+02	0.517e+02	0.517e+02	0.517e+02	0,518e+02	0.518e+02	0,518e+02	0.518e+02	0.517e+02	0.517e+02	0,517e+02	0.516e+02
1540	7 0.270e+02	0.270e+02	0.270e+02	0.270e+02	0 <b>.270e+02</b>	0.270e+02	0.2700+02	0,270e+02	0,270e+02	0.270e+02	0.2700+02	0.270e+02
1541												
1542						pla	ne k=28					
1543	i j=2											
1544	2 0.516e+02	0,517e+02	0.517e+02	0.518e+02	0.518e+02	0.518e+02	0,518e+02	0,518e+02	0.518e+02	0.517e+02	0.517e+02	0.516e+02
1545	3 0.517e+02	0,517e+02	0.518e+02	0,518e+02	0,518e+02	0.518e+02	0.518e+02	0.518e+02	0.518e+02	0.518e+02	0.517e+02	0.517e+02
1546	4 0.519e+02	0.519e+02	0.519e+02	0.520e+02	0.520e+02	0.520e+02	0.5200+02	0.520e+02	0.520e+02	0.519e+02	0.519e+02	0.519e+02
1547	5 0.518e+02	0.519e+02	0.519e+02	0.520e+02	0.520e+02	0.5200+02	0.520e+02	0.520e+02	0.520e+02	0.519e+02	0.519e+02	0 <b>,</b> 518e+02
1548	6 0.518e+02	0 <b>.518e+</b> 02	0.519e+02	0.519e+02	0 <b>.520e+</b> 02	0.520e+02	0.520e+02	0.520e+02	0.519e+02	0 <b>.</b> 519e+02	0.518e+02	0.518e+02
1549	7 0 <b>.270e+02</b>	0.270e+02	0.270e+02	0 <b>.</b> 270e+02	0 <b>.</b> 270e+02	0.270e+02	0.270e+02	0.270e+02	0.270e+02	0 <b>.</b> 270e+02	0 <b>.270e+02</b>	0 <b>,270e+02</b>
1550												
1551						pla	ne k=27					
1552	i j= 2											
1553	2 0 <b>.</b> 519e+02	0.520e+02	0 <b>.</b> 520e+02	0.521e+02	0.521e+02	0.521e+02	0.521e+02	0.521e+02	0.521e+02	0 <b>.</b> 520e+02	0,520e+02	0 <b>.</b> 519e+02
1554	3 0,520e+02	0.521e+02	0 <b>.</b> 521e+02	0 <b>.</b> 522e+02	0,522e+02	0 <b>.</b> 522e+02	0 <b>.</b> 522e+02	0 <b>.</b> 522e+02	0.522e+02	0.5210+02	0 <b>.</b> 521e+02	0 <b>.</b> 520e+02
1555	4 0.522e+02	0,523e+02	0,523e+02	0.523e+02	0 <b>.</b> 524e+02	0 <b>.</b> 524e+02	0.5240+02	0,524e+02	0 <b>.</b> 523e+02	0 <b>.</b> 523e+02	0 <b>.</b> 523e+02	0 <b>.</b> 522e+02
1556	5 0.522e+02	0.5220+02	0.523e+02	0.523e+02	0,5240+02	0 <b>.</b> 524e+02	0.5240+02	0.524e+02	0 <b>.</b> 523e+02	0 <b>.</b> 523e+02	0,522e+02	0 <b>.</b> 522e+02
1557	6 0 <b>.</b> 522e+02	0.522e+02	0,522e+02	0.523e+02	0 <b>.</b> 523e+02	0.523e+02	0 <b>.</b> 523e+02	0.523e+02	0.523e+02	0.522e+02	0.522e+02	0 <b>.</b> 522e+02
1558	7 0 <b>.</b> 270 <del>0</del> +02	0,270e+02	0 <b>.</b> 270e+02	0,270e+02	0 <b>.</b> 270 <del>0</del> +02	0 <b>.</b> 270 <del>0</del> +02	0.270e+02	0 <b>.</b> 270e+02	0.270e+02	0.270e+02	0 <b>.</b> 270e+02	0 <b>,</b> 270e+02
1559												
1560						pla	ne k=26					
1560	j= 2	0 600 .00	A EQA	0 E00 .44		0 ETO					0 500	0 500 .00
1202	2 0.5280+02	U.528e+02	0.5296+02	0.5298+02	0.5290+02	0.5500+02	U.550e+02	U.529e+02	U. 529e+02	U. 529e+02	U. 528e+02	U. 528e+02
1202	> U. 528e+02	U.528e+02	0.5290+02	U, 529e+02	0.5298+02	0.5290+02	U.5290+02	0.5290+02	0.529e+02	0.5290+02	0.5280+02	0,5280+02
1204	4 U. 528e+02	U. 528e+02	U. 529e+02	v <b>.</b> 529e+02	U. 529e+02	v. 529e+02	U. 529e+02	U. 529e+02	U. 529e+02	U. 529e+02	U. 528e+02	U.528e+02

;

1565 1566 1567 7 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 1568 1569 plane k=25 1570 i i= 2 1571 2 0.539e+02 0.540e+02 0.540e+02 0.541e+02 0.541e+02 0.541e+02 0.541e+02 0.541e+02 0.541e+02 0.541e+02 0.540e+02 0.540e+02 0.539e+02 1572 3 0.539e+02 0.540e+02 0.540e+02 0.541e+02 0.541e+02 0.541e+02 0.541e+02 0.541e+02 0.541e+02 0.541e+02 0.540e+02 0.540e+02 0.539e+02 1573 4 0,539e+02 0,539e+02 0,540e+02 0,540e+02 0,541e+02 0,541e+02 0,541e+02 0,541e+02 0,540e+02 0,540e+02 0,539e+02 0,539e+02 0,539e+02 1574 5 0,539e+02 0,539e+02 0,540e+02 0,540e+02 0,540e+02 0,541e+02 0,541e+02 0,540e+02 0,540e+02 0,540e+02 0,539e+02 0,539e+02 0,539e+02 1575 6 0,538e+02 0,539e+02 0,539e+02 0,540e+02 0,540e+02 0,540e+02 0,540e+02 0,540e+02 0,540e+02 0,539e+02 0,539e+02 0,538e+02 1576 7 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.27 1577 1578 plane k=24 1579 i i= 2 1580 2 0.553e+02 0.553e+02 0.554e+02 0.555e+02 0.555e+02 0.555e+02 0.555e+02 0.555e+02 0.555e+02 0.555e+02 0.554e+02 0.553e+02 0.553e+02 0.553e+02 0.555e+02 0.556e+02 0.555e+02 0.556e+02 0.555e+02 0.556e+02 0.55 1581 1582 1583 5 0.552e+02 0.553e+02 0.553e+02 0.554e+02 0.555e+02 0.555e+02 0.555e+02 0.555e+02 0.555e+02 0.555e+02 0.553e+02 0.553e+02 0.553e+02 0.552e+02 1584 1585 7 0,270e+02 0,270e+02 0,270e+02 0,270e+02 0,270e+02 0,270e+02 0,270e+02 0,270e+02 0,270e+02 0,270e+02 0,270e+02 0,270e+02 0,270e+02 0,270e+02 0,270e+02 0,270e+02 0,270e+02 0,270e+02 0,270e+02 0,270e+02 0,270e+02 0,270e+02 0,270e+02 0,270e+02 0,270e+02 0,270e+02 0,270e+02 0,270e+02 0,270e+02 0,270e+02 0,270e+02 0,270e+02 0,270e+02 0,270e+02 0,270e+02 0,270e+02 0,270e+02 0,270e+02 0,270e+02 0,270e+02 0,270e+02 0,270e+02 0,270e+02 0,270e+02 0,270e+02 0,270e+02 0,270e+02 0,270e+02 0,270e+02 0,270e+02 0,270e+02 0,270e+02 0,270e+02 0,270e+02 0,270e+02 0,270e+02 0,270e+02 0,270e+02 0,270e+02 0,270e+02 0,270e+02 0,270e+02 0,270e+02 0,270e+02 0,270e+02 0,270e+02 0,270e+02 0,270e+02 0,270e+02 0,270e+02 0,270e+02 0,270e+02 0,270e+02 0,270e+02 0,270e+02 0,270e+02 0,270e+02 0,270e+02 0,270e+02 0,270e+02 0,270e+02 0,270e+02 0,270e+02 0,270e+02 0,270e+02 0,270e+02 0,270e+02 0,270e+02 0,270e+02 0,270e+02 0,270e+02 0,270e+02 0,270e+02 0,270e+02 0,270e+02 0,270e+02 0,270e+02 0,270e+02 0,270e+02 0,270e+02 0,270e+02 0,270e+02 0,270e+02 0,270e+02 0,270e+02 0,270e+02 0,270e+02 0,270e+02 0,270e+02 0,270e+02 0,270e+02 0,270e+02 0,270e+02 0,270e+02 0,270e+02 0,270e+02 0,270e+02 0,270e+02 0,270e+02 0,270e+02 0,270e+02 0,270e+02 0,270e+02 0,270e+02 0,270e+02 0,270e+02 0,270e+02 0,270e+02 0,270e+02 0,270e+02 0,270e+02 0,270e+02 0,270e+02 0,270e+02 0,270e+02 0,270e+02 0,270e+02 0,270e+02 0,270e+02 0,270e+02 0,270e+02 0,270e+02 0,270e+02 0,270e+02 0,270e+02 0,270e+02 0,270e+02 0,270e+02 0,270e+02 0,270e+02 0,270e+02 0,270e+02 0,270e+02 0,270e+02 0,270e+02 0,270e+02 0,270e+02 0,270e+02 0,270e+02 0,270e+02 0,270e+02 0,270e+02 0,270e+02 0,270e+02 0,270e+02 0,270e+02 0,270e+02 0,270e+02 0,270e+02 0,270e+02 0,270e+02 0,270e+02 0,270e+02 0,270e+02 0,270e+02 0,270e+02 0,270e+02 0,270e+02 0,270e+02 0,270e+02 0,270e+02 1586 1587 plane k=23 1588 i i= 2 1589 2 0,570e+02 0,570e+02 0,571e+02 0,572e+02 0,573e+02 0,574e+02 0,574e+02 0,573e+02 0,572e+02 0,571e+02 0,570e+02 0,57 3 0.570e+02 0.570e+02 0.571e+02 0.572e+02 0.573e+02 0.574e+02 0.574e+02 0.573e+02 0.572e+02 0.571e+02 0.570e+02 0.570e+02 1590 1591 4 0.569e+02 0.570e+02 0.571e+02 0.572e+02 0.573e+02 0.573e+02 0.573e+02 0.573e+02 0.572e+02 0.571e+02 0.570e+02 0.569e+02 1592 5 0.569e+02 0.569e+02 0.570e+02 0.571e+02 0.572e+02 0.573e+02 0.573e+02 0.572e+02 0.571e+02 0.570e+02 0.569e+02 0.569e+02 1593 6 0,568e+02 0,569e+02 0,570e+02 0,571e+02 0,572e+02 0,572e+02 0,572e+02 0,572e+02 0,571e+02 0,570e+02 0,569e+02 0,568e+02 1594 7 0,270e+02 0,270e+02 0,270e+02 0,270e+02 0,270e+02 0,270e+02 0,270e+02 0,270e+02 0,270e+02 0,270e+02 0,270e+02 0,270e+02 0,270e+02 0,270e+02 0,270e+02 0,270e+02 0,270e+02 0,270e+02 0,270e+02 0,270e+02 0,270e+02 0,270e+02 0,270e+02 0,270e+02 0,270e+02 0,270e+02 0,270e+02 0,270e+02 0,270e+02 0,270e+02 0,270e+02 0,270e+02 0,270e+02 0,270e+02 0,270e+02 0,270e+02 0,270e+02 0,270e+02 0,270e+02 0,270e+02 0,270e+02 0,270e+02 0,270e+02 0,270e+02 0,270e+02 0,270e+02 0,270e+02 0,270e+02 0,270e+02 0,270e+02 0,270e+02 0,270e+02 0,270e+02 0,270e+02 0,270e+02 0,270e+02 0,270e+02 0,270e+02 0,270e+02 0,270e+02 0,270e+02 0,270e+02 0,270e+02 0,270e+02 0,270e+02 0,270e+02 0,270e+02 0,270e+02 0,270e+02 0,270e+02 0,270e+02 0,270e+02 0,270e+02 0,270e+02 0,270e+02 0,270e+02 0,270e+02 0,270e+02 0,270e+02 0,270e+02 0,270e+02 0,270e+02 0,270e+02 0,270e+02 0,270e+02 0,270e+02 0,270e+02 0,270e+02 0,270e+02 0,270e+02 0,270e+02 0,270e+02 0,270e+02 0,270e+02 0,270e+02 0,270e+02 0,270e+02 0,270e+02 0,270e+02 0,270e+02 0,270e+02 0,270e+02 0,270e+02 0,270e+02 0,270e+02 0,270e+02 0,270e+02 0,270e+02 0,270e+02 0,270e+02 0,270e+02 0,270e+02 0,270e+02 0,270e+02 0,270e+02 0,270e+02 0,270e+02 0,270e+02 0,270e+02 0,270e+02 0,270e+02 0,270e+02 0,270e+02 0,270e+02 0,270e+02 0,270e+02 0,270e+02 0,270e+02 0,270e+02 0,270e+02 0,270e+02 0,270e+02 0,270e+02 0,270e+02 0,270e+02 0,270e+02 0,270e+02 0,270e+02 0,270e+02 0,270e+02 0,270e+02 0,270e+02 0,270e+02 0,270e+02 0,270e+02 0,270e+02 0,270e+02 0,270e+02 0,270e+02 0,270e+02 0,270e+02 0,270e+02 0,270e+02 0,270e+02 0,270e+02 0,270e+02 0,270e+02 0,270e+02 0,270e+02 0,270e+02 0,270e+02 0,270e+02 0,270e+02 0,270e+02 0,270e+02 0,270e+02 0,270e+02 0,270e+02 0,270e+02 0,270e+02 0,270e+02 0,270e+02 0,270e+02 0,270e+02 0,270e+02 0,270e+02 0,270e+02 0,270e+02 0,270e+02 0,270e+02 0,270e+02 0,270e+02 0,270e+02 0,270e+02 0,270e+02 0,270e+02 0,270e+02 0,270e+02 0,270e+02 0,270e+02 0,270e+02 0,270e+02 0,270e+02 0,270e+02 0,270e+02 0,270e+02 0,270e+02 0,270e+02 0,270e+02 0,270e+02 0,270e+02 0,270e+02 0,270e+02 0,270e+02 0,270 1595 1596 plane k=22 1597 1 _j= 2 1598 2 0,591e+02 0,591e+02 0,592e+02 0,594e+02 0,597e+02 0,600e+02 0,600e+02 0,597e+02 0,594e+02 0,592e+02 0,591e+02 0,591e+02 1599 3 0.590e+02 0.590e+02 0.591e+02 0.593e+02 0.595e+02 0.597e+02 0.597e+02 0.595e+02 0.595e+02 0.593e+02 0.591e+02 0.590e+02 0.590e+02 1600 4 0,589e+02 0,589e+02 0,590e+02 0,592e+02 0,594e+02 0,595e+02 0,595e+02 0,594e+02 0,592e+02 0,590e+02 0,589e+02 0,589e+02 0,589e+02 1601 5 0.588e+02 0.589e+02 0.590e+02 0.591e+02 0.593e+02 0.593e+02 0.593e+02 0.593e+02 0.591e+02 0.590e+02 0.589e+02 0.588e+02 1602 6 0,587e+02 0,588e+02 0,589e+02 0,590e+02 0,592e+02 0,593e+02 0,593e+02 0,592e+02 0,590e+02 0,589e+02 0,588e+02 0,587e+02 1603 7 0,270e+02 0,270e+02 0,270e+02 0,270e+02 0,270e+02 0,270e+02 0,270e+02 0,270e+02 0,270e+02 0,270e+02 0,270e+02 0,270e+02 0,270e+02 1604 1605 plane k=21 1606 1 .j= 2 1607 2 0.615e+02 0.615e+02 0.617e+02 0.619e+02 0.622e+02 0.626e+02 0.626e+02 0.622e+02 0.619e+02 0.617e+02 0.615e+02 0.615e+02 1608 3 0,614e+02 0,614e+02 0,616e+02 0,618e+02 0,620e+02 0,623e+02 0,623e+02 0,620e+02 0,618e+02 0,616e+02 0,614e+02 0,614e+02 1609 4 0.612e+02 0.613e+02 0.614e+02 0.616e+02 0.618e+02 0.620e+02 0.620e+02 0.618e+02 0.616e+02 0.614e+02 0.613e+02 0.612e+02 1610 5 0.611e+02 0.612e+02 0.613e+02 0.615e+02 0.617e+02 0.618e+02 0.618e+02 0.617e+02 0.615e+02 0.613e+02 0.612e+02 0.611e+02

1611 6 0,611e+02 0,611e+02 0,613e+02 0,614e+02 0,616e+02 0,617e+02 0,617e+02 0,616e+02 0,614e+02 0,613e+02 0,611e+02 0,611e+02 7 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270 1612 1613 1614 plane k=20 1615 i j= 2 1616 2 0.646e+02 0.647e+02 0.649e+02 0.651e+02 0.655e+02 0.659e+02 0.659e+02 0.655e+02 0.651e+02 0.649e+02 0.647e+02 0.646e+02 1617 3 0.645e+02 0.646e+02 0.648e+02 0.650e+02 0.653e+02 0.656e+02 0.655e+02 0.653e+02 0.650e+02 0.648e+02 0.646e+02 0.645e+02 4 0,644e+02 0,645e+02 0,646e+02 0,648e+02 0,651e+02 0,652e+02 0,652e+02 0,651e+02 0,648e+02 0,646e+02 0,645e+02 0,644e+02 1618 1619 5 0.643e+02 0.644e+02 0.645e+02 0.647e+02 0.649e+02 0.650e+02 0.650e+02 0.649e+02 0.647e+02 0.645e+02 0.644e+02 0.643e+02 1620 6 0.642e+02 0.643e+02 0.644e+02 0.646e+02 0.648e+02 0.650e+02 0.650e+02 0.648e+02 0.648e+02 0.644e+02 0.643e+02 0.642e+02 1621 7 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270 1622 1623 plane k=19 1624 1 j= 2 2 0.687e+02 0.688e+02 0.690e+02 0.693e+02 0.697e+02 0.702e+02 0.702e+02 0.697e+02 0.693e+02 0.693e+02 0.688e+02 0.688e+02 0.687e+02 1625 1626 3 0.686e+02 0.687e+02 0.688e+02 0.691e+02 0.694e+02 0.697e+02 0.697e+02 0.694e+02 0.691e+02 0.688e+02 0.687e+02 0.686e+02 1627 1628 5 0,683e+02 0,684e+02 0,686e+02 0,688e+02 0,690e+02 0,692e+02 0,692e+02 0,690e+02 0,688e+02 0,686e+02 0,684e+02 0,683e+02 1629 6 0.682e+02 0.683e+02 0.685e+02 0.685e+02 0.687e+02 0.689e+02 0.691e+02 0.691e+02 0.689e+02 0.687e+02 0.685e+02 0.683e+02 0.683e+02 0.682e+02 1630 7 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270 1631 1632 plane k=18 1633 **i**= 2 1 2 0.737e+02 0.738e+02 0.740e+02 0.743e+02 0.747e+02 0.753e+02 0.753e+02 0.747e+02 0.743e+02 0.740e+02 0.738e+02 0.737e+02 1634 1635 3 0.735e+02 0.736e+02 0.738e+02 0.741e+02 0.745e+02 0.748e+02 0.748e+02 0.745e+02 0.741e+02 0.738e+02 0.738e+02 0.735e+02 1636 4 0.734e+02 0.734e+02 0.736e+02 0.736e+02 0.742e+02 0.744e+02 0.744e+02 0.744e+02 0.742e+02 0.739e+02 0.736e+02 0.736e+02 0.734e+02 0.73 1637 5 0.732e+02 0.733e+02 0.735e+02 0.737e+02 0.740e+02 0.741e+02 0.741e+02 0.740e+02 0.737e+02 0.735e+02 0.735e+02 0.733e+02 0.732e+02 1638 6 0.731e+02 0.732e+02 0.734e+02 0.736e+02 0.739e+02 0.741e+02 0.741e+02 0.739e+02 0.736e+02 0.734e+02 0.734e+02 0.731e+02 1639 7 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.27 1640 1641 plane k=17 1642 i= 2 1 1643 2 0.791e+02 0.792e+02 0.794e+02 0.797e+02 0.802e+02 0.807e+02 0.807e+02 0.802e+02 0.797e+02 0.794e+02 0.792e+02 0.791e+02 1644 3 0.789e+02 0.790e+02 0.792e+02 0.795e+02 0.799e+02 0.802e+02 0.802e+02 0.799e+02 0.795e+02 0.795e+02 0.792e+02 0.790e+02 0.789e+02 1645 4 0,787e+02 0,788e+02 0,790e+02 0,793e+02 0,796e+02 0,798e+02 0,798e+02 0,796e+02 0,795e+02 0,793e+02 0,790e+02 0,788e+02 0,787e+02 1646 5 0.786e+02 0.787e+02 0.788e+02 0.791e+02 0.794e+02 0.795e+02 0.795e+02 0.794e+02 0.791e+02 0.788e+02 0.788e+02 0.786e+02 1647 6 0.785e+02 0.786e+02 0.788e+02 0.790e+02 0.793e+02 0.794e+02 0.794e+02 0.793e+02 0.790e+02 0.788e+02 0.788e+02 0.785e+02 1648 7 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270 1649 1650 ptane k≠16 1651 i _i= 2 1652 2 0.837e+02 0.838e+02 0.840e+02 0.843e+02 0.847e+02 0.853e+02 0.853e+02 0.847e+02 0.843e+02 0.840e+02 0.838e+02 0.837e+02 1653 3 0.835e+02 0.836e+02 0.838e+02 0.841e+02 0.844e+02 0.848e+02 0.848e+02 0.844e+02 0.841e+02 0.838e+02 0.838e+02 0.835e+02 1654 4 0.833e+02 0.834e+02 0.836e+02 0.838e+02 0.842e+02 0.844e+02 0.844e+02 0.842e+02 0.838e+02 0.838e+02 0.836e+02 0.834e+02 0.833e+02 1655 5 0.831e+02 0.832e+02 0.834e+02 0.837e+02 0.839e+02 0.841e+02 0.841e+02 0.839e+02 0.837e+02 0.834e+02 0.832e+02 0.831e+02 1656 6 0.831e+02 0.832e+02 0.833e+02 0.836e+02 0.838e+02 0.840e+02 0.840e+02 0.838e+02 0.838e+02 0.833e+02 0.833e+02 0.832e+02 0.831e+02

1657 7 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270 1658 1659 plane k=15 1660 1 j= 2 1661 2 0.845e+02 0.845e+02 0.849e+02 0.852e+02 0.856e+02 0.852e+02 0.852e+02 0.855e+02 0.855e+02 0.852e+02 0.849e+02 0.846e+02 0.846e+02 1662 3 0.844e+02 0.845e+02 0.847e+02 0.850e+02 0.853e+02 0.857e+02 0.857e+02 0.853e+02 0.853e+02 0.850e+02 0.847e+02 0.845e+02 0.844e+02 4 0.842e+02 0.843e+02 0.845e+02 0.847e+02 0.850e+02 0.853e+02 0.853e+02 0.850e+02 0.847e+02 0.845e+02 0.845e+02 0.843e+02 0.842e+02 1663 1664 5 0.840e+02 0.841e+02 0.843e+02 0.846e+02 0.848e+02 0.850e+02 0.850e+02 0.848e+02 0.848e+02 0.845e+02 0.843e+02 0.841e+02 0.841e+02 0.840e+02 1665 6 0.839e+02 0.840e+02 0.842e+02 0.845e+02 0.847e+02 0.849e+02 0.849e+02 0.847e+02 0.845e+02 0.842e+02 0.842e+02 0.839e+02 1666 7 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.27 1667 1668 plane k=14 1669 i= 2 1 1670 2 0.816e+02 0.817e+02 0.819e+02 0.823e+02 0.827e+02 0.833e+02 0.833e+02 0.827e+02 0.823e+02 0.819e+02 0.817e+02 0.816e+02 3 0.815e+02 0.815e+02 0.817e+02 0.820e+02 0.824e+02 0.828e+02 0.828e+02 0.824e+02 0.824e+02 0.820e+02 0.817e+02 0.815e+02 0.815e+02 1671 1672 4 0.813e+02 0.813e+02 0.815e+02 0.818e+02 0.821e+02 0.824e+02 0.824e+02 0.821e+02 0.818e+02 0.815e+02 0.815e+02 0.813e+02 0.81 1673 5 0.811e+02 0.812e+02 0.814e+02 0.816e+02 0.819e+02 0.821e+02 0.821e+02 0.819e+02 0.816e+02 0.814e+02 0.812e+02 0.811e+02 1674 6 0.810e+02 0.811e+02 0.813e+02 0.815e+02 0.818e+02 0.820e+02 0.820e+02 0.818e+02 0.815e+02 0.813e+02 0.813e+02 0.811e+02 0.810e+02 1675 7 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270 1676 1677 plane k=13 1678 i j= 2 1679 1680 3 0.774e+02 0.775e+02 0.777e+02 0.780e+02 0.784e+02 0.787e+02 0.787e+02 0.784e+02 0.784e+02 0.780e+02 0.777e+02 0.775e+02 0.775e+02 0.774e+02 1681 4 0.772e+02 0.773e+02 0.775e+02 0.775e+02 0.781e+02 0.783e+02 0.783e+02 0.783e+02 0.781e+02 0.778e+02 0.775e+02 0.775e+02 0.773e+02 0.772e+02 1682 5 0.770e+02 0.771e+02 0.773e+02 0.776e+02 0.779e+02 0.780e+02 0.780e+02 0.779e+02 0.775e+02 0.773e+02 0.771e+02 0.771e+02 0.770e+02 1683 6 0.770e+02 0.771e+02 0.772e+02 0.775e+02 0.778e+02 0.779e+02 0.779e+02 0.778e+02 0.775e+02 0.775e+02 0.772e+02 0.771e+02 0.771e+02 0.770e+02 1684 7 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270 1685 1686 plane k=12 1687 j= 2 1 1688 2 0.736e+02 0.737e+02 0.739e+02 0.742e+02 0.747e+02 0.752e+02 0.752e+02 0.747e+02 0.747e+02 0.739e+02 0.739e+02 0.737e+02 0.736e+02 1689 3 0.734e+02 0.735e+02 0.737e+02 0.740e+02 0.744e+02 0.747e+02 0.747e+02 0.744e+02 0.744e+02 0.737e+02 0.737e+02 0.735e+02 0.73 1690 4 0.733e+02 0.733e+02 0.735e+02 0.735e+02 0.738e+02 0.741e+02 0.743e+02 0.743e+02 0.741e+02 0.738e+02 0.735e+02 0.733e+02 0.733e+02 0.733e+02 1691 5 0.731e+02 0.732e+02 0.734e+02 0.736e+02 0.739e+02 0.741e+02 0.741e+02 0.739e+02 0.736e+02 0.734e+02 0.734e+02 0.731e+02 1692 6 0.730e+02 0.731e+02 0.733e+02 0.736e+02 0.738e+02 0.740e+02 0.740e+02 0.738e+02 0.738e+02 0.735e+02 0.733e+02 0.731e+02 0.730e+02 1693 7 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.27 1694 1695 plane k=11 1696 1 1= 2 1697 2 0.703e+02 0.703e+02 0.705e+02 0.708e+02 0.713e+02 0.718e+02 0.718e+02 0.713e+02 0.708e+02 0.705e+02 0.705e+02 0.703e+02 0.703e+02 1698 3 0.701e+02 0.702e+02 0.704e+02 0.707e+02 0.710e+02 0.713e+02 0.713e+02 0.710e+02 0.707e+02 0.704e+02 0.704e+02 0.702e+02 0.701e+02 1699 4 0.700e+02 0.700e+02 0.702e+02 0.705e+02 0.708e+02 0.710e+02 0.710e+02 0.708e+02 0.705e+02 0.702e+02 0.702e+02 0.700e+02 0.700e+02 1700 5 0.698e+02 0.699e+02 0.701e+02 0.703e+02 0.706e+02 0.707e+02 0.707e+02 0.706e+02 0.703e+02 0.701e+02 0.699e+02 0.699e+02 0.698e+02 1701 6 0.697e+02 0.698e+02 0.700e+02 0.702e+02 0.705e+02 0.706e+02 0.706e+02 0.705e+02 0.702e+02 0.700e+02 0.698e+02 0.698e+02 0.697e+02 1702 7 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270e+02 0.270

1703													
1704							pla	ne k=10					
1705	i	j= 2											
1706	2	0.677e+02	0.677e+02	0.679e+02	0.6820+02	0.686e+02	0.6900+02	0.690e+02	0.686e+02	0.682e+02	0.679e+02	0.677e+02	0 <b>.677e+02</b>
1707	- 3	0.675e+02	0,676e+02	0.678e+02	0.680e+02	0.684e+02	0.686e+02	0.686e+02	0.684e+02	0.680e+02	0.678e+02	0.6760+02	0,675e+02
1708	4	0.674e+02	0.6750+02	0.676e+02	0 <b>.679e+</b> 02	0.681e+02	0.683e+02	0.683e+02	0.681e+02	0.679e+02	0.676e+02	0.675e+02	0.6740+02
1709	5	0,673e+02	0.673e+02	0.675e+02	0.677e+02	0.679e+02	0.681e+02	0.681e+02	0.6790+02	0,677e+02	0.675e+02	0.673e+02	0,673e+02
1710	6	0,672e+02	0.673e+02	0.674e+02	0.6760+02	0.679e+02	0.680.+02	0.680e+02	0.679e+02	0.676e+02	0.6740+02	0.673e+02	0.672e+02
1711	7	0,270e+02	0.270e+02	0,270e+02	0.270e+02	0,270e+02	0.270e+02	0.2700+02	0.270e+02	0,270e+02	0.270e+02	0,270e+02	0 <b>.270e+</b> 02
1712													
1713							pla	ne k= 9					
1714	I	j= 2											
1715	2	0 <b>.657e+0</b> 2	0 <b>.658e+02</b>	0 <b>.</b> 660e+02	0.6620+02	0 <b>.</b> 665e+02	0 <b>.</b> 669e+02	0.6690+02	0.6650+02	0.662e+02	0.660e+02	0 <b>.658e+02</b>	0.657e+02
1716	3	0 <b>.</b> 656e+02	0.657e+02	0,6590+02	0.661e+02	0 <b>.</b> 663e+02	0.666e+02	0.6660+02	0.663e+02	0.661e+02	0.659e+02	0.657e+02	0.6569+02
1717	4	0.655e+02	0 <b>.656e+</b> 02	0.657e+02	0 <b>.659e+0</b> 2	0.661e+02	0 <b>.663e+</b> 02	0 <b>.663e+02</b>	0.661e+02	0.659e+02	0.657e+02	0.6560+02	0,655e+02
1718	5	0 <b>.654e+</b> 02	0 <b>.654e+02</b>	0.656e+02	0.6580+02	0.660e+02	0.6610+02	0.661e+02	0.660.+02	0.658e+02	0.656e+02	0.654e+02	0.654e+02
1719	6	0.653e+02	0 <b>. 654e+</b> 02	0 <b>, 655e+</b> 02	0 <b>.657e+02</b>	0.659e+02	0.660e+02	0.660e+02	0.659e+02	0.657e+02	0.6550+02	0.654+02	0.653e+02
1720	7	0 <b>.270e+0</b> 2	0 <b>.</b> 270e+02	0 <b>.</b> 270e+02	0 <b>.270e+</b> 02	0 <b>.</b> 270e+02	0.270e+02	0 <b>.270e+</b> 02	0.270e+02	0 <b>.270e+02</b>	0 <b>.</b> 270e+02	0 <b>.270e+02</b>	0.270e+02
1721													
1722							pta	nek≖8					
1723	1	j= 2											
1724	2	0 <b>.642e+0</b> 2	0 <b>.</b> 642e+02	0.6440+02	0.646e+02	0 <b>.649e+0</b> 2	0.652e+02	0.652e+02	0 <b>.649e+0</b> 2	0.646e+02	0 <b>.644e+</b> 02	0 <b>.642e+02</b>	0 <b>.642e+02</b>
1725	3	0.641e+02	0 <b>.</b> 642e+02	0 <b>.</b> 643e+02	0 <b>.</b> 645 <del>0</del> +02	0 <b>.</b> 647e+02	0.649e+02	0.649e+02	0,647e+02	0,645e+02	0 <b>.</b> 643e+02	0.642e+02	0.641e+02
1726	4	0.640e+02	0.6400+02	0.642e+02	0 <b>.643e+</b> 02	0 <b>.645e+</b> 02	0 <b>.</b> 647 <del>e</del> +02	0 <b>.647e+</b> 02	0.645e+02	0 <b>.643e+</b> 02	0.642e+02	0 <b>.640e+02</b>	0 <b>.640e+02</b>
1727	5	0.639e+02	0.639e+02	0.641e+02	0.6420+02	0,644e+02	0.645e+02	0,645e+02	0 <b>.644e+02</b>	0.642e+02	0.641e+02	0.639e+02	0 <b>.</b> 639e+02
1728	6	0.638e+02	0 <b>.639e+0</b> 2	0.640e+02	0.6420+02	0 <b>.643e+</b> 02	0.644e+02	0.6440+02	0 <b>.643e+0</b> 2	0.6420+02	0 <b>.640e+</b> 02	0.6390+02	0 <b>.</b> 638e+02
1729	7	0 <b>,</b> 270 <del>0</del> +02	0.2700+02	0.270e+02	0 <b>.</b> 270 <del>.</del> +02	0,270e+02	0,270 <del>0</del> +02	0.270e+02	0.270e+02	0.270e+02	0.270e+02	0 <b>.</b> 270e+02	0 <b>,</b> 270e+02
1730													
1731							pla	nek≍7					
1732	i	j≖ 2											
1733	2	0.628e+02	0.6280+02	0.629e+02	0.631e+02	0.633e+02	0.635e+02	0,635e+02	0.633e+02	0.631e+02	0 <b>.</b> 629 <del>0</del> +02	0 <b>.628e+</b> 02	0.628e+02
1734	3	0,627e+02	0.6280+02	0.6290+02	0.630e+02	0.632e+02	0.634e+02	0,634e+02	0.632e+02	0.630e+02	0.6290+02	0.628e+02	0 <b>.</b> 627e+02
1735	4	0.626e+02	0.6270+02	0.628e+02	0.6290+02	0.631e+02	0.6320+02	0.632e+02	0,631e+02	0.629e+02	0.628e+02	0 <b>.</b> 627e+02	0 <b>.</b> 626e+02
1736	5	0.6250+02	0.626e+02	0,627e+02	0,6290+02	0.630e+02	0.6310+02	0.631e+02	0.630e+02	0,629e+02	0.6270+02	0.626e+02	0.6250+02
1737	6	0,625e+02	0.625e+02	0.627e+02	0.6280+02	0.629e+02	0,630e+02	0.6300+02	0.629e+02	0.628e+02	0.6270+02	0.625e+02	0.625e+02
1738	7	0,270e+02	0.270e+02	0.270e+02	0.270e+02	0 <b>.</b> 270e+02	0.270e+02	0 <b>.</b> 270e+02	0,270e+02	0 <b>.</b> 270 <del>0</del> +02	0.270e+02	0.2700+02	0 <b>.</b> 270e+02
1759								_					
1740							pla	nek≖6					
1/41	I	j= 2											
1742	2	0,616e+02	0.617e+02	0.618e+02	0,6190+02	0,621e+02	0.6220+02	0,622e+02	0.621e+02	0.619e+02	0.618e+02	0,617e+02	0.616e+02
1745	د	0.0100+02	U.016e+02	U.017e+02	0.6190+02	U.620e+02	U.621e+02	0,621e+02	U.620e+02	0.619e+02	0.617e+02	0.6160+02	0.616e+02
1744	4	0.0150+02	U.6168+02	U_01/e+02	U.618e+02	0.619e+02	0.620e+02	0.6200+02	U.619e+02	0.618e+02	0.617e+02	U.616e+02	0.615e+02
1743	2	0.0140+02	0.0150+02	0.0100+02	U.617e+02	0.0190+02	U.619e+02	0.619e+02	U.619e+02	U.617e+02	U.616e+02	U.615e+02	U.614e+02
1/40	0	0.0140+02	0.0150+02	U.016e+02	U.617e+02	U.618e+02	U.618e+02	U.618e+02	U.618e+02	0.617e+02	0.616e+02	U.615e+02	U.614e+02
174/	1	u,270e+02	0.270e+02	U,270e+02	0,270e+02	0,270e+02	U.270e+02	0.270e+02	U.270e+02	0.2700+02	0 _• 270 <del>•</del> +02	0 <b>.</b> 270e+02	0,2700+02
1/48													

B•38

1740						- • •						
1760	1 1- 2					pla	ne k= 0					
1750	I J= ∠	0.000.000	0.610.000	0.611-100	0 617.100	0 614-100	0.614.100	0 617.102	0.611.100	0.610.100	0 600 100	0.000.000
1751	2 0,0000+02	0.600.402	0.610.02	0.611-+02	0.6120702	0.613-+02	0.611.102	0.612-102	0.611.02	0.610.02	0.600.102	0.6000702
1752		0.6099102	0.600-402	0.610-102	0.611-+02	0.612-102	0.612-102	0.6110402	0.610-402	0.600-+02	0.6099102	0.607-102
1755	4 0.00/0+02	0.607-402	0.609-102	0.600-102	0.610-402	0.610-+02	0.610-102	0.610.107	0.600-102	0.6090+02	0.607.102	0.605-402
1755	5 0,0000102	0.606+102	0.607-402	0.6090102	0.600-+02	0.610+02	0.6109402	0.600+02	0.6099102	0.607-102	0.606-102	0.606-+02
1756	7 0 270-+02	0.270+02	0.270-402	0.270+02	0.270-402	0.270.402	0.270-402	0.270+02	0.270-+02	0.0070-+02	0.270+02	0.270.402
1757	/ 0.2/00102	0.2708102	0.2708102	0.2708102	0.2708102	0.2709102	0.2708102	0.2708402	0.2708102	0.2700.02	0.2708102	0.2/00102
1758						ota	ne k= 4					
1759	i i= 2					pro						
1760	2 0.608e+02	0.609+02	0_610e+02	0.612e+02	0.614a+02	0.617e+02	0.617e+02	0.614+02	0_612e+02	0.610e+02	0.609e+02	0_608e+02
1761	3 0,607e+02	0.6080+02	0.609+02	0.611e+02	0.613e+02	0.614e+02	0.614+02	0.613e+02	0.611e+02	0.609e+02	0.608e+02	0.607e+02
1762	4 0.6030+02	0.603+02	0.6040+02	0.605+02	0.606+02	0.607e+02	0.607e+02	0.606+02	0.605+02	0,604+02	0.603e+02	0.603e+02
1763	5 0,602e+02	0.603e+02	0.604+02	0.605+02	0,606+02	0.606+02	0.6060+02	0.606e+02	0,605e+02	0.604e+02	0.6030+02	0,602e+02
1764	6 0.6020+02	0.6020+02	0,603+02	0.6040+02	0,6059+02	0.605e+02	0.605+02	0.605+02	0.604+02	0.603+02	0.6020+02	0,602e+02
1765	7 0,270e+02	0,2700+02	0 <u>.</u> 270 <del>0+</del> 02	0 <b>.</b> 270e+02	0.270e+02	0.270e+02	0.270e+02	0.270e+02	0.2708+02	0.270e+02	0.270e+02	0.270e+02
1766												
1767						pla	ne k= 3					
1768	i j= 2											
1769	2 0.608e+02	0.608e+02	0,609e+02	0.611e+02	0.613e+02	0.614e+02	0.614e+02	0.613e+02	0.611e+02	0,609e+02	0.6080+02	0.608e+02
1770	3 0.607e+02	0.607e+02	0.608e+02	0.610e+02	0.612e+02	0.613e+02	0.613e+02	0.612e+02	0.610e+02	0.608e+02	0.607e+02	0.607e+02
1771	4 0.601e+02	0.601e+02	0.602e+02	0,603e+02	0.604e+02	0 <b>.604e+0</b> 2	0.604e+02	0.604e+02	0.603e+02	0.6020+02	0.601e+02	0.601e+02
1772	5 0,600e+02	0.6010+02	0,602e+02	0 <b>.603e+02</b>	0.604e+02	0.604e+02	0.6040+02	0.6040+02	0.603e+02	0.602e+02	0.6010+02	0,600e+02
1773	6 0 <b>.</b> 600 <del>0</del> +02	0,6000+02	0,601e+02	0.6020+02	0.603e+02	0.603e+02	0,603 <del>0</del> +02	0 <b>.</b> 603 <del>0</del> +02	0.602e+02	0.601e+02	0.600e+02	0.600e+02
1774	7 0 <b>.</b> 270 <del>0</del> +02	0,270e+02	0,270e+02	0,270e+02	0 <b>.</b> 270e+02	0,270e+02	0.270e+02	0.270a+02	0.270e+02	0.270e+02	0,270e+02	0 <b>.</b> 270e+02
1775												
1776						pla	ne k= 2					
1777	i j= 2											
1778	2 0.606e+02	0.6060+02	0,608e+02	0,6090+02	0,611e+02	0.6120+02	0.612e+02	0.611e+02	0.6098+02	0.608e+02	0.606e+02	0.6060+02
1779	3 0,604e+02	0,6050+02	0.605e+02	0,607e+02	0.6090+02	0,6096+02	0,6090+02	0.6090+02	0.607e+02	0.6060+02	0.605e+02	0.6040+02
1780	4 0,601e+02	0.6020+02	0.603e+02	0.6048+02	0.605e+02	0.6068+02	0.606e+02	0.6050+02	0.6040+02	0.6050+02	0.602e+02	0.601e+02
1781	5 0.600e+02	0.6008+02	0.601e+02	0.6020+02	0.6050+02	0.604e+02	0.6046402	0.6030+02	0.6020+02	0.6010402	0.600e+02	0.5000+02
1782	0 0.5998+02	0.0000+02	0.0010+02	0.0020+02	0.0020+02	0.0006+02	0.00000002	0.0020+02	0.0028402	0.0010+02	0.0000+02	0.03996+02
1703	/ 0,2/08+02	0.2708702	0.2/08102	0.2708402	0.2/08+02	0,2/08+02	0.2708+02	0.2708402	0,2708+02	0,2/08+02	0.2/08+02	0.2708402
1795						- 1-	1					
1786	1 1- 7					pia	ne K= 1					
1787	1 J- 2	0 270-402	0 270-102	0 270-+02	0 270-402	0 270-+02	0 270-102	0 270-102	0 270-102	0 270-102	0 270-102	0 270-+02
1799	Z 0.2700+02	0 270++02	0,270,102	0.2700+02	0.270-+02	0.270-402	0.2708102	0.270-102	0.2700+02	0.270-402	0.2700+02	0.2700+02
1780	4 0.270-402	0.2700+02	0.270.402	0.2700+02	0.2704-02	0 270-102	0 270-402	0.270.102	0 270-102	0.2700+02	0.2700+02	0.270.00
1790	5 0.270-+02	0.270-+02	0.270.402	0.270-+02	0.270-+02	0.2704402	0.270-402	0.270.402	0 270-+02	0.270-402	0.270-402	0.2704402
1791	6 0.270+02	0.270+102	0.270+02	0.270+02	0.270+02	0.270+02	0.270+02	0.270-+02	0.2700+02	0.270+02	0.2700+02	0 270+02
1792	7 0.000+00	0_000+00	0.000+00	0.000+00	0.000-+00	0.000±+00	0.000+00	0.000-+00	0.000+02	0.000_+00	0_000_+00	0.000+00
1793			<b>U U U U U</b>	<b>4</b> , 4448 / 00		v. vv.a. 100		4.0000.00	0.0000100	v. vova · vv	0,000,00	0.0000.00
1794 1												

(

B.39

1795	* * * mass flux in i-direction, g/sq. cm sec * * *
1796	
1797	plane k= 2
1790	j I= 4 11=0.132a=05=0.422a=05=0.774a=05=0.120a=04=0.188a=04=0.134a=03=0.153a=03=0.828a=04=0.187a=04
1800	10-0, 129e-05-0, 405e-05-0, 746e-05-0, 117e-04-0, 185e-04-0, 133e-03-0, 150e-03-0, 792e-04-0, 174e-04
1801	9-0. 106e-05-0. 328e-05-0. 624e-05-0. 103e-04-0. 173e-04-0. 130e-03-0. 136e-03-0. 596e-04-0. 895e-05
1802	8-0.683-06-0.210-05-0.411-05-0.712-05-0.156-04-0.113-03-0.969-04-0.197-04 0.000+00
1803	7-0.295e-06-0.802e-06-0.104e-05 0.125e-05 0.101e-20-0.105e-20-0.140e-04 0.000e+00 0.000e+00
1804	6-0,121e-04-0,344e-04-0,385e-04-0,311e-20-0,144e-21-0,155e-21_0,000e+00_0,000e+00
1805	5-0.169e-04-0.487e-04-0.702e-04-0.821e-04-0.232e-04 0.000e+00 0.000e+00
1806	4-0,151e-04-0,416e-04-0,527e-04-0,491e-04 0,000e+00 0,000e+00
1807	3-0,849e-05-0,203e-04-0,146e-04 0,000e+00 0,000e+00
1808	2-0,288e-05-0,559e-05 0,000e+00 0,000e+00
1809	
1811	
1812	J 7 2 11 0.840e-08 0.251e-07 0.381e-07 0.363e-07 0.302e-21-0.298e-21 0.988e-06 0.107e-05 0.330e-06
1813	10 0.839e-08 0.247e-07 0.375e-07 0.362e-07 0.115e-21-0.107e-21 0.963e-06 0.101e-05 0.298e-06
1814	9 0,780-08 0.225-07 0.347-07 0.347-07-0.390-22 0.467-22 0.854-06 0.746-06 0.143-06
1815	8 0.729e-08 0.206e-07 0.322e-07 0.326e-07-0.702e-23 0.148e-22 0.617e-06 0.258e-06 0.000e+00
1816	7 0.765e-08 0.210e-07 0.321e-07 0.308e-07 0.119e-21-0.111e-21 0.332e-06 0.000e+00 0.000e+00
1817	6 0.420e-21 0.733e-21 0.606e-21 0.569e-21 0.893e-21 0.889e-21 0.000e+00 0.000e+00
1818	5 0.190e-06 0.568e-06 0.875e-06 0.102e-05 0.604e-06 0.000e+00 0.000e+00
1819	4 0.557e+06 0.104e+05 0.159e+05 0.106e+05 0.000e+00 0.000e+00
1820	2 0 10005 0 22405 0 000-+00 0 000-+00
1822	
1823	1
1824	* * * mass flux in k-direction, g/sq. cm sec * * *
1825	
1826	plane k= 2
1827	j i= 2
1828	11 0.926e-05 0.959e-05 0.985e-05 0.985e-05 0.130e-04 0.331e-03 0.113e-03-0.136e-03-0.220e-03-0.105e-03
1829	
1830	9 0,9029-02 0,9029-02 0,1049-04 0,1029-04 0,1289-04 0,2099-02 0,2229-04-0,1079-0,2069-02-0,0219-04 8 0,98405 0,98905 0,10504 0,10504 0,10904 0,17503-0,24904-0,21303-0,10203-0,000-400
1832	
1833	6 0.331e-03 0.326e-03 0.289e-03 0.176e-03-0.814e-22-0.119e-22-0.581e-04 0.000e+00
1834	5 0,113e-03 0,104e-03 0,555e-04-0,248e-04-0,630e-04-0,581e-04 0,000e+00
1835	4-0,136e-03-0,145e-03-0,187e-03-0,213e-03-0,123e-03 0,000e+00
1836	3-0,220e-03-0,220e-03-0,208e-03-0,102e-03 0,000e+00
1837	2-0,105e-03-0,103e-03-0,651e-04 0,000e+00
1838	
1839	ptane k≖10
1840	j <b>!</b> ≖ 2

1841	11 0.237e-04 0.236e-04 0.233e-04 0.224e-04 0.200e-04 0.241e-22 0.353e-03 0.174e-03-0.210e-03-0.185e-03
1842	10 0.236e-04 0.236e-04 0.233e-04 0.223e-04 0.199e-04 0.456e-22 0.338e-03 0.142e-03-0.226e-03-0.182e-03
1843	9 0.2330-04 0.2330-04 0.2300-04 0.2220-04 0.1970-04 0.4380-22 0.2730-03-0.1000-04-0.3150-03-0.1460-03
1844	8 0,2240-04 0,2230-04 0,2220-04 0,2140-04 0,1880-04 0,4060-22 0,1630-03-0,2270-03-0,2340-03 0,0000+00
1845	7 0,200e-04 0,199e-04 0,197e-04 0,188e-04 0,164e-04 0,359e-22-0,130e-04-0,310e-03 0,000e+00
1846	6 0,241e-22 0,456e-22 0,438e-22 0,406e-22 0,359e-22 0,955e-23-0,167e-03 0,000e+00
1847	5 0,353e-03 0,338e-03 0,273e-03 0,163e-03-0,130e-04-0,167e-03 0,000e+00
1848	4 0,174-03 0,142-03-0,100-04-0,227-03-0,310-03 0,000+00
1849	3-0,2108-03-0,2268-03-0,3158-03-0,2348-03 0,0008+00
1850	2-0, 1859-03-0, 1829-03-0, 1469-03 0, 0009+00
1851	
1852 1	
1853	* * * pressure change, dynes/sg, cm * * *
1854	
1855	plane k≖ 8
1855 1856	plane k= 8
1855 1856 1857	plane k= 8 j i= 2 11-0.247e-03-0.247e-03-0.247e-03-0.247e-03-0.247e-03 0.136e+03-0.251e-03 0.251e-03-0.251e-03-0.251e-03-0.251e-03
1855 1856 1857 1858	plane k= 8 j i= 2 11-0.247e-03-0.247e-03-0.247e-03-0.247e-03-0.247e-03 0.136e+03-0.251e-03 0.251e-03-0.251e-03-0.251e-03 10-0.247e-03-0.247e-03-0.247e-03-0.247e-03-0.247e-03 0.414e+02-0.251e-03 -0.251e-03-0.251e-03-0.251e-03-0.251e-03
1855 1856 1857 1858 1859	plane k= 8 j i= 2 11-0.247e-03-0.247e-03-0.247e-03-0.247e-03-0.247e-03 0.136e+03-0.251e-03 0.251e-03-0.251e-03-0.251e-03-0.251e-03-0.251e-03-0.251e-03-0.251e-03-0.251e-03-0.251e-03-0.251e-03-0.251e-03-0.251e-03-0.251e-03-0.251e-03-0.251e-03-0.251e-03-0.251e-03-0.251e-03-0.251e-03-0.251e-03-0.251e-03-0.251e-03-0.251e-03-0.251e-03-0.251e-03-0.251e-03-0.251e-03-0.251e-03-0.251e-03-0.251e-03-0.251e-03-0.251e-03-0.251e-03-0.251e-03-0.251e-03-0.251e-03-0.251e-03-0.251e-03-0.251e-03-0.251e-03-0.251e-03-0.251e-03-0.251e-03-0.251e-03-0.251e-03-0.251e-03-0.251e-03-0.251e-03-0.251e-03-0.251e-03-0.251e-03-0.251e-03-0.251e-03-0.251e-03-0.251e-03-0.251e-03-0.251e-03-0.251e-03-0.251e-03-0.251e-03-0.251e-03-0.251e-03-0.251e-03-0.251e-03-0.251e-03-0.251e-03-0.251e-03-0.251e-03-0.251e-03-0.251e-03-0.251e-03-0.251e-03-0.251e-03-0.251e-03-0.251e-03-0.251e-03-0.251e-03-0.251e-03-0.251e-03-0.251e-03-0.251e-03-0.251e-03-0.251e-03-0.251e-03-0.251e-03-0.251e-03-0.251e-03-0.251e-03-0.251e-03-0.251e-03-0.251e-03-0.251e-03-0.251e-03-0.251e-03-0.251e-03-0.251e-03-0.251e-03-0.251e-03-0.251e-03-0.251e-03-0.251e-03-0.251e-03-0.251e-03-0.251e-03-0.251e-03-0.251e-03-0.251e-03-0.251e-03-0.251e-03-0.251e-03-0.251e-03-0.251e-03-0.251e-03-0.251e-03-0.251e-03-0.251e-03-0.251e-03-0.251e-03-0.251e-03-0.251e-03-0.251e-03-0.251e-03-0.251e-03-0.251e-03-0.251e-03-0.251e-03-0.251e-03-0.251e-03-0.251e-03-0.251e-03-0.251e-03-0.251e-03-0.251e-03-0.251e-03-0.251e-03-0.251e-03-0.251e-03-0.251e-03-0.251e-03-0.251e-03-0.251e-03-0.251e-03-0.251e-03-0.251e-03-0.251e-03-0.251e-03-0.251e-03-0.251e-03-0.251e-03-0.251e-03-0.251e-03-0.251e-03-0.251e-03-0.251e-03-0.251e-03-0.251e-03-0.251e-03-0.251e-03-0.251e-03-0.251e-03-0.251e-03-0.251e-03-0.251e-03-0.251e-03-0.251e-03-0.251e-03-0.251e-03-0.251e-03-0.251e-03-0.251e-03-0.251e-03-0.251e-03-0.251e-03-0.251e-03-0.251e-03-0.251e-03-0.251e-03-0.251e-03-0.251e-03-0.251e-03-0.251e-03-0.251e-03-0.251e-03-0.251e-03-0.251e-03-0.251e-03-0.251e-03-0.251e-03-0.251e-03-0.251e-03-0.251e-03-0.251e-03-0.251e-03-0.251e-03-0.251e-03-0
1855 1856 1857 1858 1859 1860	plane k = 8 $j = 2$ $11-0.247e-03-0.247e-03-0.247e-03-0.247e-03-0.247e-03 = 0.136e+03-0.251e-03 = 0.251e-03-0.251e-03-0.251e-03$ $10-0.247e-03-0.247e-03-0.247e-03-0.247e-03-0.247e-03 = 0.414e+02-0.251e-03 = 0.251e-03-0.251e-03-0.251e-03$ $9-0.247e-03-0.247e-03-0.247e-03-0.247e-03-0.247e-03 = 0.342e+02-0.251e-03 = 0.251e-03-0.251e-03-0.251e-03$ $8-0.247e-03-0.247e-03-0.247e-03-0.247e-03-0.247e-03 = 0.339e+02-0.251e-03 = 0.251e-03-0.251e-03 = 0.201e+03$
1855 1856 1857 1858 1859 1860 1861	plane k = 8 j i = 2 11-0.247e-03-0.247e-03-0.247e-03-0.247e-03 0.136e+03-0.251e-03 0.251e-03-0.251e-03-0.251e-03 10-0.247e-03-0.247e-03-0.247e-03-0.247e-03 0.414e+02-0.251e-03 -0.251e-03-0.251e-03-0.251e-03 9-0.247e-03-0.247e-03-0.247e-03-0.247e-03 0.342e+02-0.251e-03 -0.251e-03-0.251e-03-0.251e-03 8-0.247e-03-0.247e-03-0.247e-03-0.247e-03 0.339e+02-0.251e-03 -0.251e-03-0.251e-03 0.000e+00 7-0.247e-03-0.247e-03-0.247e-03-0.247e-03-0.247e-03 0.371e+02-0.251e-03 -0.251e-03 0.000e+00
1855 1856 1857 1858 1859 1860 1861 1862	plane k = 8 j i = 2 11-0.247e-03-0.247e-03-0.247e-03-0.247e-03 0.136e+03-0.251e-03 0.251e-03-0.251e-03-0.251e-03 10-0.247e-03-0.247e-03-0.247e-03-0.247e-03 0.414e+02-0.251e-03 -0.251e-03-0.251e-03-0.251e-03 9-0.247e-03-0.247e-03-0.247e-03-0.247e-03 0.342e+02-0.251e-03 -0.251e-03-0.251e-03-0.251e-03 8-0.247e-03-0.247e-03-0.247e-03-0.247e-03 0.339e+02-0.251e-03 -0.251e-03-0.251e-03 0.000e+00 7-0.247e-03-0.247e-03-0.247e-03-0.247e-03-0.247e-03 0.371e+02-0.251e-03 -0.251e-03 0.000e+00 6 0.136e+03 0.414e+02 0.342e+02 0.339e+02 0.371e+02 0.677e+02-0.251e-03 0.000e+00
1855 1856 1857 1858 1859 1860 1861 1862 1863	plane k = 8 j i= 2 11-0.247e-03-0.247e-03-0.247e-03-0.247e-03-0.247e-03 0.136e+03-0.251e-03 0.251e-03-0.251e-03-0.251e-03 10-0.247e-03-0.247e-03-0.247e-03-0.247e-03 0.414e+02-0.251e-03 -0.251e-03-0.251e-03-0.251e-03 9-0.247e-03-0.247e-03-0.247e-03-0.247e-03 0.342e+02-0.251e-03 -0.251e-03-0.251e-03-0.251e-03 8-0.247e-03-0.247e-03-0.247e-03-0.247e-03 0.339e+02-0.251e-03 -0.251e-03-0.251e-03 0.000e+00 7-0.247e-03-0.247e-03-0.247e-03-0.247e-03-0.247e-03 0.371e+02-0.251e-03 -0.251e-03 0.000e+00 6 0.136e+03 0.414e+02 0.342e+02 0.339e+02 0.371e+02 0.677e+02-0.251e-03 0.000e+00 5-0.251e-03-0.251e-03-0.251e-03-0.251e-03-0.251e-03-0.251e-03 0.000e+00
1855 1856 1857 1858 1859 1860 1861 1862 1863 1864	plane k = 8 j i= 2 11-0.247e-03-0.247e-03-0.247e-03-0.247e-03 0.136e+03-0.251e-03 0.251e-03-0.251e-03-0.251e-03 10-0.247e-03-0.247e-03-0.247e-03-0.247e-03 0.414e+02-0.251e-03 -0.251e-03-0.251e-03-0.251e-03 9-0.247e-03-0.247e-03-0.247e-03-0.247e-03 0.342e+02-0.251e-03 -0.251e-03-0.251e-03-0.251e-03 8-0.247e-03-0.247e-03-0.247e-03-0.247e-03 0.339e+02-0.251e-03 -0.251e-03-0.251e-03 0.000e+00 7-0.247e-03-0.247e-03-0.247e-03-0.247e-03-0.247e-03 0.371e+02-0.251e-03 -0.251e-03 0.000e+00 6 0.136e+03 0.414e+02 0.342e+02 0.339e+02 0.371e+02 0.677e+02-0.251e-03 0.000e+00 5-0.251e-03-0.251e-03-0.251e-03-0.251e-03-0.251e-03 0.000e+00 4-0.251e-03-0.251e-03-0.251e-03-0.251e-03 0.000e+00
1855 1856 1857 1858 1859 1860 1861 1862 1863 1864 1865	plane k = 8 j i= 2 11-0.247e-03-0.247e-03-0.247e-03-0.247e-03-0.247e-03 0.136e+03-0.251e-03 0.251e-03-0.251e-03-0.251e-03 10-0.247e-03-0.247e-03-0.247e-03-0.247e-03 0.414e+02-0.251e-03 -0.251e-03-0.251e-03-0.251e-03 9-0.247e-03-0.247e-03-0.247e-03-0.247e-03 0.342e+02-0.251e-03 -0.251e-03-0.251e-03-0.251e-03 8-0.247e-03-0.247e-03-0.247e-03-0.247e-03 0.339e+02-0.251e-03 -0.251e-03-0.251e-03 0.000e+00 7-0.247e-03-0.247e-03-0.247e-03-0.247e-03 0.371e+02-0.251e-03 0.000e+00 6 0.136e+03 0.414e+02 0.342e+02 0.339e+02 0.371e+02 0.677e+02-0.251e-03 0.000e+00 5-0.251e-03-0.251e-03-0.251e-03-0.251e-03-0.251e-03 0.000e+00 4-0.251e-03-0.251e-03-0.251e-03-0.251e-03 0.000e+00 3-0.251e-03-0.251e-03-0.251e-03-0.251e-03 0.000e+00
1855 1856 1857 1858 1859 1860 1861 1862 1863 1864 1865 1866	plane k = 8 j i= 2 11-0.247e-03-0.247e-03-0.247e-03-0.247e-03-0.247e-03 0.136e+03-0.251e-03 0.251e-03-0.251e-03-0.251e-03 10-0.247e-03-0.247e-03-0.247e-03-0.247e-03 0.414e+02-0.251e-03 -0.251e-03-0.251e-03-0.251e-03 9-0.247e-03-0.247e-03-0.247e-03-0.247e-03 0.342e+02-0.251e-03 -0.251e-03-0.251e-03-0.251e-03 8-0.247e-03-0.247e-03-0.247e-03-0.247e-03 0.339e+02-0.251e-03 -0.251e-03-0.251e-03 0.000e+00 7-0.247e-03-0.247e-03-0.247e-03-0.247e-03 0.371e+02-0.251e-03 0.000e+00 6 0.136e+03 0.414e+02 0.342e+02 0.339e+02 0.371e+02 0.677e+02-0.251e-03 0.000e+00 5-0.251e-03-0.251e-03-0.251e-03-0.251e-03-0.251e-03 0.000e+00 4-0.251e-03-0.251e-03-0.251e-03-0.251e-03 0.000e+00 3-0.251e-03-0.251e-03-0.251e-03 0.000e+00 2-0.251e-03-0.251e-03-0.251e-03 0.000e+00
1855 1856 1857 1858 1859 1860 1861 1862 1863 1864 1865 1866 1867	plane k = 8 j i= 2 11-0.247e-03-0.247e-03-0.247e-03-0.247e-03 0.136e+03-0.251e-03 0.251e-03-0.251e-03-0.251e-03 10-0.247e-03-0.247e-03-0.247e-03-0.247e-03 0.414e+02-0.251e-03 -0.251e-03-0.251e-03-0.251e-03 9-0.247e-03-0.247e-03-0.247e-03-0.247e-03 0.342e+02-0.251e-03 -0.251e-03-0.251e-03-0.251e-03 8-0.247e-03-0.247e-03-0.247e-03-0.247e-03 0.339e+02-0.251e-03 -0.251e-03-0.251e-03 0.000e+00 7-0.247e-03-0.247e-03-0.247e-03-0.247e-03 0.371e+02-0.251e-03 0.000e+00 6 0.136e+03 0.414e+02 0.342e+02 0.339e+02 0.371e+02 0.677e+02-0.251e-03 0.000e+00 5-0.251e-03-0.251e-03-0.251e-03-0.251e-03-0.251e-03 0.000e+00 4-0.251e-03-0.251e-03-0.251e-03-0.251e-03 0.000e+00 2-0.251e-03-0.251e-03-0.251e-03 0.000e+00
1855 1856 1857 1858 1859 1860 1861 1862 1863 1864 1865 1866 1867 1868 1	plane k = 8 j i= 2 11-0.247e-03-0.247e-03-0.247e-03-0.247e-03-0.247e-03 0.136e+03-0.251e-03 0.251e-03-0.251e-03-0.251e-03 10-0.247e-03-0.247e-03-0.247e-03-0.247e-03 0.414e+02-0.251e-03 -0.251e-03-0.251e-03-0.251e-03 9-0.247e-03-0.247e-03-0.247e-03-0.247e-03 0.342e+02-0.251e-03 -0.251e-03-0.251e-03-0.251e-03 8-0.247e-03-0.247e-03-0.247e-03-0.247e-03 0.339e+02-0.251e-03 -0.251e-03-0.251e-03 0.000e+00 7-0.247e-03-0.247e-03-0.247e-03-0.247e-03 0.371e+02-0.251e-03 0.000e+00 6 0.136e+03 0.414e+02 0.342e+02 0.339e+02 0.371e+02 0.677e+02-0.251e-03 0.000e+00 5-0.251e-03-0.251e-03-0.251e-03-0.251e-03-0.251e-03 0.000e+00 4-0.251e-03-0.251e-03-0.251e-03-0.251e-03 0.000e+00 2-0.251e-03-0.251e-03-0.251e-03 0.000e+00

(

### DISTRIBUTION

No. of Copies

## OFFSITE

77 DOE Technical Information Center
H. J. Hale

U.S. Department of Energy Office of Civilian Radioactive Waste Management RW-33 Washington, DC 20585

L. Barrett U.S. Department of Energy Office of Civilian Radioactive Waste Management RW-33 Washington, DC 20585

J. Epstein U.S. Department of Energy Office of Civilian Radioactive Waste Management RW-32 Washington, DC 20585

K. A. Klein
U.S. Department of Energy
Office of Civilian Radioactive
Waste Management
RW-32
Washington, DC 20585

D. E. Shelor U.S. Department of Energy Office of Civilian Radioactive Waste Management RW-32 Washington, DC 20585

# No. of

<u>Copies</u>

H. Steinburg U.S. Department of Energy Office of Storage and Transportation Systems **RW-33** 1000 Independence Avenue Washington, DC 20585 W. Stringfield U.S. Department of Energy Office of Civilian Radioactive Waste Management RW-32 Washington, DC 20585 J. S. Finucane U.S. Department of Energy **Energy Information** Administration EI-53 Washington, DC 20585 M. Fisher U.S. Department of Energy Idaho Operations Office 550 2nd Street Idaho Falls, ID 83401 K. G. Golliher U.S. Department of Energy Albuquerque Operations Office P.O. Box 5400 Albuquerque, NM 87115 C. J. Daukowski U.S. Department of Energy Attention: Defense Programs San Francisco Operations Office 1333 Broadway Oakland, CA 94612

No. of Copies C. Matthews U.S. Department of Energy Oak Ridge National Laboratory P.O. Box E Oak Ridge, TN 37830 M. Kunich U.S. Department of Energy Nevada Operations Office P.O. Box 14100 Las Vegas, NV 89114 N. H. Davison U.S. Nuclear Regulatory Commission Office of Nuclear Materials Safety and Safeguards Washington, DC 20555 C. Feldman U.S. Nuclear Regulatory Commission Office of Nuclear Regulatory Research MS 1130-SS Washington, DC 20555 W. Lake U.S. Nuclear Regulatory Commission Office of Nuclear Materials Safety and Safeguards MS 396-SS Washington, DC 20555 C. H. Peterson U.S. Nuclear Regulatory Commission Office of Nuclear Material Safety and Safeguards MS 623-SS Washington, DC 20555

#### No. of Copies

J. Roberts U.S. Nuclear Regulatory Commission Office of Nuclear Material Safety and Safeguards MS 396-SS Washington, DC 20555 L. C. Ruse U.S. Nuclear Regulatory Commission Office of Spent Fuel Storage Installation Division of Fuel Cycle and Material Safety Washington, DC 20555 J. A. Carr Battelle Memorial Institute Office of Nuclear Waste Isolation 505 King Avenue Columbus, OH 43201 Technical Library Battelle Memorial Institute Office of Nuclear Waste Isolation 505 King Avenue Columbus, OH 43201 L. J. Jardine Bechtel National PQ. Box 3965 San Francisco, CA 94119 R. Kunita Carolina Power & Light Co. P.O. Box 1551 Raleigh, NC 27602 C. K. Anderson Combustion Engineering, Inc. 1000 Prospect Hill Road

Windsor, CT 06095

No. of Copies

T. Grant Ebasco Services Incorporated Two World Trade Center New York, NY 10048 M. F. Jensen EG&G P.O. Box 1625 Idaho Falls, ID 83415 P. E. Eggers Eggers Ridihalgh Partners, Inc. 1445 Summit Street Columbus, OH 43201 FLUOR Engineers, Inc. Advanced Technology Division P.O. Box C-11944 Santa Anna, CA 92711-1944 E. E. Voiland General Electric Company Nuclear Fuel & Services Division 7555 E. Collins Road Morris, IL 60450 R. Anderson General Nuclear Services, Inc. 135 Darling Drive Avon, CT 06001 W. R. Juergens Brooks and Perkins 12633 Inkster Road Livonia, MI 48150 L. B. Ballou Lawrence Livermore National Laboratory P.O. Box 808 Livermore, CA 94550 M. W. Schwartz Lawrence Livermore National

Laboratory

Livermore, CA 94550

P.O. Box 808

No. of Copies

> C. E. Walter Lawrence Livermore National Laboratory P.O. Box 808 Livermore, CA 94550 H. Lowenberg Lowenberg Associates 10901 Rosemont Drive Rockville, MD 20852 J. Houston Nuclear Assurance Corporation 5720 Peach Tree Parkway Norcross, GA 30092 R. T. Haelsig Nuclear Packaging Inc. 1010 S. 336th Street Federal Way, WA 98003 L. E. Wiles Numerical Applications, Inc. 825 Goethals Drive Richland, WA 99352 B. Lehnert NUTECH Engineers 145 Martinvale Lane San Jose, CA 95116 C. V. Parks Oak Ridge National Laboratory P.O. Box X Oak Ridge, TN 37831 D. Woods Ralph M. Parsons Co. 100 West Walnut Street Pasadena, CA 91124 J. V. Massey Reedy and Associates 103 Albright Way Los Gatos, CA 95030

No. of Copies T. L. Sanders Sandia National Laboratory Albuquerque, NM 87115 M. E. Mason Transnuclear, Inc. 1 N. Broadway White Plains, NY 10601 TRW Exploration/PRO P.O. Box 441807 Houston, TX 77244-1807 C. E. King Uranium Mgt. Corp. 175 Curtner Ave. MC 620 San Jose, CA 95125 M. L. Smith Virginia Electric Power Co. P.O. Box 26666 Richmond, VA 23261 K. L. Basehore Virginia Electric and Power Co. Power Station Engineering The Electric Building P.O. Box 564 7th and Franklin Richmond, VA 23204 D. L. Larkin Washington Public Power Supply System P.O. Box 968 Richland, WA 99352 R. O. Anderson Northern States Power Company 15 S. 15th Street Minneapolis, MN 55401 G. Swindlehurst Duke Power Company P.O. Box 33189 422 S. Church Street Charlotte, NC 28242

Copies D. Hamilton Middle South Services, Inc. Box 61000 New Orleans, LA 70161 G. R. Bond Manager, Nuclear Fuels General Public Utilities, NUC 100 Interpace Parkway Parsippany, NJ 07054 J. R. Ratliff Tennessee Valley Authority 409 Krystal Building Chattanooga, TN 37401 B. Rice Texas Utilities Generating Co. Skyway Tower 400 North Olive Street LD81 Dallas, TX 75201 H. E. Bliss Nuclear Fuel Services Commonwealth Edison 72 West Adams Street P.O. Box 767 Chicago, IL 60690 R. T. Harris Northeast Utilities P.O. Box 270 Hartford, CN 06101 A. Ladieu Yankee Atomic Electric Company 1671 Worcester Road Framingham, MA 01701 D. S. Rowe Rowe and Associates Suite 200 2050 112th Avenue NE Bellevue, WA 98007

No. of
No. of Copies

Y. Hsii Division of Systems Integration Office of Nuclear Regulation U.S. Nuclear Regulatory Commission Washington, DC 20555 L. Phillips Division of Systems Integration Office of Nuclear Regulation U.S. Nuclear Regulatory Commission Washington, DC 20555 L. Agee Electric Power Research Institute P.O. Box 10412 Palo Alto, CA 94303 R. Lambert Electric Power Research Institute P.O. Box 10412 Palo Alto, CA 94303 G. S. Srikantiah Electric Power Research Institute P.O. Box 10412 Palo Alto, CA 94303 R. Rice EG&G Idaho, Inc. P.O. Box 1625 Idaho Falls, ID 83415 C. R. Bolmgren Westinghouse Electric Corp. Nuclear Waste Department P.O. Box 3912 Pittsburgh, PA 15230 D. Klein Mechanical Engineering Department

University of Texas Austin, TX 78712

No. of Copies

4

3

42

B. A. Chin Mechanical Engineering Dept. 247 Wilmore Labs Auburn University Auburn, AL 36849 ONSITE DOE Richland Operations Office J. P. Collins D. E. Crouter M. S. Karol D. L. Oleson Westinghouse Hanford Company C. L. Brown G. T. Harper R. E. Stover Pacific Northwest Laboratory G. H. Beeman D. J. Bradley J. L. Braitman J. M. Cuta J. M. Creer (5) L. R. Dodd R. E. Einziger M. D. Freshley C. M. Heeb A. B. Johnson, Jr. B. M. Johnson L. T. Lakey D. L. Lessor N. J. Lombardo P. S. Lowery R. A. McCann (10) T. E. Michener D. R. Rector C. W. Stewart R. A. Stokes D. S. Trent C. L. Wheeler Technical Report Files (5)

Publishing Coordination (2)