

Quantification of the $\alpha(O)$ and Prior- β phase fractions and their oxygen contents in high temperature (HT) oxidised Zr alloys (Zy-4, M5TM)

J.C. Brachet(*), L. Portier, D. Hamon, Ph. Trouslard, S. Urvoy, V. Rabeau - CEA - Saclay
A. Lesbros (EDF-Septen) and J.P. Mardon (FRA-ANP), France
(*) Corresponding author: jean-christophe.brachet@cea.fr

ABSTRACT

This paper describes a methodology which allows us to quantify the $\alpha(O)$ and Prior- β phase fractions and their oxygen contents in high temperature (HT) oxidised fuel cladding tubes. The methodology has mainly been applied to Framatome-ANP's Zy-4 and M5TM alloys. One of the practical objectives is to be able to quantify the local « ECR » of HT oxidised cladding tubes i.e. to characterize locally the resultant clad microstructure after a LOCA test leading to an inhomogeneous oxidation of the cladding tube, for example: due to azimuthal and/or axial thermal gradients along the tube, due to secondary oxidation in the vicinity of a failure, etc.

After describing the experimental methodology, we illustrate an application which consists of a study of the influence of the oxidation mode, that is :

- (1) Conventional Furnace Heating (FH) vs. Induction Heating (IH)
- (2) Single Face (SF) vs. Double Face (DF) oxidation mode

on M5TM oxidised at 1000°C for a variety of oxidation times, including the «break-away» phenomenon occurrence. This last study has shown no significant influences of the heating (FH vs. IH) and of the oxidation (SF vs. DF) modes on the $\alpha(o)$ thickness evolution and thus on the break-away occurrence at 1000°C on M5TM alloy. This allowed us to check the consistency between the two main HT-oxidation facilities used in CEA labs on non-irradiated clads (i.e., “Dezirox” and “Cinog” facilities).