

Westinghouse Non-Proprietary Class 3



A BNFL Group company

---

# BEACON™-COLSS Integration

NRC/Westinghouse Meeting  
Pittsburgh, PA  
August 18, 2004

# Introduction

---

- Westinghouse currently has 2 PWR core monitoring systems with online power distribution and thermal hydraulic models
  - COLSS (Core Operating Limit Supervisory System)
    - Last topical on uncertainty methodology approved in 1987
    - Operating at 12 C-E designed plants (7 in the US)
  - BEACON<sup>TM</sup> (Best Estimate Analyzer for Core Operation - Nuclear)
    - Topical report approved in 1994
    - Topical report addendums approved in 1999 and 2002
    - Operating at ~50 W and C-E plant types (25 in the US)

BEACON<sup>TM</sup> is a trademark of the Westinghouse Electric Company

# COLSS

---

- Developed to help maintain selected C-E plant types within LCOs
  - Digital core monitoring system
  - Uses data from plant computer with analytical model to determine reactor power, measured power distribution & power operating limits
  - Provides measured information on DNBR, LHR, ASI, tilt & core power level to verify against Tech. Spec. limits
  - Displays margin to limits and provide alarms upon approach to limits

# BEACON

---

- Developed to help maintain W, C-E and other PWR plant types within LCOs
  - Digital core monitoring system
  - Uses data from plant computer with analytical model to generate measured power distribution
  - Provides measured information on DNBR, LHR ( $F_Q$ ), Fr ( $F_{\Delta h}$ ) and ASI (AO) to verify against Tech. Spec. limits
  - Provides predictive functions for estimated criticality, load maneuvers and reactivity balance calculations
  - Provides core analysis and incore flux map analysis capability

# BEACON-COLSS Project

---

- Project started in 2002 to merge COLSS and BEACON™ core monitoring systems
  - Each have some features that are not in the other
  - Combine the best parts of BEACON & COLSS to develop an upgrade for COLSS

a, c

# Functional Design

---

- BEACON-COLSS Functional Design Requirements

a, c

# BEACON-COLSS Overview

---

a, c



# BEACON Measured Power Distribution

---

- Receives current core information from plant computer

a, c

# BEACON Measured Power Distribution

---

a, c



# COLSS Merged Functions

---

- Core Flow
- Reactor Power Function

a, c

# CETOP-D Code

---

a, c

# BEACON-COLSS Product Level

---

a, c

# BEACON-COLSS Uncertainty Methods

---

a, c

# Power Peaking Uncertainty Methodology

---

- Compares BEACON “measured” results with “true” 3-D results



# DNBR POL Uncertainty Methodology

---

- Compares BEACON “measured” results with “true” 3-D results





# Application of Uncertainty Methodology

---

- Two C-E designed plants analyzed for uncertainties
- Previously analyzed using standard COLSS methods

a, b, c

# Application of Uncertainty Methodology

- Pairs of “true” and “predicted” 3-D power distributions generated with following bounding conditions

a, c

# Application for Power Peaking Limits


---



# Application for Power Peaking Limits

---

a, c



# Application for Power Peaking Limits

---

a, c



# Power Peaking Uncertainty 95/95 UTL

---


a, c

# Application for Power Peaking Limits

---

## I. Measured Power Peaking Factor and Uncertainty

a, c



# Application of Methodology for DNBR POL

---

## II. DNBR POL and Uncertainty

a, c



# Results for LHR POL

---

Plant A Measured LHR Uncertainty 95/95 UTL

a, b, c



# Results for LHR POL

---

Plant B Measured LHR Uncertainty 95/95 UTL

a, b, c



# Results for LHR POL

---

- Comparison of LHR POL total uncertainty from standard COLSS method and BEACON-COLSS method
- Comparison made with 2.0 % ICI variability and 40 % ICI detectors deleted

a, b, c

# Application of Methodology for DNBR POL

---

a, c

# Application of Methodology for DNBR POL

---

a, c



# Application of Methodology for DNBR POL

---

a, b, c



# Application of Methodology for DNBR POL

---

a, c

# Application of Methodology for DNBR POL

---

a, c



# Application of Methodology for DNBR POL

---

- Shift distribution until positive with 95/95 UTL

a, c



# Uncertainty of DNBR POL

---

a, c



# Application of Methodology for DNBR POL

---

## I. DNBR POL and Uncertainty

a, c



# Application of Methodology for DNBR POL

---

## II. DNBR POL and Uncertainty

a, c

# Results for DNBR POL

---

- Comparison of DNBR POL uncertainty from standard COLSS method and BEACON-COLSS method

a, b, c

# Technical Specification Modifications

---

a, c

# Technical Specification Modifications

---



# Technical Specification Modifications

---





# Westinghouse Licensing Submittal

---


- Submit licensing document as Addendum 3 to the BEACON Topical Report for COLSS application

a, c

# Status / Schedule

---

a, c



# Westinghouse

A BNFL Group company