

State Links: Utah.gov | [State Online Services](#) | [Agency List](#) | Business.utah.gov | [Search](#).

Division of Administrative Rules

A Service of the Department of Administrative Services.

[Division of Administrative Rules Home] [UTAH ADMINISTRATIVE CODE List of Titles]

ATTENTION AGENCIES: Looking for a copy of a rule so you can prepare an amendment? E- mail the Division to obtain a correctly formatted copy. **DO NOT USE the HTML version for preparing an amendment.**

TABLE OF CONTENTS

Title R313. Environmental Quality, Radiation Control.

As In effect on August 1, 2005

1. R313-12. General Provisions.
2. R313-14. Violations and Escalated Enforcement.
3. R313-15. Standards for Protection Against Radiation.
4. R313-16. General Requirements Applicable to the Installation, Registration, Inspection, and Use of Radiation Machines.
5. R313-17. Administrative Procedures.
6. R313-18. Notices, Instructions and Reports to Workers by Licensees or Registrants-- Inspections.
7. R313-19. Requirements of General Applicability to Licensing of Radioactive Material.
8. R313-21. General Licenses.
9. R313-22. Specific Licenses.
10. R313-24. Uranium Mills and Source Material Mill Tailings Disposal Facility Requirements.
11. R313-25. License Requirements for Land Disposal of Radioactive Waste - General Provisions.
12. R313-26. Generator Site Access Permit Requirements for Accessing Utah Radioactive Waste Disposal Facilities.
13. R313-28. Use of X-Rays in the Healing Arts.
14. R313-30. Therapeutic Radiation Machines.
15. R313-32. Medical Use of Radioactive Material.
16. R313-34. Requirements for Irradiators.
17. R313-35. Requirements for X-Ray Equipment Used for Non-Medical Applications.
18. R313-36. Special Requirements for Industrial Radiographic Operations.
19. R313-38. Licenses and Radiation Safety Requirements for Well Logging.
20. R313-70. Payments, Categories and Types of Fees.

U.S. NUCLEAR REGULATORY COMMISSION

In the Matter of Louisiana Energy Services LP

Docket No. 10-310-ML Official Exhibit No. 259

OFFERED by: Applicant/Licensee Intervenor NRC Staff Other

IDENTIFIED on 10/27/05 Witness Panel Wadhvani

Action Taken: ADMITTED REJECTED WITHDRAWN

Reporter/Clerk Bethmann Engel

Title table of contents prepared by the Division of Administrative Rules.

For questions regarding the *content* or *application* of rules under Title R313, please contact the promulgating agency. A list of agencies with links to their homepages is available at <http://www.utah.gov/government/agencylist.html>.

For questions about the *rulemaking process*, please contact the Division of Administrative Rules. *Please Note:* The Division of Administrative Rules is *not able* to answer questions about the content or application of these rules.

The HTML version of the UTAH ADMINISTRATIVE CODE is a convenience copy. This information is made available on the Internet as a public service. **Please see this disclaimer about information available from www.rules.utah.gov.**

[Division of Administrative Rules Home] | [UTAH ADMINISTRATIVE CODE List of Titles]

State Links: [Utah.gov Home](#) | [Utah.gov Terms of Use](#) | [Utah.gov Privacy Policy](#) | [Utah.gov Accessibility Policy](#).

DOCKETED
USNRC

2005 DEC 21 PM 3:30

OFFICE OF THE SECRETARY

REGULATIONS STAFF

State Links: Utah.gov | [State Online Services](#) | [Agency List](#) | Business.utah.gov | [Search](#).

Division of Administrative Rules.

A Service of the Department of Administrative Services.

[Division of Administrative Rules Home] | [UTAH ADMINISTRATIVE CODE List of Titles]

ATTENTION AGENCIES: Looking for a copy of a rule so you can prepare an amendment? E-mail the Division to obtain a correctly formatted copy. **DO NOT USE the HTML version for preparing an amendment.**

Rule R313-15. Standards for Protection Against Radiation.

As in effect on August 1, 2005

Table of Contents

- R313-15-1. Purpose, Authority and Scope.
- R313-15-2. Definitions.
- R313-15-3. Implementation.
- R313-15-101. Radiation Protection Programs.
- R313-15-201. Occupational Dose Limits for Adults.
- R313-15-202. Compliance with Requirements for Summation of External and Internal Doses.
- R313-15-203. Determination of External Dose from Airborne Radioactive Material.
- R313-15-204. Determination of Internal Exposure.
- R313-15-205. Determination of Prior Occupational Dose.
- R313-15-206. Planned Special Exposures.
- R313-15-207. Occupational Dose Limits for Minors.
- R313-15-208. Dose to an Embryo/Fetus.
- R313-15-301. Dose Limits for Individual Members of the Public.
- R313-15-302. Compliance with Dose Limits for Individual Members of the Public.
- R313-15-401. Radiological Criteria for License Termination - General Provisions.
- R313-15-402. Radiological Criteria for Unrestricted Use.
- R313-15-403. Criteria for License Termination Under Restricted Conditions.
- R313-15-404. Alternate Criteria for License Termination.
- R313-15-405. Public Notification and Public Participation.
- R313-15-406. Minimization of Contamination.
- R313-15-501. Surveys and Monitoring - General.
- R313-15-502. Conditions Requiring Individual Monitoring of External and Internal Occupational Dose.
- R313-15-503. Location of Individual Monitoring Devices.
- R313-15-601. Control of Access to High Radiation Areas.
- R313-15-602. Control of Access to Very High Radiation Areas.
- R313-15-603. Control of Access to Very High Radiation Areas – Irradiators.
- R313-15-701. Use of Process or Other Engineering Controls.

- R313-15-702. Use of Other Controls.
- R313-15-703. Use of Individual Respiratory Protection Equipment.
- R313-15-704. Further Restrictions on the Use of Respiratory Protection Equipment.
- R313-15-705. Application for Use of Higher Assigned Protection Factors.
- R313-15-801. Security and Control of Licensed or Registered Sources of Radiation.
- R313-15-901. Caution Signs.
- R313-15-902. Posting Requirements.
- R313-15-903. Exceptions to Posting Requirements.
- R313-15-904. Labeling Containers and Radiation Machines.
- R313-15-905. Exemptions to Labeling Requirements.
- R313-15-906. Procedures for Receiving and Opening Packages.
- R313-15-1001. Waste Disposal - General Requirements.
- R313-15-1002. Method for Obtaining Approval of Proposed Disposal Procedures.
- R313-15-1003. Disposal by Release into Sanitary Sewerage.
- R313-15-1004. Treatment or Disposal by Incineration.
- R313-15-1005. Disposal of Specific Wastes.
- R313-15-1006. Transfer for Disposal and Manifests.
- R313-15-1007. Compliance with Environmental and Health Protection Rules.
- R313-15-1008. Classification and Characteristics of Low-Level Radioactive Waste.
- R313-15-1101. Records - General Provisions.
- R313-15-1102. Records of Radiation Protection Programs.
- R313-15-1103. Records of Surveys.
- R313-15-1104. Records of Tests for Leakage or Contamination of Sealed Sources.
- R313-15-1105. Records of Prior Occupational Dose.
- R313-15-1106. Records of Planned Special Exposures.
- R313-15-1107. Records of Individual Monitoring Results.
- R313-15-1108. Records of Dose to Individual Members of the Public.
- R313-15-1109. Records of Waste Disposal.
- R313-15-1110. Records of Testing Entry Control Devices for Very High Radiation Areas.
- R313-15-1111. Form of Records.
- R313-15-1201. Reports of Stolen, Lost, or Missing Licensed or Registered Sources of Radiation.
- R313-15-1202. Notification of Incidents.
- R313-15-1203. Reports of Exposures, Radiation Levels, and Concentrations of Radioactive Material Exceeding the Constraints or Limits.
- R313-15-1204. Reports of Planned Special Exposures.
- R313-15-1205. Reports to Individuals of Exceeding Dose Limits.
- R313-15-1207. Notifications and Reports to Individuals.
- R313-15-1208. Reports of Leaking or Contaminated Sealed Sources.
- R313-15-1301. Vacating Premises.
- R313-15-1401. Testing for Leakage or Contamination of Sealed Sources.
- KEY
- Date of Enactment or Last Substantive Amendment
- Notice of Continuation
- Authorizing, Implemented, or Interpreted Law

R313-15-1. Purpose, Authority and Scope.

(1) Rule R313-15 establishes standards for protection against ionizing radiation resulting from activities conducted pursuant to licenses issued by the Executive

Secretary. These rules are issued pursuant to Subsections 19-3-104(4) and 19-3-104(8).

(2) The requirements of Rule R313-15 are designed to control the receipt, possession, use, transfer, and disposal of sources of radiation by any licensee or registrant so the total dose to an individual, including doses resulting from all sources of radiation other than background radiation, does not exceed the standards for protection against radiation prescribed in Rule R313-15. However, nothing in Rule R313-15 shall be construed as limiting actions that may be necessary to protect health and safety.

(3) Except as specifically provided in other sections of these rules, Rule R313-15 applies to persons licensed or registered by the Executive Secretary to receive, possess, use, transfer, or dispose of sources of radiation. The limits in Rule R313-15 do not apply to doses due to background radiation, to exposure of patients to radiation for the purpose of medical diagnosis or therapy, to exposure from individuals administered radioactive material and released in accordance with Rule R313-32 (incorporating 10 CFR 35.75 by reference), or to exposure from voluntary participation in medical research programs.

R313-15-2. Definitions.

"Annual limit on intake" (ALI) means the derived limit for the amount of radioactive material taken into the body of an adult worker by inhalation or ingestion in a year. ALI is the smaller value of intake of a given radionuclide in a year by the reference man that would result in a committed effective dose equivalent of 0.05 Sv (5 rem) or a committed dose equivalent of 0.5 Sv (50 rem) to any individual organ or tissue. ALI values for intake by ingestion and by inhalation of selected radionuclides are given in Table I, Columns 1 and 2, of Appendix B of 10 CFR 20.1001 to 20.2402, 2001 ed., which is incorporated by reference.

"Air-purifying respirator" means a respirator with an air-purifying filter, cartridge, or canister that removes specific air contaminants by passing ambient air through the air-purifying element.

"Assigned protection factor" (APF) means the expected workplace level of respiratory protection that would be provided by a properly functioning respirator or a class of respirators to properly fitted and trained users. Operationally, the inhaled concentration can be estimated by dividing the ambient airborne concentration by the APF.

"Atmosphere-supplying respirator" means a respirator that supplies the respirator user with breathing air from a source independent of the ambient atmosphere, and includes supplied-air respirators (SARs) and self-contained breathing apparatus (SCBA) units.

"Class" means a classification scheme for inhaled material according to its rate of clearance from the pulmonary region of the lung. Materials are classified as D, W, or Y, which applies to a range of clearance half-times: for Class D, Days, of less than ten days, for Class W, Weeks, from ten to 100 days, and for Class Y, Years, of

greater than 100 days. For purposes of these rules, "lung class" and "inhalation class" are equivalent terms.

"Constraint (dose constraint)" in accordance with 10 CFR 20.1003, 2001 ed., means a value above which specified licensee actions are required.

"Declared pregnant woman" means a woman who has voluntarily informed her employer, in writing, of her pregnancy and the estimated date of conception. The declaration remains in effect until the declared pregnant woman withdraws the declaration in writing or is no longer pregnant.

"Demand respirator" means an atmosphere-supplying respirator that admits breathing air to the facepiece only when a negative pressure is created inside the facepiece by inhalation.

"Derived air concentration" (DAC) means the concentration of a given radionuclide in air which, if breathed by the reference man for a working year of 2,000 hours under conditions of light work, results in an intake of one ALI. For purposes of these rules, the condition of light work is an inhalation rate of 1.2 cubic meters of air per hour for 2,000 hours in a year. DAC values are given in Table I, Column 3, of Appendix B of 10 CFR 20.1001 to 20.2402, 2001 ed., which is incorporated by reference.

"Derived air concentration-hour" (DAC-hour) means the product of the concentration of radioactive material in air, expressed as a fraction or multiple of the derived air concentration for each radionuclide, and the time of exposure to that radionuclide, in hours. A licensee or registrant may take 2,000 DAC-hours to represent one ALI, equivalent to a committed effective dose equivalent of 0.05 Sv (5 rem).

"Disposable respirator" means a respirator for which maintenance is not intended and that is designed to be discarded after excessive breathing resistance, sorbent exhaustion, physical damage, or end-of-service-life renders it unsuitable for use. Examples of this type of respirator are a disposable half-mask respirator or a disposable escape- only self-contained breathing apparatus (SCBA).

"Dosimetry processor" means an individual or an organization that processes and evaluates individual monitoring devices in order to determine the radiation dose delivered to the monitoring devices.

"Filtering facepiece" (dust mask) means a negative pressure particulate respirator with a filter as an integral part of the facepiece or with the entire facepiece composed of the filtering medium, not equipped with elastomeric sealing surfaces and adjustable straps.

"Fit factor" means a quantitative estimate of the fit of a particular respirator to a specific individual, and typically estimates the ratio of the concentration of a substance in ambient air to its concentration inside the respirator when worn.

"Fit test" means the use of a protocol to qualitatively or quantitatively evaluate the fit of a respirator on an individual.

"Helmet" means a rigid respiratory inlet covering that also provides head protection against impact and penetration.

"Hood" means a respiratory inlet covering that completely covers the head and neck and may also cover portions of the shoulders and torso.

"Inhalation class", refer to **"Class"**.

"Labeled package" means a package labeled with a Radioactive White I, Yellow II, or Yellow III label as specified in U.S. Department of Transportation regulations 49 CFR 172.403 and 49 CFR 172.436 through 440, 2000 ed. Labeling of packages containing radioactive materials is required by the U.S. Department of Transportation if the amount and type of radioactive material exceeds the limits for an excepted quantity or article as defined and limited by U.S. Department of Transportation regulations 49 CFR 173.403(m) and (w) and 49 CFR 173.421 through 424, 2000 ed.

"Loose-fitting facepiece" means a respiratory inlet covering that is designed to form a partial seal with the face.

"Lung class", refer to **"Class"**.

"Negative pressure respirator" (tight fitting) means a respirator in which the air pressure inside the facepiece is negative during inhalation with respect to the ambient air pressure outside the respirator.

"Nonstochastic effect" means a health effect, the severity of which varies with the dose and for which a threshold is believed to exist. Radiation-induced cataract formation is an example of a nonstochastic effect. For purposes of these rules, **"deterministic effect"** is an equivalent term.

"Planned special exposure" means an infrequent exposure to radiation, separate from and in addition to the annual occupational dose limits.

"Positive pressure respirator" means a respirator in which the pressure inside the respiratory inlet covering exceeds the ambient air pressure outside the respirator.

"Powered air-purifying respirator" (PAPR) means an air-purifying respirator that uses a blower to force the ambient air through air-purifying elements to the inlet covering.

"Pressure demand respirator" means a positive pressure atmosphere-supplying respirator that admits breathing air to the facepiece when the positive pressure is reduced inside the facepiece by inhalation.

"Qualitative fit test" (QLFT) means a pass/fail fit test to assess the adequacy of respirator fit that relies on the individual's response to the test agent.

"Quantitative fit test" (QNFT) means an assessment of the adequacy of respirator fit by numerically measuring the amount of leakage into the respirator.

"Quarter" means a period of time equal to one-fourth of the year observed by the licensee, approximately 13 consecutive weeks, providing that the beginning of the first quarter in a year coincides with the starting date of the year and that no day is omitted or duplicated in consecutive quarters.

"Reference Man" means a hypothetical aggregation of human physical and physiological characteristics determined by international consensus. These characteristics may be used by researchers and public health employees to standardize results of experiments and to relate biological insult to a common base. A description of the Reference Man is contained in the International Commission on Radiological Protection report, ICRP Publication 23, "Report of the Task Group on Reference Man."

"Respiratory protective equipment" means an apparatus, such as a respirator, used to reduce an individual's intake of airborne radioactive materials.

"Sanitary sewerage" means a system of public sewers for carrying off waste water and refuse, but excluding sewage treatment facilities, septic tanks, and leach fields owned or operated by the licensee or registrant.

"Self-contained breathing apparatus" (SCBA) means an atmosphere-supplying respirator for which the breathing air source is designed to be carried by the user.

"Stochastic effect" means a health effect that occurs randomly and for which the probability of the effect occurring, rather than its severity, is assumed to be a linear function of dose without threshold. Hereditary effects and cancer incidence are examples of stochastic effects. For purposes of these rules, "probabilistic effect" is an equivalent term.

"Supplied-air respirator" (SAR) or airline respirator means an atmosphere-supplying respirator for which the source of breathing air is not designed to be carried by the user.

"Tight-fitting facepiece" means a respiratory inlet covering that forms a complete seal with the face.

"User seal check" (fit check) means an action conducted by the respirator user to determine if the respirator is properly seated to the face. Examples include negative pressure check, positive pressure check, irritant smoke check, or isoamyl acetate check.

"Very high radiation area" means an area, accessible to individuals, in which radiation levels from radiation sources external to the body could result in an individual receiving an absorbed dose in excess of five Gy (500 rad) in one hour at one meter from a radiation source or one meter from any surface that the radiation penetrates.

"Weighting factor" w_T for an organ or tissue (T) means the proportion of the risk of stochastic effects resulting from irradiation of that organ or tissue to the total risk of stochastic effects when the whole body is irradiated uniformly. For calculating the effective dose equivalent, the values of w_T are:

TABLE

FACTORS	ORGAN DOSE WEIGHTING
Organ or Tissue	w_T
Gonads	0.25
Breast	0.15
Red bone marrow	0.12
Lung	0.12
Thyroid	0.03
Bone surfaces	0.03
Remainder	0.30 (1)
Whole Body	1.00 (2)

(1) 0.30 results from 0.06 for each of five "remainder" organs, excluding the skin and the lens of the eye, that receive the highest doses.

(2) For the purpose of weighting the external whole body dose, for adding it to the internal dose, a single weighting factor, $w_T = 1.0$, has been specified. The use of other weighting factors for external exposure will be approved on a case-by-case basis until such time as specific guidance is issued.

R313-15-3. Implementation.

(1) Any existing license or registration condition that is more restrictive than Rule R313-15 remains in force until there is an amendment or renewal of the license or registration.

(2) If a license or registration condition exempts a licensee or registrant from a provision of Rule R313-15 in effect on or before January 1, 1994, it also exempts the licensee or registrant from the corresponding provision of Rule R313-15.

(3) If a license or registration condition cites provisions of Rule R313-15 in effect prior to January 1, 1994, which do not correspond to any provisions of Rule R313-15, the license or registration condition remains in force until there is an amendment or renewal of the license or registration that modifies or removes this condition.

R313-15-101. Radiation Protection Programs.

(1) Each licensee or registrant shall develop, document, and implement a radiation protection program sufficient to ensure compliance with the provisions of Rule R313-15. See Section R313-15-1102 for recordkeeping requirements relating to these programs.

(2) The licensee or registrant shall use, to the extent practical, procedures and engineering controls based upon sound radiation protection principles to achieve occupational doses and doses to members of the public that are as low as is reasonably achievable (ALARA).

(3) The licensee or registrant shall, at intervals not to exceed 12 months, review the radiation protection program content and implementation.

(4) To implement the ALARA requirements of Subsection R313-15-101(2), and notwithstanding the requirements in Section R313-15-301, a constraint on air emissions of radioactive material to the environment, excluding radon-222 and its decay products, shall be established by licensees or registrants such that the individual member of the public likely to receive the highest dose will not be expected to receive a total effective dose equivalent in excess of 0.1 mSv (0.01 rem) per year from these emissions. If a licensee or registrant subject to this requirement exceeds this dose constraint, the licensee or registrant shall report the exceedance as provided in Section R313-15-1203 and promptly take appropriate corrective action to ensure against recurrence.

R313-15-201. Occupational Dose Limits for Adults.

(1) The licensee or registrant shall control the occupational dose to individual adults, except for planned special exposures pursuant to Section R313-15-206, to the following dose limits:

(a) An annual limit, which is the more limiting of:

(i) The total effective dose equivalent being equal to 0.05 Sv (5 rem); or

(ii) The sum of the deep dose equivalent and the committed dose equivalent to any individual organ or tissue other than the lens of the eye being equal to 0.50 Sv (50 rem).

(b) The annual limits to the lens of the eye, to the skin of the whole body, and to the skin of the extremities which are:

(i) A lens dose equivalent of 0.15 Sv (15 rem), and

(ii) A shallow dose equivalent of 0.50 Sv (50 rem) to the skin of the whole body or to the skin of any extremity.

(2) Doses received in excess of the annual limits, including doses received during accidents, emergencies, and planned special exposures, shall be subtracted from the limits for planned special exposures that the individual may receive during the current year and during the individual's lifetime. See Subsections R313-15-206(5)(a) and R313-15-206(5)(b).

(3) The assigned deep dose equivalent must be for the part of the body receiving the highest exposure. The assigned shallow dose equivalent must be the dose averaged over the contiguous ten square centimeters of skin receiving the highest exposure.

(a) The deep dose equivalent, lens dose equivalent and shallow dose equivalent may be assessed from surveys or other radiation measurements for the purpose of demonstrating compliance with the occupational dose limits, if the individual

monitoring device was not in the region of highest potential exposure, or the results of individual monitoring are unavailable; or

(b) When a protective apron is worn while working with medical fluoroscopic equipment and monitoring is conducted as specified in Subsection R313-15-502(1)(d), the effective dose equivalent for external radiation shall be determined as follows:

(i) When only one individual monitoring device is used and it is located at the neck outside the protective apron, and the reported dose exceeds 25 percent of the limit specified in Subsection R313-15-201(1), the reported deep dose equivalent value multiplied by 0.3 shall be the effective dose equivalent for external radiation; or

(ii) When individual monitoring devices are worn, both under the protective apron at the waist and outside the protective apron at the neck, the effective dose equivalent for external radiation shall be assigned the value of the sum of the deep dose equivalent reported for the individual monitoring device located at the waist under the protective apron multiplied by 1.5 and the deep dose equivalent reported for the individual monitoring device located at the neck outside the protective apron multiplied by 0.04.

(4) Derived air concentration (DAC) and annual limit on intake (ALI) values are specified in Table I of Appendix B of 10 CFR 20.1001 to 20.2402, 2001 ed., which is incorporated by reference, and may be used to determine the individual's dose and to demonstrate compliance with the occupational dose limits. See Section R313-15-1107.

(5) Notwithstanding the annual dose limits, the licensee shall limit the soluble uranium intake by an individual to ten milligrams in a week in consideration of chemical toxicity. See footnote 3, of Appendix B of 10 CFR 20.1001 to 20.2402, 2001 ed., which is incorporated by reference.

(6) The licensee or registrant shall reduce the dose that an individual may be allowed to receive in the current year by the amount of occupational dose received while employed by any other person. See Subsection R313-15-205(5).

R313-15-202. Compliance with Requirements for Summation of External and Internal Doses.

(1) If the licensee or registrant is required to monitor pursuant to both Subsections R313-15-502(1) and R313-15-502(2), the licensee or registrant shall demonstrate compliance with the dose limits by summing external and internal doses. If the licensee or registrant is required to monitor only pursuant to Subsection R313-15-502(1) or only pursuant to Subsection R313-15-502(2), then summation is not required to demonstrate compliance with the dose limits. The licensee or registrant may demonstrate compliance with the requirements for summation of external and internal doses pursuant to Subsections R313-15-202(2), R313-15-202(3) and R313-15-202(4). The dose equivalents for the lens of the eye, the skin, and the extremities are not included in the summation, but are subject to separate limits.

(2) Intake by Inhalation. If the only intake of radionuclides is by inhalation, the total effective dose equivalent limit is not exceeded if the sum of the deep dose equivalent divided by the total effective dose equivalent limit, and one of the following, does not exceed unity:

(a) The sum of the fractions of the inhalation ALI for each radionuclide, or

(b) The total number of derived air concentration-hours (DAC-hours) for all radionuclides divided by 2,000, or

(c) The sum of the calculated committed effective dose equivalents to all significantly irradiated organs or tissues (T) calculated from bioassay data using appropriate biological models and expressed as a fraction of the annual limit. For purposes of this requirement, an organ or tissue is deemed to be significantly irradiated if, for that organ or tissue, the product of the weighting factors, w_T , and the committed dose equivalent, $H_{T,50}$, per unit intake is greater than ten percent of the maximum weighted value of $H_{T,50}$, that is, $w_T H_{T,50}$, per unit intake for any organ or tissue.

(3) Intake by Oral Ingestion. If the occupationally exposed individual receives an intake of radionuclides by oral ingestion greater than ten percent of the applicable oral ALI, the licensee or registrant shall account for this intake and include it in demonstrating compliance with the limits.

(4) Intake through Wounds or Absorption through Skin. The licensee or registrant shall evaluate and, to the extent practical, account for intakes through wounds or skin absorption. The intake through intact skin has been included in the calculation of DAC for hydrogen-3 and does not need to be evaluated or accounted for pursuant to Subsection R313-15-202(4).

R313-15-203. Determination of External Dose from Airborne Radioactive Material.

(1) Licensees or registrants shall, when determining the dose from airborne radioactive material, include the contribution to the deep dose equivalent, lens dose equivalent, and shallow dose equivalent from external exposure to the radioactive cloud. See footnotes 1 and 2 of Appendix B of 10 CFR 20.1001 to 20.2402, 2001 ed., which is incorporated by reference.

(2) Airborne radioactivity measurements and DAC values shall not be used as the primary means to assess the deep dose equivalent when the airborne radioactive material includes radionuclides other than noble gases or if the cloud of airborne radioactive material is not relatively uniform. The determination of the deep dose equivalent to an individual shall be based upon measurements using instruments or individual monitoring devices.

R313-15-204. Determination of Internal Exposure.

(1) For purposes of assessing dose used to determine compliance with occupational dose equivalent limits, the licensee or registrant shall, when required pursuant to Section R313-15-502, take suitable and timely measurements of:

(a) Concentrations of radioactive materials in air in work areas; or

(b) Quantities of radionuclides in the body; or

(c) Quantities of radionuclides excreted from the body; or

(d) Combinations of these measurements.

(2) Unless respiratory protective equipment is used, as provided in Section R313-15-703, or the assessment of intake is based on bioassays, the licensee or registrant shall assume that an individual inhales radioactive material at the airborne concentration in which the individual is present.

(3) When specific information on the physical and biochemical properties of the radionuclides taken into the body or the behavior of the material in an individual is known, the licensee or registrant may:

(a) Use that information to calculate the committed effective dose equivalent, and, if used, the licensee or registrant shall document that information in the individual's record; and

(b) Upon prior approval of the Executive Secretary, adjust the DAC or ALI values to reflect the actual physical and chemical characteristics of airborne radioactive material, for example, aerosol size distribution or density; and

(c) Separately assess the contribution of fractional intakes of Class D, W, or Y compounds of a given radionuclide to the committed effective dose equivalent. See Appendix B of 10 CFR 20.1001 to 20.2402, 2001 ed., which is incorporated by reference.

(4) If the licensee or registrant chooses to assess intakes of Class Y material using the measurements given in Subsections R313-15-204(1)(b) or R313-15-204(1)(c), the licensee or registrant may delay the recording and reporting of the assessments for periods up to seven months, unless otherwise required by Section R313-15-1202 or Section R313-15-1203. This delay permits the licensee or registrant to make additional measurements basic to the assessments.

(5) If the identity and concentration of each radionuclide in a mixture are known, the fraction of the DAC applicable to the mixture for use in calculating DAC-hours shall be either:

(a) The sum of the ratios of the concentration to the appropriate DAC value, that is, D, W, or Y, from Appendix B of 10 CFR 20.1001 to 20.2402, 2001 ed., which is incorporated by reference, for each radionuclide in the mixture; or

(b) The ratio of the total concentration for all radionuclides in the mixture to the most restrictive DAC value for any radionuclide in the mixture.

(6) If the identity of each radionuclide in a mixture is known, but the concentration of one or more of the radionuclides in the mixture is not known, the DAC for the mixture shall be the most restrictive DAC of any radionuclide in the mixture.

(7) When a mixture of radionuclides in air exists, a licensee or registrant may disregard certain radionuclides in the mixture if:

(a) The licensee or registrant uses the total activity of the mixture in demonstrating compliance with the dose limits in Section R313-15-201 and in complying with the monitoring requirements in Subsection R313-15-502(2), and

(b) The concentration of any radionuclide disregarded is less than ten percent of its DAC, and

(c) The sum of these percentages for all of the radionuclides disregarded in the mixture does not exceed 30 percent.

(8) When determining the committed effective dose equivalent, the following information may be considered:

(a) In order to calculate the committed effective dose equivalent, the licensee or registrant may assume that the inhalation of one ALI, or an exposure of 2,000 DAC-hours, results in a committed effective dose equivalent of 0.05 Sv (5 rem) for radionuclides that have their ALIs or DACs based on the committed effective dose equivalent.

(b) For an ALI and the associated DAC determined by the nonstochastic organ dose limit of 0.50 Sv (50 rem), the intake of radionuclides that would result in a committed effective dose equivalent of 0.05 Sv (5 rem), that is, the stochastic ALI, is listed in parentheses in Table I of Appendix B of 10 CFR 20.1001 to 20.2402, 2001 ed., which is incorporated by reference. The licensee or registrant may, as a simplifying assumption, use the stochastic ALI to determine committed effective dose equivalent. However, if the licensee or registrant uses the stochastic ALI, the licensee or registrant shall also demonstrate that the limit in Subsection R313-15-201(1)(a)(ii) is met.

R313-15-205. Determination of Prior Occupational Dose.

(1) For each individual likely to receive, in a year, an occupational dose requiring monitoring pursuant to Section R313-15-502, the licensee or registrant shall:

(a) Determine the occupational radiation dose received during the current year; and

(b) Attempt to obtain the records of cumulative occupational radiation dose. A licensee or registrant may accept, as the record of cumulative radiation dose, an up-to-date form DRC-05 or equivalent, signed by the individual and countersigned by an appropriate official of the most recent employer for work involving radiation exposure, or the individual's current employer, if the individual is not employed by the licensee or registrant.

(2) Prior to permitting an individual to participate in a planned special exposure, the licensee or registrant shall determine:

(a) The internal and external doses from all previous planned special exposures; and

(b) All doses in excess of the limits, including doses received during accidents and emergencies, received during the lifetime of the individual.

(3) In complying with the requirements of Subsection R313-15-205(1), a licensee or registrant may:

(a) Accept, as a record of the occupational dose that the individual received during the current year, a written signed statement from the individual, or from the individual's most recent employer for work involving radiation exposure, that discloses the nature and the amount of any occupational dose that the individual received during the current year; and

(b) Obtain reports of the individual's dose equivalents from the most recent employer for work involving radiation exposure, or the individual's current employer, if the individual is not employed by the licensee or registrant, by telephone, telegram, facsimile, other electronic media or letter. The licensee or registrant shall request a written verification of the dose data if the authenticity of the transmitted report cannot be established.

(4) The licensee or registrant shall record the exposure history, as required by Subsection R313-15-205(1), on form DRC-05, or other clear and legible record, of all the information required on that form.

(a) The form or record shall show each period in which the individual received occupational exposure to radiation or radioactive material and shall be signed by the individual who received the exposure. For each period for which the licensee or registrant obtains reports, the licensee or registrant shall use the dose shown in the report in preparing form DRC-05 or equivalent. For any period in which the licensee or registrant does not obtain a report, the licensee or registrant shall place a notation on form DRC-05 or equivalent indicating the periods of time for which data are not available.

(b) For the purpose of complying with this requirement, licensees or registrants are not required to reevaluate the separate external dose equivalents and internal committed dose equivalents or intakes of radionuclides assessed pursuant to the rules in Rule R313-15 in effect before January 1, 1994. Further, occupational exposure histories obtained and recorded on form DRC-05 or equivalent before January 1, 1994, would not have included effective dose equivalent, but may be used in the absence of specific information on the intake of radionuclides by the individual.

(5) If the licensee or registrant is unable to obtain a complete record of an individual's current and previously accumulated occupational dose, the licensee or registrant shall assume:

(a) In establishing administrative controls under Subsection R313-15-201(6) for the current year, that the allowable dose limit for the individual is reduced by 12.5 mSv (1.25 rem) for each quarter for which records were unavailable and the

individual was engaged in activities that could have resulted in occupational radiation exposure; and

(b) That the individual is not available for planned special exposures.

(6) The licensee or registrant shall retain the records on form DRC-05 or equivalent until the Executive Secretary terminates each pertinent license or registration requiring this record. The licensee or registrant shall retain records used in preparing form DRC-05 or equivalent for three years after the record is made.

R313-15-206. Planned Special Exposures.

A licensee or registrant may authorize an adult worker to receive doses in addition to and accounted for separately from the doses received under the limits specified in Section R313-15-201 provided that each of the following conditions is satisfied:

(1) The licensee or registrant authorizes a planned special exposure only in an exceptional situation when alternatives that might avoid the dose estimated to result from the planned special exposure are unavailable or impractical.

(2) The licensee or registrant, and employer if the employer is not the licensee or registrant, specifically authorizes the planned special exposure, in writing, before the exposure occurs.

(3) Before a planned special exposure, the licensee or registrant ensures that each individual involved is:

(a) Informed of the purpose of the planned operation; and

(b) Informed of the estimated doses and associated potential risks and specific radiation levels or other conditions that might be involved in performing the task; and

(c) Instructed in the measures to be taken to keep the dose ALARA considering other risks that may be present.

(4) Prior to permitting an individual to participate in a planned special exposure, the licensee or registrant ascertains prior doses as required by Subsection R313-15-205(2) during the lifetime of the individual for each individual involved.

(5) Subject to Subsection R313-15-201(2), the licensee or registrant shall not authorize a planned special exposure that would cause an individual to receive a dose from all planned special exposures and all doses in excess of the limits to exceed:

(a) The numerical values of any of the dose limits in Subsection R313-15-201(1) in any year; and

(b) Five times the annual dose limits in Subsection R313-15-201(1) during the individual's lifetime.

(6) The licensee or registrant maintains records of the conduct of a planned special exposure in accordance with Section R313-15-1106 and submits a written report in accordance with Section R313-15-1204.

(7) The licensee or registrant records the best estimate of the dose resulting from the planned special exposure in the individual's record and informs the individual, in writing, of the dose within 30 days from the date of the planned special exposure. The dose from planned special exposures shall not be considered in controlling future occupational dose of the individual pursuant to Subsection R313-15-201(1) but shall be included in evaluations required by Subsections R313-15-206(4) and R313-15-206(5).

R313-15-207. Occupational Dose Limits for Minors.

The annual occupational dose limits for minors are ten percent of the annual occupational dose limits specified for adult workers in Section R313-15-201.

R313-15-208. Dose to an Embryo/Fetus.

(1) The licensee or registrant shall ensure that the dose equivalent to the embryo/fetus during the entire pregnancy, due to occupational exposure of a declared pregnant woman, does not exceed five mSv (0.5 rem). See Section R313-15-1107 for recordkeeping requirements.

(2) The licensee or registrant shall make efforts to avoid substantial variation above a uniform monthly exposure rate to a declared pregnant woman so as to satisfy the limit in Subsection R313-15-208(1).

(3) The dose equivalent to an embryo/fetus is the sum of:

(a) The deep dose equivalent to the declared pregnant woman; and

(b) The dose equivalent resulting from radionuclides in the embryo/fetus and radionuclides in the declared pregnant woman.

(4) If the dose equivalent to the embryo/fetus is found to have exceeded five mSv (0.5 rem) or is within 0.5 mSv (0.05 rem) of this dose by the time the woman declares the pregnancy to the licensee or registrant, the licensee or registrant shall be deemed to be in compliance with Subsection R313-15-208(1) if the additional dose equivalent to the embryo/fetus does not exceed 0.50 mSv (0.05 rem) during the remainder of the pregnancy.

R313-15-301. Dose Limits for Individual Members of the Public.

(1) Each licensee or registrant shall conduct operations so that:

(a) The total effective dose equivalent to individual members of the public from the licensed or registered operation does not exceed one mSv (0.1 rem) in a year, exclusive of the dose contributions from background radiation, from any medical administration the individual has received, from exposure to individuals

administered radioactive material and released, under Rule R313-32 (incorporating 10 CFR 35.75 by reference), from voluntary participation in medical research programs, and from the licensee's or registrant's disposal of radioactive material into sanitary sewerage in accordance with Section R313-15-1003; and

(b) The dose in any unrestricted area from external sources, exclusive of the dose contributions from patients administered radioactive material and released in accordance with Rule R313-32 (incorporating 10 CFR 35.75 by reference), does not exceed 0.02 mSv (0.002 rem) in any one hour; and

(c) Notwithstanding Subsection R313-15-301(1)(a), a licensee may permit visitors to an individual who cannot be released, under R313-32 (incorporating 10 CFR 35.75 by reference), to receive a radiation dose greater than one mSv (0.1 rem) if:

(i) The radiation dose received does not exceed five mSv (0.5 rem); and

(ii) The authorized user, as defined in R313-32, has determined before the visit that it is appropriate.; and

(d) The total effective dose equivalent to individual members of the public from infrequent exposure to radiation from radiation machines does not exceed 5 mSv (0.5 rem) in a year.

(2) If the licensee or registrant permits members of the public to have access to controlled areas, the limits for members of the public continue to apply to those individuals.

(3) A licensee, registrant, or an applicant for a license or registration may apply for prior Executive Secretary authorization to operate up to an annual dose limit for an individual member of the public of five mSv (0.5 rem). This application shall include the following information:

(a) Demonstration of the need for and the expected duration of operations in excess of the limit in Subsection R313-15-301(1); and

(b) The licensee's or registrant's program to assess and control dose within the five mSv (0.5 rem) annual limit; and

(c) The procedures to be followed to maintain the dose ALARA.

(4) In addition to the requirements of R313-15, a licensee subject to the provisions of the United States Environmental Protection Agency's generally applicable environmental radiation standards in 40 CFR 190 shall comply with those standards.

(5) The Executive Secretary may impose additional restrictions on radiation levels in unrestricted areas and on the total quantity of radionuclides that a licensee or registrant may release in effluents in order to restrict the collective dose.

R313-15-302. Compliance with Dose Limits for Individual Members of the Public.

(1) The licensee or registrant shall make or cause to be made surveys of radiation levels in unrestricted and controlled areas and radioactive materials in effluents released to unrestricted and controlled areas to demonstrate compliance with the dose limits for individual members of the public in Section R313-15-301.

(2) A licensee or registrant shall show compliance with the annual dose limit in Section R313-15-301 by:

(a) Demonstrating by measurement or calculation that the total effective dose equivalent to the individual likely to receive the highest dose from the licensed or registered operation does not exceed the annual dose limit; or

(b) Demonstrating that:

(i) The annual average concentrations of radioactive material released in gaseous and liquid effluents at the boundary of the unrestricted area do not exceed the values specified in Table II of Appendix B of 10 CFR 20.1001 to 20.2402, 2001 ed., which is incorporated by reference; and

(ii) If an individual were continuously present in an unrestricted area, the dose from external sources would not exceed 0.02 mSv (0.002 rem) in an hour and 0.50 mSv (0.05 rem) in a year.

(3) Upon approval from the Executive Secretary, the licensee or registrant may adjust the effluent concentration values in Appendix B, Table II of 10 CFR 20.1001 to 20.2402, 2001 ed., which is incorporated by reference, for members of the public, to take into account the actual physical and chemical characteristics of the effluents, such as, aerosol size distribution, solubility, density, radioactive decay equilibrium, and chemical form.

R313-15-401. Radiological Criteria for License Termination - General Provisions.

(1) The criteria in Sections R313-15-401 through R313-15-406 apply to the decommissioning of facilities licensed under Rules R313-22 and R313-25, as well as other facilities subject to the Board's jurisdiction under the Act. For low-level waste disposal facilities (Rule R313-25), the criteria apply only to ancillary surface facilities that support radioactive waste disposal activities.

(2) The criteria in Sections R313-15-401 through R313-15-406 do not apply to sites which:

(a) Have been decommissioned prior to the effective date of the rule in accordance with criteria approved by the Executive Secretary;

(b) Have previously submitted and received Executive Secretary approval on a license termination plan or decommissioning plan; or

(c) Submit a sufficient license termination plan or decommissioning plan before the effective date of the rule with criteria approved by the Executive Secretary.

(3) After a site has been decommissioned and the license terminated in accordance with the criteria in Sections R313-15-401 through R313-15-406, the Executive Secretary will require additional cleanup only if, based on new information, the Executive Secretary determines that the criteria in Sections R313-15-401 through R313-15-406 was not met and residual radioactivity remaining at the site could result in significant threat to public health and safety.

(4) When calculating the total effective dose equivalent to the average member of the critical group, the licensee shall determine the peak annual total effective dose equivalent dose expected within the first 1000 years after decommissioning.

R313-15-402. Radiological Criteria for Unrestricted Use.

A site will be considered acceptable for unrestricted use if the residual radioactivity that is distinguishable from background radiation results in a total effective dose equivalent to an average member of the critical group that does not exceed 0.25 mSv (0.025 rem) per year, including no greater than 0.04 mSv (0.004 rem) committed effective dose equivalent or total effective dose equivalent to an average member of the critical group from groundwater sources, and the residual radioactivity has been reduced to levels that are as low as reasonably achievable (ALARA). Determination of the levels which are ALARA must take into account consideration of any detriments, such as deaths from transportation accidents, expected to potentially result from decontamination and waste disposal.

R313-15-403. Criteria for License Termination Under Restricted Conditions.

A site will be considered acceptable for license termination under restricted conditions if:

(1) The licensee can demonstrate that further reductions in residual radioactivity necessary to comply with the provisions of Section R313-15-402 would result in net public or environmental harm or were not being made because the residual levels associated with restricted conditions are ALARA. Determination of the levels which are ALARA must take into account consideration of any detriments, such as traffic accidents, expected to potentially result from decontamination and waste disposal; and

(2) The licensee has made provisions for legally enforceable institutional controls that provide reasonable assurance that the total effective dose equivalent from residual radioactivity distinguishable from background to the average member of the critical group will not exceed 0.25 mSv (0.025 rem) per year; and

(3) The licensee has provided sufficient financial assurance to enable an independent third party, including a governmental custodian of a site, to assume and carry out responsibilities for any necessary control and maintenance of the site. Acceptable financial assurance mechanisms are:

(a) Funds placed into an account segregated from the licensee's assets outside the licensee's administrative control as described in Subsection R313-22-35(6)(a);

(b) Surety method, insurance, or other guarantee method as described in Subsection R313-22- 35(6)(b);

(c) A statement of intent in the case of Federal, State, or local Government licensees, as described in Subsection R313-22-35(6)(d); or

(d) When a governmental entity is assuming custody and ownership of a site, an arrangement that is deemed acceptable by such governmental entity; and

(4) The licensee has submitted a decommissioning plan or license termination plan to the Executive Secretary indicating the licensee's intent to decommission in accordance with Subsection R313-22-36(4) and specifying that the licensee intends to decommission by restricting use of the site. The licensee shall document in the license termination plan or decommissioning plan how the advice of individuals and institutions in the community who may be affected by the decommissioning has been sought and incorporated, as appropriate, following analysis of that advice;

(a) Licensees proposing to decommission by restricting use of the site shall seek advice from such affected parties regarding the following matters concerning the proposed decommissioning:

(i) Whether provisions for institutional controls proposed by the licensee;

(A) Will provide reasonable assurance that the total effective dose equivalent from residual radioactivity distinguishable from background to the average member of the critical group will not exceed 0.25 mSv (0.025 rem) total effective dose equivalent per year;

(B) Will be enforceable; and

(C) Will not impose undue burdens on the local community or other affected parties; and

(ii) Whether the licensee has provided sufficient financial assurance to enable an independent third party, including a governmental custodian of a site, to assume and carry out responsibilities for any necessary control and maintenance of the site; and

(b) In seeking advice on the issues identified in Subsection R313-15-403(4)(a), the licensee shall provide for:

(i) Participation by representatives of a broad cross section of community interests who may be affected by the decommissioning;

(ii) An opportunity for a comprehensive, collective discussion on the issues by the participants represented; and

(iii) A publicly available summary of the results of all such discussions, including a description of the individual viewpoints of the participants on the issues and the extent of agreement and disagreement among the participants on the issues; and

(5) Residual radioactivity at the site has been reduced so that if the institutional controls were no longer in effect, there is reasonable assurance that the total effective dose equivalent from residual radioactivity distinguishable from background to the average member of the critical group is as low as reasonably achievable and would not exceed either:

(a) one mSv (0.1 rem) per year; or

(b) five mSv (0.5 rem) per year provided the licensee:

(i) Demonstrates that further reductions in residual radioactivity necessary to comply with the one mSv (0.1 rem) per year value of Subsection R313-15-403(5)(a) are not technically achievable, would be prohibitively expensive, or would result in net public or environmental harm;

(ii) Makes provisions for durable institutional controls; and

(iii) Provides sufficient financial assurance to enable a responsible government entity or independent third party, including a governmental custodian of a site, both to carry out periodic rechecks of the site no less frequently than every five years to assure that the institutional controls remain in place as necessary to meet the criteria of Subsection R313-15-403(2) and to assume and carry out responsibilities for any necessary control and maintenance of those controls. Acceptable financial assurance mechanisms are those in Subsection R313-15-403(3).

R313-15-404. Alternate Criteria for License Termination.

(1) The Executive Secretary may terminate a license using alternative criteria greater than the dose criterion of Section R313-15-402, and Subsections R313-15-403(2) and R313-15-403(4)(a)(i)(A), if the licensee:

(a) Provides assurance that public health and safety would continue to be protected, and that it is unlikely that the dose from all man-made sources combined, other than medical, would be more than the one mSv (0.1 rem) per year limit of Subsection R313-15-301(1)(a), by submitting an analysis of possible sources of exposure; and

(b) Has employed, to the extent practical, restrictions on site use according to the provisions of Section R313-15-403 in minimizing exposures at the site; and

(c) Reduces doses to ALARA levels, taking into consideration any detriments such as traffic accidents expected to potentially result from decontamination and waste disposal; and

(d) Has submitted a decommissioning plan or license termination plan to the Executive Secretary indicating the licensee's intent to decommission in accordance with Subsection R313-22-36(4), and specifying that the licensee proposes to decommission by use of alternate criteria. The licensee shall document in the decommissioning plan or license termination plan how the advice of individuals and institutions in the community who may be affected by the decommissioning has

been sought and addressed, as appropriate, following analysis of that advice. In seeking such advice, the licensee shall provide for:

(i) Participation by representatives of a broad cross section of community interests who may be affected by the decommissioning; and

(ii) An opportunity for a comprehensive, collective discussion on the issues by the participants represented; and

(iii) A publicly available summary of the results of all such discussions, including a description of the individual viewpoints of the participants on the issues and the extent of agreement and disagreement among the participants on the issues.

(2) The use of alternate criteria to terminate a license requires the approval of the Executive Secretary after consideration of recommendations from the Division's staff, comments provided by federal, state and local governments, and any public comments submitted pursuant to Section R313-15-405.

R313-15-405. Public Notification and Public Participation.

Upon the receipt of a license termination plan or decommissioning plan from the licensee, or a proposal by the licensee for release of a site pursuant to Sections R313-15-403 or R313-15-404, or whenever the Executive Secretary deems such notice to be in the public interest, the Executive Secretary shall:

(1) Notify and solicit comments from:

(a) Local and State governments in the vicinity of the site and any Indian Nation or other indigenous people that have treaty or statutory rights that could be affected by the decommissioning; and

(b) Federal, state and local governments for cases where the licensee proposes to release a site pursuant to Section R313-15-404.

(2) Publish a notice in a forum, such as local newspapers, letters to State or local organizations, or other appropriate forum, that is readily accessible to individuals in the vicinity of the site, and solicit comments from affected parties.

R313-15-406. Minimization of Contamination.

Applicants for licenses, other than renewals, shall describe in the application how facility design and procedures for operation will minimize, to the extent practicable, contamination of the facility and the environment, facilitate eventual decommissioning, and minimize, to the extent practicable, the generation of waste.

R313-15-501. Surveys and Monitoring - General.

(1) Each licensee or registrant shall make, or cause to be made, surveys that:

(a) Are necessary for the licensee or registrant to comply with Rule R313-15; and

(b) Are necessary under the circumstances to evaluate:

(i) The magnitude and the extent of radiation levels; and

(ii) Concentrations or quantities of radioactive material; and

(iii) The potential radiological hazards.

(2) The licensee or registrant shall ensure that instruments and equipment used for quantitative radiation measurements, for example, dose rate and effluent monitoring, are calibrated at intervals not to exceed 12 months for the radiation measured, except when a more frequent interval is specified in another applicable part of these rules or a license condition.

(3) All personnel dosimeters, except for direct and indirect reading pocket ionization chambers and those dosimeters used to measure the dose to any extremity, that require processing to determine the radiation dose and that are used by licensees and registrants to comply with Section R313-15-201, with other applicable provisions of these rules, or with conditions specified in a license or registration shall be processed and evaluated by a dosimetry processor:

(a) Holding current personnel dosimetry accreditation from the National Voluntary Laboratory Accreditation Program (NVLAP) of the National Institute of Standards and Technology; and

(b) Approved in this accreditation process for the type of radiation or radiations included in the NVLAP program that most closely approximates the type of radiation or radiations for which the individual wearing the dosimeter is monitored.

(4) The licensee or registrant shall ensure that adequate precautions are taken to prevent a deceptive exposure of an individual monitoring device.

R313-15-502. Conditions Requiring Individual Monitoring of External and Internal Occupational Dose.

Each licensee or registrant shall monitor exposures from sources of radiation at levels sufficient to demonstrate compliance with the occupational dose limits of Rule R313-15. As a minimum:

(1) Each licensee or registrant shall monitor occupational exposure to radiation from licensed, unlicensed, and registered radiation sources under the control of the licensee and shall supply and require the use of individual monitoring devices by:

(a) Adults likely to receive, in one year from sources external to the body, a dose in excess of ten percent of the limits in Subsection R313-15-201(1); and

(b) Minors likely to receive, in one year, from radiation sources external to the body, a deep dose equivalent in excess of one mSv (0.1 rem), a lens dose

equivalent in excess of 1.5 mSv (0.15 rem), or a shallow dose equivalent to the skin or to the extremities in excess of five mSv (0.5 rem); and

(c) Declared pregnant women likely to receive during the entire pregnancy, from radiation sources external to the body, a deep dose equivalent in excess of one mSv (0.1 rem); and

(d) Individuals entering a high or very high radiation area; and

(e) Individuals working with medical fluoroscopic equipment.

(i) An individual monitoring device used for the dose to an embryo/fetus of a declared pregnant woman, pursuant to Subsection R313-15-208(1), shall be located under the protective apron at the waist.

(A) If an individual monitoring device worn by a declared pregnant woman has a monthly reported dose equivalent value in excess of 0.5 mSv (50 mrem), the value to be used for determining the dose to the embryo/fetus, pursuant to Subsection R313-15-208(3)(a) for radiation from medical fluoroscopy, may be the value reported by the individual monitoring device worn at the waist underneath the protective apron which has been corrected for the potential overestimation of dose recorded by the monitoring device because of the overlying tissue of the pregnant individual. This correction shall be performed by a radiation safety officer of an institutional radiation safety committee, a qualified expert approved by the Board, or a representative of the Executive Secretary.

(ii) An individual monitoring device used for lens dose equivalent shall be located at the neck, or an unshielded location closer to the eye, outside the protective apron.

(iii) When only one individual monitoring device is used to determine the effective dose equivalent for external radiation pursuant to Subsection R313-15-201(3)(b), it shall be located at the neck outside the protective apron. When a second individual monitoring device is used, for the same purpose, it shall be located under the protective apron at the waist. Note: The second individual monitoring device is required for a declared pregnant woman.

(iv) A registrant is not required to supply and require the use of individual monitoring devices provided the registrant has conducted a survey, pursuant to Section R313-15-501, that demonstrates that the working environment the individual encounters will not likely result in a dose in excess of ten percent of the limits in Subsection R313-15-201(1), and that the individual is neither a minor nor a declared pregnant woman.

(2) Each licensee or registrant shall monitor, to determine compliance with Section R313-15-204, the occupational intake of radioactive material by and assess the committed effective dose equivalent to:

(a) Adults likely to receive, in one year, an intake in excess of ten percent of the applicable ALI(s) in Table I, Columns 1 and 2, of Appendix B of 10 CFR 20.1001 to 20.2402, 2001 ed., which is incorporated by reference; and

(b) Minors likely to receive, in one year, a committed effective dose equivalent in excess of one mSv (0.1 rem); and

(c) Declared pregnant women likely to receive, during the entire pregnancy, a committed effective dose equivalent in excess of one mSv (0.1 rem).

Note: All of the occupational doses in Section R313-15-201 continue to be applicable to the declared pregnant worker as long as the embryo/fetus dose limit is not exceeded.

R313-15-503. Location of Individual Monitoring Devices.

Each licensee or registrant shall ensure that individuals who are required to monitor occupational doses in accordance with Subsection R313-15-502(1) wear individual monitoring devices as follows:

(1) An individual monitoring device used for monitoring the dose to the whole body shall be worn at the unshielded location of the whole body likely to receive the highest exposure. When a protective apron is worn, the location of the individual monitoring device is typically at the neck (collar).

(2) An individual monitoring device used for monitoring the dose to an embryo/fetus of a declared pregnant woman, pursuant to Subsection R313-15-208(1), shall be located at the waist under any protective apron being worn by the woman.

(3) An individual monitoring device used for monitoring the lens dose equivalent, to demonstrate compliance with Subsection R313-15-201(1)(b)(i), shall be located at the neck (collar), outside any protective apron being worn by the monitored individual, or at an unshielded location closer to the eye.

(4) An individual monitoring device used for monitoring the dose to the extremities, to demonstrate compliance with Subsection R313-15-201(1)(b)(ii), shall be worn on the extremity likely to receive the highest exposure. Each individual monitoring device shall be oriented to measure the highest dose to the extremity being monitored.

R313-15-601. Control of Access to High Radiation Areas.

(1) The licensee or registrant shall ensure that each entrance or access point to a high radiation area has one or more of the following features:

(a) A control device that, upon entry into the area, causes the level of radiation to be reduced below that level at which an individual might receive a deep dose equivalent of one mSv (0.1 rem) in one hour at 30 centimeters from the source of radiation or from any surface that the radiation penetrates; or

(b) A control device that energizes a conspicuous visible or audible alarm signal so that the individual entering the high radiation area and the supervisor of the activity are made aware of the entry; or

(c) Entryways that are locked, except during periods when access to the areas is required, with positive control over each individual entry.

(2) In place of the controls required by Subsection R313-15-601(1) for a high radiation area, the licensee or registrant may substitute continuous direct or electronic surveillance that is capable of preventing unauthorized entry.

(3) The licensee or registrant may apply to the Executive Secretary for approval of alternative methods for controlling access to high radiation areas.

(4) The licensee or registrant shall establish the controls required by Subsections R313-15-601(1) and R313-15-601(3) in a way that does not prevent individuals from leaving a high radiation area.

(5) The licensee or registrant is not required to control each entrance or access point to a room or other area that is a high radiation area solely because of the presence of radioactive materials prepared for transport and packaged and labeled in accordance with the rules of the U.S. Department of Transportation provided that:

(a) The packages do not remain in the area longer than three days; and

(b) The dose rate at one meter from the external surface of any package does not exceed 0.1 mSv (0.01 rem) per hour.

(6) The licensee or registrant is not required to control entrance or access to rooms or other areas in hospitals solely because of the presence of patients containing radioactive material, provided that there are personnel in attendance who are taking the necessary precautions to prevent the exposure of individuals to radiation or radioactive material in excess of the established limits in Rule R313-15 and to operate within the ALARA provisions of the licensee's or registrant's radiation protection program.

(7) The registrant is not required to control entrance or access to rooms or other areas containing sources of radiation capable of producing a high radiation area as described in Section R313-15-601 if the registrant has met all the specific requirements for access and control specified in other applicable sections of these rules, such as, Rule R313-36 for industrial radiography, Rule R313-28 for x rays in the healing arts, Rule R313-30 for therapeutic radiation machines, and Rule R313-35 for industrial use of x-ray systems.

R313-15-602. Control of Access to Very High Radiation Areas.

(1) In addition to the requirements in Section R313-15-601, the licensee or registrant shall institute measures to ensure that an individual is not able to gain unauthorized or inadvertent access to areas in which radiation levels could be encountered at five Gy (500 rad) or more in one hour at one meter from a source of radiation or any surface through which the radiation penetrates. This requirement does not apply to rooms or areas in which diagnostic x-ray systems are the only source of radiation, or to non-self-shielded irradiators.

(2) The registrant is not required to control entrance or access to rooms or other areas containing sources of radiation capable of producing a very high radiation area as described in Subsection R313-15-602(1) if the registrant has met all the specific requirements for access and control specified in other applicable sections of these rules, such as, Rule R313-36 for industrial radiography, Rule R313-28 for x rays in the healing arts, Rule R313-30 for therapeutic radiation machines, and Rule R313-35 for industrial use of x-ray systems.

R313-15-603. Control of Access to Very High Radiation Areas -- Irradiators.

(1) Section R313-15-603 applies to licensees or registrants with sources of radiation in non-self-shielded irradiators. Section R313-15-603 does not apply to sources of radiation that are used in teletherapy, in industrial radiography, or in completely self-shielded irradiators in which the source of radiation is both stored and operated within the same shielding radiation barrier and, in the designed configuration of the irradiator, is always physically inaccessible to any individual and cannot create a high levels of radiation in an area that is accessible to any individual.

(2) Each area in which there may exist radiation levels in excess of five Gy (500 rad) in one hour at one meter from a source of radiation that is used to irradiate materials shall meet the following requirements:

(a) Each entrance or access point shall be equipped with entry control devices which:

(i) Function automatically to prevent any individual from inadvertently entering a very high radiation area; and

(ii) Permit deliberate entry into the area only after a control device is actuated that causes the radiation level within the area, from the source of radiation, to be reduced below that at which it would be possible for an individual to receive a deep dose equivalent in excess of one mSv (0.1 rem) in one hour; and

(iii) Prevent operation of the source of radiation if it would produce radiation levels in the area that could result in a deep dose equivalent to an individual in excess of one mSv (0.1 rem) in one hour.

(b) Additional control devices shall be provided so that, upon failure of the entry control devices to function as required by Subsection R313-15-603(2)(a):

(i) The radiation level within the area, from the source of radiation, is reduced below that at which it would be possible for an individual to receive a deep dose equivalent in excess of one mSv (0.1 rem) in one hour; and

(ii) Conspicuous visible and audible alarm signals are generated to make an individual attempting to enter the area aware of the hazard and at least one other authorized individual, who is physically present, familiar with the activity, and prepared to render or summon assistance, aware of the failure of the entry control devices.

(c) The licensee or registrant shall provide control devices so that, upon failure or removal of physical radiation barriers other than the sealed source's shielded storage container:

(i) The radiation level from the source of radiation is reduced below that at which it would be possible for an individual to receive a deep dose equivalent in excess of one mSv (0.1 rem) in one hour; and

(ii) Conspicuous visible and audible alarm signals are generated to make potentially affected individuals aware of the hazard and the licensee or registrant or at least one other individual, who is familiar with the activity and prepared to render or summon assistance, aware of the failure or removal of the physical barrier.

(d) When the shield for stored sealed sources is a liquid, the licensee or registrant shall provide means to monitor the integrity of the shield and to signal, automatically, loss of adequate shielding.

(e) Physical radiation barriers that comprise permanent structural components, such as walls, that have no credible probability of failure or removal in ordinary circumstances need not meet the requirements of Subsections R313-15-603(2)(c) and R313-15-603(2)(d).

(f) Each area shall be equipped with devices that will automatically generate conspicuous visible and audible alarm signals to alert personnel in the area before the source of radiation can be put into operation and in time for any individual in the area to operate a clearly identified control device, which shall be installed in the area and which can prevent the source of radiation from being put into operation.

(g) Each area shall be controlled by use of such administrative procedures and such devices as are necessary to ensure that the area is cleared of personnel prior to each use of the source of radiation.

(h) Each area shall be checked by a radiation measurement to ensure that, prior to the first individual's entry into the area after any use of the source of radiation, the radiation level from the source of radiation in the area is below that at which it would be possible for an individual to receive a deep dose equivalent in excess of one mSv (0.1 rem) in one hour.

(i) The entry control devices required in Subsection R313-15-603(2)(a) shall be tested for proper functioning. See Section R313-15-1110 for recordkeeping requirements.

(i) Testing shall be conducted prior to initial operation with the source of radiation on any day, unless operations were continued uninterrupted from the previous day; and

(ii) Testing shall be conducted prior to resumption of operation of the source of radiation after any unintentional interruption; and

(iii) The licensee or registrant shall submit and adhere to a schedule for periodic tests of the entry control and warning systems.

(j) The licensee or registrant shall not conduct operations, other than those necessary to place the source of radiation in safe condition or to effect repairs on controls, unless control devices are functioning properly.

(k) Entry and exit portals that are used in transporting materials to and from the irradiation area, and that are not intended for use by individuals, shall be controlled by such devices and administrative procedures as are necessary to physically protect and warn against inadvertent entry by any individual through these portals. Exit portals for irradiated materials shall be equipped to detect and signal the presence of any loose radioactive material that is carried toward such an exit and automatically to prevent loose radioactive material from being carried out of the area.

(3) Licensees, registrants, or applicants for licenses or registrations for sources of radiation within the purview of Subsection R313-15-603(2) which will be used in a variety of positions or in locations, such as open fields or forests, that make it impractical to comply with certain requirements of Subsection R313-15-603(2), such as those for the automatic control of radiation levels, may apply to the Executive Secretary for approval of alternative safety measures. Alternative safety measures shall provide personnel protection at least equivalent to those specified in Subsection R313-15-603(2). At least one of the alternative measures shall include an entry-preventing interlock control based on a measurement of the radiation that ensures the absence of high radiation levels before an individual can gain access to the area where such sources of radiation are used.

(4) The entry control devices required by Subsections R313-15-603(2) and R313-15-603(3) shall be established in such a way that no individual will be prevented from leaving the area.

R313-15-701. Use of Process or Other Engineering Controls.

The licensee or registrant shall use, to the extent practical, process or other engineering controls, such as, containment, decontamination, or ventilation, to control the concentration of radioactive material in air.

R313-15-702. Use of Other Controls.

(1) When it is not practical to apply process or other engineering controls to control the concentration of radioactive material in the air to values below those that define an airborne radioactivity area, the licensee or registrant shall, consistent with maintaining the total effective dose equivalent ALARA, increase monitoring and limit intakes by one or more of the following means:

- (a) Control of access; or
- (b) Limitation of exposure times; or
- (c) Use of respiratory protection equipment; or
- (d) Other controls.

(2) If the licensee or registrant performs an ALARA analysis to determine whether or not respirators should be used, the licensee may consider safety factors other than radiological factors. The licensee or registrant should also consider the impact of respirator use on workers' industrial health and safety.

R313-15-703. Use of Individual Respiratory Protection Equipment.

If the licensee or registrant uses respiratory protection equipment to limit the intake of radioactive material:

(1) Except as provided in Subsection R313-15-703(2), the licensee or registrant shall use only respiratory protection equipment that is tested and certified by the National Institute for Occupational Safety and Health.

(2) The licensee or registrant may use equipment that has not been tested or certified by the National Institute for Occupational Safety and Health or for which there is no schedule for testing or certification, provided the licensee or registrant has submitted to the Executive Secretary and the Executive Secretary has approved an application for authorized use of that equipment. The application must include a demonstration by testing, or a demonstration on the basis of reliable test information, that the material and performance characteristics of the equipment are capable of providing the proposed degree of protection under anticipated conditions of use.

(3) The licensee or registrant shall implement and maintain a respiratory protection program that includes:

(a) Air sampling sufficient to identify the potential hazard, permit proper equipment selection, and estimate doses; and

(b) Surveys and bioassays, as necessary, to evaluate actual intakes; and

(c) Testing of respirators for operability, user seal check for face sealing devices and functional check for others, immediately prior to each use; and

(d) Written procedures regarding

(i) Monitoring, including air sampling and bioassays;

(ii) Supervision and training of respirator users;

(iii) Fit testing;

(iv) Respirator selection;

(v) Breathing air quality;

(vi) Inventory and control;

(vii) Storage, issuance, maintenance, repair, testing, and quality assurance of respiratory protection equipment;

(viii) Recordkeeping; and

(ix) Limitations on periods of respirator use and relief from respirator use; and

(e) Determination by a physician prior to initial fitting of respirators, before the first field use of non-face sealing respirators, and either every 12 months thereafter or periodically at a frequency determined by a physician, that the individual user is medically fit to use the respiratory protection equipment; and

(f) Fit testing, with fit factor greater than or equal to ten times the APF for negative pressure devices, and a fit factor greater than or equal to 500 for positive pressure, continuous flow, and pressure-demand devices, before the first field use of tight fitting, face-sealing respirators and periodically thereafter at a frequency not to exceed one year. Fit testing must be performed with the facepiece operating in the negative pressure mode.

(4) The licensee or registrant shall advise each respirator user that the user may leave the area at any time for relief from respirator use in the event of equipment malfunction, physical or psychological distress, procedural or communication failure, significant deterioration of operating conditions, or any other conditions that might require such relief.

(5) The licensee or registrant shall also consider limitations appropriate to the type and mode of use. When selecting respiratory devices the licensee shall provide for vision correction, adequate communication, low temperature work environments, and the concurrent use of other safety or radiological protection equipment. The licensee or registrant shall use equipment in such a way as not to interfere with the proper operation of the respirator.

(6) Standby rescue persons are required whenever one-piece atmosphere-supplying suits, or any combination of supplied air respiratory protection device and personnel protective equipment are used from which an unaided individual would have difficulty extricating himself or herself. The standby persons must be equipped with respiratory protection devices or other apparatus appropriate for the potential hazards. The standby rescue persons shall observe or otherwise maintain continuous communication with the workers (visual, voice, signal line, telephone, radio, or other suitable means), and be immediately available to assist them in case of a failure of the air supply or for any other reason that requires relief from distress. A sufficient number of standby rescue persons must be immediately available to assist all users of this type of equipment and to provide effective emergency rescue if needed.

(7) Atmosphere-supplying respirators must be supplied with respirable air of grade D quality or better as defined by the Compressed Gas Association in publication G-7.1, "Commodity Specification for Air," 1997 ed. and included in 29 CFR 1910.134(i)(1)(ii)(A) through (E), 2000 ed. Grade D quality air criteria include:

(a) Oxygen content (v/v) of 19.5 to 23.5%;

(b) Hydrocarbon (condensed) content of five milligrams per cubic meter of air or less;

(c) Carbon monoxide (CO) content of ten ppm or less;

(d) Carbon dioxide content of 1,000 ppm or less; and

(e) Lack of noticeable odor.

(8) The licensee shall ensure that no objects, materials or substances, such as facial hair, or any conditions that interfere with the face and facepiece seal or valve function, and that are under the control of the respirator wearer, are present between the skin of the wearer's face and the sealing surface of a tight-fitting respirator facepiece.

(9) In estimating the dose to individuals from intake of airborne radioactive materials, the concentration of radioactive material in the air that is inhaled when respirators are worn is initially assumed to be the ambient concentration in air without respiratory protection, divided by the assigned protection factor. If the dose is later found to be greater than the estimated dose, the corrected value must be used. If the dose is later found to be less than the estimated dose, the corrected value may be used.

R313-15-704. Further Restrictions on the Use of Respiratory Protection Equipment.

The Executive Secretary may impose restrictions in addition to the provisions of Section R313-15-702, Section R313-15-703, and Appendix A of 10 CFR 20.1001 to 20.2402, 2001 ed., which is incorporated by reference to:

(1) Ensure that the respiratory protection program of the licensee or registrant is adequate to limit doses to individuals from intakes of airborne radioactive materials consistent with maintaining total effective dose equivalent ALARA; and

(2) Limit the extent to which a licensee or registrant may use respiratory protection equipment instead of process or other engineering controls.

R313-15-705. Application for Use of Higher Assigned Protection Factors.

The licensee or registrant shall obtain authorization from the Executive Secretary before using assigned protection factors in excess of those specified in Appendix A of 10 CFR 20.1001 to 20.2402, 2001 ed., which is incorporated by reference. The Executive Secretary may authorize a licensee or registrant to use higher assigned protection factors on receipt of an application that:

(1) Describes the situation for which a need exists for higher protection factors; and

(2) Demonstrates that the respiratory protection equipment provides these higher protection factors under the proposed conditions of use.

R313-15-801. Security and Control of Licensed or Registered Sources of Radiation.

- (1) The licensee or registrant shall secure licensed or registered radioactive material from unauthorized removal or access.
- (2) The licensee or registrant shall maintain constant surveillance, and use devices or administrative procedures to prevent unauthorized use of licensed or registered radioactive material that is in an unrestricted area and that is not in storage.
- (3) The registrant shall secure registered radiation machines from unauthorized removal.
- (4) The registrant shall use devices or administrative procedures to prevent unauthorized use of registered radiation machines.

R313-15-901. Caution Signs.

- (1) Standard Radiation Symbol. Unless otherwise authorized by the Executive Secretary, the symbol prescribed by 10 CFR 20.1901, 2001 ed., which is incorporated by reference, shall use the colors magenta, or purple, or black on yellow background. The symbol prescribed is the three-bladed design as follows:
 - (a) Cross-hatched area is to be magenta, or purple, or black, and
 - (b) The background is to be yellow.
- (2) Exception to Color Requirements for Standard Radiation Symbol. Notwithstanding the requirements of 10 CFR 20.1901(a), 2001 ed., which is incorporated by reference, licensees or registrants are authorized to label sources, source holders, or device components containing sources of radiation that are subjected to high temperatures, with conspicuously etched or stamped radiation caution symbols and without a color requirement.
- (3) Additional Information on Signs and Labels. In addition to the contents of signs and labels prescribed in Rule R313-15, the licensee or registrant shall provide, on or near the required signs and labels, additional information, as appropriate, to make individuals aware of potential radiation exposures and to minimize the exposures.

R313-15-902. Posting Requirements.

- (1) Posting of Radiation Areas. The licensee or registrant shall post each radiation area with a conspicuous sign or signs bearing the radiation symbol and the words "CAUTION, RADIATION AREA."
- (2) Posting of High Radiation Areas. The licensee or registrant shall post each high radiation area with a conspicuous sign or signs bearing the radiation symbol and the words "CAUTION, HIGH RADIATION AREA" or "DANGER, HIGH RADIATION AREA."

(3) Posting of Very High Radiation Areas. The licensee or registrant shall post each very high radiation area with a conspicuous sign or signs bearing the radiation symbol and words "GRAVE DANGER, VERY HIGH RADIATION AREA."

(4) Posting of Airborne Radioactivity Areas. The licensee or registrant shall post each airborne radioactivity area with a conspicuous sign or signs bearing the radiation symbol and the words "CAUTION, AIRBORNE RADIOACTIVITY AREA" or "DANGER, AIRBORNE RADIOACTIVITY AREA."

(5) Posting of Areas or Rooms in which Licensed or Registered Material is Used or Stored. The licensee or registrant shall post each area or room in which there is used or stored an amount of licensed or registered material exceeding ten times the quantity of such material specified in Appendix C of 10 CFR 20.1001 to 20.2402, 2001 ed., which is incorporated by reference, with a conspicuous sign or signs bearing the radiation symbol and the words "CAUTION, RADIOACTIVE MATERIAL" or "DANGER, RADIOACTIVE MATERIAL."

R313-15-903. Exceptions to Posting Requirements.

(1) A licensee or registrant is not required to post caution signs in areas or rooms containing sources of radiation for periods of less than eight hours, if each of the following conditions is met:

(a) The sources of radiation are constantly attended during these periods by an individual who takes the precautions necessary to prevent the exposure of individuals to sources of radiation in excess of the limits established in Rule R313-15; and

(b) The area or room is subject to the licensee's or registrant's control.

(2) Rooms or other areas in hospitals that are occupied by patients are not required to be posted with caution signs pursuant to Section R313-15-902 provided that the patient could be released from licensee control pursuant to Section R313-32-75.

(3) A room or area is not required to be posted with a caution sign because of the presence of a sealed source provided the radiation level at 30 centimeters from the surface of the sealed source container or housing does not exceed 0.05 mSv (0.005 rem) per hour.

(4) A room or area is not required to be posted with a caution sign because of the presence of radiation machines used solely for diagnosis in the healing arts.

(5) Rooms in hospitals or clinics that are used for teletherapy are exempt from the requirement to post caution signs under Section R313-15-902 if:

(a) Access to the room is controlled pursuant to Section R313-32-615; and

(b) Personnel in attendance take necessary precautions to prevent the inadvertent exposure of workers, other patients, and members of the public to radiation in excess of the limits established in Rule R313-15.

R313-15-904. Labeling Containers and Radiation Machines.

- (1) The licensee or registrant shall ensure that each container of licensed or registered material bears a durable, clearly visible label bearing the radiation symbol and the words "CAUTION, RADIOACTIVE MATERIAL" or "DANGER, RADIOACTIVE MATERIAL." The label shall also provide information, such as the radionuclides present, an estimate of the quantity of radioactivity, the date for which the activity is estimated, radiation levels, kinds of materials, and mass enrichment, to permit individuals handling or using the containers, or working in the vicinity of the containers, to take precautions to avoid or minimize exposures.
- (2) Each licensee or registrant shall, prior to removal or disposal of empty uncontaminated containers to unrestricted areas, remove or deface the radioactive material label or otherwise clearly indicate that the container no longer contains radioactive materials.
- (3) Each registrant shall ensure that each radiation machine is labeled in a conspicuous manner which cautions individuals that radiation is produced when it is energized.

R313-15-905. Exemptions to Labeling Requirements.

A licensee or registrant is not required to label:

- (1) Containers holding licensed or registered material in quantities less than the quantities listed in Appendix C of 10 CFR 20.1001 to 20.2402, 2001 ed., which is incorporated by reference; or
- (2) Containers holding licensed or registered material in concentrations less than those specified in Table III of Appendix B of 10 CFR 20.1001 to 20.2402, 2001 ed., which is incorporated by reference; or
- (3) Containers attended by an individual who takes the precautions necessary to prevent the exposure of individuals in excess of the limits established by Rule R313-15; or
- (4) Containers when they are in transport and packaged and labeled in accordance with the rules of the U.S. Department of Transportation; or
- (5) Containers that are accessible only to individuals authorized to handle or use them, or to work in the vicinity of the containers, if the contents are identified to these individuals by a readily available written record. Examples of containers of this type are containers in locations such as water-filled canals, storage vaults, or hot cells. The record shall be retained as long as the containers are in use for the purpose indicated on the record; or
- (6) Installed manufacturing or process equipment, such as piping and tanks.

R313-15-906. Procedures for Receiving and Opening Packages.

(1) Each licensee or registrant who expects to receive a package containing quantities of radioactive material in excess of a Type A quantity, as used in Section R313-19-100, which incorporates 10 CFR 71.4 by reference, shall make arrangements to receive:

(a) The package when the carrier offers it for delivery; or

(b) The notification of the arrival of the package at the carrier's terminal and to take possession of the package expeditiously.

(2) Each licensee or registrant shall:

(a) Monitor the external surfaces of a labeled package for radioactive contamination unless the package contains only radioactive material in the form of gas or in special form as defined in Section R313-12-3; and

(b) Monitor the external surfaces of a labeled package for radiation levels unless the package contains quantities of radioactive material that are less than or equal to the Type A quantity, as used in Section R313-19-100, which incorporates 10 CFR 71.4 by reference; and

(c) Monitor all packages known to contain radioactive material for radioactive contamination and radiation levels if there is evidence of degradation of package integrity, such as packages that are crushed, wet, or damaged.

(3) The licensee or registrant shall perform the monitoring required by Subsection R313-15-906(2) as soon as practical after receipt of the package, but not later than three hours after the package is received at the licensee's or registrant's facility if it is received during the licensee's or registrant's normal working hours or if there is evidence of degradation of package integrity, such as a package that is crushed, wet, or damaged. If a package is received after working hours, and has no evidence of degradation of package integrity, the package shall be monitored no later than three hours from the beginning of the next working day.

(4) The licensee or registrant shall immediately notify the final delivery carrier and, by telephone and telegram, mailgram, or facsimile, the Executive Secretary when:

(a) Removable radioactive surface contamination exceeds the limits of Section R313-19-100 which incorporates 10 CFR 71.87(i) by reference; or

(b) External radiation levels exceed the limits of Section R313-19-100 which incorporates 10 CFR 71.47 by reference.

(5) Each licensee or registrant shall:

(a) Establish, maintain, and retain written procedures for safely opening packages in which radioactive material is received; and

(b) Ensure that the procedures are followed and that due consideration is given to special instructions for the type of package being opened.

(6) Licensees or registrants transferring special form sources in vehicles owned or operated by the licensee or registrant to and from a work site are exempt from the contamination monitoring requirements of Subsection R313- 15-906(2), but are not exempt from the monitoring requirement in Subsection R313-15-906(2) for measuring radiation levels that ensures that the source is still properly lodged in its shield.

R313-15-1001. Waste Disposal - General Requirements.

(1) A licensee or registrant shall dispose of licensed or registered material only:

(a) By transfer to an authorized recipient as provided in Section R313-15-1006 or in Rules R313-21, R313-22, R313-24, or R313-25, or to the U.S. Department of Energy; or

(b) By decay in storage; or

(c) By release in effluents within the limits in Section R313-15-301; or

(d) As authorized pursuant to Sections R313-15-1002, R313-15-1003, R313-15-1004, or R313-15-1005.

(2) A person shall be specifically licensed or registered to receive waste containing licensed or registered material from other persons for:

(a) Treatment prior to disposal; or

(b) Treatment or disposal by incineration; or

(c) Decay in storage; or

(d) Disposal at a land disposal facility licensed pursuant to Rule R313-25; or

(e) Storage until transferred to a storage or disposal facility authorized to receive the waste.

R313-15-1002. Method for Obtaining Approval of Proposed Disposal Procedures.

A licensee or registrant or applicant for a license or registration may apply to the Executive Secretary for approval of proposed procedures, not otherwise authorized in these rules, to dispose of licensed or registered material generated in the licensee's or registrant's operations. Each application shall include:

(1) A description of the waste containing licensed or registered material to be disposed of, including the physical and chemical properties that have an impact on risk evaluation, and the proposed manner and conditions of waste disposal; and

(2) An analysis and evaluation of pertinent information on the nature of the environment; and

(3) The nature and location of other potentially affected facilities; and

(4) Analyses and procedures to ensure that doses are maintained ALARA and within the dose limits in Rule R313-15.

R313-15-1003. Disposal by Release into Sanitary Sewerage.

(1) A licensee or registrant may discharge licensed or registered material into sanitary sewerage if each of the following conditions is satisfied:

(a) The material is readily soluble, or is readily dispersible biological material, in water; and

(b) The quantity of licensed or registered radioactive material that the licensee or registrant releases into the sewer in one month divided by the average monthly volume of water released into the sewer by the licensee or registrant does not exceed the concentration listed in Table III of Appendix B of 10 CFR 20.1001 to 20.2402, 2001 ed., which is incorporated by reference; and

(c) If more than one radionuclide is released, the following conditions shall also be satisfied:

(i) The licensee or registrant shall determine the fraction of the limit in Table III of Appendix B of 10 CFR 20.1001 to 20.2402, 2001 ed., which is incorporated by reference, represented by discharges into sanitary sewerage by dividing the actual monthly average concentration of each radionuclide released by the licensee or registrant into the sewer by the concentration of that radionuclide listed in Table III of Appendix B of 10 CFR 20.1001 to 20.2402, 2001 ed., which is incorporated by reference; and

(ii) The sum of the fractions for each radionuclide required by Subsection R313-15-1003(1)(c)(i) does not exceed unity; and

(d) The total quantity of licensed or registered radioactive material that the licensee or registrant releases into the sanitary sewerage system in a year does not exceed 185 GBq (five Ci) of hydrogen-3, 37 GBq (one Ci) of carbon-14, and 37 GBq (one Ci) of all other radioactive materials combined.

(2) Excreta from individuals undergoing medical diagnosis or therapy with radioactive material are not subject to the limitations contained in Subsection R313-15-1003(1).

R313-15-1004. Treatment or Disposal by Incineration.

A licensee or registrant may treat or dispose of licensed or registered material by incineration only in the form and concentration specified in Section R313-15-1005 or as specifically approved by the Executive Secretary pursuant to Section R313-15-1002.

R313-15-1005. Disposal of Specific Wastes.

(1) A licensee or registrant may dispose of the following licensed or registered material as if it were not radioactive:

(a) 1.85 kBq (0.05 uCi), or less, of hydrogen-3 or carbon-14 per gram of medium used for liquid scintillation counting; and

(b) 1.85 kBq (0.05 uCi) or less, of hydrogen-3 or carbon-14 per gram of animal tissue, averaged over the weight of the entire animal.

(2) A licensee or registrant shall not dispose of tissue pursuant to Subsection R313-15-1005(1)(b) in a manner that would permit its use either as food for humans or as animal feed.

(3) The licensee or registrant shall maintain records in accordance with Section R313-15-1109.

R313-15-1006. Transfer for Disposal and Manifests.

(1) The requirements of Section R313-15-1006 and Appendix G of 10 CFR 20.1001 to 20.2402, 2001 ed., which are incorporated into these rules by reference, are designed to:

(a) control transfers of low-level radioactive waste by any waste generator, waste collector, or waste processor licensee, as defined in Appendix G in 10 CFR 20.1001 to 20.2402, 2001 ed., who ships low-level waste either directly, or indirectly through a waste collector or waste processor, to a licensed low-level waste land disposal facility as defined in Section R313-25-2;

(b) establish a manifest tracking system; and

(c) supplement existing requirements concerning transfers and recordkeeping for those wastes.

(2) Any licensee shipping radioactive waste intended for ultimate disposal at a licensed land disposal facility must document the information required on the U.S. Nuclear Regulatory Commission's Uniform Low-Level Radioactive Waste Manifest and transfer this recorded manifest information to the intended consignee in accordance with Appendix G to 10 CFR 20.1001 to 20.2402, 2001 ed., which is incorporated into these rules by reference.

(3) Each shipment manifest shall include a certification by the waste generator as specified in Section II of Appendix G to 10 CFR 20.1001 to 20.2402, 2001 ed., which is incorporated by reference.

(4) Each person involved in the transfer of waste for disposal or in the disposal of waste, including the waste generator, waste collector, waste processor, and disposal facility operator, shall comply with the requirements specified in Section III of Appendix G to 10 CFR 20.1001 to 20.2402, 2001 ed., which is incorporated by reference.

R313-15-1007. Compliance with Environmental and Health Protection Rules.

Nothing in Sections R313-15-1001, R313-15-1002, R313-15-1003, R313-15-1004, R313-15-1005, or R313-15-1006 relieves the licensee or registrant from complying with other applicable Federal, State and local rules governing any other toxic or hazardous properties of materials that may be disposed of pursuant to Sections R313-15-1001, R313-15-1002, R313-15-1003, R313-15-1004, R313-15-1005, or R313-15-1006.

R313-15-1008. Classification and Characteristics of Low-Level Radioactive Waste.

(1) Classification of Radioactive Waste for Land Disposal

(a) Considerations. Determination of the classification of radioactive waste involves two considerations. First, consideration shall be given to the concentration of long-lived radionuclides (and their shorter-lived precursors) whose potential hazard will persist long after such precautions as institutional controls, improved waste form, and deeper disposal have ceased to be effective. These precautions delay the time when long-lived radionuclides could cause exposures. In addition, the magnitude of the potential dose is limited by the concentration and availability of the radionuclide at the time of exposure. Second, consideration shall be given to the concentration of shorter-lived radionuclides for which requirements on institutional controls, waste form, and disposal methods are effective.

(b) Classes of waste.

(i) Class A waste is waste that is usually segregated from other waste classes at the disposal site. The physical form and characteristics of Class A waste shall meet the minimum requirements set forth in Subsection R313-15-1008(2)(a). If Class A waste also meets the stability requirements set forth in Subsection R313-15-1008(2)(b), it is not necessary to segregate the waste for disposal.

(ii) Class B waste is waste that shall meet more rigorous requirements on waste form to ensure stability after disposal. The physical form and characteristics of Class B waste shall meet both the minimum and stability requirements set forth in Subsection R313-15-1008(2).

(iii) Class C waste is waste that not only shall meet more rigorous requirements on waste form to ensure stability but also requires additional measures at the disposal facility to protect against inadvertent intrusion. The physical form and characteristics of Class C waste shall meet both the minimum and stability requirements set forth in Subsection R313-15-1008(2).

(c) Classification determined by long-lived radionuclides. If the radioactive waste contains only radionuclides listed in Table I, classification shall be determined as follows:

(i) If the concentration does not exceed 0.1 times the value in Table I, the waste is Class A.

(ii) If the concentration exceeds 0.1 times the value in Table I, but does not exceed the value in Table I, the waste is Class C.

(iii) If the concentration exceeds the value in Table I, the waste is not generally acceptable for land disposal.

(iv) For wastes containing mixtures of radionuclides listed in Table I, the total concentration shall be determined by the sum of fractions rule described in Subsection R313-15-1008(1)(g).

TABLE I

Radionuclide	Concentration	
	curie/cubic meter(1)	nanocurie/gram(2)
C-14	8	
C-14 in activated metal	80	
Ni-59 in activated metal	220	
Nb-94 in activated metal	0.2	
Tc-99	3	
I-129	0.08	
Alpha emitting transuranic radionuclides with half-life greater than five years		100
Pu-241		3,500
Cm-242		20,000
Ra-226		100

NOTE: (1) To convert the Ci/m³ values to gigabecquerel (GBq)/cubic meter, multiply the Ci/m³ value by 37.

(2) To convert the nCi/g values to becquerel (Bq)/gram, multiply the nCi/g value by 37.

(d) Classification determined by short-lived radionuclides. If the waste does not contain any of the radionuclides listed in Table I, classification shall be determined based on the concentrations shown in Table II. However, as specified in Subsection R313-15-1008(1)(f), if radioactive waste does not contain any nuclides listed in either Table I or II, it is Class A.

(i) If the concentration does not exceed the value in Column 1, the waste is Class A.

(ii) If the concentration exceeds the value in Column 1 but does not exceed the value in Column 2, the waste is Class B.

(iii) If the concentration exceeds the value in Column 2 but does not exceed the value in Column 3, the waste is Class C.

(iv) If the concentration exceeds the value in Column 3, the waste is not generally acceptable for near-surface disposal.

(v) For wastes containing mixtures of the radionuclides listed in Table II, the total concentration shall be determined by the sum of fractions rule described in Subsection R313-15-1008(1)(g).

TABLE II

Radionuclide	Concentration, curie/cubic meter (1)		
	Column 1	Column 2	Column 3
Total of all radionuclides with less than 5-year half-life	700	(2)	(2)
H-3	40	(2)	(2)
Co-60	700	(2)	(2)
Ni-63	3.5	70	700
Ni-63 in activated metal	35	700	7000
Sr-90	0.04	150	7000
Cs-137	1	44	4600

NOTE: (1) To convert the Ci/m³ value to gigabecquerel (GBq)/cubic meter, multiply the Ci/m³ value by 37.

(2) There are no limits established for these radionuclides in Class B or C wastes. Practical considerations such as the effects of external radiation and internal heat generation on transportation, handling, and disposal will limit the concentrations for these wastes. These wastes shall be Class B unless the concentrations of other radionuclides in Table II determine the waste to be Class C independent of these radionuclides.

(e) Classification determined by both long- and short-lived radionuclides. If the radioactive waste contains a mixture of radionuclides, some of which are listed in Table I and some of which are listed in Table II, classification shall be determined as follows:

(i) If the concentration of a radionuclide listed in Table I is less than 0.1 times the value listed in Table I, the class shall be that determined by the concentration of radionuclides listed in Table II.

(ii) If the concentration of a radionuclide listed in Table I exceeds 0.1 times the value listed in Table I, but does not exceed the value in Table I, the waste shall be Class C, provided the concentration of radionuclides listed in Table II does not exceed the value shown in Column 3 of Table II.

(f) Classification of wastes with radionuclides other than those listed in Tables I and II. If the waste does not contain any radionuclides listed in either Table I or II, it is Class A.

(g) The sum of the fractions rule for mixtures of radionuclides. For determining classification for waste that contains a mixture of radionuclides, it is necessary to determine the sum of fractions by dividing each radionuclide's concentration by the appropriate limit and adding the resulting values. The appropriate limits shall all be taken from the same column of the same table. The sum of the fractions for the column shall be less than 1.0 if the waste class is to be determined by that column. Example: A waste contains Sr-90 in a concentration of 1.85 TBq/m³ (50 Ci/m³) and Cs-137 in a concentration of 814 GBq/m³ (22 Ci/m³). Since the concentrations both exceed the values in Column 1, Table II, they shall be compared to Column 2 values. For Sr-90 fraction, $50/150 = 0.33.$, for Cs-137 fraction, $22/44 = 0.5$; the sum of the fractions = 0.83. Since the sum is less than 1.0, the waste is Class B.

(h) Determination of concentrations in wastes. The concentration of a radionuclide may be determined by indirect methods such as use of scaling factors which relate the inferred concentration of one radionuclide to another that is measured, or radionuclide material accountability, if there is reasonable assurance that the indirect methods can be correlated with actual measurements. The concentration of a radionuclide may be averaged over the volume of the waste, or weight of the waste if the units are expressed as becquerel (nanocurie) per gram.

(2) Radioactive Waste Characteristics

(a) The following are minimum requirements for all classes of waste and are intended to facilitate handling and provide protection of health and safety of personnel at the disposal site.

(i) Wastes shall be packaged in conformance with the conditions of the license issued to the site operator to which the waste will be shipped. Where the conditions of the site license are more restrictive than the provisions of Rule R313-15, the site license conditions shall govern.

(ii) Wastes shall not be packaged for disposal in cardboard or fiberboard boxes.

(iii) Liquid waste shall be packaged in sufficient absorbent material to absorb twice the volume of the liquid.

(iv) Solid waste containing liquid shall contain as little free-standing and non-corrosive liquid as is reasonably achievable, but in no case shall the liquid exceed one percent of the volume.

(v) Waste shall not be readily capable of detonation or of explosive decomposition or reaction at normal pressures and temperatures, or of explosive reaction with water.

(vi) Waste shall not contain, or be capable of generating, quantities of toxic gases, vapors, or fumes harmful to persons transporting, handling, or disposing of the waste. This does not apply to radioactive gaseous waste packaged in accordance with Subsection R313-15-1008(2)(a)(viii).

(vii) Waste shall not be pyrophoric. Pyrophoric materials contained in wastes shall be treated, prepared, and packaged to be nonflammable.

(viii) Wastes in a gaseous form shall be packaged at an absolute pressure that does not exceed 1.5 atmospheres at 20 degrees celsius. Total activity shall not exceed 3.7 TBq (100 Ci) per container.

(ix) Wastes containing hazardous, biological, pathogenic, or Infectious material shall be treated to reduce to the maximum extent practical the potential hazard from the non-radiological materials.

(b) The following requirements are intended to provide stability of the waste. Stability is intended to ensure that the waste does not degrade and affect overall stability of the site through slumping, collapse, or other failure of the disposal unit and thereby lead to water infiltration. Stability is also a factor in limiting exposure to an inadvertent intruder, since it provides a recognizable and nondispersible waste.

(i) Waste shall have structural stability. A structurally stable waste form will generally maintain its physical dimensions and its form, under the expected disposal conditions such as weight of overburden and compaction equipment, the presence of moisture, and microbial activity, and internal factors such as radiation effects and chemical changes. Structural stability can be provided by the waste form itself, processing the waste to a stable form, or placing the waste in a disposal container or structure that provides stability after disposal.

(ii) Notwithstanding the provisions in Subsections R313-15-1008(2)(a)(iii) and R313-15-1008(2)(a)(iv), liquid wastes, or wastes containing liquid, shall be converted into a form that contains as little free-standing and non-corrosive liquid as is reasonably achievable, but in no case shall the liquid exceed one percent of the volume of the waste when the waste is in a disposal container designed to ensure stability, or 0.5 percent of the volume of the waste for waste processed to a stable form.

(iii) Void spaces within the waste and between the waste and its package shall be reduced to the extent practical.

(3) Labeling. Each package of waste shall be clearly labeled to identify whether it is Class A, Class B, or Class C waste, in accordance with Subsection R313-15-1008(1).

R313-15-1101. Records - General Provisions.

(1) Each licensee or registrant shall use the SI units becquerel, gray, sievert and coulomb per kilogram, or the special units, curie, rad, rem, and roentgen, including multiples and subdivisions, and shall clearly indicate the units of all quantities on records required by Rule R313-15.

(2) Notwithstanding the requirements of Subsection R313-15-1101(1), when recording information on shipment manifests, as required in Subsection R313-15-1006(2), information must be recorded in SI units or in SI units and the special units specified in Subsection R313-15-1101(1).

(3) The licensee or registrant shall make a clear distinction among the quantities entered on the records required by Rule R313-15, such as, total effective dose equivalent, total organ dose equivalent, shallow dose equivalent, lens dose equivalent, deep dose equivalent, or committed effective dose equivalent.

R313-15-1102. Records of Radiation Protection Programs.

(1) Each licensee or registrant shall maintain records of the radiation protection program, including:

(a) The provisions of the program; and

(b) Audits and other reviews of program content and implementation.

(2) The licensee or registrant shall retain the records required by Subsection R313-15-1102(1)(a) until the Executive Secretary terminates each pertinent license or registration requiring the record. The licensee or registrant shall retain the records required by Subsection R313-15-1102(1)(b) for three years after the record is made.

R313-15-1103. Records of Surveys.

(1) Each licensee or registrant shall maintain records showing the results of surveys and calibrations required by Section R313-15-501 and Subsection R313-15-906(2). The licensee or registrant shall retain these records for three years after the record is made.

(2) The licensee or registrant shall retain each of the following records until the Executive Secretary terminates each pertinent license or registration requiring the record:

(a) Records of the results of surveys to determine the dose from external sources of radiation used, in the absence of or in combination with individual monitoring data, in the assessment of individual dose equivalents; and

(b) Records of the results of measurements and calculations used to determine individual intakes of radioactive material and used in the assessment of internal dose; and

(c) Records showing the results of air sampling, surveys, and bioassays required pursuant to Subsections R313-15-703(3)(a) and R313-15-703(3)(b); and

(d) Records of the results of measurements and calculations used to evaluate the release of radioactive effluents to the environment.

R313-15-1104. Records of Tests for Leakage or Contamination of Sealed Sources.

Records of tests for leakage or contamination of sealed sources required by Section R313-15-1401 shall be kept in units of becquerel or microcurie and maintained for inspection by the Executive Secretary for five years after the records are made.

R313-15-1105. Records of Prior Occupational Dose.

For each individual who is likely to receive in a year an occupational dose requiring monitoring pursuant to Section R313-15-502, the licensee or registrant shall retain the records of prior occupational dose and exposure history as specified in Section R313-15-205 on form DRC-05 or equivalent until the Executive Secretary terminates each pertinent license requiring this record. The licensee or registrant shall retain records used in preparing form DRC-05 or equivalent for three years after the record is made.

R313-15-1106. Records of Planned Special Exposures.

(1) For each use of the provisions of Section R313-15-206 for planned special exposures, the licensee or registrant shall maintain records that describe:

(a) The exceptional circumstances requiring the use of a planned special exposure; and

(b) The name of the management official who authorized the planned special exposure and a copy of the signed authorization; and

(c) What actions were necessary; and

(d) Why the actions were necessary; and

(e) What precautions were taken to assure that doses were maintained ALARA; and

(f) What individual and collective doses were expected to result; and

(g) The doses actually received in the planned special exposure.

(2) The licensee or registrant shall retain the records until the Executive Secretary terminates each pertinent license or registration requiring these records.

R313-15-1107. Records of Individual Monitoring Results.

(1) Recordkeeping Requirement. Each licensee or registrant shall maintain records of doses received by all individuals for whom monitoring was required pursuant to Section R313-15-502, and records of doses received during planned special exposures, accidents, and emergency conditions. Assessments of dose equivalent and records made using units in effect before January 1, 1994, need not be changed. These records shall include, when applicable:

(a) The deep dose equivalent to the whole body, lens dose equivalent, shallow dose equivalent to the skin, and shallow dose equivalent to the extremities; and

- (b) The estimated intake of radionuclides, see Section R313-15-202; and
 - (c) The committed effective dose equivalent assigned to the intake of radionuclides; and
 - (d) The specific information used to calculate the committed effective dose equivalent pursuant to Subsections R313-15-204(1) and R313-15-204(3) and when required by Section R313-15-502; and
 - (e) The total effective dose equivalent when required by Section R313-15-202; and
 - (f) The total of the deep dose equivalent and the committed dose to the organ receiving the highest total dose.
- (2) Recordkeeping Frequency. The licensee or registrant shall make entries of the records specified in Subsection R313-15-1107(1) at intervals not to exceed one year.
- (3) Recordkeeping Format. The licensee or registrant shall maintain the records specified in Subsection R313-15-1107(1) on form DRC-06, in accordance with the instructions for form DRC-06, or in clear and legible records containing all the information required by form DRC-06.
- (4) The licensee or registrant shall maintain the records of dose to an embryo/fetus with the records of dose to the declared pregnant woman. The declaration of pregnancy, including the estimated date of conception, shall also be kept on file, but may be maintained separately from the dose records.
- (5) The licensee or registrant shall retain each required form or record until the Executive Secretary terminates each pertinent license or registration requiring the record.

R313-15-1108. Records of Dose to Individual Members of the Public.

- (1) Each licensee or registrant shall maintain records sufficient to demonstrate compliance with the dose limit for individual members of the public. See Section R313-15-301.
- (2) The licensee or registrant shall retain the records required by Subsection R313-15-1108(1) until the Executive Secretary terminates each pertinent license or registration requiring the record. Requirements for disposition of these records, prior to license termination, are located in Section R313-12-51 for activities licensed under these rules.

R313-15-1109. Records of Waste Disposal.

- (1) Each licensee or registrant shall maintain records of the disposal of licensed or registered materials made pursuant to Sections R313-15-1002, R313-15-1003, R313-15-1004, R313-15-1005, Rule R313-25, and disposal by burial in soil, including burials authorized before January 28, 1981.

(2) The licensee or registrant shall retain the records required by Subsection R313-15-1109(1) until the Executive Secretary terminates each pertinent license or registration requiring the record.

R313-15-1110. Records of Testing Entry Control Devices for Very High Radiation Areas.

(1) Each licensee or registrant shall maintain records of tests made pursuant to Subsection R313-15- 603(2)(i) on entry control devices for very high radiation areas. These records shall include the date, time, and results of each such test of function.

(2) The licensee or registrant shall retain the records required by Subsection R313-15-1110(1) for three years after the record is made.

R313-15-1111. Form of Records.

Each record required by Rule R313-15 shall be legible throughout the specified retention period. The record shall be the original or a reproduced copy or a microform, provided that the copy or microform is authenticated by authorized personnel and that the microform is capable of producing a clear copy throughout the required retention period or the record may also be stored in electronic media with the capability for producing legible, accurate, and complete records during the required retention period. Records, such as letters, drawings, and specifications, shall include all pertinent information, such as stamps, initials, and signatures. The licensee shall maintain adequate safeguards against tampering with and loss of records.

R313-15-1201. Reports of Stolen, Lost, or Missing Licensed or Registered Sources of Radiation.

(1) Telephone Reports. Each licensee or registrant shall report to the Executive Secretary by telephone as follows:

(a) Immediately after its occurrence becomes known to the licensee or registrant, stolen, lost, or missing licensed or registered radioactive material in an aggregate quantity equal to or greater than 1,000 times the quantity specified in Appendix C of 10 CFR 20.1001 to 20.2402, 2001 ed., which is incorporated by reference, under such circumstances that it appears to the licensee or registrant that an exposure could result to individuals in unrestricted areas;

(b) Within 30 days after its occurrence becomes known to the licensee or registrant, lost, stolen, or missing licensed or registered radioactive material in an aggregate quantity greater than ten times the quantity specified in Appendix C of 10 CFR 20.1001 to 20.2402, 2001 ed., which is incorporated by reference, that is still missing.

(c) Immediately after its occurrence becomes known to the registrant, a stolen, lost, or missing radiation machine.

(2) Written Reports. Each licensee or registrant required to make a report pursuant to Subsection R313-15-1201(1) shall, within 30 days after making the telephone report, make a written report to the Executive Secretary setting forth the following information:

(a) A description of the licensed or registered source of radiation involved, including, for radioactive material, the kind, quantity, and chemical and physical form; and, for radiation machines, the manufacturer, model and serial number, type and maximum energy of radiation emitted;

(b) A description of the circumstances under which the loss or theft occurred; and

(c) A statement of disposition, or probable disposition, of the licensed or registered source of radiation involved; and

(d) Exposures of individuals to radiation, circumstances under which the exposures occurred, and the possible total effective dose equivalent to persons in unrestricted areas; and

(e) Actions that have been taken, or will be taken, to recover the source of radiation; and

(f) Procedures or measures that have been, or will be, adopted to ensure against a recurrence of the loss or theft of licensed or registered sources of radiation.

(3) Subsequent to filing the written report, the licensee or registrant shall also report additional substantive information on the loss or theft within 30 days after the licensee or registrant learns of such information.

(4) The licensee or registrant shall prepare any report filed with the Executive Secretary pursuant to Section R313-15-1201 so that names of individuals who may have received exposure to radiation are stated in a separate and detachable portion of the report.

R313-15-1202. Notification of Incidents.

(1) Immediate Notification. Notwithstanding other requirements for notification, each licensee or registrant shall immediately report each event involving a source of radiation possessed by the licensee or registrant that may have caused or threatens to cause any of the following conditions:

(a) An individual to receive:

(i) A total effective dose equivalent of 0.25 Sv (25 rem) or more; or

(ii) A lens dose equivalent of 0.75 Sv (75 rem) or more; or

(iii) A shallow dose equivalent to the skin or extremities or a total organ dose equivalent of 2.5 Gy (250 rad) or more; or

(b) The release of radioactive material, inside or outside of a restricted area, so that, had an individual been present for 24 hours, the individual could have received an intake five times the occupational ALI. This provision does not apply to locations where personnel are not normally stationed during routine operations, such as hot- cells or process enclosures.

(2) Twenty-Four Hour Notification. Each licensee or registrant shall, within 24 hours of discovery of the event, report to the Executive Secretary each event involving loss of control of a licensed or registered source of radiation possessed by the licensee or registrant that may have caused, or threatens to cause, any of the following conditions:

(a) An individual to receive, in a period of 24 hours:

(i) A total effective dose equivalent exceeding 0.05 Sv (five rem); or

(ii) A lens dose equivalent exceeding 0.15 Sv (15 rem); or

(iii) A shallow dose equivalent to the skin or extremities or a total organ dose equivalent exceeding 0.5 Sv (50 rem); or

(b) The release of radioactive material, inside or outside of a restricted area, so that, had an individual been present for 24 hours, the individual could have received an intake in excess of one occupational ALI. This provision does not apply to locations where personnel are not normally stationed during routine operations, such as hot- cells or process enclosures.

(3) The licensee or registrant shall prepare each report filed with the Executive Secretary pursuant to Section R313-15-1202 so that names of individuals who have received exposure to sources of radiation are stated in a separate and detachable portion of the report.

(4) Licensees or registrants shall make the reports required by Subsections R313-15-1202(1) and R313-15-1202(2) to the Executive Secretary by telephone, telegram, mailgram, or facsimile.

(5) The provisions of Section R313-15-1202 do not apply to doses that result from planned special exposures, provided such doses are within the limits for planned special exposures and are reported pursuant to Section R313-15-1204.

R313-15-1203. Reports of Exposures, Radiation Levels, and Concentrations of Radioactive Material Exceeding the Constraints or Limits.

(1) Reportable Events. In addition to the notification required by Section R313-15-1202, each licensee or registrant shall submit a written report within 30 days after learning of any of the following occurrences:

(a) Incidents for which notification is required by Section R313-15-1202; or

(b) Doses in excess of any of the following:

- (i) The occupational dose limits for adults in Section R313-15-201; or
 - (ii) The occupational dose limits for a minor in Section R313-15-207; or
 - (iii) The limits for an embryo/fetus of a declared pregnant woman in Section R313-15-208; or
 - (iv) The limits for an individual member of the public in Section R313-15-301; or
 - (v) Any applicable limit in the license or registration; or
 - (vi) The ALARA constraints for air emissions established under Subsection R313-15-101(4); or
- (c) Levels of radiation or concentrations of radioactive material in:
- (i) A restricted area in excess of applicable limits in the license or registration; or
 - (ii) An unrestricted area in excess of ten times the applicable limit set forth in Rule R313-15 or in the license or registration, whether or not involving exposure of any individual in excess of the limits in Section R313-15-301; or
- (d) For licensees subject to the provisions of U.S. Environmental Protection Agency's generally applicable environmental radiation standards in 40 CFR 190, levels of radiation or releases of radioactive material in excess of those standards, or of license conditions related to those standards.

(2) Contents of Reports.

- (a) Each report required by Subsection R313-15-1203(1) shall describe the extent of exposure of individuals to radiation and radioactive material, including, as appropriate:
- (i) Estimates of each individual's dose; and
 - (ii) The levels of radiation and concentrations of radioactive material involved; and
 - (iii) The cause of the elevated exposures, dose rates, or concentrations; and
 - (iv) Corrective steps taken or planned to ensure against a recurrence, including the schedule for achieving conformance with applicable limits, ALARA constraints, generally applicable environmental standards, and associated license or registration conditions.
- (b) Each report filed pursuant to Subsection R313-15-1203(1) shall include for each occupationally overexposed individual: the name, Social Security account number, and date of birth. With respect to the limit for the embryo/fetus in Section R313-15-208, the identifiers should be those of the declared pregnant woman. The report shall be prepared so that this information is stated in a separate and detachable portion of the report.

(3) All licensees or registrants who make reports pursuant to Subsection R313-15-1203(1) shall submit the report in writing to the Executive Secretary.

R313-15-1204. Reports of Planned Special Exposures.

The licensee or registrant shall submit a written report to the Executive Secretary within 30 days following any planned special exposure conducted in accordance with Section R313-15-206, informing the Executive Secretary that a planned special exposure was conducted and indicating the date the planned special exposure occurred and the information required by Section R313-15-1106.

R313-15-1205. Reports to Individuals of Exceeding Dose Limits.

When a licensee or registrant is required, pursuant to the provisions of Sections R313-15-1203 or R313-15-1204, to report to the Executive Secretary any exposure of an identified occupationally exposed individual, or an identified member of the public, to sources of radiation, the licensee or registrant shall also provide a copy of the report submitted to the Executive Secretary to the individual. This report shall be transmitted at a time no later than the transmittal to the Executive Secretary.

R313-15-1207. Notifications and Reports to Individuals.

(1) Requirements for notification and reports to individuals of exposure to radiation or radioactive material are specified in Rule R313-18.

(2) When a licensee or registrant is required pursuant to Section R313-15-1203 to report to the Executive Secretary any exposure of an individual to radiation or radioactive material, the licensee or registrant shall also notify the individual. Such notice shall be transmitted at a time not later than the transmittal to the Executive Secretary, and shall comply with the provisions of Rule R313-18.

R313-15-1208. Reports of Leaking or Contaminated Sealed Sources.

If the test for leakage or contamination required pursuant to Section R313-15-1401 indicates a sealed source is leaking or contaminated, a report of the test shall be filed within five days with the Executive Secretary describing the equipment involved, the test results and the corrective action taken.

R313-15-1301. Vacating Premises.

Each specific licensee or registrant shall, no less than 30 days before vacating or relinquishing possession or control of premises which may have been contaminated with radioactive material as a result of his activities, notify the Executive Secretary in writing of intent to vacate. When deemed necessary by the Executive Secretary, the licensee shall decontaminate the premises in such a manner that the annual total effective dose equivalent to any individual after the site is released for unrestricted use should not exceed 0.1 mSv (0.01 rem) above background and that the annual total effective dose equivalent from any specific environmental source

during decommissioning activities should not exceed 0.1 mSv (0.01 rem) above background.

R313-15-1401. Testing for Leakage or Contamination of Sealed Sources.

(1) The licensee or registrant in possession of any sealed source shall assure that:

(a) Each sealed source, except as specified in Subsection R313-15-1401(2), is tested for leakage or contamination and the test results are received before the sealed source is put into use unless the licensee or registrant has a certificate from the transferor indicating that the sealed source was tested within six months before transfer to the licensee or registrant.

(b) Each sealed source that is not designed to emit alpha particles is tested for leakage or contamination at intervals not to exceed six months or at alternative intervals approved by the Executive Secretary, an Agreement State, a Licensing State, or the U.S. Nuclear Regulatory Commission.

(c) Each sealed source that is designed to emit alpha particles is tested for leakage or contamination at intervals not to exceed three months or at alternative intervals approved by the Executive Secretary, an Agreement State, a Licensing State, or the Nuclear Regulatory Commission.

(d) For each sealed source that is required to be tested for leakage or contamination, at any other time there is reason to suspect that the sealed source might have been damaged or might be leaking, the licensee or registrant shall assure that the sealed source is tested for leakage or contamination before further use.

(e) Tests for leakage for all sealed sources, except brachytherapy sources manufactured to contain radium, shall be capable of detecting the presence of 185 Bq (0.005 uCi) of radioactive material on a test sample. Test samples shall be taken from the sealed source or from the surfaces of the container in which the sealed source is stored or mounted on which one might expect contamination to accumulate. For a sealed source contained in a device, test samples are obtained when the source is in the "off" position.

(f) The test for leakage for brachytherapy sources manufactured to contain radium shall be capable of detecting an absolute leakage rate of 37 Bq (0.001 uCi) of radon-222 in a 24 hour period when the collection efficiency for radon-222 and its daughters has been determined with respect to collection method, volume and time.

(g) Tests for contamination from radium daughters shall be taken on the interior surface of brachytherapy source storage containers and shall be capable of detecting the presence of 185 Bq (0.005 uCi) of a radium daughter which has a half-life greater than four days.

(2) A licensee or registrant need not perform tests for leakage or contamination on the following sealed sources:

(a) Sealed sources containing only radioactive material with a half-life of less than 30 days;

(b) Sealed sources containing only radioactive material as a gas;

(c) Sealed sources containing 3.7 MBq (100 uCi) or less of beta or photon-emitting material or 370 kBq (ten uCi) or less of alpha-emitting material;

(d) Sealed sources containing only hydrogen-3;

(e) Seeds of iridium-192 encased in nylon ribbon; and

(f) Sealed sources, except teletherapy and brachytherapy sources, which are stored, not being used and identified as in storage. The licensee or registrant shall, however, test each such sealed source for leakage or contamination and receive the test results before any use or transfer unless it has been tested for leakage or contamination within six months before the date of use or transfer.

(3) Tests for leakage or contamination from sealed sources shall be performed by persons specifically authorized by the Executive Secretary, an Agreement State, a Licensing State, or the U.S. Nuclear Regulatory Commission to perform such services.

(4) Test results shall be kept in units of becquerel or microcurie and maintained for inspection by representatives of the Executive Secretary. Records of test results for sealed sources shall be made pursuant to Section R313-15-1104.

(5) The following shall be considered evidence that a sealed source is leaking:

(a) The presence of 185 Bq (0.005 uCi) or more of removable contamination on any test sample.

(b) Leakage of 37 Bq (0.001 uCi) of radon-222 per 24 hours for brachytherapy sources manufactured to contain radium.

(c) The presence of removable contamination resulting from the decay of 185 Bq (0.005 uCi) or more of radium.

(6) The licensee or registrant shall immediately withdraw a leaking sealed source from use and shall take action to prevent the spread of contamination. The leaking sealed source shall be repaired or disposed of in accordance with Rule R313-15.

(7) Reports of test results for leaking or contaminated sealed sources shall be made pursuant to Section R313-15-1208.

KEY

radioactive material, contamination, waste disposal, safety

Date of Enactment or Last Substantive Amendment

May 13, 2005

Notice of Continuation

January 14, 2003

Authorizing, Implemented, or Interpreted Law

19-3-104; 19-3-108

Rule converted into HTML by the Division of Administrative Rules.

For questions regarding the *content* or *application* of rules under Title R313, please contact the promulgating agency (Environmental Quality, Radiation Control). A list of agencies with links to their homepages is available at <http://www.utah.gov/government/agencylist.html>.

For questions about the *rulemaking process*, please contact **the Division of Administrative Rules**. *Please Note:* The Division of Administrative Rules is ***not able*** to answer questions about the content or application of these rules.

The HTML version of this rule is a convenience copy. This information is made available on the Internet as a public service. **Please see this disclaimer about information available from www.rules.utah.gov**.

[Division of Administrative Rules Home] | **[UTAH ADMINISTRATIVE CODE List of Titles]**

State Links: **Utah.gov Home** | **Utah.gov Terms of Use** | **Utah.gov Privacy Policy** | **Utah.gov Accessibility Policy**.

State Links: Utah.gov | [State Online Services](#) | [Agency List](#) | Business.utah.gov | [Search](#).

Division of Administrative Rules.

A Service of the Department of Administrative Services.

[Division of Administrative Rules Home] | [UTAH ADMINISTRATIVE CODE List of Titles]

ATTENTION AGENCIES: Looking for a copy of a rule so you can prepare an amendment? E-mail the Division to obtain a correctly formatted copy. **DO NOT USE the HTML version for preparing an amendment.**

Rule R313-25. License Requirements for Land Disposal of Radioactive Waste - General Provisions.

As in effect on August 1, 2005

Table of Contents

- R313-25-1. Purpose and Scope.
- R313-25-2. Definitions.
- R313-25-3. Pre-licensing Plan Approval Criteria for Siting of Commercial Radioactive Waste Disposal Facilities.
- R313-25-4. License Required.
- R313-25-5. Content of Application.
- R313-25-6. General Information.
- R313-25-7. Specific Technical Information.
- R313-25-8. Technical Analyses.
- R313-25-9. Institutional Information.
- R313-25-10. Financial Information.
- R313-25-11. Requirements for Issuance of a License.
- R313-25-12. Conditions of Licenses.
- R313-25-13. Application for Renewal or Closure.
- R313-25-14. Contents of Application for Site Closure and Stabilization.
- R313-25-15. Post-Closure Observation and Maintenance.
- R313-25-16. Transfer of License.
- R313-25-17. Termination of License.
- R313-25-18. General Requirement.
- R313-25-19. Protection of the General Population from Releases of Radioactivity.
- R313-25-20. Protection of Individuals from Inadvertent Intrusion.
- R313-25-21. Protection of Individuals During Operations.
- R313-25-22. Stability of the Disposal Site After Closure.
- R313-25-23. Disposal Site Suitability Requirements for Land Disposal - Near-Surface Disposal.
- R313-25-24. Disposal Site Design for Near-Surface Land Disposal.
- R313-25-25. Near Surface Land Disposal Facility Operation and Disposal Site Closure.

- R313-25-26. Environmental Monitoring.
- R313-25-27. Alternative Requirements for Design and Operations.
- R313-25-28. Institutional Requirements.
- R313-25-30. Applicant Qualifications and Assurances.
- R313-25-31. Funding for Disposal Site Closure and Stabilization.
- R313-25-32. Financial Assurances for Institutional Controls.
- R313-25-33. Maintenance of Records, Reports, and Transfers.
- R313-25-34. Tests on Land Disposal Facilities.
- R313-25-35. Executive Secretary Inspections of Land Disposal Facilities.
- KEY
- Date of Enactment or Last Substantive Amendment
- Notice of Continuation
- Authorizing, Implemented, or Interpreted Law

R313-25-1. Purpose and Scope.

The rules in this chapter establish procedures, criteria, and terms and conditions upon which the Executive Secretary issues licenses for the land disposal of wastes received from other persons. The requirements of R313- 25 are in addition to, and not in substitution for, other applicable requirements of these rules.

R313-25-2. Definitions.

As used in R313-25, the following definitions apply:

"Active maintenance" means significant activity needed during the period of institutional control to maintain a reasonable assurance that the performance objectives in R313-25-19 and R313-25-20 are met. Active maintenance may include the pumping and treatment of water from a disposal unit, the replacement of a disposal unit cover, or other episodic or continuous measures. Active maintenance does not include custodial activities like repair of fencing, repair or replacement of monitoring equipment, revegetation, minor additions to soil cover, minor repair of disposal unit covers, and general disposal site upkeep.

"Buffer zone" means a portion of the disposal site that is controlled by the licensee and that lies under the disposal units and between the disposal units and the boundary of the site.

"Commencement of construction" means clearing of land, excavation, or other substantial action that could adversely affect the environment of a land disposal facility. The term does not mean disposal site exploration, necessary roads for disposal site exploration, borings to determine foundation conditions, or other preconstruction monitoring or testing to establish background information related to the suitability of the disposal site or the protection of environmental values.

"Custodial agency" means an agency of the government designated to act on behalf of the government owner of the disposal site.

"Disposal" means the isolation of wastes from the biosphere by placing them in a land disposal facility.

"Disposal site" means that portion of a land disposal facility which is used for disposal of waste. It consists of disposal units and a buffer zone.

"Disposal unit" means a discrete portion of the disposal site into which waste is placed for disposal. For near-surface disposal, the disposal unit may be a trench.

"Engineered barrier" means a man-made structure or device intended to improve the land disposal facility's performance under R313-25.

"Hydrogeologic unit" means a soil or rock unit or zone that has a distinct influence on the storage or movement of ground water.

"Inadvertent intruder" means a person who may enter the disposal site after closure and engage in activities unrelated to post closure management, such as agriculture, dwelling construction, or other pursuits which could, by disturbing the site, expose individuals to radiation.

"Intruder barrier" means a sufficient depth of cover over the waste that inhibits contact with waste and helps to ensure that radiation exposures to an inadvertent intruder will meet the performance objectives set forth in R313-25, or engineered structures that provide equivalent protection to the inadvertent intruder.

"Land disposal facility" means the land, buildings and structures, and equipment which are intended to be used for the disposal of radioactive waste.

"Monitoring" means observing and making measurements to provide data to evaluate the performance and characteristics of the disposal site.

"Near-surface disposal facility" means a land disposal facility in which waste is disposed of within approximately the upper 30 meters of the earth's surface.

"Site closure and stabilization" means those actions that are taken upon completion of operations that prepare the disposal site for custodial care, and that assure that the disposal site will remain stable and will not need ongoing active maintenance.

"Stability" means structural stability.

"Surveillance" means monitoring and observation of the disposal site to detect needs for maintenance or custodial care, to observe evidence of intrusion, and to ascertain compliance with other license and regulatory requirements.

"Treatment" means the stabilization or the reduction in volume of waste by a chemical or a physical process.

"Waste" means those low-level radioactive wastes as defined in Section 19-3-102 that are acceptable for disposal in a land disposal facility. For the purposes of this definition, low-level waste has the same meaning as it does in the Low-Level Radioactive Waste Policy Act, Pub.L. 96-573, 94 Stat. 3347; thus, the term denotes radioactive waste not classified as high-level radioactive waste, transuranic waste, spent nuclear fuel, waste does not mean byproduct material as defined in 42 U.S.C. 2011(e)(2) of the Atomic Energy Act, uranium or thorium tailings and waste.

R313-25-3. Pre-licensing Plan Approval Criteria for Siting of Commercial Radioactive Waste Disposal Facilities.

(1) Persons proposing to construct or operate commercial radioactive waste disposal facilities, including waste incinerators, shall obtain a plan approval from the Executive Secretary before applying for a license. Plans shall meet the siting criteria and plan approval requirements of Section R313-25-3.

(2) The siting criteria and plan approval requirements in R313-25-3 apply to prelicensing plan approval applications.

(3) Treatment and disposal facilities, including commercial radioactive waste incinerators, shall not be located:

(a) within or underlain by:

(i) national, state, and county parks, monuments, and recreation areas; designated wilderness and wilderness study areas; wild and scenic river areas;

(ii) ecologically and scientifically significant natural areas, including wildlife management areas and habitats for listed or proposed endangered species as designated by federal law;

(iii) 100 year floodplains;

(iv) areas 200 feet distant from Holocene faults;

(v) underground mines, salt domes and salt beds;

(vi) dam failure flood areas;

(vii) areas subject to landslide, mud flow, or other earth movement, unless adverse impacts can be mitigated;

(viii) farmlands classified or evaluated as "prime", "unique", or of "statewide importance" by the U.S. Department of Agricultural Soil Conservation Service under the Prime Farmland Protection Act;

(ix) areas five miles distant from existing permanent dwellings, residential areas, and other habitable structures, including schools, churches, and historic structures;

(x) areas five miles distant from surface waters including intermittent streams, perennial streams, rivers, lakes, reservoirs, and wetlands;

(xi) areas 1000 feet distant from archeological sites to which adverse impacts cannot reasonably be mitigated;

(xii) recharge zones of aquifers containing ground water which has a total dissolved solids content of less than 10,000 mg/l; or

(xiii) drinking water source protection areas designated by the Utah Drinking Water Board;

(b) in areas:

(i) above or underlain by aquifers containing ground water which has a total dissolved solids content of less than 500 mg/l and which aquifers do not exceed state ground water standards for pollutants;

(ii) above or underlain by aquifers containing ground water which has a total dissolved solids content between 3000 and 10,000 mg/l when the distance from the surface to the ground water is less than 100 ft.;

(iii) areas of extensive withdrawal of water, mineral or energy resources.

(iv) above or underlain by weak and unstable soils, including soils that lose their ability to support foundations as a result of hydrocompaction, expansion, or shrinkage;

(v) above or underlain by karst terrains.

(4) Commercial radioactive waste disposal facilities may not be located within a distance to existing drinking water wells and watersheds for public water supplies of five years ground water travel time plus 1000 feet.

(5) The plan approval siting application shall include hydraulic conductivity and other information necessary to estimate adequately the ground water travel distance.

(6) The plan approval siting application shall include the results of studies adequate to identify the presence of ground water aquifers in the area of the proposed site and to assess the quality of the ground water of all aquifers identified in the area of the proposed site.

(7) Emergency response and safety.

(a) The plan approval siting application shall demonstrate the availability and adequacy of services for on-site emergencies, including medical and fire response. The application shall provide written evidence that the applicant has coordinated on-site emergency response plans with the local emergency planning committee (LEPC).

(b) The plan approval siting application shall include a comprehensive plan for responding to emergencies at the site.

(c) The plan approval siting application shall show proposed routes for transportation of radioactive wastes within the state. The plan approval siting application shall address the transportation means and routes available to evacuate the population at risk in the event of on-site accidents, including spills and fires.

(8) The plan approval siting application shall provide evidence that if the proposed disposal site is on land not owned by state or federal government, that arrangements have been made for assumption of ownership in fee by a state or federal agency.

(9) Siting Authority. The Executive Secretary recognizes that Titles 10 and 17 of the Utah Code give cities and counties authority for local use planning and zoning. Nothing in R313-25-3 precludes cities and counties from establishing additional requirements as provided by applicable state and federal law.

R313-25-4. License Required.

(1) Persons shall not receive, possess, or dispose of waste at a land disposal facility unless authorized by a license issued by the Executive Secretary pursuant to R313-25 and R313-22.

(2) Persons shall file an application with the Executive Secretary pursuant to R313-22-32 and obtain a license as provided in R313-25 before commencement of construction of a land disposal facility. Failure to comply with this requirement may be grounds for denial of a license and other penalties established by law and rules.

R313-25-5. Content of Application.

In addition to the requirements set forth in R313-22-33, an application to receive from others, possess, and dispose of wastes shall consist of general information, specific technical information, institutional information, and financial information as set forth in R313-25-6 through R313-25-10.

R313-25-6. General Information.

The general information shall include the following:

(1) identity of the applicant including:

(a) the full name, address, telephone number, and description of the business or occupation of the applicant;

(b) if the applicant is a partnership, the names and addresses of the partners and the principal location where the partnership does business;

(c) if the applicant is a corporation or an unincorporated association;

(i) the state where it is incorporated or organized and the principal location where it does business; and

(ii) the names and addresses of its directors and principal officers; and

(d) If the applicant is acting as an agent or representative of another person in filing the application, the applicant shall provide, with respect to the other person, information required under R313-25-6(1).

(2) Qualifications of the applicant shall include the following;

(a) the organizational structure of the applicant, both offsite and onsite, including a description of lines of authority and assignments of responsibilities, whether in the form of administrative directives, contract provisions, or otherwise;

(b) the technical qualifications, including training and experience of the applicant and members of the applicant's staff, to engage in the proposed activities. Minimum training and experience requirements for personnel filling key positions described in R313-25-6(2)(a) shall be provided;

(c) a description of the applicant's personnel training program; and

(d) the plan to maintain an adequate complement of trained personnel to carry out waste receipt, handling, and disposal operations in a safe manner.

(3) A description of:

(a) the location of the proposed disposal site;

(b) the general character of the proposed activities;

(c) the types and quantities of waste to be received, possessed, and disposed of;

(d) plans for use of the land disposal facility for purposes other than disposal of wastes; and

(e) the proposed facilities and equipment; and

(4) proposed schedules for construction, receipt of waste, and first emplacement of waste at the proposed land disposal facility.

R313-25-7. Specific Technical Information.

The application shall include certain technical information. The following information is needed to determine whether or not the applicant can meet the performance objectives and the applicable technical requirements of R313-25:

(1) A description of the natural and demographic disposal site characteristics shall be based on and determined by disposal site selection and characterization activities. The description shall include geologic, geochemical, geotechnical, hydrologic, ecologic, archaeologic, meteorologic, climatologic, and biotic features of the disposal site and vicinity.

(2) Descriptions of the design features of the land disposal facility and of the disposal units for near-surface disposal shall include those design features related

to infiltration of water; integrity of covers for disposal units; structural stability of backfill, wastes, and covers; contact of wastes with standing water; disposal site drainage; disposal site closure and stabilization; elimination to the extent practicable of long-term disposal site maintenance; inadvertent intrusion; occupational exposures; disposal site monitoring; and adequacy of the size of the buffer zone for monitoring and potential mitigative measures.

(3) Descriptions of the principal design criteria and their relationship to the performance objectives.

(4) Descriptions of the natural events or phenomena on which the design is based and their relationship to the principal design criteria.

(5) Descriptions of codes and standards which the applicant has applied to the design, and will apply to construction of the land disposal facilities.

(6) Descriptions of the construction and operation of the land disposal facility. The description shall include as a minimum the methods of construction of disposal units; waste emplacement; the procedures for and areas of waste segregation; types of intruder barriers; onsite traffic and drainage systems; survey control program; methods and areas of waste storage; and methods to control surface water and ground water access to the wastes. The description shall also include a description of the methods to be employed in the handling and disposal of wastes containing chelating agents or other non-radiological substances which might affect meeting the performance objectives of R313-25

(7) A description of the disposal site closure plan, including those design features which are intended to facilitate disposal site closures and to eliminate the need for active maintenance after closure.

(8) Identification of the known natural resources at the disposal site whose exploitation could result in inadvertent intrusion into the wastes after removal of active institutional control.

(9) Descriptions of the kind, amount, classification and specifications of the radioactive material proposed to be received, possessed, and disposed of at the land disposal facility.

(10) Descriptions of quality assurance programs, tailored to low-level waste disposal, including audit and managerial controls, for the determination of natural disposal site characteristics and for quality control during the design, construction, operation, and closure of the land disposal facility and the receipt, handling, and emplacement of waste.

(11) A description of the radiation safety program for control and monitoring of radioactive effluents to ensure compliance with the performance objective in R313-25-19 and monitoring of occupational radiation exposure to ensure compliance with the requirements of R313-15 and to control contamination of personnel, vehicles, equipment, buildings, and the disposal site. The applicant shall describe procedures, instrumentation, facilities, and equipment appropriate to both routine and emergency operations.

(12) A description of the environmental monitoring program to provide data and to evaluate potential health and environmental impacts and the plan for taking corrective measures if migration is indicated.

(13) Descriptions of the administrative procedures that the applicant will apply to control activities at the land disposal facility.

(14) A description of the facility electronic recordkeeping system as required in R313-25-33.

R313-25-8. Technical Analyses.

The specific technical information shall also include the following analyses needed to demonstrate that the performance objectives of R313-25 will be met:

(1) Analyses demonstrating that the general population will be protected from releases of radioactivity shall consider the pathways of air, soil, ground water, surface water, plant uptake, and exhumation by burrowing animals. The analyses shall clearly identify and differentiate between the roles performed by the natural disposal site characteristics and design features in isolating and segregating the wastes. The analyses shall clearly demonstrate a reasonable assurance that the exposures to humans from the release of radioactivity will not exceed the limits set forth in R313-25-19.

(2) Analyses of the protection of inadvertent intruders shall demonstrate a reasonable assurance that the waste classification and segregation requirements will be met and that adequate barriers to inadvertent intrusion will be provided.

(3) Analysis of the protection of individuals during operations shall include assessments of expected exposures due to routine operations and likely accidents during handling, storage, and disposal of waste. The analysis shall provide reasonable assurance that exposures will be controlled to meet the requirements of R313-15.

(4) Analyses of the long-term stability of the disposal site shall be based upon analyses of active natural processes including erosion, mass wasting, slope failure, settlement of wastes and backfill, infiltration through covers over disposal areas and adjacent soils, and surface drainage of the disposal site. The analyses shall provide reasonable assurance that there will not be a need for ongoing active maintenance of the disposal site following closure.

R313-25-9. Institutional Information.

The institutional information submitted by the applicant shall include:

(1) A certification by the federal or state agency which owns the disposal site that the agency is prepared to accept transfer of the license when the provisions of R313-25-16 are met and will assume responsibility for institutional control after site closure and for post-closure observation and maintenance.

(2) Evidence, if the proposed disposal site is on land not owned by the federal or a state government, that arrangements have been made for assumption of ownership in fee by the federal or a state agency.

R313-25-10. Financial Information.

This information shall demonstrate that the applicant is financially qualified to carry out the activities for which the license is sought. The information shall meet other financial assurance requirements of R313- 25.

R313-25-11. Requirements for Issuance of a License.

A license for the receipt, possession, and disposal of waste containing radioactive material will be issued by the Executive Secretary upon finding that:

(1) the issuance of the license will not constitute an unreasonable risk to the health and safety of the public;

(2) the applicant is qualified by reason of training and experience to carry out the described disposal operations in a manner that protects health and minimizes danger to life or property;

(3) the applicant's proposed disposal site, disposal design, land disposal facility operations, including equipment, facilities, and procedures, disposal site closure, and post-closure institutional control, are adequate to protect the public health and safety as specified in the performance objectives of R313-25-19;

(4) the applicant's proposed disposal site, disposal site design, land disposal facility operations, including equipment, facilities, and procedures, disposal site closure, and post-closure institutional control are adequate to protect the public health and safety in accordance with the performance objectives of R313-25-20;

(5) the applicant's proposed land disposal facility operations, including equipment, facilities, and procedures, are adequate to protect the public health and safety in accordance with R313-15;

(6) the applicant's proposed disposal site, disposal site design, land disposal facility operations, disposal site closure, and post-closure institutional control plans are adequate to protect the public health and safety in that they will provide reasonable assurance of the long-term stability of the disposed waste and the disposal site and will eliminate to the extent practicable the need for continued maintenance of the disposal site following closure;

(7) the applicant's demonstration provides reasonable assurance that the requirements of R313-25 will be met;

(8) the applicant's proposal for institutional control provides reasonable assurance that control will be provided for the length of time found necessary to ensure the findings in R313-25-11(3) through (6) and that the institutional control meets the requirements of R313-25-28.

(9) the financial or surety arrangements meet the requirements of R313-25.

R313-25-12. Conditions of Licenses.

(1) A license issued under R313-25, or a right thereunder, may not be transferred, assigned, or disposed of, either voluntarily or involuntarily, directly or indirectly, through transfer of control of the license to a person, unless the Executive Secretary finds, after securing full information, that the transfer is in accordance with the provisions of the Radiation Control Act and Rules and gives his consent in writing in the form of a license amendment.

(2) The Executive Secretary may require the licensee to submit written statements under oath.

(3) The license will be terminated only on the full implementation of the final closure plan, including post-closure observation and maintenance, as approved by the Executive Secretary.

(4) The licensee shall submit to the provisions of the Act now or hereafter in effect, and to all findings and orders of the Executive Secretary. The terms and conditions of the license are subject to amendment, revision, or modification, by reason of amendments to, or by reason of rules, and orders issued in accordance with the terms of the Act and these rules.

(5) Persons licensed by the Executive Secretary pursuant to R313-25 shall confine possession and use of the materials to the locations and purposes authorized in the license.

(6) The licensee shall not dispose of waste until the Executive Secretary has inspected the land disposal facility and has found it to conform with the description, design, and construction described in the application for a license.

(7) The Executive Secretary may incorporate, by rule or order, into licenses at the time of issuance or thereafter, additional requirements and conditions with respect to the licensee's receipt, possession, and disposal of waste as the Executive Secretary deems appropriate or necessary in order to:

(a) protect health or to minimize danger to life or property;

(b) require reports and the keeping of records, and to provide for inspections of licensed activities as the Executive Secretary deems necessary or appropriate to effectuate the purposes of the Radiation Control Act and Rules.

(8) The authority to dispose of wastes expires on the expiration date stated in the license. An expiration date on a license applies only to the above ground activities and to the authority to dispose of waste. Failure to renew the license shall not relieve the licensee of responsibility for implementing site closure, post-closure observation, and transfer of the license to the site owner.

R313-25-13. Application for Renewal or Closure.

(1) An application for renewal or an application for closure under R313-25-14 shall be filed at least 90 days prior to license expiration.

(2) Applications for renewal of a license shall be filed in accordance with R313-25-5 through 25-10. Applications for closure shall be filed in accordance with R313-25-14. Information contained in previous applications, statements, or reports filed with the Executive Secretary under the license may be incorporated by reference if the references are clear and specific.

(3) If a licensee has filed an application in proper form for renewal of a license, the license shall not expire unless and until the Executive Secretary has taken final action to deny application for renewal.

(4) In evaluating an application for license renewal, the Executive Secretary will apply the criteria set forth in R313-25-11.

R313-25-14. Contents of Application for Site Closure and Stabilization.

(1) Prior to final closure of the disposal site, or as otherwise directed by the Executive Secretary, the licensee shall submit an application to amend the license for closure. This closure application shall include a final revision and specific details of the disposal site closure plan included in the original license application submitted and approved under R313-25-7(7). The plan shall include the following:

(a) additional geologic, hydrologic, or other data pertinent to the long-term containment of emplaced wastes obtained during the operational period;

(b) the results of tests, experiments, or other analyses relating to backfill of excavated areas, closure and sealing, waste migration and interaction with emplacement media, or other tests, experiments, or analyses pertinent to the long-term containment of emplaced waste within the disposal site;

(c) proposed revision of plans for:

(i) decontamination or dismantlement of surface facilities;

(ii) backfilling of excavated areas; or

(iii) stabilization of the disposal site for post-closure care.

(d) Significant new information regarding the environmental impact of closure activities and long-term performance of the disposal site.

(2) Upon review and consideration of an application to amend the license for closure submitted in accordance with R313-25-14(1), the Executive Secretary shall issue an amendment authorizing closure if there is reasonable assurance that the long-term performance objectives of R313-25 will be met.

R313-25-15. Post-Closure Observation and Maintenance.

The licensee shall observe, monitor, and carry out necessary maintenance and repairs at the disposal site until the site closure is complete and the license is transferred by the Executive Secretary in accordance with R313- 25-16. The licensee shall remain responsible for the disposal site for an additional five years. The Executive Secretary may approve closure plans that provide for shorter or longer time periods of post-closure observation and maintenance, if sufficient rationale is developed for the variance.

R313-25-16. Transfer of License.

Following closure and the period of post-closure observation and maintenance, the licensee may apply for an amendment to transfer the license to the disposal site owner. The license shall be transferred when the Executive Secretary finds:

- (1) that the disposal site was closed according to the licensee's approved disposal site closure plan;
- (2) that the licensee has provided reasonable assurance that the performance objectives of R313-25 have been met;
- (3) that funds for care and records required by R313-25-33(4) and (5) have been transferred to the disposal site owner;
- (4) that the post-closure monitoring program is operational and can be implemented by the disposal site owner; and
- (5) that the Federal or State agency which will assume responsibility for institutional control of the disposal site is prepared to assume responsibility and ensure that the institutional requirements found necessary under R313-25-11(8) will be met.

R313-25-17. Termination of License.

- (1) Following the period of institutional control needed to meet the requirements of R313-25-11, the licensee may apply for an amendment to terminate the license.
- (2) This application will be reviewed in accordance with the provisions of R313-22-32.
- (3) A license shall be terminated only when the Executive Secretary finds:
 - (a) that the institutional control requirements of R313-25-11(8) have been met;
 - (b) that additional requirements resulting from new information developed during the institutional control period have been met;
 - (c) that permanent monuments or markers warning against intrusion have been installed; and

(d) that records required by R313-25-33(4) and (5) have been sent to the party responsible for institutional control of the disposal site and a copy has been sent to the Executive Secretary immediately prior to license termination.

R313-25-18. General Requirement.

Land disposal facilities shall be sited, designed, operated, closed, and controlled after closure so that reasonable assurance exists that exposures to individuals do not exceed the limits stated in R313-25-19 and 25-22.

R313-25-19. Protection of the General Population from Releases of Radioactivity.

Concentrations of radioactive material which may be released to the general environment in ground water, surface water, air, soil, plants or animals shall not result in an annual dose exceeding an equivalent of 0.25 mSv (0.025 rem) to the whole body, 0.75 mSv (0.075 rem) to the thyroid, and 0.25 mSv (0.025 rem) to any other organ of any member of the public. No greater than 0.04 mSv (0.004 rem) committed effective dose equivalent or total effective dose equivalent to any member of the public shall come from groundwater. Reasonable efforts should be made to maintain releases of radioactivity in effluents to the general environment as low as is reasonably achievable.

R313-25-20. Protection of Individuals from Inadvertent Intrusion.

Design, operation, and closure of the land disposal facility shall ensure protection of any individuals inadvertently intruding into the disposal site and occupying the site or contacting the waste after active institutional controls over the disposal site are removed.

R313-25-21. Protection of Individuals During Operations.

Operations at the land disposal facility shall be conducted in compliance with the standards for radiation protection set out in R313-15 of these rules, except for release of radioactivity in effluents from the land disposal facility, which shall be governed by R313-25-19. Every reasonable effort should be made to maintain radiation exposures as low as is reasonably achievable, ALARA.

R313-25-22. Stability of the Disposal Site After Closure.

The disposal facility shall be sited, designed, used, operated, and closed to achieve long-term stability of the disposal site and to eliminate, to the extent practicable, the need for ongoing active maintenance of the disposal site following closure so that only surveillance, monitoring, or minor custodial care are required.

R313-25-23. Disposal Site Suitability Requirements for Land Disposal - Near-Surface Disposal.

(1) The primary emphasis in disposal site suitability is given to isolation of wastes and to disposal site features that ensure that the long-term performance objectives are met.

(2) The disposal site shall be capable of being characterized, modeled, analyzed and monitored.

(3) Within the region where the facility is to be located, a disposal site should be selected so that projected population growth and future developments are not likely to affect the ability of the disposal facility to meet the performance objectives of R313-25.

(4) Areas shall be avoided having known natural resources which, if exploited, would result in failure to meet the performance objectives of R313-25.

(5) The disposal site shall be generally well drained and free of areas of flooding or frequent ponding. Waste disposal shall not take place in a 100-year flood plain, coastal high-hazard area or wetland, as defined in Executive Order 11988, "Floodplain Management Guidelines."

(6) Upstream drainage areas shall be minimized to decrease the amount of runoff which could erode or inundate waste disposal units.

(7) The disposal site shall provide sufficient depth to the water table that ground water intrusion, perennial or otherwise, into the waste will not occur. The Executive Secretary will consider an exception to this requirement to allow disposal below the water table if it can be conclusively shown that disposal site characteristics will result in molecular diffusion being the predominant means of radionuclide movement and the rate of movement will result in the performance objectives being met. In no case will waste disposal be permitted in the zone of fluctuation of the water table.

(8) The hydrogeologic unit used for disposal shall not discharge ground water to the surface within the disposal site.

(9) Areas shall be avoided where tectonic processes such as faulting, folding, seismic activity, vulcanism, or similar phenomena may occur with such frequency and extent to significantly affect the ability of the disposal site to meet the performance objectives of R313-25 or may preclude defensible modeling and prediction of long-term impacts.

(10) Areas shall be avoided where surface geologic processes such as mass wasting, erosion, slumping, landsliding, or weathering occur with sufficient such frequency and extent to significantly affect the ability of the disposal site to meet the performance objectives of R313-25, or may preclude defensible modeling and prediction of long-term impacts.

(11) The disposal site shall not be located where nearby facilities or activities could adversely impact the ability of the site to meet the performance objectives of R313-25 or significantly mask the environmental monitoring program.

R313-25-24. Disposal Site Design for Near-Surface Land Disposal.

- (1) Site design features shall be directed toward long-term isolation and avoidance of the need for continuing active maintenance after site closure.
- (2) The disposal site design and operation shall be compatible with the disposal site closure and stabilization plan and lead to disposal site closure that provides reasonable assurance that the performance objectives will be met.
- (3) The disposal site shall be designed to complement and improve, where appropriate, the ability of the disposal site's natural characteristics to assure that the performance objectives will be met.
- (4) Covers shall be designed to minimize, to the extent practicable, water infiltration, to direct percolating or surface water away from the disposed waste, and to resist degradation by surface geologic processes and biotic activity.
- (5) Surface features shall direct surface water drainage away from disposal units at velocities and gradients which will not result in erosion that will require ongoing active maintenance in the future.
- (6) The disposal site shall be designed to minimize to the extent practicable the contact of water with waste during storage, the contact of standing water with waste during disposal, and the contact of percolating or standing water with wastes after disposal.

R313-25-25. Near Surface Land Disposal Facility Operation and Disposal Site Closure.

- (1) Wastes designated as Class A pursuant to R313-15-1008 of these rules shall be segregated from other wastes by placing them in disposal units which are sufficiently separated from disposal units for the other waste classes so that any interaction between Class A wastes and other wastes will not result in the failure to meet the performance objectives of R313-25. This segregation is not necessary for Class A wastes if they meet the stability requirements of R313-15-1008(2)(b).
- (2) Wastes designated as Class C pursuant to R313-15-1008 shall be disposed of so that the top of the waste is a minimum of five meters below the top surface of the cover or shall be disposed of with intruder barriers that are designed to protect against an inadvertent intrusion for at least 500 years.
- (3) Except as provided in R313-25-1(1), only waste classified as Class A, B, or C shall be acceptable for near-surface disposal. Wastes shall be disposed of in accordance with the requirements of R313-25-25(4) through 11.
- (4) Wastes shall be emplaced in a manner that maintains the package integrity during emplacement, minimizes the void spaces between packages, and permits the void spaces to be filled.
- (5) Void spaces between waste packages shall be filled with earth or other material to reduce future subsidence within the fill.

(6) Waste shall be placed and covered in a manner that limits the radiation dose rate at the surface of the cover to levels that at a minimum will permit the licensee to comply with all provisions of R313-15-105 at the time the license is transferred pursuant to R313-25-16.

(7) The boundaries and locations of disposal units shall be accurately located and mapped by means of a land survey. Near-surface disposal units shall be marked in such a way that the boundaries of the units can be easily defined. Three permanent survey marker control points, referenced to United States Geological Survey or National Geodetic Survey control stations, shall be established on the site to facilitate surveys. The United States Geological Survey or National Geodetic Survey control stations shall provide horizontal and vertical controls as checked against United States Geological Survey or National Geodetic Survey record files.

(8) A buffer zone of land shall be maintained between any buried waste and the disposal site boundary and beneath the disposed waste. The buffer zone shall be of adequate dimensions to carry out environmental monitoring activities specified in R313-25-26(4) and take mitigative measures if needed.

(9) Closure and stabilization measures as set forth in the approved site closure plan shall be carried out as the disposal units are filled and covered.

(10) Active waste disposal operations shall not have an adverse effect on completed closure and stabilization measures.

(11) Only wastes containing or contaminated with radioactive material shall be disposed of at the disposal site.

(12) Proposals for disposal of waste that are not generally acceptable for near-surface disposal because the wastes form and disposal methods shall be different and, in general, more stringent than those specified for Class C waste, may be submitted to the Executive Secretary for approval.

R313-25-26. Environmental Monitoring.

(1) At the time a license application is submitted, the applicant shall have conducted a preoperational monitoring program to provide basic environmental data on the disposal site characteristics. The applicant shall obtain information about the ecology, meteorology, climate, hydrology, geology, geochemistry, and seismology of the disposal site. For those characteristics that are subject to seasonal variation, data shall cover at least a 12-month period.

(2) During the land disposal facility site construction and operation, the licensee shall maintain an environmental monitoring program. Measurements and observations shall be made and recorded to provide data to evaluate the potential health and environmental impacts during both the construction and the operation of the facility and to enable the evaluation of long-term effects and need for mitigative measures. The monitoring system shall be capable of providing early warning of releases of waste from the disposal site before they leave the site boundary.

(3) After the disposal site is closed, the licensee responsible for post-operational surveillance of the disposal site shall maintain a monitoring system based on the operating history and the closure and stabilization of the disposal site. The monitoring system shall be capable of providing early warning of releases of waste from the disposal site before they leave the site boundary.

(4) The licensee shall have plans for taking corrective measures if the environmental monitoring program detects migration of waste which would indicate that the performance objectives may not be met.

R313-25-27. Alternative Requirements for Design and Operations.

The Executive Secretary may, upon request or on his own initiative, authorize provisions other than those set forth in R313-25-24 and 25-26 for the segregation and disposal of waste and for the design and operation of a land disposal facility on a specific basis, if it finds reasonable assurance of compliance with the performance objectives of R313-25.

R313-25-28. Institutional Requirements.

(1) Land Ownership. Disposal of waste received from other persons may be permitted only on land owned in fee by the Federal or a State government.

(2) Institutional Control. The land owner or custodial agency shall conduct an institutional control program to physically control access to the disposal site following transfer of control of the disposal site from the disposal site operator. The institutional control program shall also include, but not be limited to, conducting an environmental monitoring program at the disposal site, periodic surveillance, minor custodial care, and other equivalents as determined by the Executive Secretary, and administration of funds to cover the costs for these activities. The period of institutional controls will be determined by the Executive Secretary, but institutional controls may not be relied upon for more than 100 years following transfer of control of the disposal site to the owner.

R313-25-30. Applicant Qualifications and Assurances.

The applicant shall show that it either possesses the necessary funds, or has reasonable assurance of obtaining the necessary funds, or by a combination of the two, to cover the estimated costs of conducting all licensed activities over the planned operating life of the project, including costs of construction and disposal.

R313-25-31. Funding for Disposal Site Closure and Stabilization.

(1) The applicant shall provide assurances prior to the commencement of operations that sufficient funds will be available to carry out disposal site closure and stabilization, including:

(a) decontamination or dismantlement of land disposal facility structures, and

(b) closure and stabilization of the disposal site so that following transfer of the disposal site to the site owner, the need for ongoing active maintenance is eliminated to the extent practicable and only minor custodial care, surveillance, and monitoring are required. These assurances shall be based on Executive Secretary approved cost estimates reflecting the Executive Secretary approved plan for disposal site closure and stabilization. The applicant's cost estimates shall take into account total costs that would be incurred if an independent contractor were hired to perform the closure and stabilization work.

(2) In order to avoid unnecessary duplication and expense, the Executive Secretary will accept financial sureties that have been consolidated with earmarked financial or surety arrangements established to meet requirements of Federal or other State agencies or local governmental bodies for decontamination, closure, and stabilization. The Executive Secretary will accept these arrangements only if they are considered adequate to satisfy the requirements of R313-25-31 and if they clearly identify that the portion of the surety which covers the closure of the disposal site is clearly identified and committed for use in accomplishing these activities.

(3) The licensee's financial or surety arrangement shall be submitted annually for review by the Executive Secretary to assure that sufficient funds will be available for completion of the closure plan.

(4) The amount of the licensee's financial or surety arrangement shall change in accordance with changes in the predicted costs of closure and stabilization. Factors affecting closure and stabilization cost estimates include inflation, increases in the amount of disturbed land, changes in engineering plans, closure and stabilization that have already been accomplished, and other conditions affecting costs. The financial or surety arrangement shall be sufficient at all times to cover the costs of closure and stabilization of the disposal units that are expected to be used before the next license renewal.

(5) The financial or surety arrangement shall be written for a specified period of time and shall be automatically renewed unless the person who issues the surety notifies the Executive Secretary; the beneficiary, the site owner; and the principal, the licensee, not less than 90 days prior to the renewal date of its intention not to renew. In such a situation, the licensee shall submit a replacement surety within 30 days after notification of cancellation. If the licensee fails to provide a replacement surety acceptable to the Executive Secretary, the beneficiary may collect on the original surety.

(6) Proof of forfeiture shall not be necessary to collect the surety so that, in the event that the licensee could not provide an acceptable replacement surety within the required time, the surety shall be automatically collected prior to its expiration. The conditions described above shall be clearly stated on surety instruments.

(7) Financial or surety arrangements generally acceptable to the Executive Secretary include surety bonds, cash deposits, certificates of deposit, deposits of government securities, escrow accounts, irrevocable letters or lines of credit, trust funds, and combinations of the above or other types of arrangements as may be approved by the Executive Secretary. Self-insurance, or an arrangement which

essentially constitutes self-insurance, will not satisfy the surety requirement for private sector applicants.

(8) The licensee's financial or surety arrangement shall remain in effect until the closure and stabilization program has been completed and approved by the Executive Secretary, and the license has been transferred to the site owner.

R313-25-32. Financial Assurances for Institutional Controls.

(1) Prior to the issuance of the license, the applicant shall provide for Executive Secretary approval, a binding arrangement, between the applicant and the disposal site owner that ensures that sufficient funds will be available to cover the costs of monitoring and required maintenance during the institutional control period. The binding arrangement shall be reviewed annually by the Executive Secretary to ensure that changes in inflation, technology, and disposal facility operations are reflected in the arrangements.

(2) Subsequent changes to the binding arrangement specified in R313-25-32(1) relevant to institutional control shall be submitted to the Executive Secretary for prior approval.

R313-25-33. Maintenance of Records, Reports, and Transfers.

(1) Licensees shall maintain records and make reports in connection with the licensed activities as may be required by the conditions of the license or by the rules and orders of the Executive Secretary.

(2) Records which are required by these rules or by license conditions shall be maintained for a period specified by the appropriate rules or by license condition. If a retention period is not otherwise specified, these records shall be maintained and transferred to the officials specified in R313-25-33(4) as a condition of license termination unless the Executive Secretary otherwise authorizes their disposition.

(3) Records which shall be maintained pursuant to R313-25 may be the original or a reproduced copy or microfilm if this reproduced copy or microfilm is capable of producing copy that is clear and legible at the end of the required retention period.

(4) Notwithstanding R313-25-33(1) through (3), copies of records of the location and the quantity of wastes contained in the disposal site shall be transferred upon license termination to the chief executive of the nearest municipality, the chief executive of the county in which the facility is located, the county zoning board or land development and planning agency, the State Governor, and other state, local, and federal governmental agencies as designated by the Executive Secretary at the time of license termination.

(5) Following receipt and acceptance of a shipment of waste, the licensee shall record the date that the shipment is received at the disposal facility, the date of disposal of the waste, a traceable shipment manifest number, a description of any engineered barrier or structural overpack provided for disposal of the waste, the location of disposal at the disposal site, the condition of the waste packages as

received, discrepancies between the materials listed on the manifest and those received, the volume of any pallets, bracing, or other shipping or onsite generated materials that are contaminated, and are disposed of as contaminated or suspect materials, and evidence of leakage or damaged packages or radiation or contamination levels in excess of limits specified in U.S. Department of Transportation and Executive Secretary regulations or rules. The licensee shall briefly describe repackaging operations of the waste packages included in the shipment, plus other information required by the Executive Secretary as a license condition.

(6) Licensees authorized to dispose of waste received from other persons shall file a copy of their financial report or a certified financial statement annually with the Executive Secretary in order to update the information base for determining financial qualifications.

(7)(a) Licensees authorized to dispose of waste received from other persons, pursuant to R313-25, shall submit annual reports to the Executive Secretary. Reports shall be submitted by the end of the first calendar quarter of each year for the preceding year.

(b) The reports shall include:

(i) specification of the quantity of each of the principal contaminants released to unrestricted areas in liquid and in airborne effluents during the preceding year;

(ii) the results of the environmental monitoring program;

(iii) a summary of licensee disposal unit survey and maintenance activities;

(iv) a summary, by waste class, of activities and quantities of radionuclides disposed of;

(v) instances in which observed site characteristics were significantly different from those described in the application for a license; and

(vi) other information the Executive Secretary may require.

(c) If the quantities of waste released during the reporting period, monitoring results, or maintenance performed are significantly different from those predicted, the report shall cover this specifically.

(8) In addition to the other requirements in R313-25-33, the licensee shall store, or have stored, manifest and other information pertaining to receipt and disposal of radioactive waste in an electronic recordkeeping system.

(a) The manifest information that must be electronically stored is:

(i) that required in Appendix G of 10 CFR 20.1001 to 20.2402, 1997 ed., which is incorporated into these rules by reference, with the exception of shipper and carrier telephone numbers and shipper and consignee certifications; and

(ii) that information required in R313-25-33(5).

(b) As specified in facility license conditions, the licensee shall report the stored information, or subsets of this information, on a computer-readable medium.

R313-25-34. Tests on Land Disposal Facilities.

Licensees shall perform, or permit the Executive Secretary to perform, any tests the Executive Secretary deems appropriate or necessary for the administration of the rules in R313-25, including, but not limited to, tests of;

(1) wastes;

(2) facilities used for the receipt, storage, treatment, handling or disposal of wastes;

(3) radiation detection and monitoring instruments; or

(4) other equipment and devices used in connection with the receipt, possession, handling, treatment, storage, or disposal of waste.

R313-25-35. Executive Secretary Inspections of Land Disposal Facilities.

(1) Licensees shall afford to the Executive Secretary, at reasonable times, opportunity to inspect waste not yet disposed of, and the premises, equipment, operations, and facilities in which wastes are received, possessed, handled, treated, stored, or disposed of.

(2) Licensees shall make available to the Executive Secretary for inspection, upon reasonable notice, records kept by it pursuant to these rules. Authorized representatives of the Executive Secretary may copy and take away copies of, for the Executive Secretary's use, any records required to be kept pursuant to R313-25.

KEY

radiation, radioactive waste disposal

Date of Enactment or Last Substantive Amendment

May 9, 2003

Notice of Continuation

October 10, 2001

Authorizing, Implemented, or Interpreted Law

19-3-104; 19-3-108

Rule converted into HTML by the Division of Administrative Rules.

For questions regarding the *content* or *application* of rules under Title R313, please contact the promulgating agency (Environmental Quality, Radiation Control). A list of agencies with links to their homepages is available at <http://www.utah.gov/government/agencylist.html>.

For questions about the *rulemaking process*, please contact the Division of Administrative Rules. *Please Note:* The Division of Administrative Rules is *not able* to answer questions about the content or application of these rules.

The HTML version of this rule is a convenience copy. This information is made available on the Internet as a public service. Please see [this disclaimer](#) about information available from www.rules.utah.gov.

[\[Division of Administrative Rules Home\]](#) | [\[UTAH ADMINISTRATIVE CODE List of Titles\]](#)

State Links: [Utah.gov Home](#) | [Utah.gov Terms of Use](#) | [Utah.gov Privacy Policy](#) | [Utah.gov Accessibility Policy](#).