3.7 PLANT SYSTEMS

3.7.1 Residual Heat Removal Service Water (RHRSW) System

LCO 3.7.1 Two RHRSW subsystems shall be OPERABLE.

APPLICABILITY: MODES 1, 2, and 3.

ACTIONS

CONDITION		REQUIRED ACTION		COMPLETION TIM
Α.	Not applicable to Unit 2 during replacement of the Division 1 CSCS isolation valves during Unit 1 Refueling 11 while Unit 1 is in Mode 4,5, or defueled. One RHRSW subsystem inoperable.	A.1	Enter applicable Conditions and Required Actions of LCO 3.4.9, "Residual Heat Removal (RHR) Shutdown Cooling System—Hot Shutdown," for RHR shutdown cooling subsystem made inoperable by RHRSW System.	
			Restore RHRSW subsystem to OPERABLE status.	7 days

(continued)

ACTIONS

	CONDITION		REQUIRED ACTION	COMPLETION TIME
В.	Only applicable to Unit 2 during replacement of the Division 1 CSCS isolation valves during Unit 1 Refueling 11 while Unit 1 is in Mode 4,5, or defueled. One RHRSW subsystem inoperable.	B.1	Enter applicable Conditions and Required Actions of LCO 3.4.9, "Residual Heat Removal (RHR) Shutdown Cooling System—Hot Shutdown," for RHR shutdown cooling subsystem made inoperable by RHRSW System.	
			Restore RHRSW subsystem to OPERABLE status.	10 days
C.	Both RHRSW subsystems inoperable.	C.1	Enter applicable Conditions and Required Actions of LCO 3.4.9 for RHR shutdown cooling subsystems made inoperable by RHRSW System.	
			Restore one RHRSW subsystem to OPERABLE status.	8 hours
D.	Required Action and associated Completion	D.1	Be in MODE 3.	12 hours
	Time not met.	<u>AND</u>		
		D.2	Be in MODE 4.	36 hours

SURVEILLANCE REQUIREMENTS

	FREQUENCY		
SR 3.7.1.1	Verify each RHRSW manual, power operated, and automatic valve in the flow path, that is not locked, sealed, or otherwise secured in position, is in the correct position or can be aligned to the correct position.	31 days	

3.	7	PΙ	ANT.	545	TEMS
J.	,			J 1 J	

3.7.2 Diesel Generator Cooling Water (DGCW) System

LCO 3.7.2 The following DGCW subsystems shall be OPERABLE:

- a. Three DGCW subsystems; and
- b. The opposite unit Division 2 DGCW subsystem.

APPLICABILITY: MODES 1, 2, and 3.

A	С	T	Ι	0	N	S

				- 	NO ⁻	TE			 		 	-
Separate	${\tt Condition}$	entry	is	allowed	for	each	DGCW	subsystem.				
			- - -						 	-,	 	-

ACTIONS

CONDITION	REQUIRED ACTION	COMPLETION TIME
NOTES 1. Not applicable to Division 1 during replacement of the Division 1 CSCS isolation valves during Unit 1 Refueling 11 while Unit 1 is in MODE 4,5, or defueled.	A.1 Declare supported component(s) inoperable.	Immediately
2. Not applicable to Division 2 during replacement of the Division 2 CSCS isolation valves during Unit 2 Refueling 11 while Unit 2 is in MODE 4,5, or defueled and during Unit 1 Refueling 12 while Unit 1 is in MODE 4,5, or defueled.		
One or more DGCW subsystems inoperable.		

(continued)

	CONDITION		REQUIRED ACTION	COMPLETION TIME
В.	1. Only applicable to Division 1 during replacement of the Division 1 CSCS isolation valves during Unit 1 Refueling 11 while Unit 1 is in Mode 4,5, or defueled.	B.1	Restore DGCW subsystem to OPERABLE status.	6 days OR 10 days if Division 1 CSCS inoperable
	2. Only applicable to Division 2 during replacement of the Division 2 CSCS isolation valves during Unit 2 Refueling 11 while Unit 2 is in MODE 4,5, or defueled and during Unit 1 Refueling 12 while Unit 1 is in MODE 4,5, or defueled.			
	One or more DGCW subsystems inoperable.			
С.	Required Action and associated Completion Time of Condition B	C.1	Be in MODE 3.	12 hours
	not met.	C.2	Be in MODE 4.	36 hours

SURVEILLANCE REQUIREMENTS

		FREQUENCY		
SR	3.7.2.1	Verify each DGCW subsystem manual, power operated, and automatic valve in the flow path, that is not locked, sealed, or otherwise secured in position, is in the correct position.	31 days	
SR	3.7.2.2	Verify each DGCW pump starts automatically on each required actual or simulated initiation signal.	24 months	