

**CERTIFICATE OF COMPLIANCE
FOR RADIOACTIVE MATERIALS PACKAGES**

1.a CERTIFICATE NUMBER 9261	b. REVISION NUMBER 24	c. PACKAGE IDENTIFICATION NUMBER USA/9261/B(U)F-85	d. PAGE NUMBER 1	e. TOTAL NUMBER PAGES 11
------------------------------------	------------------------------	---	-------------------------	---------------------------------

2. PREAMBLE

- a. This certificate is issued to certify that the packaging and contents described in Item 5 below, meets the applicable safety standards set forth in Title 10, Code of Federal Regulations, Part 71, "Packaging and Transportation of Radioactive Material."
- b. This certificate does not relieve the consignor from compliance with any requirement of the regulations of the U.S. Department of Transportation or other applicable regulatory agencies, including the government of and country through or into which the package will be transported.

3. THIS CERTIFICATE IS ISSUED ON THE BASIS OF A SAFETY ANALYSIS REPORT OF THE PACKAGE DESIGN OR APPLICATION

a. ISSUED TO (<i>Name and Address</i>) Holtec International Holtec Center 555 Lincoln Drive West Marlton, NJ 08053	b. TITLE AND IDENTIFICATION OF REPORT OR APPLICATION: Holtec International application dated October 23, 1995, as supplemented c. DOCKET NUMBER 71-9261
--	---

4. CONDITIONS

This certificate is conditional upon fulfilling the requirements of 10CFR Part 71, as applicable, and the conditions specified below.

5.

5.a. Packaging

(1) Model No.: HI-STAR 100 System

(2) Description

The HI-STAR 100 System is a canister system comprising a Multi-Purpose Canister (MPC) inside of an overpack designed for both storage and transportation (with impact limiters) of irradiated nuclear fuel. The HI-STAR 100 System consists of interchangeable MPCs that house the spent nuclear fuel and an overpack that provides the containment boundary, helium retention boundary, gamma and neutron radiation shielding, and heat rejection capability. The outer diameter of the overpack of the HI-STAR 100 is approximately 96 inches without impact limiters and approximately 128 inches with impact limiters. Maximum gross weight for transportation (including overpack, MPC, fuel, and impact limiters) is 282,000 pounds. Specific tolerances germane to the safety analyses for the package are called out in drawings listed below.

Multi-Purpose Canister

There are ~~five~~ six Multi-Purpose Canister (MPC) models, designated the MPC-24, MPC-24E, MPC-24EF, MPC-32, MPC-68, and MPC-68F. All MPCs are designed to have identical exterior dimensions, except those MPC-24E/EFs custom-designed for the Trojan plant, which are approximately nine inches shorter than the generic Holtec MPC design. A single overpack design is provided that is capable of containing each type of MPC. The two digits after the MPC designate the number of reactor fuel assemblies for which the respective MPCs are designed. The MPC-24 series is designed to contain up to 24 Pressurized Water Reactor (PWR) fuel assemblies; *the MPC-32 is*

5. a. (2) Description (continued)

designed to contain up to 32 PWR fuel assemblies; and the MPC-68 and MPC-68F are designed to contain up to 68 Boiling Water Reactor (BWR) fuel assemblies. Any MPC-68 loaded with material classified as fuel debris is designated as MPC-68F. Any MPC-24E loaded with material classified as fuel debris is designated as MPC-24EF.

The HI-STAR 100 MPC is a welded cylindrical structure with flat ends. Each MPC is an assembly consisting of a honeycombed fuel basket, baseplate, canister shell, lid, and closure ring. The outer diameter and cylindrical height of each generic MPC is fixed. The outer diameter of the Trojan MPCs is the same as the generic MPC, but the height is approximately nine inches shorter than the generic MPC design. A steel spacer is used with the Trojan plant MPCs to ensure the MPC-overpack interface is bounded by the generic design. The fuel basket designs vary based on the MPC model. For the HI-STAR 100 System transporting fuel debris in a MPC-68F or MPC-24EF, the MPC provides the second inner container, in accordance with 10CFR71.63. The MPC pressure boundary is a strength-welded enclosure constructed entirely of a stainless steel alloy.

Overpack

The HI-STAR 100 overpack is a multi-layer steel cylinder with a welded baseplate and bolted lid (closure plate). The inner shell of the overpack forms an internal cylindrical cavity for housing the MPC. The outer surface of the overpack inner shell is buttressed with intermediate steel shells for radiation shielding. The overpack closure plate incorporates a dual O-ring design to ensure its containment function. The containment system consists of the overpack inner shell, bottom plate, top flange, top closure plate, top closure inner O-ring seal, vent port plug and seal, and drain port plug and seal.

Impact Limiters

The HI-STAR 100 overpack is fitted with two impact limiters fabricated of aluminum honeycomb completely enclosed by an all-welded austenitic stainless steel skin. The two impact limiters are attached to the overpack with 20 and 16 bolts at the top and bottom, respectively.

(3) Drawings

The package shall be constructed and assembled in accordance with the following drawings or figures in Holtec International Report No. HI-951251, *Safety Analysis Report for the Holtec International Storage, Transport, And Repository Cask System (HI-STAR 100 Cask System)*, Revision 1240:

- | | |
|---|----------------------------------|
| (a) HI-STAR 100 MPC-24
Fuel Basket | Drawing 3926, Sheets 1-4, Rev. 5 |
| (b) HI-STAR 100 MPC-24E/EF
Fuel Basket | Drawing 3925, Sheets 1-4, Rev. 4 |

Page 3 - Certificate No. 9261 - Revision No. 1 - Docket No. 71-9261

5. a. (3) Drawings (continued)

- | | |
|---|---|
| (c) HI-STAR 100 MPC-68/68F/68FF
Fuel Basket | Drawing 3928, Sheets 1-4, Rev. 4 |
| (d) HI-STAR 100 MPC
Enclosure Vessel | Drawing 3923, Sheets 1-5, Rev. 8 |
| (e) HI-STAR 100 Overpack | Drawing 3913, Sheets 1-9, Rev. 5 |
| (f) HI-STAR 100 Impact Limiters | Drawing C1765, Sheets 1-6, Rev. 1; and Sheet 7, Rev. 0 |
| (g) HI-STAR 100 Assembly
for Transport | Drawing 3930, Sheets 1-3, Rev. 1 |
| (h) Trojan MPC Spacer | Drawing 4111, Sheets 1 and 2, Rev. 0 |
| (i) Trojan Failed Fuel Can | SNC Drawings PFFC-001, Rev. 8 and PFFC-002, Sheets 1
and 2, Rev. 7 |
| (j) Trojan Failed Fuel Can Spacer | Drawing 4122, Sheets 1 and 2, Rev. 0 |
| (k) Holtec Damaged Fuel Container
for Trojan plant SNF | Drawing 4119, Sheet 1-4, Rev. 1 |
| (l) <i>HI-STAR 100 MPC-32
Fuel Basket</i> | <i>Drawing 3927, Sheets 1-4, Rev. 6</i> |

5. b. Contents

(1) Type and Form, and Quantity of Material

(a) Fuel assemblies meeting the specifications and quantities provided in Appendix A to this Certificate of Compliance and meeting the requirements provided in Conditions 5.b(1)(b) through 5.b(1)(g) below are authorized for transportation.

(b) The following definitions apply:

Damaged Fuel Assemblies are fuel assemblies with known or suspected cladding defects, as determined by review of records, greater than pinhole leaks or hairline cracks, empty fuel rod locations that are not filled with dummy fuel rods, or those that cannot be handled by normal means. Fuel assemblies which cannot be handled by normal means due to fuel cladding damage are considered fuel debris.

5.b.1.(b) Definitions (continued)

Damaged Fuel Containers (or Canisters) (DFCs) are specially designed fuel containers for damaged fuel assemblies or fuel debris that permit gaseous and liquid media to escape while minimizing dispersal of gross particulates. The DFC designs authorized for use in the HI-STAR 100 are shown in Figures 1.2.10 and 1.2.11 of the HI-STAR 100 System SAR, Rev. 4012.

Fuel Debris is ruptured fuel rods, severed fuel rods, loose fuel pellets, or fuel assemblies with known or suspected defects which cannot be handled by normal means due to fuel cladding damage. Fuel debris also includes certain Trojan plant-specific fuel material contained in Trojan Failed Fuel Cans.

Incore Grid Spacers are fuel assembly grid spacers located within the active fuel region (i.e., not including top and bottom spacers).

Intact Fuel Assemblies are fuel assemblies without known or suspected cladding defects greater than pinhole leaks or hairline cracks and which can be handled by normal means. Fuel assemblies without fuel rods in fuel rod locations shall not be classified as intact fuel assemblies unless dummy fuel rods are used to displace an amount of water greater than or equal to that displaced by the original fuel rod(s).

Minimum Enrichment is the minimum assembly average enrichment. Natural uranium blankets are not considered in determining minimum enrichment.

Non-Fuel Hardware is defined as Burnable Poison Rod Assemblies (BPRAs), Thimble Plug Devices (TPDs), and Rod Cluster Control Assemblies (RCCAs).

Planar-Average Initial Enrichment is the average of the distributed fuel rod initial enrichments within a given axial plane of the assembly lattice.

Trojan Damaged Fuel Containers (or Canisters) are Holtec damaged fuel containers custom-designed for Trojan plant damaged fuel and fuel debris as depicted in Drawing 4119, Rev. 0.

Trojan Failed Fuel Cans are non-Holtec designed Trojan plant-specific damaged fuel containers that may be loaded with Trojan plant damaged fuel assemblies, Trojan fuel assembly metal fragments (e.g., portions of fuel rods and grid assemblies, bottom nozzles, etc.), a Trojan fuel rod storage container, a Trojan Fuel Debris Process Can Capsule, or a Trojan Fuel Debris Process Can. The Trojan Failed Fuel Can is depicted in Drawings PFFC-001, Rev. 8 and PFFC-002, Rev. 7.

Page 5 - Certificate No. 9261 - Revision No. 1 - Docket No. 71-9261

5.b.1.(b) Definitions (continued)

Trojan Fuel Debris Process Cans are Trojan plant-specific canisters containing fuel debris (metal fragments) and were used to process organic media removed from the Trojan plant spent fuel pool during cleanup operations in preparation for spent fuel pool decommissioning. Trojan Fuel Debris Process Cans are loaded into Trojan Fuel Debris Process Can Capsules or directly into Trojan Failed Fuel Cans. The Trojan Fuel Debris Process Can is depicted in Figure 1.2.10B of the HI-STAR 100 System SAR, Rev. 4012.

Trojan Fuel Debris Process Can Capsules are Trojan plant-specific canisters that contain up to five Trojan Fuel Debris Process Cans and are vacuumed, purged, backfilled with helium and then seal-welded closed. The Trojan Fuel Debris Process Can Capsule is depicted in Figure 1.2.10C of the HI-STAR 100 System SAR, Rev. 4012.

ZR means any zirconium-based fuel cladding material authorized for use in a commercial nuclear power plant reactor.

- (c) For MPCs partially loaded with stainless steel clad fuel assemblies, all remaining fuel assemblies in the MPC shall meet the more restrictive of the two limits for the stainless steel clad fuel assemblies or the applicable ZR clad fuel assemblies.
- (d) For MPC-68s and MPC-68Fs partially loaded with damaged fuel assemblies or fuel debris, all remaining ZR clad intact fuel assemblies in the MPC shall meet the more restrictive of the two limits for the damaged fuel assemblies or the intact fuel assemblies.
- (e) For MPC-68s partially loaded with array/class 6x6A, 6x6B, 6x6C, 7x7A, or 8x8A fuel assemblies, all remaining Zircaloy-clad intact fuel assemblies in the MPC shall meet the more restrictive of the two limits for the 6x6A, 6x6B, 6x6C, 7x7A, and 8x8A fuel assemblies or the applicable Zircaloy-clad fuel assemblies.
- (f) PWR non-fuel hardware and neutron sources are not authorized for transportation except as specifically provided for in Appendix A to this CoC.
- (g) BWR stainless-steel channels and control blades are not authorized for transportation.

c. Transport Index for Criticality Control

The minimum transport index to be shown on the label for nuclear criticality control: 0

6. ~~For operating controls and procedures,~~ In addition to the requirements of Subpart G of 10 CFR Part 71:
- a. Each package shall be both prepared for shipment and operated in accordance with ~~detailed written operating procedures. Procedures for both preparation and operation shall be developed. At a minimum, those procedures shall include~~ the following provisions *in Chapter 7 of the Application.*

Page 6 - Certificate No. 9261 - Revision No. 1 - Docket No. 71-9261

6.a (continued)

- ~~(1) Identification of the fuel to be loaded and independent verification that the fuel meets the specifications of Condition 5.b above.~~
- ~~(2) Before each shipment, the licensee or shipper shall verify and document that each of the requirements of 10 CFR 71.87 has been satisfied.~~
- ~~(3) The package must satisfy the following leak testing requirements:
 - ~~(a) All overpack containment boundary seals shall be leak tested to show a total leak rate of not greater than 4.3×10^{-6} atm cm³/sec (helium). The leak test shall have a minimum sensitivity of 2.15×10^{-6} atm cm³/sec (helium) and shall be performed:
 - ~~(i) within the 12-month period prior to each shipment;~~
 - ~~(ii) after detensioning one or more overpack lid bolts or the vent port plug; and~~
 - ~~(iii) After each seal replacement.~~~~
 - ~~(b) Within 30 days before each shipment, all overpack containment boundary seals shall be leak tested using a test with a minimum sensitivity of 1×10^{-5} atm cm³/sec. If leakage is detected on a seal, then the seal must be replaced and leak tested per Condition 6.a(3)(a) above.~~
 - ~~(c) Each overpack containment boundary seal must be replaced after each use of the seal.~~~~
- ~~(4) The relief devices on the neutron shield vessel shall be replaced every 5 years.~~
- ~~(5) MPC-68F and MPC-24EF shall be leak tested prior to shipment to show a leak rate of no greater than 5×10^{-6} atm cm³/sec (helium). The leak test shall have a minimum sensitivity of 2.5×10^{-6} atm cm³/sec (helium).~~
- ~~(6) MPCs deployed at an ISFSI under 10 CFR 72 prior to transportation may be dried using the vacuum drying method or the Forced Helium Dehydration (FHD) method. MPCs placed directly into transportation service under 10 CFR 71 without first being deployed at an ISFSI must be dried using the FHD method. Water and residual moisture shall be removed from the MPC in accordance with the following specifications:~~

Page 7 - Certificate No. 9261 - Revision No. 1 - Docket No. 71-9261

~~6.a.(6) (continued)~~

~~For those MPCs vacuum dried:~~

~~(a) The MPC shall be evacuated to a pressure of less than or equal to 3 torr.~~

~~(b) The MPC cavity shall hold a stable pressure of less than or equal to 3 torr for at least 30 minutes.~~

~~For those MPCs dried using the FHD System:~~

~~(a) Following bulk moisture removal, the temperature of the gas exiting the demoisurizer shall be $< 21^{\circ}\text{F}$ for > 30 minutes.~~

(7) Following drying, the MPC shall be backfilled with 99.995% minimum purity helium: > 0 psig and < 44.8 psig at a reference temperature of 70°F .

(8) Water and residual moisture shall be removed from the III-STAR 100 overpack in accordance with the following specifications:

~~(a) The overpack annulus shall be evacuated to a pressure of less than or equal to 3 torr.~~

~~(b) The overpack annulus shall hold a stable pressure of less than or equal to 3 torr for at least 30 minutes.~~

(9) Following vacuum drying, the overpack shall be backfilled with helium to > 10 psig and < 14 psig.

(10) The following fasteners shall be tightened to the torque values specified below:

Fastener	Torque (ft-lbs)
Overpack Closure Plate Bolts	2985 + 90
Overpack Vent and Drain Port Plugs	45 +5/-2
Top Impact Limiter Attachment Bolts	256 +10/-0
Bottom Impact Limiter Attachment Bolts	1500 +45/-0

(11) Verify that the appropriate fuel spacers, as necessary, are used to position the fuel in the MPC cavity.

b. All acceptance tests and maintenance shall be performed in accordance with detailed written procedures. Procedures for fabrication, acceptance testing, and maintenance shall be developed and shall include the following provisions in Chapter 8 of the Application.

(1) The overpack lifting trunnions shall be tested at 300% of the maximum design lifting load.

Page 8 - Certificate No. 9261 - Revision No. 1 - Docket No. 71-9261

6.b (continued)

- ~~(2) The MPC shall be pressure tested in accordance with ASME Section III, Subsection NB, Article NB-6110 and applicable sub-articles. If hydrostatic testing is used, the MPC shall be pressure tested to 125% of the design pressure. The minimum hydrostatic test pressure shall be 125 psig. If pneumatic testing is used, the MPC shall be pressure tested to 120% of the design pressure. The minimum pneumatic test pressure shall be 120 psig.~~
- ~~(3) The overpack shall be pressure tested to 150% of the Maximum Normal Operating Pressure (MNOP). The minimum test pressure shall be 150 psig.~~
- ~~(4) The MPC lid-to-shell (LTS) weld shall be verified by either volumetric examination using the Ultrasonic (UT) method or multi-layer liquid penetrant (PT) examination. The root and final weld layers shall be PT examined in either case. If PT alone is used, additional intermediate PT examination(s) shall be conducted after each approximately 3/8 inch of the weld is completed. The inspection of the weld must be performed by qualified personnel and shall meet the acceptance requirements of ASME B&PV Section III, NB-5350. The inspection results, including all relevant indications shall be made a permanent part of the licensee's records by video, photographic, or other means providing an equivalent retrievable record of weld integrity.~~
- ~~(5) The radial neutron shield shall have a minimum thickness of 4.3 inches and the impact limiter neutron shields shall have a minimum thickness of 2.5 inches. Before first use, the neutron shielding integrity shall be confirmed through a combination of fabrication process control and radiation measurements with either loaded contents or a check source. Measurements shall be performed over the entire exterior surface of the radial neutron shield and each impact limiter using, at a maximum, a 6 x 6 inch test grid.~~
- ~~(6) Periodic verification of the neutron shield integrity shall be performed within 5 years of each shipment. The periodic verification shall be performed by radiation measurements with either loaded contents or a check source. Measurements shall be taken at three cross sectional planes through the radial shield and at four points along each plane's circumference. The average measurement results from each sectional plane shall be compared to calculated values to assess the continued effectiveness of the neutron shield. The calculated values shall be representative of the loaded contents (i.e., fuel type, enrichment, burnup, cooling time, etc.) or the particular check source used for the measurements.~~
- ~~(7) The first fabricated HI-STAR 100 overpack shall be tested to confirm its heat transfer capability. The test shall be conducted after the radial channels, enclosure shell panels, and neutron shield material have been installed and all inside and outside surfaces are painted per the Design Drawings specified in Section 1.4 of the SAR, Rev. 9. A test cover plate shall be used to seal the overpack cavity. Testing shall be performed in accordance with written and approved procedures. The test must demonstrate that the overpack is fabricated adequately to meet the design heat transfer capability.~~

Page 9 - Certificate No. 9261 - Revision No. 1 - Docket No. 71-9261

6.b (continued)

- ~~(8) For each package, a periodic thermal performance test shall be performed every 5 years or prior to next use, if the package has not been used for transport for greater than 5 years, to demonstrate that the thermal capabilities of the cask remain within its design basis.~~
- ~~(9) The MPC neutron absorber's minimum acceptable ^{10}B loading is 0.0267 g/cm² for the MPC-24 and 0.0372 g/cm² for the MPC-24E, MPC-24EF, MPC-32, and MPC-68; and 0.01 g/cm² for the MPC-68F. The ^{10}B loading shall be verified by chemistry or neutron attenuation techniques. The neutron absorber test requirements in Section 8.1.5.3 of the HI-STAR 100 SAR are hereby incorporated by reference into this CoC.~~
- ~~(10) a. The minimum flux trap size for the MPC-24 is 1.09 inches.~~
~~b. The minimum flux trap sizes for the generic MPC-24E and MPC-24EF are 0.776 inch for cells 3, 6, 9, and 22; and 1.076 inch for the remaining cells.~~
~~c. The minimum flux trap sizes for the Trojan MPC-24E and MPC-24EF are 0.526 inch for cells 3, 6, 9, and 22; and 1.076 inch for the remaining cells.~~
- ~~(11) a. The minimum fuel cell pitch for the MPC-68 and MPC-68F is 6.43 inches.~~
~~b. The minimum fuel cell pitch for the MPC-32 is 9.158 inches.~~
- ~~(12) The package containment verification leak test shall be per ANSI N14.5-1997.~~

- 7. The maximum gross weight of the package as presented for shipment shall not exceed 282,000 pounds.
- 8. The package shall be located on the transport vehicle such that the bottom surface of the bottom impact limiter is at least 9 feet (along the axis of the overpack) from the edge of the vehicle.
- 9. The personnel barrier shall be installed at all times while transporting a loaded overpack.
- 10. The package authorized by this certificate is hereby approved for use under the general license provisions of 10 CFR 71.12.
- 11. Expiration Date: ~~March 31, 2004~~ TBD

Attachment: Appendix A

REFERENCES:

Holtec International Report No. HI-951251, *Safety Analysis Report for the Holtec International Storage, Transport, And Repository Cask System (HI-STAR 100 Cask System)*, Revision 4012, dated TBD.

FOR THE U.S. NUCLEAR REGULATORY COMMISSION

Page 10 - Certificate No. 9261 - Revision No. 1 - Docket No. 71-9261

E. William Brach, Director
Spent Fuel Project Office
Office of Nuclear Material Safety
and Safeguards

Date: TBD

|

APPENDIX A

CERTIFICATE OF COMPLIANCE NO. 9261, REVISION 24

MODEL NO. HI-STAR 100 SYSTEM

INDEX TO APPENDIX A

Page:	Table:	Description:
Page A-1 to A-20	Table A1	Fuel Assembly Limits
Page A-1		MPC-24: Uranium oxide, PWR intact fuel assemblies listed in Table A.2.
A-2		MPC-68: Uranium oxide, BWR intact fuel assemblies listed in Table A.3, with or without Zircaloy channels.
A-3		MPC-68: Uranium oxide, BWR damaged fuel assemblies, with or without Zircaloy channels, placed in damaged fuel containers. Uranium oxide BWR damaged fuel assemblies shall meet the criteria specified in Table A.3 for fuel assembly array/class 6x6A, 6x6C, 7x7A, or 8x8A.
A-4		MPC-68: Mixed oxide (MOX), BWR intact fuel assemblies, with or without Zircaloy channels. MOX BWR intact fuel assemblies shall meet the criteria specified in Table A.3 for fuel assembly array/class 6x6B.
A-5		MPC-68: Mixed oxide (MOX), BWR damaged fuel assemblies, with or without Zircaloy channels, placed in damaged fuel containers. MOX BWR damaged fuel assemblies shall meet the criteria specified in Table A.3 for fuel assembly array/class 6x6B.
A-6		MPC-68: Thoria rods (ThO_2 and UO_2) placed in Dresden Unit 1 Thoria Rod Canisters
A-7		MPC-68F: Uranium oxide, BWR intact fuel assemblies, with or without Zircaloy channels. Uranium oxide BWR intact fuel assemblies shall meet the criteria in Table A.3 for fuel assembly array/class 6x6A, 6x6C, 7x7A, or 8x8A.
A-8		MPC-68F: Uranium oxide, BWR damaged fuel assemblies, with or without Zircaloy channels, placed in damaged fuel containers. Uranium oxide BWR damaged fuel assemblies shall meet the criteria specified in Table A.3 for fuel assembly array/class 6x6A, 6x6C, 7x7A, or 8x8A.

Appendix A - Certificate of Compliance 9261

INDEX TO APPENDIX A

Page	Table:	Description:
A-9	Table A.1 (Cont'd)	MPC-68F: Uranium oxide, BWR fuel debris, with or without Zircaloy channels, placed in damaged fuel containers. The original fuel assemblies for the uranium oxide BWR fuel debris shall meet the criteria specified in Table A.3 for fuel assembly array/class 6x6A, 6x6C, 7x7A, or 8x8A.
A-10		MPC-68F: Mixed oxide (MOX), BWR intact fuel assemblies, with or without Zircaloy channels. MOX BWR intact fuel assemblies shall meet the criteria specified in Table A.3 for fuel assembly array/class 6x6B.
A-11		MPC-68F: Mixed oxide (MOX), BWR damaged fuel assemblies, with or without Zircaloy channels placed in damaged fuel containers. MOX BWR damaged fuel assemblies shall meet the criteria specified in Table A.3 for fuel assembly array/class 6x6B.
A-12		MPC-68F: Mixed Oxide (MOX), BWR fuel debris, with or without Zircaloy channels, placed in damaged fuel containers. The original fuel assemblies for the MOX BWR fuel debris shall meet the criteria specified in Table A.3 for fuel assembly array/class 6x6B.
A-13		MPC-68F: Allowable Contents - Thoria rods (ThO_2 and UO_2) placed in Thoria Rod Canisters
A-15		MPC-24E: Uranium oxide, PWR intact fuel assemblies listed in Table A.2.
A-16		MPC-24E: Trojan plant damaged fuel assemblies.
A-17		MPC-24EF: Uranium oxide, PWR intact fuel assemblies listed in Table A.2.
A-18		MPC-24EF: Trojan plant damaged fuel assemblies.
A-19		MPC-24EF: Trojan plant Fuel Debris Process Can Capsules and/or Trojan plant fuel assemblies classified as fuel debris.
A-20		<i>MPC-32: Uranium oxide, PWR intact fuel assemblies in array classes 15x15D, E, F, and H and 17x17A, B, and C as listed in Table A.2.</i>
A-21 to A-24	Table A.2	PWR Fuel Assembly Characteristics

Appendix A - Certificate of Compliance 9261

INDEX TO APPENDIX A

Page:	Table:	Description:
A-25 to A-29	Table A.3	BWR Fuel Assembly Characteristics
A-30	Table A.4	Fuel Assembly Cooling, Average Burnup, and Minimum Enrichment MPC-24/24E/24EF PWR Fuel with Zircaloy Clad and with Non-Zircaloy In-Core Grid Spacers.
A-30	Table A.5	Fuel Assembly Cooling, Average Burnup, and Minimum Enrichment MPC-24/24E/24EF PWR Fuel with Zircaloy and with Zircaloy In-Core Grid Spacers.
A-31	Table A.6	Fuel Assembly Cooling, Average Burnup, and Minimum Enrichment MPC-24/24E/24EF PWR Fuel with Stainless Steel Clad.
A-31	Table A.7	Fuel Assembly Cooling, Average Burnup, and Minimum Enrichment MPC-68.
A-32	Table A.8	<i>Trojan Plant Fuel Assembly Cooling, Average Burnup, and Minimum Enrichment Limits.</i>
A-32	Table A.9	<i>Trojan Plant Non-Fuel Hardware and Neutron Source Cooling and Burnup Limits.</i>
A-33	Table A.10	<i>Fuel Assembly Cooling, Average Burnup, and Minimum Enrichment MPC-32 PWR Fuel with Zircaloy Clad and with Non-Zircaloy In-Core Grid Spacers.</i>
A-33	Table A.11	<i>Fuel Assembly Cooling, Average Burnup, and Minimum Enrichment MPC-32 PWR Fuel with Zircaloy Clad and with Zircaloy In-Core Grid Spacers</i>
A-34	Table A.12	<i>Fuel Assembly Maximum Enrichment and Minimum Burnup Requirements for Transportation in MPC-32</i>
A-35	Table A.13	<i>Loading Configurations for the MPC-32</i>
A-35		References

Table A.1 (Page 1 of 20)
Fuel Assembly Limits

I. MPC MODEL: MPC-24

A. Allowable Contents

1. Uranium oxide, PWR intact fuel assemblies listed in Table A.2 and meeting the following specifications:

- a. Cladding type: ZR or Stainless Steel (SS) as specified in Table A.2 for the applicable fuel assembly array/class
- b. Maximum Initial Enrichment: As specified in Table A.2 for the applicable fuel assembly array/class.
- c. Post-irradiation cooling time, average burnup, and minimum initial enrichment per assembly
 - i. ZR Clad: An assembly post-irradiation cooling time, average burnup, and minimum initial enrichment as specified in Table A.4 or A.5, as applicable.
 - ii. SS Clad: An assembly post-irradiation cooling time, average burnup, and minimum initial enrichment as specified in Table A.6, as applicable.
- d. Decay heat per assembly
 - i. ZR Clad: ≤ 833 Watts
 - ii. SS Clad: ≤ 488 Watts
- e. Fuel assembly length: ≤ 176.8 inches (nominal design)
- f. Fuel assembly width: ≤ 8.54 inches (nominal design)
- g. Fuel Assembly Weight: $\leq 1,680$ lbs

B. Quantity per MPC: Up to 24 PWR fuel assemblies.

C. Fuel assemblies shall not contain non-fuel hardware or neutron sources.

D. Damaged fuel assemblies and fuel debris are not authorized for transport in the MPC-24.

E. Trojan plant fuel is not permitted to be transported in the MPC-24.

Table A.1 (Page 2 of 20)
Fuel Assembly Limits

II. MPC MODEL: MPC-68

A. Allowable Contents

1. Uranium oxide, BWR intact fuel assemblies listed in Table A.3, with or without Zircaloy channels, and meeting the following specifications:

- a. Cladding type: ZR or Stainless Steel (SS) as specified in Table A.3 for the applicable fuel assembly array/class.
- b. Maximum planar-average initial enrichment: As specified in Table A.3 for the applicable fuel assembly array/class.
- c. Initial maximum rod enrichment: As specified in Table A.3 for the applicable fuel assembly array/class.
- d. Post-irradiation cooling time, average burnup, and minimum initial enrichment per assembly:
 - i. ZR Clad: An assembly post-irradiation cooling time, average burnup, and minimum initial enrichment as specified in Table A.7, except for (1) array/class 6x6A, 6x6C, 7x7A, and 8x8A fuel assemblies, which shall have a cooling time ≥ 18 years, an average burnup $\leq 30,000$ MWD/MTU, and a minimum initial enrichment ≥ 1.8 wt% ^{235}U and (2) array/class 8x8F fuel assemblies, which shall have a cooling time ≥ 10 years, an average burnup $\leq 27,500$ MWD/MTU, and a minimum initial enrichment ≥ 2.4 wt% ^{235}U .
 - ii. SS Clad: An assembly cooling time after discharge ≥ 16 years, an average burnup $\leq 22,500$ MWD/MTU, and a minimum initial enrichment ≥ 3.5 wt% ^{235}U .
- e. Decay heat per assembly
 - i. ZR Clad: ≤ 272 Watts, except for array/class 8x8F fuel assemblies, which shall have a decay heat ≤ 183.5 Watts
 - ii. SS Clad: ≤ 83 Watts
- f. Fuel assembly length: ≤ 176.2 inches (nominal design)
- g. Fuel assembly width: ≤ 5.85 inches (nominal design)
- h. Fuel assembly weight: ≤ 700 lbs, including channels

Table A.1 (Page 3 of 20)
Fuel Assembly Limits

II. MPC MODEL: MPC-68 (continued)

A. Allowable Contents (continued)

2. Uranium oxide, BWR damaged fuel assemblies, with or without Zircaloy channels, placed in damaged fuel containers. Uranium oxide BWR damaged fuel assemblies shall meet the criteria specified in Table A.3 for fuel assembly array/class 6x6A, 6x6C, 7x7A, or 8x8A, and meet the following specifications:

- | | |
|--|--|
| a. Cladding type: | ZR |
| b. Maximum planar-average initial enrichment: | As specified in Table A.3 for the applicable fuel assembly array/class. |
| c. Initial maximum rod enrichment: | As specified in Table A.3 for the applicable fuel assembly array/class. |
| d. Post-irradiation cooling time, average burnup, and minimum initial enrichment per assembly: | An assembly post-irradiation cooling time ≥ 18 years, an average burnup $\leq 30,000$ MWD/MTU, and a minimum initial enrichment ≥ 1.8 wt% ^{235}U . |
| e. Fuel assembly length: | ≤ 135.0 inches (nominal design) |
| f. Fuel assembly width: | ≤ 4.70 inches (nominal design) |
| g. Fuel assembly weight | ≤ 550 lbs, including channels and damaged fuel container |

Table A.1 (Page 4 of 20)
Fuel Assembly Limits

II. MPC MODEL: MPC-68 (continued)

A. Allowable Contents (continued)

3. Mixed oxide (MOX), BWR intact fuel assemblies, with or without Zircaloy channels. MOX BWR intact fuel assemblies shall meet the criteria specified in Table A.3 for fuel assembly array/class 6x6B and meet the following specifications:

- | | |
|--|--|
| a. Cladding type: | ZR |
| b. Maximum Planar-Average Initial Enrichment: | As specified in Table A.3 for fuel assembly array/class 6x6B. |
| c. Initial Maximum Rod Enrichment: | As specified in Table A.3 for fuel assembly array/class 6x6B. |
| d. Post-irradiation cooling time, average burnup, and minimum initial enrichment per assembly: | An assembly post-irradiation cooling time ≥ 18 years, an average burnup $\leq 30,000$ MWD/MTIHM, and a minimum initial enrichment ≥ 1.8 wt% ^{235}U for the UO_2 rods. |
| e. Fuel assembly length: | ≤ 135.0 inches (nominal design) |
| f. Fuel assembly width: | ≤ 4.70 inches (nominal design) |
| g. Fuel assembly weight | ≤ 400 lbs, including channels |

Table A.1 (Page 5 of 20)
Fuel Assembly Limits

II. MPC MODEL: MPC-68 (continued)

A. Allowable Contents (continued)

4. Mixed oxide (MOX), BWR damaged fuel assemblies, with or without Zircaloy channels, placed in damaged fuel containers. MOX BWR intact fuel assemblies shall meet the criteria specified in Table A.3 for fuel assembly array/class 6x6B and meet the following specifications:

- | | |
|--|--|
| a. Cladding type: | ZR |
| b. Maximum planar-average initial enrichment: | As specified in Table A.3 for array/class 6x6B. |
| c. Initial Maximum Rod Enrichment: | As specified in Table A.3 for array/class 6x6B. |
| d. Post-irradiation cooling time, average burnup, and minimum initial enrichment per assembly: | An assembly post-irradiation cooling time ≥ 18 years, an average burnup $\leq 30,000$ MWD/MTIHM, and a minimum initial enrichment ≥ 1.8 wt% ^{235}U for the UO_2 rods. |
| e. Fuel assembly length: | ≤ 135.0 inches (nominal design) |
| f. Fuel assembly width: | ≤ 4.70 inches (nominal design) |
| g. Fuel assembly weight | ≤ 550 lbs, including channels and damaged fuel container |

Table A.1(Page 6 of 20)
Fuel Assembly Limits

II. MPC MODEL: MPC-68 (continued)

A. Allowable Contents (continued)

5. Thoria rods (ThO_2 and UO_2) placed in Dresden Unit 1 Thoria Rod Canisters (as shown in Figure 1.2.11A of the HI-STAR 100 System SAR, Revision 12) and meeting the following specifications:

- a. Cladding Type: ZR
- b. Composition: 98.2 wt.% ThO_2 , 1.8 wt. % UO_2 with an enrichment of 93.5 wt. % ^{235}U .
- c. Number of rods Per Thoria Rod Canister: ≤ 18
- d. Decay heat per Thoria Rod Canister: ≤ 115 Watts
- e. Post-irradiation fuel cooling time and average burnup per Thoria Rod Canister: A fuel post-irradiation cooling time ≥ 18 years and an average burnup $\leq 16,000$ MWD/MTIHM.
- f. Initial heavy metal weight: ≤ 27 kg/canister
- g. Fuel cladding O.D.: ≥ 0.412 inches
- h. Fuel cladding I.D.: ≤ 0.362 inches
- i. Fuel Pellet O.D.: ≤ 0.358 inches
- j. Active fuel length: ≤ 111 inches
- k. Canister weight: ≤ 550 lbs, including fuel

B. Quantity per MPC: Up to one (1) Dresden Unit 1 Thoria Rod Canister plus any combination of damaged fuel assemblies in damaged fuel containers and intact fuel assemblies, up to a total of 68.

C. Fuel assemblies with stainless steel channels are not authorized for loading in the MPC-68.

D. Dresden Unit 1 fuel assemblies (fuel assembly array/class 6x6A, 6x6B, 6x6C, or 8x8A) with one Antimony-Beryllium neutron source are authorized for loading in the MPC-68. The Antimony-Beryllium neutron source material shall be in a water rod location.

Table A.1 (Page 7 of 20)
Fuel Assembly Limits

III. MPC MODEL: MPC-68F

A. Allowable Contents

1. Uranium oxide, BWR intact fuel assemblies, with or without Zircaloy channels. Uranium oxide BWR intact fuel assemblies shall meet the criteria specified in Table A.3 for fuel assembly array/class 6x6A, 6x6C, 7x7A, or 8x8A and meet the following specifications:

- | | |
|--|--|
| a. Cladding type: | ZR |
| b. Maximum planar-average initial enrichment: | As specified in Table A.3 for the applicable fuel assembly array/class. |
| c. Initial maximum rod enrichment: | As specified in Table A.3 for the applicable fuel assembly array/class. |
| d. Post-irradiation cooling time, average burnup, and minimum enrichment per assembly: | An assembly post-irradiation cooling time ≥ 18 years, an average burnup $\leq 30,000$ MWD/MTU, and a minimum initial enrichment ≥ 1.8 wt% ^{235}U . |
| e. Fuel assembly length: | ≤ 176.2 inches (nominal design) |
| f. Fuel assembly width: | ≤ 5.85 inches (nominal design) |
| g. Fuel assembly weight | ≤ 400 lbs, including channels |

Table A.1 (Page 8 of 20)
Fuel Assembly Limits

III. MPC MODEL: MPC-68F (continued)

A. Allowable Contents (continued)

2. Uranium oxide, BWR damaged fuel assemblies, with or without Zircaloy channels, placed in damaged fuel containers. Uranium oxide BWR damaged fuel assemblies shall meet the criteria specified in Table A.3 for fuel assembly array/class 6x6A, 6x6C, 7x7A, or 8x8A, and meet the following specifications:

- | | |
|--|--|
| a. Cladding type: | ZR |
| b. Maximum planar-average initial enrichment: | As specified in Table A.3 for the applicable fuel assembly array/class. |
| c. Initial Maximum Rod Enrichment: | As specified in Table A.3 for the applicable fuel assembly array/class. |
| d. Post-irradiation cooling time, average burnup, and minimum initial enrichment per assembly: | An assembly post-irradiation cooling time ≥ 18 years, an average burnup $\leq 30,000$ MWD/MTU, and a minimum initial enrichment ≥ 1.8 wt% ^{235}U . |
| e. Fuel assembly length: | ≤ 135.0 inches (nominal design) |
| f. Fuel assembly width: | ≤ 4.70 inches (nominal design) |
| g. Fuel assembly weight | ≤ 550 lbs, including channels and damaged fuel container |

Table A.1 (Page 9 of 20)
Fuel Assembly Limits

III. MPC MODEL: MPC-68F (continued)

A. Allowable Contents (continued)

3. Uranium oxide, BWR fuel debris, with or without Zircaloy channels, placed in damaged fuel containers. The original fuel assemblies for the uranium oxide BWR fuel debris shall meet the criteria specified in Table A.3 for fuel assembly array/class 6x6A, 6x6C, 7x7A, or 8x8A, and meet the following specifications:
 - a. Cladding type: ZR
 - b. Maximum planar-average initial enrichment: As specified in Table A.3 for the applicable fuel assembly array/class.
 - c. Initial Maximum Rod Enrichment: As specified in Table A.3 for the applicable fuel assembly array/class.
 - d. Post-irradiation cooling time, average burnup, and minimum initial enrichment per assembly: An assembly post-irradiation cooling time ≥ 18 years, an average burnup $\leq 30,000$ MWD/MTU, and a minimum initial enrichment ≥ 1.8 wt% ^{235}U for the original fuel assembly.
 - e. Fuel assembly length: ≤ 135.0 inches (nominal design)
 - f. Fuel assembly width: ≤ 4.70 inches (nominal design)
 - g. Fuel assembly weight ≤ 550 lbs, including channels and damaged fuel container

Table A.1 (Page 10 of 20)
Fuel Assembly Limits

III. MPC MODEL: MPC-68F (continued)

A. Allowable Contents (continued)

4. Mixed oxide(MOX), BWR intact fuel assemblies, with or without Zircaloy channels. MOX BWR intact fuel assemblies shall meet the criteria specified in Table A.3 for fuel assembly array/class 6x6B and meet the following specifications:
 - a. Cladding type: ZR
 - b. Maximum planar-average initial enrichment: As specified in Table A.3 for fuel assembly array/class 6x6B.
 - c. Initial maximum rod enrichment: As specified in Table A.3 for fuel assembly array/class 6x6B.
 - d. Post-irradiation cooling time, average burnup, and minimum initial enrichment per assembly: An assembly post-irradiation cooling time ≥ 18 years, an average burnup $\leq 30,000$ MWD/MTIHM, and a minimum initial enrichment ≥ 1.8 wt% ^{235}U for the UO_2 rods.
 - e. Fuel assembly length: ≤ 135.0 inches (nominal design)
 - f. Fuel assembly width: ≤ 4.70 inches (nominal design)
 - g. Fuel assembly weight ≤ 400 lbs, including channels

Table A.1 (Page 11 of 20)
Fuel Assembly Limits

III. MPC MODEL: MPC-68F (continued)

A. Allowable Contents (continued)

5. Mixed oxide (MOX), BWR damaged fuel assemblies, with or without Zircaloy channels, placed in damaged fuel containers. MOX BWR intact fuel assemblies shall meet the criteria specified in Table A.3 for fuel assembly array/class 6x6B and meet the following specifications:

- | | |
|--|--|
| a. Cladding type: | ZR |
| b. Maximum planar-average initial enrichment: | As specified in Table A.3 for array/class 6x6B. |
| c. Initial Maximum Rod Enrichment: | As specified in Table A.3 for array/class 6x6B. |
| d. Post-irradiation cooling time, average burnup, and minimum initial enrichment per assembly: | An assembly post-irradiation cooling time ≥ 18 years, an average burnup $\leq 30,000$ MWD/MTIHM, and a minimum initial enrichment ≥ 1.8 wt% ^{235}U for the UO_2 rods. |
| e. Fuel assembly length: | ≤ 135.0 inches (nominal design) |
| f. Fuel assembly width: | ≤ 4.70 inches (nominal design) |
| g. Fuel assembly weight | ≤ 550 lbs, including channels and damaged fuel container |

Table A.1 (Page 12 of 20)
Fuel Assembly Limits

III. MPC MODEL: MPC-68F (continued)

A. Allowable Contents (continued)

6. Mixed oxide (MOX), BWR fuel debris, with or without Zircaloy channels, placed in damaged fuel containers. The original fuel assemblies for the MOX BWR fuel debris shall meet the criteria specified in Table A.3 for fuel assembly array/class 6x6B and meet the following specifications:

- | | |
|--|--|
| a. Cladding type: | ZR |
| b. Maximum planar-average initial enrichment: | As specified in Table A.3 for array/class 6x6B. |
| c. Initial Maximum Rod Enrichment: | As specified in Table A.3 for array/class 6x6B. |
| d. Post-irradiation cooling time, average burnup, and minimum initial enrichment per assembly: | An assembly post-irradiation cooling time ≥ 18 years, an average burnup $\leq 30,000$ MWD/MTIHM, and a minimum initial enrichment ≥ 1.8 wt% ^{235}U for the UO_2 rods in the original fuel assembly. |
| e. Fuel assembly length: | ≤ 135.0 inches (nominal design) |
| f. Fuel assembly width: | ≤ 4.70 inches (nominal design) |
| g. Fuel assembly weight | ≤ 550 lbs, including channels and damaged fuel container |

Table A.1(Page 13 of 20)
Fuel Assembly Limits

III. MPC MODEL: MPC-68F (continued)

A. Allowable Contents (continued)

7. Thoria rods (ThO_2 and UO_2) placed in Dresden Unit 1 Thoria Rod Canisters (as shown in Figure 1.2.11A the HI-STAR 100 System SAR, Revision 12) and meeting the following specifications:

- | | |
|---|--|
| a. Cladding Type: | ZR |
| b. Composition: | 98.2 wt.% ThO_2 , 1.8 wt. % UO_2 with an enrichment of 93.5 wt. % ^{235}U . |
| c. Number of rods per Thoria Rod Canister: | ≤ 18 |
| d. Decay heat per Thoria Rod Canister: | ≤ 115 Watts |
| e. Post-irradiation fuel cooling time and average burnup per Thoria Rod Canister: | An assembly post-irradiation cooling time ≥ 18 years and an average burnup $\leq 16,000$ MWD/MTIHM. |
| f. Initial heavy metal weight: | ≤ 27 kg/canister |
| g. Fuel cladding O.D.: | ≥ 0.412 inches |
| h. Fuel cladding I.D.: | ≤ 0.362 inches |
| i. Fuel pellet O.D.: | ≤ 0.358 inches |
| j. Active fuel length: | ≤ 111 inches |
| k. Canister weight: | ≤ 550 lbs, including fuel |

Table A.1(Page 14 of 20)
Fuel Assembly Limits

III. MPC MODEL: MPC-68F (continued)

B. Quantity per MPC:

Up to four (4) damaged fuel containers containing uranium oxide or MOX BWR fuel debris. The remaining MPC-68F fuel storage locations may be filled with array/class 6x6A, 6x6B, 6x6C, 7x7A, and 8x8A fuel assemblies of the following type, as applicable:

1. Uranium oxide BWR intact fuel assemblies;
2. MOX BWR intact fuel assemblies;
3. Uranium oxide BWR damaged fuel assemblies placed in damaged fuel containers;
4. MOX BWR damaged fuel assemblies placed in damaged fuel containers; or
5. Up to one (1) Dresden Unit 1 Thoria Rod Canister.

C. Fuel assemblies with stainless steel channels are not authorized for loading in the MPC-68F.

D. Dresden Unit 1 fuel assemblies (fuel assembly array/class 6x6A, 6x6B, 6x6C, or 8x8A) with one Antimony-Beryllium neutron source are authorized for loading in the MPC-68F. The Antimony-Beryllium neutron source material shall be in a water rod location.

Table A.1(Page 15 of 20)
Fuel Assembly Limits

IV. MPC MODEL: MPC-24E

A. Allowable Contents

1. Uranium oxide, PWR intact fuel assemblies listed in Table A.2 and meeting the following specifications:

- a. Cladding type: ZR or Stainless Steel (SS) as specified in Table A.2 for the applicable fuel assembly array/class
- b. Maximum Initial Enrichment: As specified in Table A.2 for the applicable fuel assembly array/class.
- c. Post-irradiation cooling time, average burnup, and minimum initial enrichment per assembly
 - i. ZR Clad: Except for Trojan plant fuel, an assembly post-irradiation cooling time, average burnup, decay heat, and minimum initial enrichment as specified in Table A.4 or A.5, as applicable.
 - ii. SS Clad: An assembly post-irradiation cooling time, average burnup, decay heat, and minimum initial enrichment as specified in Table A.6, as applicable.
 - iii. Trojan plant fuel: An assembly post-irradiation cooling time, average burnup, and minimum initial enrichment as specified in Table A.8.
 - iv. Trojan plant non-fuel hardware and neutron sources: Post-irradiation cooling time, and average burnup ss specified in Table A.9
- d. Decay heat per assembly
 - i. ZR Clad: Except for Trojan plant fuel, decay heat \leq 833 Watts. Trojan plant fuel decay heat: \leq 725 Watts
 - ii. SS Clad: \leq 488 Watts
- e. Fuel assembly length: \leq 176.8 inches (nominal design)
- f. Fuel assembly width: \leq 8.54 inches (nominal design)
- g. Fuel Assembly Weight: \leq 1,680 lbs, including non-fuel hardware and neutron sources

Table A.1(Page 16 of 20)
Fuel Assembly Limits

IV. MPC MODEL: MPC-24E

A. Allowable Contents (continued)

2. Trojan plant damaged fuel assemblies meeting the applicable criteria listed in Table A.2 and meeting the following specifications:

- a. Cladding type: ZR
- b. Maximum Initial Enrichment: 3.7% ²³⁵U
- c. Fuel assembly post-irradiation cooling time, average burnup, decay heat, and minimum initial enrichment per assembly: An assembly post-irradiation cooling time, average burnup, and initial enrichment as specified in Table A.11
- d. Fuel assembly length: ≤ 169.3 inches (nominal design)
- e. Fuel assembly width: ≤ 8.43 inches (nominal design)
- f. Fuel Assembly Weight: ≤ 1,680 lbs, including DFC or Failed Fuel Can

- B. Quantity per MPC: Up to 24 PWR intact fuel assemblies. For Trojan plant fuel only, up to four (4) damaged fuel assemblies may be stored in fuel storage locations 3, 6, 19, and/or 22. The remaining MPC-24E fuel storage locations may be filled with Trojan plant intact fuel assemblies.
- C. Trojan plant fuel must be transported in the custom-designed Trojan MPCs with the MPC spacer installed. Fuel from other plants is not permitted to be transported in the Trojan MPCs.
- D. Except for Trojan plant fuel, the fuel assemblies shall not contain non-fuel hardware. Trojan intact fuel assemblies containing non-fuel hardware may be transported in any fuel storage location.
- E. Trojan plant damaged fuel assemblies must be transported in a Trojan Failed Fuel Can or a Holtec damaged fuel container designed for Trojan plant fuel.
- F. One (1) Trojan plant Sb-Be and/or up to two (2) Cf neutron sources in a Trojan plant intact fuel assembly (one source per fuel assembly) may be transported in any one MPC. Each fuel assembly neutron source may be transported in any fuel storage location.
- G. Fuel debris is not authorized for transport in the MPC-24E.
- H. Trojan plant non-fuel hardware and neutron sources may not be transported in the same fuel storage location as a damaged fuel assembly.

Table A.1(Page 17 of 20)
Fuel Assembly Limits

V. MPC MODEL: MPC-24EF

A. Allowable Contents

1. Uranium oxide, PWR intact fuel assemblies listed in Table A.2 and meeting the following specifications:

- | | |
|---|--|
| a. Cladding type: | ZR or Stainless Steel (SS) as specified in Table A.2 for the applicable fuel assembly array/class |
| b. Maximum Initial Enrichment: | As specified in Table A.2 for the applicable fuel assembly array/class. |
| c. Post-irradiation cooling time, average burnup, and minimum initial enrichment per assembly | |
| i. Zr Clad: | Except for Trojan plant fuel, an assembly post-irradiation cooling time, average burnup, decay heat, and minimum initial enrichment as specified in Table A.4 or A.5, as applicable. |
| ii. SS Clad: | An assembly post-irradiation cooling time, average burnup, decay heat, and minimum initial enrichment as specified in Table A.6, as applicable. |
| iii. Trojan plant fuel | An assembly post-irradiation cooling time, average burnup, and minimum initial enrichment as specified in Table A.8. |
| iv. Trojan plant non-fuel hardware and neutron sources | Post-irradiation cooling time, and average burnup ss specified in Table A.9 |
| d. Decay heat per assembly | |
| i. ZR Clad: | Except for Trojan plant fuel, decay heat \leq 833 Watts.
Trojan plant fuel decay heat: \leq 725 Watts |
| ii. SS Clad: | \leq 488 Watts |
| e. Fuel assembly length: | \leq 176.8 inches (nominal design) |
| f. Fuel assembly width: | \leq 8.54 inches (nominal design) |
| g. Fuel Assembly Weight: | \leq 1,680 lbs, including non-fuel hardware and neutron sources |

Table A.1(Page 18 of 20)
Fuel Assembly Limits

V. MPC MODEL: MPC-24EF

A. Allowable Contents (continued)

2. Trojan plant damaged fuel assemblies meeting the applicable criteria listed in Table A.2 and meeting the following specifications:

- | | |
|---|--|
| a. Cladding type: | ZR |
| b. Maximum Initial Enrichment: | 3.7% ²³⁵ U |
| c. Fuel assembly post-irradiation cooling time, average burnup, decay heat, and minimum initial enrichment per assembly | An assembly post-irradiation cooling time, average burnup, and initial enrichment as specified in Table A.11 |
| d. Fuel assembly length: | ≤ 169.3 inches (nominal design) |
| e. Fuel assembly width: | ≤ 8.43 inches (nominal design) |
| f. Fuel Assembly Weight: | ≤ 1,680 lbs, including DFC or Failed Fuel Can |

Table A.1(Page 19 of 20)
Fuel Assembly Limits

V. MPC MODEL: MPC-24EF

A. Allowable Contents (continued)

3. Trojan Fuel Debris Process Can Capsules and/or Trojan plant fuel assemblies classified as fuel debris, for which the original fuel assemblies meet the applicable criteria listed in Table A.2 and meet the following specifications:

- | | |
|---|--|
| a. Cladding type: | ZR |
| b. Maximum Initial Enrichment: | 3.7% ²³⁵ U |
| c. Fuel debris post-irradiation cooling time, average burnup, decay heat, and minimum initial enrichment per assembly | An assembly post-irradiation cooling time, average burnup, and initial enrichment as specified in Table A.11 |
| d. Fuel assembly length: | ≤ 169.3 inches (nominal design) |
| e. Fuel assembly width: | ≤ 8.43 inches (nominal design) |
| f. Fuel Assembly Weight: | ≤ 1,680 lbs, including non-fuel hardware and DFC or Failed Fuel Can |

- B. Quantity per MPC: Up to 24 PWR intact fuel assemblies. For Trojan plant fuel only, up to four (4) damaged fuel assemblies, fuel assemblies classified as fuel debris, and/or Trojan Fuel Debris Process Can Capsules may be transported in fuel storage locations 3, 6, 19, and/or 22. The remaining MPC-24EF fuel storage locations may be filled with Trojan plant intact fuel assemblies.
- C. Trojan plant fuel must be transported in the custom-designed Trojan MPCs with the MPC spacer installed. Fuel from other plants is not permitted to be transported in the Trojan MPCs.
- D. Except for Trojan plant fuel, the fuel assemblies shall not contain non-fuel hardware or neutron sources. Trojan intact fuel assemblies containing non-fuel hardware may be transported in any fuel storage location.
- E. Trojan plant damaged fuel assemblies, fuel assemblies classified as fuel debris, and Fuel Debris Process Can Capsules must be transported in a Trojan Failed Fuel Can or a Holtec damaged fuel container designed for Trojan plant fuel.
- F. One (1) Sb-Be and/or two (2) Cf neutron sources may be transported. Each neutron source may be transported in any fuel storage location.
- G. Trojan plant non-fuel hardware and neutron sources may not be transported in the same fuel storage location as a damaged fuel assembly or fuel classified as fuel debris.

Table A.1(Page 20 of 20)
Fuel Assembly Limits

VI. MPC MODEL: MPC-32

A. Allowable Contents

1. Uranium oxide, PWR intact fuel assemblies in array/classes 15x15D, E, F, and H and 17x17A, B, and C listed in Table A.2 and meeting the following specifications:

a. Cladding type:	ZR
b. Maximum Initial Enrichment:	As specified in Table A.2 for the applicable fuel assembly array/class.
c. Post-irradiation cooling time, maximum average burnup, maximum and minimum initial enrichment per assembly	An assembly post-irradiation cooling time, average burnup, decay heat, and minimum initial enrichment as specified in Table A.10 or A.11, as applicable.
d. Minimum average burnup per assembly (Assembly Burnup shall be confirmed per Subsection 1.2.3.7.2 of the Application, which is hereby included by reference)	Calculated value as a function of initial enrichment. See Table A.12
e. Decay heat per assembly	≤ 625 Watts
f. Fuel assembly length:	≤ 176.8 inches (nominal design)
g. Fuel assembly width:	≤ 8.54 inches (nominal design)
h. Fuel Assembly Weight:	$\leq 1,680$ lbs
i. Operating parameters during irradiation of the assembly (Assembly operating parameters shall be determined per Subsection 1.2.3.7.1 of the Application, which is hereby included by reference)	/
Average in-core soluble boron concentration	≤ 1000 ppmb
Average core outlet water temperature	≤ 601 K for array/classes 15x15D, E, F and H ≤ 610 K for array/classes 17x17A, B and C
Average specific power	≤ 47.36 kW/kg-U for array/classes 15x15D, E, F and H ≤ 61.61 Kw/kg-U for array/classes 17x17A, B and C

B. Quantity per MPC: Up to 32 PWR intact fuel assemblies.

C. Fuel assemblies shall not contain non-fuel hardware.

D. Damaged fuel assemblies and fuel debris are not authorized for transport in the MPC-32.

E. Trojan plant fuel is not permitted to be transported in the MPC-32.

Appendix A-Certificate of Compliance No. 9261

Table A.2 (Page 1 of 4)
PWR FUEL ASSEMBLY CHARACTERISTICS (Note 1)

Fuel Assembly Array/Class	14x14A	14x14B	14x14C	14x14D	14x14E
Clad Material (Note 2)	ZR	ZR	ZR	SS	SS
Design Initial U (kg/assy.) (Note 3)	≤ 407	≤ 407	≤ 425	≤ 400	≤ 206
Initial Enrichment (MPC-24, 24E, and 24EF) (wt % ²³⁵ U)	≤ 4.6 (24) ≤ 5.0 (24E/EF)	≤ 4.6 (24) ≤ 5.0 (24E/EF)	≤ 4.6 (24) ≤ 5.0 (24E/EF)	≤ 4.0 (24) ≤ 5.0 (24E/EF)	≤ 5.0
Initial Enrichment (MPC-32) (wt % ²³⁵ U) (Note 5)	N/A	N/A	N/A	N/A	N/A
No. of Fuel Rod Locations	179	179	176	180	173
Fuel Clad O.D. (in.)	≥ 0.400	≥ 0.417	≥ 0.440	≥ 0.422	≥ 0.3415
Fuel Clad I.D. (in.)	≤ 0.3514	≤ 0.3734	≤ 0.3880	≤ 0.3890	≤ 0.3175
Fuel Pellet Dia. (in.)	≤ 0.3444	≤ 0.3659	≤ 0.3805	≤ 0.3835	≤ 0.3130
Fuel Rod Pitch (in.)	≤ 0.556	≤ 0.556	≤ 0.580	≤ 0.556	Note 6
Active Fuel Length (in.)	≤ 150	≤ 150	≤ 150	≤ 144	≤ 102
No. of Guide and/or Instrument Tubes	17	17	5 (Note 4)	16	0
Guide/Instrument Tube Thickness (in.)	≥ 0.017	≥ 0.017	≥ 0.038	≥ 0.0145	N/A

Table A.2 (Page 2 of 4)
 PWR FUEL ASSEMBLY CHARACTERISTICS (Note 1)

Fuel Assembly Array/Class	15x15A	15x15B	15x15C	15x15D	15x15E	15x15F
Clad Material (Note 2)	ZR	ZR	ZR	ZR	ZR	ZR
Design Initial U (kg/assy.) (Note 3)	≤ 464	≤ 464	≤ 464	≤ 475	≤ 475	≤ 475
Initial Enrichment (MPC-24, 24E, and 24EF) (wt % ²³⁵ U)	≤ 4.1 (24) ≤ 4.5 (24E/EF)					
Initial Enrichment (MPC-32) (wt % ²³⁵ U) (Note 5)	N/A	N/A	N/A	≤ 5.0 (Note 5)	≤ 5.0 (Note 5)	≤ 5.0 (Note 5)
No. of Fuel Rod Locations	204	204	204	208	208	208
Fuel Clad O.D. (in.)	≥ 0.418	≥ 0.420	≥ 0.417	≥ 0.430	≥ 0.428	≥ 0.428
Fuel Clad I.D. (in.)	≤ 0.3660	≤ 0.3736	≤ 0.3640	≤ 0.3800	≤ 0.3790	≤ 0.3820
Fuel Pellet Dia. (in.)	≤ 0.3580	≤ 0.3671	≤ 0.3570	≤ 0.3735	≤ 0.3707	≤ 0.3742
Fuel Rod Pitch (in.)	≤ 0.550	≤ 0.563	≤ 0.563	≤ 0.568	≤ 0.568	≤ 0.568
Active Fuel Length (in.)	≤ 150	≤ 150	≤ 150	≤ 150	≤ 150	≤ 150
No. of Guide and/or Instrument Tubes	21	21	21	17	17	17
Guide/Instrument Tube Thickness (in.)	≥ 0.0165	≥ 0.015	≥ 0.0165	≥ 0.0150	≥ 0.0140	≥ 0.0140

Table A.2 (Page 3 of 4)
PWR FUEL ASSEMBLY CHARACTERISTICS (Note 1)

Fuel Assembly Array/ Class	15x15G	15x15H	16x16A	17x17A	17x17B	17x17C
Clad Material (Note 2)	SS	ZR	ZR	ZR	ZR	ZR
Design Initial U (kg/assy.) (Note 3)	≤ 420	≤ 475	≤ 443	≤ 467	≤ 467	≤ 474
Initial Enrichment (MPC-24, 24E, and 24EF) (wt % ²³⁵ U)	≤ 4.0 (24) ≤ 4.5 (24E/EF)	≤ 3.8 (24) ≤ 4.2 (24E/EF)	≤ 4.6 (24) ≤ 5.0 (24E/EF)	≤ 4.0 (24) ≤ 4.4 (24E/EF)	≤ 4.0 (24) ≤ 4.4 (24E/EF) (Note 7)	≤ 4.0 (24) ≤ 4.4 (24E/EF)
Initial Enrichment (MPC-32) (wt % ²³⁵ U) (Note 5)	N/A	≤5.0 (Note 5)	N/A	≤5.0 (Note 5)	≤5.0 (Note 5)	≤5.0 (Note 5)
No. of Fuel Rod Locations	204	208	236	264	264	264
Fuel Clad O.D. (in.)	≥ 0.422	≥ 0.414	≥ 0.382	≥ 0.360	≥ 0.372	≥ 0.377
Fuel Clad I.D. (in.)	≤ 0.3890	≤ 0.3700	≤ 0.3320	≤ 0.3150	≤ 0.3310	≤ 0.3330
Fuel Pellet Dia. (in.)	≤ 0.3825	≤ 0.3622	≤ 0.3255	≤ 0.3088	≤ 0.3232	≤ 0.3252
Fuel Rod Pitch (in.)	≤ 0.563	≤ 0.568	≤ 0.506	≤ 0.496	≤ 0.496	≤ 0.502
Active Fuel Length (in.)	≤ 144	≤ 150	≤ 150	≤ 150	≤ 150	≤ 150
No. of Guide and/or Instrument Tubes	21	17	5 (Note 4)	25	25	25
Guide/Instrument Tube Thickness (in.)	≥ 0.0145	≥ 0.0140	≥ 0.0400	≥ 0.016	≥ 0.014	≥ 0.020

Table A.2 (Page 4 of 4)
PWR FUEL ASSEMBLY CHARACTERISTICS (Note 1)

Notes:

1. All dimensions are design nominal values. Maximum and minimum dimensions are specified to bound variations in design nominal values among fuel assemblies within a given array/class.
2. ZR. Designates cladding material made of Zirconium or Zirconium alloys.
3. Design initial uranium weight is the nominal uranium weight specified for each assembly by the fuel manufacturer or reactor user. For each PWR fuel assembly, the total uranium weight limit specified in this table may be increased up to 2.0 percent for comparison with users' fuel records to account for manufacturer tolerances.
4. Each guide tube replaces four fuel rods.
5. *Minimum burnup and maximum initial enrichment as specified in Table A.12.*
6. This fuel assembly array/class includes only the Indian Point Unit 1 fuel assembly. This fuel assembly has two pitches in different sectors of the assembly. These pitches are 0.441 inches and 0.453 inches.
7. Trojan plant-specific fuel is governed by the limits specified for array/class 17x17B and will be transported in the custom-designed Trojan MPC-24E/EF canisters. The Trojan MPC-24E/EF design is authorized to store only Trojan plant fuel with a maximum initial enrichment of 3.7 wt.% ²³⁵U.

Table A.3 (Page 1 of 5)
 BWR FUEL ASSEMBLY CHARACTERISTICS (Note 1)

Fuel Assembly Array/Class	6x6A	6x6B	6x6C	7x7A	7x7B	8x8A
Clad Material (Note 2)	ZR	ZR	ZR	ZR	ZR	ZR
Design Initial U (kg/assy.) (Note 3)	≤ 110	≤ 110	≤ 110	≤ 100	≤ 195	≤ 120
Maximum planar-average initial enrichment (wt.% ²³⁵ U)	≤ 2.7	≤ 2.7 for the UO ₂ rods. See Note 4 for MOX rods	≤ 2.7	≤ 2.7	≤ 4.2	≤ 2.7
Initial Maximum Rod Enrichment (wt.% ²³⁵ U)	≤ 4.0	≤ 4.0	≤ 4.0	≤ 5.5	≤ 5.0	≤ 4.0
No. of Fuel Rod Locations	35 or 36	35 or 36 (up to 9 MOX rods)	36	49	49	63 or 64
Fuel Clad O.D. (in.)	≥ 0.5550	≥ 0.5625	≥ 0.5630	≥ 0.4860	≥ 0.5630	≥ 0.4120
Fuel Clad I.D. (in.)	≤ 0.5105	≤ 0.4945	≤ 0.4990	≤ 0.4204	≤ 0.4990	≤ 0.3620
Fuel Pellet Dia. (in.)	≤ 0.4980	≤ 0.4820	≤ 0.4880	≤ 0.4110	≤ 0.4910	≤ 0.3580
Fuel Rod Pitch (in.)	≤ 0.710	≤ 0.710	≤ 0.740	≤ 0.631	≤ 0.738	≤ 0.523
Active Fuel Length (in.)	≤ 120	≤ 120	≤ 77.5	≤ 80	≤ 150	≤ 120
No. of Water Rods (Note 11)	1 or 0	1 or 0	0	0	0	1 or 0
Water Rod Thickness (in.)	≥ 0	≥ 0	N/A	N/A	N/A	≥ 0
Channel Thickness (in.)	≤ 0.060	≤ 0.060	≤ 0.060	≤ 0.060	≤ 0.120	≤ 0.100

Table A.3 (Page 2 of 5)
BWR FUEL ASSEMBLY CHARACTERISTICS (Note 1)

Fuel Assembly Array/Class	8x8B	8x8C	8x8D	8x8E	8x8F	9x9A
Clad Material (Note 2)	ZR	ZR	ZR	ZR	ZR	ZR
Design Initial U (kg/assy.) (Note 3)	≤ 185	≤ 185	≤ 185	≤ 185	≤ 185	≤ 177
Maximum planar-average initial enrichment (wt.% ²³⁵ U)	≤ 4.2	≤ 4.2	≤ 4.2	≤ 4.2	≤ 4.0	≤ 4.2
Initial Maximum Rod Enrichment (wt.% ²³⁵ U)	≤ 5.0	≤ 5.0	≤ 5.0	≤ 5.0	≤ 5.0	≤ 5.0
No. of Fuel Rod Locations	63 or 64	62	60 or 61	59	64	74/66 (Note 5)
Fuel Clad O.D. (in.)	≥ 0.4840	≥ 0.4830	≥ 0.4830	≥ 0.4930	≥ 0.4576	≥ 0.4400
Fuel Clad I.D. (in.)	≤ 0.4295	≤ 0.4250	≤ 0.4230	≤ 0.4250	≤ 0.3996	≤ 0.3840
Fuel Pellet Dia. (in.)	≤ 0.4195	≤ 0.4160	≤ 0.4140	≤ 0.4160	≤ 0.3913	≤ 0.3760
Fuel Rod Pitch (in.)	≤ 0.642	≤ 0.641	≤ 0.640	≤ 0.640	≤ 0.609	≤ 0.566
Design Active Fuel Length (in.)	≤ 150	≤ 150	≤ 150	≤ 150	≤ 150	≤ 150
No. of Water Rods (Note 11)	1 or 0	2	1 - 4 (Note 7)	5	N/A (Note 12)	2
Water Rod Thickness (in.)	≥ 0.034	> 0.00	> 0.00	≥ 0.034	≥ 0.0315	> 0.00
Channel Thickness (in.)	≤ 0.120	≤ 0.120	≤ 0.120	≤ 0.100	≤ 0.055	≤ 0.120

Table A.3 (Page 3 of 5)
 BWR FUEL ASSEMBLY CHARACTERISTICS (Note 1)

Fuel Assembly Array/Class	9x9B	9x9C	9x9D	9x9E (Note 13)	9x9F (Note 13)	9x9G
Clad Material (Note 2)	ZR	ZR	ZR	ZR	ZR	ZR
Design Initial U (kg/assy.) (Note 3)	≤ 177	≤ 177	≤ 177	≤ 177	≤ 177	≤ 177
Maximum planar-average initial enrichment (wt.% ²³⁵ U)	≤ 4.2	≤ 4.2	≤ 4.2	≤ 4.0	≤ 4.0	≤ 4.2
Initial Maximum Rod Enrichment (wt.% ²³⁵ U)	≤ 5.0	≤ 5.0	≤ 5.0	≤ 5.0	≤ 5.0	≤ 5.0
No. of Fuel Rod Locations	72	80	79	76	76	72
Fuel Clad O.D. (in.)	≥ 0.4330	≥ 0.4230	≥ 0.4240	≥ 0.4170	≥ 0.4430	≥ 0.4240
Fuel Clad I.D. (in.)	≤ 0.3810	≤ 0.3640	≤ 0.3640	≤ 0.3640	≤ 0.3860	≤ 0.3640
Fuel Pellet Dia. (in.)	≤ 0.3740	≤ 0.3565	≤ 0.3565	≤ 0.3530	≤ 0.3745	≤ 0.3565
Fuel Rod Pitch (in.)	≤ 0.572	≤ 0.572	≤ 0.572	≤ 0.572	≤ 0.572	≤ 0.572
Design Active Fuel Length (in.)	≤ 150	≤ 150	≤ 150	≤ 150	≤ 150	≤ 150
No. of Water Rods (Note 11)	1 (Note 6)	1	2	5	5	1 (Note 6)
Water Rod Thickness (in.)	> 0.00	≥ 0.020	≥ 0.0300	≥ 0.0120	≥ 0.0120	≥ 0.0320
Channel Thickness (in.)	≤ 0.120	≤ 0.100	≤ 0.100	≤ 0.120	≤ 0.120	≤ 0.120

Table A.3 (Page 4 of 5)
BWR FUEL ASSEMBLY CHARACTERISTICS (Note 1)

Fuel Assembly Array/Class	10x10A	10x10B	10x10C	10x10D	10x10E
Clad Material (Note 2)	ZR	ZR	ZR	SS	SS
Design Initial U (kg/assy.) (Note 3)	≤ 186	≤ 186	≤ 186	≤ 125	≤ 125
Maximum planar-average initial enrichment (wt.% ²³⁵ U)	≤ 4.2	≤ 4.2	≤ 4.2	≤ 4.0	≤ 4.0
Initial Maximum Rod Enrichment (wt.% ²³⁵ U)	≤ 5.0	≤ 5.0	≤ 5.0	≤ 5.0	≤ 5
No. of Fuel Rod Locations	92/78 (Note 8)	91/83 (Note 9)	96	100	96
Fuel Clad O.D. (in.)	≥ 0.4040	≥ 0.3957	≥ 0.3780	≥ 0.3960	≥ 0.3940
Fuel Clad I.D. (in.)	≤ 0.3520	≤ 0.3480	≤ 0.3294	≤ 0.3560	≤ 0.3500
Fuel Pellet Dia. (in.)	≤ 0.3455	≤ 0.3420	≤ 0.3224	≤ 0.3500	≤ 0.3430
Fuel Rod Pitch (in.)	≤ 0.510	≤ 0.510	≤ 0.488	≤ 0.565	≤ 0.557
Design Active Fuel Length (in.)	≤ 150	≤ 150	≤ 150	≤ 83	≤ 83
No. of Water Rods (Note 11)	2	1 (Note 6)	5 (Note 10)	0	4
Water Rod Thickness (in.)	≥ 0.0300	> 0.00	≥ 0.031	N/A	≥ 0.022
Channel Thickness (in.)	≤ 0.120	≤ 0.120	≤ 0.055	≤ 0.080	≤ 0.080

Table A.3 (Page 5 of 5)
BWR FUEL CHARACTERISTICS (Note 1)

Notes:

1. All dimensions are design nominal values. Maximum and minimum dimensions are specified to bound variations in design nominal values among fuel assemblies within a given array/class.
2. ZR designates cladding material made from Zirconium or Zirconium alloys.
3. Design initial uranium weight is the uranium weight specified for each assembly by the fuel manufacturer or reactor user. For each BWR fuel assembly, the total uranium weight limit specified in this table may be increased up to 1.5% for comparison with users' fuel records to account for manufacturer's tolerances.
4. ≤ 0.635 wt. % ^{235}U and ≤ 1.578 wt. % total fissile plutonium (^{239}Pu and ^{241}Pu), (wt. % of total fuel weight, i.e., UO_2 plus PuO_2).
5. This assembly class contains 74 total fuel rods; 66 full length rods and 8 partial length rods.
6. Square, replacing nine fuel rods.
7. Variable
8. This assembly class contains 92 total fuel rods; 78 full length rods and 14 partial length rods.
9. This assembly class contains 91 total fuel rods, 83 full length rods and 8 partial length rods.
10. One diamond-shaped water rod replacing the four center fuel rods and four rectangular water rods dividing the assembly into four quadrants.
11. These rods may be sealed at both ends and contain Zr material in lieu of water.
12. This assembly is known as "QUAD+." It has four rectangular water cross segments dividing the assembly into four quadrants.
13. For the SPC 9x9-5 fuel assembly, each fuel rod must meet either the 9x9E or 9x9F set of limits for clad O.D., clad I.D., and pellet diameter.

Table A.4

FUEL ASSEMBLY COOLING, AVERAGE BURNUP, AND MINIMUM ENRICHMENT
MPC-24/24E/24EF PWR FUEL WITH ZIRCALOY CLAD AND
WITH NON-ZIRCALOY IN-CORE GRID SPACERS

Post-irradiation Cooling Time (years)	Assembly Burnup (MWD/MTU)	Assembly Minimum Enrichment (wt. % U-235)
≥ 9	≤ 24,500	≥ 2.3
≥ 11	≤ 29,500	≥ 2.6
≥ 13	≤ 34,500	≥ 2.9
≥ 15	≤ 39,500	≥ 3.2
≥ 18	≤ 44,500	≥ 3.4

Table A.5

FUEL ASSEMBLY COOLING, AVERAGE BURNUP, AND MINIMUM ENRICHMENT
MPC-24/24E/24EF PWR FUEL WITH ZIRCALOY CLAD AND
WITH ZIRCALOY IN-CORE GRID SPACERS

Post-irradiation Cooling Time (years)	Assembly Burnup (MWD/MTU)	Assembly Minimum Enrichment (wt. % U-235)
≥ 6	≤ 24,500	≥ 2.3
≥ 7	≤ 29,500	≥ 2.6
≥ 9	≤ 34,500	≥ 2.9
≥ 12	≤ 39,500	≥ 3.2
≥ 15	≤ 44,500	≥ 3.4

Table A.6

FUEL ASSEMBLY COOLING, AVERAGE BURNUP, AND MINIMUM ENRICHMENT
MPC-24/24E/24EF PWR FUEL WITH STAINLESS STEEL CLAD

Post-irradiation Cooling Time (years)	Assembly Burnup (MWD/MTU)	Assembly Minimum Enrichment (wt. % U-235)
≥ 19	≤ 30,000	≥ 3.1
≥ 24	≤ 40,000	≥ 3.1

Table A.7

FUEL ASSEMBLY COOLING, AVERAGE BURNUP, AND MINIMUM ENRICHMENT
MPC-68

Post-irradiation Cooling Time (years)	Assembly Burnup (MWD/MTU)	Assembly Minimum Enrichment (wt. % U-235)
≥ 8	≤ 24,500	≥ 2.1
≥ 9	≤ 29,500	≥ 2.4
≥ 11	≤ 34,500	≥ 2.6
≥ 14	≤ 39,500	≥ 2.9
≥ 19	≤ 44,500	≥ 3.0

Table A.8

TROJAN PLANT FUEL ASSEMBLY COOLING, AVERAGE BURNUP, AND MINIMUM ENRICHMENT LIMITS

Post-irradiation Cooling Time (years)	Assembly Burnup (MWD/MTU)	Assembly Minimum Enrichment (wt. % ²³⁵ U)
≥ 16	≤ 42,000	≥ 3.09
≥ 16	≤ 37,500	≥ 2.6
≥ 16	≤ 30,000	≥ 2.1

Table A.9

TROJAN PLANT NON-FUEL HARDWARE AND NEUTRON SOURCE COOLING AND BURNUP LIMITS

Type of Hardware or Neutron Source	Burnup (MWD/MTU)	Post-irradiation Cooling Time (Years)
BPRAs	≤ 15,998	≥ 24
TPDs	≤ 118,674	≥ 11
RCCAs	≤ 125,515	≥ 9
Cf neutron source	≤ 15,998	≥ 24
Sb-Be neutron source with 4 source rods, 16 burnable poison rods, and 4 thimble plug rods	≤ 45,361	≥ 19
Sb-Be neutron source with 4 source rods, 20 thimble plug rods	≤ 88,547	≥ 9

Table A.10

FUEL ASSEMBLY COOLING, AVERAGE BURNUP, AND MINIMUM ENRICHMENT
MPC-32 PWR FUEL WITH ZIRCALOY CLAD AND
WITH NON-ZIRCALOY IN-CORE GRID SPACERS

Post-irradiation Cooling Time (years)	Assembly Burnup (MWD/MTU)	Assembly Minimum Enrichment (wt. % U-235)
≥ 12	≤ 24,500	≥ 2.3
≥ 14	≤ 29,500	≥ 2.6
≥ 16	≤ 34,500	≥ 2.9
≥ 19	≤ 39,500	≥ 3.2
≥ 20	≤ 42,500	≥ 3.4

Table A.11

FUEL ASSEMBLY COOLING, AVERAGE BURNUP, AND MINIMUM ENRICHMENT
MPC-32 PWR FUEL WITH ZIRCALOY CLAD AND
WITH ZIRCALOY IN-CORE GRID SPACERS

Post-irradiation Cooling Time (years)	Assembly Burnup (MWD/MTU)	Assembly Minimum Enrichment (wt. % U-235)
≥ 8	≤ 24,500	≥ 2.3
≥ 9	≤ 29,500	≥ 2.6
≥ 12	≤ 34,500	≥ 2.9
≥ 14	≤ 39,500	≥ 3.2
≥ 19	≤ 44,500	≥ 3.4

Table A.12

FUEL ASSEMBLY MAXIMUM ENRICHMENT AND MINIMUM BURNUP REQUIREMENTS FOR TRANSPORTATION IN MPC-32

FUEL ASSEMBLY ARRAY/CLASS	Configuration (Note 2)	Maximum Enrichment (wt% ²³⁵ U)	MINIMUM BURNUP (B) AS A FUNCTION OF INITIAL ENRICHMENT (E) (Note 1) (GWD/MTU)
15X15D, E, F, H	A	4.79	$B = +(1.6733) * E^3 -(18.72) * E^2 + (80.5967) * E -88.3$
	B	4.54	$B = +(2.175) * E^3 -(23.355) * E^2 + (94.77) * E -99.95$
	C	4.64	$B = +(1.9517) * E^3 -(21.45) * E^2 + (89.1783) * E -94.6$
	D	4.59	$B = +(1.93) * E^3 -(21.095) * E^2 + (87.785) * E -93.06$
17x17A, B, C	A	4.70	$B = +(1.08) * E^3 -(12.25) * E^2 + (60.13) * E -70.86$
	B	4.31	$B = +(1.1) * E^3 -(11.56) * E^2 + (56.6) * E -62.59$
	C	4.45	$B = +(1.36) * E^3 -(14.83) * E^2 + (67.27) * E -72.93$
	D	4.38	$B = +(1.4917) * E^3 -(16.26) * E^2 + (72.9883) * E -79.7$

NOTES:

1. E = Initial enrichment, i.e., for 4.05 wt.%, E = 4.05.
2. See Table A.13.
3. Fuel Assemblies must be cooled 5 years or more.

Table A.13

LOADING CONFIGURATIONS FOR THE MPC-32

CONFIGURATION	ASSEMBLY SPECIFICATIONS
A	<ul style="list-style-type: none"> • <i>Assemblies that have not been located in any cycle under a control rod bank that was permitted to be inserted during full power operation (per plant operating procedures); or</i> • <i>Assemblies that have been located under a control rod bank that was permitted to be inserted during full power operation (per plant operating procedures), but where it can be demonstrated, based on operating records, that the insertion never exceeded 8 inches from the top of the active length during full power operation.</i>
B	<ul style="list-style-type: none"> • <i>Of the 32 assemblies in a basket, up to 8 assemblies can be from core locations where they were located under a control rod bank, that was permitted to be inserted more than 8 inches during full power operation. There is no limit on the duration (in terms of burnup) under this bank.</i> • <i>The remaining assemblies in the basket must satisfy the same conditions as specified for configuration A.</i>
C	<ul style="list-style-type: none"> • <i>Of the 32 assemblies in a basket, up to 8 assemblies can be from core locations where they were located under a control rod bank, that was permitted to be inserted more than 8 inches during full power operation. Location under such a control rod bank is limited to 20 GWd/mtU of the assembly.</i> • <i>The remaining assemblies in the basket must satisfy the same conditions as specified for configuration A.</i>
D	<ul style="list-style-type: none"> • <i>Of the 32 assemblies in a basket, up to 8 assemblies can be from core locations where they were located under a control rod bank, that was permitted to be inserted more than 8 inches during full power operation. Location under such a control rod bank is limited to 30 GWd/mtU of the assembly.</i> • <i>The remaining assemblies in the basket must satisfy the same conditions as specified for configuration A.</i>

REFERENCE:

Holtec International Report No. HI-951251, *Safety Analysis Report for the Holtec International Storage, Transport, And Repository Cask System (HI-STAR 100 Cask System)*, Revision 12 dated TBD.