OPTIONAL FORM NO. 10

## UNITED STATES GOVERNMENT

TO :Lyall E. Johnson, Chief Licensing Branch DATE: MAY 1 8 1960

FROM : Edson G. Case, Acting Chief Hazards Evaluation Branch

SUBJECT: MALLINCKRODT NUCLEAR CORP.

We have reviewed the Mallinckrodt application dated March 3, 1960, requesting approval of shipping procedures for uranium compounds having a maximum enrichment of 10%.

The shipping container is a 5-gallon pail braced with angle iron supports inside a 55-gallon "shorty" drum. During previous reviews, dating back to December 16, 1958, we have been unable to approve previous applications for this type container because of spacing inadequacy and because the inner container would not be substantially filled with material in the higher enrichment range. Mallinckrodt has now overcome these objections. Additional edge-to-edge spacing is provided by a steel skirt welded around each 55-gallon drum, to provide an overall diameter of 27". Stacking of the 55-gallon drums will be prevented by welding an angle-iron pyramid to the top of each drum. The higher enriched material, for which the volume is much less than that of a 5-gallon pail, will be packaged in a metal can or polyethylene bottle which is packed in the 5-gallon pail with vermiculite.

The shipping container is now appropriate for mass limited quantities (Table II, TID-7019) and spacing is such that the solid angle criterion for a planar array of 24 drums is satisfied. The applicant will obtain certification from the carrier that no other SNM will be combined enroute with the Mallinckrodt shipment.

We recommend approval of the March 3 application.

Lyall E. Johnson, Chief Licensing Branch

1 - - 3 - 3

Project 3-3 Docket 70-36

Edson G. Case, Acting Chief Hazards Evaluation Branch

MALLINCERODT MUCLEAR CORP.


We have reviewed the Mallinckrodt application dated March 3, 1960, requesting approval of shipping procedures for uranium compounds having a maximum enrichment of 10%.

The shipping container is a 5-gallon pail braced with angle iron supports inside a 55-gallon "shorty" drum. During previous reviews, dating back to December 16, 1958, we have been unable to approve previous applications for this type container because of spacing inadiquacy and because the inner container would not be substantially filled with material in the higher earlchment range. Hellinckrodt has now evercome these objections. Additional edge-to-edge spacing is provided by a steel skirt welded around each 55-gallon drums, to provide an everall dismeter of 27". Stacking of the 55-gallon drums will be prevented by welding an angle-iron pyremid to the top of each drum. The higher enriched material, for which the volume is much less than that of a 5-gallon pail, will be packaged in a metal can or polyethyleme bottle which is packed in the 5-gallon pail with vermiculite.

The shipping container is now appropriate for mass limited quantities (Table II, TID-7019) and spacing is such that the source angle exiterion for a planar array of 26 draws is satisfied. The applicant will obtain cortification from the service that no other SMM will be combined encoute with the Mellinchrodt shipment.

We recommend approval of the March 3 application.

Form AEC-318 (Rev. 9-53)		B. S. GOVERNMENT PRINTING OFFICE 16-62761-3						
DATE ►	5/18/60	<u>5 M</u>	8/60				<u> </u>	 
•	CDLuke:alp		ase		• •••	Albert Kinderegi Albert Kinderegi		······
OFITICE >	HEB:DL&R	HEB						



## EXER CAMPAGES A MARK NUCLEAR MATERIAL DRAFT

A STATE AND A STATE AND A STATE AND A STATE OF A STATE AND AND A STATE 7100-805-23-264-141.(25) ON OR ABOUT (Doile of Delivery)-

THE FOLLOWING NUCLEAR MATERIAL

DESCRIPTION AND NOTES

6 Mg WY, carieled to 4% U-235 content

te 28 kg 27 mariabet to 81 U-235 content

Deliney, Chief, Weelvar Materials

tes Librosing Pres Birs of Lon

MALLS mes cans of above approx. 3.02 kg

Hebdauerters Division Director

1. .....

.....


4th Quarter FY 50

CONCURRENCE TLUGBON OF

CERTIFIED I HEREBY CERTIFY THAT THE ABOVE QUALITITY WILL NOT BY STO MATERIAL APPROVED FOR THIS DIVERTOR TOTAL APPROVED FOR THIS DIVERTOR AND A THE APPROVED FOR THIS DIVERTICAL APPROVED FOR THIS DIVERE

Director Division of Marless Moter division games a

DIVISION OF HUCLEAR MATERIALS MAILAGEN



erla

.67 V

and the second second

NUCLEAR MATERIAL DRAFT

TO THE REAL OF THE REAL OF ADD ADD THE TOENTING AND HO

en landeren bestere Gerge

THE FOLLOWING NUCLEAR MATERIAL

DESCRIPTION AND NOTES

ME 35.4 kg WV. surfaced to 4% U-235 content

my, Chief, Welver Heterials

... Liensing Bras Bir. of LAR

Hendquerters Division Director

1. A. S. A.

the state of the s

The ser test of above appres. 3.02 kg

G NUCLEAR MATERIAL,

ofes -

THOP-BUC-13-DCA-161(25) ON OR ABOUT (Dote of Delivery)

Ath Onertes FY 50

· . ·

CONCURRENCE: MC MK.Kellegy rsame

Director Division of Nuclear Motor 3's Concigance i MN

DIVISION OF MUCLEAR MATERIALS MANAGENT