TITLE:		Number:		Effective Date:
Cs-137 CDC.80	00/CDC.700	I4	-OP-60	TBD
OVER ENCAP	SULATION			
PRI:		Page:		Superceded Date:
Steve Laflin		1 of 7		original
PRI Signature and Date:	Document Control Signatu	ire and Date:	Quality Assurar	nce Signature and Date:
DRAFT				

# print name signature initials print name signature initials print name signature initials print name signature initials print name signature initials

### 1.0 PURPOSE

To outline the procedure for over encapsulation of CDC.800 and CDC.700 cesium-137 source capsules and to document source measurement, leak test, and other information required on each sealed source certificate.

# 2.0 POTENTIAL HAZARDS

The hazards associated with the implementation of this procedure include:

- Potential exposure to radioactive material.
- Industrial hazards associated with the inspection and handling of transportation packages such as rigging, crane operations, forklift operations, pinch points, manual lifting, strains, trips, slips and falls.

### 3.0 APPLICABILITY AND LIMITATIONS

This procedure addresses over encapsulation of the Models CDC.800 and CDC.700 Cs-137 sealed sources in the INIS-SF-CS-1J and INIS-SF-CS-2J capsules. Only sealed sources meeting the criteria established in Section 7.4 are eligible for over encapsulation.

# 4.0 **DEFINITIONS**

Sealed Source – Any source that is of a design which has been successfully tested against the criteria of ANSI/HPS N43.6 or ISO 2919-1999 and is listed in the National Sealed Source and Device Registry.

Special Form – A solid form or capsule design which has been successfully tested against the criteria established in 49 CFR § 173.469 or equivalent foreign regulations.

TITLE:	Number:	Effective Date:
Cs-137 CDC.800/CDC.700	I4-OP-60	TBD
OVER ENCAPSULATION		
	Page:	Superceded Date:
DRAFT	2 of 7	original

CS-13/ CDC.800/CDC.700	14-OF-00	188
OVER ENCAPSULATION		
DRAFT	Page:	Superceded Date:
DRAFI	2 of 7	original
5.0 RESPONSIBILITIES		
<b>5.1</b> I <sup>3</sup> Quality		
5.1.1 Verify this procedure is the most current revi	ision.	
Ensures INIS source capsules and caps are w	vithin specification.	
<b>5.1.3</b> Reviews completed procedure and releases so	ources for shipment.	
5.2 I <sup>3</sup> Radiation Safety Officer		
5.2.1 Authorizes distribution of completed sources	i.	
5.3 I <sup>3</sup> Technician		
Performs steps outlined in this procedure to i welding of capsules and decontaminating as		ıles, assaying capsul
Equipment and Materials		
Qualified Model CDC.800 and CDC.700 Cs-137	sealed source(s).	
6.2 INIS-SF-CS-1J and or INIS-SF-CS-2J componer	nts per I <sup>3</sup> drawing, DV	VG.
6.3 Q-tip smears		
Leak testing apparatus		
6.5 Certificate of Analysis Template		
7.0 PROCEDURE		
7.1 Operation Supervisor (OP) verify that technician Testing) of Sealed Sources are qualified and cert	_	ling and N.D.T. (Lea
OP Signature:		Date
Name of Welder:		
Name of N.D.T. Inspector:		
7.2 Acquire customer loading request information ar		
Customer Name:	P.O. Numbe	r:
Number of INIS-SF-CS-1J:		

Number of INIS-SF-CS-2J: \_\_\_\_\_ Activity per source: \_\_\_\_\_

TITLE:	Number:	Effective Date:
Cs-137 CDC.800/CDC.700	I4-OP-60	TBD
OVER ENCAPSULATION		
DDAET	Page:	Superceded Date:
DRAFT	3 of 7	original

7.3 List CDC.800/CDC.700 Cs-137 source(s) to be re-encapsulated

Item	Manufacturer	Model/Serial Number	SS&D Number	Current Activity (Ci)
1				
2				
3				
4				
5				
Use add	litional sheets as nec	essary		-

- 7.4 Verify the CDC.800 and CDC.700 Cs-137 source(s) comply with the following:
- 7.4.1 The source is constructed from a Series 300 Stainless Steel to ensure material compatibility with the INIS Type 304 (304L, 316, 316L) S.S. outer capsule. This information should be included in the Sealed Source Safety Evaluation and/or Special Form CoC document
- 7.4.2 The source successfully passes either the wipe (smear) test or dry wipe test in accordance with ANSI/HPS N43.6-1997 Annex A Paragraphs A.2.1.1 or A.2.1.2 respectively. Attach survey records to this procedure. (Wipe test must be accomplished within 6 months of over encapsulation).
- 7.4.3 The source successfully passes either a vacuum bubble test, hot liquid bubble test or the helium pressurization bubble test in accordance with ANSI/HPS N43.6-1997 Annex A Paragraph A.2.2.1, A.2.2.2 or A.2.2.3 respectively. Attach completed leak test sheets. (Leak check must be accomplished within 6 months of over encapsulation).
- **7.4.4** The source passes a visual inspection indicating it is free of defects. (A magnification device may be used to perform this check.)
- **7.4.5** The source's outside dimensions are compatible the International Isotopes Inc. INIS-SF-CS-1J and or INIS-SF-CS-2J, verified via go-no-go fit test.
- **7.4.6** Initial the appropriate columns in the table below. Note Item numbers correspond to the Item numbers from Section 7.3.

	7.4	<b>l.</b> 1	7.4	1.2	7.4	1.3	7.4	1.4	7.4	1.5
Item	PASS	FAIL	PASS	FAIL	PASS	FAIL	PASS	FAIL	PASS	FAIL
1										
2										
3										
4										
5										

Use additional sheets as necessary

TITLE:	Number:	Effective Date:
Cs-137 CDC.800/CDC.700	I4-OP-60	TBD
OVER ENCAPSULATION		
DD A CT	Page:	Superceded Date:
DRAFT	4 of 7	original

7.5 Determine INIS Source model number(s) and serial number(s). Record item from Step 7.4 that will be over encapsulated in each INIS source. NOTE, serial number is in the format of MMYY-## where -## is the next sequential number of source model number built for the current month.

INIS Model Number	Serial Number	CDC.800/CDC.700 from Step 7.4	Total Activity (Ci)			
Use additional sheets as necessary						

- **7.6** Coordinate with I<sup>3</sup> Quality Assurance Manager to procure necessary INIS source capsules and lids.
- 7.7 Coordinate with I<sup>3</sup> Quality Assurance Manager to laser mark each source capsule with the isotope, Cs-137, INIS Model and Serial Number.

NOTE: All work with Cs-137 sources is to be performed in the clean hot cell

- 7.8 Clean the Cs-137 source capsule(s) to be over encapsulated by dipping in a 50% 50% isopropyl alcohol de-mineralized water bath and pat dry.
- **7.9** Prepare INIS capsules for welding and transfer into the Cs-137 source welding hot cell.
- **7.10** Prepare INIS Cs-137 sources in accordance with the table from Step 7.5
- **7.11** Set up welder in accordance with the weld log.
- **7.12** Weld INIS Cs-137 sources in accordance with the table from Step 7.5.

INIS Model Number	Serial Number	Qualified Welder Signature	Weld Date
Use additional sheets as	s necessary		

TITLE:	Number:	Effective Date:
Cs-137 CDC.800/CDC.700	I4-OP-60	TBD
OVER ENCAPSULATION		
DD A CT	Page:	Superceded Date:
DRAFT	5 of 7	original

**7.13** Perform a leak check on the completed INIS Cs-137 source in accordance with Paragraph A.2.2.1, A.2.2.2 of A.2.2.3 from ANSI/HPS N43.6-1997. Document leak test results on Source Certificate for each source.

INIS Model / Serial No.	Test Performed	Results (Pass/Fail)	NDT Signature	Leak Test Date				
Use additional sheets as no	Use additional sheets as necessary							

**7.14** Perform a wet Q-Tip smear of outer sealed source. Count the smear. When source smear is less than 1000 dpm, place in clean container (quart can). Document survey results in space provided below, and complete Sealed Source Certificate.

Instrument	Serial No.	Cal. Due	Efficiency		Background Count Time t <sub>s</sub> (min)	Sample Count time t <sub>b</sub> (cpm)	MDA (dpm)
***************************************		MDA =	= {3 +3 29[R <sub>b</sub>	$t_s(1+(t_s/t_b))^{1/2}]$	/{Efficiency x	t <sub>o</sub> }	

INIS Model and Serial No.	Gross Count Rate (cpm)	Net Count Rate (cpm)	Wipe Results (dpm)	Technician initial	Date
Use additional sheets as neces	ssary			1	

TITLE:	Number:	Effective Date:
Cs-137 CDC.800/CDC.700	I4-OP-60	TBD
OVER ENCAPSULATION		
DDAET	Page:	Superceded Date:
DRAFT	6 of 7	original

- 7.15 If sealed source is not to be removed from hot cell following smear test, then identify outside of clean container and log on Isotope Storage board all pertinent information.
- **7.16** Forward this procedure and any accompanying paperwork or certificates to Q.A. for approval.
- 8.0 REFERENCES
- **8.1** ANSI/HPS N43.6-1997, Sealed Radioactive Sources-Classifications
- **8.2** ISO 9978 Radiation protection Sealed radioactive sources -Leakage test methods.
- **8.3** INIS Drawing, DWG No. INIS-SF-CS-040606
- **8.4** Weld Standard
- **8.5** N.D.T. Examiner Standard
- 9.0 ATTACHMENTS
- **9.1** Sealed Source Certificate

TITLE:	Number:	Effective Date:
Cs-137 CDC.800/CDC.700	I4-OP-60	TBD
OVER ENCAPSULATION		
DDAET	Page:	Superceded Date:
DRAFT	7 of 7	original

Attachment 9.1



# SEALED SOURCE CALIBRATION CONTAMINATION AND LEAK TEST CERTIFICATE OF CS-137 SOURCE FOR

CUSTOMER:		ACTIVITY		
I <sup>3</sup> MODEL NUMBER: <u>INIS-SF-CS-</u>	Ci			
SERIAL NUMBER: MMYY-##		TBq		
REFERENCE DATE: N. M/DD/Y YY  Each source is may ufactured by conting encountry within innoverse.			ım in diameter	
	Physical Data			
Isotope: Cs-137 Half-life: 11018.3 days λ: 6.29E-05 d	Thysical Bala	<b>0</b> ,	Yield 35.10%	
Type Removable Contamination Leakage Test	Method Wet Swab Vacuum Bubble	Results < 1000 dj No Leakage O	pm	
NDT Class II Technician:	g:	_		
NDT Class II Verifier:	Signature	Date		
	Signature	Date		
Quality Assurance:	Signature	Date		
I Manufacturer: ASHCROFT Model/Serial Number:: 251009AWL02L/1	eak Test Gauge Description		4-Mar-06 Sep-06	