

**RELEASE TO PUBLISH UNCLASSIFIED NRC CONTRACTOR
SPEECHES, PAPERS, AND JOURNAL ARTICLES**
(Please type or print)

1. **TITLE** (State in full as it appears on the speech, paper, or journal article)
Evolution of Fluid Chemistry Inside A Waste Package Due to Carbon-Steel and Simulated High-Level Waste Glass Corrosion

2. **AUTHOR(s)**
Vijay Jain and Xihua He

3. **NAME OF CONFERENCE, LOCATION, AND DATE(s)**
Materials Science & Technology 2006 Conference and Exhibition
Cincinnati, Ohio October 15-19, 2006

4. **NAME OF PUBLICATION**

5. NAME AND ADDRESS OF THE PUBLISHER	TELEPHONE NUMBER OF THE PUBLISHER
---	-----------------------------------

6. CONTRACTOR NAME AND COMPLETE MAILING ADDRESS (Include ZIP code) Center for Nuclear Waste Regulatory Analyses Southwest Research Institute 6220 Culebra Rd. San Antonio, TX 78238	TELEPHONE NUMBER OF THE CONTRACTOR 210/522-5304
--	--

**7. CERTIFICATION
(ANSWER ALL QUESTIONS)**

YES	NO	
	X	A. COPYRIGHTED MATERIAL - Does this speech, paper, or journal article contain copyrighted material? If yes, attach a letter of release from the source that holds the copyright.

YES	NO	
	X	B. PATENT CLEARANCE - Does this speech, paper, or journal article require patent clearance? If yes, the NRC Patent Counsel must signify clearance by signing below.

NRC PATENT COUNSEL (Type or Print Name)	SIGNATURE	DATE
---	-----------	------

YES	NO	
X		C. REFERENCE AVAILABILITY - Is all material referenced in this speech, paper, or journal article available to the public either through a public library, the Government Printing Office, the National Technical Information Service, or the NRC Public Document Room? If no, list below the specific availability of each referenced document.

SPECIFIC AVAILABILITY

YES	NO	
	X	D. METRIC UNIT CONVERSION - Does this speech, paper, or journal article contain measurement and weight values? If yes, all must be converted to the International System of Units, followed by the English units in brackets, pursuant to the NRC Policy Statement implementing the Omnibus Trade and Competitiveness Act of 1988, Executive Order 12770, July 25, 1991.

8. AUTHORIZATION

The signatures of the NRC project manager and the contractor official certify that the NRC contractor speech, paper, or journal article is authorized by NRC, that it has undergone appropriate peer review for technical content and for material that might compromise commercial proprietary rights, and that it does not contain classified, sensitive unclassified, or nonpublic information. (NRC MD 3.9, Part II(A)(1)(d))

A. CONTRACTOR AUTHORIZING OFFICIAL (Type or print name) Gordon W. Wittmeyer, Assistant Director	SIGNATURE 	DATE 2/13/06
---	---	-----------------

B. NRC RESPONSIBLE PROJECT MANAGER (Type or print name)	OFFICE/DIVISION	MAIL STOP
--	-----------------	-----------

TELEPHONE NUMBER	E-MAIL I.D.	Did you place the speech, paper, or journal article in the PDR? YES _____ NO _____
------------------	-------------	---

SIGNATURE	DATE
-----------	------

EVOLUTION OF FLUID CHEMISTRY INSIDE A WASTE PACKAGE DUE TO CARBON STEEL AND SIMULATED HIGH-LEVEL WASTE GLASS CORROSION

Vijay Jain and Xihua He
Center for Nuclear Waste Regulatory Analyses
Southwest Research Institute®
6220 Culebra Road
San Antonio, Texas 78238

ABSTRACT

A co-disposal waste package (WP) designed for the potential high-level waste (HLW) repository at Yucca Mountain (YM) may contain a mix of 304L stainless steel (SS) canisters with HLW glass and U.S. Department of Energy (DOE)-owned spent nuclear fuel canisters. These canisters are placed inside a WP with carbon steel inserts that provide support to individual canisters.

Radionuclide release from the WP is a complex process that depends upon the chemical composition and flux of groundwater contacting the wasteforms; the dissolution rate of HLW glass and spent nuclear fuel; the corrosion rates of WP components made of Alloy 22, 304L, 316L SS, and carbon steel; the solubility of radionuclides; and the retention of radionuclides in secondary phases. Typically, the corrosion rate for carbon steel is significantly higher than for stainless steel or Alloy 22 and has a significant effect on the chemical evolution of the in-package solutions.

In this study, a series of bench-scale experiments were conducted to monitor the evolution of the chemical composition, pH, and redox potential of the fluid inside the WP for corroding carbon steel samples for expected groundwater compositions. The pH of the solution is an important parameter that controls the dissolution of wasteforms and determines the speciation of radionuclides between solid and aqueous phases. Results indicate that the corrosion processes increased the pH of the solution from near-neutral to alkaline (pH > 9), accompanied by the formation of iron-bearing corrosion product precipitates. The addition of simulated HLW glass to the corroding carbon steel solution caused a further increase in pH. These results are in contrast to the DOE proposed model abstraction for in-package chemistry for YM in which the pH is expected to remain near neutral after initially acidic conditions (pH around 4).

This abstract was prepared to document work performed by the Center for Nuclear Waste Regulatory Analyses (CNWRA) and its contractors for the U.S. Nuclear Regulatory Commission (NRC) under Contract No. NRC-02-02-012. The activities reported here were performed on behalf of the NRC Office of Nuclear Material Safety and Safeguards, Division of High-Level Waste Repository Safety. This abstract is an independent product of CNWRA and does not necessarily reflect the view or regulatory position of NRC.