

**RELEASE TO PUBLISH UNCLASSIFIED NRC CONTRACTOR
SPEECHES, PAPERS, AND JOURNAL ARTICLES**
(Please type or print)

1. TITLE (State in full as it appears on the speech, paper, or journal article)
The Role of Engineered Barriers at the Potential Yucca Mountain Repository

2. AUTHOR(s)
V. Jain

3. NAME OF CONFERENCE, LOCATION, AND DATE(s)
Materials Science & Technology 2006 Conference and Exhibition
Cincinnati, Ohio October 15-19, 2006

4. NAME OF PUBLICATION

5. NAME AND ADDRESS OF THE PUBLISHER	TELEPHONE NUMBER OF THE PUBLISHER
--------------------------------------	-----------------------------------

6. CONTRACTOR NAME AND COMPLETE MAILING ADDRESS (include ZIP code) Center for Nuclear Waste Regulatory Analyses Southwest Research Institute 6220 Culebra Rd. San Antonio, TX 78238	TELEPHONE NUMBER OF THE CONTRACTOR 210/522-5185
---	--

**7. CERTIFICATION
(ANSWER ALL QUESTIONS)**

YES	NO	A. COPYRIGHTED MATERIAL - Does this speech, paper, or journal article contain copyrighted material? If yes, attach a letter of release from the source that holds the copyright.
-----	----	--

X	X	B. PATENT CLEARANCE - Does this speech, paper, or journal article require patent clearance? If yes, the NRC Patent Counsel must signify clearance by signing below.
---	---	---

NRC PATENT COUNSEL (Type or Print Name)	SIGNATURE	DATE
---	-----------	------

X	X	C. REFERENCE AVAILABILITY - Is all material referenced in this speech, paper, or journal article available to the public either through a public library, the Government Printing Office, the National Technical Information Service, or the NRC Public Document Room? If no, list below the specific availability of each referenced document.
---	---	---

SPECIFIC AVAILABILITY

X	X	D. METRIC UNIT CONVERSION - Does this speech, paper, or journal article contain measurement and weight values? If yes, all must be converted to the International System of Units, followed by the English units in brackets, pursuant to the NRC Policy Statement implementing the Omnibus Trade and Competitiveness Act of 1988, Executive Order 12770, July 25, 1991.
---	---	--

8. AUTHORIZATION

The signatures of the NRC project manager and the contractor official certify that the NRC contractor speech, paper, or journal article is authorized by NRC, that it has undergone appropriate peer review for technical content and for material that might compromise commercial proprietary rights, and that it does not contain classified, sensitive unclassified, or nonpublic information. (NRC MD 3.9, Part II(A)(1)(d))

A. CONTRACTOR AUTHORIZING OFFICIAL (Type or print name) Sitakanta Mohanty	SIGNATURE <i>Sitakanta Mohanty</i>	DATE 2/22/2006
--	---------------------------------------	-------------------

B. NRC RESPONSIBLE PROJECT MANAGER (Type or print name)	OFFICE/DIVISION	MAIL STOP
---	-----------------	-----------

TELEPHONE NUMBER	E-MAIL I.D.	Did you place the speech, paper, or journal article in the PDR? YES _____ NO _____
------------------	-------------	---

SIGNATURE	DATE
-----------	------

Materials Science & Technology 2006 Conference and Exhibition, October 15–19, 2006,
Cincinnati, Ohio

The Role of Engineered Barriers at the Potential Yucca Mountain Repository

Vijay Jain
Center for Nuclear Waste Regulatory Analyses
Southwest Research Institute®
6220 Culebra Road
San Antonio, Texas
e-mail: vjain@swri.org

Abstract

The U.S. Nuclear Regulatory Commission (NRC) will be reviewing a potential license application for the high-level radioactive waste repository to be located at Yucca Mountain. The U.S. Department of Energy is considering the disposal of 70,000 MTHM (metric tons of heavy metals) of high-level radioactive waste in the form of spent nuclear fuel and vitrified waste at the potential repository. The potential repository is expected to provide protection to the public and environment through natural and engineered barriers. The engineered barriers may be constructed approximately 300 m [1,000 ft] below the land surface of Yucca Mountain and may enclose the wasteform in a corrosion resistant Alloy 22 waste package. The waste packages may be placed on a pallet in a drift and covered with a titanium drip shield. The release of radionuclides from the wasteform depends on the quantity and chemistry of water that enters through the breached waste packages. The breach could occur because of initial defects, corrosion, or stress corrosion cracking during the performance period. Because of the long time scales and process uncertainties, a probabilistic approach has been adopted to evaluate the performance of engineered barriers. The presentation will discuss how the performance of engineered barriers, including wasteforms, is incorporated in the probabilistic performance assessment.

Disclaimer

This abstract is an independent product of the Center for Nuclear Waste Regulatory Analyses and does not necessarily reflect the view or regulatory position of NRC.