

<p><b>NRC FORM 313</b> (8-1999) 10 CFR 30, 32, 33 34, 35, 36, 39 and 40</p> <p style="text-align: center;"><b>U. S. NUCLEAR REGULATORY COMMISSION</b></p> <p style="text-align: center; font-size: 1.2em;"><b>APPLICATION FOR MATERIAL LICENSE</b></p>	<p>APPROVED BY OMB: NO. 3150-0120</p> <p style="text-align: right;">EXPIRES 08/31/2002</p> <p><small>Estimated burden per response to comply with this mandatory information collection request: 7.4 hours. Submittal of the application is necessary to determine that the applicant is qualified and that adequate procedures exist to protect the public health and safety. Send comments regarding burden estimate to the Records Management Branch (T-8 E6), U.S. Nuclear Regulatory Commission, Washington, DC 20555-0001, or by internet e-mail to bjs1@nrc.gov and to the Desk Officer, Office of Information and Regulatory Affairs, NE08-10202, (3150-0120), Office of Management and Budget, Washington, DC 20503. If a means used to impose an information collection does not display a currently valid OMB control number, NRC may not conduct or sponsor, and a person is not required to respond to, the information collection.</small></p>				
<p><b>INSTRUCTIONS: SEE THE APPROPRIATE LICENSE APPLICATION GUIDE FOR DETAILED INSTRUCTIONS FOR COMPLETING APPLICATION. SEND TWO COPIES OF THE ENTIRE COMPLETED APPLICATION TO THE NRC OFFICE SPECIFIED BELOW.</b></p>					
<p><b>APPLICATION FOR DISTRIBUTION OF EXEMPT PRODUCTS FILE APPLICATIONS WITH:</b></p> <p>DIVISION OF INDUSTRIAL AND MEDICAL NUCLEAR SAFETY OFFICE OF NUCLEAR MATERIALS SAFETY AND SAFEGUARDS U. S. NUCLEAR REGULATORY COMMISSION WASHINGTON, DC 20555-0001</p> <p><b>ALL OTHER PERSONS FILE APPLICATIONS AS FOLLOWS:</b></p> <p><b>IF YOU ARE LOCATED IN:</b></p> <p>CONNECTICUT, DELAWARE, DISTRICT OF COLUMBIA, MAINE, MARYLAND, MASSACHUSETTS, NEW HAMPSHIRE, NEW JERSEY, NEW YORK, PENNSYLVANIA, RHODE ISLAND, OR VERMONT, SEND APPLICATIONS TO:</p> <p>LICENSING ASSISTANT SECTION NUCLEAR MATERIALS SAFETY BRANCH U. S. NUCLEAR REGULATORY COMMISSION, REGION I 475 ALLENDALE ROAD KING OF PRUSSIA, PA 19406-1415</p> <p>ALABAMA, FLORIDA, GEORGIA, KENTUCKY, MISSISSIPPI, NORTH CAROLINA, PUERTO RICO, SOUTH CAROLINA, TENNESSEE, VIRGINIA, VIRGIN ISLANDS, OR WEST VIRGINIA, SEND APPLICATIONS TO:</p> <p>SAM NUNN ATLANTA FEDERAL CENTER U. S. NUCLEAR REGULATORY COMMISSION, REGION II 61 FORSYTH STREET, S.W. SUITE 23785 ATLANTA, GEORGIA 30303-8931</p>	<p><b>IF YOU ARE LOCATED IN:</b></p> <p>ILLINOIS, INDIANA, IOWA, MICHIGAN, MINNESOTA, MISSOURI, OHIO, OR WISCONSIN, SEND APPLICATIONS TO:</p> <p>MATERIALS LICENSING SECTION U. S. NUCLEAR REGULATORY COMMISSION, REGION III 801 WARRENVILLE RD. LISLE, IL 60532-4351</p> <p>ALASKA, ARIZONA, ARKANSAS, CALIFORNIA, COLORADO, HAWAII, IDAHO, KANSAS, LOUISIANA, MONTANA, NEBRASKA, NEVADA, NEW MEXICO, NORTH DAKOTA, OKLAHOMA, OREGON, PACIFIC TRUST TERRITORIES, SOUTH DAKOTA, TEXAS, UTAH, WASHINGTON, OR WYOMING, SEND APPLICATIONS TO:</p> <p>NUCLEAR MATERIALS LICENSING SECTION U. S. NUCLEAR REGULATORY COMMISSION, REGION IV 611 RYAN PLAZA DRIVE, SUITE 400 ARLINGTON, TX 78011-8064</p>				
<p><b>PERSONS LOCATED IN AGREEMENT STATES SEND APPLICATIONS TO THE U.S. NUCLEAR REGULATORY COMMISSION ONLY IF THEY WISH TO POSSESS AND USE LICENSED MATERIAL IN STATES SUBJECT TO U.S. NUCLEAR REGULATORY COMMISSION JURISDICTIONS.</b></p>					
<p>1 THIS IS AN APPLICATION FOR (Check appropriate item)</p> <p><input type="checkbox"/> A NEW LICENSE</p> <p><input type="checkbox"/> B AMENDMENT TO LICENSE NUMBER</p> <p><input checked="" type="checkbox"/> C RENEWAL OF LICENSE NUMBER <u>13-20167-01</u></p>	<p>2 NAME AND MAILING ADDRESS OF APPLICANT (include Zip code)</p> <p><u>SOIL TESTING INC.</u> <u>8308 YOUNG RD</u> <u>FT. WAYNE, IN, 46835</u></p>				
<p>3 ADDRESS(ES) WHERE LICENSED MATERIAL WILL BE USED OR POSSESSED</p> <p><u>8308 YOUNG RD</u> <u>FT. WAYNE, IN, 46835</u> } <u>STORAGE</u> <u>VARIOUS JOB SITES</u></p>	<p>4 NAME OF PERSON TO BE CONTACTED ABOUT THIS APPLICATION</p> <p><u>KEVIN D. SNYDER</u></p> <p>TELEPHONE NUMBER <u>(216) 241-3105</u></p>				
<p>SUBMIT ITEMS 5 THROUGH 11 ON 8-1/2 X 11" PAPER. THE TYPE AND SCOPE OF INFORMATION TO BE PROVIDED IS DESCRIBED IN THE LICENSE APPLICATION GUIDE.</p>					
<p>5 RADIOACTIVE MATERIAL</p> <p>a. Element and mass number, b. chemical and/or physical form, and c. maximum amount which will be possessed at any one time</p>	<p>6. PURPOSE(S) FOR WHICH LICENSED MATERIAL WILL BE USED</p>				
<p>7. INDIVIDUAL(S) RESPONSIBLE FOR RADIATION SAFETY PROGRAM AND THEIR TRAINING EXPERIENCE</p>	<p>8. TRAINING FOR INDIVIDUALS WORKING IN OR FREQUENTING RESTRICTED AREAS</p>				
<p>9. FACILITIES AND EQUIPMENT</p>	<p>10. RADIATION SAFETY PROGRAM</p>				
<p>11. WASTE MANAGEMENT</p>	<p>12. LICENSEE FEES (See 10 CFR 170 and Section 170.31)</p> <p>FEE CATEGORY: _____ AMOUNT ENCLOSED: <u>PAID</u></p>				
<p>13. CERTIFICATION. (Must be completed by applicant) THE APPLICANT UNDERSTANDS THAT ALL STATEMENTS AND REPRESENTATIONS MADE IN THIS APPLICATION ARE BINDING UPON THE APPLICANT.</p> <p>THE APPLICANT AND ANY OFFICIAL EXECUTING THIS CERTIFICATION ON BEHALF OF THE APPLICANT, NAMED IN ITEM 2, CERTIFY THAT THIS APPLICATION IS PREPARED IN CONFORMITY WITH TITLE 10, CODE OF FEDERAL REGULATIONS, PARTS 30, 32, 33, 34, 35, 36, 39 AND 40, AND THAT ALL INFORMATION CONTAINED HEREIN IS TRUE AND CORRECT TO THE BEST OF THEIR KNOWLEDGE AND BELIEF.</p> <p>WARNING: 18 U.S.C. SECTION 1001 ACT OF JUNE 25, 1948 82 STAT. 749 MAKES IT A CRIMINAL OFFENSE TO MAKE A WILLFULLY FALSE STATEMENT OR REPRESENTATION TO ANY DEPARTMENT OR AGENCY OF THE UNITED STATES AS TO ANY MATTER WITHIN ITS JURISDICTION.</p>					
<p>CERTIFYING OFFICER - TYPED/PRINTED NAME AND TITLE</p> <p><u>KEVIN D. SNYDER PRESIDENT/RSD</u></p>					
<p>SIGNATURE</p> <p><u>[Signature]</u></p>					
<p>DATE</p> <p><u>7-27-07</u></p>					
<p><b>FOR NRC USE ONLY</b></p>					
TYPE OF FEE	FEE LOG	FEE CATEGORY	AMOUNT RECEIVED	CHECK NUMBER	COMMENTS
			\$		
APPROVED BY				DATE	

RECEIVED AUG 01 2007

NUREG - 1556, Vol. 1, Rev. 1

**ITEMS 5 AND 6: MATERIALS TO BE POSSESSED AND PROPOSED USES**

Yes	No	Radioisotope	Manufacturer or Distributor Model No.	Quantity	Use As Listed on SSD Certificate	Specify Other Uses Not Listed on SSD Certificate
X		Cesium-137	Sealed source manufacturer or distributor and model number: <u>TROXLER</u> <u>3430</u>  Device manufacturer or distributor and model number: <u>TROXLER</u> <u>3430</u>	Not to exceed either the maximum activity per source or maximum activity per device as specified in Sealed Source and Device Registration Certificate	Yes <input checked="" type="checkbox"/> Specific description of the gauge use: <u>COMPACTOR</u> <u>TESTING</u>	<input checked="" type="checkbox"/> Not applicable  <input type="checkbox"/> Uses are:  (Submit safety analysis supporting safe use)
X		Americium-241	Sealed source manufacturer or distributor and model number: <u>TROXLER</u> <u>3430</u>  Device manufacturer or distributor and model number: <u>TROXLER</u> <u>3430</u>	Not to exceed either the maximum activity per source or maximum activity per device as specified in Sealed Source and Device Registration Certificate	Yes <input checked="" type="checkbox"/> Specific description of the gauge use: <u>COMPACTOR</u> <u>TESTING</u>	<input checked="" type="checkbox"/> Not applicable  <input type="checkbox"/> Uses are:  (Submit safety analysis supporting safe use)

APPENDIX B

Yes	No	Radioisotope	Manufacturer or Distributor Model No.	Quantity	Use As Listed on SSD Certificate	Specify Other Uses Not Listed on SSD Certificate
	x	Californium-252	Sealed source manufacturer or distributor and model number: _____ Device manufacturer or distributor and model number: _____	Not to exceed either the maximum activity per source or maximum activity per device as specified in Sealed Source and Device Registration Certificate	Yes <input type="checkbox"/> Specific description of the gauge use: _____ _____ _____ _____ _____	<input type="checkbox"/> Not applicable _____ <input type="checkbox"/> Uses are: _____ (Submit safety analysis supporting safe use)
	x	Other Isotope (Specify):	Sealed source manufacturer or distributor and model number: _____ Device manufacturer or distributor and model number: _____	Not to exceed either the maximum activity per source or maximum activity per device as specified in Sealed Source and Device Registration Certificate	Yes <input type="checkbox"/> Specific description of the gauge use: _____	<input type="checkbox"/> Not applicable _____ <input type="checkbox"/> Uses are: _____ (Submit safety analysis supporting safe use)
<i>Financial Assurance Required and Evidence of Financial Assurance Provided</i>						

**ITEMS 7 THROUGH 11: TRAINING AND EXPERIENCE, FACILITIES AND EQUIPMENT, RADIATION SAFETY PROGRAM, AND WASTE DISPOSAL**

Item No. And Title	Suggested Response	Yes	Alternative Procedures Attached
<p>7. <b>INDIVIDUAL(S) RESPONSIBLE FOR RADIATION SAFETY PROGRAM AND THEIR TRAINING AND EXPERIENCE – RADIATION SAFETY OFFICER</b></p> <p>Name: <u>KEVIN D. Snyder</u></p>	<p>Before obtaining licensed materials, the proposed RSO will have successfully completed one of the training courses described in Criteria in the section entitled "Individual(s) Responsible for Radiation Safety Program and Their Training and Experience – Radiation Safety Officer" in NUREG-1556, Vol. 1, Rev. 1, dated November 2001.</p>	<input checked="" type="checkbox"/>	<input type="checkbox"/>
<p>8. <b>TRAINING FOR INDIVIDUALS WORKING IN OR FREQUENTING RESTRICTED AREAS</b></p>	<p>Before using licensed materials, authorized users will have successfully completed one of the training course described in Criteria in the section entitled "Training for Individuals Working In or Frequenting Restricted Areas" in NUREG-1556, Vol. 1, Rev 1, dated November 2001.</p>	<input checked="" type="checkbox"/>	<input type="checkbox"/>
<p>9. <b>FACILITIES AND EQUIPMENT</b></p>	<p>No information needs to be submitted in response to this item; key issues are addressed under "Radiation Safety Program – Public Dose" and "Radiation Safety Program – Operating and Emergency Procedures."</p>	<p><b>Separate Item 9 Response</b> <b>Need Not Be Submitted With Application</b></p>	
<p>10. <b>RADIATION SAFETY PROGRAM – AUDIT PROGRAM</b></p>	<p>The applicant is <i>not</i> required to, and should not, submit its audit program to NRC for review during the licensing phase.</p>	<p><b>Need Not Be Submitted With Application</b></p>	
<p>10. <b>RADIATION SAFETY PROGRAM – TERMINATION OF ACTIVITIES</b></p>	<p>The applicant is <i>not</i> required to submit a response to the termination of activities section during the initial application. However, when the license expires when the licensee ceases operation, NRC Form 314 must be submitted.</p>	<p><b>Need Not Be Submitted With Application</b></p>	
<p>10. <b>RADIATION SAFETY PROGRAM – SURVEY INSTRUMENTS</b></p>	<p>We will either possess and use, or have access to and use, a radiation survey meter that meets the Criteria in the section entitled "Radiation Safety Program – Instruments" in NUREG-1556, Vol. 1, Rev. 1, dated November 2001.</p>	<input checked="" type="checkbox"/>	<input type="checkbox"/>

APPENDIX B

Item No. And Title	Suggested Response	Yes	Alternative Procedures Attached
10. RADIATION SAFETY PROGRAM – MATERIAL RECEIPT AND ACCOUNTABILITY	Physical inventories will be conducted at intervals not to exceed 6 months, to account for all sealed sources and devices received and possessed under the license.	<input checked="" type="checkbox"/>	<input type="checkbox"/>
10. RADIATION SAFETY PROGRAM – OCCUPATIONAL DOSIMETRY	Either we will maintain, for inspection by NRC, documentation demonstrating that unmonitored individuals are not likely to receive a radiation dose in excess of 10 percent of the allowable limits in 10 CFR Part 20, or we will provide dosimetry processed and evaluated by an NVLAP-approved processor that is exchanged at a frequency recommended by the processor.	<input checked="" type="checkbox"/>	<input type="checkbox"/>
10. RADIATION SAFETY PROGRAM – PUBLIC DOSE	The applicant is <i>not</i> required to submit a response to the public dose section during the licensing phase. This matter will be examined during an inspection.	<b>Need Not Be Submitted With Application</b>	
10. RADIATION SAFETY PROGRAM – OPERATING AND EMERGENCY PROCEDURES	<p>We will implement and maintain the operating and emergency procedures in Appendix H of NUREG-1556, Vol. 1, Rev. 1, dated November 2001, and provide copies of these procedures to all gauge users and at each job site.</p> <p style="text-align: center;"><b>OR</b></p> <p>Operating and emergency procedures will be developed, implemented, and maintained and will meet the criteria in the section entitled “Radiation Safety Program – Operating and Emergency Procedures” in NUREG-1556, Vol. 1, Rev. 1, dated November 2001.</p>	<input type="checkbox"/>          <input checked="" type="checkbox"/>	<input type="checkbox"/>
10. RADIATION SAFETY PROGRAM – LEAK TEST	Leak tests will be performed at intervals approved by NRC or an Agreement State and specified in the Sealed Source and Device Registration Sheet. Leak tests will be performed by an organization authorized by NRC or an Agreement State to provide leak testing services for other licensees or using a leak test kit supplied by an organization authorized by NRC or an Agreement State to provide leak test kits to other licensees and according to the kit supplier’s instructions.	<input checked="" type="checkbox"/>	<input type="checkbox"/>          <b>The information in Appendix J supporting a request to perform leak testing and sample analysis is attached.</b>



## **Appendix H**

# **Operating, Emergency, and Security Procedures**

## Operating Procedures

- If personnel dosimetry is provided:
  - Always wear your assigned National Voluntary Laboratory Accreditation Program (NVAP) approved thermoluminescent dosimeter (TLD), optical stimulated dosimeter (OSL), or film badge when using the portable gauge;
  - Never wear another person's TLD, OSL, or film badge;
  - Never store your TLD, OSL, or film badge near the portable gauge.
- Before removing the portable gauge from its place of storage, ensure that, where applicable, each portable gauge sealed source is in the fully shielded position and that in portable gauges with a movable rod containing a sealed source, the source rod is locked (e.g., keyed lock, padlock, mechanical control) in the shielded position. Place the portable gauge in the transport case and lock the case.
- Use a minimum of two independent physical controls that form tangible barriers to secure portable gauges from unauthorized removal whenever the portable gauges are not under the licensee's control and constant surveillance (i.e., in storage). Guidance regarding this requirement is discussed below in the "Security Procedures" section of this Appendix.
- Sign out the portable gauge in a log book (that remains at the storage location) including the date(s) of use, name(s) of the authorized users who will be responsible for the portable gauge, and the temporary job site(s) where the portable gauge will be used.
- Block and brace the portable gauge to prevent movement during transport and lock the portable gauge in or to the vehicle. Follow all applicable Department of Transportation (DOT) requirements when transporting the portable gauge.
- Use the portable gauge according to the manufacturer's instructions and recommendations.
- Do not touch the unshielded source rod with your fingers, hands, or any part of your body.
- Do not place hands, fingers, feet, or other body parts in the radiation field from an unshielded source.
- Unless absolutely necessary, do not look under the portable gauge when the source rod is being lowered into the ground. If you must look under the portable gauge to align the source rod with the hole, follow the manufacturer's procedures to minimize radiation exposure.
- After completing each measurement in which the source is unshielded, immediately return the source to the shielded position.



- Always maintain constant surveillance and immediate control of the portable gauge when it is not in storage. At job sites, do not walk away from the portable gauge when it is left on the ground. Take action necessary to protect the portable gauge and yourself from danger of moving heavy equipment.
- When the portable gauge is not in use at a temporary job site, place the portable gauge in a secured storage location with two independent physical controls. Examples of two independent physical controls are: (1) securing the portable gauge in a locked storage facility located in a separate secured area in a warehouse; (2) securing the portable gauge inside a locked van and secured to the vehicle with a steel cable; (3) or storing the portable gauge inside a locked, nonremovable box and further securing the box with a steel cable or chain. If chains or cables are used as a method of providing security, one of the two chains or cables used, should be substantially more robust and more difficult to cut than the other. Simply having two chains or cables with locks would not satisfy the security rule unless each chain and lock combination were physically robust enough to provide both a deterrence and a reasonable delay mechanism.
- Always keep unauthorized persons away from the portable gauge.
- Perform routine cleaning and maintenance according to the manufacturer's instructions and recommendations.
- Before transporting the portable gauge, ensure that, where applicable, each portable gauge source is in the fully shielded position. Ensure that in portable gauges with a movable source rod, the source rod is locked in the shielded position (e.g., keyed lock, padlock, mechanical control). Place the portable gauge in the transport case and lock the case. Block and brace the case to prevent movement during transportation. Lock the case in or to the vehicle, preferably in a closed compartment.
- Return the portable gauge to its proper locked storage location at the end of the work shift.
- Log the portable gauge into the daily use log when it is returned to storage.
- If portable gauges are used for measurements with the unshielded source extended more than 3 feet beneath the surface, use piping, tubing, or other casing material to line the hole from the lowest depth to 12 inches above the surface. If the piping, tubing, or other casing material cannot extend 12 inches above the surface, cap the hole liner or take other steps to ensure that the hole is free of debris (and it is unlikely that debris will re-enter the cased hole) so that the unshielded source can move freely (e.g., use a dummy probe to verify that the hole is free of obstructions).
- After making changes affecting the portable gauge storage area (e.g., changing the location of portable gauges within the storage area, removing shielding, adding portable gauges, changing the occupancy of adjacent areas, moving the storage area to a new location), reevaluate compliance with public dose limits and ensure proper security of portable gauges.

## Emergency Procedures

If the source fails to return to the shielded position (e.g., as a result of being damaged, source becomes stuck below the surface), or if any other emergency or unusual situation arises (e.g., the portable gauge is struck by a moving vehicle, is dropped, is in a vehicle involved in an accident):

- Immediately secure the area and keep people at least 15 feet away from the portable gauge until the situation is assessed and radiation levels are known. However, perform first aid for any injured individuals and remove them from the area only when medically safe to do so.
- If any heavy equipment is involved, detain the equipment and operator until it is determined there is no contamination present.
- Portable gauge users and other potentially contaminated individuals should not leave the scene until emergency assistance arrives.
- Notify the following persons, in the order listed below, of the situation:

NAME <sup>1</sup>	WORK PHONE NUMBER <sup>1</sup>	HOME PHONE NUMBER <sup>1</sup>
<u>KEVIN SHYDER</u>	<u>(260) 241-3105</u>	<u>(260) 485-4637</u>
<u>CONNIE SHYDER</u>	<u>(260) 241-3111</u>	<u>(260) 485-4637</u>
<u>KRIS BOHRER</u>	<u>(260) 241-3108</u>	<u>(260) 485-6692</u>

Follow the directions provided by the person contacted above.

## RSO and Licensee Management

- Arrange for a radiation survey to be conducted as soon as possible by a knowledgeable person using appropriate radiation detection instrumentation. This person could be a licensee employee using a survey meter located at the job site or a consultant. To accurately assess the radiation danger or potential contamination, it is essential that the person performing the survey be competent in the use of the survey meter.
- If portable gauges are used for measurements with the unshielded source extended more than 3 feet below the surface, contact persons listed on the emergency procedures need to know the steps to be followed to retrieve a stuck source and to convey those steps to the staff on site.
- Make necessary and timely notifications to local authorities as well as to NRC as

---

<sup>1</sup> Fill in with (and update, as needed) the names and telephone numbers of appropriate personnel (e.g., the RSO or other knowledgeable licensee staff, licensee's consultant, portable gauge manufacturer) to be contacted in the event of an emergency.

required. (Even if it is not required, you may report *any* incident to NRC by calling NRC's Emergency Operations Center at (301) 816-5100, which is staffed 24 hours a day and accepts collect calls.) NRC notification is required when portable gauges containing licensed material are lost or stolen, when portable gauges are damaged or involved in incidents that result in doses in excess of 10 CFR Part 20.2203 limits, and when it becomes apparent that attempts to recover a sealed source stuck below the surface will be unsuccessful.

- Reports to NRC must be made within the reporting time frames specified by the regulations.
- Reporting requirements to NRC are found in 10 CFR Parts 20.2201-2203 and 10 CFR Part 30.50.

### **Security Procedures**

NRC regulations require a portable gauge licensee to use a minimum of two independent physical controls that form tangible barriers to secure portable gauges from unauthorized removal whenever the portable gauge is **not** under the control and constant surveillance by the licensee.

**Note:** The NRC staff interprets "control and maintain constant surveillance" of portable gauges to mean being immediately present or remaining in close proximity to the portable gauge so as to be able to prevent unauthorized removal of the portable gauge.

The objective of the security guidance is to reduce the opportunity for unauthorized removal and/or theft by providing a delay and deterrent mechanism. By following this guidance, it will become more difficult and time-consuming to defeat security measures.

The following security requirements apply to portable gauge licensees regardless of the location, situation, and activities involving the portable gauge. **The security requirements apply to: (1) storage on vehicles; (2) storage at temporary facilities (e.g., residence, hotel, job site trailer); and (3) storage at permanent facilities.** At all times, licensees are required to either maintain control and constant surveillance of the portable gauge when in use and, at a minimum, use two independent physical controls to secure the portable gauge from unauthorized removal while in storage. The physical controls used must be designed and constructed of materials suitable for securing the portable gauge from unauthorized removal, and both physical controls must be defeated in order for the portable gauge to be removed. The construction and design of the physical controls used must be such that they will deter theft by requiring a more determined effort to remove the portable gauge. The security procedures used must ensure that the two physical barriers chosen clearly increase the deterrence value over that of a single barrier and the two physical barriers would make unauthorized removal of the portable gauge more difficult.

are encouraged to use other combinations. The security rule permits the usage of two chains under certain circumstances in order to allow licensees flexibility; however, having two chains with locks would not satisfy the NRC's requirement unless **each** chain and lock combination used is physically robust enough to provide **both** a deterrence, and a reasonable delay mechanism. When two chains or cables are used, the second chain or cable should be substantially more robust and more difficult to cut than the first chain or cable.

If possible, the licensee should consider storing their portable gauges inside a locked facility or other non-portable structure overnight, instead of storage in a vehicle.

As long as the licensee maintains constant control and surveillance while transporting the portable gauges, the licensee need only to comply with the DOT requirements for transportation (e.g., placarding, labeling, shipping papers, blocking and bracing). However, if the licensee leaves the vehicle and portable gauge unattended (e.g., while visiting a gas station, restaurant, store), the licensee needs to ensure that the portable gauge is secured by two independent controls in order to comply with the requirements of 10 CFR Part 30.34(i)

While transporting a portable gauge, a licensee should not modify the transportation case if it is being used as the Type A container for transporting the device. This includes, but is not limited to, drilling holes to mount the case to the vehicle or to mount brackets or other devices used for securing the case to the vehicle. In order to maintain its approval as a Type A shipping container, the modified package must be re-evaluated by any of the methods described in 49 CFR Part 178.350 or 173.461(a). The re-evaluation must be documented and maintained on file in accordance with DOT regulations.

Physical controls used may include, but are not limited to, a metal chain with a lock, a steel cable with a lock, a secured enclosure, a locked tool box, a locked camper, a locked trailer, a locked trunk of a car, inside a locked vehicle, a locked shelter, a secured fenced-in area, a locked garage, a locked non-portable cabinet, a locked room, or a secured building. To assist licensees, some common scenarios are illustrated and examples of two independent physical controls are provided below.

### **Securing a Portable Gauge at a Licensed Facility**

Long term storage of a portable gauge is usually at a permanent facility listed in the license or license application. Routine storage of a portable gauge in a vehicle or at temporary or permanent residential quarters is usually reviewed and may be authorized by NRC or the applicable Agreement State during the licensing process. In accordance with NRC security regulations, when a portable gauge is stored at a licensed facility, the licensee would be specifically required to use a minimum of two independent physical controls to secure the gauge.

**Examples of two independent physical controls used by to secure a portable gauge when stored at a licensed facility are --**

1. The portable gauge or transportation case containing the portable gauge is stored inside a locked storage shed within a secured outdoor area, such as a fenced parking area with a locked gate;
2. The portable gauge or transportation case containing the portable gauge is stored in a room with a locked door within a secured building for which the licensee controls access by lock and key or by a security guard;
3. The portable gauge or transportation case containing the portable gauge is stored inside a locked, non-portable cabinet inside a room with a locked door, if the building is not secured;
4. The portable gauge or transportation case containing the portable gauge is stored in a separate secured area inside a secured mini-warehouse or storage facility; or
5. The portable gauge or transportation case containing the portable gauge is physically secured to the inside structure of a secured mini-warehouse or storage facility.

**Securing a Portable Gauge in a Vehicle**

Regulations in 10 CFR Part 71 requires that licensees who transport licensed material, or who may offer such material to a carrier for transport, must comply with the applicable requirements of the United States Department of Transportation (DOT) that are found in 49 CFR Parts 170 through 189.

Licensees commonly use a chain and a padlock to secure a portable gauge in its transportation case to the open bed of a pickup truck, while using the vehicle for storage. Because the transportation case is portable, a theft could occur if the chain is cut and the transportation case with the portable gauge is taken. If a licensee simply loops the chain through the handles of the transportation case, a thief could open the transportation case and take the portable gauge without removing the chain or the case. Similarly, because the transportation case is also portable, it must be protected by two independent physical controls if the portable gauge is inside. A lock on the transportation case, or a lock on the portable gauge source rod handle, is not sufficient because both the case and the gauge are portable.

A vehicle may be used for storage, however, it is recommended by NRC and DOT that this practice only be used for short periods of time or when a portable gauge is in transit. A portable gauge should only be kept in a vehicle overnight if it is not

practicable to provide temporary storage in a permanent structure. When a portable gauge is being stored in a vehicle, the licensee is specifically required to use a minimum of two independent physical controls to secure the portable gauge.

**Examples of two such independent physical controls approved by NRC to secure portable gauges in this situation are --**

1. The locked transportation case containing the portable gauge is physically secured to a vehicle with brackets, and a chain or steel cable (attached to the vehicle) is wrapped around the transportation case such that the case can not be opened unless the chain or cable is removed. In this example, the locked transportation case would count as one control because the brackets would prevent easy removal of the case. The chain or cable looped only through the transportation case handle is not acceptable;
2. The portable gauge or transportation case containing the portable gauge is stored in a box physically attached to a vehicle, and the box is secured with (1) two independent locks; (2) two separate chains or steel cables attached independently to the vehicle in such a manner that the box cannot be opened without the removal of the chains or cables; or (3) one lock and one chain or steel cable is attached to the vehicle in such a manner that the box cannot be opened without the removal of the chain or cable; or
3. The portable gauge or transportation case containing the portable gauge is stored in a locked trunk, camper shell, van, or other similar enclosure and is physically secured to the vehicle by a chain or steel cable in such a manner that one would not be able to open the case or remove the portable gauge without removal of the chain or cable.

**Securing a Portable Gauge at a Temporary Jobsite or at Locations Other Than a Licensed Facility**

When a job conducted requires storage of a portable gauge at a temporary jobsite or at a location other than a licensed facility, the licensee should use a permanent structure for storage, if practicable to do so. When storing a portable gauge in temporary or permanent residential quarters, the licensee should limit access by storing the gauge in a separate room away from residents and other members of the public. The licensee must also meet the radiation exposure limits specified in 10 CFR Part 20. When a portable gauge is stored at a temporary jobsite or at a location other than an authorized facility, the licensee is required to use a minimum of two independent physical controls to secure the portable gauge.

**Examples of two independent physical controls to secure portable gauges at these locations are --**

1. At a temporary job site, the portable gauge or transportation case containing the

portable gauge is stored inside a locked building or in a locked non-portable structure (e.g., construction trailer, sea container, etc.), and is physically secured by a chain or steel cable to a non-portable structure in such a manner that an individual would not be able to open the transportation case or remove the portable gauge without removing the chain or cable. A lock on the transportation case or a lock on the portable gauge source rod handle would not be sufficient because the case and the portable gauge are portable;

2. The portable gauge or transportation case containing the portable gauge is stored inside a locked room within temporary or permanent residential quarters, and is physically secured by a chain or steel cable to a permanent or non-portable structure (e.g., large metal drain pipe, support column, etc.) such that an individual would not be able to open the transportation case or remove the portable gauge without removing the chain or cable;


3. The portable gauge or transportation case containing the portable gauge is stored in a locked garage, and is within a locked vehicle or is physically secured by a chain or steel cable to the vehicle in such a manner that an individual would not be able to open the transportation case or remove the portable gauge without removing the chain or cable; or

4. The portable gauge or transportation case containing the portable gauge is stored in a locked garage, and is within a locked enclosure or is physically secured by a chain or steel cable to a permanent or non-portable structure in such a manner that an individual would not be able to open the transportation case or remove the portable gauge without removing the chain or cable.

**Extremely Urgent**

Call 1-800-PICK

- For UPS Next Day Air® containing electronic media, use a UPS Next Day Air Express Envelope. Envelopes containing electronic media are subject to the corresponding rates for the applicable weight.
- For UPS WorldWide Express® Envelopes weighing one pound or more are subject to the corresponding rates for the applicable weight.
- Do not use UPS 2nd Day Air® envelopes weighing over 13 ounces in this envelope. For 2nd Day Air services, UPS Express Envelopes weighing one pound or more are subject to the corresponding rates for the applicable weight.
- Do not send cash or cash equivalent.



*Handwritten:*  
1/10/07  
USP

**Window Envelope**

Use this envelope with shipping documents printed from a laser or inkjet printer on plain paper.

This envelope is for use with the following services: **UPS Next Day Air®**  
**UPS Worldwide Express®**  
**UPS 2nd Day Air®**

◀ **Insert shipping document under window for tracking**

Do not use this envelope with:  
**UPS Ground**  
**UPS Standard**  
**UPS 3 Day Select™**  
**UPS Worldwide Expedite™**

JOIL TESTING INC  
(260) 490-2800  
THE UPS STORE #4682  
921 EAST DUPONT ROAD  
ORT WAYNE IN 46825

LTR 1 OF 1  
SHP WT LTR  
DATE 30 JUL 2007

SHIP TO: **US NUCLEAR REGULATORY COMMISSION**

**US NUCLEAR REGULATORY COMMISSION**  
**2443 WARRENVILLE RD**  
**210**  
**Lisle IL 60532 3673**




**IL 603 9-03**



120R196V0195611950

UPS NEXT DAY AIR  
TRACKING #: 1Z 8R1 96V 01 9561 1950

**1**



BILLING: P/P

B.00 E2844 66 0A 04/2007

