



July 31, 2007

ST Environmental Professionals, Inc.
114 Lutz Road
Boyertown, PA 19512
Phone: 610-845-3070
Fax: 610-845-3137
E-Mail: STEP_CORP@att.net

40-9027

US Nuclear Regulatory Commission
Attn: Document Control Desk
Mail Stop O-3 H8
11555 Rockville Pike
Rockville, Maryland 20852-2738

Subject: Rock Selection Procedures
Reading Slag Pile Site
STEP Project Number 90C057

Dear Mr. Smith,

This letter serves as a follow-up to recent telephone conversations with Ted Johnson and Robert Johnson, and, on behalf of Cabot Corporation (Cabot), presents the procedures for the selection of rock to construct the proposed rip-rap cover at the Reading Slag Pile Site (Site). These rock selection procedures will ensure that the rock used is homogeneous and generally absent of characteristics that would adversely affect the durability of the overall cover system.

The specifications for the testing and placement of the rock will follow under separate cover.

I. Background/Supporting Information for Procedures and Specifications

The rock selection procedures and specifications for the testing and placement of the rip rap were developed based on information presented in the Decommissioning Plan and information more recently obtained from the selected quarry regarding its operations.

A. Summary of Rock Characteristics (Durability)

The rock for the rip-rap cover will be the diabase (diorite) from the Dyer Quarry located approximately 7 miles from the Site. Section 3.0 of Addendum 1 to the Reading Slag Pile Site Decommissioning Plan (Revision 4, August 2006, prepared by ST Environmental Professionals) provides a detailed description of the physical and chemical characteristics and testing of this rock, as well as a general description of the quarrying operations. Based on this information, Addendum 1 concludes that the diabase rock can be used to construct the cover over the slag because it is sufficiently durable to resist weathering and remain stable throughout the 1,000 year period of interest (NUREG-1623, p. 14) without reliance upon active ongoing maintenance.

UMSSO1
FSME

The following observations from quarry visits and conclusions from Addendum 1 (reference pages cited in parentheses) were considered in developing the rock selection procedures:

- The diabase rock has been well characterized by physical testing, inspection and current uses. Based on the properties reported by the quarry and independent laboratory tests the diabase easily exceeds the criteria in NUREG-1623 of 85% (pg. 3-8);
- Potential adverse heterogeneities in the diabase include joints, fractures, flow zones, chilled margins, alteration zones, zones of higher porosity and xenoliths. However, these features comprise only an insignificant fraction of the overall rock mass are easily recognizable and not all will actually be detrimental. For example, only joints that remain within individual pieces after the quarrying operations will have a potential impact on the durability of the rip rap (pg. 3-9)
 - Other than in the upper bench, nearly all joints and fractures appeared to be unweathered (pg 3-9)
 - It did not appear that joints remained in individual pieces of rock after being quarried. (pg. 3-9).
 - No carbonate minerals or veins were reported by the quarry analyses, the independent Cabot analyses, or noted during the site visit (pg 3-9);
 - Xenoliths were not observed during the site visit and are not believed to be common (pg. 3-10).
 - Alteration zones occur only in the surrounding country rock that is not to be quarried for the rip rap (pg. 3-10).
 - The diabase has essentially no primary porosity and a very low secondary porosity due to widely spaced joints and fractures. It is homogeneous, lacking bedding planes or foliation (pg. 3-10).

B. General Quarrying Operations

The diabase at the Dyer quarry consists of a nearly vertical massive dike approximately 1,000 feet thick. The quarry operates in 50-foot high benches. The uppermost benches have been largely removed and the current deepest bench is approximately 400 feet below the original ground surface. The country rock is present only in the perimeter portions of the uppermost benches and is laterally and vertically distant from the current diabase quarrying areas. The quarry operator reported that the “country rock” around the diabase (which consists of baked sandstone) is quarried and processed separately from the diabase. Inclusions of country rock in the diabase being quarried and stockpiled were not observed or noted during the quarry inspections (Addendum 1; pg 3-3);

The quarry processes approximately 60,000 tons of rock each week. After each blast, large impact hammers mounted on hydraulic excavators are used to break the larger pieces such that the material can be loaded into trucks. Large rocks are selectively removed from the blast material and transported to a stockpile area. The remaining rock is then transported to the hydraulic rock crusher by large dump trucks. The rock first passes through a primary crusher. Rock which passes through the screens in the primary crusher is then moved by conveyor to be further processed, screened and placed in stockpiles via conveyors. The FS-2, FS-3, and R-4 material is being constantly produced and shipped precluding the ability to select and track material-specific rock source location or characteristics. During the quarry visit(s), stockpiles of R-4, FS-2 and FS-3 were observed to be 30-50 feet tall.

II. Personnel Involved in Rock Selection and Testing

The selection and testing of the rock will be performed by a geologist and an engineer contracted to Cabot. Primarily, but not exclusively, the geologist will be responsible for inspection of the quarry blast face; training of the quarry operator in the selection and/or processing (by hydraulic hammer) of the R-6 and R-7 rock; selection of the R-6 and R-7 material; and visual inspection of the stockpiled R-4, FS-3 and FS-2 during loading. The engineer will be responsible for the selection of rock samples for laboratory testing and inspection of the rip-rap placement at the project site. Cabot's Site Manager will have overall responsibility for the rock selection and placement operations.

III. Rock Selection Procedure

Five gradations of material for the cover construction will be obtained from the Dyer quarry; FS-2, FS-3, R-4, R-6, and R-7. The procedures for rock selection incorporate the processing methods used at the quarry and the use of the materials in constructing the cover. The overall goal of the rock selection process is to minimize the potential that the diabase for the project contains deleterious material, primarily the country rock or chill zone material.

A. Blast Face Inspection

The quantity of rock required for this project does not allow Cabot to be directly involved in the quarrying operations, such as selecting a blast face for the project material. At initiation of the project, the geologist will meet with representatives of the quarry to understand the locations and schedule for future blasts. If the schedule allows, rock selection will follow blast areas which are as far away from the country rock as possible. If accessible, the geologist will inspect the next 3-4 scheduled blast faces. The geologist will either accept or reject the blast face or section of the face, with regard to whether the R-6 and R-7 project material could come from this blast, based on the inclusion of significant amounts of country rock, highly weathered zones, highly fractured zones, extensive veins of calcite, or rock types that are significantly different from the typical diabase in texture or composition. Some variations in texture and composition are typical and acceptable if the changes are gradational without sharp contacts.

B. Selection of R-6 and R-7 Material

As mentioned above, large rock is stockpiled at the quarry. The geologist will work with the quarry operator to select and generate sample piles of rocks consisting of the desired size and characteristics. If possible, a pile of material with undesirable characteristics will also be created to guide the operator. The geologist will be onsite for at least the first two days of work for every operator used to ensure that the operator is able to recognize and select the desired materials. The geologist will be on site at least one day per week thereafter to inspect the material as it is stockpiled. The interval between the inspections will be adjusted so that all the rock selected can be adequately assessed. This will be accomplished by having the operator produce low-height stockpiles over a large area and not adding more height between inspections than the maximum size of each gradation class (i.e. no more than 24-inch lifts for the R-6 material and no more than 30-inch lifts for the R-7 material).

As described above and stated in Addendum 1 to the Decommissioning Plan, specific undesirable characteristics include highly weathered pieces (a weathering rind greater than 1 cm), internal carbonate veins, or obvious unexpressed planes of weakness such as joints and seams. A maximum acceptance limit of 5% for each type of feature and maximum 10% total will be allowed for this material. The percentage will be the number of visible rock pieces with undesirable characteristics relative to the total number of visible rock pieces within a specified area, as described below. This small amount would not have a significant impact on the performance of the cover in the lower portions of the slope and the toe at the bottom of the slope where this material will be used.

The selection process is designed to preclude rock with undesirable characteristics. To ensure that the material meets the selection criteria, the material will be evaluated each day that the geologist is on site. The evaluation will consist of staking out a random square area of each stockpile (R-6 and R-7) that is ten times the d50 of the material on each side (10' by 10' for the R-6 material and 15' by 15' for the R-7 material). The stakes will be connected by surveyors flagging. The geologist will then inspect the visible rocks within the staked area and count the number of rocks that contain one or more of the undesirable features of country rock inclusions, internal fractures or carbonate veins, or weathering rinds thicker than 1 cm. Because the area is equal to 100 times the average d50 size of the material, the number of rocks with visible undesirable features will be approximately equivalent to percentage. If the random section fails the selection criteria, the stockpile may be re-worked to remove rocks with undesirable pieces and the test performed again.

C. Selection of R-4, FS-3 and FS-2 Material

The FS-2 and FS-3 material will be used only for the drainage layer beneath the rip-rap cover. The cover design is relatively insensitive to variations in the characteristics of this material other than the initial size gradation. The R-4 material will be used to construct the rip-rap cover on the upper portions of the slope.

Large stockpiles of R-4, FS-3 and FS-2 exist at the quarry and this material is routinely sold and replenished as part of quarrying operations. To the extent practical and as the quarry schedule and project schedule allow, selection of this material will be based (in part) on knowing that the material in the stock pile came from one of the blast faces inspected by the geologist. However, it is understood that this may not be possible.


The numerous crushing and sorting processes used to produce this material ensures that the piles will be fairly homogenous and the visual portions will be representative of the entire pile. The processing also ensures that unexpressed planes of weakness will be rare or absent in this material.

The geologist will inspect the stockpiles of this material prior to loading for transport to the project site. The inspection will focus on ensuring that there is not a significant amount of country rock in that portion of the stockpile to be used. Because the quarry is careful to not include country rock in the diabase quarrying and the stockpiles consist of material that comes from multiple blasts, the likelihood of there being significant country rock in the stockpiles is low.

The geologist will also observe the loading of the rock into the trucks from a safe distance. If the geologist observes significant country rock to be present, he will notify the loading operator to stop. The geologist will inspect the stockpile and, if unacceptable, have the truck emptied and reloaded. If appropriate, the geologist may instruct the operator to load from a different area of the stockpile.

We trust that these procedures will meet with the NRC's concurrence. We look forward to discussing these procedures at the quarry visit currently scheduled for Monday, August 6. In the interim, please call with any questions.

Yours truly,

A handwritten signature in black ink that reads "Steffan R. Helbig". The signature is written in a cursive style with a large initial 'S'.

Steffan R. Helbig, P.G.

cc (5x)
Ted Smith
Mail Stop T8F5
11545 Rockville Pike
Rockville, Maryland 20852-2738

cc (1x)
Robert L. Johnson
11545 Rockville Pike
Rockville, Maryland 20852-2738

cc Wayne Rieber, Cabot
Kelly Fifer, DMI
Dave Harmanos, GeoSystems