

Mail Envelope Properties (46C34C73.2D7 : 0 : 58071)

Subject: Changes to section 3.2 of ISG on communications
Creation Date 8/15/2007 2:56:07 PM
From: <wesley.bowers@exeloncorp.com>
Created By: wesley.bowers@exeloncorp.com

Recipients

nrc.gov
EBGWPO01.HQGWDO01
DDT1 (Diana Diaz-Toro)

nrc.gov
OWGWPO04.HQGWDO01
WEK (William Kemper)

nrc.gov
TWGWPO03.HQGWDO01
PJR1 (Paul Rebstock)

nei.org
gac CC

Post Office

EBGWPO01.HQGWDO01
OWGWPO04.HQGWDO01
TWGWPO03.HQGWDO01

Route

nrc.gov
nrc.gov
nrc.gov
nei.org

Files	Size	Date & Time
MESSAGE	2612	8/15/2007 2:56:07 PM
TEXT.htm	3350	
Mime.822	8627	

Options

Expiration Date: None
Priority: Standard
ReplyRequested: No
Return Notification: None

Concealed Subject: No
Security: Standard

From: Wes Bowers <wesley.bowers@exeloncorp.com>
To: Diana Diaz-Toro, Paul Rebstock, William Kemper
Date: 8/15/2007 2:57 PM
cc: Gordon Cleffon <gac@nei.org>
Subject: Changes to section 3.2 of ISG on communications

Diana, Paul, and Bill,

I thought about the discussion we had yesterday concerning section 3.2 of the communications ISG. I propose replacing the first three paragraphs of section 3.2 of the communications ISG (revision F) with the following:

IEEE 603 contains requirements concerning safety system manual controls and operator displays. Regulatory Guide 1.97 contains requirements for accident monitoring instrumentation. IEEE 603 and Regulatory Guide 1.97 specify design and qualification requirements applicable to the instrumentation based on the function of the controls and displays. In addition, human factors requirements include a concept called minimum inventory. The minimum inventory is based on the needs of the operator; inclusion on the list does not imply a specific set of design and qualification criteria. The requirements of IEEE 603 and Regulatory Guide 1.97 apply to the minimum inventory based on the function of the controls and displays.

Safety-related controls and displays may be provided via operator workstations, or they may be provided via hardwired devices such as switches, relays, indicators, and analog signal processing circuits. In either case, the safety-related controls and indications must consist of safety-related devices with safety-related software and must be dedicated to specific safety divisions. Instrumentation and controls required by IEEE 603 and Regulatory Guide 1.97 to meet less stringent design and qualification requirements may be included on non-safety related multidivisional control and display stations provided that the design and qualification requirements are met.

Please consider this input as you revise the ISG.

Wes