NRC FORM 618 U.S. NUCLEAR REGULAT					JLATORY	ATORY COMMISSION			
(8- 10	(8-2000) 10 CFR 71 CERTIFICATE OF COMPLIANCE								
	FOR RADIOACTIVE MATERIAL PACKAGES								
1.	a. CERTIFICATE NUMBER	b. REVISION NUMBER	c. DOCKET NUMBER	d. PACKAGE IDENTIFICATION NUMBER	PAGE		PAGES		
	5797	16	71-5797	USA/5797/B(U)F	1	OF	3		

2. PREAMBLE

- a. This certificate is issued to certify that the package (packaging and contents) described in Item 5 below meets the applicable safety standards set forth in Title 10, Code of Federal Regulations, Part 71, "Packaging and Transportation of Radioactive Material."
- b. This certificate does not relieve the consignor from compliance with any requirement of the regulations of the U.S. Department of Transportation or other applicable regulatory agencies, including the government of any country through or into which the package will be transported.
- 3. THIS CERTIFICATE IS ISSUED ON THE BASIS OF A SAFETY ANALYSIS REPORT OF THE PACKAGE DESIGN OR APPLICATION
 - a. ISSUED TO (Name and Address)
 U.S. Department of Energy
 Washington, D.C. 20585
- b. TITLE AND IDENTIFICATION OF REPORT OR APPLICATION U.S. Department of Energy application dated May 30, 1991, as supplemented

4. CONDITIONS

This certificate is conditional upon fulfilling the requirements of 10 CFR Part 71, as applicable, and the conditions specified below.

5.

- (a) Packaging
 - (1) Model No.: Inner HFIR Unirradiated Fuel Element Shipping Container, and Outer HFIR Unirradiated Fuel Element Shipping Container
 - (2) Description

Packaging for unirradiated fissile radioactive material as fuel elements for the High Flux Isotope Reactor (HFIR). The containers are right circular cylinders with an 11-gauge carbon steel shell. The lid is attached to the container with sixteen 3/8-16x1-inch steel bolts. The steel shell is filled with stacked fir plywood rings. The plywood rings form a central cavity which is lined with 1-inch thick polyethylene foam.

The packaging for the inner HFIR fuel element has overall dimension of 25 inches OD bye 45 inches high, a 10-7/8-inch diameter by 30-1/4-inch deep cavity, and a 660 pound gross weight.

The packaging for the outer HFIR fuel element has overall dimensions of 31.5 inches OD x 45.75 inches high, a 17-3/8-inch diameter by 31-1/8-inch deep cavity, and a 1,050 pound gross weight.

- (3) Drawings
 - (i) The packaging for the inner HFIR fuel is constructed in accordance with Martin Marietta Energy Systems, Inc., Drawing Nos.
 M-20978-EL-003E, Rev. E, and M-20978-EL-008E, Rev. C

_	NRC FORM 618 U.S. NUCLEAR REGULATORY COMMISS						ISSION
1	(8-2000) 10 CFR 71 CERTIFICATE OF COMPLIANCE FOR RADIOACTIVE MATERIAL PACKAGES						
1	. a. CERTIFICATE NUMBER	b. REVISION NUMBER	c. DOCKET NUMBER	d. PACKAGE IDENTIFICATION NUMBER	PAGE		PAGES
	5797	16	71-5797	USA/5797/B(U)F	2	OF	3

- 5. (a) (3) Drawings (continued)
 - (ii) The packaging for the outer HFIR fuel is constructed in accordance with Martin Marietta Energy Systems, Inc., Drawing Nos. M-20978-EL-002E, Rev. D, and M-20978-EL-008E, Rev. C
 - (b) Contents
 - (1) Type and form of material

Uranium as U₃O₈-Al cermet, enriched up to 95% in the U-235 isotope, and clad in aluminum, 10-mils thick, and:

- (i) For the packaging described in 5(a)(3)(i), the contents are described in ORNL/TM-9220, "Specifications for High Flux Isotope Reactor Fuel Elements HFIR-FE-3," and in the following Oak Ridge National Laboratory Drawing Nos.: E-42118, Rev. Q; E-42112, Rev. H; D-42113, Rev. G; E-42114, Rev. H; and E-42117, Rev. H.
- (ii) For the packaging described in 5(a)(3)(ii) the contents are described in ORNL/TM-9220, "Specifications for High Flux Isotope Reactor Fuel Elements HFIR-FE-3," and in the following Oak Ridge National Laboratory Drawing Nos.: E-42126, Rev. M; E-42120, Rev. H; D-42121, Rev. H; D-42122, Rev H; and E-42125, Rev. J.
- (2) Maximum quantity of material per package
 - (i) For the contents described in 5(b)(1)(i) not more than 2.63 kg of U-235.
 - (ii) For the contents described in 5(b)(1)(ii) not more than 6.88 kg of U-235.
- (c) Criticality Safety Index

0.4

6. The lid lifting attachments must be blocked as shown on Martin Marietta Energy Systems, Inc., Drawing No. M-20978-EL-009E, Rev. 2, to prevent inadvertent use of the attachments during transport.

NRC FORM 618 U.S. NUCLEAR REGULATORY COMMIS						ISSION	
(8-2000) 10 CFR 71 CERTIFICATE OF COMPLIANCE							
FOR RADIOACTIVE MATERIAL PACKAGES							
1. a. CERTIFICATE NUMBER	b. REVISION NUMBER	c. DOCKET NUMBER	d. PACKAGE IDENTIFICATION NUMBER	PAGE	•	PAGES	
5797	16	71-5797	USA/5797/B(U)F	3	OF	3	

- 7. In addition to the requirements of Subpart G of 10 CFR Part 71:
 - (a) Each package shall be maintained in accordance with the Maintenance Program in Chapter 8 of the application;
 - (b) Each package shall be operated and prepared for shipment in accordance with the Operating Procedures in Chapter 7 of the application; and
 - (c) The fuel element shall meet the fabrication inspection requirements of ORNL/TM-9220, "Specifications for High Flux Isotope Reactor Fuel Elements HFIR-FE-3."
- 8. Use of packaging fabricated after December 31, 1976, is not authorized.
- 9. The packaging authorized by this certificate is hereby approved for use under the general license provisions of 10 CFR 71.17.
- 10. Transport by air of fissile material is not authorized.
- 11. Expiration date: September 30, 2012.

REFERENCES

U.S. Department of Energy Application dated May 30, 1991.

Supplements dated: February 26, 1992; April 2, 1993; September 23, 1996; September 2, 1998; February 24, 2000; February 4, 2002; and August 20, 2007.

FOR THE U.S. NUCLEAR REGULATORY COMMISSION

/RA/

Robert A. Nelson, Chief Licensing Branch Division of Spent Fuel Storage and Transportation Office of Nuclear Material Safety and Safeguards

Date: October 29, 2007.