

NRC Weld Residual Stress Model Validation Program




U.S. NRC
UNITED STATES NUCLEAR REGULATORY COMMISSION
Protecting People and the Environment

Aladar A. Csontos
Office of Nuclear Regulatory Research
U.S. Nuclear Regulatory Commission
January 10, 2008

PWSCC in LBB Systems Research Programs

PWSCC in LBB Systems Research Programs

Purpose: Support NRR in considering appropriate regulatory requirements to address PWSCC of susceptible LBB components within the next 2 years.






Residual Stress Validation: PNNL – Tom Taylor

- Background:
 - Component integrity analyses (AFEAs) for DMW showed that the results were highly dependent upon WRS profiles.
- Purpose:
 - Assess uncertainties and inform/validate WRS models used in NRC/industry PWSCC flaw evaluation and LBB analyses through a blind study of well controlled fabricated mockups, FEA modeling, and WRS measurements.
- Project Objectives:
 - Develop more accurate WRS models.
 - Blind validation of WRS models to measurements.
 - Determine uncertainties in WRS modeling.




- Phase I Validation (2007):
 - DEI, BMI, & Emc² WRS models validated to the EU Network for Evaluating Structural Components-III (NESC-III) round robin study on 309L DMW integrity.
- Phase II Blind Validation (2008):
 - Validate WRS models to controlled research & ASME Section III (NB) fabricated 82/182 DM mockups.
 - Open to those groups willing to participate in a blind validation of their WRS models.
 - NRC will provide the data packages for each mockup to the program participants.
 - NRC may need some support for multiple WRS measurements.

Phase I: Summary of EU NESC III WRS Validation



Phase I: Summary of EU NESC III WRS Validation




Phase II: Blind Validation of Welded Mockups

- Tensile properties will be provided in a data package sent to WRS modelers as a function of temperature in the as-welded and solution-annealed condition.
- Obtaining 2-4 well controlled research & ASME Section III (NB) fabricated 82/182 DM mockups.
- Model validation to evaluate sequentially harder welded mockups to aid model development.

Geometry	Weld	Plate Material	Diameter	Weld Fabrication	Butter	Safe End	PA Repair	360° Last Pass Weld	Overlay	Start/Stop
Plate	82/182	SS - SS	-	Research	No	-	-	-	-	-
Cylinder	82/182	SS - SS	12"	Research	No	No	Yes (1/4)	No	No	All in 1 Quadrant
Cylinder	82/182	Ferritic - SS	12"	Research	Yes	Yes	Yes (1/4)	No	No	All in 1 Quadrant
Full Scale	82/182	Ferritic - SS	12"	ASME NB	Yes	Yes	Yes (1/2)	Yes (1/2)	Yes	

SS-SS Welded Plate 20"(w)x30"(l)x1"(t)



Fill V-groove with INCONEL 82

60.0°

20.00

30.00

10.00

1.00

DETAIL R
 SCALE 1 : 1

No weld repairs

Specifications:

1. Record amperage, voltage, and weld travel speed for each weld.
2. Record weld bevel/groove geometry before welding
3. Provide a pass location map (where each pass is laid) and the order of each pass. The size of each pass is also desirable.
4. Place marks on each cylinder indicating starting position. Provide drawing indicating direction of welding process for each fabricated cylinder.
5. The history of the welding process needs to be recorded. For example, if the welding stopped for some reason, and was allowed to cool overnight or longer, this needs to be noted. This is for all welds, including the overlay welds.
6. Weld repair information and history of repair passes needs to be recorded.
7. Inter-pass cooling temperatures and pre-heat, if any, must be recorded.
8. Record weld pipe boundary conditions, e.g. imposed constraint to prevent warpage.
9. Material certifications (CMTRs) are needed for base/filler metals
10. All welding data sheets and the welding procedure needs to be provided
11. Shrinkage measurements need to be documented
12. NDE records need to be provided
13. Plate material 304 or 316 stainless steel
14. Weld material Inconel 82


Additional Information Desirable:

1. Thermocouple temperature data near the weld for some of the passes and overlays
2. Video taping of the welding process including close up of the weld (please provide cost estimate for doing this).

REV	DATE	BY	CHK'D	APP'VD	DESCRIPTION/NOTE

Drawn by: JTM	Checked by: JTM	Approved by: A
Designed by: JTM	App'vd by: JTM	Scale: NONE
Material: 304 or 316 stainless steel	Weld Material: Inconel 82	DWG No: 1
Rev: 0	Proj: NRC WELD PROJECT	Rev: 0

SS-SS Welded Cylinder 12"(d)x24"(l)x1.3"(t)




**Partial Arc ID weld repair
 All start/stops in one quadrant**

Specifications:


1. Record amperage, voltage, and weld travel speed for each weld.
2. Record weld bevel/groove geometry before welding.
3. Provide a pass location map (where each pass is laid) and the order of each pass. The size of each pass is also desirable.
4. Place marks on each cylinder indicating starting position. Provide drawing indicating direction of welding process for each fabricated cylinder.
5. The history of the welding process needs to be recorded. For example, if the welding stopped for some reason, and was allowed to cool overnight or longer, this needs to be noted. This is for all welds, including the overlay welds.
6. Weld repair information and history of repair passes needs to be recorded.
7. Inter-pass cooling temperatures and pre-heat, if any, must be recorded.
8. Record weld pipe boundary conditions, e.g. imposed constraint to prevent warpage.
9. Material certifications (CMTRs) are needed for base/filler metals.
10. All welding data sheets and the welding procedure needs to be provided.
11. Shrinkage measurements need to be documented.
12. NDE records need to be provided.
13. Weld repair from inside, one quarter wall thickness, one quadrant.
14. Start and stop in same quadrant.
15. All welds to be done in the 1G position.

Additional Information Desirable:

1. Thermocouple temperature data near the weld for some of the passes and overlays.
2. Video taping of the welding process including close up of the weld (please provide cost estimate for doing this).

 RICHLAND, WASHINGTON PACIFIC NORTHWEST NATIONAL LABORATORY U.S. DEPARTMENT OF ENERGY		Project: NRC WELD PROJECT DWG: 12in. Pipe Similar MtIs.
DRAWN BY JTM DATE: 31 Oct 2007	DESIGNED BY JTM	REV. DATE BY CHK'D APP'VD DESCRIPTION/REVISION 1 2 3 4 5
CHECKED BY ...	APPROVED BY ...	SHEET A SCALE 1:4 DWG NO 1 REV 0

DM Weld w/ Safe-End Weld 12"(d)x27.4"(l)x1.3"(t)



**Partial Arc ID weld repair
 All start/stops in one quadrant**

Specifications:

1. Record amperage, voltage, and weld travel speed for each weld.
2. Record weld bevel/groove geometry before welding
3. Provide a pass location map (where each pass is laid) and the order of each pass. The size of each pass is also desirable.
4. Place marks on each cylinder indicating starting position. Provide drawing indicating direction of welding process for each fabricated cylinder.
5. The history of the welding process needs to be recorded. For example, if the welding stopped for some reason, and was allowed to cool overnight or longer, this needs to be noted. This is for all welds, including the overlay welds.
6. Weld repair information and history of repair passes needs to be recorded.
7. Inter-pass cooling temperatures and pre-heat, if any, must be recorded.
8. Record weld pipe boundary conditions, e.g. imposed constraint to prevent warpage.
9. Material certifications (CMTRs) are needed for base/filler metals
10. All welding data sheets and the welding procedure needs to be provided
11. Shrinkage measurements need to be documented
12. NDE records need to be provided
13. Weld Repair buttered weld from inside, one quarter wall thickness, one quadrant
14. Start and stop in the same quadrant
15. All welds to be done in the 1G position


Additional Information Desirable:

1. Thermocouple temperature data near the weld for some of the passes and overlays
2. Video taping of the welding process including close up of the weld (please provide cost estimate for doing this).

REV	DATE	BY	CHKD	APPROV	DESCRIPTION

 <i>The Business of Innovation</i>		RICHLAND, WASHINGTON PACIFIC NORTHWEST NATIONAL LABORATORY U.S. DEPARTMENT OF ENERGY
DESIGNED BY JTM	DATE 10 October 2007	Project: NRC WELD PROJECT DWG: Buttered 12in. Pipe w/Safe End
SPEC'D BY JTM	DATE	
CHECK'D BY ...	DATE	
APPROVED BY ...	DATE	
APPROVED BY ...	DATE	
REV Δ	SCALP 1:1	DWG NO 1

Prototypical Surge DMW 12"(d)x24"(l)x1.3"(t)



SECTION R-R
 SCALE 1 : 4

**Partial Arc ID weld repair
 Start/stops random**

REV	DATE	BY	CHK'D	APP'VD	DESCRIPTION/ESSE

- Specifications: ASME Boiler and Pressure Vessel Code, Section 3, Class 1
1. Record amperage, voltage, and weld travel speed for each weld.
 2. Record weld bevel/groove geometry before welding
 3. Provide a pass location map (where each pass is laid) and the order of each pass. The size of each pass is also desirable.
 4. Place marks on each cylinder indicating starting position. Provide drawing indicating direction of welding process for each fabricated cylinder.
 5. The history of the welding process needs to be recorded. For example, if the welding stopped for some reason, and was allowed to cool overnight or longer, this needs to be noted. This is for all welds, including the overlay welds.
 6. Weld repair information and history of repair passes needs to be recorded.
 7. Inter-pass cooling temperatures and pre-heat, if any, must be recorded.
 8. Record weld pipe boundary conditions, e.g. imposed constraint to prevent warpage.
 9. Material certifications (CMTRs) are needed for base/filler metals
 10. All welding data sheets and the welding procedure needs to be provided
 11. Shrinkage measurements need to be documented
 12. NDE records need to be provided
 13. Provide two (2) cylinders, one with full structural overlay welds and the other without. Overlay material to be Inconel 52 or 152
 14. Weld repairs buttered weld both assemblies, from inside one half wall thickness, one quadrant
 15. 360 degree beak chipping inside diameter both welds.
 16. All welds to be done in the 1G position
- Additional Information Desirable:
1. Thermocouple temperature data near the weld for some of the passes and overlays
 2. Video taping of the welding process including close up of the weld (please provide cost estimate for doing this).
- Please provide estimate for:
1. Price for fabricating each of the weld samples discussed above.
 2. Estimated time to complete order

Battelle
The Business of Innovation RICHLAND, WASHINGTON
 PACIFIC NORTHWEST NATIONAL LABORATORY
 U.S. DEPARTMENT OF ENERGY

Project: NRC WELD PROJECT
 DWG: Full Scale Geometry

DESIGN BY	JIM	DATE	04/30 October 2007
DRAWN BY	JIM	DATE	
CHECKED BY	JIM	DATE	
APPROVED BY	JIM	DATE	
REV	EDID	DATE	
A	NONE		1

Specifications for the Welded Mockups

1. Record amperage, voltage, & weld travel speed for each weld.
 2. Record weld bevel/groove geometry before welding.
 3. Provide a pass location map and the order of each pass.
 4. Place marks on each cylinder indicating starting position.
 5. The history of the welding process needs to be recorded.
 6. Weld repair and history of repair passes needs to be recorded.
 7. Inter-pass cooling temps and pre-heat must be recorded.
 8. Record weld pipe boundary conditions, e.g. imposed constraint to prevent warpage.
 9. Material certs (CMTRs) are needed for base/filler metals
 10. All welding data sheets and procedure need to be provided
 11. Shrinkage measurements need to be documented.
 12. NDE records need to be provided.
- * Thermocouple data near the weld & video tape the welding.

Phase II: Blind Validation of Welded Mockups

- Measurement techniques under consideration:
 - NDE:
 - X-ray diffraction for ID & OD surfaces (Proto)
 - Neutron diffraction (potential free beam time at ORNL)
 - Need a D_0 stress free sample to normalize data
 - DE:
 - Deep-hole drilling (<http://www.veqter.co.uk/>)
 - Hole drilling
 - Strain gauging
 - Contour method
 - Slitting method
- List of techniques to interrogate the DMW will be finalized at a TAG meeting later this year.