SOUTHWEST RESEARCH INSTITUTE® 6220 Culebra Road, P.O. Drawer 28510 Institute Quality Systems Institute Calibration Laboratory Phone: 210-522-5215 Fax 210-522-4834 Calibration Laboratory **Certificate of Calibration** Certificate #0972-01 Work Order: 303077939 Submitted By: DIV20 Address: B57 Date Issued: Dec 28, 2007 Contact: DON BANNON Calibration Date: Dec 28, 2007 Manufacturer / Model: DURO-SENSE / TYPE K *Calibration Due: Jun 28, 2008 **Description:** THERMOCOUPLE Calibration Location: Bldg. 64 Serial No: 0003 Environment: Temp. 73.0°F Hum. 40 %RH **Data Type: FOUND-LEFT Asset No: 011659 **DivID/Location:** N/A Procedure: TEMPERATURE PROBES - 5 JUN 06 This certificate documents traceability to the National Institute of Standards and Technology (NIST) and the International System of Units (SI). The Laboratory quality system conforms to ISO/IEC 17025, 2005, ANSI/NCSL Z540-1-1994 and relevant requirements of the ISO 9000-2000 standard. This certificate shall not be reproduced, except in full, without the written approval of the Southwest Research Institute Calibration Laboratory. This certificate shall not be used to claim product endorsement by Southwest Research Institute, American Association for Laboratory Accreditation (A2LA) or any agency of the U.S. Government. Results of this calibration relate only to the instrument described above at the time of calibration and does not imply any long term stability of the instrument. *Determined by the customer, does not imply the instrument will remain within tolerance as any number of factors may cause an out-of-tolerance condition before this date. **Found/Left = adjustment and/or repair was not required, As Left = adjusted and/or repaired was required. The client has sole responsibility for determination of in-/out-of-tolerance or compliance/noncompliance. See Remarks or attached Measurement Report with the same Work Order number for data. Reported uncertainty calculated in accordance with the ISO "Guide to the Expression of Uncertainty in Measurement" (GUM) and represents an expanded uncertainty with a coverage factor of k=2 to approximate a 95% confidence level. Remarks: Cal'd @ 0° and 150° C Standards Used Asset No. Serial No. Manufacturer Model Description Cal Due 009137 A21208 HART SCIENTIFIC 1575 SUPER THERMOMETER Jun 17, 08 010814 A44625 HART SCIENTIFIC 1529 THERMOCOUPLE THERMOMETER Oct 16.08 HART SCIENTIFIC 013500 PLATINUM RESISTANCE THERMOMETER Nov 12, 08 0222 5624

Reviewed by: () wgh () srk () jrg () blt () pwc Metrology Technician m:\a2la1.rpt Rev date August 15, 2005

Measurements by: Bob Trollir Metrology Technician

Page 1 of 1

Southwest Research Institute Calibration Laboratory Measurement Report

Work Order:	303077939	Mfr.	Duro-Sense	· · · · · · · · · · · · · · · · · · ·	Technician	blt
Asset No:	011659	Model	Туре К			
Serial No:	0003	Туре	Thermocouple		Cal Date	28-Dec-07
Remarks:	Limits taken	from ASTM E	230-02 and are ba	sed on brand	new unused therr	nocouples.
<u> </u>		Limited Cal -	Tested at 0 and 15	50 °C		
Function/Range	Test Point	TI Read	Difference	+/-Limit	+/-Uncertainty	Found/Left
Temperature	°C	°C	°C	°C	°C	Result
0	0.169	0.11	0.06	2.2	0.18	Pass
150	150.082	150.93	-0.85	2.2	0.18	Pass
		END	OF REPORT			

-

-