

STPEGS UFSAR

TABLE OF CONTENTS

CHAPTER 15

ACCIDENT ANALYSES

<u>Section</u>	<u>Title</u>	<u>Page</u>
15.0	ACCIDENT ANALYSIS	15.0-1
15.0.1	Classification of Plant Conditions	15.0-1
15.0.2	Optimization of Control Systems	15.0-5
15.0.3	Plant Characteristics and Initial Conditions Assumed in the Accident Analyses	15.0-5
15.0.4	Reactivity Coefficients Assumed in the Accident Analyses	15.0-8
15.0.5	Rod Cluster Control Assembly Insertion Characteristics	15.0-8
15.0.6	Trip Points and Time Delays to Trip Assumed in Accident Analyses	15.0-9
15.0.7	Instrumentation Drift and Calorimetric Errors	15.0-9
15.0.8	Plant Systems and Components Available for Mitigation of Accident Effects	15.0-10
15.0.9	Residual Decay Heat	15.0-12
15.0.10	Computer Codes Utilized	15.0-12
15.0.11	Summary of Accident Results	15.0-14
15.1	INCREASE IN HEAT REMOVAL BY THE SECONDARY SYSTEM	15.1-1
15.1.1	Feedwater System Malfunctions Causing a Reduction in Feedwater Temperature	15.1-1
15.1.2	Feedwater System Malfunctions Causing an Increase in Feedwater Flow	15.1-3
15.1.3	Excessive Increase in Secondary Steam Flow	15.1-5
15.1.4	Inadvertent Opening of a Steam Generator Relief or Safety Valve Causing a Depressurization of the Main Steam System	15.1-8
15.1.5	Spectrum of Steam System Piping Failure Inside and Outside Containment	15.1-10
15.2	DECREASE IN HEAT REMOVAL BY THE SECONDARY SYSTEM	15.2-1
15.2.1	Steam Pressure Regulator Malfunction or Failure That Results in Decreasing Steam Flow	15.2-1
15.2.2	Loss of External Electrical Load	15.2-1
15.2.3	Turbine Trip	15.2-3

STPEGS UFSAR

TABLE OF CONTENTS (Continued)

CHAPTER 15

<u>Section</u>	<u>Title</u>	<u>Page</u>
15.2.4	Inadvertent Closure of Main Steam Isolation Valves	15.2-8
15.2.5	Loss of Condenser Vacuum and Other Events Causing a Turbine Trip	15.2-8
15.2.6	Loss of Nonemergency AC Power to the Plant Auxiliaries (Loss of Offsite Power)	15.2-8
15.2.7	Loss of Normal Feedwater Flow	15.2-10
15.2.8	Feedwater System Pipe Break	15.2-13
15.3	DECREASE IN REACTOR COOLANT SYSTEM FLOW RATE	15.3-1
15.3.1	Partial Loss of Forced Reactor Coolant Flow	15.3-1
15.3.2	Complete Loss of Forced Reactor Coolant Flow	15.3-3
15.3.3	Reactor Coolant Pump Shaft Seizure (Locked Rotor)	15.3-6
15.3.4	Reactor Coolant Pump Shaft Break	15.3-10
15.4	REACTIVITY AND POWER DISTRIBUTION ANOMALIES	15.4-1
15.4.1	Uncontrolled Rod Cluster Control Assembly Bank Withdrawal from a Subcritical or Low Power Startup Condition	15.4-1
15.4.2	Uncontrolled Rod Cluster Control Assembly Bank Withdrawal at Power	15.4-5
15.4.3	Rod Cluster Control Assembly Misoperation	15.4-10
15.4.4	Startup of an Inactive Reactor Coolant Loop at an Incorrect Temperature	15.4-16
15.4.5	A Malfunction or Failure of the Flow Controller in a BWR Loop That Results in an Increased Reactor Coolant Flow Rate	15.4-18
15.4.6	Chemical and Volume Control System Malfunction That Results in a Decrease in Boron Concentration in the Reactor Coolant	15.4-18
15.4.7	Inadvertent Loading of a Fuel Assembly into an Improper Position	15.4-23
15.4.8	Spectrum of Rod Cluster Control Assembly Ejection Accidents	15.4-25
15.4.9	Spectrum of Rod Drop Accidents in a BWR	15.4-36

STPEGS UFSAR

TABLE OF CONTENTS (Continued)

CHAPTER 15

<u>Section</u>	<u>Title</u>	<u>Page</u>
15.5	INCREASE IN REACTOR COOLANT INVENTORY	15.5-1
15.5.1	Inadvertent Operation of ECCS During Power Operation	15.5-1
15.5.2	Chemical and Volume Control Systems Malfunction That Increases Reactor Coolant Inventory	15.5-2
15.6	DECREASE IN REACTOR COOLANT INVENTORY	15.6-1
15.6.1	Inadvertent Opening of a Pressurizer Safety or Relief Valve	15.6-1
15.6.2	Failure of Small Lines Carrying Primary Coolant Outside Containment	15.6-3
15.6.3	Steam Generator Tube Rupture	15.6-5
15.6.4	Radiological Consequences of Main Steam Line Failure Outside Containment (BWR)	15.6-11
15.6.5	Loss of Coolant Accidents	15.6-11
15.7	RADIOACTIVE RELEASE FROM A SUBSYSTEM OR COMPONENT	15.7-1
15.7.1	Waste Gas System Failure	15.7-1
15.7.2	Postulated Radioactive Releases due to Liquid-Containing Tank Failure (Release to Atmosphere)	15.7-1
15.7.3	Postulated Radioactive Releases Due to Liquid-Containing Tank Failures (Ground Release)	15.7-1
15.7.4	Design Basis Fuel Handling Accidents	15.7-2
15.7.5	Spent Fuel Cask Drop Accident	15.7-6
15.8	ANTICIPATED TRANSIENTS WITHOUT SCRAM	15.8-1
APPENDIX	FISSION PRODUCT INVENTORIES	15.A-1
15.A		
15.A.1	Activities in the Core	15.A-1
15.A.2	Activities in the Fuel Pellet-Cladding Gap	15.A-1
15.A.3	Concentrations in the Coolants	15.A-1
15.A.4	The Impact of Extended Burnup Fuel on Source Terms	15.A-2
15.A.5	Applicability of V5H Fuel Upgrade	15.A-2
15.A.6	The Impact of Operating at a Reduced Feedwater Temperature on Source Terms	15.A-2

STPEGS UFSAR

TABLE OF CONTENTS (Continued)

CHAPTER 15

<u>Section</u>	<u>Title</u>	<u>Page</u>
15.A.7	The Impact of Replacement Steam Generators on Source Terms	15.A-3
APPENDIX	DOSE MODELS	15.B-1
15.B		
15.B.1	General Accident Parameters	15.B-1
15.B.2	Offsite Radiological Consequences Calculational Models	15.B-1
15.B.2.1	Accident Release Pathways	15.B-1
15.B.2.2	Single-Region Release Model	15.B-2
15.B.2.3	Two Region Spray Model in Containment-LOCA	15.B-3
15.B.2.4	Offsite Thyroid Dose Calculation Model	15.B-4
15.B.2.5	Offsite Beta Skin Dose Calculational Model	15.B-4
15.B.2.6	Offsite Gamma Body Dose Calculational Model	15.B-5
15.B.2.7	Offsite Beta-Skin Dose Calculational Model for SGTR	15.B-5
15.B.2.8	Offsite Gamma Whole-Body Dose Calculational Model for SGTR	15.B-5
15.B.3	Control Room Radiological Consequences Calculation Models	15.B-6
	Radioactive Cloud External to the Control Room	15.B-6
15.B.3.1	Integrated Activity in the Control Room	15.B-6
15.B.3.2	Integrate Activity Concentration in the Control Room from Single-Region System	15.B-6
15.B.3.3	Control Room Thyroid Dose Calculational Model	15.B-7
15.B.3.4	Control Room Beta Skin Dose Calculational Model	15.B-7
15.B.3.5	Control Room Gamma Body Dose Calculation	15.B-8
15.B.4	Dose Conversion Factors	15.B-8

STPEGS UFSAR

LIST OF TABLES

CHAPTER 15

<u>Table</u>	<u>Title</u>	<u>Page</u>
15.0-1	Nuclear Steam Supply System Power Ratings	15.0-18
15.0-2	Summary of Initial Conditions and Computer Codes	15.0-19
15.0-3	Nominal Values of Pertinent Plant Parameters Supported by the Accident Analyses	15.0-23
15.0-4	Trip Points and Time Delays to Trip Assumed in Accident Analyses	15.0-24
15.0-6	Plant Systems and Equipment Available for Transient and Accident Conditions	15.0-26
15.0-7	Single Failures Assumed in Accident Analyses	15.0-31
15.1-1	Time Sequence of Events for Incidents Which Cause an Increase in Heat Removal by the Secondary System	15.1-19
15.1-2	Parameters Used in Steam Line Break Analysis	15.1-21
15.1-3	Doses Resulting From Steam Line Break	15.1-22
15.2-1	Time Sequence of Events for Incidents Which Cause a Decrease in Heat Removal by the Secondary System	15.2-20
15.3-1	Time Sequence of Events for Incidents Which Result in a Decrease in Reactor Coolant System Flow	15.3-13
15.3-2	Summary of Results for Locked Rotor Transients without Offsite Power	15.3-15
15.3-3	Parameters Used in Reactor Coolant Pump Shaft Seizure Accident Analysis	15.3-16
15.3-4	Doses Resulting from Reactor Coolant Pump Shaft Seizure Accident	15.3-17
15.4-1	Time Sequence of Events for Incidents Which Cause Reactivity and Power Distribution Anomalies	15.4-39

STPEGS UFSAR

LIST OF TABLES (Continued)

CHAPTER 15		
<u>Table</u>	<u>Title</u>	<u>Page</u>
15.4-3	Parameters Used in the Rod Cluster Control Assembly Ejection Accident Analysis	15.4-42
15.4-4	Parameters Used in Rod Ejection Accident Analysis	15.4-43
15.4-5	Doses Resulting from Rod Ejection Accident	15.4-45
15.5-1	CVCS Malfunction Time Sequences	15.5-7
15.6-1	Time Sequence of Events for Incidents Which Cause a Decrease in Reactor Coolant Inventory	15.6-28
15.6-2	Parameters Used in Sample Line Failure Radiological Analysis	15.6-29
15.6-3	Parameters Used in Steam Generator Tube Rupture Radiological Analyses	15.6-30
15.6-4	Doses Resulting from Steam Generator Tube Rupture	15.6-31
15.6-5	Input Parameters Used in Small Break LOCA Analyses	15.6-32
15.6-5a	Input Parameters Used in Large Break LOCA Analyses	15.6-34
15.6-6	Large Break Time Sequence of Events	15.6-35
15.6-7	Large Break LOCA Analysis Results	15.6-36
15.6-8	Small Break (2-inch) - Time Sequence of Events	15.6-37
15.6-8a	Small Break (2-inch) - Analysis Results	15.6-38
15.6-9	Small Break (3-inch) - Time Sequence of Events	15.6-39
15.6-9a	Small Break (3-inch) - Analysis Results	15.6-40
15.6-10	Parameters Used in Analysis of Loss-of-Coolant Accident Offsite Doses	15.6-41
15.6-11	Doses Resulting From Large Break Loss-of-Coolant Accident	15.6-43
15.6-12	Maximum Potential Recirculation Loop Leakage External to Containment	15.6-44
15.6-13	Parameters Used in CVCS Letdown Line Failure Radiological Analysis	15.6-45
15.6-14	Dose from Small Line Breaks Outside Containment	15.6-46
15.7-3	Parameters Used in Analysis of Liquid-Containing Tank Failure	15.7-7
15.7-4	Activity Available for Release	15.7-8
15.7-7	Activities in the Peak Inventory Discharged Assembly (Fuel Handling Accident in the FHB)	15.7-9
15.7-9	Parameters Used for the Fuel Handling Accident in the FHB	15.7-10
15.7-10	Doses Resulting from a Fuel Handling Accident in the FHB	15.7-11
15.7-11	Activities in the Peak Inventory Discharged Assembly (Fuel Handling Accident in the RCB)	15.7-12

STPEGS UFSAR

LIST OF TABLES (Continued)

CHAPTER 15		
<u>Table</u>	<u>Title</u>	<u>Page</u>
15.7-12	Parameters Used for the Fuel Handling Accident in the RCB	15.7-13
15.7-13	Doses Resulting from a Fuel Handling Accident in the RCB	15.7-14
15.A-1	Core and Gap Activities Based upon Full-Power Operation for 900 Days	15.A-5
15.A-1A	Core Activities for V5H Fuel Upgrade and the Parameters Used in Calculation	15.A-6
15.A-2	Coolant Concentrations - Design Basis	15.A-7
15.A-4	Reactor Coolant Iodine Concentrations	15.A-8
15.A-5	Secondary Coolant Iodine Concentration	15.A-9
15.A-6	Iodine Appearance Rates in the Reactor Coolant	15.A-10
15.B-1	Dispersion Factors	15.B-11
15.B-2	Breathing Rates for an Individual Offsite	15.B-12
15.B-3	Dose Conversion Factors Used in Accident Analysis	15.B-13
15.B-4	Average Gamma and Beta Energy for Noble Gases and Iodines	15.B-14

STPEGS UFSAR

LIST OF FIGURES

CHAPTER 15 Figure

<u>Number</u>	<u>Title</u>
15.0-1A	Range of Programmed T_{avg} Considered in the Safety Analysis
15.0-1B	Nominal Pressurizer Water Level Assumptions
15.0-1C	Illustration of Overtemperature and Overpower Delta T Protection
15.0-2	Doppler Power Coefficient Used in Accident Analysis
15.0-3	RCCA Position versus Time to Dashpot
15.0-4	Minimum Trip Reactivity versus Rod Position
15.0-5	Normalized RCCA Negative Reactivity Insertion versus Time
15.0-6	Moderator Density Coefficient
15.0-6a	Abbreviations and Symbols Used in Sequence Diagrams
15.0-7	Excessive Heat Removal Due to Feedwater System Malfunction
15.0-8	Excessive Load Increase Incident
15.0-9	Accidental Depressurization of the Main Steam System
15.0-10	Loss of External Electrical Load
15.0-11	Loss of Offsite Power to the Station Auxiliaries
15.0-12	Loss of Normal Feedwater
15.0-13	Major Rupture of a Main Feedwater Line
15.0-14	Loss of Forced Reactor Coolant Flow
15.0-15	Uncontrolled Rod Cluster Control Assembly Bank Withdrawal
15.0-16	Dropped Rod Cluster Control Assembly
15.0-17	Single Rod Cluster Control Assembly Withdrawal at Full Power
15.0-18	Startup of an Inactive Reactor Coolant Loop

STPEGS UFSAR

LIST OF FIGURES (Continued)

CHAPTER 15

<u>Figure Number</u>	<u>Title</u>
15.0-19	Uncontrolled Boron Dilution
15.0-20	Rupture of Control Rod Drive Mechanism Housing
15.0-21	Inadvertent ECCS Operation at Power
15.0-22	Accidental Depressurization of the Reactor Coolant System
15.0-23	Sample Line Failure
15.0-24	Steam Generator Tube Rupture
15.0-25	Loss of Coolant Accident
15.0-27	Liquid Waste Processing System Tank(s) Failure
15.0-28	Fuel Handling Accident in the Fuel Building
15.0-29	Fuel Handling Accident in the Containment
15.0-30	Spent Fuel Cask Drop (From Ht < 30 ft)
15.0-31	CVCS Letdown Line Break Outside Containment
15.1-1	Feedwater Control Valve Malfunction, Manual Rod Control - DNBR and Power
15.1-2	Feedwater Control Valve Malfunction, Manual Rod Control - Pressurizer Pressure and Vessel Temperature
15.1-3	Ten Percent Step Load Increase, Minimum Moderator Feedback, Manual Reactor Control
15.1-4	Ten Percent Step Load Increase, Minimum Moderator Feedback, Manual Reactor Control
15.1-5	Ten Percent Step Load Increase, Maximum Moderator Feedback, Manual Reactor Control
15.1-6	Ten Percent Step Load Increase, Maximum Moderator Feedback, Manual Reactor Control

STPEGS UFSAR

LIST OF FIGURES (Continued)

CHAPTER 15

<u>Figure Number</u>	<u>Title</u>
15.1-7	Ten Percent Step Load Increase, Minimum Moderator Feedback, Automatic Reactor Control
15.1-8	Ten Percent Step Load Increase, Minimum Moderator Feedback, Automatic Reactor Control
15.1-9	Ten Percent Step Load Increase, Maximum Moderator Feedback, Automatic Reactor Control
15.1-10	Ten Percent Step Load Increase, Maximum Moderator Feedback, Automatic Reactor Control
15.1-11	K_{eff} versus Core Average Temperature
15.1-14	Doppler Power Feedback
15.1-15	1.4 ft ² Steam Line Rupture, Offsite Power Available - Heat Flux, Average Temperature, Plant Steam Flow
15.1-16	1.4 ft ² Steam Line Rupture, Offsite Power Available - RCS Pressure and Pressurizer Water Volume
15.1-17	1.4 ft ² Steam Line Rupture, Offsite Power Available - Boron Concentration and Reactivity
15.2-1	Turbine Trip Accident with Pressurizer Spray and Power-Operated Relief Valves - Power and Vessel Temperature
15.2-1A	Turbine Trip Accident with Pressure Operated Spray and Power-Operated Relief Valves
15.2-2	Turbine Trip Accident with Pressurizer Spray and Power-Operated Relief Valves - Pressurizer Pressure and Volume
15.2-2A	Turbine Trip Accident with Pressure Operated Spray and Power Operated Relief Valves
15.2-3	Turbine Trip Accident with Pressurizer Spray and Power-Operated Relief Valves - DNBR and Steam Pressure
15.2-3A	Turbine Trip Accident with Pressure Operated Spray and Power-Operated Relief Valves

STPEGS UFSAR

LIST OF FIGURES (Continued)

CHAPTER 15

<u>Figure Number</u>	<u>Title</u>
15.2-4	Turbine Trip Accident without Pressurizer Spray or Power-Operated Relief Valves - Power and Vessel Temperature
15.2-5	Turbine Trip Accident without Pressurizer Spray or Power-Operated Relief Valves - Pressurizer Pressure and Volume
15.2-6	Turbine Trip Accident without Pressurizer Spray or Power-Operated Relief Valves - Steam Pressure
15.2-9A	Loss of Normal Feedwater without Offsite Power - Power and Core Heat Flux
15.2-9B	Loss of Normal Feedwater without Offsite Power - RCS Flow
15.2-9C	Loss of Normal Feedwater without Offsite Power - Loop Temperatures
15.2-9D	Loss of Normal Feedwater without Offsite Power - Pressurizer Pressure and Volume
15.2-10	Loss of Normal Feedwater without Offsite Power - SG Pressure and Mass
15.2-11	Feedline Break with Offsite Power - Core Power and Break Flow
15.2-12	Feedline Break with Offsite Power - Pressurizer Pressure and Volume
15.2-13	Feedline Break with Offsite Power - SG Pressure and Mass
15.2-14	Feedline Break with Offsite Power - Loop Temperatures
15.2-15	Feedline Break without Offsite Power - Power and Break Flow
15.2-16	Feedline Break without Offsite Power - Pressurizer Pressure and Volume
15.2-17	Feedline Break without Offsite Power - SG Pressure and Mass
15.2-18	Feedline Break without Offsite Power - Loop Temperatures
15.3-1	Flow Transients for Partial Loss of Flow, Four Loops in Operation, One Pump Coasting Down
15.3-2	Nuclear Power Transient and Pressurizer Pressure Transient for Partial Loss of Flow, Four Loops in Operation, One Pump Coasting Down

STPEGS UFSAR

LIST OF FIGURES (Continued)

CHAPTER 15

<u>Figure Number</u>	<u>Title</u>
15.3-3	Average and Hot Channel Heat Flux Transients for Partial Loss of Flow, Four Loops in Operation, One Pump Coasting Down
15.3-4	DNBR versus Time for Partial Loss of Flow, Four Loops in Operation, One Pump Coasting Down
15.3-9	Core Flow Coastdown versus Time for Four Loops in Operation, Four Pumps Coasting Down, Complete Loss of Flow
15.3-10	Nuclear Power Transient and Pressurizer Pressure Transient for Four Loops in Operation, Four Pumps Coasting Down, Complete Loss of Flow
15.3-11	Average and Hot Channel Heat Flux Transients for Four Loops in Operation, Four Pumps Coasting Down, Complete Loss of Flow
15.3-12	DNBR versus Time for Four Loops in Operation, Four Pumps Coasting Down, Complete Loss of Flow
15.3-17	Flow Transients for Four Loops in Operation, One Locked Rotor
15.3-18	Reactor Coolant System Pressure Transient for Four Loops in Operation, One Locked Rotor
15.3-19	Nuclear Power Transient, Average and Hot Channel Heat Flux Transients for Four Loops in Operation, One Locked Rotor
15.3-20	Maximum Clad Temperature at Hot Spot for Four Loops in Operation, One Locked Rotor
15.4-1	Neutron Power Transient for Uncontrolled Rod Withdrawal from a Subcritical Condition
15.4-2	Thermal Flux Transient for Uncontrolled Rod Withdrawal from a Subcritical Condition
15.4-3	Fuel and Clad Temperature Transients for Uncontrolled Rod Withdrawal from a Subcritical Condition
15.4-4	Nuclear Power Transient and Core Heat Flux Transient for Uncontrolled Rod Withdrawal from Full Power with Minimum Feedback and 3 pcm/sec Withdrawal Rate

STPEGS UFSAR

LIST OF FIGURES (Continued)

CHAPTER 15

<u>Figure Number</u>	<u>Title</u>
15.4-5	Pressurizer Pressure and Water Volume Transients for Uncontrolled Rod Withdrawal from Full Power with Minimum Feedback and 3 pcm/sec Withdrawal Rate
15.4-6	Core Average Temperature Transient and DNBR Transient for Uncontrolled Rod Withdrawal from Full Power with Minimum Feedback and 3 pcm/sec Withdrawal Rate
15.4-10	Minimum DNBR versus Reactivity Insertion Rate - Rod Withdrawal at Power (100% Power)
15.4-11	Minimum DNBR versus Reactivity Insertion Rate - Rod Withdrawal at Power (60% Power)
15.4-12	Minimum DNBR versus Reactivity Insertion Rate - Rod Withdrawal at Power (10% Power)
15.4-13	Nuclear Power and Core Heat Flux Transients for Rod Cluster Control Assembly Misoperation (2 sheets)
15.4-14	Pressurizer Pressure Transient and Core Average Temperature Transient for Rod Cluster Control Assembly Misoperation (2 sheets)
15.4-16	Nuclear Power Transient During Startup of an Inactive Loop
15.4-17	Average and Hot Channel Heat Flux Transients During Startup of an Inactive Loop

STPEGS UFSAR

LIST OF FIGURES (Continued)

CHAPTER 15

<u>Figure Number</u>	<u>Title</u>
15.4-18	Core Flow During Startup of an Inactive Loop
15.4-19	Pressurizer Pressure Transient and Core Average Temperature Transient During Startup of an Inactive Loop
15.4-20	DNBR Transient During Startup of an Inactive Loop
15.4-21	Interchange Between Region 1 and Region 3 Assembly
15.4-22	Interchange Between Region 1 and Region 2 Assembly, Burnable Absorber Rods Being Retained by the Region 2 Assembly
15.4-23	Interchange Between Region 1 and 2 Assembly, Burnable Absorber Rods Being Transferred to the Region 1 Assembly
15.4-24	Enrichment Error: a Region 2 Assembly Loaded into the Core Central Position
15.4-25	Loading a Region 2 Assembly into a Region 1 Position Near Core Periphery
15.4-26	Nuclear Power Transient, BOL HZP Rod Ejection Accident
15.4-27	Hot Spot Fuel and Clad Temperature versus Time, BOL HZP Rod Ejection Accident
15.4-28	Nuclear Power Transient, EOL HFP Rod Ejection Accident
15.4-29	Hot Spot Fuel and Clad Temperature versus Time, EOL HFP Rod Ejection Accident
15.4-30	BOL HFP Rod Ejection Accident FQ versus Ejected Rod Worth
15.4-31	EOL HZP Rod Ejection Accident FQ versus Ejected Rod Worth
15.5-1A	Charging System Malfunction with Pressurizer Spray and Heaters, Minimum Reactivity Feedback
15.5-1B	Charging System Malfunction with Pressurizer Spray and Heaters, Minimum Reactivity Feedback

STPEGS UFSAR

LIST OF FIGURES (Continued)

CHAPTER 15

<u>Figure Number</u>	<u>Title</u>
15.5-2A	Charging System Malfunction with Pressurizer Spray and Heaters, Maximum Reactivity Feedback
15.5-2B	Charging System Malfunction with Pressurizer Spray and Heaters, Maximum Reactivity Feedback
15.6-1	Nuclear Power Transient for Inadvertent Opening of a Pressurizer Safety Valve
15.6-2	Pressurizer Pressure Transient and Core Average Temperature Transient for Inadvertent Opening of a Pressurizer Safety Valve
15.6-3	DNBR Transient for Inadvertent Opening of a Pressurizer Safety Valve
15.6-4	Steam Generator Tube Rupture Margin to Overfill Analysis - Ruptured SG Water Volume
15.6-5	Sequence of Events for Large Break Loss of Coolant Analysis
15.6-6	Code Interface Description for Large Break Model
15.6-7	Code Interface Description for Small Break Model
15.6-8	Peak Clad Temperature - DECLG, $C_D = 0.6$, Min SI, High T_{AVG} , non-IFBA
15.6-9	Core Pressure - DECLG, $C_D = 0.6$, Min SI, High T_{AVG} , non-IFBA
15.6-10	Reflood Transient Downcomer and Core Water Levels - DECLG, $C_D = 0.6$, Min SI, High T_{AVG} , non-IFBA
15.6-11	Reflood Transient Core Inlet Fluid Velocity - DECLG, $C_D = 0.6$, Min SI, High T_{AVG} , non-IFBA
15.6-12	Core Power Transient - DECLG, $C_D = 0.6$, Min SI, High T_{AVG} , non-IFBA
15.6-13	Containment Pressure - DECLG, $C_D = 0.6$, Min SI, High T_{AVG} , non-IFBA
15.6-14	Peak Clad Temperature - DECLG, $C_D = 0.8$, Min SI, High T_{AVG} , non-IFBA

STPEGS UFSAR

LIST OF FIGURES (Continued)

CHAPTER 15

<u>Figure Number</u>	<u>Title</u>
15.6-14a	Peak Clad Temperature - DECLG, $C_D = 0.8$, Min SI, Low T_{AVG} , non-IFBA
15.6-14b	Peak Clad Temperature - DECLG, $C_D = 0.8$, Max SI, High T_{AVG} , IFBA
15.6-15	Core Pressure - DECLG, $C_D = 0.8$, Min SI, High T_{AVG} , non-IFBA
15.6-15a	Core Pressure - DECLG, $C_D = 0.8$, Min SI, Low T_{AVG} , non-IFBA
15.6-15b	Core Pressure - DECLG, $C_D = 0.8$, Max SI, High T_{AVG} , IFBA
15.6-16	Reflood Transient Downcomer and Core Water Levels - DECLG, $C_D = 0.8$, Min SI, High T_{AVG} , non-IFBA
15.6-16a	Reflood Transient Downcomer and Core Water Levels - DECLG, $C_D = 0.8$, Min SI, Low T_{AVG} , non-IFBA
15.6-16b	Reflood Transient Downcomer and Core Water Levels - DECLG, $C_D = 0.8$, Max SI, High T_{AVG} , IFBA
15.6-17	Reflood Transient Core Inlet Fluid Velocity - DECLG, $C_D = 0.8$, Min SI, High T_{AVG} , non-IFBA
15.6-17a	Reflood Transient Core Inlet Fluid Velocity - DECLG, $C_D = 0.8$, Min SI, Low T_{AVG} , non-IFBA
15.6-17b	Reflood Transient Core Inlet Fluid Velocity - DECLG, $C_D = 0.8$, Max SI, High T_{AVG} , IFBA
15.6-18	Core Power Transient - DECLG, $C_D = 0.8$, Min SI, High T_{AVG} , non-IFBA
15.6-18a	Core Power Transient - DECLG, $C_D = 0.8$, Min SI, Low T_{AVG} , non-IFBA
15.6-18b	Core Power Transient - DECLG, $C_D = 0.8$, Max SI, High T_{AVG} , IFBA

STPEGS UFSAR

LIST OF FIGURES (Continued)

CHAPTER 15

<u>Figure Number</u>	<u>Title</u>
15.6-19	Containment Pressure - DECLG, $C_D = 0.8$, Min SI, High T_{AVG} , non-IFBA
15.6-19a	Containment Pressure - DECLG, $C_D = 0.8$, Min SI, Low T_{AVG} , non-IFBA
15.6-19b	Containment Pressure - DECLG, $C_D = 0.8$, Max SI, High T_{AVG} , IFBA
15.6-20	Peak Clad Temperature - DECLG, $C_D = 1.0$, Min SI, High T_{AVG} , non-IFBA
15.6-21	Core Pressure - DECLG, $C_D = 1.0$, Min SI, High T_{AVG} , non-IFBA
15.6-22	Reflood Transient Downcomer and Core Water Levels - DECLG, $C_D = 1.0$, Min SI, High T_{AVG} , non-IFBA
15.6-23	Reflood Transient Core Inlet Fluid Velocity - DECLG, $C_D = 1.0$, Min SI, High T_{AVG} , non-IFBA
15.6-24	Core Power Transient - DECLG, $C_D = 1.0$, Min SI, High T_{AVG} , non-IFBA
15.6-25	Containment Pressure - DECLG, $C_D = 1.0$, Min SI, High T_{AVG} , non-IFBA
15.6-26	Peak Clad Temperature - DECLG, $C_D = 0.8$, Min SI, High T_{AVG} , IFBA
15.6-27	Core Pressure - DECLG, $C_D = 0.8$, Min SI, High T_{AVG} , IFBA
15.6-28	Reflood Transient Downcomer and Core Water Levels - DECLG, $C_D = 0.8$, Min SI, High T_{AVG} , IFBA
15.6-29	Reflood Transient Core Inlet Fluid Velocity - DECLG, $C_D = 0.8$, Min SI, High T_{AVG} , IFBA
15.6-30	Core Power Transient - DECLG, $C_D = 0.8$, Min SI, High T_{AVG} , IFBA
15.6-31	Containment Pressure - DECLG, $C_D = 0.8$, Min SI, High T_{AVG} , IFBA
15.6-32	Core Flow, Inlet and Outlet - DECLG, $C_D = 0.8$, Min SI, High T_{AVG} , IFBA
15.6-33	Heat Transfer Coefficient - DECLG, $C_D = 0.8$, Min SI, High T_{AVG} , IFBA

STPEGS UFSAR

LIST OF FIGURES (Continued)

CHAPTER 15

<u>Figure Number</u>	<u>Title</u>
15.6-34	Fluid Temperature at Hot Spot - DECLG, $C_D = 0.8$, Min SI, High T_{AVG} , IFBA
15.6-35	Break Mass Flow Rate - DECLG, $C_D = 0.8$, Min SI, High T_{AVG} , IFBA
15.6-36	Break Energy Flow Rate to Containment - DECLG, $C_D = 0.8$, Min SI, High T_{AVG} , IFBA
15.6-37	Fluid Quality at Hot Spot - DECLG, $C_D = 0.8$, Min SI, High T_{AVG} , IFBA
15.6-38	Mass Flux at Hot Spot - DECLG, $C_D = 0.8$, Min SI, High T_{AVG} , IFBA
15.6-39	Accumulator Flow Rate (Blowdown) - DECLG, $C_D = 0.8$, Minimum SI, High T_{AVG} , IFBA
15.6-40	ECCS Injection Rate During Reflood - DECLG, $C_D = 0.8$, Minimum SI, High T_{AVG} , IFBA
15.6-41	RCS Depressurization Transient (2-in. Break, High Loop Temperature, High MFW Temperature)
15.6-42	Core Mixture Height (2-in. Break, High Loop Temperature, High MFW Temperature)
15.6-43	Core Steam Flow (2-in. Break, High Loop Temperature, High MFW Temperature)
15.6-44	Clad Temperature Transient (2-in. Break, High Loop Temperature, High MFW Temperature)
15.6-45	Hot Spot Fluid Temperature - 2-in. Break, High Loop Temperature, High MFW Temperature
15.6-46	Rod Film Heat Transfer Coefficient - 2-in. Break, High Loop Temperature, High MFW Temperature
15.6-47	Core Power After Reactor Trip
15.6-48	RCS Depressurization Transient - 2-in. Break, High Loop Temperature, Low MFW Temperature

STPEGS UFSAR

LIST OF FIGURES (Continued)

CHAPTER 15

<u>Figure Number</u>	<u>Title</u>
15.6-49	Core Mixture Height - 2-in. Break, High Loop Temperature, Low MFW Temperature
15.6-50	Clad Temperature Transient - 2-in. Break, High Loop Temperature, Low MFW Temperature
15.6-51	RCS Depressurization Transient - 2-in. Break, Low Loop Temperature, High MFW Temperature
15.6-52	Core Mixture Height - 2-in. Break, Low Loop Temperature, High MFW Temperature
15.6-53	Clad Temperature Transient - 2-in. Break, Low Loop Temperature, High MFW Temperature
15.6-54	RCS Depressurization Transient - 2-in. Break, Low Loop Temperature, Low MFW Temperature
15.6-55	Core Mixture Height - 2-in. Break, Low Loop Temperature, Low MFW Temperature
15.6-56	Clad Temperature Transient - 2-in. Break, Low Loop Temperature, Low MFW Temperature
15.6-57	Small Break Safety Injection Flow Rate vs. RCS Pressure
15.6-58	Small Break Power Shape
15.B-2	Release Pathways
15.B-3	Control Room Pathways