ESBWR DCD CHAPTER 9
26A6642BD Revision 4 to Revision 5 Change List
Appendix 9B

Item	Location (e.g. subsection with paragraph/sentence/item, table with column,/row, or figure)	Description of Change
1	S9B5.1, Example 2, 1st para., 2nd sent.	Revised sentence to be consistent with existing design from: "Figure 9B-1 is developed from that figure and extrapolated for the period of time of zero to three hours." To: "Figure 9B-1 is developed from that figure and extrapolated for the period of time of two to three hours."
2	S9B5.2, 3rd para., 3rd sent.	Revised sentence to add the corresponding metric units from: "…heat release rate of approximately 200 Btu/sec/ft^2, which is equivalent…" To: "…heat release rate of approximately 2,270 kW/m^2 (200 Btu/sec/ft^2), which is equivalent…"
3	S9B5.3, 2nd para., last sent.	Revised sentence to add the corresponding English units from: "…determined by 5,320 MJ/m of cable tray stack divided by 700 MJ/m^2." To: "…determined by 5,320 MJ/m (1,538 MBtu/ft) of cable tray stack divided by 700 MJ/m^2 (61.64 kBtu/ft^2)."
4	F9B-1,	Add note to clarify that "values after the first 120 minutes are extrapolated".
5		
6		
7		
8		
9		
10		
11		
12		
13		