

## SOUTHWEST RESEARCH INSTITUTE®

6220 Culebra Road, P.O. Drawer 28510 Institute Quality Systems Institute Calibration Laboratory Phone: 210-522-5215 Fax 210-522-4834



Calibration Laboratory Certificate #0972-01

## **Certificate of Calibration**

Submitted By: DIV20 Address: B51

Contact: DON BANNON

Manufacturer / Model: DURO-SENSE / TYPE K

**Description:** THERMOCOUPLE

**Serial No:** 12400 **Asset No:** 012400

Procedure: TEMPERATURE PROBES - 5 JUN 06

Work Order: 303082202
Date Issued: Jul 23, 2008
Calibration Date: Jul 23, 2008
\*Calibration Due: Jul 23, 2009

Calibration Location: Bldg. 64
Environment: Temp. 74.0°F Hum. 40 %RH

\*\*Data Type: FOUND-LEFT

DivID/Location: N/A

This certificate documents traceability to the National Institute of Standards and Technology (NIST) and the International System of Units (SI). The Laboratory quality system conforms to ISO/IEC 17025, 2005, ANSI/NCSL Z540-1-1994 and relevant requirements of the ISO 9000-2000 standard. This certificate shall not be reproduced, except in full, without the written approval of the Southwest Research Institute Calibration Laboratory. This certificate shall not be used to claim product endorsement by Southwest Research Institute, American Association for Laboratory Accreditation (A2LA) or any agency of the U. S. Government. Results of this calibration relate only to the instrument described above at the time of calibration and does not imply any long term stability of the instrument.

\*Determined by the customer, does not imply the instrument will remain within tolerance as any number of factors may cause an out-of-tolerance condition before this date. \*\*Found/Left = adjustment and/or repair was not required, As Left = adjusted and/or repaired was required. The client has sole responsibility for determination of in-/out-of-tolerance or compliance/noncompliance. See Remarks or attached Measurement Report with the same Work Order number for data.

Reported uncertainty calculated in accordance with the ISO "Guide to the Expression of Uncertainty in Measurement" (GUM) and represents an expanded uncertainty with a coverage factor of k=2 to approximate a 95% confidence level.

Remarks: Calibrated at 25°, 100° and 200°C

## Standards Used

١.						
	Asset No.	Serial No.	Manufacturer	Model	Description	Cal Due
ŀ	009137	A21208	HART SCIENTIFIC	1575	SUPER THERMOMETER	Dec 16, 08
1	010281	0421	HART SCIENTIFIC	5628	SPRT	Dec 21, 09
ŀ	010814	A44625	HART SCIENTIFIC	1529	THERMOCOUPLE THERMOMETER	Oct 16, 08
1	013908	1641	HART SCIENTIFIC	5628	SPRT	Feb 20, 10

eviewed by:  $(\sqrt{)}$  srk ( ) mar ( ) wgh

m:\a2la1.rpt Rev date August 15, 2005

Measurements by: Bob Trollinger

Metrology Technician

Page 1 of 1

## Southwest Research Institute Calibration Laboratory Measurement Report

Work Order:	303082202	Mfr.	DURE-SENSE	Technician	blt		
Asset No:	012400	Model	Туре К				
Serial No:	12400	Туре	Thermocouple	Cal Date	23-Jul-08		
Remarks: Limits taken from ASTM E230-02 and are based on brand new unused thermocouples.							
Limited Cal - tested at 25, 100 and 200 °C							

 Function/Range	Test Point	TI Read	Difference	+/-Limit	+/-Uncertainty	Found/Left
Temperature	°C	°C	°C	°C	°C	Result
·	25.096	25.05	0.05	2.2	0.30	Pass
	100.047	100.10	-0.05	2.2	0.30	Pass
	198.119	198.35	-0.23	2.2	0.30	Pass
		END (	OF REPORT			