WATTS BAR NUCLEAR PLANT	1C Document Control Unit, 1520 CST2-C
TECHNICAL INSTRUCTION	1C Nuclear Safety Review Staff
	1C Plant Master File
<u>TI-31.13</u>	Plant Manager
THE STREET OF STREET OF	Asst. Plant Manager Plant Supt. (Opers & Engg)
WALL THICKNESS MEASUREMENT OF PIPING, TANKS, AND VESSELS	Plant Supt. (Maint)
FIFTING, TANKS, AND VESSES	Adm. Svs. Supervisor
	Asst. Mechanical Maint. Sup.
	Chemical Laboratory
	Chemical Unit Supervisor Chief, Nuclear Safety Staff
	16 Chief, Nuclear Training Branch
and the second s	Compliance Unit
	DPSO-WBN
	Document Control Supervisor
	Electrical Maint. Supervisor Electrical Shop
	1C Engineering Supervisor
	1C Field Quality Engineering Supv.
	IC Field Services Supervisor
	/C Health Physicist
	Health Physics Laboratory Instrument Engineer
	1C Instrument Maint. Supervisor
	1C Instrument Shop
	Janitor & Labor Supervisor
	1C Mechanical Maint. Supervisor
	1C Mechanical Maint. Supervisor 1C Mechanical Unit Supervisor
	C Operations Supervisor
	Plant Program Section Supv.
	Planning & Scheduling Supv.
	Plant Training Officer Plant Training Shift Engineer
CURRENT REVISION LEVEL0	1C Power Stores Unit Supervisor
Prepared By Sam Linginfelter	Preop Test Supervisor
	Public Safety
Revised By N/A	Chief, Operations QA Branch
Au m m m n	Reactor Unit Supervisor Safety Engineer
Submitted By // 5. Coros	1C Shift Engineer's Office
Surervisor	Stationary Equipment Group
PORC Review Date //6/84	Technical Support Center
186.	Unit 1 Control Room C Unit 2 Control Room
Approved By Plant Manager	1U Metallurgy & Codes Section
allial	1410 CST-2
Date Approved 1/6/89	1U Regulatory Engineer
Last page of this instruction: 5	
base page of cars instruction.	

WBN TI-31.13 Page 1 of 1

HISTORY OF REVISION/REVIEW

REV.			REASON FOR CURRENT REVISION (INCLUDE
NO.	DATE	REVISED PAGES	ALL TEMPORARY CHANGE NUMBERS)
0	7/6/84	N/A	New Procedure

WBN TI-31.13 Page 1 of 2 Revision 0

WALL THICKNESS MEASUREMENT OF PIPING, TANKS AND VESSELS

1.0 SCOPE

This instruction is for ultrasonic examination of piping, tanks, and vessels for wall thinning conditions such as pitting, erosion and corrosion. This procedure is for thicknesses up and including 1/2 inch.

2.0 REFERENCES

- 2.1 DPM N80E3, procedure N-UT-26
- 2.2 Inspection program TS 09.01.01,14.02

3.0 TEST EQUIPMENT

rabore 1/2 inch is fine

- 3.1 Krautkramer-Branson Model USL-38 with dual element 3/8" diameter search unit.
- 3.2 Couplant material (petroleum jelly or ultra gel), TI-35 approved.
- 3.3 Calibration standards (standard step wedge .1" .5" thick in .1" graduations).
- 3.4 Form TVA 7931 for ultrasonic test inspection. (See Attachment 1.)

4.0 PRECAUTIONS AND PREREQUISITES

- 4.1 Notify the SRO prior to start of test.
- 4.2 Use proper ear and eye protection.
- 4.3 Prior to working in any suspected radiation or contaminated areas notify HP for assistance.
- 4.4 Personnel must be qualified Level II or III for reading scope.

5.0 INSTRUCTIONS

- 5.1 Couple the probe to the 0.1" step of the step wedge and adjust the fine sweep control so that the back reflection appears at the second major screen division.
- 5.2 Couple the probe to the 0.5" step of the step wedge and adjust the delay controls so that the back reflection appears at the tenth major screen division.
- 5.3 Repeat steps 5.1 and 5.2 until the respective echoes from each step appear at their correct position on the horizontal sweep scale.

. NOTE: The instrument is now calibrated.

WBN . TI-31.13 Page 2 of 2 Revision 0

- 5.4 For each surface being inspected, make an appropriate grid, number it and record this grid on page 2 of TVA 7931. (See Attachment 1.) Esure the location is described so it can be located at a later date.
- 5.5 Ensure the examination surface is free of any roughness that interferes with sound transmission or transducer movement. Conduct the general scanning with the instrument adjustment that will produce a first reflection from the I.D. surface of a defect-free area of the component to 100 percent full screen height. Several areas of the component should be checked to ensure a defect-free area is located. Record this value as SR₁ on Attachment 2.

NOTE: When scanning curved surfaces, the acoustic barrier between the transducers shall be oriented parallel to the longitudinal axis of the component and scanning shall be in the circumferential direction.

Areas of suspected pitting, erosion, and corrosion shall be examined over the entire area. Each pass of the search unit shall overlap a minimum of ten percent of the transducer dimension. The rate of the transducer movement shall not exceed six inches per second.

- 5.6 Measure each area of the grid and record this value as SR_2 on Attachment 2.
- 5.7 Notify the SRO of completion of examinations.
- 5.8 Fill in remaining information on Attachments 1 and 2. For line 5, specify either schedule or nominal wall.
- 5.9 Record wall thickness values for each area in their respective area on Attachment 1.
- 5.10 Return the test package to Mechanical Engineering for review and filing.

6.0 ACCEPTANCE CRITERIA

6.1 Piping shall be evaluated for continued operation when wall loss reaches 0.080 inch or greater.

NOTE: The Metallurgy and Codes Section will assist in evaluating UT data, making material recommendations, or evaluating continued operation beyond 0.080 inch wall loss (as needed).

6.2 Notify the Metallurgy and Codes Section for evaluation of tank's and vessel's wall losses. WBN . TI-31.13 Page 1 of 1 Revision 0

ATTACHMENT 2

$$\frac{SR_2}{SR_2} \times t = \text{wall thickness}$$

$$\frac{SR_2}{(1 - \frac{SR_2}{SR_1}) \times t} = \text{wall loss}$$

 SR_1 = Sweep reading established on defect-free area of component. (Step 5.5)

SR₂ = Sweep reading obtained on probable defective area of component. (Step 5.6)

t = Nominal component wall thickness established from drawing, design thickness, pipe size, and schedule, etc.

Date: Reviewed By:	100
Meviewed by.	Mech Engg

	SR ₁		
LOCATION	SR ₂	WALL LOSS	WALL TRICKNESS
0			
		• • • • • • • • • • • • • • • • • • •	
		•	The state of the s
ý.			
.,			

WBN TI-31.13 Page 2 of 2 Revision 0

ATTACHMENT 1

						GRI	D NO.			-	INITIA	LS		DATE	,				
Ī	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	17	18	19
٨																			
В																•			
c								• •											
D																			
E															• ;				
F					is.												1		
G													,						
H																			
I																		-	
J													•						
K																			
L		; ;																	
н													0	41				i	
N		1-		,															

WBN TI-31.13 Page 1 of 2 Revision 0

ATTACHMENT 1

DATA FORM FOR ULTRASONIC TEST INSPECTION OF CARBON STEEL PIPING

1.	Unit and System:	
2.	Location:	
3.	Grid No.:	
4.	Pipe Diameter:	
5.	Schedule or Nominal Wall:	
6.	Date:	
7.	Sketch of Grid Location:	
8.	Inspector (Signature):	

Comments:

1C Document Control Unit-C 1C Nuclear Safety Review Staff 1C Plant Master File Plant Manager Supt. (0 & E) Supt. (Maint) ASE Duty Station Building Svs. Supv. Chem. Eng. Unit Supv. Chem Lab Chief, Nuc. Safety Staff IC Chief, Nuc. Training Branch Chief, Quality Audits Branch Compliance Unit Supv. Component & Eng. Svs. Group DPSO Supv. - WB Dr. & VM Unit Supv. Elect. Maint. Sup". IC Eng. Sect. Supv. Health Physics Supv. Industrial Safety Supv. 1C Instrument Maint. Supv. 1C Instrument Shop Materials Unit Supv. 1C Mech. Eng. Unit Supv. 1C Inservice Inspection

1C Mech. Maint. Supv. 1C Mech. Maint. Shop Office 1C Modifications Mgr. 1C NEB-John Raulston Operating Instruction Coordinator 1C Operations Supv. Oper, Training Classroom 1C Oper. Training Sect. Supv. Planning & Scheduling Supv. 1C Plant QA Supv. Plant Training Officer Power Stores Supv. Preop Test Supv. Public Safety Services Reactor Eng. Unit Supv. 1C Shift Engineer's Office Site Director Staff Reference Copy Support Svs. Supv. Technical Support Center 1C Unit 1 Control Room 1C Unit 2 Control Room Units 1 & 2 Planning IC Watts Bar Technical Svs. Library 1U Metallurzy & Codes Section-:410 CST2-C

TO: Those Listed

FROM: Document Control Supp., NUC PR, Watts Bar Nuclear Plant

DATE: 8/27/85

SUBJECT: Transmittal of Watts Bar Nuclear Plant Instructions

Due to our requirements, there is a ten-day limit:

1. to acknowledge receipt of the following materia.

2. to affirm that it has been placed in the appropriate manual, 3. to update the table of contents, and

4. to remove and discard the superseded instruction.

INSTRUCTION # TI-31.13

REMOVE AND DESTROY PAGES All

INSERT PAGES All

DATE/KEVISION S/23/35 RC

Return to: Document Control Supv., TSOB, NUC PR, Watts Bar Nuclear Plant

TENNESSEE VALLEY AUTHORITY WATTS BAR NUCLEAR PLANT TECHNICAL INSTRUCTION MANUAL Table of Contents

EFFECTIVE AUG 27 1985 (Date)

TITLE	NUMBER	REV. NO.	UNITS
Auxiliary Building Safety Injection System External Leakage	TI-31.7.2	. 1	
Auxiliary Building Residual Heat Removal System External Leakage	TI-31.7.3	1	
Auxiliary Building Chemical and Volume Control System External Leakage	TI-31.7.4	.1	•
Auxiliary Building Reactor Coolant Sample System External Leakage	TI-31.7.5	1	
Flow Balancing Valves Setpoints	TI-31.8	4	
Ice Condenser Heat Gain Calculations	TI-31.10 (Canceled)	1	: 1
Vibration Monitoring of Reactor Coolant Pumps	TI-31.12	0	1 & 2
all Thickness Measurement of Piping, Tanks, langes, and Vessels	TI-31.13	2	
Piping Vibration Measurements	TI-31.14	1	7
Dew Point Measurement	TI-31.15	0	
· Valve Full Stroke Exercising During Plant Operation - Control Air	TI-31.17	1	1 & 2
Auxiliary Boiler Isolation Valve Closure Time	TI-31.18	0	1 or 2
Leak Testing (Bubble Method) Nuclear Air- Cleaning Systems	TI-31.19	0	· ·······
Flux Map Calculations Using Incore Program	TI-33		1 or 2
Loose Parts Alarm Response	TI-34.1	0	
System Tape Recorder Data	TI-34.2	0	•
Audio Monitoring of the Loose Parts Monitoring	TI-34.3	1	1 5 2
Specification Standards Of Materials Commonly Associated With Maintenance Which May Come In Contact With Reactor Coolant	TI-35	22	1 & 2