

## SOUTHWEST RESEARCH INSTITUTE®

6220 Culebra Road, P.O. Drawer 28510 Institute Quality Systems Institute Calibration Laboratory Phone: 210-522-5215 Fax 210-522-4834



Calibration Laboratory Certificate #0972-01

## Certificate of Calibration

Submitted By: DIV20 Address: B51

Contact: DON BANNON

Manufacturer / Model: DURO-SENSE / TYPE K

Description: THERMOCOUPLE

**Serial No:** 12405 **Asset No:** 012405

Procedure: TEMPERATURE PROBES - 5 JUN 06

Work Order: 303083287
Date Issued: Sep 15, 2008
Calibration Date: Sep 15, 2008
\*Calibration Due: Sep 15, 2009

Calibration Location: Bldg. 64
Environment: Temp. 72.0°F Hum. 40 %RH

\*\*Data Type: FOUND-LEFT

DivID/Location: N/A

This certificate documents traceability to the National Institute of Standards and Technology (NIST) and the International System of Units (SI). The Laboratory quality system conforms to ISO/IEC 17025, 2005, ANSI/NCSL Z540-1-1994 and relevant requirements of the ISO 9000-2000 standard. This certificate shall not be reproduced, except in full, without the written approval of the Southwest Research Institute Calibration Laboratory. This certificate shall not be used to claim product endorsement by Southwest Research Institute, American Association for Laboratory Accreditation (A2LA) or any agency of the U. S. Government. Results of this calibration relate only to the instrument described above at the time of calibration and does not imply any long term stability of the instrument.

\*Determined by the customer, does not imply the instrument will remain within tolerance as any number of factors may cause an out-of-tolerance condition before this date. \*\*Found/Left = adjustment and/or repair was not required, As Left = adjusted and/or repaired was required. The client has sole responsibility for determination of in-/out-of-tolerance or compliance/noncompliance. See Remarks or attached Measurement Report with the same Work Order number for data.

Reported uncertainty calculated in accordance with the ISO "Guide to the Expression of Uncertainty in Measurement" (GUM) and represents an expanded uncertainty with a coverage factor of k=2 to approximate a 95% confidence level.

Remarks: Cal'd at 25°, 100°, 200° C

## Standards Used

1						
ł	Asset No.	Serial No.	Manufacturer	Model	Description	Cal Due
l	009137	A21208	HART SCIENTIFIC	1575	SUPER THERMOMETER	Dec 16, 08
ı	010814	A44625	HART SCIENTIFIC	1529	THERMOCOUPLE THERMOMETER	Oct 16, 08
l	013908	1641	HART SCIENTIFIC	5628	SPRT	Feb 20, 10

Reviewed by ( ) srk ( ) mar ( ) woh

m:\a2la1.rpt Rev date August 15, 2005

Measurements by: Bob Trollinger

Metrology Technician

Page 1 of 1

## Southwest Research Institute Calibration Laboratory Measurement Report

Work Order:	303083287	Mfr.	DURE-SENSE	Technician	blt			
Asset No:	012405	Model	Type K					
Serial No:	12505	Туре	Thermocouple	Cal Date	15-Sep-08			
Remarks: Limits taken from ASTM E230-02 and are based on brand new unused thermocouples.								
Limited Cal - tested at 25, 100 and 200 °C								

Function/Range	Test Point	TI Read	Difference	+/-Limit	+/-Uncertainty	Found/Left
Temperature	°C	°C	°C	°C	°C	Result
	25.143	25.07	0.07	2.2	0.30	Pass
	100.044	100.19	-0.15	2.2	0.30	Pass
	200.316	199.81	0.51	2.2	0.30	Pass
		FND	OF REPORT			