

SOUTHWEST RESEARCH INSTITUTE®

6220 Culebra Road, P.O. Drawer 28510 Institute Quality Systems Institute Calibration Laboratory Phone: 210-522-5215 Fax 210-522-4834



Certificate #0972-01

Certificate of Calibration

Submitted By: DIV20 Address: B51

Contact: DON BANNON

Manufacturer / Model: FISHER SCIENTIFIC / 14-983-10B

Description: THERMOMETER, GLASS

Serial No: 12609 Asset No: 012609

Procedure: THERMOMETERS, GLASS - 11 SEP 06

Work Order: 303083285 Date Issued: Sep 22, 2008 Calibration Date: Sep 22, 2008 *Calibration Due: Dec 22, 2008

Calibration Location: Bldg. 64

Environment: Temp. 74.0°F Hum. 40 %RH

**Data Type: FOUND-LEFT

DivID/Location: N/A

This certificate documents traceability to the National Institute of Standards and Technology (NIST) and the International System of Units (SI). The Laboratory quality system conforms to ISO/IEC 17025, 2005, ANSI/NCSL Z540-1-1994 and relevant requirements of the ISO 9000-2000 standard. This certificate shall not be reproduced, except in full, without the written approval of the Southwest Research Institute Calibration Laboratory. This certificate shall not be used to claim product endorsement by Southwest Research Institute, American Association for Laboratory Accreditation (A2LA) or any agency of the U. S. Government. Results of this calibration relate only to the instrument described above at the time of calibration and does not imply any long term stability of the instrument.

*Determined by the customer, does not imply the instrument will remain within tolerance as any number of factors may cause an out-of-tolerance condition before this date. **Found/Left = adjustment and/or repair was not required, As Left = adjusted and/or repaired was required. The client has sole responsibility for determination of in-/out-of-tolerance or compliance/noncompliance. See Remarks or attached Measurement Report with the same Work Order number for data.

Reported uncertainty calculated in accordance with the ISO "Guide to the Expression of Uncertainty in Measurement" (GUM) and represents an expanded uncertainty with a coverage factor of k=2 to approximate a 95% confidence level.

Remarks: +/- 1°C

Standards Used

| | Asset No. | Serial No. | Manufacturer | Model | Description | Cal Due |
|---|-----------|------------|-----------------|-------|-------------------|------------|
| 1 | 009137 | A21208 | HART SCIENTIFIC | 1575 | SUPER THERMOMETER | Dec 16, 08 |
| | 013908 | 1641 | HART SCIENTIFIC | 5628 | SPRT | Feb 20, 10 |

m:\a2la1.rpt Rev date August 15, 2005

Measurements by: Bob Trollinger

Metrology Technician

Page 1 of 1

Southwest Research Institute Calibration Laboratory Measurement Report

| Work Order: | 303083285 | Mfr: | Fisher-Scientific | Technician: | blt |
|-----------------|-------------|---------------|------------------------------|-------------------------|-----------|
| Asset No: | 012609 | Model: | 14-983-10B | | |
| Serial No: | 12609 | Type: | Thermometer | Cal Date: | 22-Sep-08 |
| Remarks: | No accuracy | s provided by | manufacturer. +/- 1 °C resol | ution is used as the ac | ccuracy |
| specification. | | | | | |
| Total Immersion | | | | | |

| Function/Range | Test Point | TI Reading | Difference | +/-Limit | +/-Uncertainty | Found/Left |
|----------------|------------|------------|------------|----------|----------------|------------|
| Temperature | °C | °C | °C | °C | °C | Result |
| | -19.77 | -19.8 | 0.0 | 1.0 | 0.58 | Pass |
| | 0.16 | 0.4 | 0.2 | 1.0 | 0.58 | Pass |
| | 50.06 | 50.1 | 0.0 | 1.0 | 0.58 | Pass |
| | 100.04 | 100.0 | 0.0 | 1.0 | 0.58 | Pass |
| END OF REPORT | | | | | | |