NRC FORM 374	RC FORM 374 PAGE1_ OF _3_ PAGE U.S. NUCLEAR REGULATORY COMMISSION					
			Amendment No. 01			
Burguant to the Atomic Energy Act of 1054		A CONTRACTOR OF CONTRACTOR	1074 (Public Low 02 429) and Title 10			
Pursuant to the Atomic Energy Act of 1954, Code of Federal Regulations, Chapter I, representations heretofore made by the licer transfer byproduct, source, and special nucle designated below; to deliver or transfer suc applicable Part(s). This license shall be deer amended, and is subject to all applicable rule and to any conditions specified below.	Parts 30, 31, 32, 33, nsee, a license is hereb ear material designated ch material to persons med to contain the cond	34, 35, 36, 39, 40, and y issued authorizing the lid below; to use such mater authorized to receive it in itions specified in Section	70, and in reliance on statements and censee to receive, acquire, possess, and ial for the purpose(s) and at the place(s) accordance with the regulations of the 183 of the Atomic Energy Act of 1954, as			
(X	02/2/		2/1538			
Licensee		In accordance with I				
	-	September 25, 200				
1. Fall Line Testing & Inspection, LL	C		32685-01 is amended in its			
		entirety to read as				
2. 1163 Maple Street		4. Expiration date May	31, 2018			
Farmington, MO 63640		5. Docket No. 030-376	57			
		Reference No.				
 Byproduct, source, and/or special nuclear material 	7. Chemical and/or	physical form 8.	Maximum amount that licensee may possess at any one time under this license			
A. Cesium-137	Drawing No. A Technology M CDC. 805 and	Sealed sources (Troxler Drawing No. A-102112, AEA Technology Model No. CDC. 805 and/or Isotope Products labs. Model No. HEG-137)A. 10 sources total not to exceed 9 millicuries for Troxler gauges and not to exceed 11 millicuires for InstroTek, Inc. gauges.				
B. Americium-241	Drawing No. A Technology M AMN.V997 an	Sealed sources (Troxler Drawing No. A-102451, AEA Technology Model No. AMN.V997 and/or Isotope Products Labs. Model No. AMI.NO2)B. 10 sources total not to exceed 44 millicuries each				
9. Authorized use:						
A. and B. In Troxler Electronic Laboratories Model No. 3400 Series and InstroTek, Inc. portable gauging devices for measuring physical properties of materials.						
CONDITIONS						
10. Licensed material may be used or stored at the licensee's facilities located at 1163 Maple Street, Farmington, Missouri and may be used at temporary job sites of the licensee anywhere in the United States where the U. S. Nuclear Regulatory Commission maintains jurisdiction for regulating the use of licensed material.						

NR	NRC FORM 374A U.S. NUCLEAR REGULATORY COMMISSION		U.S. NUCLEAR REGULATORY COMMISSION	PAGE 2 of 3 PAGES		
				License Number 24-32685-01		
			FERIALS LICENSE	Docket or Reference Number 030-37657		
				Amendment No. 01		
11.	 Licensed material shall only be used by, or under the supervision and in the physical presence of, individuals who have received the training described in application dated February 15, 2008. 					
12.	12. The Radiation Safety Officer (RSO) for this license is Scot Hughson.					
13.	13. A. Sealed sources shall be tested for leakage and/or contamination at intervals not to exceed the intervals specified in the certificate of registration issued by NRC under 10 CFR 32.210 or by an Agreement State.					
	B. In the absence of a certificate from a transferor indicating that a leak test has been made within the intervals specified in the certificate of registration issued by NRC under 10 CFR 32.210 or by an Agreement State prior to the transfer, a sealed source received from another person shall not be put into use until tested.					
	C. Sealed sources need not be tested if they are in storage and are not being used. However, when they are removed from storage for use or transferred to another person, and have not been tested within the required leak test interval, they shall be tested before use or transfer. No sealed source shall be stored for a period of more than 10 years without being tested for leakage and/or contamination.					
	D.	D. The leak test shall be capable of detecting the presence of 0.005 microcurie (185 becquerels) of radioactive material on the test sample. If the test reveals the presence of 0.005 microcurie (185 becquerels) or more of removable contamination, a report shall be filed with the U.S. Nuclear Regulatory Commission in accordance with 10 CFR 30.50(c)(2), and the source shall be removed immediately from service and decontaminated, repaired, or disposed of in accordance with Commission regulations.				
	E. Tests for leakage and/or contamination shall be performed by persons specifically licensed by the Commission or an Agreement State to perform such services. In addition, the licensee is authorized to collect leak test samples but not perform the analysis: analysis of leak samples must be performed by persons specifically licensed by the Commission or an Agreement State to perform such services.					
	F. Records of leak tests results shall be kept in units of microcuries and shall be maintained for 3 years.					
14.	 Sealed sources or source rods containing licensed material shall not be opened or sources removed or detached from source rods or gauges by the licensee. 					
	 The licensee shall conduct a physical inventory every 6 months, or at other intervals approved by the U.S. Nuclear Regulatory Commission, to account for all sources and/or devices received and possessed under the license. 					
16.	16. Except for maintaining labeling as required by 10 CFR Part 20 or 71, the licensee shall obtain authorization from NRC before making any changes in the sealed source, device, or source-device combination that would alter the description or specifications as indicated in the respective Certificates of Registration issued either by the Commission pursuant to 10 CFR 32.210 or by an Agreement State.					

NRC FORM 374A U.S. NUCLEAR REGULATORY COMMISSION	PAGE 3 of 3 PAGES			
	24-32685-01			
MATERIALS LICENSE SUPPLEMENTARY SHEET	Docket or Reference Number 030-37657			
	Amendment No. 01			
17. Each portable nuclear gauge shall have a lock or outer locked container designed to prevent unauthorized or accidental removal of the sealed source from its shielded position. The gauge or its container must be locked when in transport. A minimum of two independent physical controls that form tangible barriers to secure portable gauges from unauthorized removal whenever the portable gauge is not under the control and constant surveillance of the licensee are required.				
18. Any cleaning, maintenance, or repair of the gauges that requires detaching the source or source rod from the gauge shall be performed only by the manufacturer or other persons specifically licensed by the U.S. Nuclear Regulatory Commission or an Agreement State to perform such services.				
9. A. If the licensee uses unshielded sealed sources extended more than 3 feet below the surface, the licensee shall use surface casing that extends from the lowest depth to 12 inches above the surface and other appropriate procedures to reduce the probability of the source or probe becoming lodged below the surface. If it is not feasible to extend the casing 12 inches above the surface, the licensee shall implement procedures to ensure that the cased hole is free of obstruction before making measurements.				
B. If a sealed source or a probe containing sealed sources becomes lodged below the surface and it becomes apparent that efforts to recover the sealed source or probe may not be successful, the licensee shall notify the U. S. Nuclear Regulatory Commission and submit the report required by 10 CFR 30.50(b)(2) and (c). The licensee shall not abandon the sealed source or probe without obtaining the Commission's prior written consent.				
20. The licensee is authorized to transport licensed material only in accordance with the provisions of 10 CFR Part 71, "Packaging and Transportation of Radioactive Material."				
21. Except as specifically provided otherwise in this license, the licensee shall conduct its program in accordance with the statements, representations, and procedures contained in the documents, including any enclosures, listed below. The Nuclear Regulatory Commission's regulations shall govern unless the statements, representations, and procedures in the licensee's application and correspondence are more restrictive than the regulations.				
A. Application dated February 15, 2008; and				
B. Letter dated April 17, 2008.				
FOR THE U	U.S. NUCLEAR REGULATORY COMMISSION			
	s R. Mullauer, M.H.S. rials Licensing Branch			

Materials Licensing Region IIII