Loose Parts Monitoring System Test Preoperational Test Witnessing Procedure No.: 70450B Issue Date: 1/1/79

## SECTION I

## INSPECTION OBJECTIVES

- Verify that the testing is conducted in accordance with approved procedures,
- 2. Independently verify the acceptability of test results, and
- 3. Evaluate the performance of licensee personnel conducting the test.

Loose Parts Monitoring System Test Preoperational Test Witnessing Procedure No.: 70450B

Issue Date: 1/1/79

#### SECTION II

# INSPECTION REQUIREMENTS

## The inspector shall:

- 1. Schedule an inspection to coincide with this testing.
- 2. Obtain and review the Loose Parts Monitoring System Test Procedure prior to witnessing the test.
- 3. Review Regulatory Guide 1.68 and applicable portions of the FSAR, SER, Technical Specifications, and docket correspondence. Verify that the Loose Parts Monitoring System is adequately tested to ensure that NRC requirements and licensee commitments are satisfied.
- 4. Observe licensee personnel conducting the test. Verify that:
  - a. tests are conducted in accordance with approved procedures,
  - b. approved test procedures are available to personnel conducting the test,
  - c. test equipment is properly installed,
  - d. test data is collected and recorded in the approved manner, and
  - e. evaluate the licensee personnel's ability to conduct the test.

Loose Parts Monitoring System Test Preoperational Test Witnessing Procedure No.: 70450B Issue Date: 1/1/79

### SECTION III

### INSPECTION GUIDANCE

- 1. By witnessing this test, the inspector should ensure that important system performance functions are adequately tested. Areas which should be witnessed include (but are not limited to):
  - a. system response to test signals,
  - b. system operation during alarm conditions,
  - c. system calibration, and
  - d. system ability to monitor various plant components.

NOTE: Items may be part of other systems tests.