

SNC000030

**Overview of GE Single-Exhaust,
Dual-Flow Turbine Designed for
“Medium Fossil Applications”**



[SEARCH](#)
[▼ PRODUCTS & SERVICES](#)
[▶ ONLINE TOOLS](#)
[▶ OUR COMMITMENT](#)
[▶ ABOUT US](#)
[▶ CONTACT US](#)

D Series Fossil Steam Turbines

[Home](#)

[Products & Services](#)

[Products](#)

[Steam Turbines](#)

[Reheat](#)

[Non-Reheat](#)

[Fossil](#)

[Nuclear](#)

[IGCC](#)

[Impulse Type](#)

[Industrial Steam/Small](#)

[Services](#)

[Lifecycle Services](#)



For Medium Fossil Applications

GE's D series are full-arc or partial-arc admission, tandem compound reheat steam turbines, ideal for 50 and 60 Hz subcritical and supercritical power generation applications up to 550 MW. D series turbines feature a two-casing, double-flow design for 2,400 or 3,500 PSI applications.

Features & Benefits

- Single-casing HP/IP section reduces turbine hall construction cost and shortens installation time
- Dense Pack™ steam path mean increased stage count, higher reaction
- Integral cover buckets (ICBs) improve tip sealing and reliability
- Partial-arc (2) or full-arc admission: 360-degree nozzle box/plate
- Control valves with individual actuators permit online selection between full-arc and partial-arc admission modes

Product Characteristics

- Power rating: 200-550 MW
- Subcritical or supercritical steam conditions
- Full-arc/partial-arc (2) admission
- Opposed-flow combined HP/IP
- Double-flow LP:
 - 60 Hz: 2x26" / 2x30" / 2x33.5" / 2x40"
 - 50 Hz: 2x26" / 2x33.5" / 2x42" / 2x48"

More About Steam Turbines

[A Series](#)

[G Series](#)

Download More Information

[Steam Turbine Products Brochure \(1.3MB PDF\)](#)